


TERMO DE ACEITE TÉCNICO

Solicitante: PRODEMGE / SEE

NOC/Operadora: Ermínio Junior Operadora/Cliente: João Widar

GRE/Prodemge: João Antinossi Responsável/cliente :Roniele Alves Santos

Consórcio **VSAT-ID** Porta kbps **Plataforma** SEE-ITBA-22032 **VSAT EMC/Vodanet** 2Mbps



OBS: TESTE FEITO COM O TEMPO NUBLADO

dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled IDU Output Power : -20 dBm IDU Max Output Power: 0.0 dBm ODU Output Power : 33.5 dBm EIRP : 46.5 dBW Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : UDP/IP

Satellite (DVB) Transmitter Status

State : On (DVB-RCS2)
IDU Output Power : -17.3 dBm
ODU Output Power : 33.9 dBm EIRP : 46.9 dBW : 15.0 dB Es/No

Header Compression : Disabled - HC for RCS2 not supported by HUB

Timing correction : -341 us (281309 us)

Frequency correction: 110 Hz

dvb rx show

```
Satellite (DVB) RX Configuration
______
                      : Enabled
Auto start
Max Traffic MODCOD : 23 16APSK-9/10 RX watchdog : 15 minute
Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName
                                                                                  Name
Enable
* 0 0
          4.883300
                        12.176420 DVB-S2 104
                                                     0 0.0 E
Yes
 1 1 16.667000
                        11.962753 DVB-S2 2
                                                     0 0.0 E
Yes
Satellite (DVB) Receiver Status
              : On
: Forward link up
: 65281, Prodemge@Vodanet
: 12.176245 GHz
: 4.883012 M
-----
Rx State
DVB State
Network
Frequency
Symbol Rate
S2 ModCod
     - receiving : 4 QPSK-1/2
- current max : 21 16APSK-5/6
              : On
Pilot
Frame length : Short DVB S2 Mode : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 0.20
SNR
                   : 17.8 dB
                   : -31 dBm
Input Power
# device show
System Information:

Name : SEE-ITBA-22032

Location : ITAMARANDIBA
    Location
                        : ITAMARANDIBA
    Contact
   System Up time : 0 days, 01:41:40 CPU Load : 10%
    System time (UTC) : 17 October 2017 13:52:12
    Broadcast Message : not set
HW:
    Model
                       : SatLink 2000
    HW ID
                       : 120033
    Main board ID
                       : 120026 R6.2
MAC addresses:
    Ethernet (LAN) : 00:20:0e:10:4c:b5
Satellite (DVB) : 00:20:0e:10:4c:b5
# arp show
                State MacAddr
                                            Τf
   NetAddr
   10.212.104.2 Dynamic 54:04:a6:8e:d3:f6 1
Pinging 10.212.104.1 with 32 bytes of data:
Reply from 10.212.104.1: bytes=32 time=547ms TTL=56
Reply from 10.212.104.1: bytes=32 time=548ms TTL=56
Reply from 10.212.104.1: bytes=32 time=549ms TTL=56
Reply from 10.212.104.1: bytes=32 time=561ms TTL=56
Reply from 10.212.104.1: bytes=32 time=568ms TTL=56
Reply from 10.212.104.1: bytes=32 time=560ms TTL=56
Reply from 10.212.104.1: bytes=32 time=577ms TTL=56
Reply from 10.212.104.1: bytes=32 time=615ms TTL=56
Reply from 10.212.104.1: bytes=32 time=577ms TTL=56
```

```
Reply from 10.212.104.1: bytes=32 time=580ms TTL=56
Ping statistics for 10.212.104.1:
   Packets: Sent = 10, Received = 10, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
   Minimum = 547ms, Maximum = 615ms, Average = 568ms
Sites acessados
www.globo.com ok
www.yahoo.com.br- ok
www.hotmail.com- ok
<u>www.google.com</u> – ok
www.prodemge.gov.br - ok
Responsável pelo teste de navegação:
Nome: Roniele Alves dos Santos
Função:Vice-Diretor
Identidade: MASP1224586-6
```