

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Wallace Teixeira


Cliente: Vivo

Empresa
EMC Brasil

VSAT-ID VIVO-PER-
31075965-MG

Link kbps 256K/128K

Plataforma VSAT



Satellite (DVB) TX Configuration

```

Auto start           : Enabled
IDU Output Power     : -18 dBm
IDU Max Output Power : 0.0 dBm
Default CW Frequency : 0.000000 GHz
ATM mode             : VC-Mux
Header Compression   : None
  
```

Satellite (DVB) Transmitter Status

```

State                : On (DVB-RCS2)
IDU Output Power     : -18.0 dBm
Es/No                 : 11.0 dB
Header Compression    : Disabled
Timing correction     : -55 us (250245 us) Frequency
correction: 140 Hz
  
```

dvb rx show

Satellite (DVB) RX Configuration

Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-
9/10
RX watchdog : 15 minute

Idx	Pri	SymbRate[Msp	Freq[GHz]	
Mode	PopId	SatId	Pos	SatName
Name	Enable			
* 0	0	30.000000	12.050000	
DVB-S2	104	0	0.0 E	
Yes				
1	1	25.333333	12.050000	
DVB-S2	4	0	0.0 E	
Yes				

Satellite (DVB) Receiver Status

Rx State : On
DVB State : Forward link up
Network : 1326, T14R Beam
Frequency : 12.050035 GHz
Symbol Rate : 30.000783 Msp
S2 ModCod
- receiving : 12 8PSK-3/5
- current max : 22 16APSK-8/9
Pilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 0.20
SNR : 16.0 dB
Input Power : -32 dBm

CMD - Atalho

Resposta de 8.8.8.8: bytes=32 tempo=2941ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=2362ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=2136ms TTL=49

Esgotado o tempo limite do pedido.

Resposta de 8.8.8.8: bytes=32 tempo=1462ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=831ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=1637ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=1519ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=2872ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=1074ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=814ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=1882ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=1036ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=1323ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=3347ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=2275ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=2833ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=2098ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=2295ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=1117ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=2887ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=2871ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=1516ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=1230ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=1675ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=2255ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=2270ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=2631ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=1036ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=1309ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=807ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=824ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=794ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=803ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=893ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=1519ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=893ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=825ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=1531ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=1401ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=2313ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=1348ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=2360ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=1136ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=999ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=1001ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=3165ms TTL=49

Resposta de 8.8.8.8: bytes=32 tempo=901ms TTL=49

Estatísticas do Ping para 8.8.8.8:
Pacotes: Enviados = 60, Recebidos = 57, Perdidos = 3 (5% de perda).
Aproximar um número redondo de vezes em milissegundos:
Mínimo = 794ms, Máximo = 3347ms, Média = 1688ms
Control-C
C:\Windows\System32>

SatLink VSAT

10.29.66.41/wmi/dwp/index_page.dwp

STM

SatLink VSAT

Status

Device Status

Satellite	Model	SatLink 2000
Statistics	Software Version	16.0.1.57
Device	LAN MAC Address	00:20:0e:10:7c:99
DHCP	DVB MAC Address	00:20:0e:10:7c:99
Eventlog	System Up Time	0 days, 00:02:41
Configuration	CPU Load	22%
Satellite	System Name	VIVO-PER-31075965-MG
IP	System Contact	
Static NAT	System Location	Caputira - MG
Lineup		
Device		

Help

Introduction

Status

Configuration

You are logged in as install (2)

© Copyright 2006-2014 STM Group. All Rights Reserved.

18:27
12/01/2018