


TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Wallace Teixeira Cliente: VIVO

Empresa VSAT-ID VIVO-PER-EMC Brasil 31298981-MG

Link kbps 256k/128k Plataforma VSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled

IDU Output Power : -20 dBm

IDU Max Output Power: 0.0 dBm

ODU Output Power : 33.2 dBm

EIRP : 46.5 dBW

Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS2)
IDU Output Power : -15.9 dBm
ODU Output Power : 35.3 dBm

EIRP : 48.6 dBW Es/No : 14.5 dB Header Compression: Disabled Timing correction: 5 us (248508 us)

Frequency correction: -160 Hz

dvb rx show

Satellite (DVB) RX Configuration

Auto start : Enabled

Max Traffic MODCOD : 23 16APSK-9/10

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name Enable

* 0 0 30.000000 11.592000 DVB-S2 102 0 0.0 E Yes

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up
Network : 1326, T14R Beam
Frequency : 11.592873 GHz
Symbol Rate : 29.999553 Msps

S2 ModCod

- receiving : 12 8PSK-3/5 - current max : 22 16APSK-8/9

Pilot : On

Frame length : Short DVB S2 Mode : ACM

DVB S2 Stream type: MPEG-TS

Roll off : 0.20 SNR : 15.7 dB Input Power : -27 dBm

