

S2 ModCod

- receiving : 15 8PSK-5/6

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais Cliente: VIVO NOC/Operador: Rogerio Momi Frias **Empresa** VSAT-ID Link kbps **Plataforma EMC** Brasil VIVO-PER-23050268-CE 256/128 VSAT SpeedOf.Me, HTML5 Spee × → C 🖍 🗋 speedof.me **₽** ☆ **S** 🔛 Apps 🔼 BR ★ Bookmarks 📑 ani 🕒 Fóruns - Forum de S... 🐧 Crie seu site - uCoz Outros favoritos SpeedOf.Me is an HTML5 Internet speed test. No Flash or Java needed! It is the smartest and most accurate online bandwidth test. It works well on iPhone, iPad, Android, Windows 8 and other mobile devices, as well as desktop computers. (i) X SpeedOf.Me Download: 220 kbps Download Upload: 20 kbps Latency: 1987 ms | Max Download: 0.22 | Max Upload: 0.06 Upload CRIE 11-04-2015 | Test Server Miami 2 IP: 200.143.6.142 1, 2, a. s. 0.1 PRÓPRIO 0.05 Gestão profissional WEBSITE de agências Time Download Speed: 220 kbps History Runrun.it Upload Speed: 20 kbps Click 'Share' to share this 1. Nov Test Again Share Date Comece Já Test Liked it? Spread the word Home | About | How It Works | Help | Privacy | API | Contact Us Copyright © 2011-2015 SPEED OF ME | v2.9.7 Satellite (DVB) RX Configuration Auto start : Enabled Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5 dB) RX watchdog : 15 minute Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable * 0 0 9.320000 12.055825 DVB-S2 4 Satellite (DVB) Receiver Status Rx State **DVB State** : Forward link up : 1326, GlobalIP@Telstar-14R Network Frequency : 12.055887 GHz Symbol Rate : 9.319932 Msps

- current max : 23 16APSK-9/10

Pilot : On
Frame length : Short
DVB S2 Mode : ACM
Roll off : 0.25
SNR : 15.0 dB
Input Power : -25 dBm

Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -30 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 34.7 dBm
EIRP : 48.0 dBW

Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (TDMA)
IDU Output Power : -16.1 dBm
ODU Output Power : 34.5 dBm
EIRP : 47.8 dBW
Eb/No : 14.5 dB

Header Compression : Disabled Timing correction : -298 us (260665 us)

Frequency correction: -70 Hz

ping 8.8.8.8

64 bytes from 8.8.8.8: time=920 ms 64 bytes from 8.8.8.8: time=630 ms 64 bytes from 8.8.8.8: time=770 ms 64 bytes from 8.8.8.8: time=1160 ms 64 bytes from 8.8.8.8: time=820 ms

--- 8.8.8.8 ping statistics ---

5 packets transmitted, 5 received, 0.00 percent packet loss rtt min/avg/max = 630/850/1160 ms