

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Rogerio Momi Frias Cliente: VIVO

Empresa
EMC BrasilVSAT-ID
VIVO-PER-26073790-PELink kbps
256/128Plataforma
VSAT



Satellite (DVB) RX Configuration

.....

Auto start : Enabled

Max Traffic MODCOD : 23 16APSK-9/10

RX watchdog : 15 minute

ldx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name Enable * 0 0 9.320000 12.055825 DVB-S2 102 0 0.0 E Yes

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up

Network : 1326, GlobalIP@Telstar-14R

Frequency : 12.055946 GHz Symbol Rate : 9.320034 Msps

S2 ModCod

- receiving : 14 8PSK-3/4 - current max : 16 8PSK-8/9

Pilot : On Frame length : Short DVB S2 Mode : ACM

DVB S2 Stream type: MPEG-TS

Roll off : 0.20 SNR : 13.2 dB Input Power : -27 dBm

Satellite (DVB) TX Configuration

·----

Auto start : Enabled
IDU Output Power : -23 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 35.0 dBm

EIRP : 48.0 dBW

Default CW Frequency: 14.125750 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS) IDU Output Power : -21.5 dBm ODU Output Power : 34.6 dBm

EIRP : 47.6 dBW Es/No : 13.0 dB

Header Compression: Disabled

Timing correction : -215 us (262046 us)

Frequency correction: -100 Hz

ping 8.8.8.8

64 bytes from 8.8.8.8: time=2890 ms 64 bytes from 8.8.8.8: time=1510 ms 64 bytes from 8.8.8.8: time=970 ms 64 bytes from 8.8.8.8: time=660 ms 64 bytes from 8.8.8.8: time=520 ms

--- ping statistics ---

5 packets transmitted, 5 received, 0.00 percent packet loss rtt min/avg/max = 520/1310/2890 ms