1 Protocol

1.1 Setup(l) \rightarrow (mpk, msk)

```
generate g, g_0, g_1 \in \mathbb{G}_1 randomly
generate w, t_1, t_2, t_3, t_4 \in \mathbb{Z}_p^*
\Omega \leftarrow e(g, g)^{t_1 t_2 w}
v \leftarrow g^{t_1}
v \leftarrow g^{t_2}
v \leftarrow g^{t_3}
v \leftarrow g^{t_4}
mpk \leftarrow (Omega, g, g_0, g_1, v_1, v_2, v_3, v_4)
msk \leftarrow (w, t_1, t_2, t_3, t_4)
return (mpk, msk)
```

$1.2 \quad ext{Extract}(\textit{Id}) ightarrow \textit{Pvk}_{\textit{Id}}$

```
\begin{array}{l} \text{generate } r1, r2 \in \mathbb{Z}_p^* \text{ randomly} \\ d_0 \leftarrow g^{r_1t_1t_2 + r_2t_3t_4} \\ d_1 \leftarrow g^{-wt_2} \cdot (g_0g_1^{Id})^{-r_1t_2} \\ d_2 \leftarrow g^{-wt_1} \cdot (g_0g_1^{Id})^{-r_1t_1} \\ d_3 \leftarrow (g_0g_1^{Id})^{-r_2t_4} \\ d_4 \leftarrow (g_0g_1^{Id})^{-r_2t_3} \\ Pvk_{Id} \leftarrow (d_0, d_1, d_2, d_3, d_4) \\ \mathbf{return} \ Pvk_{Id} \end{array}
```

1.3 $\mathbf{Encrypt}(\mathbf{Id}, m) \to \mathbf{CT}$

```
generate s, s_1, s_2 \in \mathbb{Z}_p^* randomly C' \leftarrow \Omega^s M (g_0 g_1^{Id})^s C_1 \leftarrow v_1^{s-s_1} C_2 \leftarrow v_2^{s_1} C_3 \leftarrow v_3^{s-s_2} C_4 \leftarrow v_4^{s_2} CT \leftarrow (C', C_0, C_1, C_2, C_3, C_4) return CT
```

1.4 $\operatorname{Dec}(Pvk_{id}, CT) \to M$

$$M \leftarrow C' \cdot e(C_0,d_0) \cdot e(C_1,d_1) \cdot e(C_2,d_2) \cdot e(C_3,d_3) \cdot e(C_4,d_4)$$
 return M