

Experiment 9

Objective:

- Concept of Commit, Rollback and check points Properties of Transactions:

Transactions have the following four standard properties, usually referred to by the acronym ACID:

- Atomicity: ensures that all operations within the work unit are completed successfully; otherwise, the transaction is aborted at the point of failure, and previous operations are rolled back to their former state.
- Consistency: ensures that the database properly changes states upon a successfully committed transaction.
- Isolation: enables transactions to operate independently of and transparent to each other.
- Durability: ensures that the result or effect of a committed transaction persists in case of a system failure.

Transaction Control:

There are following commands used to control transactions:

- COMMIT: to save the changes.
- ROLLBACK: to rollback the changes.
- SAVEPOINT: creates points within groups of transactions in which to ROLLBACK
- SET TRANSACTION: Places a name on a transaction.

Transactional control commands are only used with the DML commands INSERT, UPDATE and DELETE only. They cannot be used while creating tables or dropping them because these operations are automatically committed in the database.

The COMMIT Command:

The COMMIT command is the transactional command used to save changes invoked by a transaction to the database.

The COMMIT command saves all transactions to the database since the last COMMIT or ROLLBACK command.

The syntax for COMMIT command is as follows:

COMMIT;

Example:

Consider the CUSTOMERS table having the following records:

ID	NAME	AGE	ADDRESS	SALARY
1	Ramesh	32	Ahmedabad	2000.00
2	Khilan	25	Delhi	1500.00
3	kaushik	23	Kota	2000.00
4	Chaitali	25	Mumbai	6500.00
5	Hardik	27	Bhopal	8500.00
6	Komal	22	MP	4500.00
7	Muffy	24	Indore	10000.00

Following is the example which would delete records from the table having age = 25 and then COMMIT the changes in the database.

```
SQL> DELETE FROM CUSTOMERS
      WHERE AGE = 25;
```

```
SQL> COMMIT;
```

As a result, two rows from the table would be deleted and SELECT statement would produce the following result:

```
+---+-----+---+-----+-----+
| ID | NAME   | AGE | ADDRESS | SALARY |
+---+-----+---+-----+-----+
| 1 | Ramesh | 32 | Ahmedabad | 2000.00 |
| 3 | kaushik | 23 | Kota     | 2000.00 |
| 5 | Hardik | 27 | Bhopal   | 8500.00 |
| 6 | Komal  | 22 | MP       | 4500.00 |
| 7 | Muffy  | 24 | Indore   | 10000.00 |
+---+-----+---+-----+-----+
```

The ROLLBACK Command:

The ROLLBACK command is the transactional command used to undo transactions that have not already been saved to the database.

The ROLLBACK command can only be used to undo transactions since the last COMMIT or ROLLBACK command was issued.

The syntax for ROLLBACK command is as follows:

```
ROLLBACK;
```

Example: Consider the CUSTOMERS table having the following records:

```
+---+-----+---+-----+-----+
| ID | NAME   | AGE | ADDRESS | SALARY |
+---+-----+---+-----+-----+
| 1 | Ramesh | 32 | Ahmedabad | 2000.00 |
| 2 | Khilan | 25 | Delhi     | 1500.00 |
| 3 | kaushik | 23 | Kota     | 2000.00 |
| 4 | Chaitali | 25 | Mumbai   | 6500.00 |
| 5 | Hardik | 27 | Bhopal   | 8500.00 |
| 6 | Komal  | 22 | MP       | 4500.00 |
| 7 | Muffy  | 24 | Indore   | 10000.00 |
```

Following is the example, which would delete records from the table having age = 25 and then ROLLBACK the changes in the database.

```
SQL> DELETE FROM CUSTOMERS
```

```
WHERE AGE = 25;
```

```
QL> ROLLBACK;
```

ID	NAME	AGE	ADDRESS	SALARY
1	Ramesh	32	Ahmedabad	2000.00
2	Khilan	25	Delhi	1500.00
3	kaushik	23	Kota	2000.00
4	Chaitali	25	Mumbai	6500.00
5	Hardik	27	Bhopal	8500.00
6	Komal	22	MP	4500.00
7	Muffy	24	Indore	10000.00

The SAVEPOINT Command:

A SAVEPOINT is a point in a transaction when you can roll the transaction back to a certain point without rolling back the entire transaction.

The syntax for SAVEPOINT command is as follows:

```
SAVEPOINT SAVEPOINT_NAME;
```

This command serves only in the creation of a SAVEPOINT among transactional statements. The ROLLBACK command is used to undo a group of transactions.

The syntax for rolling back to a SAVEPOINT is as follows:

```
ROLLBACK TO SAVEPOINT_NAME;
```

Following is an example where you plan to delete the three different records from the CUSTOMERS table. You want to create a SAVEPOINT before each delete, so that you can ROLLBACK to any SAVEPOINT at any time to return the appropriate data to its original state:

Example:

Consider the CUSTOMERS table having the following records:

ID	NAME	AGE	ADDRESS	SALARY
1	Ramesh	32	Ahmedabad	2000.00
2	Khilan	25	Delhi	1500.00
3	kaushik	23	Kota	2000.00
4	Chaitali	25	Mumbai	6500.00
5	Hardik	27	Bhopal	8500.00
6	Komal	22	MP	4500.00
7	Muffy	24	Indore	10000.00

Now, here is the series of operations:

SQL> SAVEPOINT SP1; Savepoint created.

SQL> DELETE FROM CUSTOMERS WHERE ID=1; 1 row deleted.

SQL> SAVEPOINT SP2; Savepoint created.

SQL> DELETE FROM CUSTOMERS WHERE ID=2; 1 row deleted.

SQL> SAVEPOINT SP3; Savepoint created.

SQL> DELETE FROM CUSTOMERS WHERE ID=3; 1 row deleted.