

#### Утегенов Батырхан Елембетұлы [ADS-Lab-05]: Submit a solution

Info	Summary	Submissions	Standings	Submit clar	Clars	Settings
Logout	[ads23_22B03045	[8]				

#### 18:18:27 / **RUNNING**

Α	В	С	D	E

## Submit a solution for E-K-th sum

Time limit: 1 s

Real time limit: 5 s

Memory limit: 256M

#### Problem E: K-th sum

Nurdana loves cookies! She stores all the cookies in separate boxes, but mom allows her to store only k boxes. Her dad is an assistant in this matter. He gives her a box in which there are n cookies. Help her calculate how many cookies she can have?

## Input format

The first line contains two integers q and k (1  $\leq q$ ,  $k \leq 10^5$ ). Each of the following q lines contains one command.

There are two types of commands:

- *insert* n dad gives a box with n cookies  $(0 \leqslant n \leqslant 10^9)$
- print print the maximum number of cookies Nurdana can have

## **Output format**

For each query of type print print the maximum sum of cookies if consider no more than k boxes.

## **Examples**

#### ınpuτ

```
6 4
print
insert 9
insert 6
print
insert 10
print
```

## Output

```
0
15
25
```

#### **Notes**

This problem must be solved using a heap.

Use long long type for the sum of elements.

Since k is fixed, you don't need to store all numbers, only k largest elements.

## Submit a solution



File Выберите файл Файл не выбран

Send! Send!

# Previous submissions of this problem

Run ID	Time	Size	Problem	Language	Result	Failed test	View source	View report
1711	1212:03:45	2112	E	g++	OK	N/A	<u>View</u>	<u>View</u>

A B C D E

ejudge 3.10.3+ (GIT 6da71ff82) (2023-08-02 06:59:26).

Copyright © 2000-2023 Alexander Chernov.