


Maridaje API

```
# Install the command line client
$ pip install coreapi-cli
```

comida

list

GET /maridaje/bodegs_api/comida/

 Interact

```
# Load the schema document
$ coreapi get http://localhost:8000/maridaje/docs/

# Interact with the API endpoint
$ coreapi action comida list
```

create

POST /maridaje/bodegs_api/comida/

 Interact

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
nombre required	
descripcion required	

```
# Load the schema document
$ coreapi get http://localhost:8000/maridaje/docs/

# Interact with the API endpoint
$ coreapi action comida create -p nombre=... -p descripcion=...
```

read

GET /maridaje/bodegs_api/comida/{id}/

 Interact

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id required	A unique integer value identifying this comida.

```
# Load the schema document
$ coreapi get http://localhost:8000/maridaje/docs/

# Interact with the API endpoint
$ coreapi action comida read -p id=...
```

update

PUT /maridaje/bodegs_api/comida/{id}/

 Interact

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id required	A unique integer value identifying this comida.

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
nombre required	
descripcion required	

```
# Load the schema document
$ coreapi get http://localhost:8000/maridaje/docs/

# Interact with the API endpoint
$ coreapi action comida update -p id=... -p nombre=... -p descripcion=...
```

partial_update

PATCH /maridaje/bodegs_api/comida/{id}/

 Interact

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id required	A unique integer value identifying this comida.

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
nombre	
descripcion	

```
# Load the schema document
$ coreapi get http://localhost:8000/maridaje/docs/

# Interact with the API endpoint
$ coreapi action comida partial_update -p id=... -p nombre=... -p descripcion=...
```

delete

DELETE

 /maridaje/bodegs_api/comida/{id}/

⇄ Interact

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id required	A unique integer value identifying this comida.

```
# Load the schema document
$ coreapi get http://localhost:8000/maridaje/docs/

# Interact with the API endpoint
$ coreapi action comida delete -p id=...
```

maridaje

list

GET

 /maridaje/bodegs_api/maridaje/

⇄ Interact

```
# Load the schema document
$ coreapi get http://localhost:8000/maridaje/docs/

# Interact with the API endpoint
$ coreapi action maridaje list
```

create

POST /maridaje/bodegs_api/maridaje/

[↔ Interact](#)

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
nombre required	
descripcion required	
foto	
vino required	
comida required	

```
# Load the schema document
$ coreapi get http://localhost:8000/maridaje/docs/

# Interact with the API endpoint
$ coreapi action maridaje create -p nombre=... -p descripcion=... -p foto=... -p vino=...
```

read

GET /maridaje/bodegs_api/maridaje/{id}/

[↔ Interact](#)

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id required	A unique integer value identifying this maridaje.

```
# Load the schema document
$ coreapi get http://localhost:8000/maridaje/docs/

# Interact with the API endpoint
$ coreapi action maridaje read -p id=...
```

update

PUT /maridaje/bodegs_api/maridaje/{id}/

 Interact

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id required	A unique integer value identifying this maridaje.

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
nombre required	
descripcion required	
foto	
vino required	
comida required	

```
# Load the schema document
$ coreapi get http://localhost:8000/maridaje/docs/

# Interact with the API endpoint
$ coreapi action maridaje update -p id=... -p nombre=... -p descripcion=... -p foto=...
```

partial_update

PATCH /maridaje/bodegs_api/maridaje/{id}/

 Interact

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id required	A unique integer value identifying this maridaje.

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
nombre	
descripcion	
foto	
vino	
comida	

```
# Load the schema document
$ coreapi get http://localhost:8000/maridaje/docs/

# Interact with the API endpoint
$ coreapi action maridaje partial_update -p id=... -p nombre=... -p descripcion=... -p
```

delete

DELETE

/maridaje/bodegs_api/maridaje/{id}/

↔

Interact

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	A unique integer value identifying this maridaje.

```
# Load the schema document
$ coreapi get http://localhost:8000/maridaje/docs/

# Interact with the API endpoint
$ coreapi action maridaje delete -p id=...
```

vino

list

GET

/maridaje/bodegs_api/vino/

↔

Interact

```
# Load the schema document
$ coreapi get http://localhost:8000/maridaje/docs/

# Interact with the API endpoint
$ coreapi action vino list
```

create

POST /maridaje/bodegs_api/vino/

[↔ Interact](#)

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
nombre required	
bodega required	
varietal required	
region required	

```
# Load the schema document
$ coreapi get http://localhost:8000/maridaje/docs/

# Interact with the API endpoint
$ coreapi action vino create -p nombre=... -p bodega=... -p varietal=... -p region=...
```

read

GET /maridaje/bodegs_api/vino/{id}/

[↔ Interact](#)

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id required	A unique integer value identifying this vino.

```
# Load the schema document
$ coreapi get http://localhost:8000/maridaje/docs/

# Interact with the API endpoint
$ coreapi action vino read -p id=...
```

update

PUT /maridaje/bodegs_api/vino/{id}/

[↔ Interact](#)

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id required	A unique integer value identifying this vino.

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
nombre required	
bodega required	
varietal required	
region required	

```
# Load the schema document
$ coreapi get http://localhost:8000/maridaje/docs/

# Interact with the API endpoint
$ coreapi action vino update -p id=... -p nombre=... -p bodega=... -p varietal=... -p region=...
```

partial_update

PATCH /maridaje/bodegs_api/vino/{id}/

⇌ Interact

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id required	A unique integer value identifying this vino.

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
nombre	
bodega	
varietal	
region	


```
# Load the schema document
$ coreapi get http://localhost:8000/maridaje/docs/

# Interact with the API endpoint
$ coreapi action vino partial_update -p id=... -p nombre=... -p bodega=... -p varietal=...
```

delete

DELETE /maridaje/bodegs_api/vino/{id}/

[↔ Interact](#)

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id required	A unique integer value identifying this vino.

```
# Load the schema document
$ coreapi get http://localhost:8000/maridaje/docs/

# Interact with the API endpoint
$ coreapi action vino delete -p id=...
```