Question 1 | Correct Mark 1.00 out of 1.00

Given an array of N integer, we have to maximize the sum of arr[i] * i, where i is the index of the element (i = 0, 1, 2, ..., N).Write an algorithm based on Greedy technique with a Complexity O(nlogn).

Input Format:

First line specifies the number of elements-n

The next n lines contain the array elements.

Output Format:

Maximum Array Sum to be printed.

Sample Input:

5

2 5 3 4 0

Sample output:

40

Answer: (penalty regime: 0 %)

```c
#include<stdio.h>
int main(){
    int n,i,j,temp;
    long long sum=0;
    scanf("%d",&n);
    int arr[n];

    for(i=0;i<n;i++){
        scanf("%d",&arr[i]);}
    for(i=0;i<n;i++){
        for(j=i+1;j<n;j++){
       if(arr[i]>arr[j]){
           temp=arr[i];
           arr[i]=arr[j];
           arr[j]=temp;
       }

    }
}
    for(i=0;i<n;i++){
        sum+=arr[i]*i;
    }
    printf("%lld",sum);
    return 0;

}
```

	Input	Expected	Got	
✔	5 2 5 3 4 0	40	40	✔

	Input	Expected	Got	
✔	10 2 2 2 4 4 3 3 5 5 5	191	191	✔
✔	2 45 3	45	45	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course