Question 1 | Correct Mark 1.00 out of 1.00

Given two arrays array_One[] and array_Two[] of same size N. We need to first rearrange the arrays such that the sum of the product of pairs(1 element from each) is minimum. That is SUM (A[i] * B[i]) for all i is minimum.

For example:

Input	Result
3 1 2 3 4 5 6	28

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
int main(){
    int n,i,j,temp;
    int a[100],b[100];
    int sum=0;
    scanf("%d",&n);
    for(i=0;i<n;i++){
 scanf("%d",&a[i]);
    }
      for(i=0;i<n;i++){
 scanf("%d",&b[i]);
    }
    for(i=0;i<n;i++){
        for(j=i+1;j<n;j++){
            if(a[i]>a[j]){
                temp=a[i];
                a[i]=a[j];
                a[j]=temp;
            }
        }
    }
    for(i=0;i<n;i++){
        for(j=i+ 1;j<n;j++){
            if(b[i]<b[j]){
                temp=b[i];
                b[i]=b[j];
                b[j]=temp;
            }
        }
    }
    for(i=0;i<n;i++){
        sum+=a[i]*b[i];}
        printf("%d",sum);
        return 0;


}
```

	Input	Expected	Got	
✔	3 1 2 3 4 5 6	28	28	✔