

```

<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="utf-8" />
    <link rel="icon" href="%PUBLIC_URL%/favicon.ico" />
    <meta name="viewport" content="width=device-width, initial-
scale=1" />
    <meta name="theme-color" content="#000000" />
    <meta
      name="description"
      content="Web site created using create-react-app"
    />
    <link rel="apple-touch-icon"
href="%PUBLIC_URL%/logo192.png" />
    <!--
      manifest.json provides metadata used when your web app is
      installed on a
        user's mobile device or desktop. See
https://developers.google.com/web/fundamentals/web-app-
manifest/
    -->
    <link rel="manifest" href="%PUBLIC_URL%/manifest.json" />
    <!--

```

Notice the use of %PUBLIC_URL% in the tags above.

It will be replaced with the URL of the `public` folder during the build.

Only files inside the `public` folder can be referenced from the HTML.

Unlike `"/favicon.ico"` or `"favicon.ico"`, `"%PUBLIC_URL%/favicon.ico"` will

work correctly both with client-side routing and a non-root public URL.

Learn how to configure a non-root public URL by running ``npm run build``.

```
-->
<title>React App</title>
</head>
<body>
  <noscript>You need to enable JavaScript to run this
app.</noscript>
  <div id="root"></div>
  <!--
    This HTML file is a template.
    If you open it directly in the browser, you will see an
empty page.

    You can add webfonts, meta tags, or analytics to this
file.

    The build step will place the bundled scripts into the
<body> tag.

    To begin the development, run `npm start` or `yarn
start`.

    To create a production bundle, use `npm run build` or
`yarn build`.
  -->
</body>
</html>
```