

In-depth
course

Bo Peng,
Ph.D.

Loading
simuPOP

Population

Individual

Operator

Mating
scheme

Simulator

Forward-time simulations using simuPOP, an in-depth course

Bo Peng, Ph.D.

Department of Epidemiology
UT MD Anderson Cancer Center
Houston, TX

June 15th, 2007
simuPOP workshop

School of Public Health, Department of Biostatistics
University of Alabama Birmingham

outline

In-depth course

Bo Peng,
Ph.D.

Loading
simuPOP
Population
Individual
Operator
Mating
scheme
Simulator

- 1 Loading simuPOP
- 2 Population
- 3 Individual
- 4 Operator
- 5 Mating scheme
- 6 Simulator

In-depth
course

Bo Peng,
Ph.D.

Loading
simuPOP

simuPOP modules

Random Number
Generator

Debug information
Getting help

Population

Individual

Operator

Mating
scheme

Simulator

1

Loading simuPOP

- simuPOP modules
- Random Number Generator
- Debug information
- Getting help

simuPOP modules

In-depth
course

Bo Peng,
Ph.D.

Loading
simuPOP

simuPOP modules

Random Number
Generator

Debug information
Getting help

Population

Individual

Operator

Mating
scheme

Simulator

simuPOP provides six types of modules

1 Possible allele states:

short $0 \sim 2^8 - 1$

long $0 \sim 2^{16} - 1$

binary 0 and 1

2 Optimization

standard with debug information and runtime
validation

optimized without debug information and runtime
validation

Note: A Message Passing Interface (parallel) version of
simuPOP is under development.

Loading appropriate module

In-depth course

Bo Peng,
Ph.D.

Loading simuPOP

simuPOP modules

Random Number
Generator

Debug information

Getting help

Population

Individual

Operator

Mating scheme

Simulator

1 Use `simuOpt.setOptions`

```
>>> from simuOpt import setOptions
>>> setOptions(alleleType='long', optimized=False, quiet=False)
>>> from simuPOP import *
simuPOP : Copyright (c) 2004-2006 Bo Peng
Developmental Version (Jun 12 2007) for Python 2.3.4
[GCC 3.4.6 20060404 (Red Hat 3.4.6-8)]
Random Number Generator is set to mt19937 with random seed 0x34679d9c2f218200
This is the standard long allele version with 65536 maximum allelic states.
For more information, please visit http://simupop.sourceforge.net,
or email simupop-list@lists.sourceforge.net (subscription required).
>>>
```

2 Set environment variables (system dependent)

- `SIMUALLELETYPE` = short/long/binary
- `SIMUOPTIMIZED` for optimized version

3 Command line argument of scripts using the `simuOpt` module (`--optimized`)

Standard modules

In-depth course

Bo Peng,
Ph.D.

Loading simuPOP

simuPOP modules

Random Number
Generator

Debug information
Getting help

Population

Individual

Operator

Mating scheme

Simulator

Perform strict runtime check. Produce proper debug information if anything goes wrong.

```
>>> pop = population(10, loci=[2])
>>> pop.locusPos(10)
Traceback (most recent call last):
  File "course.py", line 1, in ?
    #!/usr/bin/env python
IndexError: src/genoStru.h:428 absolute locus index (10) out of range of 0 - 1
>>> pop.individual(20).setAllele(1, 0)
Traceback (most recent call last):
  File "course.py", line 1, in ?
    #!/usr/bin/env python
IndexError: src/population.h:452 individual index (20) is out of range of 0 ~ 9
>>>
```

Optimized modules

In-depth course

Bo Peng,
Ph.D.

Loading simuPOP

simuPOP modules

Random Number
Generator

Debug information
Getting help

Population

Individual

Operator

Mating scheme

Simulator

No runtime check. Improper usages may crash simuPOP.

```
% setenv SIMUOPTIMIZED
% python
Python 2.3.4 (#1, Jan 9 2007, 16:40:09)
[GCC 3.4.6 20060404 (Red Hat 3.4.6-3)] on linux2
Type "help", "copyright", "credits" or "license" for more information.
>>> from simuPOP import *
simuPOP : Copyright (c) 2004-2006 Bo Peng
Developmental Version (May 21 2007) for Python 2.3.4
[GCC 3.4.6 20060404 (Red Hat 3.4.6-3)]
Random Number Generator is set to mt19937 with random seed 0x2f04b9dc5ca0fc00
This is the optimied short allele version with 256 maximum allelic states.
For more information, please visit http://simupop.sourceforge.net,
or email simupop-list@lists.sourceforge.net (subscription required).
>>> pop = population(10, loci=[2])
>>> pop.locusPos(10)
1.2731974748756028e-313
>>> pop.individual(20).setAllele(1, 0)
Segmentation fault
```

Random Number Generator

In-depth
course

Bo Peng,
Ph.D.

Loading
simuPOP

simuPOP modules

Random Number
Generator

Debug information

Getting help

Population

Individual

Operator

Mating
scheme

Simulator

simuPOP uses RNG from the GNU Scientific Library

```
>>> rng().name()
'mt19937'
>>> rng().seed()
3776160106704634368
>>> r = ListAllRNG()
>>> print r[:5]
('gfsr4', 'mt19937', 'mt19937_1999', 'mt19937_1998', 'r250')
>>> SetRNG('taus2', 1234)
>>> rng().name()
'taus2'
>>> rng().seed()
1234
>>> rng().randUniform01()
0.82989443955011666
>>>
```

Note: simuPOP uses system clock to set random seeds under windows.

Debug information

In-depth course

Bo Peng,
Ph.D.

Loading simuPOP

simuPOP modules
Random Number
Generator

Debug information

Getting help

Population

Individual

Operator

Mating
scheme

Simulator

Several ways to turn on/off debug information

- Set environment variable `SIMUDEBUG`
- Use function `TurnOnDebug`, `TurnOffDebug`
- Use operator `turnOnDebug`, `turnOffDebug` to turn on/off debug at specific generations

Debug information (cont.)

In-depth course

Bo Peng,
Ph.D.

Loading simuPOP

simuPOP modules

Random Number
Generator

Debug information

Getting help

Population

Individual

Operator

Mating scheme

Simulator

```
>>> TurnOnDebug(DBG_POPULATION)
>>> ind = population(10, loci=[5]).individual(1)
Constructor of population is called
Destructor of population is called
>>> # This line may crash simuPOP
>>> print ind.allele(2)
0
>>> # Show all debug code
>>> ListDebugCode()
```

Debug code	On/Off
DBG_ALL	0
DBG_GENERAL	1
DBG_UTILITY	0
DBG_OPERATOR	0
DBG_SIMULATOR	0
DBG_INDIVIDUAL	0
DBG_OUTPUTTER	0
DBG_MUTATOR	0
DBG_RECOMBINATOR	0
DBG_INITIALIZER	0
DBG_POPULATION	1

Getting help

In-depth course

Bo Peng,
Ph.D.

Loading simuPOP

simuPOP modules
Random Number
Generator
Debug information
Getting help

Population

Individual

Operator

Mating scheme

Simulator

```
>>> help(population.addInfoFields)
Help on method population_addInfoFields:

population_addInfoFields(...) unbound simuPOP_la.population method
    Description:

        add one or more information fields to a population

    Usage:

        x.addInfoFields(fields, init=0)

    Arguments:

        fields:          new information fields. If one or more of the
                        fields already exist, they will simply be re-
                        initialized.
        init:            initial value for the new fields.

>>>
```

Outline

In-depth
course

Bo Peng,
Ph.D.

Loading
simuPOP

Population

Structure of
population

Genotypic
structure

Population
structure

Population
variables

Manipulate
population

Individual

Operator

Mating
scheme

Simulator

2

Population

- Structure of population
- Genotypic structure
- Population structure
- Population variables
- Manipulate population

Structure of a population

In-depth
course

Bo Peng,
Ph.D.

Loading
simuPOP

Population

Structure of
population

Genotypic
structure

Population
structure

Population
variables

Manipulate
population


Individual

Operator

Mating
scheme

Simulator

- Unaffected
- Affected



Structure of a population

In-depth
course

Bo Peng,
Ph.D.

Loading
simuPOP

Population

Structure of
population

Genotypic
structure

Population
structure

Population
variables

Manipulate
population


Individual

Operator

Mating
scheme

Simulator

- Unaffected
- Affected



Current generation

Structure of a population

In-depth
course

Bo Peng,
Ph.D.

Loading
simuPOP

Population

Structure of
population

Genotypic
structure

Population
structure

Population
variables

Manipulate
population


Individual

Operator

Mating
scheme

Simulator

- Unaffected
- Affected



Current generation

Structure of a population

In-depth
course

Bo Peng,
Ph.D.

Loading
simuPOP

Population

Structure of
population

Genotypic
structure

Population
structure

Population
variables

Manipulate
population


Individual

Operator

Mating
scheme

Simulator

- Unaffected
- Affected



Current generation

Structure of a population

In-depth
course

Bo Peng,
Ph.D.

Loading
simuPOP

Population

Structure of
population

Genotypic
structure

Population
structure

Population
variables

Manipulate
population


Individual

Operator

Mating
scheme

Simulator

- Unaffected
- Affected



Current generation

Structure of a population

In-depth
course

Bo Peng,
Ph.D.

Loading
simuPOP

Population

Structure of
population

Genotypic
structure

Population
structure

Population
variables

Manipulate
population


Individual

Operator

Mating
scheme

Simulator

- Unaffected
- Affected



Ancestral generation 1

Current generation

Structure of a population

In-depth
course

Bo Peng,
Ph.D.

Loading
simuPOP

Population

Structure of
population

Genotypic
structure

Population
structure

Population
variables

Manipulate
population


Individual

Operator

Mating
scheme

Simulator

- Unaffected
- Affected




Ancestral generation 2

Ancestral generation 1

Current generation

Structure of a population

- Unaffected
- Affected



Ancestral generation 2

Ancestral generation 1

Current generation

Population variables

In-depth
course

Bo Peng,
Ph.D.

Loading
simuPOP

Population

Structure of
population

Genotypic
structure

Population
structure

Population
variables

Manipulate
population

Individual

Operator

Mating
scheme

Simulator

Genotypic Structure

In-depth
course

Bo Peng,
Ph.D.

Loading
simuPOP

Population

Structure of
population

Genotypic
structure

Population
structure

Population
variables

Manipulate
population

Individual

Operator

Mating
scheme

Simulator

All individuals have the same genotypic structure, which refers to

- Ploidy (diploid, haploid, triploid, ...)
- Number of chromosomes
- Number of loci on each chromosome
- Names and positions of loci
- Names of information fields
- Allele names
- Existence of sex chromosome

Create a population

In-depth course

Bo Peng,
Ph.D.

Loading simuPOP

Population

Structure of
population

Genotypic
structure

Population
structure

Population
variables

Manipulate
population

Individual

Operator

Mating scheme

Simulator

```
>>> pop = population(size=10, loci=[2, 3])
>>> Dump(pop)
Ploidy:                2
Number of chrom:       2
Number of loci:        2 3
Maximum allele state:   65535
Loci positions:
                1 2
                1 2 3

Loci names:
                loc1-1 loc1-2
                loc2-1 loc2-2 loc2-3

population size:       10
Number of subPop:      1
Subpop sizes:         10
Number of ancestral populations: 0
individual info:
sub population 0:
    0: MU    0 0 0 0 0 | 0 0 0 0 0
    1: MU    0 0 0 0 0 | 0 0 0 0 0
    2: MU    0 0 0 0 0 | 0 0 0 0 0
    3: MU    0 0 0 0 0 | 0 0 0 0 0
```

Genotypic structure

In-depth course

Bo Peng,
Ph.D.

Loading simuPOP

Population

Structure of
population

Genotypic
structure

Population
structure

Population
variables

Manipulate
population

Individual

Operator

Mating scheme

Simulator

```
>>> pop = population(subPop=[200, 300], loci=[3, 2],
...     maxAllele=3, ploidy=4,
...     lociPos=[[1, 3, 5], [2.5, 4]],
...     alleleNames=['A', 'C', 'T', 'G'])
>>> pop.numLoci(0)
3
>>> pop.totNumLoci()
5
>>> pop.locusPos(4)
4.0
>>> pop.subPopSize(1)
300
>>> pop.popSize()
500
>>> pop.ploidyName()
'tetraploid'
>>> pop.individual(1).allele(1, 2)
0
>>>
```

Create a population with subpopulations

In-depth course

Bo Peng,
Ph.D.

Loading simuPOP

Population

Structure of
population

Genotypic
structure

Population
structure

Population
variables

Manipulate
population

Individual

Operator

Mating scheme

Simulator

```
>>> pop = population(subPop=[2, 5, 6], loci=[2])
>>> print pop.popSize()
13
>>> print pop.subPopSizes()
(2, 5, 6)
>>> print pop.subPopSize(1)
5
>>> Dump(pop, infoOnly=True)
Ploidy:                2
Number of chrom:       1
Number of loci:        2
Maximum allele state:  65535
Loci positions:
                        1 2
Loci names:
                        loc1-1 loc1-2
population size:       13
Number of subPop:      3
Subpop sizes:          2 5 6
Number of ancestral populations: 0
>>>
```


Mating happens within subpopulation

In-depth course

Bo Peng,
Ph.D.

Loading simuPOP

Population

Structure of population

Genotypic structure

Population structure

Population variables

Manipulate population

Individual

Operator

Mating scheme

Simulator

```
>>> pop = population(subPop=[5, 6], loci=[2])
>>> simu = simulator(pop, randomMating())
>>> simu.evolve(
...     preOps = [
...         initByFreq(alleleFreq=[0.2, 0.8], subPop=[0]),
...         initByFreq([0, 0, 0, 0.5, 0.5], subPop=[1])
...     ],
...     ops = [
...         dumper(alleleOnly=True, indRange=[[0, 3], [5, 7]]),
...         recombinator(rate=0.1) ],
...     end = 1
... )
```

Mating happens within subpopulation (cont.)

In-depth course

Bo Peng,
Ph.D.

Loading simuPOP

Population

Structure of
population
Genotypic
structure

Population
structure

Population
variables

Manipulate
population

Individual

Operator

Mating scheme

Simulator

```
individual info:
sub population 0:
  0: MU    1  1 |    1  1
  1: FU    0  1 |    1  1
  2: FU    1  1 |    1  1
sub population 1:
  5: FU    4  4 |    4  3
  6: MU    4  4 |    4  4
End of individual info.
```

No ancestral population recorded.

```
individual info:
sub population 0:
  0: FU    1  1 |    0  1
  1: FU    1  1 |    1  1
  2: MU    1  1 |    0  1
sub population 1:
  5: MU    4  4 |    4  3
  6: FU    4  4 |    4  3
End of individual info.
```

Population variables

In-depth course

Bo Peng,
Ph.D.

Loading simuPOP

Population

Structure of
population

Genotypic
structure

Population
structure

Population
variables

Manipulate
population

Individual

Operator

Mating scheme

Simulator

```
>>> pop = population(subPop=[5, 10], loci=[5])
>>> InitByFreq(pop, [.6, .3, .1])
>>> Stat(pop, alleleFreq=[1], genoFreq=[2])
>>> print pop.dvars().alleleFreq[1][0]
0.7
>>> from simuUtil import ListVars
>>> ListVars(pop.dvars(), useWxPython=False)
grp : -1
rep : -1
alleleNum :
  [1]
    [0]      21
    [1]       8
    [2]       1
genoFreq :
  [2]
    [0]
      0 :      0.2666666666667
      1 :      0.4
      2 :      0.2666666666667
    [1]
      1 :      0.0666666666667
genoNum :
  [2]
    [0]
      0 :      4.0
      1 :      6.0
      2 :      4.0
    [1]
      1 :      1.0
alleleFreq :
```

Population variables (cont.)

In-depth course

Bo Peng,
Ph.D.

Loading simuPOP

Population

Structure of
population

Genotypic
structure

Population
structure

Population
variables

Manipulate
population

Individual

Operator

Mating scheme

Simulator

```
subPop
[0]
  alleleNum :
    [1]
      [0] 6
      [1] 3
      [2] 1
  genoNum :
    [2]
      [0]
        1 : 3.0
        2 : 2.0
  genoFreq :
    [2]
      [0]
        1 : 0.6
        2 : 0.4
  alleleFreq :
    [1]
      [0] 0.6
      [1] 0.3
      [2] 0.1
[1]
  alleleNum :
    [1]
      [0] 15
```

Population manipulation

In-depth course

Bo Peng,
Ph.D.

Loading simuPOP

Population

Structure of
population

Genotypic
structure

Population
structure

Population
variables

Manipulate
population

Individual

Operator

Mating scheme

Simulator

```
>>> # make a copy of pop
>>> pop = population(1000, loci=[2,3])
>>> pop1 = pop.clone()
>>> # remove loci 2, 3, 4
>>> pop.removeLoci(keep=[0, 1])
>>> # pop2 will have 3 chromosomes, with loci 2, 3, 2
>>> pop2 = MergePopulationsByLoci(pops=[pop, pop1])
>>> # randomly assign alleles using given allele frequencies
>>> InitByFreq(pop2, [0.8, .2])
>>> # assign affection status using a penetrance model
>>> MapPenetrance(pop2, locus=1,
...               penetrance={'0-0': 0.05, '0-1': 0.2, '1-1': 0.8})
>>> # draw case control sample
>>> (sample,) = CaseControlSample(pop2, cases=5, controls=5)
>>> # save sample in Merlin QTDT format
>>> from simuUtil import SaveQTDT
>>> SaveQTDT(sample, output='sample', affectionCode=['U', 'A'],
...          fields=['affection'])
```

Population manipulation (cont.)

In-depth course

Bo Peng,
Ph.D.

Loading simuPOP

Population

Structure of
population

Genotypic
structure

Population
structure

Population
variables

Manipulate
population

Individual

Operator

Mating scheme

Simulator

```
>>> # have a look at the sample in Merlin-QTDT Format
>>> print open('sample.map').read()
CHROMOSOME MARKER POSITION
1      loc1-1  1.000000
1      loc1-2  2.000000
2      loc1-1_1      1.000000
2      loc1-2_1      2.000000
3      loc2-1  1.000000
3      loc2-2  2.000000
3      loc2-3  3.000000

>>> print open('sample.dat').read()
A      affection
M      loc1-1
M      loc1-2
M      loc1-1_1
M      loc1-2_1
M      loc2-1
M      loc2-2
M      loc2-3
```

Population manipulation (cont.)

In-depth course

Bo Peng,
Ph.D.

Loading simuPOP

Population

Structure of
population

Genotypic
structure

Population
structure

Population
variables

Manipulate
population

Individual

Operator

Mating scheme

Simulator

```
>>> print open('sample.ped').read()
1 1 0 0 2 A 1 1 1 2 2 1 1 1 1 1 1 1 2 1
2 1 0 0 1 A 1 1 1 1 1 1 1 1 1 1 1 1 1
3 1 0 0 2 A 1 2 2 1 1 1 1 1 1 1 2 1 1
4 1 0 0 1 A 1 1 1 2 1 1 1 1 1 1 1 1 1
5 1 0 0 2 A 2 1 2 2 1 1 1 1 1 1 1 1 1
6 1 0 0 1 U 1 1 1 1 1 1 2 2 1 1 1 1 2
7 1 0 0 1 U 1 1 1 1 1 1 1 1 1 1 1 1 1
8 1 0 0 2 U 1 1 1 2 1 1 1 2 2 1 1 1 2
9 1 0 0 2 U 1 1 1 1 1 1 1 1 1 1 2 1 1
10 1 0 0 1 U 1 2 1 2 1 1 1 1 2 1 2 1 1
>>>
```

Outline

In-depth
course

Bo Peng,
Ph.D.

Loading
simuPOP

Population

Individual

Structure of
individual

Individual object

Information fields

Iterate through a
population

Operator

Mating
scheme

Simulator

3 Individual

- Structure of individual
- Individual object
- Information fields
- Iterate through a population

Structure of individual

In-depth
course

Bo Peng,
Ph.D.

Loading
simuPOP

Population

Individual

Structure of
individual

Individual object
Information fields
Iterate through a
population

Operator

Mating
scheme

Simulator

Assume ploidy = 2, maxAllele = 1

0	1	2	3	4	5	6
0	1	1	1	0	0	1
0	0	1	1	1	0	1

0	1	2	3	4	5
0	1	0	0	0	1
1	0	1	1	0	0

Male

● Affected

fitness | father_idx | ...

Structure of individual

In-depth
course

Bo Peng,
Ph.D.

Loading
simuPOP

Population

Individual

Structure of
individual

Individual object
Information fields
Iterate through a
population

Operator

Mating
scheme

Simulator

Assume ploidy = 2, maxAllele = 1

0	1	2	3	4	5	6
0	1	1	1	0	0	1
0	0	1	1	1	0	1

Chromosome 0

0	1	2	3	4	5
0	1	0	0	0	1
1	0	1	1	0	0

Male

● Affected

fitness | father_idx | ...

Structure of individual

In-depth
course

Bo Peng,
Ph.D.

Loading
simuPOP

Population

Individual

Structure of
individual

Individual object
Information fields
Iterate through a
population

Operator

Mating
scheme

Simulator

Assume ploidy = 2, maxAllele = 1

0	1	2	3	4	5	6
0	1	1	1	0	0	1
0	0	1	1	1	0	1

Chromosome 0

0	1	2	3	4	5
0	1	0	0	0	1
1	0	1	1	0	0

Chromosome 1

Male

● Affected

fitness	father_idx	...
---------	------------	-----

Structure of individual

In-depth
course

Bo Peng,
Ph.D.

Loading
simuPOP

Population

Individual

Structure of
individual

Individual object
Information fields
Iterate through a
population

Operator

Mating
scheme

Simulator

Assume ploidy = 2, maxAllele = 1

0	1	2	3	4	5	6
0	1	1	1	0	0	1
0	0	1	1	1	0	1

Chromosome 0

0	1	2	3	4	5
0	1	0	0	0	1
1	0	1	1	0	0

Chromosome 1

Male

Sex

● Affected

fitness | father_idx | ...

Structure of individual

In-depth
course

Bo Peng,
Ph.D.

Loading
simuPOP

Population

Individual

Structure of
individual

Individual object
Information fields
Iterate through a
population

Operator

Mating
scheme

Simulator

Assume ploidy = 2, maxAllele = 1

0	1	2	3	4	5	6
0	1	1	1	0	0	1
0	0	1	1	1	0	1

Chromosome 0

0	1	2	3	4	5
0	1	0	0	0	1
1	0	1	1	0	0

Chromosome 1

Male

Sex

● Affected

Affection status

fitness | father_idx | ...

Structure of individual

In-depth course

Bo Peng,
Ph.D.

Loading
simuPOP

Population

Individual

Structure of
individual

Individual object
Information fields
Iterate through a
population

Operator

Mating
scheme

Simulator

Assume ploidy = 2, maxAllele = 1

0	1	2	3	4	5	6
0	1	1	1	0	0	1
0	0	1	1	1	0	1

Chromosome 0

0	1	2	3	4	5
0	1	0	0	0	1
1	0	1	1	0	0

Chromosome 1

Male

Sex

● Affected

Affection status

fitness | father_idx | ...

Information
fields

Individual

In-depth course

Bo Peng,
Ph.D.

Loading simuPOP

Population

Individual

Structure of individual

Individual object

Information fields Iterate through a population

Operator

Mating scheme

Simulator

```
>>> pop = population(subPop=[100, 200], loci=[2, 3])
>>> # the first individual
>>> ind1 = pop.individual(0)
>>> # the second individual in the second subpop
>>> ind2 = pop.individual(1, 1)
>>> # genotypic strcuture
>>> print ind1.numLoci(1)
3
>>> print ind1.numChrom()
2
>>> # an editable allele list
>>> alleles = ind1.arrGenotype(0)
>>> alleles[:] = range(ind1.totNumLoci())
>>> print ind1.arrGenotype(0)
[0, 1, 2, 3, 4]
>>> # ploidy 1, index 4
>>> ind1.setAllele(3, 4, 1)
>>> print ind1.allele(4, 1)
3
>>>
```

Information fields

In-depth course

Bo Peng,
Ph.D.

Loading simuPOP

Population

Individual

Structure of individual
Individual object

Information fields

Iterate through a population

Operator

Mating scheme

Simulator

Pieces of information that can be attached to each individual, e.g.

- `fitness`: fitness of each individual, calculated by selectors
- `father_idx`, `mother_idx`: index of parents in the parental generation
- `old_index`: index of an individual in the population where it is sampled

Or, self-defined

- birthday
- geographic location
- ...

Information fields

In-depth course

Bo Peng,
Ph.D.

Loading simuPOP

Population

Individual

Structure of
individual

Individual object

Information fields

Iterate through a
population

Operator

Mating
scheme

Simulator

```
>>> pop = population(100, loci=[5, 8],  
...                 infoFields=['father_idx', 'mother_idx'])  
>>> simu = simulator(pop, randomMating(numOffspring=2))  
>>> simu.evolve(ops=[parentsTagger()], end=5)  
True  
>>> ind = simu.population(0).individual(0)  
>>> ind1 = simu.population(0).individual(1)  
>>> print ind.info('father_idx'), ind.info('mother_idx')  
48.0 40.0  
>>> print ind1.info('father_idx'), ind1.info('mother_idx')  
48.0 40.0  
>>>  
>>>
```

Iterate through a population

In-depth course

Bo Peng,
Ph.D.

Loading simuPOP

Population

Individual

Structure of individual

Individual object

Information fields

Iterate through a population

Operator

Mating scheme

Simulator

```
>>> pop = population(subPop=[5, 8], loci=[5],
...   infoFields=['penetrance'])
>>> InitByFreq(pop, [.6, .3, .1])
>>> MaPenetrance(pop, locus=2, penetrance=[0.05, 0.2, 0.5],
...   wildtype=[0], infoFields=['penetrance'])
>>> # iterate through all individuals in subPop 1
>>> for ind in pop.individuals(1):
...     print 'Aff: %d Fit: %.3f Geno: %d %d' % \
...           (ind.affected(), ind.info('penetrance'), \
...           ind.allele(2, 0), ind.allele(2, 1))
...
Aff: 1 Fit: 0.200 Geno: 0 1
Aff: 0 Fit: 0.200 Geno: 0 2
Aff: 0 Fit: 0.200 Geno: 1 0
Aff: 0 Fit: 0.200 Geno: 1 0
Aff: 0 Fit: 0.200 Geno: 2 0
Aff: 0 Fit: 0.050 Geno: 0 0
Aff: 0 Fit: 0.050 Geno: 0 0
Aff: 0 Fit: 0.500 Geno: 1 1
>>>
```

Outline

In-depth course

Bo Peng,
Ph.D.

Loading simuPOP

Population

Individual

Operator

Function form of an
operator

Stage of an
operator

Applicable
generations

Replicates and
replicate groups

Output and output
expression

Python Operators

Mating scheme

Simulator

4

Operator

- Function form of an operator
- Stage of an operator
- Applicable generations
- Replicates and replicate groups
- Output and output expression
- Python Operators

Function form of an operator

In-depth
course

Bo Peng,
Ph.D.

Loading
simuPOP

Population

Individual

Operator

Function form of an
operator

Stage of an
operator

Applicable
generations

Replicates and
replicate groups

Output and output
expression

Python Operators

Mating
scheme

Simulator

Many operators can be applied to a population in its function form. For example `Dump(pop, args)` is equivalent to `dumper(args).apply(pop)`. For example

operator	Function	operator	Function
<code>dumper</code>	<code>Dump</code>	<code>mergeSubPops</code>	<code>MergeSubPops</code>
<code>initByFreq</code>	<code>InitByFreq</code>	<code>splitSubPop</code>	<code>SplitSubPop</code>
<code>initByValue</code>	<code>InitByValue</code>	<code>mapSelector</code>	<code>MapSelect</code>
<code>stat</code>	<code>Stat</code>	<code>maSelector</code>	<code>MaSelect</code>
<code>kamMutator</code>	<code>KamMutate</code>	<code>mapPenetrance</code>	<code>MapPenetrance</code>
<code>smmMutator</code>	<code>SmmMutate</code>	<code>caseControlSample</code>	<code>CaseControlSample</code>
<code>pyMutator</code>	<code>PyMutate</code>	<code>largePedigreeSample</code>	<code>LargePedigreeSample</code>

Stage of an operator

In-depth course

Bo Peng,
Ph.D.

Loading simuPOP

Population

Individual

Operator

Function form of an operator

Stage of an operator

Applicable generations


Replicates and replicate groups

Output and output expression

Python Operators

Mating scheme

Simulator



Parental
generation

Stage of an operator

In-depth
course

Bo Peng,
Ph.D.

Loading
simuPOP

Population

Individual

Operator

Function form of an
operator

Stage of an
operator

Applicable
generations

Replicates and
replicate groups


Output and output
expression

Python Operators

Mating
scheme

Simulator

Pre-mating
operators



Parental
generation

Stage of an operator

In-depth
course

Bo Peng,
Ph.D.

Loading
simuPOP

Population

Individual

Operator

Function form of an
operator

Stage of an
operator

Applicable
generations


Replicates and
replicate groups

Output and output
expression

Python Operators

Mating
scheme

Simulator



Stage of an operator

In-depth course

Bo Peng,
Ph.D.

Loading simuPOP

Population

Individual

Operator

Function form of an operator

Stage of an operator

Applicable generations


Replicates and replicate groups

Output and output expression

Python Operators

Mating scheme

Simulator



Stage of an operator

In-depth course

Bo Peng,
Ph.D.

Loading simuPOP

Population

Individual

Operator

Function form of an operator

Stage of an operator

Applicable generations


Replicates and replicate groups

Output and output expression

Python Operators

Mating scheme

Simulator



Stage of an operator

In-depth course

Bo Peng,
Ph.D.

Loading simuPOP

Population

Individual

Operator

Function form of an operator

Stage of an operator

Applicable generations


Replicates and replicate groups

Output and output expression

Python Operators

Mating scheme

Simulator



Stage of an operator

In-depth course

Bo Peng,
Ph.D.

Loading simuPOP

Population

Individual

Operator

Function form of an operator

Stage of an operator

Applicable generations


Replicates and replicate groups

Output and output expression

Python Operators

Mating scheme

Simulator



Pre-, During-, and PostMating operators

In-depth course

Bo Peng,
Ph.D.

Loading simuPOP

Population

Individual

Operator

Function form of an operator

Stage of an operator

Applicable generations

Replicates and replicate groups

Output and output expression

Python Operators

Mating scheme

Simulator

```
>>> simu = simulator(
...     population(subPop=[20, 80], loci=[3]),
...     randomMating())
>>> simu.evolve(
...     preOps = [initByFreq([0.2, 0.8])],
...     ops = [
...         kamMutator(maxAllele=10, rate=0.00005, atLoci=[0,2]),
...         recombinator(rate=0.001),
...         dumper(stage=PrePostMating),
...         stat(alleleFreq=[1]),
...     ],
...     dryrun=True
... )
```

Dryrun mode: display calling sequence

Apply pre-evolution operators

```
Replicate 0
- <simuPOP::initByFreq> end at 1
```

Start evolution

```
Replicate 0
Pre-mating operators
- <simuPOP::dumper> at all generations
Start mating
- <simuPOP::recombination> at all generations
```

Apply post-mating operators

```
- <simuPOP::k-allele model mutator K=10> at all generations
- <simuPOP::dumper> at all generations
- <simuPOP::statistics> at all generations
```

True

```
>>>
```

Applicable generations

In-depth course

Bo Peng,
Ph.D.

Loading simuPOP

Population

Individual

Operator

Function form of an operator

Stage of an operator

Applicable generations

Replicates and replicate groups

Output and output expression

Python Operators

Mating scheme

Simulator

```
>>> simu = simulator(
...     population(10000, loci=[3]),
...     randomMating())
>>> eval1 = r"'Gen: %3d Freq: %f\n' % (gen, alleleFreq[1][0])"
>>> eval2 = r"'Last Gen: %3d Freq: %s\n' % (gen, alleleFreq[1])"
>>> simu.evolve(
...     preOps = [initByFreq([0.3, 0.7])],
...     ops = [
...         recombinator(rate=0.01, begin=10, end=30),
...         stat(alleleFreq=[1], step=10),
...         pyEval(eval1, step=10),
...         pyEval(eval2, at=[-1])
...     ],
...     end = 50
... )
Gen: 0 Freq: 0.304200
Gen: 10 Freq: 0.290700
Gen: 20 Freq: 0.285300
Gen: 30 Freq: 0.288750
Gen: 40 Freq: 0.283750
Gen: 50 Freq: 0.284100
Last Gen: 50 Freq: [0.28410000000000002, 0.71589999999999998]
True
>>>
```

Applicable replicates

In-depth course

Bo Peng,
Ph.D.

Loading simuPOP

Population

Individual

Operator

Function form of an operator

Stage of an operator

Applicable generations

Replicates and replicate groups

Output and output expression

Python Operators

Mating scheme

Simulator

```
>>> simu = simulator(
...     population(100, loci=[3]),
...     randomMating(),
...     rep=5, grp=[1,1,2,2,2])
>>> simu.evolve(
...     preOps = [initByFreq([0.5, 0.5])],
...     ops = [
...         stat(alleleFreq=[1]),
...         recombinator(rate=0.01, grp=1),
...         recombinator(rate=0.01, grp=2),
...         pyEval(r"'%.2f ' % alleleFreq[1][0]", grp=1),
...         pyEval(r"'\\n'", rep=REP_LAST),
...     ],
...     end=5
... )
0.47 0.52
0.49 0.56
0.51 0.60
0.52 0.62
0.56 0.60
0.52 0.62
True
>>>
```

Output

In-depth course

Bo Peng,
Ph.D.

Loading simuPOP

Population

Individual

Operator

Function form of an operator

Stage of an operator

Applicable generations

Replicates and replicate groups

Output and output expression

Python Operators

Mating scheme

Simulator

```
>>> simu = simulator(
...     population(100, loci=[3]),
...     randomMating(),
...     rep=5, grp=[1,1,2,2,2])
>>> simu.evolve(
...     preOps = [initByFreq([0.5, 0.5])],
...     ops = [
...         stat(alleleFreq=[1]),
...         pyEval(r"'%.2f ' % alleleFreq[1][0]",
...             output='>>out'),
...         pyEval(r"\n", rep=REP_LAST, output='>>out'),
...         pyEval(r"'%.2f ' % alleleFreq[1][0]",
...             outputExpr=">>out%d' % grp"),
...     ],
...     end=2
... )
True
>>> print open('out').read()
0.56 0.55 0.46 0.47 0.54
0.56 0.55 0.42 0.55 0.57
0.58 0.56 0.40 0.57 0.56

>>> print open('out1').read()
0.56 0.55 0.56 0.55 0.58 0.56
>>> print open('out2').read()
0.46 0.47 0.54 0.42 0.55 0.57 0.40 0.57 0.56
>>>
```

Python operator

In-depth course

Bo Peng,
Ph.D.

Loading simuPOP

Population

Individual

Operator

Function form of an
operator

Stage of an
operator

Applicable
generations

Replicates and
replicate groups

Output and output
expression

Python Operators

Mating scheme

Simulator

A **Python operator** is an operator that calls a user-provided Python function when it is applied to a population. A **hybrid operator** performs its main function at the C++ level, and a **pure Python operator** depends on this user-provided function for its functionality.

A hybrid operator

In-depth course

Bo Peng,
Ph.D.

Loading simuPOP

Population

Individual

Operator

Function form of an operator

Stage of an operator

Applicable generations

Replicates and replicate groups

Output and output expression

Python Operators

Mating scheme

Simulator

A (weird) selector with fitness

	BB	Bb	bb
AA	1.	1.01	1.02
Aa	1.	0.99	0.98
aa	1.	1.01	1.02

```
>>> def mySelector(geno, gen):
...     if geno[0] + geno[1] == 0:
...         return (1, 1.01, 1.02)[geno[2] + geno[3]]
...     elif geno[0] + geno[1] == 1:
...         return (1, 0.99, 0.98)[geno[2] + geno[3]]
...     else:
...         return (1, 1.01, 1.02)[geno[2] + geno[3]]
... 
```

Note: This operator can be more efficiently implemented using other non-Python operators.

A hybrid operator (cont.).

In-depth course

Bo Peng,
Ph.D.

Loading simuPOP

Population

Individual

Operator

Function form of an operator

Stage of an operator

Applicable generations

Replicates and replicate groups

Output and output expression

Python Operators

Mating scheme

Simulator

```
>>> expr = r'"%.3f %.3f\n" % (alleleFreq[0][0], alleleFreq[1][0])'
>>> simu = simulator(
...     population(10000, loci=[1,1],
...     infoFields=['fitness']),
...     randomMating(),
... )
>>> simu.evolve(
...     preOps = [initByFreq([0.3, 0.7])],
...     ops = [
...         pySelector(loci=[0, 1], func=mySelector),
...         stat(alleleFreq=[0, 1], step=20),
...         pyEval(expr, step=20)
...     ],
...     end = 100
... )
0.294 0.298
0.252 0.278
0.184 0.246
0.134 0.232
0.078 0.215
0.047 0.209
True
>>>
```

A pure Python operator

In-depth course

Bo Peng,
Ph.D.

Loading simuPOP

Population

Individual

Operator

Function form of an operator

Stage of an operator

Applicable generations

Replicates and replicate groups

Output and output expression

Python Operators

Mating scheme

Simulator

```
>>> from random import normalvariate
>>> def trait(ind):
...     return [ind.info('trait') + normalvariate(0, 1)]
...
>>> def avgTrait(pop):
...     t = sum(pop.indInfo('trait', False))/pop.popSize()
...     pop.dvars().trait = t
...     print 'Average trait at gen %4d : %.4f' % (pop.gen(), t)
...     return True
...
>>> simu = simulator(
...     population(100, infoFields=['trait']),
...     randomMating()
... )
>>> simu.evolve(
...     ops = [
...         pyIndOperator(func=trait, infoFields=['trait']),
...         pyOperator(func=avgTrait, step=100),
...     ],
...     end = 500
... )
Average trait at gen    0 : 0.0218
Average trait at gen  100 : 1.2040
Average trait at gen  200 : 0.8297
Average trait at gen  300 : 0.9698
Average trait at gen  400 : 0.3187
Average trait at gen  500 : -0.2373
True
>>>
```

Outline

In-depth
course

Bo Peng,
Ph.D.

Loading
simuPOP

Population

Individual

Operator

Mating
scheme

Demographic
model

Number of
offspring

Simulator

5

Mating scheme

- Demographic model
- Number of offspring

Mating schemes

In-depth
course

Bo Peng,
Ph.D.

Loading
simuPOP

Population

Individual

Operator

Mating
scheme

Demographic
model

Number of
offspring

Simulator

Mating schemes

- Populate offspring subpopulation from corresponding parental subpopulation
- Can not change number of subpopulations
- Can change subpopulation size
- Select parents according to their `fitness` value (information field)
- Can produce more than one offspring

Demographic model

In-depth course

Bo Peng,
Ph.D.

Loading simuPOP

Population

Individual

Operator

Mating scheme

Demographic model

Number of offspring

Simulator

```
>>> def lin_inc(gen, oldsize=[]):
...     return [10+gen]*5
...
>>> simu = simulator(
...     population(subPop=lin_inc(1), loci=[1]),
...     randomMating(newSubPopSizeFunc=lin_inc)
... )
>>> simu.evolve(
...     ops = [
...         stat(popSize=True),
...         pyEval(r'"%d %d\n"%(gen, subPop[0]["popSize"])'),
...     ],
...     end=5
... )
0 10
1 11
2 12
3 13
4 14
5 15
True
>>>
```

Number of offspring

In-depth course

Bo Peng,
Ph.D.

Loading simuPOP

Population

Individual

Operator

Mating scheme

Demographic
model

Number of
offspring

Simulator

```
>>> simu = simulator(  
...     population(size=10000, loci=[1]),  
...     randomMating(),  
... )  
>>> simu.evolve(  
...     preOps = [initByFreq([0.1, 0.9])],  
...     ops = [ ], end=100  
... )  
True  
>>> simu.setMatingScheme(randomMating(numOffspring=2))  
>>> simu.addInfoFields(['father_idx', 'mother_idx'])  
>>> simu.setAncestralDepth(1)  
>>> simu.step(ops=[parentsTagger()])  
True  
>>> pop = simu.getPopulation(0)  
>>> MaPenetrance(pop, locus=0, penetrance=[0.05, 0.1, 0.5])  
>>> AffectedSibpairSample(pop, size=100)  
[<simuPOP::population of size 200>]  
>>>
```

Outline

In-depth
course

Bo Peng,
Ph.D.

Loading
simuPOP

Population

Individual

Operator

Mating
scheme

Simulator

What a simulator
does

Simulator
operations

Retrieve
populations

6 Simulator

- What a simulator does
- Simulator operations
- Retrieve populations

Simulator

In-depth course

Bo Peng,
Ph.D.

Loading simuPOP

Population

Individual

Operator

Mating scheme

Simulator

What a simulator
does

Simulator
operations

Retrieve
populations

A simulator manages

- Replicates of a population
- A mating scheme
- Many operators

and evolve the populations.

simulator operations

In-depth course

Bo Peng,
 Ph.D.

Loading
 simuPOP

Population

Individual

Operator

Mating
 scheme

Simulator

What a simulator
 does

Simulator
 operations

Retrieve
 populations

```
>>> simu = simulator(
...     population(size=10000, loci=[3]),
...     randomMating(),
... )
>>> # genotypic structure can be accessed at the simulator level
>>> print simu.lociPos()
(1.0, 2.0, 3.0)
>>> simu.step(ops = [])
True
>>> print simu.gen()
1
>>> # add information fields to all populations
>>> simu.addInfoFields(['father_idx', 'mother_idx'])
>>> simu.setMatingScheme(randomMating(numOffspring=2))
>>>
```

Get populations from a simulator

In-depth course

Bo Peng,
Ph.D.

Loading simuPOP

Population

Individual

Operator

Mating scheme

Simulator

What a simulator
does

Simulator
operations

Retrieve
populations

```
>>> # get a reference to the first replicate
>>> pop = simu.population(0)
>>> pop.individual(0).setAllele(1, 0)
>>> print simu.population(0).individual(0).allele(0)
1
>>> # get a real copy
>>> pop = simu.getPopulation(0)
>>> pop.individual(0).setAllele(1, 1)
>>> print simu.population(0).individual(0).allele(1)
0
>>>
```