

# BCurve

P. Baillehache

October 30, 2017

## Contents

<b>1</b>	<b>Definitions</b>	<b>2</b>
1.1	BCurve definition . . . . .	2
1.2	BCurve from cloud points . . . . .	2
<b>2</b>	<b>Interface</b>	<b>3</b>
<b>3</b>	<b>Code</b>	<b>6</b>
<b>4</b>	<b>Makefile</b>	<b>21</b>
<b>5</b>	<b>Usage</b>	<b>21</b>

## Introduction

BCurve is C library to manipulate Bezier curves of any dimension and order.

It offers function to create, clone, load, save and modify a curve, to print it, to scale, rotate (in 2D) or translate it, to get its approximate length (sum of distance between control points), to create a BCurve connecting points of a point cloud, to get the weights (coefficients of each control point given the value of the parameter of the curve), and to get the bounding box.

The library also includes a SCurve structure which is simply a GSet|BCurve| to manipulate a set of curves.

# 1 Definitions

## 1.1 BCurve definition

A BCurve  $B$  is defined by its dimension  $D \in \mathbb{N}_+^*$ , its order  $O \in \mathbb{N}_+$  and its  $(O + 1)$  control points  $\vec{C}_i$  (vectors of dimension  $D$ ). The curve in dimension  $D$  associated to the BCurve  $B$  is defined by  $\vec{B}(t)$ :

$$\begin{cases} \vec{B}(t) = \sum_{i=0}^O W_i^O(t) \vec{C}_i & \text{if } t \in [0.0, 1.0] \\ \vec{B}(t) = \vec{C}_0 & \text{if } t < 0.0 \\ \vec{B}(t) = \vec{C}_O & \text{if } t > 1.0 \end{cases} \quad (1)$$

where, if  $O = 0$

$$W_0^0(t) = 1.0 \quad (2)$$

and if  $O \neq 0$

$$\begin{cases} W_0^1(t) = 1.0 - t \\ W_1^1(t) = t \\ W_{-1}^i(t) = 0.0 \\ W_j^i(t) = (1.0 - t)W_j^{i-1}(t) + tW_{j-1}^{i-1}(t) & \text{for } i \in [2, O], j \in [0, i] \end{cases} \quad (3)$$

## 1.2 BCurve from cloud points

Given the cloud points made of  $N$  points  $\vec{P}_i$ , the BCurve of order  $N - 1$  passing through the  $N$  points (in the same order  $\vec{P}_0, \vec{P}_1, \vec{P}_2, \dots$  as given in input) can be obtained as follow.

If  $N = 1$  the solution is trivial:  $\vec{C}_0 = \vec{P}_0$ . As well, if  $N = 2$  the solution is trivial:  $\vec{C}_0 = \vec{P}_0$  and  $\vec{C}_1 = \vec{P}_1$ .

If  $N > 2$ , we need first to define the  $N$  values  $t_i$  corresponding to each  $\vec{P}_i$  ( $\vec{B}(t_i) = \vec{P}_i$ ). We will consider here  $t_i$  such as

$$t_i = \frac{L(\vec{P}_i)}{L(\vec{P}_{N-1})} \quad (4)$$

where

$$\begin{cases} L(P_0) = 0.0 \\ L(P_i) = \sum_{j=1}^i \left\| \overrightarrow{P_{j-1}P_j} \right\| \end{cases} \quad (5)$$

then we can calculate the  $C_i$  as follow. We have  $\vec{C}_0 = \vec{P}_0$  and  $\vec{C}_{N-1} = \vec{P}_{N-1}$ , and others  $\vec{C}_i$  can be obtained by solving the linear system below for each dimension:

$$\begin{bmatrix} W_1^{N-1}(t_1) & \dots & W_{N-2}^{N-1}(t_1) \\ \vdots & \ddots & \vdots \\ W_1^{N-1}(t_{N-2}) & \dots & W_{N-2}^{N-1}(t_{N-2}) \end{bmatrix} \begin{bmatrix} C_1 \\ \vdots \\ C_{N-2} \end{bmatrix} = \begin{bmatrix} P_1 - (W_0^{N-1}(t_1)P_0 + W_{N-1}^{N-1}(t_1)P_{N-1}) \\ \vdots \\ P_{N-2} - (W_0^{N-1}(t_{N-2})P_0 + W_{N-1}^{N-1}(t_{N-2})P_{N-1}) \end{bmatrix} \quad (6)$$

## 2 Interface

```
// ===== BCURVE.H =====

#ifndef BCURVE_H
#define BCURVE_H

// ===== Include =====

#include <stdlib.h>
#include <stdio.h>
#include <math.h>
#include <string.h>
#include <stdbool.h>
#include "pbmath.h"
#include "gset.h"

// ===== Define =====

// ===== Data structure =====

typedef struct BCurve {
    // Order
    int _order;
    // Dimension
    int _dim;
    // array of (_order + 1) control points defining the curve
    VecFloat **_ctrl;
} BCurve;

typedef struct SCurve {
    // Dimension
    int _dim;
    // Set of BCurve
    GSet *_curves;
} SCurve;

// ===== Functions declaration =====

// Create a new BCurve of order 'order' and dimension 'dim'
// Return NULL if we couldn't create the BCurve
BCurve* BCurveCreate(int order, int dim);
```

```

// Clone the BCurve
// Return NULL if we couldn't clone the BCurve
BCurve* BCurveClone(BCurve *that);

// Load the BCurve from the stream
// If the BCurve is already allocated, it is freed before loading
// Return 0 in case of success, or:
// 1: invalid arguments
// 2: can't allocate memory
// 3: invalid data
// 4: fscanf error
// 5: VecLoad error
int BCurveLoad(BCurve **that, FILE *stream);

// Save the BCurve to the stream
// Return 0 upon success, else
// 1: invalid arguments
// 2: fprintf error
// 3: VecSave error
int BCurveSave(BCurve *that, FILE *stream);

// Free the memory used by a BCurve
// Do nothing if arguments are invalid
void BCurveFree(BCurve **that);

// Print the BCurve on 'stream'
// Do nothing if arguments are invalid
void BCurvePrint(BCurve *that, FILE *stream);

// Set the value of the iCtrl-th control point to v
// Do nothing if arguments are invalid
void BCurveSet(BCurve *that, int iCtrl, VecFloat *v);

// Get the value of the BCurve at parameter 'u' (in [0.0, 1.0])
// Return NULL if arguments are invalid or malloc failed
// if 'u' < 0.0 it is replaced by 0.0
// if 'u' > 1.0 it is replaced by 1.0
VecFloat* BCurveGet(BCurve *that, float u);

// Get the order of the BCurve
// Return -1 if argument is invalid
int BCurveOrder(BCurve *that);

// Get the dimension of the BCurve
// Return 0 if argument is invalid
int BCurveDim(BCurve *that);

// Get the approximate length of the BCurve (sum of dist between
// control points)
// Return 0.0 if argument is invalid
float BCurveApproxLen(BCurve *that);

// Rotate the curve CCW by 'theta' radians relatively to the origin
// Do nothing if arguments are invalid
void BCurveRot2D(BCurve *that, float theta);

// Scale the curve by 'v' relatively to the origin
// Do nothing if arguments are invalid
void BCurveScale(BCurve *that, VecFloat *v);

// Translate the curve by 'v'

```

```

// Do nothing if arguments are invalid
void BCurveTranslate(BCurve *that, VecFloat *v);

// Create a BCurve which pass through the points given in the GSet 'set'
// The GSet must contains VecFloat of same dimensions
// The BCurve pass through the points in the order they are given
// in the GSet. The points don't need to be uniformly distributed
// The created BCurve is of same dimension as the VecFloat and of order
// equal to the number of VecFloat in 'set' minus one
// Return NULL if it couldn't create the BCurve or the arguments are
// invalid
BCurve* BCurveFromCloudPoint(GSet *set);

// Get a VecFloat of dimension equal to the number of control points
// Values of the VecFloat are the weight of each control point in the
// BCurve given the curve's order and the value of 't' (in [0.0,1.0])
// Return null if the arguments are invalid or memory allocation failed
VecFloat* BCurveGetWeightCtrlPt(BCurve *that, float t);

// Get the bounding box of the BCurve.
// Return a Facoid whose axis are aligned on the standard coordinate
// system.
// Return NULL if arguments are invalid.
Shapoid* BCurveGetBoundingBox(BCurve *that);

// Create a new SCurve of dimension 'dim'
// Return NULL if we couldn't create the SCurve
SCurve* SCurveCreate(int dim);

// Clone the SCurve
// Return NULL if we couldn't clone the SCurve
SCurve* SCurveClone(SCurve *that);

// Load the SCurve from the stream
// If the SCurve is already allocated, it is freed before loading
// Return 0 in case of success, or:
// 1: invalid arguments
// 2: can't allocate memory
// 3: invalid data
// 4: fscanff error
// 5: BCurveLoad error
int SCurveLoad(SCurve **that, FILE *stream);

// Save the SCurve to the stream
// Return 0 upon success, else
// 1: invalid arguments
// 2: fprintf error
// 3: BCurveSave error
int SCurveSave(SCurve *that, FILE *stream);

// Free the memory used by a SCurve
// Do nothing if arguments are invalid
void SCurveFree(SCurve **that);

// Print the SCurve on 'stream'
// Do nothing if arguments are invalid
void SCurvePrint(SCurve *that, FILE *stream);

// Set the 'iCurve'-th BCurve to a clone of 'curve'
// 'iCurve' must be in [0, current number of BCurve]
// 'curve' 's dimension must be equal to SCurve's dimension
// Do nothing if arguments are invalid

```

```

void SCurveSet(SCurve *that, int iCurve, BCurve *curve);

// Append a clone of 'curve'
// 'curve' 's dimension must be equal to SCurve's dimension
// Do nothing if arguments are invalid
void SCurveAdd(SCurve *that, BCurve *curve);

// Remove the 'iCurve'-th BCurve from the SCurve
// Return NULL if arguments are invalid
BCurve* SCurveRemove(SCurve *that, int iCurve);

// Get the 'iCurve'-th BCurve of the SCurve without removing it
// Return NULL if arguments are invalid
BCurve* SCurveGet(SCurve *that, int iCurve);

// Get the number of BCurve in the SCurve
// Return 0 if arguments are invalid
int SCurveGetNbCurve(SCurve *that);

// Get the dimension of the SCurve
// Return 0 if argument is invalid
int SCurveDim(SCurve *that);

// Get the approximate length of the SCurve (sum of approxLen
// of its BCurves)
// Return 0.0 if argument is invalid
float SCurveApproxLen(SCurve *that);

// Rotate the SCurve CCW by 'theta' radians relatively to the origin
// Do nothing if arguments are invalid
void SCurveRot2D(SCurve *that, float theta);

// Scale the SCurve by 'v' relatively to the origin
// Do nothing if arguments are invalid
void SCurveScale(SCurve *that, VecFloat *v);

// Translate the SCurve by 'v'
// Do nothing if arguments are invalid
void SCurveTranslate(SCurve *that, VecFloat *v);

// Get the bounding box of the SCurve.
// Return a Facoid whose axis are aligned on the standard coordinate
// system.
// Return NULL if arguments are invalid.
Shapoid* SCurveGetBoundingBox(SCurve *that);

#endif

```

### 3 Code

```

// ===== BCURVE.C =====

// ===== Include =====

#include "bcurve.h"

// ===== Define =====

// ===== Functions implementation =====

```

```

// Create a new BCurve of order 'order' and dimension 'dim'
// Return NULL if we couldn't create the BCurve
BCurve* BCurveCreate(int order, int dim) {
    // Check arguments
    if (order < 0 || dim < 1)
        return NULL;
    // Allocate memory
    BCurve *that = (BCurve*)malloc(sizeof(BCurve));
    // If we could allocate memory
    if (that != NULL) {
        // Set the values
        that->_dim = dim;
        that->_order = order;
        // Allocate memory for the array of control points
        that->_ctrl = (VecFloat**)malloc(sizeof(VecFloat*) * (order + 1));
        // If we couldn't allocate memory
        if (that->_ctrl == NULL) {
            // Free memory
            free(that);
            // Stop here
            return NULL;
        }
        // For each control point
        for (int iCtrl = 0; iCtrl < order + 1; ++iCtrl) {
            // Allocate memory
            that->_ctrl[iCtrl] = VecFloatCreate(dim);
            // If we couldn't allocate memory
            if (that->_ctrl[iCtrl] == NULL) {
                // Free memory
                BCurveFree(&that);
                // Stop here
                return NULL;
            }
        }
    }
    // Return the new BCurve
    return that;
}

// Clone the BCurve
// Return NULL if we couldn't clone the BCurve
BCurve* BCurveClone(BCurve *that) {
    // Check argument
    if (that == NULL)
        return NULL;
    // Allocate memory for the clone
    BCurve *clone = (BCurve*)malloc(sizeof(BCurve));
    // If we could allocate memory
    if (clone != NULL) {
        // Clone the properties
        clone->_dim = that->_dim;
        clone->_order = that->_order;
        // Allocate memory for the array of control points
        clone->_ctrl = (VecFloat**)malloc(sizeof(VecFloat*) *
            (clone->_order + 1));
        // If we couldn't allocate memory
        if (clone->_ctrl == NULL) {
            // Free memory
            free(clone);
            // Stop here
            return NULL;
        }
    }
}

```

```

    }
    // For each control point
    for (int iCtrl = 0; iCtrl < clone->_order + 1; ++iCtrl) {
        // Clone the control point
        clone->_ctrl[iCtrl] = VecClone(that->_ctrl[iCtrl]);
        // If we couldn't clone the control point
        if (clone->_ctrl[iCtrl] == NULL) {
            // Free memory
            BCurveFree(&clone);
            // Stop here
            return NULL;
        }
    }
}
// Return the clone
return clone;
}

// Load the BCurve from the stream
// If the BCurve is already allocated, it is freed before loading
// Return 0 in case of success, or:
// 1: invalid arguments
// 2: can't allocate memory
// 3: invalid data
// 4: fscanf error
// 5: VecLoad error
int BCurveLoad(BCurve **that, FILE *stream) {
    // Check arguments
    if (that == NULL || stream == NULL)
        return 1;
    // If 'that' is already allocated
    if (*that != NULL) {
        // Free memory
        BCurveFree(that);
    }
    // Read the order and dimension
    int order;
    int dim;
    int ret = fscanf(stream, "%d %d", &order, &dim);
    // If we couldn't read
    if (ret == EOF) {
        return 4;
    }
    // Allocate memory
    *that = BCurveCreate(order, dim);
    // If we couldn't allocate memory
    if (*that == NULL) {
        return 2;
    }
    // For each control point
    for (int iCtrl = 0; iCtrl < (order + 1); ++iCtrl) {
        // Load the control point
        ret = VecLoad((*that)->_ctrl + iCtrl, stream);
        // If we couldn't read the control point or the control point
        // is not of the correct dimension
        if (ret != 0 || VecDim((*that)->_ctrl[iCtrl]) != (*that)->_dim) {
            // Free memory
            BCurveFree(that);
            // Stop here
            return 5;
        }
    }
}

```



```

    // Return success code
    return 0;
}

// Save the BCurve to the stream
// Return 0 upon success, or
// 1: invalid arguments
// 2: fprintf error
// 3: VecSave error
int BCurveSave(BCurve *that, FILE *stream) {
    // Check arguments
    if (that == NULL || stream == NULL)
        return 1;
    // Save the order and dimension
    int ret = fprintf(stream, "%d %d\n", that->_order, that->_dim);
    // If the fprintf failed
    if (ret < 0) {
        // Stop here
        return 2;
    }
    // For each control point
    for (int iCtrl = 0; iCtrl < that->_order + 1; ++iCtrl) {
        // Save the control point
        ret = VecSave(that->_ctrl[iCtrl], stream);
        // If we couldn't save the control point
        if (ret != 0) {
            // Stop here
            return 3;
        }
    }
    // Return success code
    return 0;
}

// Free the memory used by a BCurve
// Do nothing if arguments are invalid
void BCurveFree(BCurve **that) {
    // Check argument
    if (that == NULL || *that == NULL)
        return;
    // If there are control points
    if ((*that)->_ctrl != NULL) {
        // For each control point
        for (int iCtrl = 0; iCtrl < (*that)->_order + 1; ++iCtrl) {
            // Free the control point
            VecFree((*that)->_ctrl + iCtrl);
        }
    }
    // Free the array of control points
    free((*that)->_ctrl);
    // Free memory
    free(*that);
    *that = NULL;
}

// Print the BCurve on 'stream'
// Do nothing if arguments are invalid
void BCurvePrint(BCurve *that, FILE *stream) {
    // Check arguments
    if (that == NULL || stream == NULL)
        return;
    // Print the order and dim

```

```

    fprintf(stream, "order(%d) dim(%d) ", that->_order, that->_dim);
    // For each control point
    for (int iCtrl = 0; iCtrl < that->_order + 1; ++iCtrl) {
        VecPrint(that->_ctrl[iCtrl], stream);
        fprintf(stream, " ");
    }
}

// Set the value of the iCtrl-th control point to v
// Do nothing if arguments are invalid
void BCurveSet(BCurve *that, int iCtrl, VecFloat *v) {
    // Check arguments
    if (that == NULL || v == NULL || iCtrl < 0 ||
        iCtrl > that->_order || VecDim(v) != BCurveDim(that))
        return;
    // Set the values
    VecCopy(that->_ctrl[iCtrl], v);
}

// Get the value of the BCurve at parameter 'u' (in [0.0, 1.0])
// Return NULL if arguments are invalid or malloc failed
// if 'u' < 0.0 it is replaced by 0.0
// if 'u' > 1.0 it is replaced by 1.0
VecFloat* BCurveGet(BCurve *that, float u) {
    // Check arguments
    if (that == NULL)
        return NULL;
    if (u < 0.0)
        u = 0.0;
    if (u > 1.0)
        u = 1.0;
    // Allocate memory for the result
    VecFloat *v = VecFloatCreate(that->_dim);
    // If we couldn't allocate memory
    if (v == NULL)
        return NULL;
    // Declare a variable for calcul
    float *val = (float*)malloc(sizeof(float) * (that->_order + 1));
    // Loop on dimension
    for (int dim = that->_dim; dim--;) {
        // Initialise the temporary variable with the value in current
        // dimension of the control points
        for (int iCtrl = 0; iCtrl < that->_order + 1; ++iCtrl)
            val[iCtrl] = VecGet(that->_ctrl[iCtrl], dim);
        // Loop on order
        int subOrder = that->_order;
        while (subOrder != 0) {
            // Loop on sub order
            for (int order = 0; order < subOrder; ++order) {
                val[order] = (1.0 - u) * val[order] + u * val[order + 1];
            }
            --subOrder;
        }
        // Set the value for the current dim
        VecSet(v, dim, val[0]);
    }
    // Free memory
    free(val);
    // Return the result
    return v;
}

```

```

// Get the order of the BCurve
// Return -1 if argument is invalid
int BCurveOrder(BCurve *that) {
    // Check arguments
    if (that == NULL)
        return -1;
    return that->_order;
}

// Get the dimension of the BCurve
// Return 0 if argument is invalid
int BCurveDim(BCurve *that) {
    // Check arguments
    if (that == NULL)
        return 0;
    return that->_dim;
}

// Get the approximate length of the BCurve (sum of dist between
// control points)
// Return 0.0 if argument is invalid
float BCurveApproxLen(BCurve *that) {
    // Check arguments
    if (that == NULL)
        return 0.0;
    // Declare a variable to calculate the length
    float res = 0.0;
    // Calculate the length
    for (int iCtrl = 0; iCtrl < that->_order; ++iCtrl)
        res += VecDist(that->_ctrl[iCtrl], that->_ctrl[iCtrl + 1]);
    // Return the length
    return res;
}

// Rotate the curve CCW by 'theta' radians relatively to the origin
// Do nothing if arguments are invalid
void BCurveRot2D(BCurve *that, float theta) {
    // Check arguments
    if (that == NULL || that->_dim != 2)
        return;
    // For each control point
    for (int iCtrl = 0; iCtrl <= that->_order; ++iCtrl)
        // Rotate the control point
        VecRot2D(that->_ctrl[iCtrl], theta);
}

// Scale the curve by 'v' relatively to the origin
// Do nothing if arguments are invalid
void BCurveScale(BCurve *that, VecFloat *v) {
    // Check arguments
    if (that == NULL || v == NULL)
        return;
    // For each control point
    for (int iCtrl = 0; iCtrl <= that->_order; ++iCtrl)
        // Scale the control point
        for (int dim = 0; dim < VecDim(that->_ctrl[iCtrl]); ++dim)
            VecSet(that->_ctrl[iCtrl], dim,
                VecGet(that->_ctrl[iCtrl], dim) * VecGet(v, dim));
}

// Translate the curve by 'v'
// Do nothing if arguments are invalid

```

```

void BCurveTranslate(BCurve *that, VecFloat *v) {
    // Check arguments
    if (that == NULL || v == NULL)
        return;
    // For each control point
    for (int iCtrl = 0; iCtrl <= that->_order; ++iCtrl)
        // Translate the control point
        VecOp(that->_ctrl[iCtrl], 1.0, v, 1.0);
}

// Create a BCurve which pass through the points given in the GSet 'set'
// The GSet must contains VecFloat of same dimensions
// The BCurve pass through the points in the order they are given
// in the GSet. The points don't need to be uniformly distributed
// The created BCurve is of same dimension as the VecFloat and of order
// equal to the number of VecFloat in 'set' minus one
// Return NULL if it couldn't create the BCurve or the arguments are
// invalid
BCurve* BCurveFromCloudPoint(GSet *set) {
    // Check arguments
    if (set == NULL || set->_nbElem < 1)
        return NULL;
    // Declare a variable to memorize the result
    int order = set->_nbElem - 1;
    int dim = VecDim((VecFloat*)(set->_head->_data));
    BCurve *curve = BCurveCreate(order, dim);
    // If we could allocate memory
    if (curve != NULL) {
        // Set the first control point to the first point in the point cloud
        BCurveSet(curve, 0, (VecFloat*)(set->_head->_data));
        // If the order is greater than 0
        if (order > 0) {
            // Set the last control point to the last point in the point cloud
            BCurveSet(curve, order, (VecFloat*)(set->_tail->_data));
            // If the order is greater than 1
            if (order > 1) {
                // Calculate the t values for intermediate control points
                // They are equal to the relative distance on the polyline
                // linking the point in the point cloud
                // Declare a variable to memorize the dimension of the matrix
                // in the linear system to solve
                VecShort *dimMat = VecShortCreate(2);
                // Declare a variable to memorize the t values
                VecFloat *t = VecFloatCreate(order + 1);
                // If we could allocate memory
                if (t != NULL && dimMat != NULL) {
                    // Set the dimensions of the matrix of the linear system
                    VecSet(dimMat, 0, order - 1);
                    VecSet(dimMat, 1, order - 1);
                    // For each point
                    GSetElem *elem = set->_head->_next;
                    int iPoint = 1;
                    while (elem != NULL) {
                        // Get the distance from the previous point
                        float d = VecDist((VecFloat*)(elem->_prev->_data),
                            (VecFloat*)(elem->_data));
                        VecSet(t, iPoint, d + VecGet(t, iPoint - 1));
                        ++iPoint;
                        elem = elem->_next;
                    }
                    // Normalize t
                    for (iPoint = 1; iPoint <= order; ++iPoint)

```

```

    VecSet(t, iPoint, VecGet(t, iPoint) / VecGet(t, order));
// For each dimension
for (int iDim = dim; iDim--;) {
    // Declare a variable to memorize the matrix and vector
    // of the linear system
    MatFloat *m = MatFloatCreate(dimMat);
    VecFloat *v = VecFloatCreate(VecGet(dimMat, 0));
    // If we could allocate memory
    if (m != NULL && v != NULL) {
        // Set the values of the linear system
        // For each line (equivalent to each intermediate point
        // in point cloud)
        for (VecSet(dimMat, 1, 0);
            VecGet(dimMat, 1) < order - 1;
            VecSet(dimMat, 1, VecGet(dimMat, 1) + 1)) {
            // Get the weight of the control point at the value
            // of t for this point
            VecFloat *weight =
                BCurveGetWeightCtrlPt(curve, VecGet(t,
                    VecGet(dimMat, 1) + 1));
            // If we could get the weights
            if (weight != NULL) {
                // For each intermediate control point
                for (VecSet(dimMat, 0, 0);
                    VecGet(dimMat, 0) < order - 1;
                    VecSet(dimMat, 0, VecGet(dimMat, 0) + 1))
                    // Set the matrix value with the corresponding
                    // weight
                    MatSet(m, dimMat, VecGet(weight,
                        VecGet(dimMat, 0) + 1));
            }
            // Set the vector value with the corresponding point
            // coordinate
            float x = VecGet((VecFloat*)(GSetGet(set,
                VecGet(dimMat, 1) + 1)), iDim);
            x -= VecGet(weight, 0) *
                VecGet((VecFloat*)(set->_head->_data), iDim);
            x -= VecGet(weight, order) *
                VecGet((VecFloat*)(set->_tail->_data), iDim);
            VecSet(v, VecGet(dimMat, 1), x);
            // Free memory
            VecFree(&weight);
        }
        // Declare a variable to memorize the linear system
        EqLinSys *sys = EqLinSysCreate(m, v);
        // If we could allocate memory
        if (sys != NULL) {
            // Solve the system
            VecFloat *solSys = EqLinSysSolve(sys);
            // If we could solve the linear system
            if (solSys != NULL) {
                // Memorize the values of control points for the
                // current dimension
                for (int iCtrl = 1; iCtrl < order; ++iCtrl)
                    VecSet(curve->_ctrl[iCtrl], iDim,
                        VecGet(solSys, iCtrl - 1));
                // Free memory
                VecFree(&solSys);
            }
        }
        // Free memory
        EqLinSysFree(&sys);
    }
}

```

```

        VecFree(&v);
        MatFree(&m);
    }
}
// Free memory
VecFree(&dimMat);
VecFree(&t);
}
}
// Return the result
return curve;
}

// Get a VecFloat of dimension equal to the number of control points
// Values of the VecFloat are the weight of each control point in the
// BCurve given the curve's order and the value of 't' (in [0.0,1.0])
// Return null if the arguments are invalid or memory allocation failed
VecFloat* BCurveGetWeightCtrlPt(BCurve *that, float t) {
    // Check arguments
    if (that == NULL || t < 0.0 || t > 1.0)
        return NULL;
    // Declare a variable to memorize the result
    VecFloat *res = VecFloatCreate(that->_order + 1);
    // If we could allocate memory
    if (res != NULL) {
        // Initilize the two first weights
        VecSet(res, 0, 1.0 - t);
        VecSet(res, 1, t);
        // For each higher order
        for (int order = 1; order < that->_order; ++order) {
            // For each control point at this order, starting by the last one
            // to avoid using a temporary buffer
            for (int iCtrl = order + 2; iCtrl--;) {
                // Calculate the weight of this control point
                // VecGet(v, - 1) = 0.0 and VecFloat is initialized to 0.0
                // => no need to check for border cases
                VecSet(res, iCtrl,
                    (1.0 - t) * VecGet(res, iCtrl) + t * VecGet(res, iCtrl - 1));
            }
        }
    }
    // Return the result
    return res;
}

// Get the bounding box of the BCurve.
// Return a Facoid whose axis are aligned on the standard coordinate
// system.
// Return NULL if arguments are invalid.
Shapoid* BCurveGetBoundingBox(BCurve *that) {
    // Check argument
    if (that == NULL)
        return NULL;
    // Declare a variable to memorize the result
    Shapoid *res = FacoidCreate(that->_dim);
    // If we could allocate memory
    if (res != NULL) {
        // For each dimension
        for (int iDim = that->_dim; iDim--;) {
            // For each control point

```

```

    for (int iCtrl = that->_order + 1; iCtrl--;) {
        // If it's the first control point in this dimension
        if (iCtrl == that->_order) {
            // Initialise the bounding box
            VecSet(res->_pos, iDim, VecGet(that->_ctrl[iCtrl], iDim));
            VecSet(res->_axis[iDim], iDim,
                VecGet(that->_ctrl[iCtrl], iDim));
        } // Else, it's not the first control point in this dimension
        else {
            // Update the bounding box
            if (VecGet(that->_ctrl[iCtrl], iDim) <
                VecGet(res->_pos, iDim))
                VecSet(res->_pos, iDim, VecGet(that->_ctrl[iCtrl], iDim));
            if (VecGet(that->_ctrl[iCtrl], iDim) >
                VecGet(res->_axis[iDim], iDim))
                VecSet(res->_axis[iDim], iDim,
                    VecGet(that->_ctrl[iCtrl], iDim));
        }
    }
    VecSet(res->_axis[iDim], iDim,
        VecGet(res->_axis[iDim], iDim) - VecGet(res->_pos, iDim));
}
}
// Return the result
return res;
}

// Create a new SCurve of dimension 'dim'
// Return NULL if we couldn't create the SCurve
SCurve* SCurveCreate(int dim) {
    // Check arguments
    if (dim <= 0)
        return NULL;
    // Declare a variable for the returned SCurve
    SCurve *ret = (SCurve*)malloc(sizeof(SCurve));
    // If we could allocate memory
    if (ret != NULL) {
        // Set the properties
        ret->_dim = dim;
        // Create the set
        ret->_curves = GSetCreate();
        // If we couldn't allocate memory
        if (ret->_curves == NULL) {
            // Free memory and stop here
            SCurveFree(&ret);
            return NULL;
        }
    }
    // Return the new SCurve
    return ret;
}

// Clone the SCurve
// Return NULL if we couldn't clone the SCurve
SCurve* SCurveClone(SCurve *that) {
    // Check arguments
    if (that == NULL)
        return NULL;
    // Allocate memory
    SCurve *ret = SCurveCreate(SCurveDim(that));
    // If we could allocate memory
    if (ret != NULL) {

```

```

    // Declare a pointer to the elements of the set
    GSetElem *ptr = that->_curves->_head;
    // Loop on elements
    while (ptr != NULL) {
        // Clone the BCurve and add it to the clone of SCurve
        GSetAppend(ret->_curves, BCurveClone((BCurve*)(ptr->_data)));
        // Move to the next element
        ptr = ptr->_next;
    }
}
// Return the cloned SCurve
return ret;
}

// Load the SCurve from the stream
// If the SCurve is already allocated, it is freed before loading
// Return 0 in case of success, or:
// 1: invalid arguments
// 2: can't allocate memory
// 3: invalid data
// 4: fscanf error
// 5: BCurveLoad error
int SCurveLoad(SCurve **that, FILE *stream) {
    // Check arguments
    if (that == NULL || stream == NULL)
        return 1;
    // If 'that' is already allocated
    if (*that != NULL) {
        // Free memory
        SCurveFree(that);
    }
    // Read the dimension and number of curve
    int dim = 0;
    int nbCurve = 0;
    int ret = fscanf(stream, "%d %d", &dim, &nbCurve);
    // If we couldn't read
    if (ret == EOF) {
        return 4;
    }
    // Allocate memory
    *that = SCurveCreate(dim);
    // If we couldn't allocate memory
    if (*that == NULL) {
        return 2;
    }
    // Loop on curves
    for (int iCurve = 0; iCurve < nbCurve; ++iCurve) {
        // Declare a variable to load the BCurve
        BCurve *curve = NULL;
        // Load the BCurve
        ret = BCurveLoad(&curve, stream);
        // If we couldn't load the BCurve
        if (ret != 0)
            return 5;
        // Check the dimension of the curve
        if (BCurveDim(curve) != dim)
            return 3;
        // Add the BCurve to the SCurve
        SCurveAdd(*that, curve);
    }
    return 0;
}

```



```

// Save the SCurve to the stream
// Return 0 upon success, else
// 1: invalid arguments
// 2: fprintf error
// 3: BCurveSave error
int SCurveSave(SCurve *that, FILE *stream) {
    // Check arguments
    if (that == NULL || stream == NULL)
        return 1;
    // Save the dimension and number of curve
    int ret = fprintf(stream, "%d %d\n", that->_dim,
        that->_curves->_nbElem);
    // If the fprintf failed
    if (ret < 0)
        // Stop here
        return 2;
    // Declare a pointer on elements of the set of curves
    GSetElem *ptr = that->_curves->_head;
    // Loop on elements
    while (ptr != NULL) {
        // Save the BCurve
        BCurveSave((BCurve*)(ptr->_data), stream);
        // Move to the next BCurve
        ptr = ptr->_next;
    }
    return 0;
}

// Free the memory used by a SCurve
// Do nothing if arguments are invalid
void SCurveFree(SCurve **that) {
    // Check argument
    if (that == NULL || *that == NULL)
        return;
    // Declare a pointer on elements of the set of curves
    GSetElem *ptr = (*that)->_curves->_head;
    // Loop on elements
    while (ptr != NULL) {
        // Free the BCurve
        BCurveFree((BCurve**>(&(ptr->_data)));
        // Move to the next BCurve
        ptr = ptr->_next;
    }
    // Free memory
    GSetFree(&((*that)->_curves));
    free(*that);
    *that = NULL;
}

// Print the SCurve on 'stream'
// Do nothing if arguments are invalid
void SCurvePrint(SCurve *that, FILE *stream) {
    // Check argument
    if (that == NULL || stream == NULL)
        return;
    // Declare a pointer on elements of the set of curves
    GSetElem *ptr = that->_curves->_head;
    // Loop on elements
    while (ptr != NULL) {
        // Print the BCurve
        BCurvePrint((BCurve*)(ptr->_data), stream);
    }
}

```

```

        fprintf(stream, "\n");
        // Move to the next BCurve
        ptr = ptr->_next;
    }
}

// Set the 'iCurve'-th BCurve to a clone of 'curve'
// 'iCurve' must be in [0, current number of BCurve]
// 'curve' 's dimension must be equal to SCurve's dimension
// Do nothing if arguments are invalid
void SCurveSet(SCurve *that, int iCurve, BCurve *curve) {
    // Check arguments
    if (that == NULL || curve == NULL || iCurve < 0 ||
        iCurve > that->_curves->_nbElem)
        return;
    // Clone the curve
    BCurve *clone = BCurveClone(curve);
    // If we could clone
    if (clone != NULL)
        // Insert a clone of the curve
        GSetInsert(that->_curves, clone, iCurve);
}

// Append a clone of 'curve'
// 'curve' 's dimension must be equal to SCurve's dimension
// Do nothing if arguments are invalid
void SCurveAdd(SCurve *that, BCurve *curve) {
    // Check arguments
    if (that == NULL || curve == NULL)
        return;
    // Append the curve
    SCurveSet(that, that->_curves->_nbElem, curve);
}

// Remove the 'iCurve'-th BCurve from the SCurve
// Return NULL if arguments are invalid
BCurve* SCurveRemove(SCurve *that, int iCurve) {
    // Check arguments
    if (that == NULL)
        return NULL;
    // Get the BCurve out of the set
    BCurve *curve = (BCurve*)GSetRemove(that->_curves, iCurve);
    // Return the curve
    return curve;
}

// Get the 'iCurve'-th BCurve of the SCurve, without removing it
// Return NULL if arguments are invalid
BCurve* SCurveGet(SCurve *that, int iCurve) {
    // Check arguments
    if (that == NULL)
        return NULL;
    // Return the BCurve
    return (BCurve*)(GSetGet(that->_curves, iCurve));
}

// Get the number of BCurve in the SCurve
// Return 0 if arguments are invalid
int SCurveGetNbCurve(SCurve *that) {
    // Check arguments
    if (that == NULL)
        return 0;
}

```

```

    // Return the number of BCurves
    return that->_curves->_nbElem;
}

// Get the dimension of the SCurve
// Return 0 if argument is invalid
int SCurveDim(SCurve *that) {
    // Check arguments
    if (that == NULL)
        return 0;
    // Return the dimension
    return that->_dim;
}

// Get the approximate length of the SCurve (sum of approxLen
// of its BCurves)
// Return 0.0 if argument is invalid
float SCurveApproxLen(SCurve *that) {
    // Check arguments
    if (that == NULL)
        return 0.0;
    // Declare a variable to calculate the length
    float length = 0.0;
    // Declare a pointer on elements of the set of curves
    GSetElem *ptr = that->_curves->_head;
    // Loop on elements
    while (ptr != NULL) {
        // Add the approximate length of this BCurve
        length += BCurveApproxLen((BCurve*)(ptr->_data));
        // Move to the next BCurve
        ptr = ptr->_next;
    }
    // Return the length
    return length;
}

// Rotate the SCurve CCW by 'theta' radians relatively to the origin
// Do nothing if arguments are invalid
void SCurveRot2D(SCurve *that, float theta) {
    // Check arguments
    if (that == NULL)
        return;
    // Declare a pointer on elements of the set of curves
    GSetElem *ptr = that->_curves->_head;
    // Loop on elements
    while (ptr != NULL) {
        // Rotate the BCurve
        BCurveRot2D((BCurve*)(ptr->_data), theta);
        // Move to the next BCurve
        ptr = ptr->_next;
    }
}

// Scale the SCurve by 'v' relatively to the origin
// Do nothing if arguments are invalid
void SCurveScale(SCurve *that, VecFloat *v) {
    // Check arguments
    if (that == NULL || v == NULL)
        return;
    // Declare a pointer on elements of the set of curves
    GSetElem *ptr = that->_curves->_head;
    // Loop on elements

```

```

while (ptr != NULL) {
    // Rotate the BCurve
    BCurveScale((BCurve*)(ptr->_data), v);
    // Move to the next BCurve
    ptr = ptr->_next;
}
}

// Translate the SCurve by 'v'
// Do nothing if arguments are invalid
void SCurveTranslate(SCurve *that, VecFloat *v) {
    // Check arguments
    if (that == NULL || v == NULL)
        return;
    // Declare a pointer on elements of the set of curves
    GSetElem *ptr = that->_curves->_head;
    // Loop on elements
    while (ptr != NULL) {
        // Translate the BCurve
        BCurveTranslate((BCurve*)(ptr->_data), v);
        // Move to the next BCurve
        ptr = ptr->_next;
    }
}

// Get the bounding box of the SCurve.
// Return a Facoid whose axis are aligned on the standard coordinate
// system.
// Return NULL if arguments are invalid.
Shapoid* SCurveGetBoundingBox(SCurve *that) {
    // Check arguments
    if (that == NULL)
        return NULL;
    // Allocate memory for the set of bounding boxes of BCurve
    GSet *set = GSetCreate();
    // If we couldn't allocate memory
    if (set == NULL) {
        return NULL;
    }
    // Add the bounding box of each BCurve
    GSetElem *ptr = set->_head;
    while (ptr != NULL) {
        GSetAppend(set, BCurveGetBoundingBox((BCurve*)(ptr->_data)));
        ptr = ptr->_next;
    }
    // Get the bounding box of the set of bounding boxes of BCurve
    Shapoid *ret = ShapoidGetBoundingBoxSet(set);
    // Free memory used by the set of bounding boxes of BCurve
    ptr = set->_head;
    while (ptr != NULL) {
        ShapoidFree((Shapoid**>(&(ptr->_data)));
        ptr = ptr->_next;
    }
    GSetFree(&set);
    // Return the result
    return ret;
}

```

## 4 Makefile

```
OPTIONS_DEBUG=-ggdb -g3 -Wall
OPTIONS_RELEASE=-O3
OPTIONS=$(OPTIONS_RELEASE)
INCPATH=/home/bayashi/Coding/Include
LIBPATH=/home/bayashi/Coding/Include

all : main

main: main.o bcurve.o $(LIBPATH)/pbmath.o $(LIBPATH)/gset.o Makefile
gcc $(OPTIONS) main.o bcurve.o $(LIBPATH)/pbmath.o $(LIBPATH)/gset.o -o main -lm

main.o : main.c bcurve.h Makefile
gcc $(OPTIONS) -I$(INCPATH) -c main.c

bcurve.o : bcurve.c bcurve.h $(INCPATH)/pbmath.h $(INCPATH)/gset.h Makefile
gcc $(OPTIONS) -I$(INCPATH) -c bcurve.c

clean :
rm -rf *.o main

valgrind :
valgrind -v --track-origins=yes --leak-check=full --gen-suppressions=yes --show-leak-kinds=all ./main

install :
cp bcurve.h ../Include; cp bcurve.o ../Include
```

## 5 Usage

```
#include <stdlib.h>
#include <stdio.h>
#include <time.h>
#include <string.h>
#include "bcurve.h"

float CloudCurveX(float t) {
    return t * t;
    //return 2.0 * cos(t * PBMath_HALFPI);
}

float CloudCurveY(float t) {
    return sqrt(t);
    //return sin(t * PBMath_HALFPI);
}

int main(int argc, char **argv) {
    // Create a BCurve
    int order = 3;
    int dim = 2;
    BCurve *curve = BCurveCreate(order, dim);
    // If we couldn't create the BCurve
    if (curve == NULL) {
        // Print a message
        fprintf(stderr, "BCurveCreate failed\n");
        // Stop here
        return 1;
    }
}
```

```

// Print the BCurve
BCurvePrint(curve, stdout);
fprintf(stdout, "\n");
// Create a VecFloat to set the values
VecFloat *v = VecFloatCreate(dim);
// If we couldn't create the VecFloat
if (v == NULL) {
    // Release memory
    BCurveFree(&curve);
    // Stop here
    return 2;
}
// Set the control points
float ctrlPts[8] = {0.0, 1.0, 2.0, 5.0, 4.0, 3.0, 6.0, 7.0};
for (int iCtrl = 0; iCtrl < order + 1; ++iCtrl) {
    VecSet(v, 0, ctrlPts[2 * iCtrl]);
    VecSet(v, 1, ctrlPts[2 * iCtrl + 1]);
    BCurveSet(curve, iCtrl, v);
}
// Print the BCurve
BCurvePrint(curve, stdout);
fprintf(stdout, "\n");
// Save the curve
FILE *file = fopen("./curve.txt", "w");
// If we couldn't open the file
if (file == NULL) {
    // Print a message
    fprintf(stderr, "Can't open file\n");
    // Free memory
    VecFree(&v);
    BCurveFree(&curve);
    // Stop here
    return 3;
}
int ret = BCurveSave(curve, file);
// If we couldn't save
if (ret != 0) {
    // Print a message
    fprintf(stderr, "BCurveSave failed (%d)\n", ret);
    // Free memory
    VecFree(&v);
    BCurveFree(&curve);
    // Stop here
    return 4;
}
fclose(file);
// Load the curve
file = fopen("./curve.txt", "r");
// If we couldn't open the file
if (file == NULL) {
    // Print a message
    fprintf(stderr, "Can't open file\n");
    // Free memory
    VecFree(&v);
    BCurveFree(&curve);
    // Stop here
    return 5;
}
BCurve *loaded = NULL;
ret = BCurveLoad(&loaded, file);
// If we couldn't load
if (ret != 0) {

```

```

    // Print a message
    fprintf(stderr, "BCurveLoad failed (%d)\n", ret);
    // Free memory
    VecFree(&v);
    BCurveFree(&curve);
    BCurveFree(&loaded);
    // Stop here
    return 6;
}
fclose(file);
// Print the loaded curve
BCurvePrint(loaded, stdout);
fprintf(stdout, "\n");
// Get some values of the curve
for (float u = 0.0; u <= 1.01; u += 0.1) {
    VecFloat *w = BCurveGet(curve, u);
    // If we couldn't get the values
    if (w == NULL) {
        // Free memory
        VecFree(&v);
        BCurveFree(&curve);
        BCurveFree(&loaded);
        // Stop here
        return 7;
    }
    fprintf(stdout, "%.1f: ", u);
    VecPrint(w, stdout);
    fprintf(stdout, "\n");
    VecFree(&w);
}
// Scale the curve
VecSet(v, 0, 0.5);
VecSet(v, 1, 1.0);
BCurveScale(curve, v);
// Rotate the curve
BCurveRot2D(curve, PB_MATH_PI * 0.5);
// Translate the curve
VecSet(v, 0, -0.5);
VecSet(v, 1, 1.0);
BCurveTranslate(curve, v);
// Get some values of the curve
fprintf(stdout, "After transformation:\n");
for (float u = 0.0; u <= 1.01; u += 0.1) {
    VecFloat *w = BCurveGet(curve, u);
    // If we couldn't get the values
    if (w == NULL) {
        // Free memory
        VecFree(&v);
        BCurveFree(&curve);
        BCurveFree(&loaded);
        // Stop here
        return 7;
    }
    fprintf(stdout, "%.1f: ", u);
    VecPrint(w, stdout);
    fprintf(stdout, "\n");
    VecFree(&w);
}
// Print the curve approximate length
fprintf(stdout, "approx length: %.3f\n", BCurveApproxLen(curve));
// Print the weight of control points
fprintf(stdout, "Control points weight:\n");

```

```

for (float t = 0.0; t <= 1.01; t += 0.05) {
    if (t > 1.0) t = 1.0;
    VecFloat *w = BCurveGetWeightCtrlPt(curve, t);
    if (w != NULL) {
        fprintf(stdout, "%.3f ", t);
        VecPrint(w, stdout);
        fprintf(stdout, "\n");
    }
    VecFree(&w);
}
// Get a curve from a cloud point
GSet *cloud = GSetCreate();
if (cloud != NULL) {
    VecFloat *w = NULL;
    fprintf(stdout, "cloud:\n");
    //for (float t = 0.0; t < 1.01; t += 0.25) {
    //for (float t = 0.0; t < 1.01; t += 0.334) {
    for (float t = 0.0; t < 1.01; t += 0.5) {
        w = VecFloatCreate(2);
        GSetAppend(cloud, w);
        VecSet(w, 0, CloudCurveX(t));
        VecSet(w, 1, CloudCurveY(t));
        VecPrint(w, stdout);
        fprintf(stdout, "\n");
    }
    w = NULL;
    BCurve *cloudCurve = BCurveFromCloudPoint(cloud);
    if (cloudCurve == NULL) {
        fprintf(stdout, "Couldn't get curve from cloud\n");
        return 8;
    }
    fprintf(stdout, "cloudCurve: ");
    BCurvePrint(cloudCurve, stdout);
    fprintf(stdout, "\n");
    for (float t = 0.0; t < 1.01; t += 0.1) {
        if (t > 1.0) t = 1.0;
        fprintf(stdout, "%.3f ", t);
        w = BCurveGet(cloudCurve, t);
        VecPrint(w, stdout);
        fprintf(stdout, "\n");
        VecFree(&w);
    }
    BCurveFree(&cloudCurve);
}
// Get the bounding box of the curve
Shapoid *bound = BCurveGetBoundingBox(curve);
if (bound == NULL) {
    fprintf(stdout, "Couldn't get the bounding box\n");
    return 9;
}
fprintf(stdout, "bounding box of \n");
BCurvePrint(curve, stdout);
fprintf(stdout, "\nis\n");
ShapoidPrint(bound, stdout);
ShapoidFree(&bound);
// Free memory
GSetElem *elem = cloud->_head;
while (elem != NULL) {
    VecFree((VecFloat**)(elem->_data));
    elem = elem->_next;
}
GSetFree(&cloud);

```



```

VecFree(&v);
BCurveFree(&curve);
BCurveFree(&loaded);
// Return success code
return 0;
}

```

Output:

```



order(3) dim(2) <0.000,0.000> <0.000,0.000> <0.000,0.000> <0.000,0.000>
order(3) dim(2) <0.000,1.000> <2.000,5.000> <4.000,3.000> <6.000,7.000>
order(3) dim(2) <0.000,1.000> <2.000,5.000> <4.000,3.000> <6.000,7.000>
0.0: <0.000,1.000>
0.1: <0.600,2.032>
0.2: <1.200,2.776>
0.3: <1.800,3.304>
0.4: <2.400,3.688>
0.5: <3.000,4.000>
0.6: <3.600,4.312>
0.7: <4.200,4.696>
0.8: <4.800,5.224>
0.9: <5.400,5.968>
1.0: <6.000,7.000>
After transformation:
0.0: <-1.500,1.000>
0.1: <-2.532,1.300>
0.2: <-3.276,1.600>
0.3: <-3.804,1.900>
0.4: <-4.188,2.200>
0.5: <-4.500,2.500>
0.6: <-4.812,2.800>
0.7: <-5.196,3.100>
0.8: <-5.724,3.400>
0.9: <-6.468,3.700>
1.0: <-7.500,4.000>
approx length: 10.482
Control points weight:
0.000 <1.000,0.000,0.000,0.000>
0.050 <0.857,0.135,0.007,0.000>
0.100 <0.729,0.243,0.027,0.001>
0.150 <0.614,0.325,0.057,0.003>
0.200 <0.512,0.384,0.096,0.008>
0.250 <0.422,0.422,0.141,0.016>
0.300 <0.343,0.441,0.189,0.027>
0.350 <0.275,0.444,0.239,0.043>
0.400 <0.216,0.432,0.288,0.064>
0.450 <0.166,0.408,0.334,0.091>
0.500 <0.125,0.375,0.375,0.125>
0.550 <0.091,0.334,0.408,0.166>
0.600 <0.064,0.288,0.432,0.216>
0.650 <0.043,0.239,0.444,0.275>
0.700 <0.027,0.189,0.441,0.343>
0.750 <0.016,0.141,0.422,0.422>
0.800 <0.008,0.096,0.384,0.512>
0.850 <0.003,0.057,0.325,0.614>
0.900 <0.001,0.027,0.243,0.729>
0.950 <0.000,0.007,0.135,0.857>
1.000 <0.000,0.000,0.000,1.000>
cloud:
<0.000,0.000>




```

```

<0.250,0.707>
<1.000,1.000>
cloudCurve: order(2) dim(2) <0.000,0.000> <0.035,0.950> <1.000,1.000>
0.000 <0.000,0.000>
0.100 <0.016,0.181>
0.200 <0.051,0.344>
0.300 <0.105,0.489>
0.400 <0.177,0.616>
0.500 <0.267,0.725>
0.600 <0.377,0.816>
0.700 <0.505,0.889>
0.800 <0.651,0.944>
0.900 <0.816,0.981>
1.000 <1.000,1.000>
bounding box of
order(3) dim(2) <-1.500,1.000> <-5.500,2.000> <-3.500,3.000> <-7.500,4.000>
is
Type: Facoid
Dim: 2
Pos: <-7.500,1.000>
Axis(0): <6.000,0.000>
Axis(1): <0.000,3.000>

```





curve.txt:

```
3 2
2 0.000000 1.000000
2 2.000000 5.000000
2 4.000000 3.000000
2 6.000000 7.000000
```