

The FMB Algorithm

P. Baillehache

December 31, 2019

Abstract

This paper introduces how to perform intersection detection of pair of static/dynamic cuboid/tetrahedron in 2D/3D by using the Fourier-Motzkin elimination method.

Contents

1	The problem as a system of linear inequations	4
1.1	Notations and definitions	4
1.2	Static case	4
1.3	Dynamic case	7
2	Resolution of the problem by Fourier-Motzkin method	11
2.1	The Fourier-Motzkin elimination method	11
2.2	Application of the Fourier-Motzkin method to the intersection problem	13
2.3	About the size of system of linear inequation	13
3	Algorithms of the solution	15
3.1	2D static	15
3.2	3D static	21
3.3	2D dynamic	27
3.4	3D dynamic	34
4	Implementation of the algorithms in C	42
4.1	Frames	42
4.1.1	Header	42
4.1.2	Body	45
4.2	FMB	67
4.2.1	2D static	67
4.2.2	3D static	75
4.2.3	2D dynamic	84
4.2.4	3D dynamic	94
5	Minimal example of use	105
5.1	2D static	105
5.2	3D static	106
5.3	2D dynamic	108
5.4	3D dynamic	109
6	Unit tests	110
6.1	Code	111
6.1.1	2D static	111
6.1.2	3D static	114
6.1.3	2D dynamic	117
6.1.4	3D dynamic	121
6.2	Results	124

6.2.1	2D static	124
6.2.2	3D static	128
6.2.3	2D dynamic	130
6.2.4	3D dynamic	130
7	Validation against SAT	131
7.1	Code	131
7.1.1	2D static	131
7.1.2	3D static	134
7.1.3	2D dynamic	138
7.1.4	3D dynamic	141
7.2	Results	145
7.2.1	Failures	145
7.2.2	2D static	145
7.2.3	2D dynamic	145
7.2.4	3D static	146
7.2.5	3D dynamic	146
8	Qualification against SAT	146
8.1	Code	146
8.1.1	2D static	146
8.1.2	3D static	157
8.1.3	2D dynamic	168
8.1.4	3D dynamic	178
8.2	Results	189
8.2.1	2D static	189
8.2.2	3D static	194
8.2.3	2D dynamic	199
8.2.4	3D dynamic	204
9	Conclusion	210
10	Annex	210
10.1	Runtime environment	210
10.2	SAT implementation	211
10.2.1	Header	211
10.2.2	Body	212
10.3	Makefile	232
10.3.1	2D static	234
10.3.2	3D static	235
10.3.3	2D dynamic	236

Introduction

This paper introduces the FMB (Fourier-Motzkin-Baillehache) algorithm which can be used to perform intersection detection of moving and resting parallelepipeds and triangles in 2D, and cuboids and tetrahedrons in 3D.

The detection result is returned has a boolean (intersection / no intersection), and if there is intersection a bounding box of the intersection.

The two first sections introduce how the problem can be expressed as a system of linear inequation, and its resolution using the Fourier-Motzkin method.

The algorithm of the solution and its implementation in the C programming language are detailed in the four following sections.

The last two sections introduce the validation and qualification in term of relative performance of the FMB algorithm against the SAT algorithm.

1 The problem as a system of linear inequations

1.1 Notations and definitions

- $[M]_{r,c}$ is the component at column c and row r of the matrix M
- $[V]_r$ is the r -th component of the vector \vec{V}
- the term "frame" is used indifferently for parallelepiped, triangle, cuboid and tetrahedron.

1.2 Static case

The two Frames are represented as a vector origin and a number of component vectors equal to the dimension D of the space where live the Frames. Each vector is of dimension equal to D .

Lets call \mathbb{A} and \mathbb{B} the two Frames tested for intersection. If A and B are two cuboids:

$$\mathbb{A} = \left\{ \begin{array}{l} \vec{X} \in [0.0, 1.0]^D \\ \vec{O}_{\mathbb{A}} + C_{\mathbb{A}} \cdot \vec{X} \end{array} \right\} \quad (1)$$

$$\mathbb{B} = \left\{ \begin{array}{l} \vec{X} \in [0.0, 1.0]^D \\ \vec{O}_{\mathbb{B}} + C_{\mathbb{B}} \cdot \vec{X} \end{array} \right\} \quad (2)$$

where $\vec{O}_{\mathbb{A}}$ is the origin of \mathbb{A} and $C_{\mathbb{A}}$ is the matrix of the components of A (one component per column). Idem for $\vec{O}_{\mathbb{B}}$ and $C_{\mathbb{B}}$.

If \mathbb{A} and \mathbb{B} are two tetrahedrons:

$$\mathbb{A} = \left\{ \begin{array}{l} \vec{X} \in [0.0, 1.0]^D \\ \sum_{i=0}^{D-1} [X]_i \leq 1.0 \\ \vec{O}_{\mathbb{A}} + C_{\mathbb{A}} \cdot \vec{X} \end{array} \right\} \quad (3)$$

$$\mathbb{B} = \left\{ \begin{array}{l} \vec{X} \in [0.0, 1.0]^D \\ \sum_{i=0}^{D-1} [X]_i \leq 1.0 \\ \vec{O}_{\mathbb{B}} + C_{\mathbb{B}} \cdot \vec{X} \end{array} \right\} \quad (4)$$

I'll assume the Frames are well formed, i.e. their components matrix is invertible. It is then possible to express \mathbb{B} in \mathbb{A} 's coordinates system, noted as $\mathbb{B}_{\mathbb{A}}$. If \mathbb{B} is a cuboid:

$$\mathbb{B}_{\mathbb{A}} = \left\{ \begin{array}{l} \vec{X} \in [0.0, 1.0]^D \\ C_{\mathbb{A}}^{-1} \cdot (\vec{O}_{\mathbb{B}} - \vec{O}_{\mathbb{A}} + C_{\mathbb{B}} \cdot \vec{X}) \end{array} \right\} \quad (5)$$

If \mathbb{B} is a tetrahedron:

$$\mathbb{B}_{\mathbb{A}} = \left\{ \begin{array}{l} \vec{X} \in [0.0, 1.0]^D \\ \sum_{i=0}^{D-1} [X]_i \leq 1.0 \\ C_{\mathbb{A}}^{-1} \cdot (\vec{O}_{\mathbb{B}} - \vec{O}_{\mathbb{A}} + C_{\mathbb{B}} \cdot \vec{X}) \end{array} \right\} \quad (6)$$

\mathbb{A} in its own coordinates system becomes, for a cuboid:

$$\mathbb{A}_{\mathbb{A}} = \left\{ \vec{X} \in [0.0, 1.0]^D \right\} \quad (7)$$

and for a tetrahedron:

$$\mathbb{A}_{\mathbb{A}} = \left\{ \begin{array}{l} \vec{X} \in [0.0, 1.0]^D \\ \sum_{i=0}^{D-1} [X]_i \leq 1.0 \end{array} \right\} \quad (8)$$

The intersection of \mathbb{A} and \mathbb{B} in \mathbb{A} 's coordinates sytem, can then be expressed as follow.

If \mathbb{A} and \mathbb{B} are two cuboids:

$$\left\{ \begin{array}{l} \vec{X} \in [0.0, 1.0]^D \\ C_{\mathbb{A}}^{-1} \cdot (\vec{O}_{\mathbb{B}} - \vec{O}_{\mathbb{A}} + C_{\mathbb{B}} \cdot \vec{X}) \cap [0.0, 1.0]^D \end{array} \right\} \quad (9)$$

If \mathbb{A} is a cuboid and \mathbb{B} is a tetrahedron:

$$\left\{ \begin{array}{l} \vec{X} \in [0.0, 1.0]^D \\ \sum_{i=0}^{D-1} [X]_i \leq 1.0 \\ C_{\mathbb{A}}^{-1} \cdot (\vec{O}_{\mathbb{B}} - \vec{O}_{\mathbb{A}} + C_{\mathbb{B}} \cdot \vec{X}) \cap [0.0, 1.0]^D \end{array} \right\} \quad (10)$$

If \mathbb{A} is a tetrahedron and \mathbb{B} is a cuboid:

$$\left\{ \begin{array}{l} \vec{X} \in [0.0, 1.0]^D \\ C_{\mathbb{A}}^{-1} \cdot (\vec{O}_{\mathbb{B}} - \vec{O}_{\mathbb{A}} + C_{\mathbb{B}} \cdot \vec{X}) \cap [0.0, 1.0]^D \\ \sum_{i=0}^{D-1} [C_{\mathbb{A}}^{-1} \cdot (\vec{O}_{\mathbb{B}} - \vec{O}_{\mathbb{A}} + C_{\mathbb{B}} \cdot \vec{X})]_i \leq 1.0 \end{array} \right\} \quad (11)$$

If \mathbb{A} and \mathbb{B} are two tetrahedrons:

$$\left\{ \begin{array}{l} \vec{X} \in [0.0, 1.0]^D \\ \sum_{i=0}^{D-1} [X]_i \leq 1.0 \\ C_{\mathbb{A}}^{-1} \cdot (\vec{O}_{\mathbb{B}} - \vec{O}_{\mathbb{A}} + C_{\mathbb{B}} \cdot \vec{X}) \cap [0.0, 1.0]^D \\ \sum_{i=0}^{D-1} [C_{\mathbb{A}}^{-1} \cdot (\vec{O}_{\mathbb{B}} - \vec{O}_{\mathbb{A}} + C_{\mathbb{B}} \cdot \vec{X})]_i \leq 1.0 \end{array} \right\} \quad (12)$$

These can in turn be expressed as systems of linear inequations as follows, given the two shortcuts $\vec{O}_{\mathbb{B}_{\mathbb{A}}} = C_{\mathbb{A}}^{-1} \cdot (\vec{O}_{\mathbb{B}} - \vec{O}_{\mathbb{A}})$ and $C_{\mathbb{B}_{\mathbb{A}}} = C_{\mathbb{A}}^{-1} \cdot C_{\mathbb{B}}$.

If \mathbb{A} and \mathbb{B} are two cuboids:

$$\left\{ \begin{array}{l} [X]_0 \leq 1.0 \\ \dots \\ [X]_{D-1} \leq 1.0 \\ -[X]_0 \leq 0.0 \\ \dots \\ -[X]_{D-1} \leq 0.0 \\ \sum_{i=0}^{D-1} [C_{\mathbb{B}_{\mathbb{A}}}]_{0,i} \cdot [X]_i \leq 1.0 - [O_{\mathbb{B}_{\mathbb{A}}}]_0 \\ \dots \\ \sum_{i=0}^{D-1} [C_{\mathbb{B}_{\mathbb{A}}}]_{D-1,i} \cdot [X]_i \leq 1.0 - [O_{\mathbb{B}_{\mathbb{A}}}]_{D-1} \\ -\sum_{i=0}^{D-1} [C_{\mathbb{B}_{\mathbb{A}}}]_{0,i} \cdot [X]_i \leq [O_{\mathbb{B}_{\mathbb{A}}}]_0 \\ \dots \\ -\sum_{i=0}^{D-1} [C_{\mathbb{B}_{\mathbb{A}}}]_{D-1,i} \cdot [X]_i \leq [O_{\mathbb{B}_{\mathbb{A}}}]_{D-1} \end{array} \right. \quad (13)$$

If \mathbb{A} is a cuboid and \mathbb{B} is a tetrahedron:

$$\left\{ \begin{array}{l} -[X]_0 \leq 0.0 \\ \dots \\ -[X]_{D-1} \leq 0.0 \\ \sum_{i=0}^{D-1} [C_{\mathbb{B}_{\mathbb{A}}}]_{0,i} \cdot [X]_i \leq 1.0 - [O_{\mathbb{B}_{\mathbb{A}}}]_0 \\ \dots \\ \sum_{i=0}^{D-1} [C_{\mathbb{B}_{\mathbb{A}}}]_{D-1,i} \cdot [X]_i \leq 1.0 - [O_{\mathbb{B}_{\mathbb{A}}}]_{D-1} \\ -\sum_{i=0}^{D-1} [C_{\mathbb{B}_{\mathbb{A}}}]_{0,i} \cdot [X]_i \leq [O_{\mathbb{B}_{\mathbb{A}}}]_0 \\ \dots \\ -\sum_{i=0}^{D-1} [C_{\mathbb{B}_{\mathbb{A}}}]_{D-1,i} \cdot [X]_i \leq [O_{\mathbb{B}_{\mathbb{A}}}]_{D-1} \\ \sum_{i=0}^{D-1} [X]_i \leq 1.0 \end{array} \right. \quad (14)$$

If \mathbb{A} is a tetrahedron and \mathbb{B} is a cuboid:

$$\left\{ \begin{array}{l} [X]_0 \leq 1.0 \\ \dots \\ [X]_{D-1} \leq 1.0 \\ -[X]_0 \leq 0.0 \\ \dots \\ -[X]_{D-1} \leq 0.0 \\ -\sum_{i=0}^{D-1} [C_{\mathbb{B}_{\mathbb{A}}}]_{0,i} \cdot [X]_i \leq [O_{\mathbb{B}_{\mathbb{A}}}]_0 \\ \dots \\ -\sum_{i=0}^{D-1} [C_{\mathbb{B}_{\mathbb{A}}}]_{D-1,i} \cdot [X]_i \leq [O_{\mathbb{B}_{\mathbb{A}}}]_{D-1} \\ \sum_{j=0}^{D-1} \left(\left(\sum_{i=0}^{D-1} [C_{\mathbb{B}_{\mathbb{A}}}]_{j,i} \right) \cdot [X]_i \right) \leq 1.0 - \sum_{i=0}^{D-1} [O_{\mathbb{B}_{\mathbb{A}}}]_i \end{array} \right. \quad (15)$$

If \mathbb{A} and \mathbb{B} are two tetrahedrons:

$$\left\{ \begin{array}{l} -[X]_0 \leq 0.0 \\ \dots \\ -[X]_{D-1} \leq 0.0 \\ -\sum_{i=0}^{D-1} [C_{\mathbb{B}_{\mathbb{A}}}]_{0,i} \cdot [X]_i \leq [O_{\mathbb{B}_{\mathbb{A}}}]_0 \\ \dots \\ -\sum_{i=0}^{D-1} [C_{\mathbb{B}_{\mathbb{A}}}]_{D-1,i} \cdot [X]_i \leq [O_{\mathbb{B}_{\mathbb{A}}}]_{D-1} \\ \sum_{i=0}^{D-1} [X]_i \leq 1.0 \\ \sum_{j=0}^{D-1} \left(\left(\sum_{i=0}^{D-1} [C_{\mathbb{B}_{\mathbb{A}}}]_{j,i} \right) \cdot [X]_i \right) \leq 1.0 - \sum_{i=0}^{D-1} [O_{\mathbb{B}_{\mathbb{A}}}]_i \end{array} \right. \quad (16)$$

1.3 Dynamic case

If the frames \mathbb{A} and \mathbb{B} are moving linearly along the vectors $\vec{V}_{\mathbb{A}}$ and $\vec{V}_{\mathbb{B}}$ respectively during the interval of time $t \in [0.0, 1.0]$, the above definition of

the problem is modified as follow.

If A and B are two cuboids:

$$\mathbb{A} = \left\{ \begin{array}{l} \vec{X} \in [0.0, 1.0]^D \\ t \in [0.0, 1.0] \\ \vec{O}_{\mathbb{A}} + C_{\mathbb{A}} \cdot \vec{X} + \vec{V}_{\mathbb{A}} \cdot t \end{array} \right\} \quad (17)$$

$$\mathbb{B} = \left\{ \begin{array}{l} \vec{X} \in [0.0, 1.0]^D \\ t \in [0.0, 1.0] \\ \vec{O}_{\mathbb{B}} + C_{\mathbb{B}} \cdot \vec{X} + \vec{V}_{\mathbb{B}} \cdot t \end{array} \right\} \quad (18)$$

where $\vec{O}_{\mathbb{A}}$ is the origin of \mathbb{A} and $C_{\mathbb{A}}$ is the matrix of the components of A (one component per column). Idem for $\vec{O}_{\mathbb{B}}$ and $C_{\mathbb{B}}$.

If \mathbb{A} and \mathbb{B} are two tetrahedrons:

$$\mathbb{A} = \left\{ \begin{array}{l} \vec{X} \in [0.0, 1.0]^D \\ t \in [0.0, 1.0] \\ \sum_{i=0}^{D-1} [X]_i \leq 1.0 \\ \vec{O}_{\mathbb{A}} + C_{\mathbb{A}} \cdot \vec{X} + \vec{V}_{\mathbb{A}} \cdot t \end{array} \right\} \quad (19)$$

$$\mathbb{B} = \left\{ \begin{array}{l} \vec{X} \in [0.0, 1.0]^D \\ t \in [0.0, 1.0] \\ \sum_{i=0}^{D-1} [X]_i \leq 1.0 \\ \vec{O}_{\mathbb{B}} + C_{\mathbb{B}} \cdot \vec{X} + \vec{V}_{\mathbb{B}} \cdot t \end{array} \right\} \quad (20)$$

If \mathbb{B} is a cuboid, $\mathbb{B}_{\mathbb{A}}$ becomes:

$$\mathbb{B}_{\mathbb{A}} = \left\{ \begin{array}{l} \vec{X} \in [0.0, 1.0]^D \\ t \in [0.0, 1.0] \\ C_{\mathbb{A}}^{-1} \cdot (\vec{O}_{\mathbb{B}} - \vec{O}_{\mathbb{A}} + C_{\mathbb{B}} \cdot \vec{X} + (\vec{V}_{\mathbb{B}} - \vec{V}_{\mathbb{A}}) \cdot t) \end{array} \right\} \quad (21)$$

If \mathbb{B} is a tetrahedron:

$$\mathbb{B}_{\mathbb{A}} = \left\{ \begin{array}{l} \vec{X} \in [0.0, 1.0]^D \\ t \in [0.0, 1.0] \\ \sum_{i=0}^{D-1} [X]_i \leq 1.0 \\ C_{\mathbb{A}}^{-1} \cdot (\vec{O}_{\mathbb{B}} - \vec{O}_{\mathbb{A}} + C_{\mathbb{B}} \cdot \vec{X} + (\vec{V}_{\mathbb{B}} - \vec{V}_{\mathbb{A}}) \cdot t) \end{array} \right\} \quad (22)$$

\mathbb{A} in its own coordinates system has the same definition as in the static case. For a cuboid:

$$\mathbb{A}_{\mathbb{A}} = \left\{ \vec{X} \in [0.0, 1.0]^D \right\} \quad (23)$$

and for a tetrahedron:

$$\mathbb{A}_{\mathbb{A}} = \left\{ \begin{array}{l} \vec{X} \in [0.0, 1.0]^D \\ \sum_{i=0}^{D-1} [X]_i \leq 1.0 \end{array} \right\} \quad (24)$$

The intersection of \mathbb{A} and \mathbb{B} in \mathbb{A} 's coordinates sytem, can then be expressed as follow.

If \mathbb{A} and \mathbb{B} are two cuboids:

$$\left\{ \begin{array}{l} \vec{X} \in [0.0, 1.0]^D \\ t \in [0.0, 1.0] \\ C_{\mathbb{A}}^{-1} \cdot (\vec{O}_{\mathbb{B}} - \vec{O}_{\mathbb{A}} + C_{\mathbb{B}} \cdot \vec{X} + (\vec{V}_{\mathbb{B}} - \vec{V}_{\mathbb{A}}) \cdot t) \cap [0.0, 1.0]^D \end{array} \right\} \quad (25)$$

If \mathbb{A} is a cuboid and \mathbb{B} is a tetrahedron:

$$\left\{ \begin{array}{l} \vec{X} \in [0.0, 1.0]^D \\ t \in [0.0, 1.0] \\ \sum_{i=0}^{D-1} [X]_i \leq 1.0 \\ C_{\mathbb{A}}^{-1} \cdot (\vec{O}_{\mathbb{B}} - \vec{O}_{\mathbb{A}} + C_{\mathbb{B}} \cdot \vec{X} + (\vec{V}_{\mathbb{B}} - \vec{V}_{\mathbb{A}}) \cdot t) \cap [0.0, 1.0]^D \end{array} \right\} \quad (26)$$

If \mathbb{A} is a tetrahedron and \mathbb{B} is a cuboid:

$$\left\{ \begin{array}{l} \vec{X} \in [0.0, 1.0]^D \\ t \in [0.0, 1.0] \\ C_{\mathbb{A}}^{-1} \cdot (\vec{O}_{\mathbb{B}} - \vec{O}_{\mathbb{A}} + C_{\mathbb{B}} \cdot \vec{X} + (\vec{V}_{\mathbb{B}} - \vec{V}_{\mathbb{A}}) \cdot t) \cap [0.0, 1.0]^D \\ \sum_{i=0}^{D-1} [C_{\mathbb{A}}^{-1} \cdot (\vec{O}_{\mathbb{B}} - \vec{O}_{\mathbb{A}} + C_{\mathbb{B}} \cdot \vec{X})]_i \leq 1.0 \end{array} \right\} \quad (27)$$

If \mathbb{A} and \mathbb{B} are two tetrahedrons:

$$\left\{ \begin{array}{l} \vec{X} \in [0.0, 1.0]^D \\ t \in [0.0, 1.0] \\ \sum_{i=0}^{D-1} [X]_i \leq 1.0 \\ C_{\mathbb{A}}^{-1} \cdot (\vec{O}_{\mathbb{B}} - \vec{O}_{\mathbb{A}} + C_{\mathbb{B}} \cdot \vec{X} + (\vec{V}_{\mathbb{B}} - \vec{V}_{\mathbb{A}}) \cdot t) \cap [0.0, 1.0]^D \\ \sum_{i=0}^{D-1} [C_{\mathbb{A}}^{-1} \cdot (\vec{O}_{\mathbb{B}} - \vec{O}_{\mathbb{A}} + C_{\mathbb{B}} \cdot \vec{X})]_i \leq 1.0 \end{array} \right\} \quad (28)$$

These lead to the following systems of linear inequations, given the three shortcuts $\vec{O}_{\mathbb{B}_{\mathbb{A}}} = C_{\mathbb{A}}^{-1} \cdot (\vec{O}_{\mathbb{B}} - \vec{O}_{\mathbb{A}})$, $\vec{V}_{\mathbb{B}_{\mathbb{A}}} = C_{\mathbb{A}}^{-1} \cdot (\vec{V}_{\mathbb{B}} - \vec{V}_{\mathbb{A}})$ and $C_{\mathbb{B}_{\mathbb{A}}} = C_{\mathbb{A}}^{-1} \cdot C_{\mathbb{B}}$.

If \mathbb{A} and \mathbb{B} are two cuboids:

$$\left\{ \begin{array}{rcl} t & \leq & 1.0 \\ -t & \leq & 0.0 \\ [X]_0 & \leq & 1.0 \\ \dots & & \\ [X]_{D-1} & \leq & 1.0 \\ -[X]_0 & \leq & 0.0 \\ \dots & & \\ -[X]_{D-1} & \leq & 0.0 \\ [V_{\mathbb{B}_A}]_0 \cdot t + \sum_{i=0}^{D-1} [C_{\mathbb{B}_A}]_{0,i} [X]_i & \leq & 1.0 - [O_{\mathbb{B}_A}]_0 \\ \dots & & \\ [V_{\mathbb{B}_A}]_{D-1} \cdot t + \sum_{i=0}^{D-1} [C_{\mathbb{B}_A}]_{D-1,i} [X]_i & \leq & 1.0 - [O_{\mathbb{B}_A}]_{D-1} \\ -[V_{\mathbb{B}_A}]_0 \cdot t - \sum_{i=0}^{D-1} [C_{\mathbb{B}_A}]_{0,i} [X]_i & \leq & [O_{\mathbb{B}_A}]_0 \\ \dots & & \\ -[V_{\mathbb{B}_A}]_{D-1} \cdot t - \sum_{i=0}^{D-1} [C_{\mathbb{B}_A}]_{D-1,i} [X]_i & \leq & [O_{\mathbb{B}_A}]_{D-1} \end{array} \right. \quad (29)$$

If \mathbb{A} is a cuboid and \mathbb{B} is a tetrahedron:

$$\left\{ \begin{array}{rcl} t & \leq & 1.0 \\ -t & \leq & 0.0 \\ -[X]_0 & \leq & 0.0 \\ \dots & & \\ -[X]_{D-1} & \leq & 0.0 \\ [V_{\mathbb{B}_A}]_0 \cdot t + \sum_{i=0}^{D-1} [C_{\mathbb{B}_A}]_{0,i} [X]_i & \leq & 1.0 - [O_{\mathbb{B}_A}]_0 \\ \dots & & \\ [V_{\mathbb{B}_A}]_{D-1} \cdot t + \sum_{i=0}^{D-1} [C_{\mathbb{B}_A}]_{D-1,i} [X]_i & \leq & 1.0 - [O_{\mathbb{B}_A}]_{D-1} \\ -[V_{\mathbb{B}_A}]_0 \cdot t - \sum_{i=0}^{D-1} [C_{\mathbb{B}_A}]_{0,i} [X]_i & \leq & [O_{\mathbb{B}_A}]_0 \\ \dots & & \\ -[V_{\mathbb{B}_A}]_{D-1} \cdot t - \sum_{i=0}^{D-1} [C_{\mathbb{B}_A}]_{D-1,i} [X]_i & \leq & [O_{\mathbb{B}_A}]_{D-1} \\ \sum_{i=0}^{D-1} [X]_i & \leq & 1.0 \end{array} \right. \quad (30)$$

If \mathbb{A} is a tetrahedron and \mathbb{B} is a cuboid:

$$\left\{ \begin{array}{rcl} t & \leq & 1.0 \\ -t & \leq & 0.0 \\ [X]_0 & \leq & 1.0 \\ \dots & & \\ [X]_{D-1} & \leq & 1.0 \\ -[X]_0 & \leq & 0.0 \\ \dots & & \\ -[X]_{D-1} & \leq & 0.0 \\ -\sum_{i=0}^{D-1} [C_{\mathbb{B}_A}]_{0,i} [X]_i & \leq & [O_{\mathbb{B}_A}]_0 \\ \dots & & \\ -[V_{\mathbb{B}_A}]_{D-1} \cdot t - \sum_{i=0}^{D-1} [C_{\mathbb{B}_A}]_{D-1,i} [X]_i & \leq & [O_{\mathbb{B}_A}]_{D-1} \\ \sum_{j=0}^{D-1} \left([V_{\mathbb{B}_A}]_j \cdot t + \sum_{i=0}^{D-1} [C_{\mathbb{B}_A}]_{j,i} [X]_i \right) & \leq & 1.0 - \sum_{i=0}^{D-1} [O_{\mathbb{B}_A}]_i \end{array} \right. \quad (31)$$

If \mathbb{A} and \mathbb{B} are two tetrahedrons:

$$\left\{ \begin{array}{rcl} t & \leq & 1.0 \\ -t & \leq & 0.0 \\ -[X]_0 & \leq & 0.0 \\ \dots & & \\ -[X]_{D-1} & \leq & 0.0 \\ -\sum_{i=0}^{D-1} [C_{\mathbb{B}_A}]_{0,i} [X]_i & \leq & [O_{\mathbb{B}_A}]_0 \\ \dots & & \\ -[V_{\mathbb{B}_A}]_{D-1} \cdot t - \sum_{i=0}^{D-1} [C_{\mathbb{B}_A}]_{D-1,i} [X]_i & \leq & [O_{\mathbb{B}_A}]_{D-1} \\ \sum_{i=0}^{D-1} [X]_i & \leq & 1.0 \\ \sum_{j=0}^{D-1} \left([V_{\mathbb{B}_A}]_j \cdot t + \sum_{i=0}^{D-1} [C_{\mathbb{B}_A}]_{j,i} [X]_i \right) & \leq & 1.0 - \sum_{i=0}^{D-1} [O_{\mathbb{B}_A}]_i \end{array} \right. \quad (32)$$

2 Resolution of the problem by Fourier-Motzkin method

2.1 The Fourier-Motzkin elimination method

The Fourier-Motzkin elimination method has been introduced by J.J.-B. Fourier in 1827 [1], and described in the Ph.D. thesis of T.S. Motzkin in 1936 [2]. This is a generalization of the Gaussian elimination method to linear systems of inequalities. This method consists of eliminating one variable of the system and rewrite a new system accordingly. Then the elimination operation is repeated on another variable in the new system, and so on until we obtain a trivial system with only one variable. From there, a solution

for each variable can be obtained if it exists. The variable elimination is performed as follow.

Lets write the linear system \mathcal{I} of m inequalities and n variables as

$$\left\{ \begin{array}{ccccccc} a_{11}.x_1 & +a_{12}.x_2 & +\cdots & +a_{1n}.x_n & \leq & b_1 \\ a_{21}.x_1 & +a_{22}.x_2 & +\cdots & +a_{2n}.x_n & \leq & b_2 \\ & & & \vdots & & \\ a_{m1}.x_1 & +a_{m2}.x_2 & +\cdots & +a_{mn}.x_n & \leq & b_m \end{array} \right. \quad (33)$$

with

$$\begin{aligned} i &\in 1, 2, \dots, m \\ j &\in 1, 2, \dots, n \\ x_i &\in \mathbb{R} \\ a_{ij} &\in \mathbb{R} \\ b_j &\in \mathbb{R} \end{aligned} \quad (34)$$

To eliminate the first variable x_1 , lets multiply each inequality by $1.0/|a_{i1}|$ where $a_{i1} \neq 0.0$. The system becomes

$$\left\{ \begin{array}{ccccccc} x_1 & +a'_{i2}.x_2 & +\cdots & +a'_{in}.x_n & \leq & b'_i & (i \in \mathcal{I}_+) \\ & a_{i2}.x_2 & +\cdots & +a_{in}.x_n & \leq & b_i & (i \in \mathcal{I}_0) \\ -x_1 & +a'_{i2}.x_2 & +\cdots & +a'_{in}.x_n & \leq & b'_i & (i \in \mathcal{I}_-) \end{array} \right. \quad (35)$$

where

$$\begin{aligned} \mathcal{I}_+ &= \{i : a_{i1} > 0.0\} \\ \mathcal{I}_0 &= \{i : a_{i1} = 0.0\} \\ \mathcal{I}_- &= \{i : a_{i1} < 0.0\} \\ a'_{ij} &= a_{ij}/|a_{i1}| \\ b'_i &= b_i/|a_{i1}| \end{aligned}$$

Then $x_1, x_2, \dots, x_n \in \mathbb{R}^n$ is a solution of \mathcal{I} if and only if

$$\left\{ \begin{array}{ll} \sum_{j=2}^n ((a'_{kj} + a'_{lj}).x_j) \leq b'_k + b'_l & (k \in \mathcal{I}_+, l \in \mathcal{I}_-) \\ \sum_{j=2}^n (a_{ij}.x_j) \leq b_i & i \in \mathcal{I}_0 \end{array} \right. \quad (36)$$

and

$$\max_{l \in \mathcal{I}_-} \left(\sum_{j=2}^n (a'_{lj}.x_j) - b'_l \right) \leq x_1 \leq \min_{k \in \mathcal{I}_+} \left(b'_k - \sum_{j=2}^n (a'_{kj}.x_j) \right) \quad (37)$$

The same method is then applied on this new system to eliminate the second variable x_2 , and so on until we reach the inequality

$$\max_{l \in \mathcal{I}_-'''} (-b_l''') \leq x_n \leq \min_{k \in \mathcal{I}_+'''} (b_k''') \quad (38)$$

If this inequality has no solution, then neither the system \mathcal{I} . If it has a solution, the minimum and maximum are the bounding values for the variable x_n . One can get a particular solution to the system \mathcal{I} by choosing a value for x_n between these bounding values, which allow us to set a particular value for the variable x_{n-1} , and so on back up to x_1 .

2.2 Application of the Fourier-Motzkin method to the intersection problem

The Fourier-Motzkin method can be directly applied to obtain the bounds of each variable, if the system has a solution. If the system has no solution, the method will eventually reach an inconsistent inequality.

One solution \vec{S} within the bounds obtained by the resolution of the system is expressed in the Frame \mathbb{B} 's coordinates system. One can get the equivalent coordinates \vec{S}' in the real world's coordinates system as follow:

$$\vec{S}' = \vec{O}_{\mathbb{B}} + C_{\mathbb{B}} \cdot \vec{S} \quad (39)$$

Only one inconsistent inequality is sufficient to prove the absence of solution, and then the non intersection of the Frames. One shall check the inconsistency of each inequality as soon as possible during the resolution of the system to optimize the speed of the algorithm.

A sufficient condition for one inequality $\sum_i a_i X_i \leq Y$ to be inconsistent is, given that $\forall i, X_i \in [0.0, 1.0]$:

$$Y < \sum_{i \in I^-} a_i \quad (40)$$

where $I^- = \{i, a_i < 0.0\}$.

2.3 About the size of system of linear inequation

During implementation in languages where the developer needs to manage memory itself the size of the systems (35) resulting from variable elimination is necessary but cannot be forecasted. Instead, a maximum size can be calculated as follow.

Lets call n_- , n_+ and n_0 the size of, respectively, \mathcal{I}_- , \mathcal{I}_+ and \mathcal{I}_0 , and N the number of inequalities in the original system and N' the number inequalities

in the resulting system. We have:

$$n_- + n_+ + n_0 = N \quad (41)$$

and

$$n_-.n_+ + n_0 = N' \quad (42)$$

Now lets define $K = N - n_0$, then we have:

$$n_- + n_+ = K \quad (43)$$

then,

$$n_-.n_+ = n_-(K - n_-) \quad (44)$$

then,

$$n_-.n_+ = K.n_-n_-^2 \quad (45)$$

The right part is polynomial whose maximum is reached for $n_- = K/2$. Then,

$$n_-.n_+ \leq K^2/2 - K^2/4 \quad (46)$$

or,

$$n_-.n_+ \leq K^2/4 \quad (47)$$

and putting back the definition of K

$$n_-.n_+ \leq (N - n_0)^2/4 \quad (48)$$

which is also

$$n_-.n_+ \leq N^2/4 \quad (49)$$

From (42) we get,

$$N' \leq N^2/4 - n_0 \quad (50)$$

and getting rid of the n_0 knowing that $n_0 \geq 0$,

$$N' \leq N^2/4 \quad (51)$$

The maximum number of inequation in the initial system is defined for each case (2D/3D, static/dynamic) in the previous section. This leads to the following maximum number of inequations:

	N	N'	N''	N'''
<i>2Dstatic</i>	8	16		
<i>2Ddynamic</i>	10	25	157	
<i>3Dstatic</i>	12	36	324	
<i>3Ddynamic</i>	14	49	601	90301

3 Algorithms of the solution

In this section I introduce the algorithms of the solution of the previous section for each case (static/dynamic and 2D/3D), and the algorithms to manipulate the structure used to represent the cuboid and tetrahedron.

Algorithms are given in pseudo code, and consequently without any optimization based on properties of one given language. One can refer to the C implementation in the following sections for possible optimization in this language.

Algorithms are also given independantly from each other. Code commonalization may be possible if one plans to gather several cases together, but this is dependant of the implementation and thus left to the developper responsibility.

3.1 2D static

```
ENUM FrameType
    FrameCuboid,
    FrameTetrahedron
END ENUM

STRUCT AAB2D
    // x,y
    real min[2]
    real max[2]
END STRUCT

STRUCT Frame2D
    FrameType type
    real orig[2]
    // comp[iComp][iAxis]
    real comp[2][2]
    AAB2D bdgBox
    real invComp[2][2]
END STRUCT

FUNCTION powi(base, exp)
    res = 1
    FOR i=0..(exp - 1)
        res = res * base
    END FOR
    RETURN res
END FUNCTION

FUNCTION Frame2DPrint(that)
    IF that.type == FrameTetrahedron
        PRINT "T"
    ELSE IF that.type == FrameCuboid
        PRINT "C"
```

```

END IF
PRINT "o("
FOR i = 0..1
  PRINT that.orig[i]
  IF i < 1
    PRINT ","
  END IF
END FOR
comp = ['x','y']
FOR j = 0..1
  PRINT ") " comp[j] "("
  FOR i = 0..1
    PRINT that.comp[j][i]
    IF i < 1
      PRINT ","
    END IF
  END FOR
END FOR
PRINT ")"
END FUNCTION

FUNCTION AAB2DPrint(that)
  PRINT "minXY("
  FOR i = 0..1
    PRINT that.min[i]
    IF i < 1
      PRINT ","
    END IF
  END FOR
  PRINT ") -maxXY("
  FOR i = 0..1
    PRINT that.max[i]
    IF i < 1
      PRINT ","
    END IF
  END FOR
  PRINT ")"
END FUNCTION

FUNCTION Frame2DExportBdgBox(that, bdgBox, bdgBoxProj)
  FOR i = 0..1
    bdgBoxProj.max[i] = that.orig[i]
    FOR j = 0..1
      bdgBoxProj.max[i] =
        bdgBoxProj.max[i] + that.comp[j][i] * bdgBox.min[j]
    END FOR
    bdgBoxProj.min[i] = bdgBoxProj.max[i]
  END FOR
  nbVertices = powi(2, 2)
  FOR iVertex = 1..(nbVertices - 1)
    FOR i = 0..1
      IF (iVertex & (1 << i)) == TRUE
        v[i] = bdgBox.max[i]
      ELSE
        v[i] = bdgBox.min[i]
      END IF
    END FOR
    FOR i = 0..1
      w[i] = that.orig[i]
      FOR j = 0..1
        w[i] = w[i] + that.comp[j][i] * v[j]
      END FOR
    END FOR
  END FOR
END FUNCTION

```



```

END FOR
FOR i = 0..1
  IF bdgBoxProj.min[i] > w[i]
    bdgBoxProj.min[i] = w[i]
  END IF
  IF bdgBoxProj.max[i] < w[i]
    bdgBoxProj.max[i] = w[i]
  END IF
END FOR
END FOR
END FUNCTION

FUNCTION Frame2DImportFrame(P, Q, Qp)
  FOR i = 0..1
    v[i] = Q.orig[i] - P.orig[i]
  END FOR
  FOR i = 0..1
    Qp.orig[i] = 0.0
    FOR j = 0..1
      Qp.orig[i] = Qp.orig[i] + P.invComp[j][i] * v[j]
      Qp.comp[j][i] = 0.0
      FOR k = 0..1
        Qp.comp[j][i] = Qp.comp[j][i] + P.invComp[k][i] * Q.comp[j][k]
      END FOR
    END FOR
  END FOR
END FUNCTION

FUNCTION Frame2DUpdateInv(that)
  det = that.comp[0][0] * that.comp[1][1] -
    that.comp[1][0] * that.comp[0][1]
  that.invComp[0][0] = that.comp[1][1] / det
  that.invComp[0][1] = -that.comp[0][1] / det
  that.invComp[1][0] = -that.comp[1][0] / det
  that.invComp[1][1] = that.comp[0][0] / det
END FUNCTION

FUNCTION Frame2DCreateStatic(type, orig, comp)
  that.type = type
  FOR iAxis = 0..1
    that.orig[iAxis] = orig[iAxis]
    FOR iComp = 0..1
      that.comp[iComp][iAxis] = comp[iComp][iAxis]
    END FOR
  END FOR
  FOR iAxis = 0..1
    min = orig[iAxis]
    max = orig[iAxis]
    FOR iComp = 0..1
      IF that.type == FrameCuboid
        IF that.comp[iComp][iAxis] < 0.0
          min += that.comp[iComp][iAxis]
        END IF
        IF that.comp[iComp][iAxis] > 0.0
          max += that.comp[iComp][iAxis]
        END IF
      ELSE IF that.type == FrameTetrahedron
        IF that.comp[iComp][iAxis] < 0.0 AND
          min > orig[iAxis] + that.comp[iComp][iAxis]
          min = orig[iAxis] + that.comp[iComp][iAxis]
        END IF
        IF that.comp[iComp][iAxis] > 0.0 AND

```

```

        max < orig[iAxis] + that.comp[iComp][iAxis]
        max = orig[iAxis] + that.comp[iComp][iAxis]
    END IF
END IF
END FOR
that.bdgBox.min[iAxis] = min
that.bdgBox.max[iAxis] = max
END FOR
Frame2DUpdateInv(that)
RETURN that
END FUNCTION

FUNCTION Sgn(v)
    IF 0.0 < v
        a = 1
    ELSE
        a = 0
    END IF
    IF v < 0.0
        b = 1
    ELSE
        b = 0
    END IF
    RETURN a - b
END FUNCTION

FUNCTION Neg(x)
    IF x < 0.0
        RETURN x
    ELSE
        RETURN 0.0
    END IF
END FUNCTION

FST_VAR = 0
SND_VAR = 1

FUNCTION ElimVar2D(iVar, M, Y, nbRows, nbCols, Mp, Yp, nbRemainRows)
    nbRemainRows = 0
    FOR iRow = 0..(nbRows - 2)
        FOR jRow = (iRow + 1)..(nbRows - 1)
            IF sgn(M[iRow][iVar]) <> sgn(M[jRow][iVar]) AND
                M[iRow][iVar] <> 0.0 AND
                M[jRow][iVar] <> 0.0
                sumNegCoeff = 0.0
                jCol = 0
                FOR iCol = 0..(nbCols - 1)
                    IF iCol <> iVar
                        Mp[nbRemainRows][jCol] =
                            M[iRow][iCol] / fabs(M[iRow][iVar]) +
                            M[jRow][iCol] / fabs(M[jRow][iVar])
                        sumNegCoeff += neg(Mp[nbRemainRows][jCol])
                        jCol = jcol + 1
                    END IF
                END FOR
                Yp[nbRemainRows] =
                    Y[iRow] / fabs(M[iRow][iVar]) +
                    Y[jRow] / fabs(M[jRow][iVar])
                IF Yp[nbRemainRows] < sumNegCoeff
                    RETURN TRUE
                END IF
                nbRemainRows = nbRemainRows + 1
            END IF
        END FOR
    END FOR
END FUNCTION

```

```

        END IF
    END FOR
END FOR
FOR iRow = 0..(nbRows - 1)
    IF M[iRow][iVar] == 0.0
        jCol = 0
        FOR iCol = 0..(nbCols - 1)
            IF iCol <> iVar
                Mp[nbRemainRows][jCol] = M[iRow][iCol]
                jCol = jCol + 1
            END IF
        END FOR
        Yp[nbRemainRows] = Y[iRow]
        nbRemainRows = nbRemainRows + 1
    END IF
END FOR
RETURN FALSE
END FUNCTION

FUNCTION GetBound2D(iVar, M, Y, nbRows, bdgBox)
    bdgBox.min[iVar] = 0.0
    bdgBox.max[iVar] = 1.0
    FOR jRow = 0..(nbRows - 1)
        IF M[jRow][0] > 0.0
            y = Y[jRow] / M[jRow][0]
            IF bdgBox.max[iVar] > y
                bdgBox.max[iVar] = y
            END IF
        ELSE IF M[jRow][0] < 0.0
            y = Y[jRow] / M[jRow][0]
            IF bdgBox.min[iVar] < y
                bdgBox.min[iVar] = y
            END IF
        END IF
    END FOR
END FUNCTION

FUNCTION FMBTestIntersection2D(that, tho, bdgBox)
    Frame2DImportFrame(that, tho, &thoProj)
    M[0][0] = -thoProj.comp[0][0]
    M[0][1] = -thoProj.comp[1][0]
    Y[0] = thoProj.orig[0]
    IF Y[0] < neg(M[0][0]) + neg(M[0][1])
        RETURN FALSE
    END IF
    M[1][0] = -thoProj.comp[0][1]
    M[1][1] = -thoProj.comp[1][1]
    Y[1] = thoProj.orig[1]
    IF Y[1] < neg(M[1][0]) + neg(M[1][1])
        RETURN FALSE
    END IF
    M[2][0] = -1.0
    M[2][1] = 0.0
    Y[2] = 0.0
    M[3][0] = 0.0
    M[3][1] = -1.0
    Y[3] = 0.0
    nbRows = 4
    IF that.type == FrameCuboid
        M[nbRows][0] = thoProj.comp[0][0]
        M[nbRows][1] = thoProj.comp[1][0]
        Y[nbRows] = 1.0 - thoProj.orig[0]
    END IF

```

```

        IF Y[nbRows] < neg(M[nbRows][0]) + neg(M[nbRows][1])
            RETURN FALSE
        END IF
        nbRows = nbRows + 1
        M[nbRows][0] = thoProj.comp[0][1]
        M[nbRows][1] = thoProj.comp[1][1]
        Y[nbRows] = 1.0 - thoProj.orig[1]
        IF Y[nbRows] < neg(M[nbRows][0]) + neg(M[nbRows][1])
            RETURN FALSE
        END IF
        nbRows = nbRows + 1
    ELSE
        M[nbRows][0] = thoProj.comp[0][0] + thoProj.comp[0][1]
        M[nbRows][1] = thoProj.comp[1][0] + thoProj.comp[1][1]
        Y[nbRows] = 1.0 - thoProj.orig[0] - thoProj.orig[1]
        IF Y[nbRows] < neg(M[nbRows][0]) + neg(M[nbRows][1])
            RETURN FALSE
        END IF
        nbRows = nbRows + 1
    END
    IF tho.type == FrameCuboid
        M[nbRows][0] = 1.0
        M[nbRows][1] = 0.0
        Y[nbRows] = 1.0
        nbRows = nbRows + 1
        M[nbRows][0] = 0.0
        M[nbRows][1] = 1.0
        Y[nbRows] = 1.0
        nbRows = nbRows + 1
    ELSE
        M[nbRows][0] = 1.0
        M[nbRows][1] = 1.0
        Y[nbRows] = 1.0
        nbRows = nbRows + 1
    END
    inconsistency = ElimVar2D(FST_VAR, M, Y, nbRows, 2, Mp, Yp, nbRowsP)
    IF inconsistency == TRUE
        RETURN FALSE
    END
    GetBound2D(SND_VAR, Mp, Yp, nbRowsP, bdgBoxLocal)
    IF bdgBoxLocal.min[SND_VAR] >= bdgBoxLocal.max[SND_VAR]
        RETURN FALSE
    END
    ElimVar2D(SND_VAR, M, Y, nbRows, 2, Mp, Yp, nbRowsP)
    GetBound2D(FST_VAR, Mp, Yp, nbRowsP, bdgBoxLocal)
    bdgBox = bdgBoxLocal
    RETURN TRUE
END

origP2D = [0.0, 0.0]
compP2D = [
    [1.0, 0.0],
    [0.0, 1.0]]
P2D = Frame2DCreateStatic(FrameCuboid, origP2D, compP2D)
origQ2D = [0.0, 0.0]
compQ2D = [
    [1.0, 0.0],
    [0.0, 1.0]]
Q2D = Frame2DCreateStatic(FrameCuboid, origQ2D, compQ2D)
isIntersecting2D = FMBTestIntersection2D(P2D, Q2D, bdgBox2DLocal)
if isIntersecting2D == TRUE
    PRINT "Intersection detected."

```

```

    Frame2DExportBdgBox(Q2D, bdgBox2DLocal, bdgBox2D);
    AABB2DPrint(bdgBox2D)
ELSE
    PRINT "No intersection."
END IF

```

3.2 3D static

```

ENUM FrameType
    FrameCuboid,
    FrameTetrahedron
END ENUM

STRUCT AABB3D
    // x,y,z
    real min[3]
    real max[3]
END STRUCT

STRUCT Frame3D
    FrameType type
    real orig[3]
    // comp[iComp][iAxis]
    real comp[3][3]
    AABB3D bdgBox
    real invComp[3][3]
END STRUCT

FUNCTION powi(base, exp)
    res = 1
    FOR i=0...(exp - 1)
        res = res * base
    END FOR
    RETURN res
END FUNCTION

FUNCTION Frame3DPrint(that)
    IF that.type == FrameTetrahedron
        PRINT "T"
    ELSE IF that.type == FrameCuboid
        PRINT "C"
    END IF
    PRINT "o("
    FOR i = 0..2
        PRINT that.orig[i]
        IF i < 2
            PRINT ", "
        END IF
    END FOR
    comp = ['x','y','z']
    FOR j = 0..2
        PRINT ") " comp[j] "("
        FOR i = 0..2
            PRINT that.comp[j][i]
            IF i < 2
                PRINT ", "
            END IF
        END FOR
    END FOR
    PRINT ")"
END FUNCTION

```

```

FUNCTION AABB3DPrint(that)
  PRINT "minXYZ("
  FOR i = 0..2
    PRINT that.min[i]
    IF i < 2
      PRINT ","
    END IF
  END FOR
  PRINT ")-maxXYZ("
  FOR i = 0..2
    PRINT that.max[i]
    IF i < 2
      PRINT ","
    END IF
  END FOR
  PRINT ")"
END FUNCTION

FUNCTION Frame3DExportBdgBox(that, bdgBox, bdgBoxProj)
  FOR i = 0..2
    bdgBoxProj.max[i] = that.orig[i]
    FOR j = 0..2
      bdgBoxProj.max[i] =
        bdgBoxProj.max[i] + that.comp[j][i] * bdgBox.min[j]
    END FOR
    bdgBoxProj.min[i] = bdgBoxProj.max[i]
  END FOR
  nbVertices = powi(2, 3)
  FOR iVertex = 1..(nbVertices - 1)
    FOR i = 0..2
      IF (iVertex & (1 << i)) == TRUE
        v[i] = bdgBox.max[i]
      ELSE
        v[i] = bdgBox.min[i]
      END IF
    END FOR
    FOR i = 0..2
      w[i] = that.orig[i]
      FOR j = 0..2
        w[i] = w[i] + that.comp[j][i] * v[j]
      END FOR
    END FOR
    FOR i = 0..2
      IF bdgBoxProj.min[i] > w[i]
        bdgBoxProj.min[i] = w[i]
      END IF
      IF bdgBoxProj.max[i] < w[i]
        bdgBoxProj.max[i] = w[i]
      END IF
    END FOR
  END FOR
END FUNCTION

FUNCTION Frame3DImportFrame(P, Q, Qp)
  FOR i = 0..2
    v[i] = Q.orig[i] - P.orig[i]
  END FOR
  FOR i = 0..2
    Qp.orig[i] = 0.0
    FOR j = 0..2
      Qp.orig[i] = Qp.orig[i] + P.invComp[j][i] * v[j]
    END FOR
  END FOR
END FUNCTION

```

```

        Qp.comp[j][i] = 0.0
        FOR k = 0..2
            Qp.comp[j][i] = Qp.comp[j][i] + P.invComp[k][i] * Q.comp[j][k]
        END FOR
    END FOR
END FOR
END FUNCTION

```

```

FUNCTION Frame3DUpdateInv(that)
    det =
        that.comp[0][0] * (that.comp[1][1] * that.comp[2][2] -
        that.comp[1][2] * that.comp[2][1]) -
        that.comp[1][0] * (that.comp[0][1] * that.comp[2][2] -
        that.comp[0][2] * that.comp[2][1]) +
        that.comp[2][0] * (that.comp[0][1] * that.comp[1][2] -
        that.comp[0][2] * that.comp[1][1])
    that.invComp[0][0] = (that.comp[1][1] * that.comp[2][2] -
    that.comp[1][2] * that.comp[2][1]) / det
    that.invComp[0][1] = (that.comp[2][1] * that.comp[0][2] -
    that.comp[2][2] * that.comp[0][1]) / det
    that.invComp[0][2] = (that.comp[0][1] * that.comp[1][2] -
    that.comp[0][2] * that.comp[1][1]) / det
    that.invComp[1][0] = (that.comp[2][0] * that.comp[1][2] -
    that.comp[2][2] * that.comp[1][0]) / det
    that.invComp[1][1] = (that.comp[0][0] * that.comp[2][2] -
    that.comp[2][0] * that.comp[0][2]) / det
    that.invComp[1][2] = (that.comp[0][2] * that.comp[1][0] -
    that.comp[1][2] * that.comp[0][0]) / det
    that.invComp[2][0] = (that.comp[1][0] * that.comp[2][1] -
    that.comp[2][0] * that.comp[1][1]) / det
    that.invComp[2][1] = (that.comp[0][1] * that.comp[2][0] -
    that.comp[2][1] * that.comp[0][0]) / det
    that.invComp[2][2] = (that.comp[0][0] * that.comp[1][1] -
    that.comp[1][0] * that.comp[0][1]) / det
END FUNCTION

```

```

FUNCTION Frame3DCreateStatic(type, orig, comp)
    that.type = type
    FOR iAxis = 0..2
        that.orig[iAxis] = orig[iAxis]
        FOR iComp = 0..2
            that.comp[iComp][iAxis] = comp[iComp][iAxis]
        END FOR
    END FOR
    FOR iAxis = 0..2
        min = orig[iAxis]
        max = orig[iAxis]
        FOR iComp = 0..2
            IF that.type == FrameCuboid) {
                IF that.comp[iComp][iAxis] < 0.0
                    min += that.comp[iComp][iAxis]
                END IF
                IF that.comp[iComp][iAxis] > 0.0
                    max += that.comp[iComp][iAxis]
                END IF
            }
            ELSE IF that.type == FrameTetrahedron
                IF that.comp[iComp][iAxis] < 0.0 AND
                    min > orig[iAxis] + that.comp[iComp][iAxis]
                    min = orig[iAxis] + that.comp[iComp][iAxis]
                END IF
                IF that.comp[iComp][iAxis] > 0.0 AND
                    max < orig[iAxis] + that.comp[iComp][iAxis]

```

```

        max = orig[iAxis] + that.comp[iComp][iAxis]
    END IF
END FOR
that.bdgBox.min[iAxis] = min
that.bdgBox.max[iAxis] = max
END FOR
Frame3DUpdateInv(that)
RETURN that
END FUNCTION

FUNCTION Sgn(v)
    IF 0.0 < v
        a = 1
    ELSE
        a = 0
    END IF
    IF v < 0.0
        b = 1
    ELSE
        b = 0
    END IF
    RETURN a - b
END FUNCTION

FUNCTION Neg(x)
    IF x < 0.0
        RETURN x
    ELSE
        RETURN 0.0
    END IF
END FUNCTION

FST_VAR = 0
SND_VAR = 1
THD_VAR = 2

FUNCTION ElimVar3D(iVar, M, Y, nbRows, nbCols, Mp, Yp, nbRemainRows)
    nbRemainRows = 0
    FOR iRow = 0..(nbRows - 2)
        FOR jRow = (iRow + 1)..(nbRows - 1)
            IF sgn(M[iRow][iVar]) <> sgn(M[jRow][iVar]) AND
                M[iRow][iVar] <> 0.0 AND
                M[jRow][iVar] <> 0.0
                sumNegCoeff = 0.0
                jCol = 0
                FOR iCol = 0..(nbCols - 1)
                    IF iCol <> iVar
                        Mp[nbRemainRows][jCol] =
                            M[iRow][iCol] / fabs(M[iRow][iVar]) +
                            M[jRow][iCol] / fabs(M[jRow][iVar])
                        sumNegCoeff += neg(Mp[nbRemainRows][jCol])
                        jCol = jCol + 1
                    END IF
                END FOR
                Yp[nbRemainRows] =
                    Y[iRow] / fabs(M[iRow][iVar]) +
                    Y[jRow] / fabs(M[jRow][iVar])
                IF Yp[nbRemainRows] < sumNegCoeff
                    RETURN TRUE
                END IF
                nbRemainRows = nbRemainRows + 1
            END IF
        END FOR
    END FOR
END FUNCTION

```



```

        END IF
    END FOR
END FOR
FOR iRow = 0..(nbRows - 1)
    IF M[iRow][iVar] == 0.0
        jCol = 0
        FOR iCol = 0..(nbCols - 1)
            IF iCol <> iVar
                Mp[nbRemainRows][jCol] = M[iRow][iCol]
                jCol = jCol + 1
            END IF
        END FOR
        Yp[nbRemainRows] = Y[iRow]
        nbRemainRows = nbRemainRows + 1
    END IF
END FOR
RETURN FALSE
END FUNCTION

FUNCTION GetBound3D(iVar, M, Y, nbRows, bdgBox)
    bdgBox.min[iVar] = 0.0
    bdgBox.max[iVar] = 1.0
    FOR jRow = 0..(nbRows - 1)
        IF M[jRow][0] > 0.0
            y = Y[jRow] / M[jRow][0]
            IF bdgBox.max[iVar] > y
                bdgBox.max[iVar] = y
            END IF
        ELSE IF M[jRow][0] < 0.0
            y = Y[jRow] / M[jRow][0]
            IF bdgBox.min[iVar] < y
                bdgBox.min[iVar] = y
            END IF
        END IF
    END FOR
END FUNCTION

FUNCTION FMBTestIntersection3D(that, tho, bdgBox)
    Frame3DImportFrame(that, tho, thoProj)
    M[0][0] = -thoProj.comp[0][0]
    M[0][1] = -thoProj.comp[1][0]
    M[0][2] = -thoProj.comp[2][0]
    Y[0] = thoProj.orig[0]
    IF Y[0] < neg(M[0][0]) + neg(M[0][1]) + neg(M[0][2])
        RETURN FALSE
    END IF
    M[1][0] = -thoProj.comp[0][1]
    M[1][1] = -thoProj.comp[1][1]
    M[1][2] = -thoProj.comp[2][1]
    Y[1] = thoProj.orig[1]
    IF Y[1] < neg(M[1][0]) + neg(M[1][1]) + neg(M[1][2])
        RETURN FALSE
    END IF
    M[2][0] = -thoProj.comp[0][2]
    M[2][1] = -thoProj.comp[1][2]
    M[2][2] = -thoProj.comp[2][2]
    Y[2] = thoProj.orig[2]
    IF Y[2] < neg(M[2][0]) + neg(M[2][1]) + neg(M[2][2])
        RETURN FALSE
    END IF
    M[3][0] = -1.0
    M[3][1] = 0.0

```

```

M[3][2] = 0.0
Y[3] = 0.0
M[4][0] = 0.0
M[4][1] = -1.0
M[4][2] = 0.0
Y[4] = 0.0
M[5][0] = 0.0
M[5][1] = 0.0
M[5][2] = -1.0
Y[5] = 0.0
nbRows = 6
IF that.type == FrameCuboid
  M[nbRows][0] = thoProj.comp[0][0]
  M[nbRows][1] = thoProj.comp[1][0]
  M[nbRows][2] = thoProj.comp[2][0]
  Y[nbRows] = 1.0 - thoProj.orig[0]
  IF Y[nbRows] < neg(M[nbRows][0]) + neg(M[nbRows][1]) +
    neg(M[nbRows][2])
    RETURN FALSE
  END IF
  nbRows = nbRows + 1
  M[nbRows][0] = thoProj.comp[0][1]
  M[nbRows][1] = thoProj.comp[1][1]
  M[nbRows][2] = thoProj.comp[2][1]
  Y[nbRows] = 1.0 - thoProj.orig[1]
  IF Y[nbRows] < neg(M[nbRows][0]) + neg(M[nbRows][1]) +
    neg(M[nbRows][2])
    RETURN FALSE
  END IF
  nbRows = nbRows + 1
  M[nbRows][0] = thoProj.comp[0][2]
  M[nbRows][1] = thoProj.comp[1][2]
  M[nbRows][2] = thoProj.comp[2][2]
  Y[nbRows] = 1.0 - thoProj.orig[2]
  IF Y[nbRows] < neg(M[nbRows][0]) + neg(M[nbRows][1]) +
    neg(M[nbRows][2])
    RETURN FALSE
  END IF
  nbRows = nbRows + 1
ELSE
  M[nbRows][0] =
    thoProj.comp[0][0] + thoProj.comp[0][1] + thoProj.comp[0][2]
  M[nbRows][1] =
    thoProj.comp[1][0] + thoProj.comp[1][1] + thoProj.comp[1][2]
  M[nbRows][2] =
    thoProj.comp[2][0] + thoProj.comp[2][1] + thoProj.comp[2][2]
  Y[nbRows] =
    1.0 - thoProj.orig[0] - thoProj.orig[1] - thoProj.orig[2]
  IF Y[nbRows] < neg(M[nbRows][0]) + neg(M[nbRows][1]) +
    neg(M[nbRows][2])
    RETURN FALSE
  END IF
  nbRows = nbRows + 1
END
IF tho.type == FrameCuboid {
  M[nbRows][0] = 1.0
  M[nbRows][1] = 0.0
  M[nbRows][2] = 0.0
  Y[nbRows] = 1.0
  nbRows = nbRows + 1
  M[nbRows][0] = 0.0
  M[nbRows][1] = 1.0

```

```

        M[nbRows][2] = 0.0
        Y[nbRows] = 1.0
        nbRows = nbRows + 1
        M[nbRows][0] = 0.0
        M[nbRows][1] = 0.0
        M[nbRows][2] = 1.0
        Y[nbRows] = 1.0
        nbRows = nbRows + 1
    ELSE
        M[nbRows][0] = 1.0
        M[nbRows][1] = 1.0
        M[nbRows][2] = 1.0
        Y[nbRows] = 1.0
        nbRows = nbRows + 1
    END
    inconsistency =
        ElimVar3D(FST_VAR, M, Y, nbRows, 3, Mp, Yp, nbRowsP)
    IF inconsistency == TRUE
        RETURN FALSE
    END
    inconsistency =
        ElimVar3D(FST_VAR, Mp, Yp, nbRowsP, 2, Mpp, Ypp, nbRowsPP)
    IF inconsistency == TRUE
        RETURN FALSE
    END
    GetBound3D(THD_VAR, Mpp, Ypp, nbRowsPP, bdgBoxLocal)
    IF bdgBoxLocal.min[THD_VAR] >= bdgBoxLocal.max[THD_VAR]
        RETURN FALSE
    END
    ElimVar3D(SND_VAR, Mp, Yp, nbRowsP, 2, Mpp, Ypp, nbRowsPP)
    GetBound3D(SND_VAR, Mpp, Ypp, nbRowsPP, bdgBoxLocal)
    ElimVar3D(THD_VAR, M, Y, nbRows, 3, Mp, Yp, nbRowsP)
    ElimVar3D(SND_VAR, Mp, Yp, nbRowsP, 2, Mpp, Ypp, nbRowsPP)
    GetBound3D(FST_VAR, Mpp, Ypp, nbRowsPP, bdgBoxLocal)
    bdgBox = bdgBoxLocal
    RETURN TRUE
END

origP3D = [0.0, 0.0, 0.0]
compP3D = [
    [1.0, 0.0, 0.0],
    [0.0, 1.0, 0.0],
    [0.0, 0.0, 1.0]]
P3D = Frame3DCreateStatic(FrameTetrahedron, origP3D, compP3D)
origQ3D = [0.5, 0.5, 0.5]
compQ3D = [
    [2.0, 0.0, 0.0],
    [0.0, 2.0, 0.0],
    [0.0, 0.0, 2.0]]
Q3D = Frame3DCreateStatic(FrameTetrahedron, origQ3D, compQ3D)
isIntersecting3D = FMBTestIntersection3D(P3D, Q3D, bdgBox3DLocal)
IF isIntersecting3D == TRUE
    PRINT "Intersection detected."
    Frame3DExportBdgBox(Q3D, bdgBox3DLocal, bdgBox3D)
    AAB3DPrint(bdgBox3D)
ELSE
    PRINT "No intersection."
END IF

```

3.3 2D dynamic

```

ENUM FrameType
    FrameCuboid,
    FrameTetrahedron
END ENUM

STRUCT AABB2DTime
    // x,y,t
    real min[3]
    real max[3]
END STRUCT

STRUCT Frame2DTime
    FrameType type
    real orig[2]
    // comp[iComp][iAxis]
    real comp[2][2]
    AABB2DTime bdgBox
    real invComp[2][2]
    real speed[2]
END STRUCT

FUNCTION powi(base, exp)
    res = 1
    FOR i=0..(exp - 1)
        res = res * base
    END FOR
    RETURN res
END FUNCTION

FUNCTION Frame2DTimePrint(that)
    IF that.type == FrameTetrahedron
        PRINT "T"
    ELSE IF that.type == FrameCuboid
        PRINT "C"
    END IF
    PRINT "o("
    FOR i = 0..1
        PRINT that.orig[i]
        IF i < 1
            PRINT ", "
        END IF
    END FOR
    PRINT ") s("
    FOR i = 0..1
        PRINT that.speed[i]
        IF i < 1
            PRINT ", "
        END IF
    END FOR
    comp = ['x', 'y']
    FOR j = 0..1
        PRINT ") " comp[j] "("
        FOR i = 0..1
            PRINT that.comp[j][i]
            IF i < 1
                PRINT ", "
            END IF
        END FOR
    END FOR
    PRINT ")"
END FUNCTION

```

```

FUNCTION AABB2DTimePrint(that)
  PRINT "minXYT("
  FOR i = 0..2
    PRINT that.min[i]
    IF i < 2
      PRINT ","
    END IF
  END FOR
  PRINT ")-maxXYT("
  FOR i = 0..2
    PRINT that.max[i]
    IF i < 2
      PRINT ","
    END IF
  END FOR
  PRINT ")"
END FUNCTION

FUNCTION Frame2DTimeExportBdgBox(that, bdgBox, bdgBoxProj)
  bdgBoxProj.min[2] = bdgBox.min[2]
  bdgBoxProj.max[2] = bdgBox.max[2]
  FOR i = 0..1
    bdgBoxProj.max[i] = that.orig[i] + that.speed[i] * bdgBox.min[2]
    FOR j = 0..1
      bdgBoxProj.max[i] =
        bdgBoxProj.max[i] + that.comp[j][i] * bdgBox.min[j]
    END FOR
    bdgBoxProj.min[i] = bdgBoxProj.max[i]
  END FOR
  nbVertices = powi(2, 2)
  FOR iVertex = 1..(nbVertices - 1)
    FOR i = 0..1
      IF (iVertex & (1 << i)) == TRUE
        v[i] = bdgBox.max[i]
      ELSE
        v[i] = bdgBox.min[i]
      END IF
    END FOR
    FOR i = 0..1
      w[i] = that.orig[i]
      FOR j = 0..1
        w[i] = w[i] + that.comp[j][i] * v[j]
      END FOR
    END FOR
    FOR i = 0..1
      IF bdgBoxProj.min[i] > w[i] + that.speed[i] * bdgBox.min[2]
        bdgBoxProj.min[i] = w[i] + that.speed[i] * bdgBox.min[2]
      END IF
      IF bdgBoxProj.min[i] > w[i] + that.speed[i] * bdgBox.max[2]
        bdgBoxProj.min[i] = w[i] + that.speed[i] * bdgBox.max[2]
      END IF
      IF bdgBoxProj.max[i] < w[i] + that.speed[i] * bdgBox.min[2]
        bdgBoxProj.max[i] = w[i] + that.speed[i] * bdgBox.min[2]
      END IF
      IF bdgBoxProj.max[i] < w[i] + that.speed[i] * bdgBox.max[2]
        bdgBoxProj.max[i] = w[i] + that.speed[i] * bdgBox.max[2]
      END IF
    END FOR
  END FOR
END FUNCTION

FUNCTION Frame2DTimeImportFrame(P, Q, Qp)

```

```

FOR i = 0..1
  v[i] = Q.orig[i] - P.orig[i]
  s[i] = Q.speed[i] - P.speed[i]
END FOR
FOR i = 0..1
  Qp.orig[i] = 0.0
  Qp.speed[i] = 0.0
  FOR j = 0..1
    Qp.orig[i] = Qp.orig[i] + P.invComp[j][i] * v[j]
    Qp.speed[i] = Qp.speed[i] + P.invComp[j][i] * s[j]
    Qp.comp[j][i] = 0.0
    FOR k = 0..1
      Qp.comp[j][i] = Qp.comp[j][i] + P.invComp[k][i] * Q.comp[j][k]
    END FOR
  END FOR
END FOR
END FUNCTION

FUNCTION Frame2DTimeUpdateInv(that)
  det = that.comp[0][0] * that.comp[1][1] -
    that.comp[1][0] * that.comp[0][1]
  that.invComp[0][0] = that.comp[1][1] / det
  that.invComp[0][1] = -that.comp[0][1] / det
  that.invComp[1][0] = -that.comp[1][0] / det
  that.invComp[1][1] = that.comp[0][0] / det
END FUNCTION

FUNCTION Frame2DTimeCreateStatic(type, orig, comp)
  that.type = type
  FOR iAxis = 0..1
    that.orig[iAxis] = orig[iAxis]
    that.speed[iAxis] = speed[iAxis]
    FOR iComp = 0..1
      that.comp[iComp][iAxis] = comp[iComp][iAxis]
    END FOR
  END FOR
  FOR iAxis = 0..1
    min = orig[iAxis]
    max = orig[iAxis]
    FOR iComp = 0..1
      IF that.type == FrameCuboid
        IF that.comp[iComp][iAxis] < 0.0
          min += that.comp[iComp][iAxis]
        END IF
        IF that.comp[iComp][iAxis] > 0.0
          max += that.comp[iComp][iAxis]
        END IF
      ELSE IF that.type == FrameTetrahedron
        IF that.comp[iComp][iAxis] < 0.0 AND
          min > orig[iAxis] + that.comp[iComp][iAxis]
          min = orig[iAxis] + that.comp[iComp][iAxis]
        END IF
        IF that.comp[iComp][iAxis] > 0.0 AND
          max < orig[iAxis] + that.comp[iComp][iAxis]
          max = orig[iAxis] + that.comp[iComp][iAxis]
        END IF
      END IF
    END FOR
  END FOR
  IF that.speed[iAxis] < 0.0
    min = min + that.speed[iAxis]
  END IF
  IF that.speed[iAxis] > 0.0

```

```

        max = max + that.speed[iAxis]
    END IF
    that.bdgBox.min[iAxis] = min
    that.bdgBox.max[iAxis] = max
END FOR
that.bdgBox.min[2] = 0.0
that.bdgBox.max[2] = 1.0
Frame2DTimeUpdateInv(that)
RETURN that
END FUNCTION

FUNCTION Sgn(v)
    IF 0.0 < v
        a = 1
    ELSE
        a = 0
    END IF
    IF v < 0.0
        b = 1
    ELSE
        b = 0
    END IF
    RETURN a - b
END FUNCTION

FUNCTION Neg(x)
    IF x < 0.0
        RETURN x
    ELSE
        RETURN 0.0
    END IF
END FUNCTION

FST_VAR = 0
SND_VAR = 1
THD_VAR = 2

FUNCTION ElimVar2DTime(iVar, M, Y, nbRows, nbCols, Mp, Yp, nbRemainRows)
    nbRemainRows = 0
    FOR iRow = 0..(nbRows - 2)
        FOR jRow = (iRow + 1)..(nbRows - 1)
            IF sgn(M[iRow][iVar]) <> sgn(M[jRow][iVar]) AND
                M[iRow][iVar] <> 0.0 AND
                M[jRow][iVar] <> 0.0
                sumNegCoeff = 0.0
                jCol = 0
                FOR iCol = 0..(nbCols - 1)
                    IF iCol <> iVar
                        Mp[nbRemainRows][jCol] =
                            M[iRow][iCol] / fabs(M[iRow][iVar]) +
                            M[jRow][iCol] / fabs(M[jRow][iVar])
                        sumNegCoeff += neg(Mp[nbRemainRows][jCol])
                        jCol = jCol + 1
                    END IF
                END FOR
                Yp[nbRemainRows] =
                    Y[iRow] / fabs(M[iRow][iVar]) +
                    Y[jRow] / fabs(M[jRow][iVar])
                IF Yp[nbRemainRows] < sumNegCoeff
                    RETURN TRUE
                END IF
            nbRemainRows = nbRemainRows + 1
        END FOR
    END FOR
END FUNCTION

```

```

        END IF
    END FOR
END FOR
FOR (int iRow = 0
    iRow < nbRows
    ++iRow) {
    IF M[iRow][iVar] == 0.0
        jCol = 0
        FOR iCol = 0..(nbCols - 1)
            IF iCol <> iVar
                Mp[nbRemainRows][jCol] = M[iRow][iCol]
                jCol = jCol + 1
            END IF
        END FOR
        Yp[nbRemainRows] = Y[iRow]
        nbRemainRows = nbRemainRows + 1
    END IF
END FOR
RETURN FALSE
END FUNCTION

FUNCTION GetBound2DTime(iVar, M, Y, nbRows, bdgBox)
    bdgBox.min[iVar] = 0.0
    bdgBox.max[iVar] = 1.0
    FOR jRow = 0..(nbRows - 1)
        IF M[jRow][0] > 0.0
            double y = Y[jRow] / M[jRow][0]
            IF bdgBox.max[iVar] > y
                bdgBox.max[iVar] = y
            END IF
        ELSE IF M[jRow][0] < 0.0
            double y = Y[jRow] / M[jRow][0]
            IF bdgBox.min[iVar] < y
                bdgBox.min[iVar] = y
            END IF
        END IF
    END FOR
END FUNCTION

FUNCTION FMBTestIntersection2DTime(that, tho, bdgBox)
    Frame2DTimeImportFrame(that, tho, &thoProj)
    M[0][0] = -thoProj.comp[0][0]
    M[0][1] = -thoProj.comp[1][0]
    M[0][2] = -thoProj.speed[0]
    Y[0] = thoProj.orig[0]
    IF (Y[0] < neg(M[0][0]) + neg(M[0][1]) + neg(M[0][2]))
        RETURN FALSE
    END IF
    M[1][0] = -thoProj.comp[0][1]
    M[1][1] = -thoProj.comp[1][1]
    M[1][2] = -thoProj.speed[1]
    Y[1] = thoProj.orig[1]
    IF (Y[1] < neg(M[1][0]) + neg(M[1][1]) + neg(M[1][2]))
        RETURN FALSE
    END IF
    M[2][0] = -1.0
    M[2][1] = 0.0
    M[2][2] = 0.0
    Y[2] = 0.0
    M[3][0] = 0.0
    M[3][1] = -1.0
    M[3][2] = 0.0

```



```

Y[3] = 0.0
M[4][0] = 0.0
M[4][1] = 0.0
M[4][2] = 1.0
Y[4] = 1.0
M[5][0] = 0.0
M[5][1] = 0.0
M[5][2] = -1.0
Y[5] = 0.0
nbRows = 6
IF that.type == FrameCuboid
  M[nbRows][0] = thoProj.comp[0][0]
  M[nbRows][1] = thoProj.comp[1][0]
  M[nbRows][2] = thoProj.speed[0]
  Y[nbRows] = 1.0 - thoProj.orig[0]
  IF Y[nbRows] < neg(M[nbRows][0]) + neg(M[nbRows][1]) +
    neg(M[nbRows][2])
    RETURN FALSE
  END IF
  nbRows = nbRows + 1
  M[nbRows][0] = thoProj.comp[0][1]
  M[nbRows][1] = thoProj.comp[1][1]
  M[nbRows][2] = thoProj.speed[1]
  Y[nbRows] = 1.0 - thoProj.orig[1]
  IF Y[nbRows] < neg(M[nbRows][0]) + neg(M[nbRows][1]) +
    neg(M[nbRows][2])
    RETURN FALSE
  nbRows = nbRows + 1
ELSE
  M[nbRows][0] = thoProj.comp[0][0] + thoProj.comp[0][1]
  M[nbRows][1] = thoProj.comp[1][0] + thoProj.comp[1][1]
  M[nbRows][2] = thoProj.speed[0] + thoProj.speed[1]
  Y[nbRows] = 1.0 - thoProj.orig[0] - thoProj.orig[1]
  IF Y[nbRows] < neg(M[nbRows][0]) + neg(M[nbRows][1]) +
    neg(M[nbRows][2])
    RETURN FALSE
  nbRows = nbRows + 1
END
IF tho.type == FrameCuboid
  M[nbRows][0] = 1.0
  M[nbRows][1] = 0.0
  M[nbRows][2] = 0.0
  Y[nbRows] = 1.0
  nbRows = nbRows + 1
  M[nbRows][0] = 0.0
  M[nbRows][1] = 1.0
  M[nbRows][2] = 0.0
  Y[nbRows] = 1.0
  nbRows = nbRows + 1
ELSE
  M[nbRows][0] = 1.0
  M[nbRows][1] = 1.0
  M[nbRows][2] = 0.0
  Y[nbRows] = 1.0
  nbRows = nbRows + 1
END IF
inconsistency =
  ElimVar2DTime(FST_VAR, M, Y, nbRows, 3, Mp, Yp, nbRowsP)
IF inconsistency == TRUE
  RETURN FALSE
END IF
inconsistency =

```

```

        ElimVar2DTime(FST_VAR, Mp, Yp, nbRowsP, 2, Mpp, Ypp, nbRowsPP)
    IF inconsistency == TRUE
        RETURN FALSE
    END IF
    GetBound2DTime(THD_VAR, Mpp, Ypp, nbRowsPP, bdgBoxLocal)
    IF bdgBoxLocal.min[THD_VAR] >= bdgBoxLocal.max[THD_VAR]
        RETURN FALSE
    END IF
    ElimVar2DTime(SND_VAR, Mp, Yp, nbRowsP, 2, Mpp, Ypp, nbRowsPP)
    GetBound2DTime(SND_VAR, Mpp, Ypp, nbRowsPP, bdgBoxLocal)
    ElimVar2DTime(THD_VAR, M, Y, nbRows, 3, Mp, Yp, nbRowsP)
    ElimVar2DTime(SND_VAR, Mp, Yp, nbRowsP, 2, Mpp, Ypp, nbRowsPP)
    GetBound2DTime(FST_VAR, Mpp, Ypp, nbRowsPP, bdgBoxLocal)
    bdgBox = bdgBoxLocal
    RETURN TRUE
END FUNCTION

origP2DTime = [0.0, 0.0]
speedP2DTime = [0.0, 0.0]
compP2DTime = [
    [1.0, 0.0],
    [0.0, 1.0]]
P2DTime =
    Frame2DTimeCreateStatic(
        FrameCuboid, origP2DTime, speedP2DTime, compP2DTime)
origQ2DTime = [0.0, 0.0]
speedQ2DTime = [0.0, 0.0]
compQ2DTime = [
    [1.0, 0.0],
    [0.0, 1.0]]
Q2DTime =
    Frame2DTimeCreateStatic(
        FrameCuboid, origQ2DTime, speedQ2DTime, compQ2DTime)
isIntersecting2DTime =
    FMBTestIntersection2DTime(P2DTime, Q2DTime, bdgBox2DTimeLocal)
IF isIntersecting2DTime == TRUE
    PRINT "Intersection detected."
    Frame2DTimeExportBdgBox(Q2DTime, bdgBox2DTimeLocal, bdgBox2DTime)
    AABB2DTimePrint(bdgBox2DTime)
ELSE
    PRINT "No intersection."
END IF

```

3.4 3D dynamic

```

ENUM FrameType
    FrameCuboid,
    FrameTetrahedron
END ENUM

STRUCT AABB3DTime
    // x,y,z,t
    real min[4]
    real max[4]
END STRUCT

STRUCT Frame3DTime
    FrameType type
    real orig[3]
    // comp[iComp][iAxis]
    real comp[3][3]

```

```

    AAB3DTime bdgBox
    real invComp[3][3]
    real speed[3]
END STRUCT

FUNCTION powi(base, exp)
    res = 1
    FOR i=0..(exp - 1)
        res = res * base
    END FOR
    RETURN res
END FUNCTION

FUNCTION Frame3DTimePrint(that)
    IF that.type == FrameTetrahedron
        PRINT "T"
    ELSE IF that.type == FrameCuboid
        PRINT "C"
    END IF
    PRINT "o("
    FOR (i = 0..2
        PRINT that.orig[i]
        IF i < 2
            PRINT ","
        END IF
    END FOR
    PRINT " s("
    FOR i = 0..2
        PRINT that.speed[i]
        IF i < 2
            PRINT ","
        END IF
    END FOR
    comp = ['x', 'y', 'z']
    FOR j = 0..2
        PRINT " " comp[j] "("
        FOR i = 0..2
            PRINT that.comp[j][i]
            IF i < 2
                PRINT ","
            END IF
        END FOR
    END FOR
    PRINT ""
END FUNCTION

FUNCTION AAB3DTimePrint(that)
    PRINT "minXYZT("
    FOR i = 0..3
        PRINT that.min[i]
        IF i < 3
            PRINT ","
        END IF
    END FOR
    PRINT ")-maxXYZT("
    FOR i = 0..3
        PRINT that.max[i]
        IF i < 3
            PRINT ","
        END IF
    END FOR
    PRINT ")"

```

```

END FUNCTION

FUNCTION Frame3DTimeExportBdgBox(that, bdgBox, bdgBoxProj)
    bdgBoxProj.min[3] = bdgBox.min[3]
    bdgBoxProj.max[3] = bdgBox.max[3]
    FOR i = 0..2
        bdgBoxProj.max[i] = that.orig[i] + that.speed[i] * bdgBox.min[3]
        FOR j = 0..2
            bdgBoxProj.max[i] =
                bdgBoxProj.max[i] + that.comp[j][i] * bdgBox.min[j]
        END FOR
        bdgBoxProj.min[i] = bdgBoxProj.max[i]
    END FOR
    nbVertices = powi(2, 3)
    FOR iVertex = 1..(nbVertices - 1)
        FOR i = 0..2
            IF (iVertex & (1 << i)) == TRUE
                v[i] = bdgBox.max[i]
            ELSE
                v[i] = bdgBox.min[i]
            END IF
        END FOR
        FOR i = 0..2
            w[i] = that.orig[i]
            FOR j = 0..2
                w[i] = w[i] + that.comp[j][i] * v[j]
            END FOR
        END FOR
        FOR i = 0..2
            IF bdgBoxProj.min[i] > w[i] + that.speed[i] * bdgBox.min[3]
                bdgBoxProj.min[i] = w[i] + that.speed[i] * bdgBox.min[3]
            END IF
            IF bdgBoxProj.min[i] > w[i] + that.speed[i] * bdgBox.max[3]
                bdgBoxProj.min[i] = w[i] + that.speed[i] * bdgBox.max[3]
            END IF
            IF bdgBoxProj.max[i] < w[i] + that.speed[i] * bdgBox.min[3]
                bdgBoxProj.max[i] = w[i] + that.speed[i] * bdgBox.min[3]
            END IF
            IF bdgBoxProj.max[i] < w[i] + that.speed[i] * bdgBox.max[3]
                bdgBoxProj.max[i] = w[i] + that.speed[i] * bdgBox.max[3]
            END IF
        END FOR
    END FOR
END FUNCTION

FUNCTION Frame3DTimeImportFrame(P, Q, Qp)
    FOR i = 0..2
        v[i] = Q.orig[i] - P.orig[i]
        s[i] = Q.speed[i] - P.speed[i]
    END FOR
    FOR i = 0..2
        Qp.orig[i] = 0.0
        Qp.speed[i] = 0.0
        FOR j = 0..2
            Qp.orig[i] = Qp.orig[i] + P.invComp[j][i] * v[j]
            Qp.speed[i] = Qp.speed[i] + P.invComp[j][i] * s[j]
            Qp.comp[j][i] = 0.0
            FOR k = 0..2
                Qp.comp[j][i] = Qp.comp[j][i] + P.invComp[k][i] * Q.comp[j][k]
            END FOR
        END FOR
    END FOR
END FUNCTION

```

END FUNCTION

FUNCTION Frame3DTimeUpdateInv(that)

```

det =
  that.comp[0][0] *
    (that.comp[1][1] * that.comp[2][2] - that.comp[1][2] * that.comp[2][1])
  -
  that.comp[1][0] *
    (that.comp[0][1] * that.comp[2][2] - that.comp[0][2] * that.comp[2][1])
  +
  that.comp[2][0] *
    (that.comp[0][1] * that.comp[1][2] - that.comp[0][2] * that.comp[1][1])
that.invComp[0][0] = (that.comp[1][1] * that.comp[2][2] -
  that.comp[2][1] * that.comp[1][2]) / det
that.invComp[0][1] = (that.comp[2][1] * that.comp[0][2] -
  that.comp[2][2] * that.comp[0][1]) / det
that.invComp[0][2] = (that.comp[0][1] * that.comp[1][2] -
  that.comp[0][2] * that.comp[1][1]) / det
that.invComp[1][0] = (that.comp[2][0] * that.comp[1][2] -
  that.comp[2][2] * that.comp[1][0]) / det
that.invComp[1][1] = (that.comp[0][0] * that.comp[2][2] -
  that.comp[2][0] * that.comp[0][2]) / det
that.invComp[1][2] = (that.comp[0][2] * that.comp[1][0] -
  that.comp[1][2] * that.comp[0][0]) / det
that.invComp[2][0] = (that.comp[1][0] * that.comp[2][1] -
  that.comp[2][0] * that.comp[1][1]) / det
that.invComp[2][1] = (that.comp[0][1] * that.comp[2][0] -
  that.comp[2][1] * that.comp[0][0]) / det
that.invComp[2][2] = (that.comp[0][0] * that.comp[1][1] -
  that.comp[1][0] * that.comp[0][1]) / det
END FUNCTION

```

FUNCTION Frame3DTimeCreateStatic(type, orig, comp)

```

that.type = type
FOR iAxis = 0..2
  that.orig[iAxis] = orig[iAxis]
  that.speed[iAxis] = speed[iAxis]
  FOR iComp = 0..2
    that.comp[iComp][iAxis] = comp[iComp][iAxis]
  END FOR
END FOR
FOR iAxis = 0..2
  min = orig[iAxis]
  max = orig[iAxis]
  FOR iComp = 0..2
    IF that.type == FrameCuboid
      IF that.comp[iComp][iAxis] < 0.0
        min += that.comp[iComp][iAxis]
      END IF
      IF that.comp[iComp][iAxis] > 0.0
        max += that.comp[iComp][iAxis]
      END IF
    ELSE IF that.type == FrameTetrahedron
      IF that.comp[iComp][iAxis] < 0.0 AND
        min > orig[iAxis] + that.comp[iComp][iAxis]
        min = orig[iAxis] + that.comp[iComp][iAxis]
      END IF
      IF that.comp[iComp][iAxis] > 0.0 AND
        max < orig[iAxis] + that.comp[iComp][iAxis]
        max = orig[iAxis] + that.comp[iComp][iAxis]
      END IF
    END IF
  END FOR
END IF

```

```

        END FOR
        IF that.speed[iAxis] < 0.0
            min = min + that.speed[iAxis]
        END IF
        IF that.speed[iAxis] > 0.0
            max = max + that.speed[iAxis]
        END IF
        that.bdgBox.min[iAxis] = min
        that.bdgBox.max[iAxis] = max
    END FOR
    that.bdgBox.min[3] = 0.0
    that.bdgBox.max[3] = 1.0
    Frame3DTimeUpdateInv(that)
    RETURN that
END FUNCTION

FUNCTION Sgn(v)
    IF 0.0 < v
        a = 1
    ELSE
        a = 0
    END IF
    IF v < 0.0
        b = 1
    ELSE
        b = 0
    END IF
    RETURN a - b
END FUNCTION

FUNCTION Neg(x)
    IF x < 0.0
        RETURN x
    ELSE
        RETURN 0.0
    END IF
END FUNCTION

FST_VAR = 0
SND_VAR = 1
THD_VAR = 2
FOR_VAR = 3

FUNCTION ElimVar3DTime(iVar, M, Y, nbRows, nbCols, Mp, Yp, nbRemainRows)
    nbRemainRows = 0
    FOR iRow = 0..(nbRows - 2)
        FOR jRow = (iRow + 1)..(nbRows - 1)
            IF Sgn(M[iRow][iVar]) <> sgn(M[jRow][iVar]) AND
                M[iRow][iVar] <> 0.0 AND
                M[jRow][iVar] <> 0.0:
                sumNegCoeff = 0.0
                jCol = 0
                FOR iCol = 0..(nbCols - 1)
                    IF iCol <> iVar
                        Mp[nbRemainRows][jCol] =
                            M[iRow][iCol] / fabs(M[iRow][iVar]) +
                            M[jRow][iCol] / fabs(M[jRow][iVar])
                        sumNegCoeff += neg(Mp[nbRemainRows][jCol])
                        jCol = jCol + 1
                    END IF
                END FOR
                nbRemainRows =
                    Yp[nbRemainRows] =

```

```

        Y[iRow] / fabs(M[iRow][iVar]) +
        Y[jRow] / fabs(M[jRow][iVar])
    IF Yp[nbRemainRows] < sumNegCoeff
        RETURN TRUE
    END IF
    nbRemainRows = nbRemainRows + 1
END IF
END FOR
FOR iRow = 0..(nbRows - 1)
    IF M[iRow][iVar] == 0.0
        jCol = 0
        FOR iCol = 0..(nbCols - 1)
            IF iCol <> iVar
                Mp[nbRemainRows][jCol] = M[iRow][iCol]
                jCol = jCol + 1
            END IF
        END FOR
        Yp[nbRemainRows] = Y[iRow]
        nbRemainRows = nbRemainRows + 1
    END IF
END FOR
RETURN FALSE
END FUNCTION

FUNCTION GetBound3DTime(iVar, M, Y, nbRows, bdgBox)
    bdgBox.min[iVar] = 0.0
    bdgBox.max[iVar] = 1.0
    FOR jRow = 0..(nbRows - 1)
        IF M[jRow][0] > 0.0
            y = Y[jRow] / M[jRow][0]
            IF bdgBox.max[iVar] > y
                bdgBox.max[iVar] = y
            END IF
        ELSE IF M[jRow][0] < 0.0
            y = Y[jRow] / M[jRow][0]
            IF bdgBox.min[iVar] < y
                bdgBox.min[iVar] = y
            END IF
        END IF
    END FOR
END FUNCTION

FUNCTION FMBTestIntersection3DTime(that, tho, bdgBox)
    Frame3DTimeImportFrame(that, tho, thoProj)
    M[0][0] = -thoProj.comp[0][0]
    M[0][1] = -thoProj.comp[1][0]
    M[0][2] = -thoProj.comp[2][0]
    M[0][3] = -thoProj.speed[0]
    Y[0] = thoProj.orig[0]
    IF (Y[0] < neg(M[0][0]) + neg(M[0][1]) + neg(M[0][2]) + neg(M[0][3]))
        RETURN FALSE
    END IF
    M[1][0] = -thoProj.comp[0][1]
    M[1][1] = -thoProj.comp[1][1]
    M[1][2] = -thoProj.comp[2][1]
    M[1][3] = -thoProj.speed[1]
    Y[1] = thoProj.orig[1]
    IF Y[1] < neg(M[1][0]) + neg(M[1][1]) + neg(M[1][2]) + neg(M[1][3])
        RETURN FALSE
    END IF
    M[2][0] = -thoProj.comp[0][2]

```

```

M[2][1] = -thoProj.comp[1][2]
M[2][2] = -thoProj.comp[2][2]
M[2][3] = -thoProj.speed[2]
Y[2] = thoProj.orig[2]
IF (Y[2] < neg(M[2][0]) + neg(M[2][1]) + neg(M[2][2]) + neg(M[2][3]))
  RETURN FALSE
nbRows = 3
IF that.type == FrameCuboid
  M[nbRows][0] = thoProj.comp[0][0]
  M[nbRows][1] = thoProj.comp[1][0]
  M[nbRows][2] = thoProj.comp[2][0]
  M[nbRows][3] = thoProj.speed[0]
  Y[nbRows] = 1.0 - thoProj.orig[0]
  IF Y[nbRows] < neg(M[nbRows][0]) + neg(M[nbRows][1]) +
    neg(M[nbRows][2]) + neg(M[nbRows][3])
    RETURN FALSE
  END IF
  nbRows = nbRows + 1
  M[nbRows][0] = thoProj.comp[0][1]
  M[nbRows][1] = thoProj.comp[1][1]
  M[nbRows][2] = thoProj.comp[2][1]
  M[nbRows][3] = thoProj.speed[1]
  Y[nbRows] = 1.0 - thoProj.orig[1]
  IF Y[nbRows] < neg(M[nbRows][0]) + neg(M[nbRows][1]) +
    neg(M[nbRows][2]) + neg(M[nbRows][3])
    RETURN FALSE
  END IF
  nbRows = nbRows + 1
  M[nbRows][0] = thoProj.comp[0][2]
  M[nbRows][1] = thoProj.comp[1][2]
  M[nbRows][2] = thoProj.comp[2][2]
  M[nbRows][3] = thoProj.speed[2]
  Y[nbRows] = 1.0 - thoProj.orig[2]
  IF Y[nbRows] < neg(M[nbRows][0]) + neg(M[nbRows][1]) +
    neg(M[nbRows][2]) + neg(M[nbRows][3])
    RETURN FALSE
  END IF
  nbRows = nbRows + 1
ELSE
  M[nbRows][0] =
    thoProj.comp[0][0] + thoProj.comp[0][1] + thoProj.comp[0][2]
  M[nbRows][1] =
    thoProj.comp[1][0] + thoProj.comp[1][1] + thoProj.comp[1][2]
  M[nbRows][2] =
    thoProj.comp[2][0] + thoProj.comp[2][1] + thoProj.comp[2][2]
  M[nbRows][3] = thoProj.speed[0] + thoProj.speed[1] + thoProj.speed[2]
  Y[nbRows] = 1.0 - thoProj.orig[0] - thoProj.orig[1] - thoProj.orig[2]
  IF Y[nbRows] < neg(M[nbRows][0]) + neg(M[nbRows][1]) +
    neg(M[nbRows][2]) + neg(M[nbRows][3])
    RETURN FALSE
  END IF
  nbRows = nbRows + 1
END IF
IF tho.type == FrameCuboid
  M[nbRows][0] = 1.0
  M[nbRows][1] = 0.0
  M[nbRows][2] = 0.0
  M[nbRows][3] = 0.0
  Y[nbRows] = 1.0
  nbRows = nbRows + 1
  M[nbRows][0] = 0.0
  M[nbRows][1] = 1.0

```



```

    M[nbRows][2] = 0.0
    M[nbRows][3] = 0.0
    Y[nbRows] = 1.0
    nbRows = nbRows + 1
    M[nbRows][0] = 0.0
    M[nbRows][1] = 0.0
    M[nbRows][2] = 1.0
    M[nbRows][3] = 0.0
    Y[nbRows] = 1.0
    nbRows = nbRows + 1
ELSE
    M[nbRows][0] = 1.0
    M[nbRows][1] = 1.0
    M[nbRows][2] = 1.0
    M[nbRows][3] = 0.0
    Y[nbRows] = 1.0
    nbRows = nbRows + 1
END IF
M[nbRows][0] = -1.0
M[nbRows][1] = 0.0
M[nbRows][2] = 0.0
M[nbRows][3] = 0.0
Y[nbRows] = 0.0
nbRows = nbRows + 1
M[nbRows][0] = 0.0
M[nbRows][1] = -1.0
M[nbRows][2] = 0.0
M[nbRows][3] = 0.0
Y[nbRows] = 0.0
nbRows = nbRows + 1
M[nbRows][0] = 0.0
M[nbRows][1] = 0.0
M[nbRows][2] = -1.0
M[nbRows][3] = 0.0
Y[nbRows] = 0.0
nbRows = nbRows + 1
M[nbRows][0] = 0.0
M[nbRows][1] = 0.0
M[nbRows][2] = 0.0
M[nbRows][3] = 1.0
Y[nbRows] = 1.0
nbRows = nbRows + 1
M[nbRows][0] = 0.0
M[nbRows][1] = 0.0
M[nbRows][2] = 0.0
M[nbRows][3] = -1.0
Y[nbRows] = 0.0
nbRows = nbRows + 1
inconsistency =
    ElimVar3DTime(FST_VAR, M, Y, nbRows, 4, Mp, Yp, nbRowsP)
IF inconsistency == TRUE
    RETURN FALSE
END IF
inconsistency =
    ElimVar3DTime(FST_VAR, Mp, Yp, nbRowsP, 3, Mpp, Ypp, nbRowsPP)
IF inconsistency == TRUE
    RETURN FALSE
END IF
inconsistency =
    ElimVar3DTime(FST_VAR, Mpp, Ypp, nbRowsPP, 2, Mppp, Yppp, nbRowsPPP)
IF inconsistency == TRUE
    RETURN FALSE

```

```

END IF
GetBound3DTime(FOR_VAR, Mppp, Yppp, nbRowsPPP, bdgBoxLocal)
IF bdgBoxLocal.min[FOR_VAR] >= bdgBoxLocal.max[FOR_VAR]
    RETURN FALSE
END IF
ElimVar3DTime(SND_VAR, Mpp, Ypp, nbRowsPP, 2, Mppp, Yppp, nbRowsPPP)
GetBound3DTime(THD_VAR, Mppp, Yppp, nbRowsPPP, bdgBoxLocal)
ElimVar3DTime(FOR_VAR, M, Y, nbRows, 4, Mp, Yp, nbRowsP)
ElimVar3DTime(THD_VAR, Mp, Yp, nbRowsP, 3, Mpp, Ypp, nbRowsPP)
ElimVar3DTime(SND_VAR, Mpp, Ypp, nbRowsPP, 2, Mppp, Yppp, nbRowsPPP)
GetBound3DTime(FST_VAR, Mppp, Yppp, nbRowsPPP, bdgBoxLocal)
ElimVar3DTime(FST_VAR, Mpp, Ypp, nbRowsPP, 2, Mppp, Yppp, nbRowsPPP)
GetBound3DTime(SND_VAR, Mppp, Yppp, nbRowsPPP, bdgBoxLocal)
bdgBox = bdgBoxLocal
RETURN TRUE
END FUNCTION

origP3DTime = [0.0, 0.0, 0.0]
speedP3DTime = [0.0, 0.0, 0.0]
compP3DTime = [
    [1.0, 0.0, 0.0],
    [0.0, 1.0, 0.0],
    [0.0, 0.0, 1.0]]
P3DTime =
    Frame3DTimeCreateStatic(
        FrameCuboid, origP3DTime, speedP3DTime, compP3DTime)
origQ3DTime = [0.0, 0.0, 0.0]
speedQ3DTime = [0.0, 0.0, 0.0]
compQ3DTime = [
    [1.0, 0.0, 0.0],
    [0.0, 1.0, 0.0],
    [0.0, 0.0, 1.0]]
Q3DTime =
    Frame3DTimeCreateStatic(
        FrameCuboid, origQ3DTime, speedQ3DTime, compQ3DTime)
isIntersecting3DTime =
    FMBTestIntersection3DTime(P3DTime, Q3DTime, bdgBox3DTimeLocal)
IF isIntersecting3DTime
    PRINT "Intersection detected."
    Frame3DTimeExportBdgBox(Q3DTime, bdgBox3DTimeLocal, bdgBox3DTime)
    AAB3DTimePrint(bdgBox3DTime)
ELSE
    PRINT "No intersection."
END IF

```

4 Implementation of the algorithms in C

In this section I introduce an implementation of the algorithms of the previous section in the C language.

4.1 Frames

4.1.1 Header

```

#ifndef __FRAME_H_
#define __FRAME_H_

```

```

// ----- Includes -----

#include <math.h>
#include <stdio.h>
#include <stdlib.h>

// ----- Macros -----

// ----- Enumerations -----

typedef enum {
    FrameCuboid,
    FrameTetrahedron
} FrameType;

// ----- Data structures -----

// Axis aligned bounding box structure
typedef struct {
    // x,y
    double min[2];
    double max[2];
} AABB2D;

typedef struct {
    // x,y,z
    double min[3];
    double max[3];
} AABB3D;

typedef struct {
    // x,y,t
    double min[3];
    double max[3];
} AABB2DTime;

typedef struct {
    // x,y,z,t
    double min[4];
    double max[4];
} AABB3DTime;

// Axis unaligned cuboid and tetrahedron structure
typedef struct {
    FrameType type;
    double orig[2];
    double comp[2][2];
    // AABB of the frame
    AABB2D bdgBox;
    // Inverted components used during computation
    double invComp[2][2];
} Frame2D;

typedef struct {
    FrameType type;
    double orig[3];
    double comp[3][3];
    // AABB of the frame
    AABB3D bdgBox;
    // Inverted components used during computation
    double invComp[3][3];
}

```

```

} Frame3D;

typedef struct {
    FrameType type;
    double orig[2];
    double comp[2][2];
    // AABB of the frame
    AABB2DTime bdgBox;
    // Inverted components used during computation
    double invComp[2][2];
    double speed[2];
} Frame2DTime;

typedef struct {
    FrameType type;
    double orig[3];
    double comp[3][3];
    // AABB of the frame
    AABB3DTime bdgBox;
    // Inverted components used during computation
    double invComp[3][3];
    double speed[3];
} Frame3DTime;

// ----- Functions declaration -----

// Print the AABB 'that' on stdout
// Output format is
// (min[0], min[1], min[2], min[3])-(max[0], max[1], max[2], max[3])
void AABB2DPrint(const AABB2D* const that);
void AABB3DPrint(const AABB3D* const that);
void AABB2DTimePrint(const AABB2DTime* const that);
void AABB3DTimePrint(const AABB3DTime* const that);

// Print the Frame 'that' on stdout
// Output format is
// (orig[0], orig[1], orig[2])
// (comp[0][0], comp[0][1], comp[0][2])
// (comp[1][0], comp[1][1], comp[1][2])
// (comp[2][0], comp[2][1], comp[2][2])
// (speed[0], speed[1], speed[2])
void Frame2DPrint(const Frame2D* const that);
void Frame3DPrint(const Frame3D* const that);
void Frame2DTimePrint(const Frame2DTime* const that);
void Frame3DTimePrint(const Frame3DTime* const that);

// Create a static Frame structure of FrameType 'type',
// at position 'orig' with components 'comp' ([iComp][iAxis])
Frame2D Frame2DCreateStatic(
    const FrameType type,
    const double orig[2],
    const double comp[2][2]);
Frame3D Frame3DCreateStatic(
    const FrameType type,
    const double orig[3],
    const double comp[3][3]);
Frame2DTime Frame2DTimeCreateStatic(
    const FrameType type,
    const double orig[2],
    const double speed[2],
    const double comp[2][2]);
Frame3DTime Frame3DTimeCreateStatic(

```

```

    const FrameType type,
        const double orig[3],
        const double speed[3],
        const double comp[3][3]);

// Project the Frame 'Q' in the Frame 'P' 's coordinates system and
// memorize the result in the Frame 'Qp'
void Frame2DImportFrame(
    const Frame2D* const P,
    const Frame2D* const Q,
    Frame2D* const Qp);
void Frame3DImportFrame(
    const Frame3D* const P,
    const Frame3D* const Q,
    Frame3D* const Qp);
void Frame2DTimeImportFrame(
    const Frame2DTime* const P,
    const Frame2DTime* const Q,
    Frame2DTime* const Qp);
void Frame3DTimeImportFrame(
    const Frame3DTime* const P,
    const Frame3DTime* const Q,
    Frame3DTime* const Qp);

// Export the ABB 'bdgBox' from 'that' 's coordinates system to
// the real coordinates system and update 'bdgBox' with the resulting
// ABB
void Frame2DExportBdgBox(
    const Frame2D* const that,
    const ABB2D* const bdgBox,
    ABB2D* const bdgBoxProj);
void Frame3DExportBdgBox(
    const Frame3D* const that,
    const ABB3D* const bdgBox,
    ABB3D* const bdgBoxProj);
void Frame2DTimeExportBdgBox(
    const Frame2DTime* const that,
    const ABB2DTime* const bdgBox,
    ABB2DTime* const bdgBoxProj);
void Frame3DTimeExportBdgBox(
    const Frame3DTime* const that,
    const ABB3DTime* const bdgBox,
    ABB3DTime* const bdgBoxProj);

// Power function for integer base and exponent
// Return 'base' ^ 'exp'
int powi(
    int base,
    unsigned int exp);

#endif

```

4.1.2 Body

```

#include "frame.h"

// ----- Macros -----

#define EPSILON 0.0000001

// ----- Functions declaration -----

```

```

// Update the inverse components of the Frame 'that'
void Frame2DUpdateInv(Frame2D* const that);
void Frame3DUpdateInv(Frame3D* const that);
void Frame2DTimeUpdateInv(Frame2DTime* const that);
void Frame3DTimeUpdateInv(Frame3DTime* const that);

// ----- Functions implementation -----

// Create a static Frame structure of FrameType 'type',
// at position 'orig' with components 'comp'
// arrangement is comp[iComp][iAxis]
Frame2D Frame2DCreateStatic(
    const FrameType type,
    const double orig[2],
    const double comp[2][2]) {

    // Create the new Frame
    Frame2D that;
    that.type = type;
    for (int iAxis = 2;
        iAxis--;) {

        that.orig[iAxis] = orig[iAxis];

        for (int iComp = 2;
            iComp--;) {

            that.comp[iComp][iAxis] = comp[iComp][iAxis];

        }

    }

    // Create the bounding box
    for (int iAxis = 2;
        iAxis--;) {

        double min = orig[iAxis];
        double max = orig[iAxis];

        for (int iComp = 2;
            iComp--;) {

            if (that.type == FrameCuboid) {

                if (that.comp[iComp][iAxis] < 0.0) {

                    min += that.comp[iComp][iAxis];

                }

                if (that.comp[iComp][iAxis] > 0.0) {

                    max += that.comp[iComp][iAxis];

                }

            } else if (that.type == FrameTetrahedron) {

                if (that.comp[iComp][iAxis] < 0.0 &&
                    min > orig[iAxis] + that.comp[iComp][iAxis]) {


```

```

        min = orig[iAxis] + that.comp[iComp][iAxis];
    }

    if (that.comp[iComp][iAxis] > 0.0 &&
        max < orig[iAxis] + that.comp[iComp][iAxis]) {

        max = orig[iAxis] + that.comp[iComp][iAxis];
    }

}

}

that.bdgBox.min[iAxis] = min;
that.bdgBox.max[iAxis] = max;
}

// Calculate the inverse matrix
Frame2DUpdateInv(&that);

// Return the new Frame
return that;
}

Frame3D Frame3DCreateStatic(
    const FrameType type,
    const double orig[3],
    const double comp[3][3]) {

    // Create the new Frame
    Frame3D that;
    that.type = type;
    for (int iAxis = 3;
        iAxis--;) {

        that.orig[iAxis] = orig[iAxis];

        for (int iComp = 3;
            iComp--;) {

            that.comp[iComp][iAxis] = comp[iComp][iAxis];
        }
    }

    // Create the bounding box
    for (int iAxis = 3;
        iAxis--;) {

        double min = orig[iAxis];
        double max = orig[iAxis];

        for (int iComp = 3;
            iComp--;) {

```

```

        if (that.type == FrameCuboid) {

            if (that.comp[iComp][iAxis] < 0.0) {

                min += that.comp[iComp][iAxis];

            }

            if (that.comp[iComp][iAxis] > 0.0) {

                max += that.comp[iComp][iAxis];

            }

        } else if (that.type == FrameTetrahedron) {

            if (that.comp[iComp][iAxis] < 0.0 &&
                min > orig[iAxis] + that.comp[iComp][iAxis]) {

                min = orig[iAxis] + that.comp[iComp][iAxis];

            }

            if (that.comp[iComp][iAxis] > 0.0 &&
                max < orig[iAxis] + that.comp[iComp][iAxis]) {

                max = orig[iAxis] + that.comp[iComp][iAxis];

            }

        }

    }

    that.bdgBox.min[iAxis] = min;
    that.bdgBox.max[iAxis] = max;

}

// Calculate the inverse matrix
Frame3DUpdateInv(&that);

// Return the new Frame
return that;

}

Frame2DTime Frame2DTimeCreateStatic(
    const FrameType type,
    const double orig[2],
    const double speed[2],
    const double comp[2][2]) {

    // Create the new Frame
    Frame2DTime that;
    that.type = type;
    for (int iAxis = 2;
        iAxis--;) {

        that.orig[iAxis] = orig[iAxis];
        that.speed[iAxis] = speed[iAxis];
    }
}

```



```

    for (int iComp = 2;
        iComp--;) {

        that.comp[iComp][iAxis] = comp[iComp][iAxis];

    }
}

// Create the bounding box
for (int iAxis = 2;
    iAxis--;) {

    double min = orig[iAxis];
    double max = orig[iAxis];

    for (int iComp = 2;
        iComp--;) {

        if (that.type == FrameCuboid) {

            if (that.comp[iComp][iAxis] < 0.0) {

                min += that.comp[iComp][iAxis];

            }

            if (that.comp[iComp][iAxis] > 0.0) {

                max += that.comp[iComp][iAxis];

            }

        } else if (that.type == FrameTetrahedron) {

            if (that.comp[iComp][iAxis] < 0.0 &&
                min > orig[iAxis] + that.comp[iComp][iAxis]) {

                min = orig[iAxis] + that.comp[iComp][iAxis];

            }

            if (that.comp[iComp][iAxis] > 0.0 &&
                max < orig[iAxis] + that.comp[iComp][iAxis]) {

                max = orig[iAxis] + that.comp[iComp][iAxis];

            }

        }

    }

    if (that.speed[iAxis] < 0.0) {

        min += that.speed[iAxis];

    }

    if (that.speed[iAxis] > 0.0) {

```

```

        max += that.speed[iAxis];

    }

    that.bdgBox.min[iAxis] = min;
    that.bdgBox.max[iAxis] = max;

}

that.bdgBox.min[2] = 0.0;
that.bdgBox.max[2] = 1.0;

// Calculate the inverse matrix
Frame2DTimeUpdateInv(&that);

// Return the new Frame
return that;

}

Frame3DTime Frame3DTimeCreateStatic(
    const FrameType type,
    const double orig[3],
    const double speed[3],
    const double comp[3][3]) {

    // Create the new Frame
    Frame3DTime that;
    that.type = type;
    for (int iAxis = 3;
        iAxis--;) {

        that.orig[iAxis] = orig[iAxis];
        that.speed[iAxis] = speed[iAxis];

        for (int iComp = 3;
            iComp--;) {

            that.comp[iComp][iAxis] = comp[iComp][iAxis];

        }

    }

}

// Create the bounding box
for (int iAxis = 3;
    iAxis--;) {

    double min = orig[iAxis];
    double max = orig[iAxis];

    for (int iComp = 3;
        iComp--;) {

        if (that.type == FrameCuboid) {

            if (that.comp[iComp][iAxis] < 0.0) {

                min += that.comp[iComp][iAxis];

            }

        }

    }

}

```

```

        if (that.comp[iComp][iAxis] > 0.0) {
            max += that.comp[iComp][iAxis];
        }
    } else if (that.type == FrameTetrahedron) {
        if (that.comp[iComp][iAxis] < 0.0 &&
            min > orig[iAxis] + that.comp[iComp][iAxis]) {
            min = orig[iAxis] + that.comp[iComp][iAxis];
        }
        if (that.comp[iComp][iAxis] > 0.0 &&
            max < orig[iAxis] + that.comp[iComp][iAxis]) {
            max = orig[iAxis] + that.comp[iComp][iAxis];
        }
    }
}

if (that.speed[iAxis] < 0.0) {
    min += that.speed[iAxis];
}

if (that.speed[iAxis] > 0.0) {
    max += that.speed[iAxis];
}

that.bdgBox.min[iAxis] = min;
that.bdgBox.max[iAxis] = max;
}

that.bdgBox.min[3] = 0.0;
that.bdgBox.max[3] = 1.0;

// Calculate the inverse matrix
Frame3DTimeUpdateInv(&that);

// Return the new Frame
return that;
}

// Update the inverse components of the Frame 'that'
void Frame2DUpdateInv(Frame2D* const that) {

    // Shortcuts
    double (*tc)[2] = that->comp;
    double (*tic)[2] = that->invComp;

```

```

double det = tc[0][0] * tc[1][1] - tc[1][0] * tc[0][1];
if (fabs(det) < EPSILON) {
    fprintf(stderr,
        "FrameUpdateInv: det == 0.0\n");
    exit(1);
}

tic[0][0] = tc[1][1] / det;
tic[0][1] = -tc[0][1] / det;
tic[1][0] = -tc[1][0] / det;
tic[1][1] = tc[0][0] / det;
}

void Frame3DUpdateInv(Frame3D* const that) {

    // Shortcuts
    double (*tc)[3] = that->comp;
    double (*tic)[3] = that->invComp;

    // Update the inverse components
    double det =
        tc[0][0] * (tc[1][1] * tc[2][2] - tc[1][2] * tc[2][1]) -
        tc[1][0] * (tc[0][1] * tc[2][2] - tc[0][2] * tc[2][1]) +
        tc[2][0] * (tc[0][1] * tc[1][2] - tc[0][2] * tc[1][1]);
    if (fabs(det) < EPSILON) {
        fprintf(stderr,
            "FrameUpdateInv: det == 0.0\n");
        exit(1);
    }

    tic[0][0] = (tc[1][1] * tc[2][2] - tc[2][1] * tc[1][2]) / det;
    tic[0][1] = (tc[2][1] * tc[0][2] - tc[2][2] * tc[0][1]) / det;
    tic[0][2] = (tc[0][1] * tc[1][2] - tc[0][2] * tc[1][1]) / det;
    tic[1][0] = (tc[2][0] * tc[1][2] - tc[2][2] * tc[1][0]) / det;
    tic[1][1] = (tc[0][0] * tc[2][2] - tc[2][0] * tc[0][2]) / det;
    tic[1][2] = (tc[0][0] * tc[1][2] - tc[1][0] * tc[0][0]) / det;
    tic[2][0] = (tc[1][0] * tc[2][1] - tc[2][0] * tc[1][1]) / det;
    tic[2][1] = (tc[0][1] * tc[2][0] - tc[2][1] * tc[0][0]) / det;
    tic[2][2] = (tc[0][0] * tc[1][1] - tc[1][0] * tc[0][1]) / det;
}

// Update the inverse components of the Frame 'that'
void Frame2DTimeUpdateInv(Frame2DTime* const that) {

    // Shortcuts
    double (*tc)[2] = that->comp;
    double (*tic)[2] = that->invComp;

    double det = tc[0][0] * tc[1][1] - tc[1][0] * tc[0][1];
    if (fabs(det) < EPSILON) {
        fprintf(stderr,
            "FrameUpdateInv: det == 0.0\n");
        exit(1);
    }

    tic[0][0] = tc[1][1] / det;
    tic[0][1] = -tc[0][1] / det;
    tic[1][0] = -tc[1][0] / det;
    tic[1][1] = tc[0][0] / det;
}

```

```

}

void Frame3DTimeUpdateInv(Frame3DTime* const that) {

    // Shortcuts
    double (*tc)[3] = that->comp;
    double (*tic)[3] = that->invComp;

    // Update the inverse components
    double det =
        tc[0][0] * (tc[1][1] * tc[2][2] - tc[1][2] * tc[2][1]) -
        tc[1][0] * (tc[0][1] * tc[2][2] - tc[0][2] * tc[2][1]) +
        tc[2][0] * (tc[0][1] * tc[1][2] - tc[0][2] * tc[1][1]);
    if (fabs(det) < EPSILON) {
        fprintf(stderr,
            "FrameUpdateInv: det == 0.0\n");
        exit(1);
    }

    tic[0][0] = (tc[1][1] * tc[2][2] - tc[2][1] * tc[1][2]) / det;
    tic[0][1] = (tc[2][1] * tc[0][2] - tc[2][2] * tc[0][1]) / det;
    tic[0][2] = (tc[0][1] * tc[1][2] - tc[0][2] * tc[1][1]) / det;
    tic[1][0] = (tc[2][0] * tc[1][2] - tc[2][2] * tc[1][0]) / det;
    tic[1][1] = (tc[0][0] * tc[2][2] - tc[2][0] * tc[0][2]) / det;
    tic[1][2] = (tc[0][2] * tc[1][0] - tc[1][2] * tc[0][0]) / det;
    tic[2][0] = (tc[1][0] * tc[2][1] - tc[2][0] * tc[1][1]) / det;
    tic[2][1] = (tc[0][1] * tc[2][0] - tc[2][1] * tc[0][0]) / det;
    tic[2][2] = (tc[0][0] * tc[1][1] - tc[1][0] * tc[0][1]) / det;

}

// Project the Frame 'Q' in the Frame 'P' 's coordinates system and
// memorize the result in the Frame 'Qp'
void Frame2DImportFrame(
    const Frame2D* const P,
    const Frame2D* const Q,
    Frame2D* const Qp) {

    // Shortcuts
    const double* qo = Q->orig;
    double* qpo = Qp->orig;
    const double* po = P->orig;

    const double (*pi)[2] = P->invComp;
    double (*qpc)[2] = Qp->comp;
    const double (*qc)[2] = Q->comp;

    // Calculate the projection
    double v[2];
    for (int i = 2;
        i--;) {

        v[i] = qo[i] - po[i];

    }

    for (int i = 2;
        i--;) {

        qpo[i] = 0.0;

        for (int j = 2;

```

```

        j--;) {

        qpo[i] += pi[j][i] * v[j];
        qpc[j][i] = 0.0;

        for (int k = 2;
              k--;) {

            qpc[j][i] += pi[k][i] * qc[j][k];

        }
    }
}

void Frame3DImportFrame(
    const Frame3D* const P,
    const Frame3D* const Q,
    Frame3D* const Qp) {

    // Shortcuts
    const double* qo = Q->orig;
    double* qpo = Qp->orig;
    const double* po = P->orig;

    const double (*pi)[3] = P->invComp;
    double (*qpc)[3] = Qp->comp;
    const double (*qc)[3] = Q->comp;

    // Calculate the projection
    double v[3];
    for (int i = 3;
         i--;) {

        v[i] = qo[i] - po[i];

    }

    for (int i = 3;
         i--;) {

        qpo[i] = 0.0;

        for (int j = 3;
              j--;) {

            qpo[i] += pi[j][i] * v[j];
            qpc[j][i] = 0.0;

            for (int k = 3;
                  k--;) {

                qpc[j][i] += pi[k][i] * qc[j][k];

            }
        }
    }
}

void Frame2DTimeImportFrame(
    const Frame2DTime* const P,
    const Frame2DTime* const Q,

```

```

        Frame3DTime* const Qp) {

// Shortcuts
const double* qo = Q->orig;
        double* qpo = Qp->orig;
const double* po = P->orig;

const double* qs = Q->speed;
        double* qps = Qp->speed;
const double* ps = P->speed;

const double (*pi)[2] = P->invComp;
        double (*qpc)[2] = Qp->comp;
const double (*qc)[2] = Q->comp;

// Calculate the projection
double v[2];
double s[2];
for (int i = 2;
    i--;) {

    v[i] = qo[i] - po[i];
    s[i] = qs[i] - ps[i];

}

for (int i = 2;
    i--;) {

    qpo[i] = 0.0;
    qps[i] = 0.0;

    for (int j = 2;
        j--;) {

        qpo[i] += pi[j][i] * v[j];
        qps[i] += pi[j][i] * s[j];
        qpc[j][i] = 0.0;

        for (int k = 2;
            k--;) {

            qpc[j][i] += pi[k][i] * qc[j][k];

        }

    }

}

}

void Frame3DTimeImportFrame(
    const Frame3DTime* const P,
    const Frame3DTime* const Q,
    Frame3DTime* const Qp) {

// Shortcuts
const double* qo = Q->orig;
        double* qpo = Qp->orig;
const double* po = P->orig;

const double* qs = Q->speed;
        double* qps = Qp->speed;
const double* ps = P->speed;

```

```

const double (*pi)[3] = P->invComp;
double (*qpc)[3] = Qp->comp;
const double (*qc)[3] = Q->comp;

// Calculate the projection
double v[3];
double s[3];
for (int i = 3;
    i--;) {

    v[i] = qo[i] - po[i];
    s[i] = qs[i] - ps[i];

}

for (int i = 3;
    i--;) {

    qpo[i] = 0.0;
    qps[i] = 0.0;

    for (int j = 3;
        j--;) {

        qpo[i] += pi[j][i] * v[j];
        qps[i] += pi[j][i] * s[j];
        qpc[j][i] = 0.0;

        for (int k = 3;
            k--;) {

            qpc[j][i] += pi[k][i] * qc[j][k];

        }
    }
}

// Export the AABB 'bdgBox' from 'that' 's coordinates system to
// the real coordinates system and update 'bdgBox' with the resulting
// AABB
void Frame2DExportBdgBox(
    const Frame2D* const that,
    const AABB2D* const bdgBox,
    AABB2D* const bdgBoxProj) {

    // Shortcuts
    const double* to = that->orig;
    const double* bbmi = bdgBox->min;
    const double* bbma = bdgBox->max;
    double* bbpmi = bdgBoxProj->min;
    double* bbpma = bdgBoxProj->max;

    const double (*tc)[2] = that->comp;

    // Initialise the coordinates of the result AABB with the projection
    // of the first corner of the AABB in argument
    for (int i = 2;
        i--;) {

        bbpma[i] = to[i];

```



```

    for (int j = 2;
        j--;) {

        bbpma[i] += tc[j][i] * bbmi[j];

    }

    bbpmi[i] = bbpma[i];
}

// Loop on vertices of the AABB
// skip the first vertex which is the origin already computed above
int nbVertices = powi(2, 2);
for (int iVertex = nbVertices;
    iVertex-- && iVertex;) {

    // Declare a variable to memorize the coordinates of the vertex in
    // 'that' 's coordinates system
    double v[2];

    // Calculate the coordinates of the vertex in
    // 'that' 's coordinates system
    for (int i = 2;
        i--;) {

        v[i] = ((iVertex & (1 << i)) ? bbma[i] : bbmi[i]);

    }

    // Declare a variable to memorize the projected coordinates
    // in real coordinates system
    double w[2];

    // Project the vertex to real coordinates system
    for (int i = 2;
        i--;) {

        w[i] = to[i];

        for (int j = 2;
            j--;) {

            w[i] += tc[j][i] * v[j];

        }

    }

    // Update the coordinates of the result AABB
    for (int i = 2;
        i--;) {

        if (bbpmi[i] > w[i]) {

            bbpmi[i] = w[i];

        }

        if (bbpma[i] < w[i]) {

            bbpma[i] = w[i];

        }

    }
}

```

```

    }
  }
}

}

void Frame3DExportBdgBox(
  const Frame3D* const that,
  const AABB3D* const bdgBox,
  AABB3D* const bdgBoxProj) {

  // Shortcuts
  const double* to      = that->orig;
  const double* bbmi    = bdgBox->min;
  const double* bbma    = bdgBox->max;
  double* bbpmi = bdgBoxProj->min;
  double* bbpma = bdgBoxProj->max;

  const double (*tc)[3] = that->comp;

  // Initialise the coordinates of the result AABB with the projection
  // of the first corner of the AABB in argument
  for (int i = 3;
       i--;) {

    bbpma[i] = to[i];

    for (int j = 3;
         j--;) {

      bbpma[i] += tc[j][i] * bbmi[j];

    }

    bbpmi[i] = bbpma[i];
  }

  // Loop on vertices of the AABB
  // skip the first vertex which is the origin already computed above
  int nbVertices = powi(2, 3);
  for (int iVertex = nbVertices;
       iVertex-- && iVertex;) {

    // Declare a variable to memorize the coordinates of the vertex in
    // 'that' 's coordinates system
    double v[3];

    // Calculate the coordinates of the vertex in
    // 'that' 's coordinates system
    for (int i = 3;
         i--;) {

      v[i] = ((iVertex & (1 << i)) ? bbma[i] : bbmi[i]);

    }

    // Declare a variable to memorize the projected coordinates
    // in real coordinates system
    double w[3];

    // Project the vertex to real coordinates system

```

```

    for (int i = 3;
        i--;) {

        w[i] = to[i];

        for (int j = 3;
            j--;) {

            w[i] += tc[j][i] * v[j];

        }
    }

    // Update the coordinates of the result AABB
    for (int i = 3;
        i--;) {

        if (bbpma[i] > w[i]) {

            bbpma[i] = w[i];

        }
        if (bbpma[i] < w[i]) {

            bbpma[i] = w[i];

        }
    }
}

void Frame2DTimeExportBdgBox(
    const Frame2DTime* const that,
    const AABB2DTime* const bdgBox,
    AABB2DTime* const bdgBoxProj) {

    // Shortcuts
    const double* to = that->orig;
    const double* ts = that->speed;
    const double* bbmi = bdgBox->min;
    const double* bbma = bdgBox->max;
    double* bbpma = bdgBoxProj->min;
    double* bbpma = bdgBoxProj->max;
    const double (*tc)[2] = that->comp;

    // The time component is not affected
    bbpma[2] = bbmi[2];
    bbpma[2] = bbma[2];

    // Initialise the coordinates of the result AABB with the projection
    // of the first corner of the AABB in argument
    for (int i = 2;
        i--;) {

        bbpma[i] = to[i] + ts[i] * bbmi[2];

        for (int j = 2;
            j--;) {

            bbpma[i] += tc[j][i] * bbmi[j];

```

```

    }

    bbpma[i] = bbpma[i];
}

// Loop on vertices of the AABB
// skip the first vertex which is the origin already computed above
int nbVertices = powi(2, 2);
for (int iVertex = nbVertices;
     iVertex-- && iVertex;) {

    // Declare a variable to memorize the coordinates of the vertex in
    // 'that' 's coordinates system
    double v[2];

    // Calculate the coordinates of the vertex in
    // 'that' 's coordinates system
    for (int i = 2;
         i--;) {

        v[i] = ((iVertex & (1 << i)) ? bbma[i] : bbmi[i]);

    }

    // Declare a variable to memorize the projected coordinates
    // in real coordinates system
    double w[2];

    // Project the vertex to real coordinates system
    for (int i = 2;
         i--;) {

        w[i] = to[i];

        for (int j = 2;
             j--;) {

            w[i] += tc[j][i] * v[j];

        }

    }

    // Update the coordinates of the result AABB
    for (int i = 2;
         i--;) {

        if (bbpma[i] > w[i] + ts[i] * bbmi[2]) {

            bbpma[i] = w[i] + ts[i] * bbmi[2];

        }

        if (bbpma[i] > w[i] + ts[i] * bbma[2]) {

            bbpma[i] = w[i] + ts[i] * bbma[2];

        }

        if (bbpma[i] < w[i] + ts[i] * bbmi[2]) {

            bbpma[i] = w[i] + ts[i] * bbmi[2];

        }

    }
}

```

```

        if (bbpma[i] < w[i] + ts[i] * bbma[2]) {
            bbpma[i] = w[i] + ts[i] * bbma[2];
        }
    }
}

void Frame3DTimeExportBdgBox(
    const Frame3DTime* const that,
    const AABB3DTime* const bdgBox,
    AABB3DTime* const bdgBoxProj) {

    // Shortcuts
    const double* to      = that->orig;
    const double* ts      = that->speed;
    const double* bbmi    = bdgBox->min;
    const double* bbma    = bdgBox->max;
    double* bbpmi = bdgBoxProj->min;
    double* bbpma = bdgBoxProj->max;
    const double (*tc)[3] = that->comp;

    // The time component is not affected
    bbpmi[3] = bbmi[3];
    bbpma[3] = bbma[3];

    // Initialise the coordinates of the result AABB with the projection
    // of the first corner of the AABB in argument
    for (int i = 3;
        i--;) {

        bbpma[i] = to[i] + ts[i] * bbmi[3];

        for (int j = 3;
            j--;) {

            bbpma[i] += tc[j][i] * bbmi[j];

        }

        bbpmi[i] = bbpma[i];
    }

    // Loop on vertices of the AABB
    // skip the first vertex which is the origin already computed above
    int nbVertices = powi(2, 3);
    for (int iVertex = nbVertices;
        iVertex-- && iVertex;) {

        // Declare a variable to memorize the coordinates of the vertex in
        // 'that' 's coordinates system
        double v[3];

        // Calculate the coordinates of the vertex in
        // 'that' 's coordinates system
        for (int i = 3;
            i--;) {

            v[i] = ((iVertex & (1 << i)) ? bbma[i] : bbmi[i]);

```

```

    }

    // Declare a variable to memorize the projected coordinates
    // in real coordinates system
    double w[3];

    // Project the vertex to real coordinates system
    for (int i = 3;
        i--;) {

        w[i] = to[i];

        for (int j = 3;
            j--;) {

            w[i] += tc[j][i] * v[j];

        }
    }

    // Update the coordinates of the result AABB
    for (int i = 3;
        i--;) {

        if (bbpmi[i] > w[i] + ts[i] * bbmi[3]) {

            bbpmi[i] = w[i] + ts[i] * bbmi[3];

        }
        if (bbpmi[i] > w[i] + ts[i] * bbma[3]) {

            bbpmi[i] = w[i] + ts[i] * bbma[3];

        }
        if (bbpma[i] < w[i] + ts[i] * bbmi[3]) {

            bbpma[i] = w[i] + ts[i] * bbmi[3];

        }
        if (bbpma[i] < w[i] + ts[i] * bbma[3]) {

            bbpma[i] = w[i] + ts[i] * bbma[3];

        }
    }
}

}

// Print the AABB 'that' on stdout
// Output format is (min[0], min[1], ...)-(max[0], max[1], ...)
void AABB2DPrint(const AABB2D* const that) {

    printf("minXY(");
    for (int i = 0;
        i < 2;
        ++i) {

        printf("%f", that->min[i]);
        if (i < 1)
            printf(",");
    }
}

```

```

    }
    printf(")-maxXY(");
    for (int i = 0;
        i < 2;
        ++i) {

        printf("%f", that->max[i]);
        if (i < 1)
            printf(",");

    }
    printf(")");
}

void AABBB3DPrint(const AABBB3D* const that) {

    printf("minXYZ(");
    for (int i = 0;
        i < 3;
        ++i) {

        printf("%f", that->min[i]);
        if (i < 2)
            printf(",");

    }
    printf(")-maxXYZ(");
    for (int i = 0;
        i < 3;
        ++i) {

        printf("%f", that->max[i]);
        if (i < 2)
            printf(",");

    }
    printf(")");
}

void AABBB2DTimePrint(const AABBB2DTime* const that) {

    printf("minXYT(");
    for (int i = 0;
        i < 3;
        ++i) {

        printf("%f", that->min[i]);
        if (i < 2)
            printf(",");

    }
    printf(")-maxXYT(");
    for (int i = 0;
        i < 3;
        ++i) {

        printf("%f", that->max[i]);
        if (i < 2)
            printf(",");

    }

```

```

    }
    printf(")");
}

void AAB3DTimePrint(const AAB3DTime* const that) {

    printf("minXYZT(");
    for (int i = 0;
         i < 4;
         ++i) {

        printf("%f", that->min[i]);
        if (i < 3)
            printf(",");

    }
    printf(")-maxXYZT(");
    for (int i = 0;
         i < 4;
         ++i) {

        printf("%f", that->max[i]);
        if (i < 3)
            printf(",");

    }
    printf(")");
}

// Print the Frame 'that' on stdout
// Output format is (orig[0], orig[1], orig[2])
// (comp[0][0], comp[0][1], comp[0][2])
// (comp[1][0], comp[1][1], comp[1][2])
// (comp[2][0], comp[2][1], comp[2][2])
void Frame2DPrint(const Frame2D* const that) {
    if (that->type == FrameTetrahedron) {
        printf("T");
    } else if (that->type == FrameCuboid) {
        printf("C");
    }
    printf("o(");
    for (int i = 0;
         i < 2;
         ++i) {

        printf("%f", that->orig[i]);
        if (i < 1)
            printf(",");

    }
    char comp[2] = {'x', 'y'};
    for (int j = 0;
         j < 2;
         ++j) {
        printf(") %c(", comp[j]);
        for (int i = 0;
             i < 2;
             ++i) {

```



```

        printf("%f", that->comp[j][i]);
        if (i < 1)
            printf(",");
    }
}
printf(")");
}

void Frame3DPrint(const Frame3D* const that) {
    if (that->type == FrameTetrahedron) {
        printf("T");
    } else if (that->type == FrameCuboid) {
        printf("C");
    }
    printf("o(");
    for (int i = 0;
         i < 3;
         ++i) {

        printf("%f", that->orig[i]);
        if (i < 2)
            printf(",");

    }
    char comp[3] = {'x', 'y', 'z'};
    for (int j = 0;
         j < 3;
         ++j) {
        printf(") %c(", comp[j]);
        for (int i = 0;
             i < 3;
             ++i) {

            printf("%f", that->comp[j][i]);
            if (i < 2)
                printf(",");

        }
    }
    printf(")");
}

void Frame2DTimePrint(const Frame2DTime* const that) {
    if (that->type == FrameTetrahedron) {
        printf("T");
    } else if (that->type == FrameCuboid) {
        printf("C");
    }
    printf("o(");
    for (int i = 0;
         i < 2;
         ++i) {

        printf("%f", that->orig[i]);
        if (i < 1)
            printf(",");

    }
    printf(") s(");
}

```

```

for (int i = 0;
    i < 2;
    ++i) {

    printf("%f", that->speed[i]);
    if (i < 1)
        printf(",");

}
char comp[2] = {'x', 'y'};
for (int j = 0;
    j < 2;
    ++j) {
    printf(") %c(", comp[j]);
    for (int i = 0;
        i < 2;
        ++i) {

        printf("%f", that->comp[j][i]);
        if (i < 1)
            printf(",");

    }
}
printf(")");
}

void Frame3DTimePrint(const Frame3DTime* const that) {
    if (that->type == FrameTetrahedron) {
        printf("T");
    } else if (that->type == FrameCuboid) {
        printf("C");
    }
    printf("o(");
    for (int i = 0;
        i < 3;
        ++i) {

        printf("%f", that->orig[i]);
        if (i < 2)
            printf(",");

    }
    printf(") s(");
    for (int i = 0;
        i < 3;
        ++i) {

        printf("%f", that->speed[i]);
        if (i < 2)
            printf(",");

    }
    char comp[3] = {'x', 'y', 'z'};
    for (int j = 0;
        j < 3;
        ++j) {
        printf(") %c(", comp[j]);
        for (int i = 0;
            i < 3;
            ++i) {

```

```

        printf("%f", that->comp[j][i]);
        if (i < 2)
            printf(",");
    }
}
printf(")");
}

// Power function for integer base and exponent
// Return 'base' ^ 'exp'
int powi(
    int base,
    unsigned int exp) {

    int res = 1;
    for (;
        exp;
        --exp) {

        res *= base;

    }
    return res;
}

```

4.2 FMB

4.2.1 2D static

Header

```

#ifndef __FMB2D_H_
#define __FMB2D_H_

#include <stdbool.h>
#include "frame.h"

// ----- Functions declaration -----

// Test for intersection between Frame 'that' and Frame 'tho'
// Return true if the two Frames are intersecting, else false
// If the Frame are intersecting the AABB of the intersection
// is stored into 'bdgBox', else 'bdgBox' is not modified
// If 'bdgBox' is null, the result AABB is not memorized (to use if
// unnecessary and want to speed up the algorithm)
// The resulting AABB may be larger than the smallest possible AABB
// The resulting AABB of FMBTestIntersection(A,B) may be different
// of the resulting AABB of FMBTestIntersection(B,A)
// The resulting AABB is given in 'tho' 's local coordinates system
bool FMBTestIntersection2D(
    const Frame2D* const that,
    const Frame2D* const tho,
    AABB2D* const bdgBox);

#endif

```

Body

```

#include "fmb2d.h"

// ----- Macros -----

// Return 1.0 if v is positive, -1.0 if v is negative, 0.0 else
#define sgn(v) (((0.0 < (v)) ? 1 : 0) - (((v) < 0.0) ? 1 : 0))

// Return x if x is negative, 0.0 else
#define neg(x) (x < 0.0 ? x : 0.0)

#define FST_VAR 0
#define SND_VAR 1

#define EPSILON 0.0000001

// ----- Functions declaration -----

// Eliminate the 'iVar'-th variable in the system 'M'.X<='Y'
// using the Fourier-Motzkin method and return
// the resulting system in 'Mp' and 'Yp', and the number of rows of
// the resulting system in 'nbRemainRows'
// Return false if the system becomes inconsistent during elimination,
// else return true
bool ElimVar2D(
    const int iVar,
    const double (*M)[2],
    const double* Y,
    const int nbRows,
    const int nbCols,
    double (*Mp)[2],
    double* Yp,
    int* const nbRemainRows);

// Get the bounds of the 'iVar'-th variable in the 'nbRows' rows
// system 'M'.X<='Y' and store them in the 'iVar'-th axis of the
// AABB 'bdgBox'
// ('M' arrangement is [iRow][iCol])
// The system is supposed to have been reduced to only one variable
// per row, the one in argument, which can be located in a different
// column than 'iVar'
// May return inconsistent values (max < min), which would
// mean the system has no solution
void GetBound2D(
    const int iVar,
    const double (*M)[2],
    const double* Y,
    const int nbRows,
    AABB2D* const bdgBox);

// ----- Functions implementation -----

// Eliminate the 'iVar'-th variable in the system 'M'.X<='Y'
// using the Fourier-Motzkin method and return
// the resulting system in 'Mp' and 'Yp', and the number of rows of
// the resulting system in 'nbRemainRows'
// ('M' arrangement is [iRow][iCol])
// Return true if the system becomes inconsistent during elimination,
// else return false
bool ElimVar2D(
    const int iVar,
    const double (*M)[2],
    const double* Y,

```

```

    const int nbRows,
    const int nbCols,
        double (*Mp)[2],
        double* Yp,
    int* const nbRemainRows) {

// Initialize the number of rows in the result system
*nbRemainRows = 0;

// First we process the rows where the eliminated variable is not null

// For each row except the last one
for (int iRow = 0;
    iRow < nbRows - 1;
    ++iRow) {

    // Shortcuts
    int sgnMIRowIVar = sgn(M[iRow][iVar]);
    double fabsMIRowIVar = fabs(M[iRow][iVar]);
    double YIRowDivideByFabsMIRowIVar = Y[iRow] / fabsMIRowIVar;

    // For each following rows
    for (int jRow = iRow + 1;
        jRow < nbRows;
        ++jRow) {

        // If coefficients of the eliminated variable in the two rows have
        // different signs and are not null
        if (sgnMIRowIVar != sgn(M[jRow][iVar]) &&
            fabsMIRowIVar > EPSILON &&
            fabs(M[jRow][iVar]) > EPSILON) {

            // Declare a variable to memorize the sum of the negative
            // coefficients in the row
            double sumNegCoeff = 0.0;

            // Add the sum of the two normed (relative to the eliminated
            // variable) rows into the result system. This actually
            // eliminate the variable while keeping the constraints on
            // others variables
            for (int iCol = 0, jCol = 0;
                iCol < nbCols;
                ++iCol ) {

                if (iCol != iVar) {

                    Mp[*nbRemainRows][jCol] =
                        M[iRow][iCol] / fabsMIRowIVar +
                        M[jRow][iCol] / fabs(M[jRow][iVar]);

                    // Update the sum of the negative coefficient
                    sumNegCoeff += neg(Mp[*nbRemainRows][jCol]);

                    // Increment the number of columns in the new inequality
                    ++jCol;

                }

            }

        }

    }

    // Update the right side of the inequality
    Yp[*nbRemainRows] =

```

```

        YIRowDivideByFabsMIRowIVar +
        Y[jRow] / fabs(M[jRow][iVar]);

    // If the right side of the inequality is lower than the sum of
    // negative coefficients in the row
    // (Add epsilon for numerical imprecision)
    if (Yp[*nbRemainRows] < sumNegCoeff - EPSILON) {

        // Given that X is in [0,1], the system is inconsistent
        return true;

    }

    // Increment the nb of rows into the result system
    ++(*nbRemainRows);

}

}

// Then we copy and compress the rows where the eliminated
// variable is null

// Loop on rows of the input system
for (int iRow = 0;
     iRow < nbRows;
     ++iRow) {

    // Shortcut
    const double* MiRow = M[iRow];

    // If the coefficient of the eliminated variable is null on
    // this row
    if (fabs(MiRow[iVar]) < EPSILON) {

        // Shortcut
        double* MpnbRemainRows = Mp[*nbRemainRows];

        // Copy this row into the result system excluding the eliminated
        // variable
        for (int iCol = 0, jCol = 0;
             iCol < nbCols;
             ++iCol) {

            if (iCol != iVar) {

                MpnbRemainRows[jCol] = MiRow[iCol];

                ++jCol;

            }

        }

        Yp[*nbRemainRows] = Y[iRow];

        // Increment the nb of rows into the result system
        ++(*nbRemainRows);

    }

}

```

```

}

// If we reach here the system is not inconsistent
return false;

}

// Get the bounds of the 'iVar'-th variable in the 'nbRows' rows
// system 'M'.X<='Y' and store them in the 'iVar'-th axis of the
// AABBB 'bdgBox'
// ('M' arrangement is [iRow][iCol])
// The system is supposed to have been reduced to only one variable
// per row, the one in argument
// May return inconsistent values (max < min), which would
// mean the system has no solution
void GetBound2D(
    const int iVar,
    const double (*M)[2],
    const double* Y,
    const int nbRows,
    AABBB2D* const bdgBox) {

    // Shortcuts
    double* min = bdgBox->min + iVar;
    double* max = bdgBox->max + iVar;

    // Initialize the bounds to there maximum maximum and minimum minimum
    *min = 0.0;
    *max = 1.0;

    // Loop on rows
    for (int jRow = 0;
        jRow < nbRows;
        ++jRow) {

        // Shortcut
        double MjRowiVar = M[jRow][0];

        // If this row has been reduced to the variable in argument
        // and it has a strictly positive coefficient
        if (MjRowiVar > EPSILON) {

            // Get the scaled value of Y for this row
            double y = Y[jRow] / MjRowiVar;

            // If the value is lower than the current maximum bound
            if (*max > y) {

                // Update the maximum bound
                *max = y;

            }

        }

        // Else, if this row has been reduced to the variable in argument
        // and it has a strictly negative coefficient
        } else if (MjRowiVar < -EPSILON) {

            // Get the scaled value of Y for this row
            double y = Y[jRow] / MjRowiVar;

            // If the value is greater than the current minimum bound

```

```

        if (*min < y) {

            // Update the minimum bound
            *min = y;

        }

    }

}

}

}

// Test for intersection between Frame 'that' and Frame 'tho'
// Return true if the two Frames are intersecting, else false
// If the Frame are intersecting the AABB of the intersection
// is stored into 'bdgBox', else 'bdgBox' is not modified
// If 'bdgBox' is null, the result AABB is not memorized (to use if
// unnecessary and want to speed up the algorithm)
// The resulting AABB may be larger than the smallest possible AABB
// The resulting AABB of FMBTestIntersection(A,B) may be different
// of the resulting AABB of FMBTestIntersection(B,A)
// The resulting AABB is given in 'tho' 's local coordinates system
bool FMBTestIntersection2D(
    const Frame2D* const that,
    const Frame2D* const tho,
    AABB2D* const bdgBox) {
//Frame2DPrint(that);printf("\n");
//Frame2DPrint(tho);printf("\n");
    // Get the projection of the Frame 'tho' in Frame 'that' coordinates
    // system
    Frame2D thoProj;
    Frame2DImportFrame(that, tho, &thoProj);

    // Declare two variables to memorize the system to be solved M.X <= Y
    // (M arrangement is [iRow][iCol])
    double M[8][2];
    double Y[8];

    // Create the inequality system

    // -sum_iC_j, iX_i <= 0_j
    M[0][0] = -thoProj.comp[0][0];
    M[0][1] = -thoProj.comp[1][0];
    Y[0] = thoProj.orig[0];
    if (Y[0] < neg(M[0][0]) + neg(M[0][1]))
        return false;

    M[1][0] = -thoProj.comp[0][1];
    M[1][1] = -thoProj.comp[1][1];
    Y[1] = thoProj.orig[1];
    if (Y[1] < neg(M[1][0]) + neg(M[1][1]))
        return false;

    // -X_i <= 0.0
    M[2][0] = -1.0;
    M[2][1] = 0.0;
    Y[2] = 0.0;

    M[3][0] = 0.0;
    M[3][1] = -1.0;
    Y[3] = 0.0;

```



```

// Variable to memorise the nb of rows in the system
int nbRows = 4;

if (that->type == FrameCuboid) {

    // sum_iC_j, iX_i <= 1.0 - 0_j
    M[nbRows][0] = thoProj.comp[0][0];
    M[nbRows][1] = thoProj.comp[1][0];
    Y[nbRows] = 1.0 - thoProj.orig[0];
    if (Y[nbRows] < neg(M[nbRows][0]) + neg(M[nbRows][1]))
        return false;
    ++nbRows;

    M[nbRows][0] = thoProj.comp[0][1];
    M[nbRows][1] = thoProj.comp[1][1];
    Y[nbRows] = 1.0 - thoProj.orig[1];
    if (Y[nbRows] < neg(M[nbRows][0]) + neg(M[nbRows][1]))
        return false;
    ++nbRows;

} else {

    // sum_j(sum_iC_j, iX_i) <= 1.0 - sum_iO_i
    M[nbRows][0] = thoProj.comp[0][0] + thoProj.comp[0][1];
    M[nbRows][1] = thoProj.comp[1][0] + thoProj.comp[1][1];
    Y[nbRows] = 1.0 - thoProj.orig[0] - thoProj.orig[1];
    if (Y[nbRows] < neg(M[nbRows][0]) + neg(M[nbRows][1]))
        return false;
    ++nbRows;

}

if (tho->type == FrameCuboid) {

    // X_i <= 1.0
    M[nbRows][0] = 1.0;
    M[nbRows][1] = 0.0;
    Y[nbRows] = 1.0;
    ++nbRows;

    M[nbRows][0] = 0.0;
    M[nbRows][1] = 1.0;
    Y[nbRows] = 1.0;
    ++nbRows;

} else {

    // sum_iX_i <= 1.0
    M[nbRows][0] = 1.0;
    M[nbRows][1] = 1.0;
    Y[nbRows] = 1.0;
    ++nbRows;

}

// Solve the system

// Declare a AABB to memorize the bounding box of the intersection
// in the coordinates system of that
AABB2D bdgBoxLocal;

```

```

// Declare variables to eliminate the first variable
double Mp[16][2];
double Yp[16];
int nbRowsP;

// Eliminate the first variable
bool inconsistency =
    ElimVar2D(
        FST_VAR,
        M,
        Y,
        nbRows,
        2,
        Mp,
        Yp,
        &nbRowsP);

// If the system is inconsistent
if (inconsistency == true) {

    // The two Frames are not in intersection
    return false;

}

// Get the bounds for the remaining second variable
GetBound2D(
    SND_VAR,
    Mp,
    Yp,
    nbRowsP,
    &bdgBoxLocal);

// If the bounds are inconsistent
if (bdgBoxLocal.min[SND_VAR] >= bdgBoxLocal.max[SND_VAR]) {

    // The two Frames are not in intersection
    return false;

// Else, if the bounds are consistent here it means
// the two Frames are in intersection.
// If the user hasn't requested for the resulting bounding box
} else if (bdgBox == NULL) {

    // Immediately return true
    return true;

}

// Now starts again from the initial systems and eliminate the
// second variable to get the bounds of the first variable
// No need to check for consistency because we already know here
// that the Frames are intersecting and the system is consistent
inconsistency =
    ElimVar2D(
        SND_VAR,
        M,
        Y,
        nbRows,
        2,
        Mp,
        Yp,

```

```

        &nbRowsP);

// Get the bounds for the remaining first variable
GetBound2D(
    FST_VAR,
    Mp,
    Yp,
    nbRowsP,
    &bdgBoxLocal);

// If the user requested the resulting bounding box
if (bdgBox != NULL) {

    // Memorize the result
    *bdgBox = bdgBoxLocal;

}

// If we've reached here the two Frames are intersecting
return true;

}

```

4.2.2 3D static

Header

```

#ifndef __FMB3D_H_
#define __FMB3D_H_

#include <stdbool.h>
#include "frame.h"

// ----- Functions declaration -----

// Test for intersection between Frame 'that' and Frame 'tho'
// Return true if the two Frames are intersecting, else false
// If the Frame are intersecting the AABB of the intersection
// is stored into 'bdgBox', else 'bdgBox' is not modified
// If 'bdgBox' is null, the result AABB is not memorized (to use if
// unnecessary and want to speed up the algorithm)
// The resulting AABB may be larger than the smallest possible AABB
// The resulting AABB of FMBTestIntersection(A,B) may be different
// of the resulting AABB of FMBTestIntersection(B,A)
// The resulting AABB is given in 'tho' 's local coordinates system
bool FMBTestIntersection3D(
    const Frame3D* const that,
    const Frame3D* const tho,
    AABB3D* const bdgBox);

#endif

```

Body

```

#include "fmb3d.h"

// ----- Macros -----

// Return 1.0 if v is positive, -1.0 if v is negative, 0.0 else
#define sgn(v) (((0.0 < (v)) ? 1 : 0) - (((v) < 0.0) ? 1 : 0))

```

```

// Return x if x is negative, 0.0 else
#define neg(x) (x < 0.0 ? x : 0.0)

#define FST_VAR 0
#define SND_VAR 1
#define THD_VAR 2

#define EPSILON 0.0000001

// ----- Functions declaration -----

// Eliminate the 'iVar'-th variable in the system 'M'.X<='Y'
// using the Fourier-Motzkin method and return
// the resulting system in 'Mp' and 'Yp', and the number of rows of
// the resulting system in 'nbRemainRows'
// Return false if the system becomes inconsistent during elimination,
// else return true
bool ElimVar3D(
    const int iVar,
    const double (*M)[3],
    const double* Y,
    const int nbRows,
    const int nbCols,
    double (*Mp)[3],
    double* Yp,
    int* const nbRemainRows);

// Get the bounds of the 'iVar'-th variable in the 'nbRows' rows
// system 'M'.X<='Y' and store them in the 'iVar'-th axis of the
// AABB 'bdgBox'
// ('M' arrangement is [iRow][iCol])
// The system is supposed to have been reduced to only one variable
// per row, the one in argument, which can be located in a different
// column than 'iVar'
// May return inconsistent values (max < min), which would
// mean the system has no solution
void GetBound3D(
    const int iVar,
    const double (*M)[3],
    const double* Y,
    const int nbRows,
    AABB3D* const bdgBox);

// ----- Functions implementation -----

// Eliminate the 'iVar'-th variable in the system 'M'.X<='Y'
// using the Fourier-Motzkin method and return
// the resulting system in 'Mp' and 'Yp', and the number of rows of
// the resulting system in 'nbRemainRows'
// ('M' arrangement is [iRow][iCol])
// Return true if the system becomes inconsistent during elimination,
// else return false
bool ElimVar3D(
    const int iVar,
    const double (*M)[3],
    const double* Y,
    const int nbRows,
    const int nbCols,
    double (*Mp)[3],
    double* Yp,
    int* const nbRemainRows) {

```

```

// Initialize the number of rows in the result system
*nbRemainRows = 0;

// First we process the rows where the eliminated variable is not null

// For each row except the last one
for (int iRow = 0;
     iRow < nbRows - 1;
     ++iRow) {

    // Shortcuts
    int sgnMIRowIVar = sgn(M[iRow][iVar]);
    double fabsMIRowIVar = fabs(M[iRow][iVar]);
    double YIRowDivideByFabsMIRowIVar = Y[iRow] / fabsMIRowIVar;

    // For each following rows
    for (int jRow = iRow + 1;
         jRow < nbRows;
         ++jRow) {

        // If coefficients of the eliminated variable in the two rows have
        // different signs and are not null
        if (sgnMIRowIVar != sgn(M[jRow][iVar]) &&
            fabsMIRowIVar > EPSILON &&
            fabs(M[jRow][iVar]) > EPSILON) {

            // Declare a variable to memorize the sum of the negative
            // coefficients in the row
            double sumNegCoeff = 0.0;

            // Add the sum of the two normed (relative to the eliminated
            // variable) rows into the result system. This actually
            // eliminate the variable while keeping the constraints on
            // others variables
            for (int iCol = 0, jCol = 0;
                 iCol < nbCols;
                 ++iCol ) {

                if (iCol != iVar) {

                    Mp[*nbRemainRows][jCol] =
                        M[iRow][iCol] / fabsMIRowIVar +
                        M[jRow][iCol] / fabs(M[jRow][iVar]);

                    // Update the sum of the negative coefficient
                    sumNegCoeff += neg(Mp[*nbRemainRows][jCol]);

                    // Increment the number of columns in the new inequality
                    ++jCol;

                }

            }

            // Update the right side of the inequality
            Yp[*nbRemainRows] =
                YIRowDivideByFabsMIRowIVar +
                Y[jRow] / fabs(M[jRow][iVar]);

            // If the right side of the inequality is lower than the sum of
            // negative coefficients in the row

```

```

        // (Add epsilon for numerical imprecision)
        if (Yp[*nbRemainRows] < sumNegCoeff - EPSILON) {

            // Given that X is in [0,1], the system is inconsistent
            return true;

        }

        // Increment the nb of rows into the result system
        ++(*nbRemainRows);

    }

}

// Then we copy and compress the rows where the eliminated
// variable is null

// Loop on rows of the input system
for (int iRow = 0;
     iRow < nbRows;
     ++iRow) {

    // Shortcut
    const double* MiRow = M[iRow];

    // If the coefficient of the eliminated variable is null on
    // this row
    if (fabs(MiRow[iVar]) < EPSILON) {

        // Shortcut
        double* MpnbRemainRows = Mp[*nbRemainRows];

        // Copy this row into the result system excluding the eliminated
        // variable
        for (int iCol = 0, jCol = 0;
             iCol < nbCols;
             ++iCol) {

            if (iCol != iVar) {

                MpnbRemainRows[jCol] = MiRow[iCol];

                ++jCol;

            }

        }

        Yp[*nbRemainRows] = Y[iRow];

        // Increment the nb of rows into the result system
        ++(*nbRemainRows);

    }

}

// If we reach here the system is not inconsistent
return false;

```

```

}

// Get the bounds of the 'iVar'-th variable in the 'nbRows' rows
// system 'M'.X<='Y' and store them in the 'iVar'-th axis of the
// AABB 'bdgBox'
// ('M' arrangement is [iRow][iCol])
// The system is supposed to have been reduced to only one variable
// per row, the one in argument
// May return inconsistent values (max < min), which would
// mean the system has no solution
void GetBound3D(
    const int iVar,
    const double (*M)[3],
    const double* Y,
    const int nbRows,
    AABB3D* const bdgBox) {

    // Shortcuts
    double* min = bdgBox->min + iVar;
    double* max = bdgBox->max + iVar;

    // Initialize the bounds to there maximum maximum and minimum minimum
    *min = 0.0;
    *max = 1.0;

    // Loop on rows
    for (int jRow = 0;
        jRow < nbRows;
        ++jRow) {

        // Shortcut
        double MjRowiVar = M[jRow][0];

        // If this row has been reduced to the variable in argument
        // and it has a strictly positive coefficient
        if (MjRowiVar > EPSILON) {

            // Get the scaled value of Y for this row
            double y = Y[jRow] / MjRowiVar;

            // If the value is lower than the current maximum bound
            if (*max > y) {

                // Update the maximum bound
                *max = y;

            }

        }

        // Else, if this row has been reduced to the variable in argument
        // and it has a strictly negative coefficient
        } else if (MjRowiVar < -EPSILON) {

            // Get the scaled value of Y for this row
            double y = Y[jRow] / MjRowiVar;

            // If the value is greater than the current minimum bound
            if (*min < y) {

                // Update the minimum bound
                *min = y;

            }

        }

    }

}

```

```

    }

    }

}

}

// Test for intersection between Frame 'that' and Frame 'tho'
// Return true if the two Frames are intersecting, else false
// If the Frame are intersecting the AABB of the intersection
// is stored into 'bdgBox', else 'bdgBox' is not modified
// If 'bdgBox' is null, the result AABB is not memorized (to use if
// unnecessary and want to speed up the algorithm)
// The resulting AABB may be larger than the smallest possible AABB
// The resulting AABB of FMBTestIntersection(A,B) may be different
// of the resulting AABB of FMBTestIntersection(B,A)
// The resulting AABB is given in 'tho' 's local coordinates system
bool FMBTestIntersection3D(
    const Frame3D* const that,
    const Frame3D* const tho,
    AABB3D* const bdgBox) {

    // Get the projection of the Frame 'tho' in Frame 'that' coordinates
    // system
    Frame3D thoProj;
    Frame3DImportFrame(that, tho, &thoProj);

    // Declare two variables to memorize the system to be solved M.X <= Y
    // (M arrangement is [iRow][iCol])
    double M[12][3];
    double Y[12];

    // Create the inequality system

    // -sum_iC_j, iX_i <= 0_j
    M[0][0] = -thoProj.comp[0][0];
    M[0][1] = -thoProj.comp[1][0];
    M[0][2] = -thoProj.comp[2][0];
    Y[0] = thoProj.orig[0];
    if (Y[0] < neg(M[0][0]) + neg(M[0][1]) + neg(M[0][2]))
        return false;

    M[1][0] = -thoProj.comp[0][1];
    M[1][1] = -thoProj.comp[1][1];
    M[1][2] = -thoProj.comp[2][1];
    Y[1] = thoProj.orig[1];
    if (Y[1] < neg(M[1][0]) + neg(M[1][1]) + neg(M[1][2]))
        return false;

    M[2][0] = -thoProj.comp[0][2];
    M[2][1] = -thoProj.comp[1][2];
    M[2][2] = -thoProj.comp[2][2];
    Y[2] = thoProj.orig[2];
    if (Y[2] < neg(M[2][0]) + neg(M[2][1]) + neg(M[2][2]))
        return false;

    // -X_i <= 0.0
    M[3][0] = -1.0;
    M[3][1] = 0.0;
    M[3][2] = 0.0;
    Y[3] = 0.0;

```



```

M[4][0] = 0.0;
M[4][1] = -1.0;
M[4][2] = 0.0;
Y[4] = 0.0;

M[5][0] = 0.0;
M[5][1] = 0.0;
M[5][2] = -1.0;
Y[5] = 0.0;

// Variable to memorise the nb of rows in the system
int nbRows = 6;

if (that->type == FrameCuboid) {

    // sum_iC_j, iX_i <= 1.0 - 0_j
    M[nbRows][0] = thoProj.comp[0][0];
    M[nbRows][1] = thoProj.comp[1][0];
    M[nbRows][2] = thoProj.comp[2][0];
    Y[nbRows] = 1.0 - thoProj.orig[0];
    if (Y[nbRows] < neg(M[nbRows][0]) + neg(M[nbRows][1]) +
        neg(M[nbRows][2]))
        return false;
    ++nbRows;

    M[nbRows][0] = thoProj.comp[0][1];
    M[nbRows][1] = thoProj.comp[1][1];
    M[nbRows][2] = thoProj.comp[2][1];
    Y[nbRows] = 1.0 - thoProj.orig[1];
    if (Y[nbRows] < neg(M[nbRows][0]) + neg(M[nbRows][1]) +
        neg(M[nbRows][2]))
        return false;
    ++nbRows;

    M[nbRows][0] = thoProj.comp[0][2];
    M[nbRows][1] = thoProj.comp[1][2];
    M[nbRows][2] = thoProj.comp[2][2];
    Y[nbRows] = 1.0 - thoProj.orig[2];
    if (Y[nbRows] < neg(M[nbRows][0]) + neg(M[nbRows][1]) +
        neg(M[nbRows][2]))
        return false;
    ++nbRows;

} else {

    // sum_j(sum_iC_j, iX_i) <= 1.0 - sum_i0_i
    M[nbRows][0] =
        thoProj.comp[0][0] + thoProj.comp[0][1] + thoProj.comp[0][2];
    M[nbRows][1] =
        thoProj.comp[1][0] + thoProj.comp[1][1] + thoProj.comp[1][2];
    M[nbRows][2] =
        thoProj.comp[2][0] + thoProj.comp[2][1] + thoProj.comp[2][2];
    Y[nbRows] =
        1.0 - thoProj.orig[0] - thoProj.orig[1] - thoProj.orig[2];
    if (Y[nbRows] < neg(M[nbRows][0]) + neg(M[nbRows][1]) +
        neg(M[nbRows][2]))
        return false;
    ++nbRows;

}

```

```

if (tho->type == FrameCuboid) {

    // X_i <= 1.0
    M[nbRows][0] = 1.0;
    M[nbRows][1] = 0.0;
    M[nbRows][2] = 0.0;
    Y[nbRows] = 1.0;
    ++nbRows;

    M[nbRows][0] = 0.0;
    M[nbRows][1] = 1.0;
    M[nbRows][2] = 0.0;
    Y[nbRows] = 1.0;
    ++nbRows;

    M[nbRows][0] = 0.0;
    M[nbRows][1] = 0.0;
    M[nbRows][2] = 1.0;
    Y[nbRows] = 1.0;
    ++nbRows;

} else {

    // sum_iX_i<=1.0
    M[nbRows][0] = 1.0;
    M[nbRows][1] = 1.0;
    M[nbRows][2] = 1.0;
    Y[nbRows] = 1.0;
    ++nbRows;

}

// Solve the system

// Declare a AABB to memorize the bounding box of the intersection
// in the coordinates system of that
AABB3D bdgBoxLocal;

// Declare variables to eliminate the first variable
double Mp[36][3];
double Yp[36];
int nbRowsP;

// Eliminate the first variable in the original system
bool inconsistency =
    ElimVar3D(
        FST_VAR,
        M,
        Y,
        nbRows,
        3,
        Mp,
        Yp,
        &nbRowsP);

// If the system is inconsistent
if (inconsistency == true) {

    // The two Frames are not in intersection
    return false;

}

```

```

// Declare variables to eliminate the second variable
double Mpp[324][3];
double Ypp[324];
int nbRowsPP;

// Eliminate the second variable (which is the first in the new system)
inconsistency =
    ElimVar3D(
        FST_VAR,
        Mp,
        Yp,
        nbRowsP,
        2,
        Mpp,
        Ypp,
        &nbRowsPP);

// If the system is inconsistent
if (inconsistency == true) {

    // The two Frames are not in intersection
    return false;

}

// Get the bounds for the remaining third variable
GetBound3D(
    THD_VAR,
    Mpp,
    Ypp,
    nbRowsPP,
    &bdgBoxLocal);

// If the bounds are inconstent
if (bdgBoxLocal.min[THD_VAR] >= bdgBoxLocal.max[THD_VAR]) {

    // The two Frames are not in intersection
    return false;

// Else, if the bounds are consistent here it means
// the two Frames are in intersection.
// If the user hasn't requested for the resulting bounding box
} else if (bdgBox == NULL) {

    // Immediately return true
    return true;

}

// Eliminate the third variable (which is the first in the new
// system)
inconsistency =
    ElimVar3D(
        SND_VAR,
        Mp,
        Yp,
        nbRowsP,
        2,
        Mpp,
        Ypp,
        &nbRowsPP);

```

```

// Get the bounds for the remaining second variable
GetBound3D(
    SND_VAR,
    Mpp,
    Ypp,
    nbRowsPP,
    &bdgBoxLocal);

// Now starts again from the initial systems and eliminate the
// second and third variables to get the bounds of the first variable
// No need to check for consistency because we already know here
// that the Frames are intersecting and the system is consistent
inconsistency =
    ElimVar3D(
        THD_VAR,
        M,
        Y,
        nbRows,
        3,
        Mp,
        Yp,
        &nbRowsP);

inconsistency =
    ElimVar3D(
        SND_VAR,
        Mp,
        Yp,
        nbRowsP,
        2,
        Mpp,
        Ypp,
        &nbRowsPP);

GetBound3D(
    FST_VAR,
    Mpp,
    Ypp,
    nbRowsPP,
    &bdgBoxLocal);

// If the user requested the resulting bounding box
if (bdgBox != NULL) {

    // Memorize the result
    *bdgBox = bdgBoxLocal;

}

// If we've reached here the two Frames are intersecting
return true;

}

```

4.2.3 2D dynamic

Header

```
#ifndef __FMB2DT_H_
```

```

#define __FMB2DT_H_

#include <stdbool.h>
#include "frame.h"

// ----- Functions declaration -----

// Test for intersection between Frame 'that' and Frame 'tho'
// Return true if the two Frames are intersecting, else false
// If the Frame are intersecting the AABB of the intersection
// is stored into 'bdgBox', else 'bdgBox' is not modified
// If 'bdgBox' is null, the result AABB is not memorized (to use if
// unnecessary and want to speed up the algorithm)
// The resulting AABB may be larger than the smallest possible AABB
// The resulting AABB of FMBTestIntersection(A,B) may be different
// of the resulting AABB of FMBTestIntersection(B,A)
// The resulting AABB is given in 'tho' 's local coordinates system
bool FMBTestIntersection2DTime(
    const Frame2DTime* const that,
    const Frame2DTime* const tho,
    AABB2DTime* const bdgBox);

#endif

Body

#include "fmb2dt.h"

// ----- Macros -----

// Return 1.0 if v is positive, -1.0 if v is negative, 0.0 else
#define sgn(v) (((0.0 < (v)) ? 1 : 0) - (((v) < 0.0) ? 1 : 0))

// Return x if x is negative, 0.0 else
#define neg(x) (x < 0.0 ? x : 0.0)

#define FST_VAR 0
#define SND_VAR 1
#define THD_VAR 2

#define EPSILON 0.0000001

// ----- Functions declaration -----

// Eliminate the 'iVar'-th variable in the system 'M'.X<='Y'
// using the Fourier-Motzkin method and return
// the resulting system in 'Mp' and 'Yp', and the number of rows of
// the resulting system in 'nbRemainRows'
// Return false if the system becomes inconsistent during elimination,
// else return true
bool ElimVar2DTime(
    const int iVar,
    const double (*M)[3],
    const double* Y,
    const int nbRows,
    const int nbCols,
    double (*Mp)[3],
    double* Yp,
    int* const nbRemainRows);

// Get the bounds of the 'iVar'-th variable in the 'nbRows' rows
// system 'M'.X<='Y' and store them in the 'iVar'-th axis of the

```

```

// AABB 'bdgBox'
// ('M' arrangement is [iRow][iCol])
// The system is supposed to have been reduced to only one variable
// per row, the one in argument, which can be located in a different
// column than 'iVar'
// May return inconsistent values (max < min), which would
// mean the system has no solution
void GetBound2DTime(
    const int iVar,
    const double (*M)[3],
    const double* Y,
    const int nbRows,
    AABB2DTime* const bdgBox);

// ----- Functions implementation -----

// Eliminate the 'iVar'-th variable in the system 'M'.X<='Y'
// using the Fourier-Motzkin method and return
// the resulting system in 'Mp' and 'Yp', and the number of rows of
// the resulting system in 'nbRemainRows'
// ('M' arrangement is [iRow][iCol])
// Return true if the system becomes inconsistent during elimination,
// else return false
bool ElimVar2DTime(
    const int iVar,
    const double (*M)[3],
    const double* Y,
    const int nbRows,
    const int nbCols,
    double (*Mp)[3],
    double* Yp,
    int* const nbRemainRows) {

    // Initialize the number of rows in the result system
    *nbRemainRows = 0;

    // First we process the rows where the eliminated variable is not null

    // For each row except the last one
    for (int iRow = 0;
        iRow < nbRows - 1;
        ++iRow) {

        // Shortcuts
        int sgnMIRowIVar = sgn(M[iRow][iVar]);
        double fabsMIRowIVar = fabs(M[iRow][iVar]);
        double YIRowDivideByFabsMIRowIVar = Y[iRow] / fabsMIRowIVar;

        // For each following rows
        for (int jRow = iRow + 1;
            jRow < nbRows;
            ++jRow) {

            // If coefficients of the eliminated variable in the two rows have
            // different signs and are not null
            if (sgnMIRowIVar != sgn(M[jRow][iVar]) &&
                fabsMIRowIVar > EPSILON &&
                fabs(M[jRow][iVar]) > EPSILON) {

                // Declare a variable to memorize the sum of the negative
                // coefficients in the row
                double sumNegCoeff = 0.0;

```

```

// Add the sum of the two normed (relative to the eliminated
// variable) rows into the result system. This actually
// eliminate the variable while keeping the constraints on
// others variables
for (int iCol = 0, jCol = 0;
    iCol < nbCols;
    ++iCol ) {

    if (iCol != iVar) {

        Mp[*nbRemainRows][jCol] =
            M[iRow][iCol] / fabs(MiRowIVar) +
            M[jRow][iCol] / fabs(M[jRow][iVar]);

        // Update the sum of the negative coefficient
        sumNegCoeff += neg(Mp[*nbRemainRows][jCol]);

        // Increment the number of columns in the new inequality
        ++jCol;

    }

}

// Update the right side of the inequality
Yp[*nbRemainRows] =
    YIRowDivideByFabsMiRowIVar +
    Y[jRow] / fabs(M[jRow][iVar]);

// If the right side of the inequality is lower than the sum of
// negative coefficients in the row
// (Add epsilon for numerical imprecision)
if (Yp[*nbRemainRows] < sumNegCoeff - EPSILON) {

    // Given that X is in [0,1], the system is inconsistent
    return true;

}

// Increment the nb of rows into the result system
++(*nbRemainRows);

}

}

// Then we copy and compress the rows where the eliminated
// variable is null

// Loop on rows of the input system
for (int iRow = 0;
    iRow < nbRows;
    ++iRow) {

    // Shortcut
    const double* MiRow = M[iRow];

    // If the coefficient of the eliminated variable is null on
    // this row

```

```

    if (fabs(MiRow[iVar]) < EPSILON) {

        // Shortcut
        double* MpnbRemainRows = Mp[*nbRemainRows];

        // Copy this row into the result system excluding the eliminated
        // variable
        for (int iCol = 0, jCol = 0;
            iCol < nbCols;
            ++iCol) {

            if (iCol != iVar) {

                MpnbRemainRows[jCol] = MiRow[iCol];

                ++jCol;

            }

        }

        Yp[*nbRemainRows] = Y[iRow];

        // Increment the nb of rows into the result system
        ++(*nbRemainRows);

    }

}

// If we reach here the system is not inconsistent
return false;

}

// Get the bounds of the 'iVar'-th variable in the 'nbRows' rows
// system 'M'.X<='Y' and store them in the 'iVar'-th axis of the
// AABBB 'bdgBox'
// ('M' arrangement is [iRow][iCol])
// The system is supposed to have been reduced to only one variable
// per row, the one in argument
// May return inconsistent values (max < min), which would
// mean the system has no solution
void GetBound2DTime(
    const int iVar,
    const double (*M)[3],
    const double* Y,
    const int nbRows,
    AABBB2DTime* const bdgBox) {

    // Shortcuts
    double* min = bdgBox->min + iVar;
    double* max = bdgBox->max + iVar;

    // Initialize the bounds to there maximum maximum and minimum minimum
    *min = 0.0;
    *max = 1.0;

    // Loop on rows
    for (int jRow = 0;
        jRow < nbRows;
        ++jRow) {

```



```

// Shortcut
double MjRowiVar = M[jRow][0];

// If this row has been reduced to the variable in argument
// and it has a strictly positive coefficient
if (MjRowiVar > EPSILON) {

    // Get the scaled value of Y for this row
    double y = Y[jRow] / MjRowiVar;

    // If the value is lower than the current maximum bound
    if (*max > y) {

        // Update the maximum bound
        *max = y;

    }

    // Else, if this row has been reduced to the variable in argument
    // and it has a strictly negative coefficient
} else if (MjRowiVar < -EPSILON) {

    // Get the scaled value of Y for this row
    double y = Y[jRow] / MjRowiVar;

    // If the value is greater than the current minimum bound
    if (*min < y) {

        // Update the minimum bound
        *min = y;

    }

}

}

}

// Test for intersection between Frame 'that' and Frame 'tho'
// Return true if the two Frames are intersecting, else false
// If the Frame are intersecting the AABB of the intersection
// is stored into 'bdgBox', else 'bdgBox' is not modified
// If 'bdgBox' is null, the result AABB is not memorized (to use if
// unnecessary and want to speed up the algorithm)
// The resulting AABB may be larger than the smallest possible AABB
// The resulting AABB of FMBTestIntersection(A,B) may be different
// of the resulting AABB of FMBTestIntersection(B,A)
// The resulting AABB is given in 'tho' 's local coordinates system
bool FMBTestIntersection2DTime(
    const Frame2DTime* const that,
    const Frame2DTime* const tho,
    AABB2DTime* const bdgBox) {

    // Get the projection of the Frame 'tho' in Frame 'that' coordinates
    // system
    Frame2DTime thoProj;
    Frame2DTimeImportFrame(that, tho, &thoProj);

    // Declare two variables to memorize the system to be solved M.X <= Y
    // (M arrangement is [iRow][iCol])

```

```

double M[10][3];
double Y[10];

// Create the inequality system

// -V_jT-sum_iC_j,iX_i<=0_j
M[0][0] = -thoProj.comp[0][0];
M[0][1] = -thoProj.comp[1][0];
M[0][2] = -thoProj.speed[0];
Y[0] = thoProj.orig[0];
if (Y[0] < neg(M[0][0]) + neg(M[0][1]) + neg(M[0][2]))
    return false;

M[1][0] = -thoProj.comp[0][1];
M[1][1] = -thoProj.comp[1][1];
M[1][2] = -thoProj.speed[1];
Y[1] = thoProj.orig[1];
if (Y[1] < neg(M[1][0]) + neg(M[1][1]) + neg(M[1][2]))
    return false;

// -X_i <= 0.0
M[2][0] = -1.0;
M[2][1] = 0.0;
M[2][2] = 0.0;
Y[2] = 0.0;

M[3][0] = 0.0;
M[3][1] = -1.0;
M[3][2] = 0.0;
Y[3] = 0.0;

// 0.0 <= t <= 1.0
M[4][0] = 0.0;
M[4][1] = 0.0;
M[4][2] = 1.0;
Y[4] = 1.0;

M[5][0] = 0.0;
M[5][1] = 0.0;
M[5][2] = -1.0;
Y[5] = 0.0;

// Variable to memorise the nb of rows in the system
int nbRows = 6;

if (that->type == FrameCuboid) {

    // V_jT+sum_iC_j,iX_i<=1.0-0_j
    M[nbRows][0] = thoProj.comp[0][0];
    M[nbRows][1] = thoProj.comp[1][0];
    M[nbRows][2] = thoProj.speed[0];
    Y[nbRows] = 1.0 - thoProj.orig[0];
    if (Y[nbRows] < neg(M[nbRows][0]) + neg(M[nbRows][1]) +
        neg(M[nbRows][2]))
        return false;
    ++nbRows;

    M[nbRows][0] = thoProj.comp[0][1];
    M[nbRows][1] = thoProj.comp[1][1];
    M[nbRows][2] = thoProj.speed[1];
    Y[nbRows] = 1.0 - thoProj.orig[1];
    if (Y[nbRows] < neg(M[nbRows][0]) + neg(M[nbRows][1]) +

```

```

        neg(M[nbRows][2]))
        return false;
        ++nbRows;
    } else {
        // sum_j(V_jT+sum_iC_j,iX_i)<=1.0-sum_i0_i
        M[nbRows][0] = thoProj.comp[0][0] + thoProj.comp[0][1];
        M[nbRows][1] = thoProj.comp[1][0] + thoProj.comp[1][1];
        M[nbRows][2] = thoProj.speed[0] + thoProj.speed[1];
        Y[nbRows] = 1.0 - thoProj.orig[0] - thoProj.orig[1];
        if (Y[nbRows] < neg(M[nbRows][0]) + neg(M[nbRows][1]) +
            neg(M[nbRows][2]))
            return false;
        ++nbRows;
    }
}

if (tho->type == FrameCuboid) {
    // X_i <= 1.0
    M[nbRows][0] = 1.0;
    M[nbRows][1] = 0.0;
    M[nbRows][2] = 0.0;
    Y[nbRows] = 1.0;
    ++nbRows;

    M[nbRows][0] = 0.0;
    M[nbRows][1] = 1.0;
    M[nbRows][2] = 0.0;
    Y[nbRows] = 1.0;
    ++nbRows;
} else {
    // sum_iX_i<=1.0
    M[nbRows][0] = 1.0;
    M[nbRows][1] = 1.0;
    M[nbRows][2] = 0.0;
    Y[nbRows] = 1.0;
    ++nbRows;
}

// Solve the system

// Declare a AABB to memorize the bounding box of the intersection
// in the coordinates system of that
AABB2DTime bdgBoxLocal;

// Declare variables to eliminate the first variable
double Mp[25][3];
double Yp[25];
int nbRowsP;

// Eliminate the first variable in the original system
bool inconsistency =
    ElimVar2DTime(
        FST_VAR,
        M,
        Y,
        nbRows,

```

```

        3,
        Mp,
        Yp,
        &nbRowsP);

// If the system is inconsistent
if (inconsistency == true) {

    // The two Frames are not in intersection
    return false;

}

// Declare variables to eliminate the second variable
double Mpp[157][3];
double Ypp[157];
int nbRowsPP;

// Eliminate the second variable (which is the first in the new system)
inconsistency =
    ElimVar2DTime(
        FST_VAR,
        Mp,
        Yp,
        nbRowsP,
        2,
        Mpp,
        Ypp,
        &nbRowsPP);

// If the system is inconsistent
if (inconsistency == true) {

    // The two Frames are not in intersection
    return false;

}

// Get the bounds for the remaining third variable
GetBound2DTime(
    THD_VAR,
    Mpp,
    Ypp,
    nbRowsPP,
    &bdgBoxLocal);

// If the bounds are inconstant
if (bdgBoxLocal.min[THD_VAR] >= bdgBoxLocal.max[THD_VAR]) {

    // The two Frames are not in intersection
    return false;

// Else, if the bounds are consistent here it means
// the two Frames are in intersection.
// If the user hasn't requested for the resulting bounding box
} else if (bdgBox == NULL) {

    // Immediately return true
    return true;

}

```

```

// Eliminate the third variable (which is the second in the new
// system)
inconsistency =
    ElimVar2DTime(
        SND_VAR,
        Mp,
        Yp,
        nbRowsP,
        2,
        Mpp,
        Ypp,
        &nbRowsPP);

// Get the bounds for the remaining second variable
GetBound2DTime(
    SND_VAR,
    Mpp,
    Ypp,
    nbRowsPP,
    &bdgBoxLocal);

// Now starts again from the initial systems and eliminate the
// second and third variables to get the bounds of the first variable
// No need to check for consistency because we already know here
// that the Frames are intersecting and the system is consistent
inconsistency =
    ElimVar2DTime(
        THD_VAR,
        M,
        Y,
        nbRows,
        3,
        Mp,
        Yp,
        &nbRowsP);

inconsistency =
    ElimVar2DTime(
        SND_VAR,
        Mp,
        Yp,
        nbRowsP,
        2,
        Mpp,
        Ypp,
        &nbRowsPP);

GetBound2DTime(
    FST_VAR,
    Mpp,
    Ypp,
    nbRowsPP,
    &bdgBoxLocal);

// If the user requested the resulting bounding box
if (bdgBox != NULL) {

    // Memorize the result
    *bdgBox = bdgBoxLocal;
}

```

```

    // If we've reached here the two Frames are intersecting
    return true;
}

```

4.2.4 3D dynamic

Header

```

#ifndef __FMB3DT_H_
#define __FMB3DT_H_

#include <stdbool.h>
#include "frame.h"

// ----- Functions declaration -----

// Test for intersection between Frame 'that' and Frame 'tho'
// Return true if the two Frames are intersecting, else false
// If the Frame are intersecting the AABB of the intersection
// is stored into 'bdgBox', else 'bdgBox' is not modified
// If 'bdgBox' is null, the result AABB is not memorized (to use if
// unnecessary and want to speed up the algorithm)
// The resulting AABB may be larger than the smallest possible AABB
// The resulting AABB of FMBTestIntersection(A,B) may be different
// of the resulting AABB of FMBTestIntersection(B,A)
// The resulting AABB is given in 'tho' 's local coordinates system
bool FMBTestIntersection3DTime(
    const Frame3DTime* const that,
    const Frame3DTime* const tho,
    AABB3DTime* const bdgBox);

#endif

```

Body

```

#include "fmb3dt.h"

// ----- Macros -----

// Return 1.0 if v is positive, -1.0 if v is negative, 0.0 else
#define sgn(v) (((0.0 < (v)) ? 1 : 0) - (((v) < 0.0) ? 1 : 0))

// Return x if x is negative, 0.0 else
#define neg(x) (x < 0.0 ? x : 0.0)

#define FST_VAR 0
#define SND_VAR 1
#define THD_VAR 2
#define FOR_VAR 3

#define EPSILON 0.0000001

// ----- Functions declaration -----

// Eliminate the 'iVar'-th variable in the system 'M'.X<='Y'
// using the Fourier-Motzkin method and return
// the resulting system in 'Mp' and 'Yp', and the number of rows of
// the resulting system in 'nbRemainRows'
// Return false if the system becomes inconsistent during elimination,

```

```

// else return true
bool ElimVar3DTime(
    const int iVar,
    const double (*M)[4],
    const double* Y,
    const int nbRows,
    const int nbCols,
    double (*Mp)[4],
    double* Yp,
    int* const nbRemainRows);

// Get the bounds of the 'iVar'-th variable in the 'nbRows' rows
// system 'M'.X<='Y' and store them in the 'iVar'-th axis of the
// AABB 'bdgBox'
// ('M' arrangement is [iRow][iCol])
// The system is supposed to have been reduced to only one variable
// per row, the one in argument, which can be located in a different
// column than 'iVar'
// May return inconsistent values (max < min), which would
// mean the system has no solution
void GetBound3DTime(
    const int iVar,
    const double (*M)[4],
    const double* Y,
    const int nbRows,
    AABB3DTime* const bdgBox);

// ----- Functions implementation -----

// Eliminate the 'iVar'-th variable in the system 'M'.X<='Y'
// using the Fourier-Motzkin method and return
// the resulting system in 'Mp' and 'Yp', and the number of rows of
// the resulting system in 'nbRemainRows'
// ('M' arrangement is [iRow][iCol])
// Return true if the system becomes inconsistent during elimination,
// else return false
bool ElimVar3DTime(
    const int iVar,
    const double (*M)[4],
    const double* Y,
    const int nbRows,
    const int nbCols,
    double (*Mp)[4],
    double* Yp,
    int* const nbRemainRows) {

    // Initialize the number of rows in the result system
    *nbRemainRows = 0;

    // First we process the rows where the eliminated variable is not null

    // For each row except the last one
    for (int iRow = 0;
        iRow < nbRows - 1;
        ++iRow) {

        // Shortcuts
        int sgnMIRowIVar = sgn(M[iRow][iVar]);
        double fabsMIRowIVar = fabs(M[iRow][iVar]);
        double YIRowDivideByFabsMIRowIVar = Y[iRow] / fabsMIRowIVar;

        // For each following rows

```

```

for (int jRow = iRow + 1;
    jRow < nbRows;
    ++jRow) {

    // If coefficients of the eliminated variable in the two rows have
    // different signs and are not null
    if (sgnMIRowIVar != sgn(M[jRow][iVar]) &&
        fabsMIRowIVar > EPSILON &&
        fabs(M[jRow][iVar]) > EPSILON) {

        // Declare a variable to memorize the sum of the negative
        // coefficients in the row
        double sumNegCoeff = 0.0;

        // Add the sum of the two normed (relative to the eliminated
        // variable) rows into the result system. This actually
        // eliminate the variable while keeping the constraints on
        // others variables
        for (int iCol = 0, jCol = 0;
            iCol < nbCols;
            ++iCol ) {

            if (iCol != iVar) {

                Mp[*nbRemainRows][jCol] =
                    M[iRow][iCol] / fabsMIRowIVar +
                    M[jRow][iCol] / fabs(M[jRow][iVar]);

                // Update the sum of the negative coefficient
                sumNegCoeff += neg(Mp[*nbRemainRows][jCol]);

                // Increment the number of columns in the new inequality
                ++jCol;

            }

        }

        // Update the right side of the inequality
        Yp[*nbRemainRows] =
            YIRowDivideByFabsMIRowIVar +
            Y[jRow] / fabs(M[jRow][iVar]);

        // If the right side of the inequality is lower than the sum of
        // negative coefficients in the row
        // (Add epsilon for numerical imprecision)
        if (Yp[*nbRemainRows] < sumNegCoeff - EPSILON) {

            // Given that X is in [0,1], the system is inconsistent
            return true;

        }

        // Increment the nb of rows into the result system
        ++(*nbRemainRows);

    }

}

}

```



```

// Then we copy and compress the rows where the eliminated
// variable is null

// Loop on rows of the input system
for (int iRow = 0;
     iRow < nbRows;
     ++iRow) {

    // Shortcut
    const double* MiRow = M[iRow];

    // If the coefficient of the eliminated variable is null on
    // this row
    if (fabs(MiRow[iVar]) < EPSILON) {

        // Shortcut
        double* MpnbRemainRows = Mp[*nbRemainRows];

        // Copy this row into the result system excluding the eliminated
        // variable
        for (int iCol = 0, jCol = 0;
             iCol < nbCols;
             ++iCol) {

            if (iCol != iVar) {

                MpnbRemainRows[jCol] = MiRow[iCol];

                ++jCol;
            }
        }

        Yp[*nbRemainRows] = Y[iRow];

        // Increment the nb of rows into the result system
        ++(*nbRemainRows);
    }
}

// If we reach here the system is not inconsistent
return false;
}

// Get the bounds of the 'iVar'-th variable in the 'nbRows' rows
// system 'M'.X<='Y' and store them in the 'iVar'-th axis of the
// AABB 'bdgBox'
// ('M' arrangement is [iRow][iCol])
// The system is supposed to have been reduced to only one variable
// per row, the one in argument
// May return inconsistent values (max < min), which would
// mean the system has no solution
void GetBound3DTime(
    const int iVar,
    const double (*M)[4],
    const double* Y,
    const int nbRows,
    AABB3DTime* const bdgBox) {

```

```

// Shortcuts
double* min = bdgBox->min + iVar;
double* max = bdgBox->max + iVar;

// Initialize the bounds to there maximum maximum and minimum minimum
*min = 0.0;
*max = 1.0;

// Loop on rows
for (int jRow = 0;
     jRow < nbRows;
     ++jRow) {

    // Shortcut
    double MjRowiVar = M[jRow][0];

    // If this row has been reduced to the variable in argument
    // and it has a strictly positive coefficient
    if (MjRowiVar > EPSILON) {

        // Get the scaled value of Y for this row
        double y = Y[jRow] / MjRowiVar;

        // If the value is lower than the current maximum bound
        if (*max > y) {

            // Update the maximum bound
            *max = y;

        }

        // Else, if this row has been reduced to the variable in argument
        // and it has a strictly negative coefficient
    } else if (MjRowiVar < -EPSILON) {

        // Get the scaled value of Y for this row
        double y = Y[jRow] / MjRowiVar;

        // If the value is greater than the current minimum bound
        if (*min < y) {

            // Update the minimum bound
            *min = y;

        }

    }

}

}

// Test for intersection between Frame 'that' and Frame 'tho'
// Return true if the two Frames are intersecting, else false
// If the Frame are intersecting the AABB of the intersection
// is stored into 'bdgBox', else 'bdgBox' is not modified
// If 'bdgBox' is null, the result AABB is not memorized (to use if
// unnecessary and want to speed up the algorithm)
// The resulting AABB may be larger than the smallest possible AABB
// The resulting AABB of FMBTestIntersection(A,B) may be different
// of the resulting AABB of FMBTestIntersection(B,A)

```

```

// The resulting AABB is given in 'tho' 's local coordinates system
bool FMBTestIntersection3DTime(
    const Frame3DTime* const that,
    const Frame3DTime* const tho,
    AABB3DTime* const bdgBox) {

    // Get the projection of the Frame 'tho' in Frame 'that' coordinates
    // system
    Frame3DTime thoProj;
    Frame3DTimeImportFrame(that, tho, &thoProj);

    // Declare two variables to memorize the system to be solved M.X <= Y
    // (M arrangement is [iRow][iCol])
    double M[14][4];
    double Y[14];

    // Create the inequality system

    // -V_jT-sum_iC_j, iX_i<=0_j
    M[0][0] = -thoProj.comp[0][0];
    M[0][1] = -thoProj.comp[1][0];
    M[0][2] = -thoProj.comp[2][0];
    M[0][3] = -thoProj.speed[0];
    Y[0] = thoProj.orig[0];
    if (Y[0] < neg(M[0][0]) + neg(M[0][1]) + neg(M[0][2]) + neg(M[0][3]))
        return false;

    M[1][0] = -thoProj.comp[0][1];
    M[1][1] = -thoProj.comp[1][1];
    M[1][2] = -thoProj.comp[2][1];
    M[1][3] = -thoProj.speed[1];
    Y[1] = thoProj.orig[1];
    if (Y[1] < neg(M[1][0]) + neg(M[1][1]) + neg(M[1][2]) + neg(M[1][3]))
        return false;

    M[2][0] = -thoProj.comp[0][2];
    M[2][1] = -thoProj.comp[1][2];
    M[2][2] = -thoProj.comp[2][2];
    M[2][3] = -thoProj.speed[2];
    Y[2] = thoProj.orig[2];
    if (Y[2] < neg(M[2][0]) + neg(M[2][1]) + neg(M[2][2]) + neg(M[2][3]))
        return false;

    // Variable to memorise the nb of rows in the system
    int nbRows = 3;

    if (that->type == FrameCuboid) {

        // V_jT+sum_iC_j, iX_i<=1.0-0_j
        M[nbRows][0] = thoProj.comp[0][0];
        M[nbRows][1] = thoProj.comp[1][0];
        M[nbRows][2] = thoProj.comp[2][0];
        M[nbRows][3] = thoProj.speed[0];
        Y[nbRows] = 1.0 - thoProj.orig[0];
        if (Y[nbRows] < neg(M[nbRows][0]) + neg(M[nbRows][1]) +
            neg(M[nbRows][2]) + neg(M[nbRows][3]))
            return false;
        ++nbRows;

        M[nbRows][0] = thoProj.comp[0][1];
        M[nbRows][1] = thoProj.comp[1][1];
        M[nbRows][2] = thoProj.comp[2][1];
    }
}

```

```

M[nbRows][3] = thoProj.speed[1];
Y[nbRows] = 1.0 - thoProj.orig[1];
if (Y[nbRows] < neg(M[nbRows][0]) + neg(M[nbRows][1]) +
    neg(M[nbRows][2]) + neg(M[nbRows][3]))
    return false;
++nbRows;

M[nbRows][0] = thoProj.comp[0][2];
M[nbRows][1] = thoProj.comp[1][2];
M[nbRows][2] = thoProj.comp[2][2];
M[nbRows][3] = thoProj.speed[2];
Y[nbRows] = 1.0 - thoProj.orig[2];
if (Y[nbRows] < neg(M[nbRows][0]) + neg(M[nbRows][1]) +
    neg(M[nbRows][2]) + neg(M[nbRows][3]))
    return false;
++nbRows;

} else {

// sum_j(V_jT+sum_iC_j,iX_i)<=1.0-sum_iO_i
M[nbRows][0] =
    thoProj.comp[0][0] + thoProj.comp[0][1] + thoProj.comp[0][2];
M[nbRows][1] =
    thoProj.comp[1][0] + thoProj.comp[1][1] + thoProj.comp[1][2];
M[nbRows][2] =
    thoProj.comp[2][0] + thoProj.comp[2][1] + thoProj.comp[2][2];
M[nbRows][3] = thoProj.speed[0] + thoProj.speed[1] + thoProj.speed[2];
Y[nbRows] = 1.0 - thoProj.orig[0] - thoProj.orig[1] - thoProj.orig[2];
if (Y[nbRows] < neg(M[nbRows][0]) + neg(M[nbRows][1]) +
    neg(M[nbRows][2]) + neg(M[nbRows][3]))
    return false;
++nbRows;

}

if (tho->type == FrameCuboid) {

// X_i <= 1.0
M[nbRows][0] = 1.0;
M[nbRows][1] = 0.0;
M[nbRows][2] = 0.0;
M[nbRows][3] = 0.0;
Y[nbRows] = 1.0;
++nbRows;

M[nbRows][0] = 0.0;
M[nbRows][1] = 1.0;
M[nbRows][2] = 0.0;
M[nbRows][3] = 0.0;
Y[nbRows] = 1.0;
++nbRows;

M[nbRows][0] = 0.0;
M[nbRows][1] = 0.0;
M[nbRows][2] = 1.0;
M[nbRows][3] = 0.0;
Y[nbRows] = 1.0;
++nbRows;

} else {

// sum_iX_i<=1.0

```

```

    M[nbRows][0] = 1.0;
    M[nbRows][1] = 1.0;
    M[nbRows][2] = 1.0;
    M[nbRows][3] = 0.0;
    Y[nbRows] = 1.0;
    ++nbRows;
}

// -X_i <= 0.0
M[nbRows][0] = -1.0;
M[nbRows][1] = 0.0;
M[nbRows][2] = 0.0;
M[nbRows][3] = 0.0;
Y[nbRows] = 0.0;
++nbRows;

M[nbRows][0] = 0.0;
M[nbRows][1] = -1.0;
M[nbRows][2] = 0.0;
M[nbRows][3] = 0.0;
Y[nbRows] = 0.0;
++nbRows;

M[nbRows][0] = 0.0;
M[nbRows][1] = 0.0;
M[nbRows][2] = -1.0;
M[nbRows][3] = 0.0;
Y[nbRows] = 0.0;
++nbRows;

// 0.0 <= t <= 1.0
M[nbRows][0] = 0.0;
M[nbRows][1] = 0.0;
M[nbRows][2] = 0.0;
M[nbRows][3] = 1.0;
Y[nbRows] = 1.0;
++nbRows;

M[nbRows][0] = 0.0;
M[nbRows][1] = 0.0;
M[nbRows][2] = 0.0;
M[nbRows][3] = -1.0;
Y[nbRows] = 0.0;
++nbRows;

// Solve the system

// Declare a AABB to memorize the bounding box of the intersection
// in the coordinates system of that
AABB3DTime bdgBoxLocal;

// Declare variables to eliminate the first variable
double Mp[49][4];
double Yp[49];
int nbRowsP;

// Eliminate the first variable in the original system
bool inconsistency =
    ElimVar3DTime(
        FST_VAR,
        M,

```

```

        Y,
        nbRows,
        4,
        Mp,
        Yp,
        &nbRowsP);

// If the system is inconsistent
if (inconsistency == true) {

    // The two Frames are not in intersection
    return false;

}

// Declare variables to eliminate the second variable
double Mpp[601][4];
double Ypp[601];
int nbRowsPP;

// Eliminate the second variable (which is the first in the new system)
inconsistency =
    ElimVar3DTime(
        FST_VAR,
        Mp,
        Yp,
        nbRowsP,
        3,
        Mpp,
        Ypp,
        &nbRowsPP);

// If the system is inconsistent
if (inconsistency == true) {

    // The two Frames are not in intersection
    return false;

}

// Declare variables to eliminate the third variable
double Mppp[90301][4];
double Yppp[90301];
int nbRowsPPP;

// Eliminate the third variable (which is the first in the new system)
inconsistency =
    ElimVar3DTime(
        FST_VAR,
        Mpp,
        Ypp,
        nbRowsPP,
        2,
        Mppp,
        Yppp,
        &nbRowsPPP);

// If the system is inconsistent
if (inconsistency == true) {

    // The two Frames are not in intersection
    return false;

}

```

```

}

// Get the bounds for the remaining fourth variable
GetBound3DTime(
    FOR_VAR,
    Mppp,
    Yppp,
    nbRowsPPP,
    &bdgBoxLocal);

// If the bounds are inconstant
if (bdgBoxLocal.min[FOR_VAR] >= bdgBoxLocal.max[FOR_VAR]) {

    // The two Frames are not in intersection
    return false;

// Else, if the bounds are consistent here it means
// the two Frames are in intersection.
// If the user hasn't requested for the resulting bounding box
} else if (bdgBox == NULL) {

    // Immediately return true
    return true;

}

// Eliminate the fourth variable (which is the second in the new
// system)
inconsistency =
    ElimVar3DTime(
        SND_VAR,
        Mpp,
        Ypp,
        nbRowsPP,
        2,
        Mppp,
        Yppp,
        &nbRowsPPP);

// Get the bounds for the remaining third variable
GetBound3DTime(
    THD_VAR,
    Mppp,
    Yppp,
    nbRowsPPP,
    &bdgBoxLocal);

// Now starts again from the initial systems and eliminate the
// third and fourth variables to get the bounds of the first and
// second variables.
// No need to check for consistency because we already know here
// that the Frames are intersecting and the system is consistent
inconsistency =
    ElimVar3DTime(
        FOR_VAR,
        M,
        Y,
        nbRows,
        4,
        Mp,
        Yp,

```

```

        &nbRowsP);

inconsistency =
    ElimVar3DTime(
        THD_VAR,
        Mp,
        Yp,
        nbRowsP,
        3,
        Mpp,
        Ypp,
        &nbRowsPP);

inconsistency =
    ElimVar3DTime(
        SND_VAR,
        Mpp,
        Ypp,
        nbRowsPP,
        2,
        Mppp,
        Yppp,
        &nbRowsPPP);

GetBound3DTime(
    FST_VAR,
    Mppp,
    Yppp,
    nbRowsPPP,
    &bdgBoxLocal);

inconsistency =
    ElimVar3DTime(
        FST_VAR,
        Mpp,
        Ypp,
        nbRowsPP,
        2,
        Mppp,
        Yppp,
        &nbRowsPPP);

GetBound3DTime(
    SND_VAR,
    Mppp,
    Yppp,
    nbRowsPPP,
    &bdgBoxLocal);

// If the user requested the resulting bounding box
if (bdgBox != NULL) {

    // Memorize the result
    *bdgBox = bdgBoxLocal;

}

// If we've reached here the two Frames are intersecting
return true;

}

```


5 Minimal example of use

In this section I give a minimal example of how to use the code given in the previous section.

5.1 2D static

```
// Include standard libraries
#include <stdlib.h>
#include <stdio.h>
#include <stdbool.h>

// Include FMB algorithm library
#include "fmb2d.h"

// Main function
int main(int argc, char** argv) {

    // Create the two objects to be tested for intersection
    double origP2D[2] = {0.0, 0.0};
    double compP2D[2][2] = {
        {1.0, 0.0}, // First component
        {0.0, 1.0}}; // Second component
    Frame2D P2D =
        Frame2DCreateStatic(
            FrameCuboid,
            origP2D,
            compP2D);

    double origQ2D[2] = {0.0, 0.0};
    double compQ2D[2][2] = {
        {1.0, 0.0},
        {0.0, 1.0}};
    Frame2D Q2D =
        Frame2DCreateStatic(
            FrameCuboid,
            origQ2D,
            compQ2D);

    // Declare a variable to memorize the result of the intersection
    // detection
    AABB2D bdgBox2DLocal;

    // Test for intersection between P and Q
    bool isIntersecting2D =
        FMBTestIntersection2D(
            &P2D,
            &Q2D,
            &bdgBox2DLocal);

    // If the two objects are intersecting
    if (isIntersecting2D) {

        printf("Intersection detected in AABB ");

        // Export the local bounding box toward the real coordinates
        // system
        AABB2D bdgBox2D;
```

```

Frame2DExportBdgBox(
    &Q2D,
    &bdgBox2DLocal,
    &bdgBox2D);

// Clip with the AABB of 'Q2D' and 'P2D' to improve results
for (int iAxis = 2;
     iAxis--;) {

    if (bdgBox2D.min[iAxis] < P2D.bdgBox.min[iAxis]) {

        bdgBox2D.min[iAxis] = P2D.bdgBox.min[iAxis];

    }
    if (bdgBox2D.max[iAxis] > P2D.bdgBox.max[iAxis]) {

        bdgBox2D.max[iAxis] = P2D.bdgBox.max[iAxis];

    }

    if (bdgBox2D.min[iAxis] < Q2D.bdgBox.min[iAxis]) {

        bdgBox2D.min[iAxis] = Q2D.bdgBox.min[iAxis];

    }
    if (bdgBox2D.max[iAxis] > Q2D.bdgBox.max[iAxis]) {

        bdgBox2D.max[iAxis] = Q2D.bdgBox.max[iAxis];

    }

}

AABB2DPrint(&bdgBox2D);
printf("\n");

// Else, the two objects are not intersecting
} else {

    printf("No intersection.\n");

}

return 0;

}

```

5.2 3D static

```

// Include standard libraries
#include <stdlib.h>
#include <stdio.h>
#include <stdbool.h>

// Include FMB algorithm library
#include "fmb3d.h"

// Main function
int main(int argc, char** argv) {

    // Create the two objects to be tested for intersection

```

```

double origP3D[3] = {0.0, 0.0, 0.0};
double compP3D[3][3] = {
    {1.0, 0.0, 0.0}, // First component
    {0.0, 1.0, 0.0}, // Second component
    {0.0, 0.0, 1.0}}; // Third component
Frame3D P3D =
    Frame3DCreateStatic(
        FrameTetrahedron,
        origP3D,
        compP3D);

double origQ3D[3] = {0.0, 0.0, 0.0};
double compQ3D[3][3] = {
    {1.0, 0.0, 0.0},
    {0.0, 1.0, 0.0},
    {0.0, 0.0, 1.0}};
Frame3D Q3D =
    Frame3DCreateStatic(
        FrameTetrahedron,
        origQ3D,
        compQ3D);

// Declare a variable to memorize the result of the intersection
// detection
AABB3D bdgBox3DLocal;

// Test for intersection between P and Q
bool isIntersecting3D =
    FMBTestIntersection3D(
        &P3D,
        &Q3D,
        &bdgBox3DLocal);

// If the two objects are intersecting
if (isIntersecting3D) {

    printf("Intersection detected in AABB ");

    // Export the local bounding box toward the real coordinates
    // system
    AABB3D bdgBox3D;
    Frame3DExportBdgBox(
        &Q3D,
        &bdgBox3DLocal,
        &bdgBox3D);

    // Clip with the AABB of 'Q3D' and 'P3D' to improve results
    for (int iAxis = 2;
        iAxis--;) {

        if (bdgBox3D.min[iAxis] < P3D.bdgBox.min[iAxis]) {

            bdgBox3D.min[iAxis] = P3D.bdgBox.min[iAxis];

        }
        if (bdgBox3D.max[iAxis] > P3D.bdgBox.max[iAxis]) {

            bdgBox3D.max[iAxis] = P3D.bdgBox.max[iAxis];

        }

        if (bdgBox3D.min[iAxis] < Q3D.bdgBox.min[iAxis]) {

```

```

        bdgBox3D.min[iAxis] = Q3D.bdgBox.min[iAxis];

    }
    if (bdgBox3D.max[iAxis] > Q3D.bdgBox.max[iAxis]) {

        bdgBox3D.max[iAxis] = Q3D.bdgBox.max[iAxis];

    }

}

AABB3DPrint(&bdgBox3D);
printf("\n");

// Else, the two objects are not intersecting
} else {

    printf("No intersection.\n");

}

return 0;
}

```

5.3 2D dynamic

```

// Include standard libraries
#include <stdlib.h>
#include <stdio.h>
#include <stdbool.h>

// Include FMB algorithm library
#include "fmb2dt.h"

// Main function
int main(int argc, char** argv) {

    // Create the two objects to be tested for intersection
    double origP2DTime[2] = {0.0, 0.0};
    double speedP2DTime[2] = {0.0, 0.0};
    double compP2DTime[2][2] = {
        {1.0, 0.0}, // First component
        {0.0, 1.0}}; // Second component
    Frame2DTime P2DTime =
        Frame2DTimeCreateStatic(
            FrameCuboid,
            origP2DTime,
            speedP2DTime,
            compP2DTime);

    double origQ2DTime[2] = {0.0, 0.0};
    double speedQ2DTime[2] = {0.0, 0.0};
    double compQ2DTime[2][2] = {
        {1.0, 0.0},
        {0.0, 1.0}};
    Frame2DTime Q2DTime =
        Frame2DTimeCreateStatic(
            FrameCuboid,
            origQ2DTime,
            speedQ2DTime,

```

```

        compQ2DTime);

// Declare a variable to memorize the result of the intersection
// detection
AABB2DTime bdgBox2DTimeLocal;

// Test for intersection between P and Q
bool isIntersecting2DTime =
    FMBTestIntersection2DTime(
        &P2DTime,
        &Q2DTime,
        &bdgBox2DTimeLocal);

// If the two objects are intersecting
if (isIntersecting2DTime) {

    printf("Intersection detected in AABB ");

    // Export the local bounding box toward the real coordinates
    // system
    AABB2DTime bdgBox2DTime;
    Frame2DTimeExportBdgBox(
        &Q2DTime,
        &bdgBox2DTimeLocal,
        &bdgBox2DTime);

    AABB2DTimePrint(&bdgBox2DTime);
    printf("\n");

// Else, the two objects are not intersecting
} else {

    printf("No intersection.\n");

}

return 0;
}

```

5.4 3D dynamic

```

// Include standard libraries
#include <stdlib.h>
#include <stdio.h>
#include <stdbool.h>

// Include FMB algorithm library
#include "fmb3dt.h"

// Main function
int main(int argc, char** argv) {

    // Create the two objects to be tested for intersection
    double origP3DTime[3] = {0.0, 0.0, 0.0};
    double speedP3DTime[3] = {0.0, 0.0, 0.0};
    double compP3DTime[3][3] = {
        {1.0, 0.0, 0.0}, // First component
        {0.0, 1.0, 0.0}, // Second component
        {0.0, 0.0, 1.0}}; // Third component
    Frame3DTime P3DTime =
        Frame3DTimeCreateStatic(

```

```

        FrameCuboid,
        origP3DTime,
        speedP3DTime,
        compP3DTime);

double origQ3DTime[3] = {0.0, 0.0, 0.0};
double speedQ3DTime[3] = {0.0, 0.0, 0.0};
double compQ3DTime[3][3] = {
    {1.0, 0.0, 0.0},
    {0.0, 1.0, 0.0},
    {0.0, 0.0, 1.0}};
Frame3DTime Q3DTime =
    Frame3DTimeCreateStatic(
        FrameCuboid,
        origQ3DTime,
        speedQ3DTime,
        compQ3DTime);

// Declare a variable to memorize the result of the intersection
// detection
AABB3DTime bdgBox3DTimeLocal;

// Test for intersection between P and Q
bool isIntersecting3DTime =
    FMBTestIntersection3DTime(
        &P3DTime,
        &Q3DTime,
        &bdgBox3DTimeLocal);

// If the two objects are intersecting
if (isIntersecting3DTime) {

    printf("Intersection detected in AABB ");

    // Export the local bounding box toward the real coordinates
    // system
    AABB3DTime bdgBox3DTime;
    Frame3DTimeExportBdgBox(
        &Q3DTime,
        &bdgBox3DTimeLocal,
        &bdgBox3DTime);

    AABB3DTimePrint(&bdgBox3DTime);
    printf("\n");

// Else, the two objects are not intersecting
} else {

    printf("No intersection.\n");

}

return 0;
}

```

6 Unit tests

In this section I introduce the code I've used to test the algorithm and its implementation. The test consists of running the algorithm on a set of cases

for which the solution has been computed by hand. The code of the implementation of the SAT algorithm is given in annex (p.211)

6.1 Code

6.1.1 2D static

```
// Include standard libraries
#include <stdlib.h>
#include <stdio.h>
#include <stdbool.h>
#include <time.h>

// Include FMB and SAT algorithm library
#include "fmb2d.h"
#include "sat.h"

// Epsilon to detect degenerated triangles
#define EPSILON 0.1
// Range of values for the random generation of Frames
#define RANGE_AXIS 100.0
// Nb of tests of the validation
#define NB_TESTS 1000000

// Helper macro to generate random number in [0.0, 1.0]
#define rnd() (double)(rand())/(double)(RAND_MAX)

// Global variables to count nb of tests resulting in intersection
// and no intersection
unsigned long int nbInter;
unsigned long int nbNoInter;

// Helper structure to pass arguments to the Validation function
typedef struct {
    FrameType type;
    double orig[2];
    double comp[2][2];
} Param2D;

// Validation function
// Takes two Frame definition as input, run the intersection test on
// them with FMB and SAT, and check the results are identical
void Validation2D(
    const Param2D paramP,
    const Param2D paramQ) {

    // Create the two Frames
    Frame2D P =
        Frame2DCreateStatic(
            paramP.type,
            paramP.orig,
            paramP.comp);

    Frame2D Q =
        Frame2DCreateStatic(
            paramQ.type,
            paramQ.orig,
```

```

        paramQ.comp);

// Helper variables to loop on the pair (that, tho) and (tho, that)
Frame2D* that = &P;
Frame2D* tho = &Q;

// Loop on pairs of Frames
for (int iPair = 2;
     iPair--;) {

    // Test intersection with FMB
    bool isIntersectingFMB =
        FMBTestIntersection2D(
            that,
            tho,
            NULL);

    // Test intersection with SAT
    bool isIntersectingSAT =
        SATTestIntersection2D(
            that,
            tho);

    // If the results are different
    if (isIntersectingFMB != isIntersectingSAT) {

        // Print the disagreement
        printf("Validation2D has failed\n");
        Frame2DPrint(that);
        printf(" against ");
        Frame2DPrint(tho);
        printf("\n");
        printf("FMB : ");
        if (isIntersectingFMB == false)
            printf("no ");
        printf("intersection\n");
        printf("SAT : ");
        if (isIntersectingSAT == false)
            printf("no ");
        printf("intersection\n");

        // Stop the validation
        exit(0);

    }

    // If the Frames are in intersection
    if (isIntersectingFMB == true) {

        // Update the number of intersection
        nbInter++;

    }

    // If the Frames are not in intersection
    } else {

        // Update the number of no intersection
        nbNoInter++;

    }

    // Flip the pair of Frames
    that = &Q;

```



```

        tho = &P;

    }

}

// Main function
void Validate2D(void) {

    // Initialise the random generator
    srand(time(NULL));

    // Declare two variables to memorize the arguments to the
    // Validation function
    Param2D paramP;
    Param2D paramQ;

    // Initialize the number of intersection and no intersection
    nbInter = 0;
    nbNoInter = 0;

    // Loop on the tests
    for (unsigned long iTest = NB_TESTS;
        iTest--;) {

        // Create two random Frame definitions
        Param2D* param = &paramP;
        for (int iParam = 2;
            iParam--;) {

            // 50% chance of being a Cuboid or a Tetrahedron
            if (rnd() < 0.5)
                param->type = FrameCuboid;
            else
                param->type = FrameTetrahedron;

            for (int iAxis = 2;
                iAxis--;) {

                param->orig[iAxis] = -RANGE_AXIS + 2.0 * rnd() * RANGE_AXIS;

                for (int iComp = 2;
                    iComp--;) {

                    param->comp[iComp][iAxis] =
                        -RANGE_AXIS + 2.0 * rnd() * RANGE_AXIS;

                }

            }

            param = &paramQ;

        }

        // Calculate the determinant of the Frames' components matrix
        double detP =
            paramP.comp[0][0] * paramP.comp[1][1] -
            paramP.comp[1][0] * paramP.comp[0][1];

        double detQ =
            paramQ.comp[0][0] * paramQ.comp[1][1] -

```

```

        paramQ.comp[1][0] * paramQ.comp[0][1];

    // If the determinants are not null, ie the Frame are not degenerate
    if (fabs(detP) > EPSILON && fabs(detQ) > EPSILON) {

        // Run the validation on the two Frames
        Validation2D(
            paramP,
            paramQ);

    }

}

// If we reached it means the validation was successfull
// Print results
printf("Validation2D has succeed.\n");
printf("Tested %lu intersections ", nbInter);
printf("and %lu no intersections\n", nbNoInter);

}

int main(int argc, char** argv) {

    printf("==== 2D static =====\n");
    Validate2D();

    return 0;
}

```

6.1.2 3D static

```

// Include standard libraries
#include <stdlib.h>
#include <stdio.h>
#include <stdbool.h>
#include <time.h>

// Include FMB and SAT algorithm library
#include "fmb3d.h"
#include "sat.h"

// Epsilon to detect degenerated triangles
#define EPSILON 0.1
// Range of values for the random generation of Frames
#define RANGE_AXIS 100.0
// Nb of tests of the validation
#define NB_TESTS 1000000

// Helper macro to generate random number in [0.0, 1.0]
#define rnd() (double)(rand())/(double)(RAND_MAX)

// Global variables to count nb of tests resulting in intersection
// and no intersection
unsigned long int nbInter;
unsigned long int nbNoInter;

// Helper structure to pass arguments to the Validation function
typedef struct {
    FrameType type;
    double orig[3];
}

```

```

    double comp[3][3];
} Param3D;

// Validation function
// Takes two Frame definition as input, run the intersection test on
// them with FMB and SAT, and check the results are identical
void Validation3D(
    const Param3D paramP,
    const Param3D paramQ) {

    // Create the two Frames
    Frame3D P =
        Frame3DCreateStatic(
            paramP.type,
            paramP.orig,
            paramP.comp);

    Frame3D Q =
        Frame3DCreateStatic(
            paramQ.type,
            paramQ.orig,
            paramQ.comp);

    // Helper variables to loop on the pair (that, tho) and (tho, that)
    Frame3D* that = &P;
    Frame3D* tho = &Q;

    // Loop on pairs of Frames
    for (int iPair = 2;
        iPair--;) {

        // Test intersection with FMB
        bool isIntersectingFMB =
            FMBTestIntersection3D(
                that,
                tho,
                NULL);

        // Test intersection with SAT
        bool isIntersectingSAT =
            SATTestIntersection3D(
                that,
                tho);

        // If the results are different
        if (isIntersectingFMB != isIntersectingSAT) {

            // Print the disagreement
            printf("Validation3D has failed\n");
            Frame3DPrint(that);
            printf(" against ");
            Frame3DPrint(tho);
            printf("\n");
            printf("FMB : ");
            if (isIntersectingFMB == false)
                printf("no ");
            printf("intersection\n");
            printf("SAT : ");
            if (isIntersectingSAT == false)
                printf("no ");
            printf("intersection\n");
        }
    }
}

```

```

        // Stop the validation
        exit(0);
    }

    // If the Frames are in intersection
    if (isIntersectingFMB == true) {

        // Update the number of intersection
        nbInter++;

    // If the Frames are not in intersection
    } else {

        // Update the number of no intersection
        nbNoInter++;

    }

    // Flip the pair of Frames
    that = &Q;
    tho = &P;

}

}

void Validate3D(void) {

    // Initialise the random generator
    srand(time(NULL));

    // Declare two variables to memorize the arguments to the
    // Validation function
    Param3D paramP;
    Param3D paramQ;

    // Initialize the number of intersection and no intersection
    nbInter = 0;
    nbNoInter = 0;

    // Loop on the tests
    for (unsigned long iTest = NB_TESTS;
        iTest--;) {

        // Create two random Frame definitions
        Param3D* param = &paramP;
        for (int iParam = 2;
            iParam--;) {

            // 50% chance of being a Cuboid or a Tetrahedron
            if (rnd() < 0.5)
                param->type = FrameCuboid;
            else
                param->type = FrameTetrahedron;

            for (int iAxis = 3;
                iAxis--;) {

                param->orig[iAxis] = -RANGE_AXIS + 2.0 * rnd() * RANGE_AXIS;

                for (int iComp = 3;

```

```

        iComp--;) {

            param->comp[iComp][iAxis] =
                -RANGE_AXIS + 2.0 * rnd() * RANGE_AXIS;

        }

    }

    param = &paramQ;

}

// Calculate the determinant of the Frames' components matrix
double detP =
    paramP.comp[0][0] * (paramP.comp[1][1] * paramP.comp[2][2] -
        paramP.comp[1][2] * paramP.comp[2][1]) -
    paramP.comp[1][0] * (paramP.comp[0][1] * paramP.comp[2][2] -
        paramP.comp[0][2] * paramP.comp[2][1]) +
    paramP.comp[2][0] * (paramP.comp[0][1] * paramP.comp[1][2] -
        paramP.comp[0][2] * paramP.comp[1][1]);

double detQ =
    paramQ.comp[0][0] * (paramQ.comp[1][1] * paramQ.comp[2][2] -
        paramQ.comp[1][2] * paramQ.comp[2][1]) -
    paramQ.comp[1][0] * (paramQ.comp[0][1] * paramQ.comp[2][2] -
        paramQ.comp[0][2] * paramQ.comp[2][1]) +
    paramQ.comp[2][0] * (paramQ.comp[0][1] * paramQ.comp[1][2] -
        paramQ.comp[0][2] * paramQ.comp[1][1]);

// If the determinants are not null, ie the Frame are not degenerate
if (fabs(detP) > EPSILON && fabs(detQ) > EPSILON) {

    // Run the validation on the two Frames
    Validation3D(
        paramP,
        paramQ);

}

}

// If we reached it means the validation was successfull
// Print results
printf("Validation3D has succeed.\n");
printf("Tested %lu intersections ", nbInter);
printf("and %lu no intersections\n", nbNoInter);

}

int main(int argc, char** argv) {

    printf("==== 3D static =====\n");
    Validate3D();

    return 0;
}

```

6.1.3 2D dynamic

```

// Include standard libraries

```

```

#include <stdlib.h>
#include <stdio.h>
#include <stdbool.h>
#include <time.h>

// Include FMB and SAT algorithm library
#include "fmb2dt.h"
#include "sat.h"

// Epsilon to detect degenerated triangles
#define EPSILON 0.1
// Range of values for the random generation of Frames
#define RANGE_AXIS 100.0
// Nb of tests of the validation
#define NB_TESTS 1000000

// Helper macro to generate random number in [0.0, 1.0]
#define rnd() (double)(rand())/(double)(RAND_MAX)

// Global variables to count nb of tests resulting in intersection
// and no intersection
unsigned long int nbInter;
unsigned long int nbNoInter;

// Helper structure to pass arguments to the Validation function
typedef struct {
    FrameType type;
    double orig[2];
    double comp[2][2];
    double speed[2];
} Param2DTime;

// Validation function
// Takes two Frame definition as input, run the intersection test on
// them with FMB and SAT, and check the results are identical
void Validation2DTime(
    const Param2DTime paramP,
    const Param2DTime paramQ) {

    // Create the two Frames
    Frame2DTime P =
        Frame2DTimeCreateStatic(
            paramP.type,
            paramP.orig,
            paramP.speed,
            paramP.comp);

    Frame2DTime Q =
        Frame2DTimeCreateStatic(
            paramQ.type,
            paramQ.orig,
            paramQ.speed,
            paramQ.comp);

    // Helper variables to loop on the pair (that, tho) and (tho, that)
    Frame2DTime* that = &P;
    Frame2DTime* tho = &Q;

    // Loop on pairs of Frames
    for (int iPair = 2;
        iPair--;) {

```

```

// Test intersection with FMB
bool isIntersectingFMB =
    FMBTestIntersection2DTime(
        that,
        tho,
        NULL);

// Test intersection with SAT
bool isIntersectingSAT =
    SATTestIntersection2DTime(
        that,
        tho);

// If the results are different
if (isIntersectingFMB != isIntersectingSAT) {

    // Print the disagreement
    printf("Validation2D has failed\n");
    Frame2DTimePrint(that);
    printf(" against ");
    Frame2DTimePrint(tho);
    printf("\n");
    printf("FMB : ");
    if (isIntersectingFMB == false)
        printf("no ");
    printf("intersection\n");
    printf("SAT : ");
    if (isIntersectingSAT == false)
        printf("no ");
    printf("intersection\n");

    // Stop the validation
    exit(0);

}

// If the Frames are in intersection
if (isIntersectingFMB == true) {

    // Update the number of intersection
    nbInter++;

// If the Frames are not in intersection
} else {

    // Update the number of no intersection
    nbNoInter++;

}

// Flip the pair of Frames
that = &Q;
tho = &P;

}

}

// Main function
void Validate2DTime(void) {

    // Initialise the random generator

```

```

srandom(time(NULL));

// Declare two variables to memorize the arguments to the
// Validation function
Param2DTime paramP;
Param2DTime paramQ;

// Initialize the number of intersection and no intersection
nbInter = 0;
nbNoInter = 0;

// Loop on the tests
for (unsigned long iTest = NB_TESTS;
     iTest--;) {

    // Create two random Frame definitions
    Param2DTime* param = &paramP;
    for (int iParam = 2;
         iParam--;) {

        // 50% chance of being a Cuboid or a Tetrahedron
        if (rnd() < 0.5)
            param->type = FrameCuboid;
        else
            param->type = FrameTetrahedron;

        for (int iAxis = 2;
             iAxis--;) {

            param->orig[iAxis] = -RANGE_AXIS + 2.0 * rnd() * RANGE_AXIS;
            param->speed[iAxis] = -RANGE_AXIS + 2.0 * rnd() * RANGE_AXIS;

            for (int iComp = 2;
                 iComp--;) {

                param->comp[iComp][iAxis] =
                    -RANGE_AXIS + 2.0 * rnd() * RANGE_AXIS;

            }

        }

        param = &paramQ;
    }

    // Calculate the determinant of the Frames' components matrix
    double detP =
        paramP.comp[0][0] * paramP.comp[1][1] -
        paramP.comp[1][0] * paramP.comp[0][1];

    double detQ =
        paramQ.comp[0][0] * paramQ.comp[1][1] -
        paramQ.comp[1][0] * paramQ.comp[0][1];

    // If the determinants are not null, ie the Frame are not degenerate
    if (fabs(detP) > EPSILON && fabs(detQ) > EPSILON) {

        // Run the validation on the two Frames
        Validation2DTime(
            paramP,
            paramQ);
    }
}

```



```

    }

}

// If we reached it means the validation was successfull
// Print results
printf("Validation2DTime has succeed.\n");
printf("Tested %lu intersections ", nbInter);
printf("and %lu no intersections\n", nbNoInter);

}

int main(int argc, char** argv) {

    printf("==== 2D dynamic =====\n");
    Validate2DTime();

    return 0;
}

```

6.1.4 3D dynamic

```

// Include standard libraries
#include <stdlib.h>
#include <stdio.h>
#include <stdbool.h>
#include <time.h>

// Include FMB and SAT algorithm library
#include "fmb3dt.h"
#include "sat.h"

// Epsilon to detect degenerated triangles
#define EPSILON 0.1
// Range of values for the random generation of Frames
#define RANGE_AXIS 100.0
// Nb of tests of the validation
#define NB_TESTS 1000000

// Helper macro to generate random number in [0.0, 1.0]
#define rnd() (double)(rand())/(double)(RAND_MAX)

// Global variables to count nb of tests resulting in intersection
// and no intersection
unsigned long int nbInter;
unsigned long int nbNoInter;

// Helper structure to pass arguments to the Validation function
typedef struct {
    FrameType type;
    double orig[3];
    double comp[3][3];
    double speed[3];
} Param3DTime;

// Validation function
// Takes two Frame definition as input, run the intersection test on
// them with FMB and SAT, and check the results are identical
void Validation3DTime(
    const Param3DTime paramP,

```

```

const Param3DTime paramQ) {

// Create the two Frames
Frame3DTime P =
    Frame3DTimeCreateStatic(
        paramP.type,
        paramP.orig,
        paramP.speed,
        paramP.comp);

Frame3DTime Q =
    Frame3DTimeCreateStatic(
        paramQ.type,
        paramQ.orig,
        paramQ.speed,
        paramQ.comp);

// Helper variables to loop on the pair (that, tho) and (tho, that)
Frame3DTime* that = &P;
Frame3DTime* tho = &Q;

// Loop on pairs of Frames
for (int iPair = 2;
    iPair--;) {

    // Test intersection with FMB
    bool isIntersectingFMB =
        FMBTestIntersection3DTime(
            that,
            tho,
            NULL);

    // Test intersection with SAT
    bool isIntersectingSAT =
        SATTestIntersection3DTime(
            that,
            tho);

    // If the results are different
    if (isIntersectingFMB != isIntersectingSAT) {

        // Print the disagreement
        printf("Validation3D has failed\n");
        Frame3DTimePrint(that);
        printf(" against ");
        Frame3DTimePrint(tho);
        printf("\n");
        printf("FMB : ");
        if (isIntersectingFMB == false)
            printf("no ");
        printf("intersection\n");
        printf("SAT : ");
        if (isIntersectingSAT == false)
            printf("no ");
        printf("intersection\n");

        // Stop the validation
        exit(0);
    }

    // If the Frames are in intersection

```

```

    if (isIntersectingFMB == true) {

        // Update the number of intersection
        nbInter++;

        // If the Frames are not in intersection
    } else {

        // Update the number of no intersection
        nbNoInter++;

    }

    // Flip the pair of Frames
    that = &Q;
    tho = &P;

}

}

// Main function
void Validate3DTime(void) {

    // Initialise the random generator
    srand(time(NULL));

    // Declare two variables to memorize the arguments to the
    // Validation function
    Param3DTime paramP;
    Param3DTime paramQ;

    // Initialize the number of intersection and no intersection
    nbInter = 0;
    nbNoInter = 0;

    // Loop on the tests
    for (unsigned long iTest = NB_TESTS;
        iTest--;) {

        // Create two random Frame definitions
        Param3DTime* param = &paramP;
        for (int iParam = 2;
            iParam--;) {

            // 50% chance of being a Cuboid or a Tetrahedron
            if (rnd() < 0.5)
                param->type = FrameCuboid;
            else
                param->type = FrameTetrahedron;

            for (int iAxis = 3;
                iAxis--;) {

                param->orig[iAxis] = -RANGE_AXIS + 2.0 * rnd() * RANGE_AXIS;
                param->speed[iAxis] = -RANGE_AXIS + 2.0 * rnd() * RANGE_AXIS;

                for (int iComp = 3;
                    iComp--;) {

                    param->comp[iComp][iAxis] =
                        -RANGE_AXIS + 2.0 * rnd() * RANGE_AXIS;

```

```

    }

}

param = &paramQ;

}

// Calculate the determinant of the Frames' components matrix
double detP =
    paramP.comp[0][0] * (paramP.comp[1][1] * paramP.comp[2][2] -
    paramP.comp[1][2] * paramP.comp[2][1]) -
    paramP.comp[1][0] * (paramP.comp[0][1] * paramP.comp[2][2] -
    paramP.comp[0][2] * paramP.comp[2][1]) +
    paramP.comp[2][0] * (paramP.comp[0][1] * paramP.comp[1][2] -
    paramP.comp[0][2] * paramP.comp[1][1]);

double detQ =
    paramQ.comp[0][0] * (paramQ.comp[1][1] * paramQ.comp[2][2] -
    paramQ.comp[1][2] * paramQ.comp[2][1]) -
    paramQ.comp[1][0] * (paramQ.comp[0][1] * paramQ.comp[2][2] -
    paramQ.comp[0][2] * paramQ.comp[2][1]) +
    paramQ.comp[2][0] * (paramQ.comp[0][1] * paramQ.comp[1][2] -
    paramQ.comp[0][2] * paramQ.comp[1][1]);

// If the determinants are not null, ie the Frame are not degenerate
if (fabs(detP) > EPSILON && fabs(detQ) > EPSILON) {

    // Run the validation on the two Frames
    Validation3DTime(
        paramP,
        paramQ);

}

}

// If we reached it means the validation was successfull
// Print results
printf("Validation3DTime has succeed.\n");
printf("Tested %lu intersections ", nbInter);
printf("and %lu no intersections\n", nbNoInter);

}

int main(int argc, char** argv) {

    printf("==== 3D dynamic =====\n");
    Validate3DTime();

    return 0;
}

```

6.2 Results

6.2.1 2D static

Co(0.000000,0.000000) x(1.000000,0.000000) y(0.000000,1.000000)
 against
 Co(0.000000,0.000000) x(1.000000,0.000000) y(0.000000,1.000000)

Succeed

Co(0.000000,0.000000) x(1.000000,0.000000) y(0.000000,1.000000)
against
Co(0.000000,0.000000) x(1.000000,0.000000) y(0.000000,1.000000)
Succeed

Co(0.000000,0.000000) x(1.000000,0.000000) y(0.000000,1.000000)
against
Co(0.500000,0.500000) x(1.000000,0.000000) y(0.000000,1.000000)
Succeed

Co(0.500000,0.500000) x(1.000000,0.000000) y(0.000000,1.000000)
against
Co(0.000000,0.000000) x(1.000000,0.000000) y(0.000000,1.000000)
Succeed

Co(-0.500000,-0.500000) x(1.000000,0.000000) y(0.000000,1.000000)
against
Co(0.500000,0.500000) x(1.000000,0.000000) y(0.000000,1.000000)
Succeed

Co(0.500000,0.500000) x(1.000000,0.000000) y(0.000000,1.000000)
against
Co(-0.500000,-0.500000) x(1.000000,0.000000) y(0.000000,1.000000)
Succeed

Co(0.000000,0.000000) x(1.000000,0.000000) y(0.000000,1.000000)
against
Co(0.250000,-0.250000) x(0.500000,0.000000) y(0.000000,2.000000)
Succeed

Co(0.250000,-0.250000) x(0.500000,0.000000) y(0.000000,2.000000)
against
Co(0.000000,0.000000) x(1.000000,0.000000) y(0.000000,1.000000)
Succeed

Co(0.000000,0.000000) x(1.000000,0.000000) y(0.000000,1.000000)
against
Co(-0.250000,0.250000) x(2.000000,0.000000) y(0.000000,0.500000)
Succeed

Co(-0.250000,0.250000) x(2.000000,0.000000) y(0.000000,0.500000)
against
Co(0.000000,0.000000) x(1.000000,0.000000) y(0.000000,1.000000)
Succeed

Co(0.000000,0.000000) x(1.000000,1.000000) y(-1.000000,1.000000)
against
Co(0.000000,0.000000) x(1.000000,0.000000) y(0.000000,1.000000)
Succeed

Co(0.000000,0.000000) x(1.000000,0.000000) y(0.000000,1.000000)
against
Co(0.000000,0.000000) x(1.000000,1.000000) y(-1.000000,1.000000)
Succeed

Co(-0.500000,-0.500000) x(1.000000,1.000000) y(-1.000000,1.000000)
against
Co(0.000000,0.000000) x(1.000000,0.000000) y(0.000000,1.000000)
Succeed

```

Co(0.000000,0.000000) x(1.000000,0.000000) y(0.000000,1.000000)
against
Co(-0.500000,-0.500000) x(1.000000,1.000000) y(-1.000000,1.000000)
Succeed

Co(1.500000,1.500000) x(1.000000,-1.000000) y(-1.000000,-1.000000)
against
Co(1.000000,0.000000) x(-1.000000,0.000000) y(0.000000,1.000000)
Succeed

Co(1.000000,0.000000) x(-1.000000,0.000000) y(0.000000,1.000000)
against
Co(1.500000,1.500000) x(1.000000,-1.000000) y(-1.000000,-1.000000)
Succeed

Co(1.000000,0.500000) x(-0.500000,0.500000) y(-0.500000,-0.500000)
against
Co(0.000000,1.000000) x(1.000000,0.000000) y(0.000000,-1.000000)
Succeed

Co(0.000000,1.000000) x(1.000000,0.000000) y(0.000000,-1.000000)
against
Co(1.000000,0.500000) x(-0.500000,0.500000) y(-0.500000,-0.500000)
Succeed

Co(0.000000,0.000000) x(1.000000,0.000000) y(1.000000,1.000000)
against
Co(2.000000,-1.000000) x(0.000000,1.000000) y(-0.500000,1.000000)
Succeed

Co(2.000000,-1.000000) x(0.000000,1.000000) y(-0.500000,1.000000)
against
Co(0.000000,0.000000) x(1.000000,0.000000) y(1.000000,1.000000)
Succeed

Co(0.000000,0.000000) x(1.000000,0.500000) y(0.500000,1.000000)
against
Co(1.000000,1.000000) x(-0.500000,-0.500000) y(0.000000,-1.000000)
Succeed

Co(1.000000,1.000000) x(-0.500000,-0.500000) y(0.000000,-1.000000)
against
Co(0.000000,0.000000) x(1.000000,0.500000) y(0.500000,1.000000)
Succeed

Co(0.000000,0.000000) x(1.000000,0.500000) y(0.500000,1.000000)
against
Co(1.000000,2.000000) x(-0.500000,-0.500000) y(0.000000,-1.000000)
Succeed

Co(1.000000,2.000000) x(-0.500000,-0.500000) y(0.000000,-1.000000)
against
Co(0.000000,0.000000) x(1.000000,0.500000) y(0.500000,1.000000)
Succeed

To(0.000000,0.000000) x(1.000000,0.500000) y(0.500000,1.000000)
against
Co(1.000000,2.000000) x(-0.500000,-0.500000) y(0.000000,-1.000000)
Succeed

Co(1.000000,2.000000) x(-0.500000,-0.500000) y(0.000000,-1.000000)
against

```

```

To(0.000000,0.000000) x(1.000000,0.500000) y(0.500000,1.000000)
Succeed

Co(0.000000,0.000000) x(1.000000,0.500000) y(0.500000,1.000000)
against
To(1.000000,2.000000) x(-0.500000,-0.500000) y(0.000000,-1.000000)
Succeed

To(1.000000,2.000000) x(-0.500000,-0.500000) y(0.000000,-1.000000)
against
Co(0.000000,0.000000) x(1.000000,0.500000) y(0.500000,1.000000)
Succeed

Co(0.000000,0.000000) x(1.000000,0.000000) y(0.000000,1.000000)
against
To(0.000000,0.000000) x(1.000000,0.000000) y(0.000000,1.000000)
Succeed

To(0.000000,0.000000) x(1.000000,0.000000) y(0.000000,1.000000)
against
Co(0.000000,0.000000) x(1.000000,0.000000) y(0.000000,1.000000)
Succeed

Co(0.000000,0.000000) x(1.000000,0.000000) y(0.000000,1.000000)
against
To(0.000000,-0.500000) x(1.000000,0.000000) y(0.000000,1.000000)
Succeed

To(0.000000,-0.500000) x(1.000000,0.000000) y(0.000000,1.000000)
against
Co(0.000000,0.000000) x(1.000000,0.000000) y(0.000000,1.000000)
Succeed

Co(0.500000,0.500000) x(-0.500000,0.000000) y(0.000000,-0.500000)
against
To(0.000000,-0.500000) x(1.000000,0.000000) y(0.000000,1.000000)
Succeed

To(0.000000,-0.500000) x(1.000000,0.000000) y(0.000000,1.000000)
against
Co(0.500000,0.500000) x(-0.500000,0.000000) y(0.000000,-0.500000)
Succeed

Co(0.500000,0.500000) x(1.000000,0.000000) y(0.000000,1.000000)
against
To(0.000000,0.000000) x(1.000000,0.000000) y(0.000000,1.000000)
Succeed

To(0.000000,0.000000) x(1.000000,0.000000) y(0.000000,1.000000)
against
Co(0.500000,0.500000) x(1.000000,0.000000) y(0.000000,1.000000)
Succeed

Co(0.000000,0.000000) x(1.000000,0.000000) y(0.000000,1.000000)
against
To(1.500000,1.500000) x(-1.500000,0.000000) y(0.000000,-1.500000)
Succeed

To(1.500000,1.500000) x(-1.500000,0.000000) y(0.000000,-1.500000)
against
Co(0.000000,0.000000) x(1.000000,0.000000) y(0.000000,1.000000)
Succeed

```

```

To(0.000000,0.000000) x(1.000000,0.000000) y(0.000000,1.000000)
against
To(1.010000,1.010000) x(-1.000000,0.000000) y(0.000000,-1.000000)
Succeed

To(1.010000,1.010000) x(-1.000000,0.000000) y(0.000000,-1.000000)
against
To(0.000000,0.000000) x(1.000000,0.000000) y(0.000000,1.000000)
Succeed

To(0.000000,0.000000) x(1.000000,0.500000) y(0.500000,1.000000)
against
To(1.000000,1.000000) x(-0.500000,-0.500000) y(0.000000,-1.000000)
Succeed

To(1.000000,1.000000) x(-0.500000,-0.500000) y(0.000000,-1.000000)
against
To(0.000000,0.000000) x(1.000000,0.500000) y(0.500000,1.000000)
Succeed

To(0.000000,0.000000) x(1.000000,0.500000) y(0.500000,1.000000)
against
To(1.010000,1.500000) x(-0.500000,-0.500000) y(0.000000,-1.000000)
Succeed

To(1.010000,1.500000) x(-0.500000,-0.500000) y(0.000000,-1.000000)
against
To(0.000000,0.000000) x(1.000000,0.500000) y(0.500000,1.000000)
Succeed

```

All unit tests 2D have succeed.

6.2.2 3D static

```

Co(0.000000,0.000000,0.000000) x(1.000000,0.000000,0.000000) y
(0.000000,1.000000,0.000000) z(0.000000,0.000000,1.000000)
against
Co(0.000000,0.000000,0.000000) x(1.000000,0.000000,0.000000) y
(0.000000,1.000000,0.000000) z(0.000000,0.000000,1.000000)
Succeed

Co(0.000000,0.000000,0.000000) x(1.000000,0.000000,0.000000) y
(0.000000,1.000000,0.000000) z(0.000000,0.000000,1.000000)
against
Co(0.000000,0.000000,0.000000) x(1.000000,0.000000,0.000000) y
(0.000000,1.000000,0.000000) z(0.000000,0.000000,1.000000)
Succeed

Co(0.000000,0.000000,0.000000) x(1.000000,0.000000,0.000000) y
(0.000000,1.000000,0.000000) z(0.000000,0.000000,1.000000)
against
Co(0.500000,0.500000,0.500000) x(1.000000,0.000000,0.000000) y
(0.000000,1.000000,0.000000) z(0.000000,0.000000,1.000000)
Succeed

Co(0.500000,0.500000,0.500000) x(1.000000,0.000000,0.000000) y
(0.000000,1.000000,0.000000) z(0.000000,0.000000,1.000000)
against
Co(0.000000,0.000000,0.000000) x(1.000000,0.000000,0.000000) y
(0.000000,1.000000,0.000000) z(0.000000,0.000000,1.000000)

```


[illegible]

```

(0.000000,1.000000,0.000000) z(0.000000,0.000000,1.000000)
Failed
Expected : no intersection
Got : intersection

```

6.2.3 2D dynamic

```

Co(0.000000,0.000000) s(0.000000,0.000000) x(1.000000,0.000000) y
(0.000000,1.000000)
against
Co(-1.000000,0.000000) s(-1.000000,0.000000) x(1.000000,0.000000) y
(0.000000,1.000000)
Succeed

```

```

Co(-1.000000,0.000000) s(-1.000000,0.000000) x(1.000000,0.000000) y
(0.000000,1.000000)
against
Co(0.000000,0.000000) s(0.000000,0.000000) x(1.000000,0.000000) y
(0.000000,1.000000)
Succeed

```

```

Co(0.000000,0.000000) s(0.000000,0.000000) x(1.000000,0.000000) y
(0.000000,1.000000)
against
Co(-1.000000,-1.000000) s(1.000000,0.000000) x(1.000000,0.000000) y
(0.000000,1.000000)
Failed
Expected : no intersection
Got : intersection

```

6.2.4 3D dynamic

```

Co(0.000000,0.000000,0.000000) s(0.000000,0.000000,0.000000) x
(1.000000,0.000000,0.000000) y(0.000000,1.000000,0.000000) z
(0.000000,0.000000,1.000000)
against
Co(-1.000000,0.000000,0.000000) s(-1.000000,0.000000,0.000000) x
(1.000000,0.000000,0.000000) y(0.000000,1.000000,0.000000) z
(0.000000,0.000000,1.000000)
Succeed

```

```

Co(-1.000000,0.000000,0.000000) s(-1.000000,0.000000,0.000000) x
(1.000000,0.000000,0.000000) y(0.000000,1.000000,0.000000) z
(0.000000,0.000000,1.000000)
against
Co(0.000000,0.000000,0.000000) s(0.000000,0.000000,0.000000) x
(1.000000,0.000000,0.000000) y(0.000000,1.000000,0.000000) z
(0.000000,0.000000,1.000000)
Succeed

```

```

Co(0.000000,0.000000,0.000000) s(0.000000,0.000000,0.000000) x
(1.000000,0.000000,0.000000) y(0.000000,1.000000,0.000000) z
(0.000000,0.000000,1.000000)
against
Co(-1.000000,-1.000000,0.000000) s(1.000000,0.000000,0.000000) x
(1.000000,0.000000,0.000000) y(0.000000,1.000000,0.000000) z
(0.000000,0.000000,1.000000)
Failed
Expected : no intersection
Got : intersection

```

7 Validation against SAT

In this section I introduce the code I've used to validate the algorithm and its implementation. The validation consists of running the FMB algorithm on randomly generated pairs of Frame and check that its result is equal to the one of running the SAT algorithm on the same pair of Frames. The code of the implementation of the SAT algorithm is given in annex (p.211)

7.1 Code

7.1.1 2D static

```
// Include standard libraries
#include <stdlib.h>
#include <stdio.h>
#include <stdbool.h>
#include <time.h>

// Include FMB and SAT algorithm library
#include "fmb2d.h"
#include "sat.h"

// Epsilon to detect degenerated triangles
#define EPSILON 0.1
// Range of values for the random generation of Frames
#define RANGE_AXIS 100.0
// Nb of tests of the validation
#define NB_TESTS 1000000

// Helper macro to generate random number in [0.0, 1.0]
#define rnd() (double)(rand())/(double)(RAND_MAX)

// Global variables to count nb of tests resulting in intersection
// and no intersection
unsigned long int nbInter;
unsigned long int nbNoInter;

// Helper structure to pass arguments to the Validation function
typedef struct {
    FrameType type;
    double orig[2];
    double comp[2][2];
} Param2D;

// Validation function
// Takes two Frame definition as input, run the intersection test on
// them with FMB and SAT, and check the results are identical
void Validation2D(
    const Param2D paramP,
    const Param2D paramQ) {

    // Create the two Frames
    Frame2D P =
        Frame2DCreateStatic(
            paramP.type,
```

```

        paramP.orig,
        paramP.comp);

Frame2D Q =
    Frame2DCreateStatic(
        paramQ.type,
        paramQ.orig,
        paramQ.comp);

// Helper variables to loop on the pair (that, tho) and (tho, that)
Frame2D* that = &P;
Frame2D* tho = &Q;

// Loop on pairs of Frames
for (int iPair = 2;
     iPair--;) {

    // Test intersection with FMB
    bool isIntersectingFMB =
        FMBTestIntersection2D(
            that,
            tho,
            NULL);

    // Test intersection with SAT
    bool isIntersectingSAT =
        SATTestIntersection2D(
            that,
            tho);

    // If the results are different
    if (isIntersectingFMB != isIntersectingSAT) {

        // Print the disagreement
        printf("Validation2D has failed\n");
        Frame2DPrint(that);
        printf(" against ");
        Frame2DPrint(tho);
        printf("\n");
        printf("FMB : ");
        if (isIntersectingFMB == false)
            printf("no ");
        printf("intersection\n");
        printf("SAT : ");
        if (isIntersectingSAT == false)
            printf("no ");
        printf("intersection\n");

        // Stop the validation
        exit(0);

    }

    // If the Frames are in intersection
    if (isIntersectingFMB == true) {

        // Update the number of intersection
        nbInter++;

    }

    // If the Frames are not in intersection
} else {

```

```

        // Update the number of no intersection
        nbNoInter++;

    }

    // Flip the pair of Frames
    that = &Q;
    tho = &P;

}

}

// Main function
void Validate2D(void) {

    // Initialise the random generator
    srand(time(NULL));

    // Declare two variables to memorize the arguments to the
    // Validation function
    Param2D paramP;
    Param2D paramQ;

    // Initialize the number of intersection and no intersection
    nbInter = 0;
    nbNoInter = 0;

    // Loop on the tests
    for (unsigned long iTest = NB_TESTS;
        iTest--;) {

        // Create two random Frame definitions
        Param2D* param = &paramP;
        for (int iParam = 2;
            iParam--;) {

            // 50% chance of being a Cuboid or a Tetrahedron
            if (rnd() < 0.5)
                param->type = FrameCuboid;
            else
                param->type = FrameTetrahedron;

            for (int iAxis = 2;
                iAxis--;) {

                param->orig[iAxis] = -RANGE_AXIS + 2.0 * rnd() * RANGE_AXIS;

                for (int iComp = 2;
                    iComp--;) {

                    param->comp[iComp][iAxis] =
                        -RANGE_AXIS + 2.0 * rnd() * RANGE_AXIS;

                }

            }

            param = &paramQ;

        }

    }
}

```

```

    // Calculate the determinant of the Frames' components matrix
    double detP =
        paramP.comp[0][0] * paramP.comp[1][1] -
        paramP.comp[1][0] * paramP.comp[0][1];

    double detQ =
        paramQ.comp[0][0] * paramQ.comp[1][1] -
        paramQ.comp[1][0] * paramQ.comp[0][1];

    // If the determinants are not null, ie the Frame are not degenerate
    if (fabs(detP) > EPSILON && fabs(detQ) > EPSILON) {

        // Run the validation on the two Frames
        Validation2D(
            paramP,
            paramQ);

    }

}

// If we reached it means the validation was successfull
// Print results
printf("Validation2D has succeed.\n");
printf("Tested %lu intersections ", nbInter);
printf("and %lu no intersections\n", nbNoInter);

}

int main(int argc, char** argv) {

    printf("==== 2D static =====\n");
    Validate2D();

    return 0;
}

```

7.1.2 3D static

```

// Include standard libraries
#include <stdlib.h>
#include <stdio.h>
#include <stdbool.h>
#include <time.h>

// Include FMB and SAT algorithm library
#include "fmb3d.h"
#include "sat.h"

// Epsilon to detect degenerated triangles
#define EPSILON 0.1
// Range of values for the random generation of Frames
#define RANGE_AXIS 100.0
// Nb of tests of the validation
#define NB_TESTS 1000000

// Helper macro to generate random number in [0.0, 1.0]
#define rnd() (double)(rand())/(double)(RAND_MAX)

// Global variables to count nb of tests resulting in intersection
// and no intersection

```

```

unsigned long int nbInter;
unsigned long int nbNoInter;

// Helper structure to pass arguments to the Validation function
typedef struct {
    FrameType type;
    double orig[3];
    double comp[3][3];
} Param3D;

// Validation function
// Takes two Frame definition as input, run the intersection test on
// them with FMB and SAT, and check the results are identical
void Validation3D(
    const Param3D paramP,
    const Param3D paramQ) {

    // Create the two Frames
    Frame3D P =
        Frame3DCreateStatic(
            paramP.type,
            paramP.orig,
            paramP.comp);

    Frame3D Q =
        Frame3DCreateStatic(
            paramQ.type,
            paramQ.orig,
            paramQ.comp);

    // Helper variables to loop on the pair (that, tho) and (tho, that)
    Frame3D* that = &P;
    Frame3D* tho = &Q;

    // Loop on pairs of Frames
    for (int iPair = 2;
        iPair--;) {

        // Test intersection with FMB
        bool isIntersectingFMB =
            FMBTestIntersection3D(
                that,
                tho,
                NULL);

        // Test intersection with SAT
        bool isIntersectingSAT =
            SATTestIntersection3D(
                that,
                tho);

        // If the results are different
        if (isIntersectingFMB != isIntersectingSAT) {

            // Print the disagreement
            printf("Validation3D has failed\n");
            Frame3DPrint(that);
            printf(" against ");
            Frame3DPrint(tho);
            printf("\n");
            printf("FMB : ");
            if (isIntersectingFMB == false)

```

```

        printf("no ");
        printf("intersection\n");
        printf("SAT : ");
        if (isIntersectingSAT == false)
            printf("no ");
        printf("intersection\n");

        // Stop the validation
        exit(0);
    }

    // If the Frames are in intersection
    if (isIntersectingFMB == true) {

        // Update the number of intersection
        nbInter++;

        // If the Frames are not in intersection
    } else {

        // Update the number of no intersection
        nbNoInter++;

    }

    // Flip the pair of Frames
    that = &Q;
    tho = &P;

}

}

void Validate3D(void) {

    // Initialise the random generator
    srand(time(NULL));

    // Declare two variables to memorize the arguments to the
    // Validation function
    Param3D paramP;
    Param3D paramQ;

    // Initialize the number of intersection and no intersection
    nbInter = 0;
    nbNoInter = 0;

    // Loop on the tests
    for (unsigned long iTest = NB_TESTS;
         iTest--;) {

        // Create two random Frame definitions
        Param3D* param = &paramP;
        for (int iParam = 2;
             iParam--;) {

            // 50% chance of being a Cuboid or a Tetrahedron
            if (rnd() < 0.5)
                param->type = FrameCuboid;
            else
                param->type = FrameTetrahedron;
        }
    }
}

```



```

    for (int iAxis = 3;
        iAxis--;) {

        param->orig[iAxis] = -RANGE_AXIS + 2.0 * rnd() * RANGE_AXIS;

        for (int iComp = 3;
            iComp--;) {

            param->comp[iComp][iAxis] =
                -RANGE_AXIS + 2.0 * rnd() * RANGE_AXIS;

        }

    }

    param = &paramQ;

}

// Calculate the determinant of the Frames' components matrix
double detP =
    paramP.comp[0][0] * (paramP.comp[1][1] * paramP.comp[2][2] -
        paramP.comp[1][2] * paramP.comp[2][1]) -
    paramP.comp[1][0] * (paramP.comp[0][1] * paramP.comp[2][2] -
        paramP.comp[0][2] * paramP.comp[2][1]) +
    paramP.comp[2][0] * (paramP.comp[0][1] * paramP.comp[1][2] -
        paramP.comp[0][2] * paramP.comp[1][1]);

double detQ =
    paramQ.comp[0][0] * (paramQ.comp[1][1] * paramQ.comp[2][2] -
        paramQ.comp[1][2] * paramQ.comp[2][1]) -
    paramQ.comp[1][0] * (paramQ.comp[0][1] * paramQ.comp[2][2] -
        paramQ.comp[0][2] * paramQ.comp[2][1]) +
    paramQ.comp[2][0] * (paramQ.comp[0][1] * paramQ.comp[1][2] -
        paramQ.comp[0][2] * paramQ.comp[1][1]);

// If the determinants are not null, ie the Frame are not degenerate
if (fabs(detP) > EPSILON && fabs(detQ) > EPSILON) {

    // Run the validation on the two Frames
    Validation3D(
        paramP,
        paramQ);

}

}

// If we reached it means the validation was successfull
// Print results
printf("Validation3D has succeed.\n");
printf("Tested %lu intersections ", nbInter);
printf("and %lu no intersections\n", nbNoInter);

}

int main(int argc, char** argv) {

    printf("==== 3D static =====\n");
    Validate3D();

```

```

    return 0;
}

```

7.1.3 2D dynamic

```

// Include standard libraries
#include <stdlib.h>
#include <stdio.h>
#include <stdbool.h>
#include <time.h>

// Include FMB and SAT algorithm library
#include "fmb2dt.h"
#include "sat.h"

// Epsilon to detect degenerated triangles
#define EPSILON 0.1
// Range of values for the random generation of Frames
#define RANGE_AXIS 100.0
// Nb of tests of the validation
#define NB_TESTS 1000000

// Helper macro to generate random number in [0.0, 1.0]
#define rnd() (double)(rand())/(double)(RAND_MAX)

// Global variables to count nb of tests resulting in intersection
// and no intersection
unsigned long int nbInter;
unsigned long int nbNoInter;

// Helper structure to pass arguments to the Validation function
typedef struct {
    FrameType type;
    double orig[2];
    double comp[2][2];
    double speed[2];
} Param2DTime;

// Validation function
// Takes two Frame definition as input, run the intersection test on
// them with FMB and SAT, and check the results are identical
void Validation2DTime(
    const Param2DTime paramP,
    const Param2DTime paramQ) {

    // Create the two Frames
    Frame2DTime P =
        Frame2DTimeCreateStatic(
            paramP.type,
            paramP.orig,
            paramP.speed,
            paramP.comp);

    Frame2DTime Q =
        Frame2DTimeCreateStatic(
            paramQ.type,
            paramQ.orig,
            paramQ.speed,
            paramQ.comp);

    // Helper variables to loop on the pair (that, tho) and (tho, that)

```

```

Frame2DTime* that = &P;
Frame2DTime* tho = &Q;

// Loop on pairs of Frames
for (int iPair = 2;
     iPair--;) {

    // Test intersection with FMB
    bool isIntersectingFMB =
        FMBTestIntersection2DTime(
            that,
            tho,
            NULL);

    // Test intersection with SAT
    bool isIntersectingSAT =
        SATTestIntersection2DTime(
            that,
            tho);

    // If the results are different
    if (isIntersectingFMB != isIntersectingSAT) {

        // Print the disagreement
        printf("Validation2D has failed\n");
        Frame2DTimePrint(that);
        printf(" against ");
        Frame2DTimePrint(tho);
        printf("\n");
        printf("FMB : ");
        if (isIntersectingFMB == false)
            printf("no ");
        printf("intersection\n");
        printf("SAT : ");
        if (isIntersectingSAT == false)
            printf("no ");
        printf("intersection\n");

        // Stop the validation
        exit(0);

    }

    // If the Frames are in intersection
    if (isIntersectingFMB == true) {

        // Update the number of intersection
        nbInter++;

    } else {

        // Update the number of no intersection
        nbNoInter++;

    }

    // Flip the pair of Frames
    that = &Q;
    tho = &P;

}

```

```

}

// Main function
void Validate2DTime(void) {

    // Initialise the random generator
    srand(time(NULL));

    // Declare two variables to memorize the arguments to the
    // Validation function
    Param2DTime paramP;
    Param2DTime paramQ;

    // Initialize the number of intersection and no intersection
    nbInter = 0;
    nbNoInter = 0;

    // Loop on the tests
    for (unsigned long iTest = NB_TESTS;
        iTest--;) {

        // Create two random Frame definitions
        Param2DTime* param = &paramP;
        for (int iParam = 2;
            iParam--;) {

            // 50% chance of being a Cuboid or a Tetrahedron
            if (rnd() < 0.5)
                param->type = FrameCuboid;
            else
                param->type = FrameTetrahedron;

            for (int iAxis = 2;
                iAxis--;) {

                param->orig[iAxis] = -RANGE_AXIS + 2.0 * rnd() * RANGE_AXIS;
                param->speed[iAxis] = -RANGE_AXIS + 2.0 * rnd() * RANGE_AXIS;

                for (int iComp = 2;
                    iComp--;) {

                    param->comp[iComp][iAxis] =
                        -RANGE_AXIS + 2.0 * rnd() * RANGE_AXIS;

                }

            }

            param = &paramQ;

        }

        // Calculate the determinant of the Frames' components matrix
        double detP =
            paramP.comp[0][0] * paramP.comp[1][1] -
            paramP.comp[1][0] * paramP.comp[0][1];

        double detQ =
            paramQ.comp[0][0] * paramQ.comp[1][1] -
            paramQ.comp[1][0] * paramQ.comp[0][1];

```

```

    // If the determinants are not null, ie the Frame are not degenerate
    if (fabs(detP) > EPSILON && fabs(detQ) > EPSILON) {

        // Run the validation on the two Frames
        Validation2DTime(
            paramP,
            paramQ);

    }

}

// If we reached it means the validation was successfull
// Print results
printf("Validation2DTime has succeed.\n");
printf("Tested %lu intersections ", nbInter);
printf("and %lu no intersections\n", nbNoInter);

}

int main(int argc, char** argv) {

    printf("==== 2D dynamic =====\n");
    Validate2DTime();

    return 0;
}

```

7.1.4 3D dynamic

```

// Include standard libraries
#include <stdlib.h>
#include <stdio.h>
#include <stdbool.h>
#include <time.h>

// Include FMB and SAT algorithm library
#include "fmb3dt.h"
#include "sat.h"

// Epsilon to detect degenerated triangles
#define EPSILON 0.1
// Range of values for the random generation of Frames
#define RANGE_AXIS 100.0
// Nb of tests of the validation
#define NB_TESTS 1000000

// Helper macro to generate random number in [0.0, 1.0]
#define rnd() (double)(rand())/(double)(RAND_MAX)

// Global variables to count nb of tests resulting in intersection
// and no intersection
unsigned long int nbInter;
unsigned long int nbNoInter;

// Helper structure to pass arguments to the Validation function
typedef struct {
    FrameType type;
    double orig[3];
    double comp[3][3];
    double speed[3];
}

```

```

} Param3DTime;

// Validation function
// Takes two Frame definition as input, run the intersection test on
// them with FMB and SAT, and check the results are identical
void Validation3DTime(
    const Param3DTime paramP,
    const Param3DTime paramQ) {

    // Create the two Frames
    Frame3DTime P =
        Frame3DTimeCreateStatic(
            paramP.type,
            paramP.orig,
            paramP.speed,
            paramP.comp);

    Frame3DTime Q =
        Frame3DTimeCreateStatic(
            paramQ.type,
            paramQ.orig,
            paramQ.speed,
            paramQ.comp);

    // Helper variables to loop on the pair (that, tho) and (tho, that)
    Frame3DTime* that = &P;
    Frame3DTime* tho = &Q;

    // Loop on pairs of Frames
    for (int iPair = 2;
        iPair--;) {

        // Test intersection with FMB
        bool isIntersectingFMB =
            FMBTestIntersection3DTime(
                that,
                tho,
                NULL);

        // Test intersection with SAT
        bool isIntersectingSAT =
            SATTestIntersection3DTime(
                that,
                tho);

        // If the results are different
        if (isIntersectingFMB != isIntersectingSAT) {

            // Print the disagreement
            printf("Validation3D has failed\n");
            Frame3DTimePrint(that);
            printf(" against ");
            Frame3DTimePrint(tho);
            printf("\n\n");
            printf("FMB : ");
            if (isIntersectingFMB == false)
                printf("no ");
            printf("intersection\n");
            printf("SAT : ");
            if (isIntersectingSAT == false)
                printf("no ");
            printf("intersection\n");
        }
    }
}

```

```

        // Stop the validation
        exit(0);
    }

    // If the Frames are in intersection
    if (isIntersectingFMB == true) {

        // Update the number of intersection
        nbInter++;

    // If the Frames are not in intersection
    } else {

        // Update the number of no intersection
        nbNoInter++;

    }

    // Flip the pair of Frames
    that = &Q;
    tho = &P;
}

}

// Main function
void Validate3DTime(void) {

    // Initialise the random generator
    srand(time(NULL));

    // Declare two variables to memorize the arguments to the
    // Validation function
    Param3DTime paramP;
    Param3DTime paramQ;

    // Initialize the number of intersection and no intersection
    nbInter = 0;
    nbNoInter = 0;

    // Loop on the tests
    for (unsigned long iTest = NB_TESTS;
        iTest--;) {

        // Create two random Frame definitions
        Param3DTime* param = &paramP;
        for (int iParam = 2;
            iParam--;) {

            // 50% chance of being a Cuboid or a Tetrahedron
            if (rnd() < 0.5)
                param->type = FrameCuboid;
            else
                param->type = FrameTetrahedron;

            for (int iAxis = 3;
                iAxis--;) {

                param->orig[iAxis] = -RANGE_AXIS + 2.0 * rnd() * RANGE_AXIS;
            }
        }
    }
}

```

```

        param->speed[iAxis] = -RANGE_AXIS + 2.0 * rnd() * RANGE_AXIS;

        for (int iComp = 3;
             iComp--;) {

            param->comp[iComp][iAxis] =
                -RANGE_AXIS + 2.0 * rnd() * RANGE_AXIS;

        }

    }

    param = &paramQ;

}

// Calculate the determinant of the Frames' components matrix
double detP =
    paramP.comp[0][0] * (paramP.comp[1][1] * paramP.comp[2][2] -
        paramP.comp[1][2] * paramP.comp[2][1]) -
    paramP.comp[1][0] * (paramP.comp[0][1] * paramP.comp[2][2] -
        paramP.comp[0][2] * paramP.comp[2][1]) +
    paramP.comp[2][0] * (paramP.comp[0][1] * paramP.comp[1][2] -
        paramP.comp[0][2] * paramP.comp[1][1]);

double detQ =
    paramQ.comp[0][0] * (paramQ.comp[1][1] * paramQ.comp[2][2] -
        paramQ.comp[1][2] * paramQ.comp[2][1]) -
    paramQ.comp[1][0] * (paramQ.comp[0][1] * paramQ.comp[2][2] -
        paramQ.comp[0][2] * paramQ.comp[2][1]) +
    paramQ.comp[2][0] * (paramQ.comp[0][1] * paramQ.comp[1][2] -
        paramQ.comp[0][2] * paramQ.comp[1][1]);

// If the determinants are not null, ie the Frame are not degenerate
if (fabs(detP) > EPSILON && fabs(detQ) > EPSILON) {

    // Run the validation on the two Frames
    Validation3DTime(
        paramP,
        paramQ);

}

}

// If we reached it means the validation was successfull
// Print results
printf("Validation3DTime has succeed.\n");
printf("Tested %lu intersections ", nbInter);
printf("and %lu no intersections\n", nbNoInter);

}

int main(int argc, char** argv) {

    printf("==== 3D dynamic =====\n");
    Validate3DTime();

    return 0;
}


```


7.2 Results

7.2.1 Failures

Validation has failed in one case: when one or both of the frame are degenerated (at least two of there components ae colinear). An example is given below for reference:

```
===== 2D static =====  
Validation2D has failed  
Co(-63.571705,-22.581119) x(55.239119,38.152177) y(-62.031537,-42.843548) against To(3.474294,22.751011)  
x(-49.195251,84.166201) y(41.179031,-95.350316)  
FMB : intersection  
SAT : no intersection
```



This case can be detected and avoided prior to the intersection test by checking the determinant of the frame: degenerated frames have a null determinant. In the example above the determinant of the first frame is equal to -0.001667.

7.2.2 2D static

```
===== 2D static =====  
Validation2D has succeed.  
Tested 470322 intersections and 1529598 no intersections
```

7.2.3 2D dynamic

```

===== 2D dynamic =====
Validation2DTime has succeed.
Tested 741478 intersections and 1258454 no intersections

```

7.2.4 3D static

```

===== 3D static =====
Validation3D has succeed.
Tested 315464 intersections and 1684532 no intersections

```

7.2.5 3D dynamic

```

===== 3D dynamic =====
Validation3DTime has succeed.
Tested 523506 intersections and 1476492 no intersections

```

8 Qualification against SAT

In this section I introduce the code I've used to qualify the algorithm and its implementation. The qualification consists of running the FMB algorithm on randomly generated pairs of Frame, and check its execution time against the one of running the SAT algorithm on the same pair of Frames.

8.1 Code

8.1.1 2D static

```

// Include standard libraries
#include <stdlib.h>
#include <stdio.h>
#include <stdbool.h>
#include <time.h>
#include <sys/time.h>

// Include FMB and SAT algorithm library
#include "fmb2d.h"
#include "sat.h"

// Epsilon to detect degenerated triangles
#define EPSILON 0.1
// Range of values for the random generation of Frames
#define RANGE_AXIS 100.0
// Nb of run
#define NB_RUNS 9
// Nb of tests per run
#define NB_TESTS 100000
// Nb of times the test is run on one pair of frame, used to
// slow down the processus and be able to measure time
#define NB_REPEAT_2D 1500

// Helper macro to generate random number in [0.0, 1.0]
#define rnd() (double)(rand())/(double)(RAND_MAX)

```

```

// Helper structure to pass arguments to the Qualification function
typedef struct {
    FrameType type;
    double orig[2];
    double comp[2][2];
} Param2D;

// Global variables to count nb of tests resulting in intersection
// and no intersection, and min/max/total time of execution for each
double minInter;
double maxInter;
double sumInter;
unsigned long countInter;
double minNoInter;
double maxNoInter;
double sumNoInter;
unsigned long countNoInter;

double minInterCC;
double maxInterCC;
double sumInterCC;
unsigned long countInterCC;
double minNoInterCC;
double maxNoInterCC;
double sumNoInterCC;
unsigned long countNoInterCC;

double minInterCT;
double maxInterCT;
double sumInterCT;
unsigned long countInterCT;
double minNoInterCT;
double maxNoInterCT;
double sumNoInterCT;
unsigned long countNoInterCT;

double minInterTC;
double maxInterTC;
double sumInterTC;
unsigned long countInterTC;
double minNoInterTC;
double maxNoInterTC;
double sumNoInterTC;
unsigned long countNoInterTC;

double minInterTT;
double maxInterTT;
double sumInterTT;
unsigned long countInterTT;
double minNoInterTT;
double maxNoInterTT;
double sumNoInterTT;
unsigned long countNoInterTT;

// Qualification function
// Takes two Frame definition as input, run the intersection test on
// them with FMB and SAT, and measure the time of execution of each
void Qualification2DStatic(
    const Param2D paramP,
    const Param2D paramQ) {

    // Create the two Frames

```

```

Frame2D P =
    Frame2DCreateStatic(
        paramP.type,
        paramP.orig,
        paramP.comp);

Frame2D Q =
    Frame2DCreateStatic(
        paramQ.type,
        paramQ.orig,
        paramQ.comp);

// Helper variables to loop on the pair (that, tho) and (tho, that)
Frame2D* that = &P;
Frame2D* tho = &Q;

// Loop on pairs of Frames
for (int iPair = 2;
     iPair--;) {

    // Declare an array to memorize the results of the repeated
    // test on the same pair,
    // to prevent optimization from the compiler to remove the for loop
    bool isIntersectingFMB[NB_REPEAT_2D] = {false};

    // Start measuring time
    struct timeval start;
    gettimeofday(&start, NULL);

    // Run the FMB intersection test
    for (int i = NB_REPEAT_2D;
         i--;) {

        isIntersectingFMB[i] =
            FMBTestIntersection2D(
                that,
                tho,
                NULL);
    }

    // Stop measuring time
    struct timeval stop;
    gettimeofday(&stop, NULL);

    // Calculate the delay of execution
    unsigned long deltausFMB = 0;
    if (stop.tv_sec < start.tv_sec) {
        printf("time warps, try again\n");
        exit(0);
    }
    if (stop.tv_sec > start.tv_sec + 1) {
        printf("deltausFMB >> 1s, decrease NB_REPEAT\n");
        exit(0);
    }
    if (stop.tv_usec < start.tv_usec) {
        deltausFMB = stop.tv_sec - start.tv_sec;
        deltausFMB += stop.tv_usec + 1000000 - start.tv_usec;
    } else {
        deltausFMB = stop.tv_usec - start.tv_usec;
    }

    // Declare an array to memorize the results of the repeated

```

```

// test on the same pair,
// to prevent optimization from the compiler to remove the for loop
bool isIntersectingSAT[NB_REPEAT_2D] = {false};

// Start measuring time
gettimeofday(&start, NULL);

// Run the FMB intersection test
for (int i = NB_REPEAT_2D;
     i--;) {

    isIntersectingSAT[i] =
        SATTestIntersection2D(
            that,
            tho);

}

// Stop measuring time
gettimeofday(&stop, NULL);

// Calculate the delay of execution
unsigned long deltausSAT = 0;
if (stop.tv_sec < start.tv_sec) {
    printf("time warps, try again\n");
    exit(0);
}
if (stop.tv_sec > start.tv_sec + 1) {
    printf("deltausSAT >> 1s, decrease NB_REPEAT\n");
    exit(0);
}
if (stop.tv_usec < start.tv_usec) {
    deltausSAT = stop.tv_sec - start.tv_sec;
    deltausSAT += stop.tv_usec + 1000000 - start.tv_usec;
} else {
    deltausSAT = stop.tv_usec - start.tv_usec;
}

// If the delays are greater than 10ms
if (deltausFMB >= 10 && deltausSAT >= 10) {

    // If FMB and SAT disagrees
    if (isIntersectingFMB[0] != isIntersectingSAT[0]) {

        printf("Qualification has failed\n");
        Frame2DPrint(that);
        printf(" against ");
        Frame2DPrint(tho);
        printf("\n");
        printf("FMB : ");
        if (isIntersectingFMB[0] == false)
            printf("no ");
        printf("intersection\n");
        printf("SAT : ");
        if (isIntersectingSAT[0] == false)
            printf("no ");
        printf("intersection\n");

        // Stop the qualification test
        exit(0);

    }
}

```

```

// Get the ratio of execution time
double ratio = ((double)deltausFMB) / ((double)deltausSAT);

// If the Frames intersect
if (isIntersectingSAT[0] == true) {

    // Update the counters
    if (countInter == 0) {

        minInter = ratio;
        maxInter = ratio;

    } else {

        if (minInter > ratio)
            minInter = ratio;
        if (maxInter < ratio)
            maxInter = ratio;

    }

    sumInter += ratio;
    ++countInter;

    if (paramP.type == FrameCuboid &&
        paramQ.type == FrameCuboid) {

        if (countInterCC == 0) {

            minInterCC = ratio;
            maxInterCC = ratio;

        } else {

            if (minInterCC > ratio)
                minInterCC = ratio;
            if (maxInterCC < ratio)
                maxInterCC = ratio;

        }

        sumInterCC += ratio;
        ++countInterCC;

    } else if (paramP.type == FrameCuboid &&
                paramQ.type == FrameTetrahedron) {

        if (countInterCT == 0) {

            minInterCT = ratio;
            maxInterCT = ratio;

        } else {

            if (minInterCT > ratio)
                minInterCT = ratio;
            if (maxInterCT < ratio)
                maxInterCT = ratio;

        }

        sumInterCT += ratio;
        ++countInterCT;
    }
}

```

```

} else if (paramP.type == FrameTetrahedron &&
           paramQ.type == FrameCuboid) {

    if (countInterTC == 0) {

        minInterTC = ratio;
        maxInterTC = ratio;

    } else {

        if (minInterTC > ratio)
            minInterTC = ratio;
        if (maxInterTC < ratio)
            maxInterTC = ratio;

    }

    sumInterTC += ratio;
    ++countInterTC;

} else if (paramP.type == FrameTetrahedron &&
           paramQ.type == FrameTetrahedron) {

    if (countInterTT == 0) {

        minInterTT = ratio;
        maxInterTT = ratio;

    } else {

        if (minInterTT > ratio)
            minInterTT = ratio;
        if (maxInterTT < ratio)
            maxInterTT = ratio;

    }

    sumInterTT += ratio;
    ++countInterTT;

}

// Else, the Frames do not intersect
} else {

    // Update the counters
    if (countNoInter == 0) {

        minNoInter = ratio;
        maxNoInter = ratio;

    } else {

        if (minNoInter > ratio)
            minNoInter = ratio;
        if (maxNoInter < ratio)
            maxNoInter = ratio;

    }

    sumNoInter += ratio;
    ++countNoInter;

    if (paramP.type == FrameCuboid &&
        paramQ.type == FrameCuboid) {

```

```

    if (countNoInterCC == 0) {

        minNoInterCC = ratio;
        maxNoInterCC = ratio;

    } else {

        if (minNoInterCC > ratio)
            minNoInterCC = ratio;
        if (maxNoInterCC < ratio)
            maxNoInterCC = ratio;

    }
    sumNoInterCC += ratio;
    ++countNoInterCC;

} else if (paramP.type == FrameCuboid &&
           paramQ.type == FrameTetrahedron) {

    if (countNoInterCT == 0) {

        minNoInterCT = ratio;
        maxNoInterCT = ratio;

    } else {

        if (minNoInterCT > ratio)
            minNoInterCT = ratio;
        if (maxNoInterCT < ratio)
            maxNoInterCT = ratio;

    }
    sumNoInterCT += ratio;
    ++countNoInterCT;

} else if (paramP.type == FrameTetrahedron &&
           paramQ.type == FrameCuboid) {

    if (countNoInterTC == 0) {

        minNoInterTC = ratio;
        maxNoInterTC = ratio;

    } else {

        if (minNoInterTC > ratio)
            minNoInterTC = ratio;
        if (maxNoInterTC < ratio)
            maxNoInterTC = ratio;

    }
    sumNoInterTC += ratio;
    ++countNoInterTC;

} else if (paramP.type == FrameTetrahedron &&
           paramQ.type == FrameTetrahedron) {

    if (countNoInterTT == 0) {

        minNoInterTT = ratio;
        maxNoInterTT = ratio;

```



```

        } else {

            if (minNoInterTT > ratio)
                minNoInterTT = ratio;
            if (maxNoInterTT < ratio)
                maxNoInterTT = ratio;

        }
        sumNoInterTT += ratio;
        ++countNoInterTT;

    }
}

// Else, if time of execution for FMB was less than a 10ms
} else if (deltausFMB < 10) {

    printf("deltausFMB < 10ms, increase NB_REPEAT\n");
    exit(0);

// Else, if time of execution for SAT was less than a 10ms
} else if (deltausSAT < 10) {

    printf("deltausSAT < 10ms, increase NB_REPEAT\n");
    exit(0);

}

// Flip the pair of Frames
that = &Q;
tho = &P;

}

}

void Qualify2DStatic(void) {

    // Initialise the random generator
    srand(time(NULL));

    // Loop on runs
    for (int iRun = 0;
        iRun < NB_RUNS;
        ++iRun) {

        // Ratio intersection/no intersection for the displayed results
        double ratioInter = 0.1 + 0.8 * (double)iRun / (double)(NB_RUNS - 1);

        // Initialize counters
        minInter = 0.0;
        maxInter = 0.0;
        sumInter = 0.0;
        countInter = 0;
        minNoInter = 0.0;
        maxNoInter = 0.0;
        sumNoInter = 0.0;
        countNoInter = 0;

        minInterCC = 0.0;
        maxInterCC = 0.0;

```

```

sumInterCC = 0.0;
countInterCC = 0;
minNoInterCC = 0.0;
maxNoInterCC = 0.0;
sumNoInterCC = 0.0;
countNoInterCC = 0;

minInterCT = 0.0;
maxInterCT = 0.0;
sumInterCT = 0.0;
countInterCT = 0;
minNoInterCT = 0.0;
maxNoInterCT = 0.0;
sumNoInterCT = 0.0;
countNoInterCT = 0;

minInterTC = 0.0;
maxInterTC = 0.0;
sumInterTC = 0.0;
countInterTC = 0;
minNoInterTC = 0.0;
maxNoInterTC = 0.0;
sumNoInterTC = 0.0;
countNoInterTC = 0;

minInterTT = 0.0;
maxInterTT = 0.0;
sumInterTT = 0.0;
countInterTT = 0;
minNoInterTT = 0.0;
maxNoInterTT = 0.0;
sumNoInterTT = 0.0;
countNoInterTT = 0;

// Declare two variables to memoize the arguments to the
// Qualification function
Param2D paramP;
Param2D paramQ;

// Loop on the number of tests
for (unsigned long iTest = NB_TESTS;
     iTest--;) {

    // Create two random Frame definitions
    Param2D* param = &paramP;
    for (int iParam = 2;
         iParam--;) {

        // 50% chance of being a Cuboid or a Tetrahedron
        if (rnd() < 0.5)
            param->type = FrameCuboid;
        else
            param->type = FrameTetrahedron;

        for (int iAxis = 2;
             iAxis--;) {

            param->orig[iAxis] = -RANGE_AXIS + 2.0 * rnd() * RANGE_AXIS;

            for (int iComp = 2;
                 iComp--;) {

```

```

        param->comp[iComp][iAxis] =
            -RANGE_AXIS + 2.0 * rnd() * RANGE_AXIS;

    }

}

param = &paramQ;

}

// Calculate the determinant of the Frames' components matrix

double detP =
    paramP.comp[0][0] * paramP.comp[1][1] -
    paramP.comp[1][0] * paramP.comp[0][1];

double detQ =
    paramQ.comp[0][0] * paramQ.comp[1][1] -
    paramQ.comp[1][0] * paramQ.comp[0][1];

// If the determinants are not null, ie the Frame are not degenerate
if (fabs(detP) > EPSILON && fabs(detQ) > EPSILON) {

    // Run the validation on the two Frames
    Qualification2DStatic(
        paramP,
        paramQ);

}

}

// Display the results
if (iRun == 0) {

    printf("percPairInter\t");
    printf("countInter\tcountNoInter\t");
    printf("minInter\tavgInter\tmaxInter\t");
    printf("minNoInter\tavgNoInter\tmaxNoInter\t");
    printf("minTotal\tavgTotal\tmaxTotal\t");

    printf("countInterCC\tcountNoInterCC\t");
    printf("minInterCC\tavgInterCC\tmaxInterCC\t");
    printf("minNoInterCC\tavgNoInterCC\tmaxNoInterCC\t");
    printf("minTotalCC\tavgTotalCC\tmaxTotalCC\t");

    printf("countInterCT\tcountNoInterCT\t");
    printf("minInterCT\tavgInterCT\tmaxInterCT\t");
    printf("minNoInterCT\tavgNoInterCT\tmaxNoInterCT\t");
    printf("minTotalCT\tavgTotalCT\tmaxTotalCT\t");

    printf("countInterTC\tcountNoInterTC\t");
    printf("minInterTC\tavgInterTC\tmaxInterTC\t");
    printf("minNoInterTC\tavgNoInterTC\tmaxNoInterTC\t");
    printf("minTotalTC\tavgTotalTC\tmaxTotalTC\t");

    printf("countInterTT\tcountNoInterTT\t");
    printf("minInterTT\tavgInterTT\tmaxInterTT\t");
    printf("minNoInterTT\tavgNoInterTT\tmaxNoInterTT\t");
    printf("minTotalTT\tavgTotalTT\tmaxTotalTT\n");
}

```

```

}

printf("%.1f\t", ratioInter);

printf("%lu\t%lu\t", countInter, countNoInter);
double avgInter = sumInter / (double)countInter;
printf("%f\t%f\t%f\t", minInter, avgInter, maxInter);
double avgNoInter = sumNoInter / (double)countNoInter;
printf("%f\t%f\t%f\t", minNoInter, avgNoInter, maxNoInter);
double avg =
    ratioInter * avgInter + (1.0 - ratioInter) * avgNoInter;
printf("%f\t%f\t%f\t",
    (minNoInter < minInter ? minNoInter : minInter),
    avg,
    (maxNoInter > maxInter ? maxNoInter : maxInter));

printf("%lu\t%lu\t", countInterCC, countNoInterCC);
double avgInterCC = sumInterCC / (double)countInterCC;
printf("%f\t%f\t%f\t", minInterCC, avgInterCC, maxInterCC);
double avgNoInterCC = sumNoInterCC / (double)countNoInterCC;
printf("%f\t%f\t%f\t", minNoInterCC, avgNoInterCC, maxNoInterCC);
double avgCC =
    ratioInter * avgInterCC + (1.0 - ratioInter) * avgNoInterCC;
printf("%f\t%f\t%f\t",
    (minNoInterCC < minInterCC ? minNoInterCC : minInterCC),
    avgCC,
    (maxNoInterCC > maxInterCC ? maxNoInterCC : maxInterCC));

printf("%lu\t%lu\t", countInterCT, countNoInterCT);
double avgInterCT = sumInterCT / (double)countInterCT;
printf("%f\t%f\t%f\t", minInterCT, avgInterCT, maxInterCT);
double avgNoInterCT = sumNoInterCT / (double)countNoInterCT;
printf("%f\t%f\t%f\t", minNoInterCT, avgNoInterCT, maxNoInterCT);
double avgCT =
    ratioInter * avgInterCT + (1.0 - ratioInter) * avgNoInterCT;
printf("%f\t%f\t%f\t",
    (minNoInterCT < minInterCT ? minNoInterCT : minInterCT),
    avgCT,
    (maxNoInterCT > maxInterCT ? maxNoInterCT : maxInterCT));

printf("%lu\t%lu\t", countInterTC, countNoInterTC);
double avgInterTC = sumInterTC / (double)countInterTC;
printf("%f\t%f\t%f\t", minInterTC, avgInterTC, maxInterTC);
double avgNoInterTC = sumNoInterTC / (double)countNoInterTC;
printf("%f\t%f\t%f\t", minNoInterTC, avgNoInterTC, maxNoInterTC);
double avgTC =
    ratioInter * avgInterTC + (1.0 - ratioInter) * avgNoInterTC;
printf("%f\t%f\t%f\t",
    (minNoInterTC < minInterTC ? minNoInterTC : minInterTC),
    avgTC,
    (maxNoInterTC > maxInterTC ? maxNoInterTC : maxInterTC));

printf("%lu\t%lu\t", countInterTT, countNoInterTT);
double avgInterTT = sumInterTT / (double)countInterTT;
printf("%f\t%f\t%f\t", minInterTT, avgInterTT, maxInterTT);
double avgNoInterTT = sumNoInterTT / (double)countNoInterTT;
printf("%f\t%f\t%f\t", minNoInterTT, avgNoInterTT, maxNoInterTT);
double avgTT =
    ratioInter * avgInterTT + (1.0 - ratioInter) * avgNoInterTT;
printf("%f\t%f\t%f\t\n",
    (minNoInterTT < minInterTT ? minNoInterTT : minInterTT),
    avgTT,

```

```

        (maxNoInterTT > maxInterTT ? maxNoInterTT : maxInterTT));

    }

}

int main(int argc, char** argv) {

    Qualify2DStatic();

    return 0;
}

```

8.1.2 3D static

```

// Include standard libraries
#include <stdlib.h>
#include <stdio.h>
#include <stdbool.h>
#include <time.h>
#include <sys/time.h>

// Include FMB and SAT algorithm library
#include "fmb3d.h"
#include "sat.h"

// Epsilon to detect degenerated triangles
#define EPSILON 0.1
// Range of values for the random generation of Frames
#define RANGE_AXIS 100.0
// Nb of run
#define NB_RUNS 9
// Nb of tests per run
#define NB_TESTS 100000
// Nb of times the test is run on one pair of frame, used to
// slow down the processus and be able to measure time
#define NB_REPEAT_3D 800

// Helper macro to generate random number in [0.0, 1.0]
#define rnd() (double)(rand())/(double)(RAND_MAX)

// Helper structure to pass arguments to the Qualification function
typedef struct {
    FrameType type;
    double orig[3];
    double comp[3][3];
} Param3D;

// Global variables to count nb of tests resulting in intersection
// and no intersection, and min/max/total time of execution for each
double minInter;
double maxInter;
double sumInter;
unsigned long countInter;
double minNoInter;
double maxNoInter;
double sumNoInter;
unsigned long countNoInter;

double minInterCC;
double maxInterCC;

```

```

double sumInterCC;
unsigned long countInterCC;
double minNoInterCC;
double maxNoInterCC;
double sumNoInterCC;
unsigned long countNoInterCC;

double minInterCT;
double maxInterCT;
double sumInterCT;
unsigned long countInterCT;
double minNoInterCT;
double maxNoInterCT;
double sumNoInterCT;
unsigned long countNoInterCT;

double minInterTC;
double maxInterTC;
double sumInterTC;
unsigned long countInterTC;
double minNoInterTC;
double maxNoInterTC;
double sumNoInterTC;
unsigned long countNoInterTC;

double minInterTT;
double maxInterTT;
double sumInterTT;
unsigned long countInterTT;
double minNoInterTT;
double maxNoInterTT;
double sumNoInterTT;
unsigned long countNoInterTT;

// Qualification function
// Takes two Frame definition as input, run the intersection test on
// them with FMB and SAT, and measure the time of execution of each
void Qualification3DStatic(
    const Param3D paramP,
    const Param3D paramQ) {

    // Create the two Frames
    Frame3D P =
        Frame3DCreateStatic(
            paramP.type,
            paramP.orig,
            paramP.comp);

    Frame3D Q =
        Frame3DCreateStatic(
            paramQ.type,
            paramQ.orig,
            paramQ.comp);

    // Helper variables to loop on the pair (that, tho) and (tho, that)
    Frame3D* that = &P;
    Frame3D* tho = &Q;

    // Loop on pairs of Frames
    for (int iPair = 2;
        iPair--;) {

```

```

// Declare an array to memorize the results of the repeated
// test on the same pair,
// to prevent optimization from the compiler to remove the for loop
bool isIntersectingFMB[NB_REPEAT_3D] = {false};

// Start measuring time
struct timeval start;
gettimeofday(&start, NULL);

// Run the FMB intersection test
for (int i = NB_REPEAT_3D;
     i--;) {

    isIntersectingFMB[i] =
        FMBTestIntersection3D(
            that,
            tho,
            NULL);
}

// Stop measuring time
struct timeval stop;
gettimeofday(&stop, NULL);

// Calculate the delay of execution
unsigned long deltausFMB = 0;
if (stop.tv_sec < start.tv_sec) {
    printf("time warps, try again\n");
    exit(0);
}
if (stop.tv_sec > start.tv_sec + 1) {
    printf("deltausFMB >> 1s, decrease NB_REPEAT\n");
    exit(0);
}
if (stop.tv_usec < start.tv_usec) {
    deltausFMB = stop.tv_sec - start.tv_sec;
    deltausFMB += stop.tv_usec + 1000000 - start.tv_usec;
} else {
    deltausFMB = stop.tv_usec - start.tv_usec;
}

// Declare an array to memorize the results of the repeated
// test on the same pair,
// to prevent optimization from the compiler to remove the for loop
bool isIntersectingSAT[NB_REPEAT_3D] = {false};

// Start measuring time
gettimeofday(&start, NULL);

// Run the FMB intersection test
for (int i = NB_REPEAT_3D;
     i--;) {

    isIntersectingSAT[i] =
        SATTestIntersection3D(
            that,
            tho);
}

// Stop measuring time
gettimeofday(&stop, NULL);

```

```

// Calculate the delay of execution
unsigned long deltausSAT = 0;
if (stop.tv_sec < start.tv_sec) {
    printf("time warps, try again\n");
    exit(0);
}
if (stop.tv_sec > start.tv_sec + 1) {
    printf("deltausSAT >> 1s, decrease NB_REPEAT\n");
    exit(0);
}
if (stop.tv_usec < start.tv_usec) {
    deltausSAT = stop.tv_sec - start.tv_sec;
    deltausSAT += stop.tv_usec + 1000000 - start.tv_usec;
} else {
    deltausSAT = stop.tv_usec - start.tv_usec;
}

// If the delays are greater than 10ms
if (deltausFMB >= 10 && deltausSAT >= 10) {

    // If FMB and SAT disagrees
    if (isIntersectingFMB[0] != isIntersectingSAT[0]) {

        printf("Qualification has failed\n");
        Frame3DPrint(that);
        printf(" against ");
        Frame3DPrint(tho);
        printf("\n");
        printf("FMB : ");
        if (isIntersectingFMB[0] == false)
            printf("no ");
        printf("intersection\n");
        printf("SAT : ");
        if (isIntersectingSAT[0] == false)
            printf("no ");
        printf("intersection\n");

        // Stop the qualification test
        exit(0);
    }

    // Get the ratio of execution time
    double ratio = ((double)deltausFMB) / ((double)deltausSAT);

    // If the Frames intersect
    if (isIntersectingSAT[0] == true) {

        // Update the counters
        if (countInter == 0) {

            minInter = ratio;
            maxInter = ratio;

        } else {

            if (minInter > ratio)
                minInter = ratio;
            if (maxInter < ratio)
                maxInter = ratio;
        }
    }
}

```



```

}
sumInter += ratio;
++countInter;

if (paramP.type == FrameCuboid &&
    paramQ.type == FrameCuboid) {

    if (countInterCC == 0) {

        minInterCC = ratio;
        maxInterCC = ratio;

    } else {

        if (minInterCC > ratio)
            minInterCC = ratio;
        if (maxInterCC < ratio)
            maxInterCC = ratio;

    }

    sumInterCC += ratio;
    ++countInterCC;

} else if (paramP.type == FrameCuboid &&
    paramQ.type == FrameTetrahedron) {

    if (countInterCT == 0) {

        minInterCT = ratio;
        maxInterCT = ratio;

    } else {

        if (minInterCT > ratio)
            minInterCT = ratio;
        if (maxInterCT < ratio)
            maxInterCT = ratio;

    }

    sumInterCT += ratio;
    ++countInterCT;

} else if (paramP.type == FrameTetrahedron &&
    paramQ.type == FrameCuboid) {

    if (countInterTC == 0) {

        minInterTC = ratio;
        maxInterTC = ratio;

    } else {

        if (minInterTC > ratio)
            minInterTC = ratio;
        if (maxInterTC < ratio)
            maxInterTC = ratio;

    }

    sumInterTC += ratio;
    ++countInterTC;

} else if (paramP.type == FrameTetrahedron &&

```

```

        paramQ.type == FrameTetrahedron) {

    if (countInterTT == 0) {

        minInterTT = ratio;
        maxInterTT = ratio;

    } else {

        if (minInterTT > ratio)
            minInterTT = ratio;
        if (maxInterTT < ratio)
            maxInterTT = ratio;

    }

    sumInterTT += ratio;
    ++countInterTT;

}

// Else, the Frames do not intersect
} else {

    // Update the counters
    if (countNoInter == 0) {

        minNoInter = ratio;
        maxNoInter = ratio;

    } else {

        if (minNoInter > ratio)
            minNoInter = ratio;
        if (maxNoInter < ratio)
            maxNoInter = ratio;

    }

    sumNoInter += ratio;
    ++countNoInter;

    if (paramP.type == FrameCuboid &&
        paramQ.type == FrameCuboid) {

        if (countNoInterCC == 0) {

            minNoInterCC = ratio;
            maxNoInterCC = ratio;

        } else {

            if (minNoInterCC > ratio)
                minNoInterCC = ratio;
            if (maxNoInterCC < ratio)
                maxNoInterCC = ratio;

        }

        sumNoInterCC += ratio;
        ++countNoInterCC;

    } else if (paramP.type == FrameCuboid &&
                paramQ.type == FrameTetrahedron) {

```

```

        if (countNoInterCT == 0) {

            minNoInterCT = ratio;
            maxNoInterCT = ratio;

        } else {

            if (minNoInterCT > ratio)
                minNoInterCT = ratio;
            if (maxNoInterCT < ratio)
                maxNoInterCT = ratio;

        }
        sumNoInterCT += ratio;
        ++countNoInterCT;

    } else if (paramP.type == FrameTetrahedron &&
               paramQ.type == FrameCuboid) {

        if (countNoInterTC == 0) {

            minNoInterTC = ratio;
            maxNoInterTC = ratio;

        } else {

            if (minNoInterTC > ratio)
                minNoInterTC = ratio;
            if (maxNoInterTC < ratio)
                maxNoInterTC = ratio;

        }
        sumNoInterTC += ratio;
        ++countNoInterTC;

    } else if (paramP.type == FrameTetrahedron &&
               paramQ.type == FrameTetrahedron) {

        if (countNoInterTT == 0) {

            minNoInterTT = ratio;
            maxNoInterTT = ratio;

        } else {

            if (minNoInterTT > ratio)
                minNoInterTT = ratio;
            if (maxNoInterTT < ratio)
                maxNoInterTT = ratio;

        }
        sumNoInterTT += ratio;
        ++countNoInterTT;

    }
}

// Else, if time of execution for FMB was less than a 10ms
} else if (deltausFMB < 10) {

    printf("deltausFMB < 10ms, increase NB_REPEAT\n");
    exit(0);
}

```

```

// Else, if time of execution for SAT was less than a 10ms
} else if (deltausSAT < 10) {

    printf("deltausSAT < 10ms, increase NB_REPEAT\n");
    exit(0);

}

// Flip the pair of Frames
that = &Q;
tho = &P;

}

}

void Qualify3DStatic(void) {

    // Initialise the random generator
    srand(time(NULL));

    // Loop on runs
    for (int iRun = 0;
        iRun < NB_RUNS;
        ++iRun) {

        // Ratio intersection/no intersection for the displayed results
        double ratioInter = 0.1 + 0.8 * (double)iRun / (double)(NB_RUNS - 1);

        // Initialize counters
        minInter = 0.0;
        maxInter = 0.0;
        sumInter = 0.0;
        countInter = 0;
        minNoInter = 0.0;
        maxNoInter = 0.0;
        sumNoInter = 0.0;
        countNoInter = 0;

        minInterCC = 0.0;
        maxInterCC = 0.0;
        sumInterCC = 0.0;
        countInterCC = 0;
        minNoInterCC = 0.0;
        maxNoInterCC = 0.0;
        sumNoInterCC = 0.0;
        countNoInterCC = 0;

        minInterCT = 0.0;
        maxInterCT = 0.0;
        sumInterCT = 0.0;
        countInterCT = 0;
        minNoInterCT = 0.0;
        maxNoInterCT = 0.0;
        sumNoInterCT = 0.0;
        countNoInterCT = 0;

        minInterTC = 0.0;
        maxInterTC = 0.0;
        sumInterTC = 0.0;
        countInterTC = 0;
    }
}

```

```

minNoInterTC = 0.0;
maxNoInterTC = 0.0;
sumNoInterTC = 0.0;
countNoInterTC = 0;

minInterTT = 0.0;
maxInterTT = 0.0;
sumInterTT = 0.0;
countInterTT = 0;
minNoInterTT = 0.0;
maxNoInterTT = 0.0;
sumNoInterTT = 0.0;
countNoInterTT = 0;

// Declare two variables to memoize the arguments to the
// Qualification function
Param3D paramP;
Param3D paramQ;

// Loop on the number of tests
for (unsigned long iTest = NB_TESTS;
     iTest--;) {

    // Create two random Frame definitions
    Param3D* param = &paramP;
    for (int iParam = 2;
         iParam--;) {

        // 50% chance of being a Cuboid or a Tetrahedron
        if (rnd() < 0.5)
            param->type = FrameCuboid;
        else
            param->type = FrameTetrahedron;

        for (int iAxis = 3;
             iAxis--;) {

            param->orig[iAxis] = -RANGE_AXIS + 2.0 * rnd() * RANGE_AXIS;

            for (int iComp = 3;
                 iComp--;) {

                param->comp[iComp][iAxis] =
                    -RANGE_AXIS + 2.0 * rnd() * RANGE_AXIS;

            }

        }

        param = &paramQ;

    }

    // Calculate the determinant of the Frames' components matrix
    double detP =
        paramP.comp[0][0] * (paramP.comp[1][1] * paramP.comp[2][2] -
        paramP.comp[1][2] * paramP.comp[2][1]) -
        paramP.comp[1][0] * (paramP.comp[0][1] * paramP.comp[2][2] -
        paramP.comp[0][2] * paramP.comp[2][1]) +
        paramP.comp[2][0] * (paramP.comp[0][1] * paramP.comp[1][2] -
        paramP.comp[0][2] * paramP.comp[1][1]);

```

```

double detQ =
    paramQ.comp[0][0] * (paramQ.comp[1][1] * paramQ.comp[2][2] -
    paramQ.comp[1][2] * paramQ.comp[2][1]) -
    paramQ.comp[1][0] * (paramQ.comp[0][1] * paramQ.comp[2][2] -
    paramQ.comp[0][2] * paramQ.comp[2][1]) +
    paramQ.comp[2][0] * (paramQ.comp[0][1] * paramQ.comp[1][2] -
    paramQ.comp[0][2] * paramQ.comp[1][1]);

// If the determinants are not null, ie the Frame are not degenerate
if (fabs(detP) > EPSILON && fabs(detQ) > EPSILON) {

    // Run the validation on the two Frames
    Qualification3DStatic(
        paramP,
        paramQ);

}

}

// Display the results
if (iRun == 0) {

    printf("percPairInter\t");
    printf("countInter\tcountNoInter\t");
    printf("minInter\tavgInter\tmaxInter\t");
    printf("minNoInter\tavgNoInter\tmaxNoInter\t");
    printf("minTotal\tavgTotal\tmaxTotal\t");

    printf("countInterCC\tcountNoInterCC\t");
    printf("minInterCC\tavgInterCC\tmaxInterCC\t");
    printf("minNoInterCC\tavgNoInterCC\tmaxNoInterCC\t");
    printf("minTotalCC\tavgTotalCC\tmaxTotalCC\t");

    printf("countInterCT\tcountNoInterCT\t");
    printf("minInterCT\tavgInterCT\tmaxInterCT\t");
    printf("minNoInterCT\tavgNoInterCT\tmaxNoInterCT\t");
    printf("minTotalCT\tavgTotalCT\tmaxTotalCT\t");

    printf("countInterTC\tcountNoInterTC\t");
    printf("minInterTC\tavgInterTC\tmaxInterTC\t");
    printf("minNoInterTC\tavgNoInterTC\tmaxNoInterTC\t");
    printf("minTotalTC\tavgTotalTC\tmaxTotalTC\t");

    printf("countInterTT\tcountNoInterTT\t");
    printf("minInterTT\tavgInterTT\tmaxInterTT\t");
    printf("minNoInterTT\tavgNoInterTT\tmaxNoInterTT\t");
    printf("minTotalTT\tavgTotalTT\tmaxTotalTT\n");

}

printf("%.1f\t", ratioInter);

printf("%lu\t%lu\t", countInter, countNoInter);
double avgInter = sumInter / (double)countInter;
printf("%f\t%f\t%f\t", minInter, avgInter, maxInter);
double avgNoInter = sumNoInter / (double)countNoInter;
printf("%f\t%f\t%f\t", minNoInter, avgNoInter, maxNoInter);
double avg =
    ratioInter * avgInter + (1.0 - ratioInter) * avgNoInter;
printf("%f\t%f\t%f\t",
    (minNoInter < minInter ? minNoInter : minInter),

```

```

        avg,
        (maxNoInter > maxInter ? maxNoInter : maxInter));

printf("%lu\t%lu\t", countInterCC, countNoInterCC);
double avgInterCC = sumInterCC / (double)countInterCC;
printf("%f\t%f\t%f\t", minInterCC, avgInterCC, maxInterCC);
double avgNoInterCC = sumNoInterCC / (double)countNoInterCC;
printf("%f\t%f\t%f\t", minNoInterCC, avgNoInterCC, maxNoInterCC);
double avgCC =
    ratioInter * avgInterCC + (1.0 - ratioInter) * avgNoInterCC;
printf("%f\t%f\t%f\t",
    (minNoInterCC < minInterCC ? minNoInterCC : minInterCC),
    avgCC,
    (maxNoInterCC > maxInterCC ? maxNoInterCC : maxInterCC));

printf("%lu\t%lu\t", countInterCT, countNoInterCT);
double avgInterCT = sumInterCT / (double)countInterCT;
printf("%f\t%f\t%f\t", minInterCT, avgInterCT, maxInterCT);
double avgNoInterCT = sumNoInterCT / (double)countNoInterCT;
printf("%f\t%f\t%f\t", minNoInterCT, avgNoInterCT, maxNoInterCT);
double avgCT =
    ratioInter * avgInterCT + (1.0 - ratioInter) * avgNoInterCT;
printf("%f\t%f\t%f\t",
    (minNoInterCT < minInterCT ? minNoInterCT : minInterCT),
    avgCT,
    (maxNoInterCT > maxInterCT ? maxNoInterCT : maxInterCT));

printf("%lu\t%lu\t", countInterTC, countNoInterTC);
double avgInterTC = sumInterTC / (double)countInterTC;
printf("%f\t%f\t%f\t", minInterTC, avgInterTC, maxInterTC);
double avgNoInterTC = sumNoInterTC / (double)countNoInterTC;
printf("%f\t%f\t%f\t", minNoInterTC, avgNoInterTC, maxNoInterTC);
double avgTC =
    ratioInter * avgInterTC + (1.0 - ratioInter) * avgNoInterTC;
printf("%f\t%f\t%f\t",
    (minNoInterTC < minInterTC ? minNoInterTC : minInterTC),
    avgTC,
    (maxNoInterTC > maxInterTC ? maxNoInterTC : maxInterTC));

printf("%lu\t%lu\t", countInterTT, countNoInterTT);
double avgInterTT = sumInterTT / (double)countInterTT;
printf("%f\t%f\t%f\t", minInterTT, avgInterTT, maxInterTT);
double avgNoInterTT = sumNoInterTT / (double)countNoInterTT;
printf("%f\t%f\t%f\t", minNoInterTT, avgNoInterTT, maxNoInterTT);
double avgTT =
    ratioInter * avgInterTT + (1.0 - ratioInter) * avgNoInterTT;
printf("%f\t%f\t%f\t",
    (minNoInterTT < minInterTT ? minNoInterTT : minInterTT),
    avgTT,
    (maxNoInterTT > maxInterTT ? maxNoInterTT : maxInterTT));
}

}

int main(int argc, char** argv) {

    Qualify3DStatic();

    return 0;
}

```

8.1.3 2D dynamic

```
// Include standard libraries
#include <stdlib.h>
#include <stdio.h>
#include <stdbool.h>
#include <time.h>
#include <sys/time.h>

// Include FMB and SAT algorithm library
#include "fmb2dt.h"
#include "sat.h"

// Epsilon to detect degenerated triangles
#define EPSILON 0.1
// Range of values for the random generation of Frames
#define RANGE_AXIS 100.0
// Nb of run
#define NB_RUNS 9
// Nb of tests per run
#define NB_TESTS 100000
// Nb of times the test is run on one pair of frame, used to
// slow down the processus and be able to measure time
#define NB_REPEAT_2D 1500

// Helper macro to generate random number in [0.0, 1.0]
#define rnd() (double)(rand())/(double)(RAND_MAX)

// Helper structure to pass arguments to the Qualification function
typedef struct {
    FrameType type;
    double orig[2];
    double comp[2][2];
    double speed[2];
} Param2DTime;

// Global variables to count nb of tests resulting in intersection
// and no intersection, and min/max/total time of execution for each
double minInter;
double maxInter;
double sumInter;
unsigned long countInter;
double minNoInter;
double maxNoInter;
double sumNoInter;
unsigned long countNoInter;

double minInterCC;
double maxInterCC;
double sumInterCC;
unsigned long countInterCC;
double minNoInterCC;
double maxNoInterCC;
double sumNoInterCC;
unsigned long countNoInterCC;

double minInterCT;
double maxInterCT;
double sumInterCT;
unsigned long countInterCT;
double minNoInterCT;
```



```

double maxNoInterCT;
double sumNoInterCT;
unsigned long countNoInterCT;

double minInterTC;
double maxInterTC;
double sumInterTC;
unsigned long countInterTC;
double minNoInterTC;
double maxNoInterTC;
double sumNoInterTC;
unsigned long countNoInterTC;

double minInterTT;
double maxInterTT;
double sumInterTT;
unsigned long countInterTT;
double minNoInterTT;
double maxNoInterTT;
double sumNoInterTT;
unsigned long countNoInterTT;

// Qualification function
// Takes two Frame definition as input, run the intersection test on
// them with FMB and SAT, and measure the time of execution of each
void Qualification2DDynamic(
    const Param2DTime paramP,
    const Param2DTime paramQ) {

    // Create the two Frames
    Frame2DTime P =
        Frame2DTimeCreateStatic(
            paramP.type,
            paramP.orig,
            paramP.speed,
            paramP.comp);

    Frame2DTime Q =
        Frame2DTimeCreateStatic(
            paramQ.type,
            paramQ.orig,
            paramQ.speed,
            paramQ.comp);

    // Helper variables to loop on the pair (that, tho) and (tho, that)
    Frame2DTime* that = &P;
    Frame2DTime* tho = &Q;

    // Loop on pairs of Frames
    for (int iPair = 2;
        iPair--;) {

        // Declare an array to memorize the results of the repeated
        // test on the same pair,
        // to prevent optimization from the compiler to remove the for loop
        bool isIntersectingFMB[NB_REPEAT_2D] = {false};

        // Start measuring time
        struct timeval start;
        gettimeofday(&start, NULL);

        // Run the FMB intersection test

```

```

for (int i = NB_REPEAT_2D;
    i--;) {

    isIntersectingFMB[i] =
        FMBTestIntersection2DTime(
            that,
            tho,
            NULL);
}

// Stop measuring time
struct timeval stop;
gettimeofday(&stop, NULL);

// Calculate the delay of execution
unsigned long deltausFMB = 0;
if (stop.tv_sec < start.tv_sec) {
    printf("time warps, try again\n");
    exit(0);
}
if (stop.tv_sec > start.tv_sec + 1) {
    printf("deltausFMB >> 1s, decrease NB_REPEAT\n");
    exit(0);
}
if (stop.tv_usec < start.tv_usec) {
    deltausFMB = stop.tv_sec - start.tv_sec;
    deltausFMB += stop.tv_usec + 1000000 - start.tv_usec;
} else {
    deltausFMB = stop.tv_usec - start.tv_usec;
}

// Declare an array to memorize the results of the repeated
// test on the same pair,
// to prevent optimization from the compiler to remove the for loop
bool isIntersectingSAT[NB_REPEAT_2D] = {false};

// Start measuring time
gettimeofday(&start, NULL);

// Run the FMB intersection test
for (int i = NB_REPEAT_2D;
    i--;) {

    isIntersectingSAT[i] =
        SATTestIntersection2DTime(
            that,
            tho);
}

// Stop measuring time
gettimeofday(&stop, NULL);

// Calculate the delay of execution
unsigned long deltausSAT = 0;
if (stop.tv_sec < start.tv_sec) {
    printf("time warps, try again\n");
    exit(0);
}
if (stop.tv_sec > start.tv_sec + 1) {
    printf("deltausSAT >> 1s, decrease NB_REPEAT\n");
    exit(0);
}

```

```

}
if (stop.tv_usec < start.tv_usec) {
    deltausSAT = stop.tv_sec - start.tv_sec;
    deltausSAT += stop.tv_usec + 1000000 - start.tv_usec;
} else {
    deltausSAT = stop.tv_usec - start.tv_usec;
}

// If the delays are greater than 10ms
if (deltausFMB >= 10 && deltausSAT >= 10) {

    // If FMB and SAT disagrees
    if (isIntersectingFMB[0] != isIntersectingSAT[0]) {

        printf("Qualification has failed\n");
        Frame2DTimePrint(that);
        printf(" against ");
        Frame2DTimePrint(tho);
        printf("\n");
        printf("FMB : ");
        if (isIntersectingFMB[0] == false)
            printf("no ");
        printf("intersection\n");
        printf("SAT : ");
        if (isIntersectingSAT[0] == false)
            printf("no ");
        printf("intersection\n");

        // Stop the qualification test
        exit(0);
    }

    // Get the ratio of execution time
    double ratio = ((double)deltausFMB) / ((double)deltausSAT);

    // If the Frames intersect
    if (isIntersectingSAT[0] == true) {

        // Update the counters
        if (countInter == 0) {

            minInter = ratio;
            maxInter = ratio;

        } else {

            if (minInter > ratio)
                minInter = ratio;
            if (maxInter < ratio)
                maxInter = ratio;

        }

        sumInter += ratio;
        ++countInter;

        if (paramP.type == FrameCuboid &&
            paramQ.type == FrameCuboid) {

            if (countInterCC == 0) {

                minInterCC = ratio;

```

```

        maxInterCC = ratio;

    } else {

        if (minInterCC > ratio)
            minInterCC = ratio;
        if (maxInterCC < ratio)
            maxInterCC = ratio;

    }
    sumInterCC += ratio;
    ++countInterCC;

} else if (paramP.type == FrameCuboid &&
           paramQ.type == FrameTetrahedron) {

    if (countInterCT == 0) {

        minInterCT = ratio;
        maxInterCT = ratio;

    } else {

        if (minInterCT > ratio)
            minInterCT = ratio;
        if (maxInterCT < ratio)
            maxInterCT = ratio;

    }
    sumInterCT += ratio;
    ++countInterCT;

} else if (paramP.type == FrameTetrahedron &&
           paramQ.type == FrameCuboid) {

    if (countInterTC == 0) {

        minInterTC = ratio;
        maxInterTC = ratio;

    } else {

        if (minInterTC > ratio)
            minInterTC = ratio;
        if (maxInterTC < ratio)
            maxInterTC = ratio;

    }
    sumInterTC += ratio;
    ++countInterTC;

} else if (paramP.type == FrameTetrahedron &&
           paramQ.type == FrameTetrahedron) {

    if (countInterTT == 0) {

        minInterTT = ratio;
        maxInterTT = ratio;

    } else {

        if (minInterTT > ratio)

```

```

        minInterTT = ratio;
        if (maxInterTT < ratio)
            maxInterTT = ratio;
    }
    sumInterTT += ratio;
    ++countInterTT;
}

// Else, the Frames do not intersect
} else {

    // Update the counters
    if (countNoInter == 0) {

        minNoInter = ratio;
        maxNoInter = ratio;

    } else {

        if (minNoInter > ratio)
            minNoInter = ratio;
        if (maxNoInter < ratio)
            maxNoInter = ratio;

    }
    sumNoInter += ratio;
    ++countNoInter;

    if (paramP.type == FrameCuboid &&
        paramQ.type == FrameCuboid) {

        if (countNoInterCC == 0) {

            minNoInterCC = ratio;
            maxNoInterCC = ratio;

        } else {

            if (minNoInterCC > ratio)
                minNoInterCC = ratio;
            if (maxNoInterCC < ratio)
                maxNoInterCC = ratio;

        }
        sumNoInterCC += ratio;
        ++countNoInterCC;

    } else if (paramP.type == FrameCuboid &&
        paramQ.type == FrameTetrahedron) {

        if (countNoInterCT == 0) {

            minNoInterCT = ratio;
            maxNoInterCT = ratio;

        } else {

            if (minNoInterCT > ratio)
                minNoInterCT = ratio;
            if (maxNoInterCT < ratio)

```

```

        maxNoInterCT = ratio;

    }
    sumNoInterCT += ratio;
    ++countNoInterCT;

} else if (paramP.type == FrameTetrahedron &&
           paramQ.type == FrameCuboid) {

    if (countNoInterTC == 0) {

        minNoInterTC = ratio;
        maxNoInterTC = ratio;

    } else {

        if (minNoInterTC > ratio)
            minNoInterTC = ratio;
        if (maxNoInterTC < ratio)
            maxNoInterTC = ratio;

    }
    sumNoInterTC += ratio;
    ++countNoInterTC;

} else if (paramP.type == FrameTetrahedron &&
           paramQ.type == FrameTetrahedron) {

    if (countNoInterTT == 0) {

        minNoInterTT = ratio;
        maxNoInterTT = ratio;

    } else {

        if (minNoInterTT > ratio)
            minNoInterTT = ratio;
        if (maxNoInterTT < ratio)
            maxNoInterTT = ratio;

    }
    sumNoInterTT += ratio;
    ++countNoInterTT;

}
}

// Else, if time of execution for FMB was less than a 10ms
} else if (deltausFMB < 10) {

    printf("deltausFMB < 10ms, increase NB_REPEAT\n");
    exit(0);

// Else, if time of execution for SAT was less than a 10ms
} else if (deltausSAT < 10) {

    printf("deltausSAT < 10ms, increase NB_REPEAT\n");
    exit(0);

}

// Flip the pair of Frames

```

```

        that = &Q;
        tho = &P;

    }

}

void Qualify2DDynamic(void) {

    // Initialise the random generator
    srand(time(NULL));

    // Loop on runs
    for (int iRun = 0;
        iRun < NB_RUNS;
        ++iRun) {

        // Ratio intersection/no intersection for the displayed results
        double ratioInter = 0.1 + 0.8 * (double)iRun / (double)(NB_RUNS - 1);

        // Initialize counters
        minInter = 0.0;
        maxInter = 0.0;
        sumInter = 0.0;
        countInter = 0;
        minNoInter = 0.0;
        maxNoInter = 0.0;
        sumNoInter = 0.0;
        countNoInter = 0;

        minInterCC = 0.0;
        maxInterCC = 0.0;
        sumInterCC = 0.0;
        countInterCC = 0;
        minNoInterCC = 0.0;
        maxNoInterCC = 0.0;
        sumNoInterCC = 0.0;
        countNoInterCC = 0;

        minInterCT = 0.0;
        maxInterCT = 0.0;
        sumInterCT = 0.0;
        countInterCT = 0;
        minNoInterCT = 0.0;
        maxNoInterCT = 0.0;
        sumNoInterCT = 0.0;
        countNoInterCT = 0;

        minInterTC = 0.0;
        maxInterTC = 0.0;
        sumInterTC = 0.0;
        countInterTC = 0;
        minNoInterTC = 0.0;
        maxNoInterTC = 0.0;
        sumNoInterTC = 0.0;
        countNoInterTC = 0;

        minInterTT = 0.0;
        maxInterTT = 0.0;
        sumInterTT = 0.0;
        countInterTT = 0;
        minNoInterTT = 0.0;

```

```

maxNoInterTT = 0.0;
sumNoInterTT = 0.0;
countNoInterTT = 0;

// Declare two variables to memoize the arguments to the
// Qualification function
Param2DTime paramP;
Param2DTime paramQ;

// Loop on the number of tests
for (unsigned long iTest = NB_TESTS;
     iTest--;) {

    // Create two random Frame definitions
    Param2DTime* param = &paramP;
    for (int iParam = 2;
         iParam--;) {

        // 50% chance of being a Cuboid or a Tetrahedron
        if (rnd() < 0.5)
            param->type = FrameCuboid;
        else
            param->type = FrameTetrahedron;

        for (int iAxis = 2;
             iAxis--;) {

            param->orig[iAxis] = -RANGE_AXIS + 2.0 * rnd() * RANGE_AXIS;
            param->speed[iAxis] = -RANGE_AXIS + 2.0 * rnd() * RANGE_AXIS;

            for (int iComp = 2;
                 iComp--;) {

                param->comp[iComp][iAxis] =
                    -RANGE_AXIS + 2.0 * rnd() * RANGE_AXIS;

            }

        }

        param = &paramQ;
    }

    // Calculate the determinant of the Frames' components matrix

    double detP =
        paramP.comp[0][0] * paramP.comp[1][1] -
        paramP.comp[1][0] * paramP.comp[0][1];

    double detQ =
        paramQ.comp[0][0] * paramQ.comp[1][1] -
        paramQ.comp[1][0] * paramQ.comp[0][1];

    // If the determinants are not null, ie the Frame are not degenerate
    if (fabs(detP) > EPSILON && fabs(detQ) > EPSILON) {

        // Run the validation on the two Frames
        Qualification2DDynamic(
            paramP,
            paramQ);
    }
}

```



```

    }

}

// Display the results
if (iRun == 0) {

    printf("percPairInter\t");
    printf("countInter\tcountNoInter\t");
    printf("minInter\tavgInter\tmaxInter\t");
    printf("minNoInter\tavgNoInter\tmaxNoInter\t");
    printf("minTotal\tavgTotal\tmaxTotal\t");

    printf("countInterCC\tcountNoInterCC\t");
    printf("minInterCC\tavgInterCC\tmaxInterCC\t");
    printf("minNoInterCC\tavgNoInterCC\tmaxNoInterCC\t");
    printf("minTotalCC\tavgTotalCC\tmaxTotalCC\t");

    printf("countInterCT\tcountNoInterCT\t");
    printf("minInterCT\tavgInterCT\tmaxInterCT\t");
    printf("minNoInterCT\tavgNoInterCT\tmaxNoInterCT\t");
    printf("minTotalCT\tavgTotalCT\tmaxTotalCT\t");

    printf("countInterTC\tcountNoInterTC\t");
    printf("minInterTC\tavgInterTC\tmaxInterTC\t");
    printf("minNoInterTC\tavgNoInterTC\tmaxNoInterTC\t");
    printf("minTotalTC\tavgTotalTC\tmaxTotalTC\t");

    printf("countInterTT\tcountNoInterTT\t");
    printf("minInterTT\tavgInterTT\tmaxInterTT\t");
    printf("minNoInterTT\tavgNoInterTT\tmaxNoInterTT\t");
    printf("minTotalTT\tavgTotalTT\tmaxTotalTT\n");

}

printf("%.1f\t", ratioInter);

printf("%lu\t%lu\t", countInter, countNoInter);
double avgInter = sumInter / (double)countInter;
printf("%f\t%f\t%f\t", minInter, avgInter, maxInter);
double avgNoInter = sumNoInter / (double)countNoInter;
printf("%f\t%f\t%f\t", minNoInter, avgNoInter, maxNoInter);
double avg =
    ratioInter * avgInter + (1.0 - ratioInter) * avgNoInter;
printf("%f\t%f\t%f\t",
    (minNoInter < minInter ? minNoInter : minInter),
    avg,
    (maxNoInter > maxInter ? maxNoInter : maxInter));

printf("%lu\t%lu\t", countInterCC, countNoInterCC);
double avgInterCC = sumInterCC / (double)countInterCC;
printf("%f\t%f\t%f\t", minInterCC, avgInterCC, maxInterCC);
double avgNoInterCC = sumNoInterCC / (double)countNoInterCC;
printf("%f\t%f\t%f\t", minNoInterCC, avgNoInterCC, maxNoInterCC);
double avgCC =
    ratioInter * avgInterCC + (1.0 - ratioInter) * avgNoInterCC;
printf("%f\t%f\t%f\t",
    (minNoInterCC < minInterCC ? minNoInterCC : minInterCC),
    avgCC,
    (maxNoInterCC > maxInterCC ? maxNoInterCC : maxInterCC));

printf("%lu\t%lu\t", countInterCT, countNoInterCT);

```

```

double avgInterCT = sumInterCT / (double)countInterCT;
printf("%f\t%f\t%f\t", minInterCT, avgInterCT, maxInterCT);
double avgNoInterCT = sumNoInterCT / (double)countNoInterCT;
printf("%f\t%f\t%f\t", minNoInterCT, avgNoInterCT, maxNoInterCT);
double avgCT =
    ratioInter * avgInterCT + (1.0 - ratioInter) * avgNoInterCT;
printf("%f\t%f\t%f\t",
    (minNoInterCT < minInterCT ? minNoInterCT : minInterCT),
    avgCT,
    (maxNoInterCT > maxInterCT ? maxNoInterCT : maxInterCT));

printf("%lu\t%lu\t", countInterTC, countNoInterTC);
double avgInterTC = sumInterTC / (double)countInterTC;
printf("%f\t%f\t%f\t", minInterTC, avgInterTC, maxInterTC);
double avgNoInterTC = sumNoInterTC / (double)countNoInterTC;
printf("%f\t%f\t%f\t", minNoInterTC, avgNoInterTC, maxNoInterTC);
double avgTC =
    ratioInter * avgInterTC + (1.0 - ratioInter) * avgNoInterTC;
printf("%f\t%f\t%f\t",
    (minNoInterTC < minInterTC ? minNoInterTC : minInterTC),
    avgTC,
    (maxNoInterTC > maxInterTC ? maxNoInterTC : maxInterTC));

printf("%lu\t%lu\t", countInterTT, countNoInterTT);
double avgInterTT = sumInterTT / (double)countInterTT;
printf("%f\t%f\t%f\t", minInterTT, avgInterTT, maxInterTT);
double avgNoInterTT = sumNoInterTT / (double)countNoInterTT;
printf("%f\t%f\t%f\t", minNoInterTT, avgNoInterTT, maxNoInterTT);
double avgTT =
    ratioInter * avgInterTT + (1.0 - ratioInter) * avgNoInterTT;
printf("%f\t%f\t%f\t",
    (minNoInterTT < minInterTT ? minNoInterTT : minInterTT),
    avgTT,
    (maxNoInterTT > maxInterTT ? maxNoInterTT : maxInterTT));

}

}

int main(int argc, char** argv) {

    Qualify2DDynamic();

    return 0;
}

```

8.1.4 3D dynamic

```

// Include standard libraries
#include <stdlib.h>
#include <stdio.h>
#include <stdbool.h>
#include <time.h>
#include <sys/time.h>

// Include FMB and SAT algorithm library
#include "fmb3dt.h"
#include "sat.h"

// Epsilon to detect degenerated triangles
#define EPSILON 0.1

```

```

// Range of values for the random generation of Frames
#define RANGE_AXIS 100.0
// Nb of run
#define NB_RUNS 9
// Nb of tests per run
#define NB_TESTS 100000
// Nb of times the test is run on one pair of frame, used to
// slow down the processus and be able to measure time
#define NB_REPEAT_3D 800

// Helper macro to generate random number in [0.0, 1.0]
#define rnd() (double)(rand())/(double)(RAND_MAX)

// Helper structure to pass arguments to the Qualification function
typedef struct {
    FrameType type;
    double orig[3];
    double comp[3][3];
    double speed[3];
} Param3DTime;

// Global variables to count nb of tests resulting in intersection
// and no intersection, and min/max/total time of execution for each
double minInter;
double maxInter;
double sumInter;
unsigned long countInter;
double minNoInter;
double maxNoInter;
double sumNoInter;
unsigned long countNoInter;

double minInterCC;
double maxInterCC;
double sumInterCC;
unsigned long countInterCC;
double minNoInterCC;
double maxNoInterCC;
double sumNoInterCC;
unsigned long countNoInterCC;

double minInterCT;
double maxInterCT;
double sumInterCT;
unsigned long countInterCT;
double minNoInterCT;
double maxNoInterCT;
double sumNoInterCT;
unsigned long countNoInterCT;

double minInterTC;
double maxInterTC;
double sumInterTC;
unsigned long countInterTC;
double minNoInterTC;
double maxNoInterTC;
double sumNoInterTC;
unsigned long countNoInterTC;

double minInterTT;
double maxInterTT;
double sumInterTT;

```

```

unsigned long countInterTT;
double minNoInterTT;
double maxNoInterTT;
double sumNoInterTT;
unsigned long countNoInterTT;

// Qualification function
// Takes two Frame definition as input, run the intersection test on
// them with FMB and SAT, and measure the time of execution of each
void Qualification3DDynamic(
    const Param3DTime paramP,
    const Param3DTime paramQ) {

    // Create the two Frames
    Frame3DTime P =
        Frame3DTimeCreateStatic(
            paramP.type,
            paramP.orig,
            paramP.speed,
            paramP.comp);

    Frame3DTime Q =
        Frame3DTimeCreateStatic(
            paramQ.type,
            paramQ.orig,
            paramQ.speed,
            paramQ.comp);

    // Helper variables to loop on the pair (that, tho) and (tho, that)
    Frame3DTime* that = &P;
    Frame3DTime* tho = &Q;

    // Loop on pairs of Frames
    for (int iPair = 2;
        iPair--;) {

        // Declare an array to memorize the results of the repeated
        // test on the same pair,
        // to prevent optimization from the compiler to remove the for loop
        bool isIntersectingFMB[NB_REPEAT_3D] = {false};

        // Start measuring time
        struct timeval start;
        gettimeofday(&start, NULL);

        // Run the FMB intersection test
        for (int i = NB_REPEAT_3D;
            i--;) {

            isIntersectingFMB[i] =
                FMBTestIntersection3DTime(
                    that,
                    tho,
                    NULL);
        }

        // Stop measuring time
        struct timeval stop;
        gettimeofday(&stop, NULL);

        // Calculate the delay of execution
        unsigned long deltausFMB = 0;
    }
}

```

```

if (stop.tv_sec < start.tv_sec) {
    printf("time warps, try again\n");
    exit(0);
}
if (stop.tv_sec > start.tv_sec + 1) {
    printf("deltausFMB >> 1s, decrease NB_REPEAT\n");
    exit(0);
}
if (stop.tv_usec < start.tv_usec) {
    deltausFMB = stop.tv_sec - start.tv_sec;
    deltausFMB += stop.tv_usec + 1000000 - start.tv_usec;
} else {
    deltausFMB = stop.tv_usec - start.tv_usec;
}

// Declare an array to memorize the results of the repeated
// test on the same pair,
// to prevent optimization from the compiler to remove the for loop
bool isIntersectingSAT[NB_REPEAT_3D] = {false};

// Start measuring time
gettimeofday(&start, NULL);

// Run the FMB intersection test
for (int i = NB_REPEAT_3D;
     i--;) {

    isIntersectingSAT[i] =
        SATTestIntersection3DTime(
            that,
            tho);
}

// Stop measuring time
gettimeofday(&stop, NULL);

// Calculate the delay of execution
unsigned long deltausSAT = 0;
if (stop.tv_sec < start.tv_sec) {
    printf("time warps, try again\n");
    exit(0);
}
if (stop.tv_sec > start.tv_sec + 1) {
    printf("deltausSAT >> 1s, decrease NB_REPEAT\n");
    exit(0);
}
if (stop.tv_usec < start.tv_usec) {
    deltausSAT = stop.tv_sec - start.tv_sec;
    deltausSAT += stop.tv_usec + 1000000 - start.tv_usec;
} else {
    deltausSAT = stop.tv_usec - start.tv_usec;
}

// If the delays are greater than 10ms
if (deltausFMB >= 10 && deltausSAT >= 10) {

    // If FMB and SAT disagrees
    if (isIntersectingFMB[0] != isIntersectingSAT[0]) {

        printf("Qualification has failed\n");
        Frame3DTimePrint(that);
    }
}

```

```

    printf(" against ");
    Frame3DTimePrint(tho);
    printf("\n");
    printf("FMB : ");
    if (isIntersectingFMB[0] == false)
        printf("no ");
    printf("intersection\n");
    printf("SAT : ");
    if (isIntersectingSAT[0] == false)
        printf("no ");
    printf("intersection\n");

    // Stop the qualification test
    exit(0);
}

// Get the ratio of execution time
double ratio = ((double)deltausFMB) / ((double)deltausSAT);

// If the Frames intersect
if (isIntersectingSAT[0] == true) {

    // Update the counters
    if (countInter == 0) {

        minInter = ratio;
        maxInter = ratio;

    } else {

        if (minInter > ratio)
            minInter = ratio;
        if (maxInter < ratio)
            maxInter = ratio;

    }

    sumInter += ratio;
    ++countInter;

    if (paramP.type == FrameCuboid &&
        paramQ.type == FrameCuboid) {

        if (countInterCC == 0) {

            minInterCC = ratio;
            maxInterCC = ratio;

        } else {

            if (minInterCC > ratio)
                minInterCC = ratio;
            if (maxInterCC < ratio)
                maxInterCC = ratio;

        }

        sumInterCC += ratio;
        ++countInterCC;

    } else if (paramP.type == FrameCuboid &&
                paramQ.type == FrameTetrahedron) {

```

```

    if (countInterCT == 0) {

        minInterCT = ratio;
        maxInterCT = ratio;

    } else {

        if (minInterCT > ratio)
            minInterCT = ratio;
        if (maxInterCT < ratio)
            maxInterCT = ratio;

    }
    sumInterCT += ratio;
    ++countInterCT;

} else if (paramP.type == FrameTetrahedron &&
           paramQ.type == FrameCuboid) {

    if (countInterTC == 0) {

        minInterTC = ratio;
        maxInterTC = ratio;

    } else {

        if (minInterTC > ratio)
            minInterTC = ratio;
        if (maxInterTC < ratio)
            maxInterTC = ratio;

    }
    sumInterTC += ratio;
    ++countInterTC;

} else if (paramP.type == FrameTetrahedron &&
           paramQ.type == FrameTetrahedron) {

    if (countInterTT == 0) {

        minInterTT = ratio;
        maxInterTT = ratio;

    } else {

        if (minInterTT > ratio)
            minInterTT = ratio;
        if (maxInterTT < ratio)
            maxInterTT = ratio;

    }
    sumInterTT += ratio;
    ++countInterTT;

}

// Else, the Frames do not intersect
} else {

    // Update the counters
    if (countNoInter == 0) {

```

```

        minNoInter = ratio;
        maxNoInter = ratio;

    } else {

        if (minNoInter > ratio)
            minNoInter = ratio;
        if (maxNoInter < ratio)
            maxNoInter = ratio;

    }
    sumNoInter += ratio;
    ++countNoInter;

    if (paramP.type == FrameCuboid &&
        paramQ.type == FrameCuboid) {

        if (countNoInterCC == 0) {

            minNoInterCC = ratio;
            maxNoInterCC = ratio;

        } else {

            if (minNoInterCC > ratio)
                minNoInterCC = ratio;
            if (maxNoInterCC < ratio)
                maxNoInterCC = ratio;

        }
        sumNoInterCC += ratio;
        ++countNoInterCC;

    } else if (paramP.type == FrameCuboid &&
        paramQ.type == FrameTetrahedron) {

        if (countNoInterCT == 0) {

            minNoInterCT = ratio;
            maxNoInterCT = ratio;

        } else {

            if (minNoInterCT > ratio)
                minNoInterCT = ratio;
            if (maxNoInterCT < ratio)
                maxNoInterCT = ratio;

        }
        sumNoInterCT += ratio;
        ++countNoInterCT;

    } else if (paramP.type == FrameTetrahedron &&
        paramQ.type == FrameCuboid) {

        if (countNoInterTC == 0) {

            minNoInterTC = ratio;
            maxNoInterTC = ratio;

        } else {

```



```

        if (minNoInterTC > ratio)
            minNoInterTC = ratio;
        if (maxNoInterTC < ratio)
            maxNoInterTC = ratio;

    }
    sumNoInterTC += ratio;
    ++countNoInterTC;

} else if (paramP.type == FrameTetrahedron &&
           paramQ.type == FrameTetrahedron) {

    if (countNoInterTT == 0) {

        minNoInterTT = ratio;
        maxNoInterTT = ratio;

    } else {

        if (minNoInterTT > ratio)
            minNoInterTT = ratio;
        if (maxNoInterTT < ratio)
            maxNoInterTT = ratio;

    }
    sumNoInterTT += ratio;
    ++countNoInterTT;

}

}

// Else, if time of execution for FMB was less than a 10ms
} else if (deltausFMB < 10) {

    printf("deltausFMB < 10ms, increase NB_REPEAT\n");
    exit(0);

// Else, if time of execution for SAT was less than a 10ms
} else if (deltausSAT < 10) {

    printf("deltausSAT < 10ms, increase NB_REPEAT\n");
    exit(0);

}

// Flip the pair of Frames
that = &Q;
tho = &P;

}

}

void Qualify3DDynamic(void) {

    // Initialise the random generator
    srand(time(NULL));

    // Loop on runs
    for (int iRun = 0;
         iRun < NB_RUNS;
         ++iRun) {

```

```

// Ratio intersection/no intersection for the displayed results
double ratioInter = 0.1 + 0.8 * (double)iRun / (double)(NB_RUNS - 1);

// Initialize counters
minInter = 0.0;
maxInter = 0.0;
sumInter = 0.0;
countInter = 0;
minNoInter = 0.0;
maxNoInter = 0.0;
sumNoInter = 0.0;
countNoInter = 0;

minInterCC = 0.0;
maxInterCC = 0.0;
sumInterCC = 0.0;
countInterCC = 0;
minNoInterCC = 0.0;
maxNoInterCC = 0.0;
sumNoInterCC = 0.0;
countNoInterCC = 0;

minInterCT = 0.0;
maxInterCT = 0.0;
sumInterCT = 0.0;
countInterCT = 0;
minNoInterCT = 0.0;
maxNoInterCT = 0.0;
sumNoInterCT = 0.0;
countNoInterCT = 0;

minInterTC = 0.0;
maxInterTC = 0.0;
sumInterTC = 0.0;
countInterTC = 0;
minNoInterTC = 0.0;
maxNoInterTC = 0.0;
sumNoInterTC = 0.0;
countNoInterTC = 0;

minInterTT = 0.0;
maxInterTT = 0.0;
sumInterTT = 0.0;
countInterTT = 0;
minNoInterTT = 0.0;
maxNoInterTT = 0.0;
sumNoInterTT = 0.0;
countNoInterTT = 0;

// Declare two variables to memoize the arguments to the
// Qualification function
Param3DTime paramP;
Param3DTime paramQ;

// Loop on the number of tests
for (unsigned long iTest = NB_TESTS;
     iTest--;) {

    // Create two random Frame definitions
    Param3DTime* param = &paramP;
    for (int iParam = 2;

```

```

        iParam--;) {

// 50% chance of being a Cuboid or a Tetrahedron
if (rnd() < 0.5)
    param->type = FrameCuboid;
else
    param->type = FrameTetrahedron;

for (int iAxis = 3;
    iAxis--;) {

    param->orig[iAxis] = -RANGE_AXIS + 2.0 * rnd() * RANGE_AXIS;
    param->speed[iAxis] = -RANGE_AXIS + 2.0 * rnd() * RANGE_AXIS;

    for (int iComp = 3;
        iComp--;) {

        param->comp[iComp][iAxis] =
            -RANGE_AXIS + 2.0 * rnd() * RANGE_AXIS;

    }

}

param = &paramQ;

}

// Calculate the determinant of the Frames' components matrix

double detP =
    paramP.comp[0][0] * (paramP.comp[1][1] * paramP.comp[2][2] -
    paramP.comp[1][2] * paramP.comp[2][1]) -
    paramP.comp[1][0] * (paramP.comp[0][1] * paramP.comp[2][2] -
    paramP.comp[0][2] * paramP.comp[2][1]) +
    paramP.comp[2][0] * (paramP.comp[0][1] * paramP.comp[1][2] -
    paramP.comp[0][2] * paramP.comp[1][1]);

double detQ =
    paramQ.comp[0][0] * (paramQ.comp[1][1] * paramQ.comp[2][2] -
    paramQ.comp[1][2] * paramQ.comp[2][1]) -
    paramQ.comp[1][0] * (paramQ.comp[0][1] * paramQ.comp[2][2] -
    paramQ.comp[0][2] * paramQ.comp[2][1]) +
    paramQ.comp[2][0] * (paramQ.comp[0][1] * paramQ.comp[1][2] -
    paramQ.comp[0][2] * paramQ.comp[1][1]);

// If the determinants are not null, ie the Frame are not degenerate
if (fabs(detP) > EPSILON && fabs(detQ) > EPSILON) {

    // Run the validation on the two Frames
    Qualification3DDynamic(
        paramP,
        paramQ);

}

}

// Display the results
if (iRun == 0) {

    printf("percPairInter\t");

```

```

printf("countInter\tcountNoInter\t");
printf("minInter\tavgInter\tmaxInter\t");
printf("minNoInter\tavgNoInter\tmaxNoInter\t");
printf("minTotal\tavgTotal\tmaxTotal\t");

printf("countInterCC\tcountNoInterCC\t");
printf("minInterCC\tavgInterCC\tmaxInterCC\t");
printf("minNoInterCC\tavgNoInterCC\tmaxNoInterCC\t");
printf("minTotalCC\tavgTotalCC\tmaxTotalCC\t");

printf("countInterCT\tcountNoInterCT\t");
printf("minInterCT\tavgInterCT\tmaxInterCT\t");
printf("minNoInterCT\tavgNoInterCT\tmaxNoInterCT\t");
printf("minTotalCT\tavgTotalCT\tmaxTotalCT\t");

printf("countInterTC\tcountNoInterTC\t");
printf("minInterTC\tavgInterTC\tmaxInterTC\t");
printf("minNoInterTC\tavgNoInterTC\tmaxNoInterTC\t");
printf("minTotalTC\tavgTotalTC\tmaxTotalTC\t");

printf("countInterTT\tcountNoInterTT\t");
printf("minInterTT\tavgInterTT\tmaxInterTT\t");
printf("minNoInterTT\tavgNoInterTT\tmaxNoInterTT\t");
printf("minTotalTT\tavgTotalTT\tmaxTotalTT\n");
}

printf("%.1f\t", ratioInter);

printf("%lu\t%lu\t", countInter, countNoInter);
double avgInter = sumInter / (double)countInter;
printf("%f\t%f\t%f\t", minInter, avgInter, maxInter);
double avgNoInter = sumNoInter / (double)countNoInter;
printf("%f\t%f\t%f\t", minNoInter, avgNoInter, maxNoInter);
double avg =
    ratioInter * avgInter + (1.0 - ratioInter) * avgNoInter;
printf("%f\t%f\t%f\t",
    (minNoInter < minInter ? minNoInter : minInter),
    avg,
    (maxNoInter > maxInter ? maxNoInter : maxInter));

printf("%lu\t%lu\t", countInterCC, countNoInterCC);
double avgInterCC = sumInterCC / (double)countInterCC;
printf("%f\t%f\t%f\t", minInterCC, avgInterCC, maxInterCC);
double avgNoInterCC = sumNoInterCC / (double)countNoInterCC;
printf("%f\t%f\t%f\t", minNoInterCC, avgNoInterCC, maxNoInterCC);
double avgCC =
    ratioInter * avgInterCC + (1.0 - ratioInter) * avgNoInterCC;
printf("%f\t%f\t%f\t",
    (minNoInterCC < minInterCC ? minNoInterCC : minInterCC),
    avgCC,
    (maxNoInterCC > maxInterCC ? maxNoInterCC : maxInterCC));

printf("%lu\t%lu\t", countInterCT, countNoInterCT);
double avgInterCT = sumInterCT / (double)countInterCT;
printf("%f\t%f\t%f\t", minInterCT, avgInterCT, maxInterCT);
double avgNoInterCT = sumNoInterCT / (double)countNoInterCT;
printf("%f\t%f\t%f\t", minNoInterCT, avgNoInterCT, maxNoInterCT);
double avgCT =
    ratioInter * avgInterCT + (1.0 - ratioInter) * avgNoInterCT;
printf("%f\t%f\t%f\t",
    (minNoInterCT < minInterCT ? minNoInterCT : minInterCT),

```

```

        avgCT,
        (maxNoInterCT > maxInterCT ? maxNoInterCT : maxInterCT));

printf("%lu\t%lu\t", countInterTC, countNoInterTC);
double avgInterTC = sumInterTC / (double)countInterTC;
printf("%f\t%f\t%f\t", minInterTC, avgInterTC, maxInterTC);
double avgNoInterTC = sumNoInterTC / (double)countNoInterTC;
printf("%f\t%f\t%f\t", minNoInterTC, avgNoInterTC, maxNoInterTC);
double avgTC =
    ratioInter * avgInterTC + (1.0 - ratioInter) * avgNoInterTC;
printf("%f\t%f\t%f\t",
    (minNoInterTC < minInterTC ? minNoInterTC : minInterTC),
    avgTC,
    (maxNoInterTC > maxInterTC ? maxNoInterTC : maxInterTC));

printf("%lu\t%lu\t", countInterTT, countNoInterTT);
double avgInterTT = sumInterTT / (double)countInterTT;
printf("%f\t%f\t%f\t", minInterTT, avgInterTT, maxInterTT);
double avgNoInterTT = sumNoInterTT / (double)countNoInterTT;
printf("%f\t%f\t%f\t", minNoInterTT, avgNoInterTT, maxNoInterTT);
double avgTT =
    ratioInter * avgInterTT + (1.0 - ratioInter) * avgNoInterTT;
printf("%f\t%f\t%f\t\n",
    (minNoInterTT < minInterTT ? minNoInterTT : minInterTT),
    avgTT,
    (maxNoInterTT > maxInterTT ? maxNoInterTT : maxInterTT));

}

}

int main(int argc, char** argv) {

    Qualify3DDynamic();

    return 0;
}

```


8.2 Results



8.2.1 2D static


percPairInter	countInter	countNoInter	minInter	avgInter		
	maxInter	minNoInter	avgNoInter	maxNoInter		
minTotal	avgTotal	maxTotal	countInterCC			
countNoInterCC	minInterCC	avgInterCC	maxInterCC			
minNoInterCC	avgNoInterCC	maxNoInterCC	minTotalCC			
avgTotalCC	maxTotalCC	countInterCT	countNoInterCT			
minInterCT	avgInterCT	maxInterCT	minNoInterCT			
avgNoInterCT	maxNoInterCT	minTotalCT	avgTotalCT			
maxTotalCT	countInterTC	countNoInterTC	minInterTC			
avgInterTC	maxInterTC	minNoInterTC	avgNoInterTC			
maxNoInterTC	minTotalTC	avgTotalTC	maxTotalTC			
countInterTT	countNoInterTT	minInterTT	avgInterTT			
maxInterTT	minNoInterTT	avgNoInterTT	maxNoInterTT			
minTotalTT	avgTotalTT	maxTotalTT				
0.1	46962	153028	0.478788	1.680693	4.288462	
0.125000		0.858409		10.733333	0.125000	0.940638
	10.733333	13314	36674	0.957746	2.187802	
4.288462		0.183333	0.794498	4.829268		0.183333
	0.933828	4.829268	11628	38198	0.688889	

	1.624381	3.551724	0.125000	0.868894	8.062500
	0.125000	0.944443	8.062500	11692	38482
0.619048	1.621586	3.431034	0.185714	0.861089	
	10.733333	0.185714	0.937138	10.733333	
10328	39674	0.478788	1.157283	2.761194	0.179104
	0.904795	6.676471	0.179104	0.930044	
	6.676471				
0.2	47086	152912	0.344538	1.686093	6.490566
	0.054054	0.863394	13.125000	0.054054	1.027934
	13.125000	12874	37040	0.430147	2.197804
6.490566	0.110294	0.803862	7.529412	0.110294	
	1.082650	7.529412	11884	38062	0.618421
1.635506	6.015873	0.054054	0.865279		
13.125000	0.054054	1.019325	13.125000	12000	
38388	0.544041	1.632829	4.100000	0.067797	
0.871729	10.866667	0.067797	1.023949		
10.866667	10328	39422	0.344538	1.168334	5.289855
	0.068571	0.909394	9.400000	0.068571	
	0.961182	9.400000			
0.3	47148	152846	0.480663	1.690696	5.849057
	0.100840	0.859934	12.400000	0.100840	1.109163
	12.400000	13406	36448	0.725000	2.196463
5.849057	0.113208	0.798751	5.744681	0.113208	
	1.218065	5.849057	11774	38188	0.560538
1.639288	4.065574	0.113043	0.867135		
12.312500	0.113043	1.098781	12.312500	11662	
38594	0.643312	1.626870	5.812500	0.123810	
0.860912	8.400000	0.123810	1.090699	8.400000	
	10306	39616	0.480663	1.163753	3.458333
0.100840	0.908329	12.400000	0.100840	0.984957	
	12.400000				
0.4	46944	153050	0.465517	1.683345	6.202899
	0.097744	0.862560	10.600000	0.097744	1.190874
	10.600000	13028	36712	0.815603	2.193450
6.202899	0.100000	0.796052	6.000000	0.100000	
	1.355012	6.202899	11736	38372	0.607843
1.630236	3.932203	0.097744	0.873062	9.666667	
	0.097744	1.175932	9.666667	11926	38416
0.481651	1.627287	4.084746	0.113043	0.865155	
	7.833333	0.113043	1.170008	7.833333	
10254	39550	0.465517	1.161224	3.800000	0.125000
	0.911586	10.600000	0.125000	1.011441	
	10.600000				
0.5	47112	152882	0.453488	1.680283	4.230769
	0.132653	0.858366	7.187500	0.132653	1.269324
	7.187500	13192	36662	1.082707	2.185578
4.230769	0.210526	0.795267	4.268293	0.210526	
	1.490423	4.268293	11884	38232	1.008403
1.625789	3.245614	0.146067	0.863856	7.062500	
	0.146067	1.244823	7.062500	11870	38500
0.675676	1.621346	3.508475	0.132653	0.864577	
	7.187500	0.132653	1.242961	7.187500	
10166	39488	0.453488	1.157100	2.805970	0.179104
	0.905578	5.928571	0.179104	1.031339	
	5.928571				
0.6	47300	152686	0.396624	1.683549	5.076923
	0.113043	0.854979	9.411765	0.113043	1.352121
	9.411765	13364	36916	0.917241	2.190781
5.076923	0.113043	0.798633	6.769231	0.113043	
	1.633922	6.769231	11926	38126	0.429245
1.627151	4.706897	0.157895	0.858416	8.642857	
	0.157895	1.319657	8.642857	11732	38060

	0.396624	1.622619	4.200000	0.147727	0.856155
	7.562500	0.147727	1.316033	7.562500	
10278	39584	0.445714	1.159011	2.909091	0.156627
	0.903086	9.411765	0.156627	1.056641	
	9.411765				
0.7	46830	153154	0.462857	1.682094	5.178571
	0.069767	0.857451	10.142857	0.069767	1.434701
	10.142857	13100	36858	0.688235	2.189836
5.178571	0.133333		0.793714	5.128205	0.133333
	1.770999	5.178571	11908	38002	0.580247
1.628544	4.163934		0.069767	0.864791	6.500000
	0.069767	1.399418	6.500000	11638	38584
0.554878	1.623077	3.816667	0.090909		0.861540
	8.066667	0.090909	1.394616	8.066667	
10184	39710	0.462857	1.159027	2.971014	0.146067
	0.905615	10.142857	0.146067	1.083004	
	10.142857				
0.8	46856	153134	0.445714	1.681043	4.210526
	0.097561	0.854423	7.666667	0.097561	1.515719
	7.666667	13398	37072	0.974790	2.184435
4.037736	0.097561		0.793168	3.763158	0.097561
	1.906182	4.037736	11478	38294	0.611111
1.624253	2.697674		0.220339	0.858477	7.428571
	0.220339	1.471098	7.428571	11706	37984
0.978947	1.620454	4.210526	0.239130		0.858422
	7.666667	0.239130	1.468047	7.666667	
10274	39784	0.445714	1.157067	2.833333	0.106557
	0.903781	6.142857	0.106557	1.106410	
	6.142857				
0.9	47260	152736	0.600000	1.681716	4.411765
	0.088000	0.856551	7.933333	0.088000	1.599199
	7.933333	13450	36628	1.173469	2.187034
4.411765	0.231884		0.792770	3.850000	0.231884
	2.047607	4.411765	11612	38350	0.824561
1.625105	2.474576		0.254902	0.867328	6.642857
	0.254902	1.549327	6.642857	11868	38176
0.600000	1.621078	3.473684	0.209677		0.858177
	6.266667	0.209677	1.544788	6.266667	
10330	39582	0.614173	1.157078	2.803030	0.088000
	0.903563	7.933333	0.088000	1.131727	
	7.933333				











8.2.2 3D static

percPairInter	countInter	countNoInter	minInter	avgInter
	maxInter	minNoInter	avgNoInter	maxNoInter
minTotal	avgTotal	maxTotal	countInterCC	
countNoInterCC	minInterCC	avgInterCC	maxInterCC	
minNoInterCC	avgNoInterCC	maxNoInterCC	minTotalCC	
avgTotalCC	maxTotalCC	countInterCT	countNoInterCT	
minInterCT	avgInterCT	maxInterCT	minNoInterCT	
avgNoInterCT	maxNoInterCT	minTotalCT	avgTotalCT	
maxTotalCT	countInterTC	countNoInterTC	minInterTC	
avgInterTC	maxInterTC	minNoInterTC	avgNoInterTC	
maxNoInterTC	minTotalTC	avgTotalTC	maxTotalTC	
countInterTT	countNoInterTT	minInterTT	avgInterTT	
minInterTT	minNoInterTT	avgNoInterTT	maxNoInterTT	
minTotalTT	avgTotalTT	maxTotalTT		
0.1	31478	168522	0.153967	0.494154
				1.104478
0.038082	0.548169	9.062500	0.038082	0.542768
	9.062500	10616	39180	0.502475
				0.741534
1.104478	0.063596	0.395844	2.951049	0.063596
	0.430413	2.951049	7858	42396
				0.224467
0.415367	0.725434	0.046053	0.536495	9.062500
	0.046053	0.524382	9.062500	7822
				42292
0.222951	0.415492	0.679012	0.045171	0.531304
	8.281250	0.045171	0.519723	8.281250
5182	44654	0.153967	0.225571	0.292978
	0.708880	7.920000	0.038082	0.660549
7.920000				
0.2	31990	168008	0.181401	0.493077
				1.062958
0.038793	0.549532	8.843750	0.038793	0.538241
	8.843750	10716	39062	0.587977
				0.741692
1.062958	0.062762	0.397876	2.965517	0.062762
	0.466639	2.965517	7820	42262
				0.274045
0.415494	0.577810	0.045902	0.537255	8.750000
	0.045902	0.512903	8.750000	8100
				42214
0.271622	0.415845	0.581197	0.045381	0.532207
	8.843750	0.045381	0.508934	8.843750
5354	44470	0.181401	0.225637	0.296252
	0.710857	8.416667	0.038793	0.613813
8.416667				
0.3	32034	167966	0.175223	0.494816
				0.871870
0.031298	0.551022	9.200000	0.031298	0.534160
	9.200000	10930	39572	0.542582
				0.741431
0.864407	0.065646	0.395645	2.944828	0.065646
	0.499381	2.944828	7728	41900
				0.274968
0.415915	0.871870	0.045161	0.537350	9.200000
	0.045161	0.500919	9.200000	7960
				41816
0.272230	0.415764	0.570381	0.045016	0.534694
	8.968750	0.045016	0.499015	8.968750
5416	44678	0.175223	0.225889	0.279213
	0.716748	8.125000	0.031298	0.569490
8.125000				
0.4	31818	168182	0.163245	0.493042
				1.250760
0.036936	0.547619	9.677419	0.036936	0.525788
	9.677419	10616	39210	0.521236
				0.741773
1.250760	0.062500	0.395155	3.027397	0.062500
	0.533802	3.027397	7940	41910
				0.274590
0.415556	0.572464	0.045677	0.529730	9.677419
	0.045677	0.484060	9.677419	8000
				42360
0.271429	0.415905	0.563609	0.045234	0.528124
	8.937500	0.045234	0.483236	8.937500
5262	44702	0.163245	0.225429	0.404678
	0.716598	8.166667	0.036936	0.520130
8.166667				

0.5	31848	168152	0.180208	0.493484	0.892791	
	0.039548	0.549296		9.129032	0.039548	0.521390
	9.129032	10718	39586	0.592424	0.741641	
0.892791	0.066514		0.396111		2.931034	0.066514
	0.568876	2.931034	7814	41986	0.216713	
0.415310	0.598837		0.044776	0.531125	9.129032	
	0.044776	0.473217	9.129032	7984	41724	
0.261034	0.415648		0.577424	0.046667	0.532189	
	9.064516	0.046667	0.473918	9.064516		
5332	44856	0.180208	0.225771	0.287860	0.039548	
	0.717407	8.565217	0.039548	0.471589		
	8.565217					
0.6	31236	168764	0.186603	0.493514	0.877323	
	0.037762	0.548509		8.937500	0.037762	0.515512
	8.937500	10400	39442	0.637048	0.741701	
0.877323	0.064302		0.394465	3.157534	0.064302	
	0.602807	3.157534	7782	42014	0.271255	
0.415913	0.602339		0.042945	0.531548	8.774194	
	0.042945	0.462167	8.774194	7988	42142	
0.267568	0.415687		0.568047	0.045752	0.533325	
	8.937500	0.045752	0.462742	8.937500		
5066	45166	0.186603	0.225930	0.316877	0.037762	
	0.712975	8.166667	0.037762	0.420748		
	8.166667					
0.7	31100	168898	0.164050	0.493901	0.837887	
	0.037037	0.546780		8.875000	0.037037	0.509765
	8.875000	10416	39924	0.593607	0.741501	
0.837887	0.066059		0.398390	3.000000	0.066059	
	0.638568	3.000000	7764	42496	0.267023	
0.415769	0.560870		0.045307	0.534521	8.718750	
	0.045307	0.451395	8.718750	7866	42116	
0.256989	0.415539		0.637037	0.045597	0.527322	
	8.875000	0.045597	0.449074	8.875000		
5054	44362	0.164050	0.225602	0.407494	0.037037	
	0.710542	8.375000	0.037037	0.371084		
	8.375000					
0.8	31570	168430	0.183099	0.494058	0.977570	
	0.041379	0.550069		9.129032	0.041379	0.505260
	9.129032	10658	38766	0.374885	0.741284	
0.977570	0.067285		0.393096	3.113772	0.067285	
	0.671646	3.113772	7898	42034	0.269076	
0.415545	0.612991		0.046205	0.536427	9.031250	
	0.046205	0.439721	9.031250	7774	42434	
0.264892	0.415891		0.572474	0.046589	0.531436	
	9.129032	0.046589	0.439000	9.129032		
5240	45196	0.183099	0.225512	0.304348	0.041379	
	0.714891	8.208333	0.041379	0.323388		
	8.208333					
0.9	31536	168464	0.184149	0.494905	0.919591	
	0.037975	0.548227		9.129032	0.037975	0.500237
	9.129032	10612	39240	0.654605	0.741446	
0.871841	0.065611		0.397763	2.917241	0.065611	
	0.707078	2.917241	7876	42208	0.271255	
0.415875	0.589706		0.045902	0.535402	8.906250	
	0.045902	0.427827	8.906250	7976	41912	
0.252488	0.416167		0.919591	0.045814	0.530613	
	9.129032	0.045814	0.427611	9.129032		
5072	45104	0.184149	0.225615	0.273973	0.037975	
	0.707499	8.120000	0.037975	0.273803		
	8.120000					











8.2.3 2D dynamic

	percPairInter	countInter	countNoInter	minInter	avgInter
	maxInter	minNoInter	avgNoInter	maxNoInter	
	minTotal	avgTotal	maxTotal	countInterCC	
	countNoInterCC	minInterCC	avgInterCC	maxInterCC	
	minNoInterCC	avgNoInterCC	maxNoInterCC	minTotalCC	
	avgTotalCC	maxTotalCC	countInterCT	countNoInterCT	
	minInterCT	avgInterCT	maxInterCT	minNoInterCT	
	avgNoInterCT	maxNoInterCT	minTotalCT	avgTotalCT	
	maxTotalCT	countInterTC	countNoInterTC	minInterTC	
	avgInterTC	maxInterTC	minNoInterTC	avgNoInterTC	
	maxNoInterTC	minTotalTC	avgTotalTC	maxTotalTC	
	countInterTT	countNoInterTT	minInterTT	avgInterTT	
	maxInterTT	minNoInterTT	avgNoInterTT	maxNoInterTT	
	minTotalTT	avgTotalTT	maxTotalTT		
0.1	74904	125088	0.887681	2.016953	4.174825
	0.091954	1.123632	16.230769	0.091954	1.212964
	16.230769	20132	29730	1.393305	2.538785
	3.503876	0.099291	1.081980	15.964286	0.099291
	1.227661	15.964286	18670	31428	0.996241
	1.974649	3.169118	0.103704	1.127723	
	14.576923	0.103704	1.212415	14.576923	18712
	31296	1.023256	1.973773	4.174825	0.091954
	1.139832	16.230769	0.091954	1.223226	
	16.230769	17390	32634	0.887681	1.504720
				1.504720	2.158537
	0.151786	1.142100	10.958333	0.151786	
	1.178362	10.958333			
0.2	74408	125588	1.104072	2.014288	3.407143
	0.113821	1.129257	13.416667	0.113821	1.306263
	13.416667	19804	29962	1.728643	2.538732
	3.121212	0.150943	1.060670	12.777778	0.150943
	1.356282	12.777778	18580	31448	1.253521
	1.975341	3.407143	0.113821	1.142465	
	13.375000	0.113821	1.309040	13.375000	18536
	31290	1.121339	1.973529	2.659420	0.140187
	1.135709	13.416667	0.140187	1.303273	
	13.416667	17488	32888	1.104072	1.504969
				1.504969	1.987342
	0.134454	1.172975	10.600000	0.134454	
	1.239374	10.600000			
0.3	74358	125638	1.186275	2.014763	3.122137
	0.114286	1.130617	14.208333	0.114286	1.395861
	14.208333	19750	30042	1.743719	2.538178
	3.122137	0.137615	1.061672	14.071429	0.137615
	1.504624	14.071429	18628	31770	1.233645
	1.974801	2.719745	0.114286	1.120817	
	14.208333	0.114286	1.377012	14.208333	18738
	31306	1.186275	1.972418	3.000000	0.148148
	1.141991	13.720000	0.148148	1.391119	
	13.720000	17242	32520	1.211340	1.504407
				1.504407	1.772152
	0.163265	1.192935	10.520000	0.163265	
	1.286377	10.520000			
0.4	74322	125672	1.216080	2.014599	3.068702
	0.137931	1.129479	13.375000	0.137931	1.483527
	13.375000	19900	30048	1.930636	2.537540
	3.068702	0.162963	1.111343	12.892857	0.162963
	1.681822	12.892857	18572	31356	1.315271
	1.973800	2.595588	0.145455	1.117667	
	13.375000	0.145455	1.460120	13.375000	18456
	31598	1.264151	1.973124	2.743056	0.137931
	1.136260	13.291667	0.137931	1.471005	
	13.291667	17394	32670	1.216080	1.503885
				1.503885	2.000000
	0.163265	1.150937	10.250000	0.163265	
	1.292116	10.250000			

0.5	74472	125514	1.042636	2.018063	3.845070	
	0.128571		1.120983	14.320000	0.128571	1.569523
		14.320000	20000	30204	1.736041	2.538760
	3.143939	0.176471		1.066312	13.464286	0.176471
		1.802536	13.464286	18764	31428	1.350515
	1.974423	2.633094		0.128571	1.151204	
	13.458333	0.128571		1.562814	13.458333	18644
	30888	1.042636	1.973501	3.845070		0.144144
	1.125652	14.320000		0.144144	1.549576	
	14.320000	17064	32994	1.129630	1.504453	1.801282
		0.155963	1.137871	10.800000	0.155963	
	1.321162		10.800000			
0.6	74282	125710	1.172589	2.014373	4.500000	
	0.145455		1.118622	13.416667	0.145455	1.656072
		13.416667	19846	30348	1.936782	2.538218
	3.126866	0.164835		1.057982	12.928571	0.164835
		1.946124	12.928571	18562	31568	1.329949
	1.974937	4.500000		0.145455	1.112257	
	13.333333	0.145455		1.629865	13.333333	18378
	31314	1.355330	1.974223	4.092199	0.145455	
	1.148040	13.416667		0.145455	1.643750	
	13.416667	17496	32480	1.172589	1.504179	1.943396
		0.160920	1.153105	10.307692	0.160920	
	1.363749		10.307692			
0.7	74126	125862	1.060606	2.015015	4.000000	
	0.120567		1.120093	13.760000	0.120567	1.746539
		13.760000	19574	30328	1.965116	2.539467
	4.000000	0.166667		1.094054	13.178571	0.166667
		2.105843	13.178571	18724	31270	1.352041
	1.975064	2.715328		0.120567	1.129948	
	13.760000	0.120567		1.721529	13.760000	18698
	31490	1.364103	1.973141	2.713287	0.131579	
	1.109659	13.416667		0.131579	1.714097	
	13.416667	17130	32774	1.060606	1.505115	1.838509
		0.132075	1.144809	10.565217	0.132075	
	1.397023		10.565217			
0.8	74850	125140	1.198198	2.014153	3.257353	
	0.128205		1.130805	13.416667	0.128205	1.837484
		13.416667	19840	29836	2.000000	2.538889
	2.984848	0.158416		1.068731	12.851852	0.158416
		2.244857	12.851852	18640	31440	1.198198
	1.974329	3.257353		0.146789	1.121343	
	13.333333	0.146789		1.803732	13.333333	18894
	31360	1.461538	1.973791	2.639706	0.128205	
	1.153944	13.416667		0.128205	1.809821	
	13.416667	17476	32504	1.210256	1.504551	1.779874
		0.144231	1.174611	10.652174	0.144231	
	1.438563		10.652174			
0.9	74332	125658	1.189320	2.014103	3.044776	
	0.104972		1.133795	13.800000	0.104972	1.926072
		13.800000	19712	29930	1.897727	2.538934
	3.044776	0.104972		1.098386	13.259259	0.104972
		2.394879	13.259259	18660	31722	1.214286
	1.974944	2.884892		0.146789	1.153082	
	13.800000	0.146789		1.892758	13.800000	18564
	31338	1.321543	1.973722	2.935714	0.146789	
	1.128099	13.375000		0.146789	1.889160	
	13.375000	17396	32668	1.189320	1.504494	2.043750
		0.144330	1.152971	10.695652	0.144330	
	1.469342		10.695652			


















8.2.4 3D dynamic

	percPairInter	countInter	countNoInter	minInter	avgInter
	maxInter	minNoInter	avgNoInter	maxNoInter	
	minTotal	avgTotal	maxTotal	countInterCC	
	countNoInterCC	minInterCC	avgInterCC	maxInterCC	
	minNoInterCC	avgNoInterCC	maxNoInterCC	minTotalCC	
	avgTotalCC	maxTotalCC	countInterCT	countNoInterCT	
	minInterCT	avgInterCT	maxInterCT	minNoInterCT	
	avgNoInterCT	maxNoInterCT	minTotalCT	avgTotalCT	
	maxTotalCT	countInterTC	countNoInterTC	minInterTC	
	avgInterTC	maxInterTC	minNoInterTC	avgNoInterTC	
	maxNoInterTC	minTotalTC	avgTotalTC	maxTotalTC	
	countInterTT	countNoInterTT	minInterTT	avgInterTT	
	maxInterTT	minNoInterTT	avgNoInterTT	maxNoInterTT	
	minTotalTT	avgTotalTT	maxTotalTT		
0.1	52834	147166	0.293536	1.621781	5.554522
	0.026941	0.673400	28.131579	0.026941	0.768238
	28.131579	16438	34000	2.030624	2.598016
	5.554522	0.037229	0.580840	12.801724	0.037229
	0.782557	12.801724	13292	36906	0.443189
	1.412200	2.560372	0.026941	0.670200	
	21.884615	0.026941	0.744400	21.884615	13130
	36886	0.473267	1.412854	2.610092	0.027265
	0.675163	23.042553	0.027265	0.748932	
	23.042553	9974	39374	0.293536	0.567197
	0.027642	0.754674	28.131579	0.027642	1.144033
	0.735926	28.131579			
0.2	52496	147504	0.297245	1.611068	4.495770
	0.025680	0.673903	27.864865	0.025680	0.861336
	27.864865	16046	34134	2.079112	2.598359
	4.495770	0.035821	0.577536	12.952991	0.035821
	0.981700	12.952991	13314	36450	0.444610
	1.413174	3.315465	0.025895	0.678187	
	21.760000	0.025895	0.825185	21.760000	12970
	36694	0.470246	1.410916	2.596774	0.026139
	0.667901	19.851852	0.026139	0.816504	
	19.851852	10166	40226	0.297245	0.567261
	0.025680	0.757268	27.864865	0.025680	0.927667
	0.719267	27.864865			
0.3	52580	147420	0.284794	1.615521	4.125326
	0.025699	0.676105	28.891892	0.025699	0.957930
	28.891892	16238	33772	1.860606	2.597153
	4.125326	0.037190	0.600904	12.893162	0.037190
	1.199778	12.893162	13096	36582	0.476882
	1.414129	3.504756	0.027195	0.658051	
	20.377358	0.027195	0.884874	20.377358	13080
	36770	0.474621	1.413627	3.389014	0.026583
	0.669740	17.750000	0.026583	0.892906	
	17.750000	10166	40296	0.284794	0.566778
	0.025699	0.761331	28.891892	0.025699	0.851471
	0.702965	28.891892			
0.4	52136	147864	0.300667	1.610720	4.310680
	0.025641	0.673124	26.081081	0.025641	1.048163
	26.081081	15984	33904	1.953926	2.598292
	4.310680	0.036585	0.578696	12.817797	0.036585
	1.386535	12.817797	13032	36908	0.468912
	1.410582	2.571210	0.026415	0.675365	
	22.183673	0.026415	0.969452	22.183673	12962
	36872	0.476412	1.412745	2.774218	0.025641
	0.672327	22.392157	0.025641	0.968494	
	22.392157	10158	40180	0.300667	0.566126
	0.025699	0.751476	26.081081	0.025699	1.253004
	0.677336	26.081081			

0.5	52316	147684	0.289695	1.603446	3.223881	
	0.025954		0.672255	28.621622	0.025954	1.137850
		28.621622	15826	33988	2.090846	2.598208
	3.223881		0.038015	0.571280		12.838298
		1.584744		12.838298	13010	36860
						0.473443
	1.411593		2.620795	0.026194		0.680416
	21.346154		0.026194	1.046005		21.346154
						13182
	36868	0.480808		1.409444	2.821536	0.026355
	0.659600		22.392157	0.026355		1.034522
	22.392157		10298	39968	0.289695	0.565401
						0.768662
		0.025954		0.762271	28.621622	0.025954
	0.663836		28.621622			
0.6	52058	147942	0.290957	1.616332	2.997412	
	0.025622		0.675253	28.297297	0.025622	1.239901
		28.297297	16046	33684	2.104635	2.597714
	2.997412		0.037736	0.591699		13.037190
		1.795308		13.037190	13154	37674
						0.476882
	1.414123		2.533643	0.025777		0.663853
	21.196078		0.025777	1.114015		21.196078
						12912
	36994	0.477554		1.410784	2.493426	0.025622
	0.675603		22.960000	0.025622		1.116712
	22.960000		9946	39590	0.290957	0.567332
						0.765647
		0.025660		0.756865	28.297297	0.025660
	0.643145		28.297297			
0.7	52652	147348	0.285806	1.606088	3.181495	
	0.025974		0.671622	28.837838	0.025974	1.325748
		28.837838	16030	34170	2.026720	2.597686
	3.181495		0.037618	0.574623		13.247934
		1.990767		13.247934	13290	36654
						0.480078
	1.409727		2.526765	0.027174		0.675366
	20.865385		0.027174	1.189419		20.865385
						13006
	36830	0.477044		1.410236	2.632716	0.026275
	0.662360		21.711538	0.026275		1.185873
	21.711538		10326	39694	0.285806	0.566149
						0.772135
		0.025974		0.760259	28.837838	0.025974
	0.624382		28.837838			
0.8	51706	148294	0.298597	1.607612	3.224184	
	0.026255		0.689141	28.135135	0.026255	1.423917
		28.135135	15726	33722	1.962745	2.597139
	3.224184		0.037190	0.592550		12.886076
		2.196221		12.886076	13024	37138
						0.477513
	1.409518		2.887615	0.026255		0.689044
	22.153846		0.026255	1.265424		22.153846
						12924
	37402	0.478232		1.411528	2.648587	0.026500
	0.683794		22.211538	0.026500		1.265981
	22.211538		10032	40032	0.298597	0.566228
						0.829452
		0.026758		0.775593	28.135135	0.026758
	0.608101		28.135135			
0.9	52292	147708	0.300539	1.619419	3.315975	
	0.025738		0.681886	27.973684	0.025738	1.525666
		27.973684	16096	34110	2.048932	2.597994
	3.315975		0.036885	0.591668		13.038793
		2.397361		13.038793	13338	36942
						0.410185
	1.410209		2.519380	0.027135		0.680580
	22.211538		0.027135	1.337246		22.211538
						13104
	36740	0.449684		1.414520	2.541764	0.026418
	0.680745		22.254902	0.026418		1.341143
	22.254902		9754	39916	0.300539	0.565933
						0.752949
		0.025738		0.761239	27.973684	0.025738
	0.585464		27.973684			







9 Conclusion

The validation proves that the FMB algorithm correctly identifies intersection of pairs of Frames in accordance with the results of the SAT algorithm.

The qualification shows that the FMB is 1.2 to 1.8 times slower than the SAT algorithm in the 2D dynamic case. However it is around 2 times faster in the 3D static case, and up to 1.25 times faster in 3D dynamic and up to 1.1 times faster in the 2D static case if the percentage of tested pairs in intersection is less than, respectively, around 40% and 25%.

On one given pair of Frame, the relative speed of the FMB algorithm varies widely, from around 20 times slower to 50 times faster. This is explained by the way the 2 algorithms works: they both make the assumption that the Frames are intersecting and run through a series of tests to try to prove it wrong. This leads to best cases and worst cases for both algorithm: a non intersecting detected right from the first test, or one detected by the last test. These best and worst cases are different for the two algorithm as the tests they performed are completely different. But globally, the FMB algorithm has the advantage.

10 Annex

10.1 Runtime environment

Results introduce in this paper have been produced by compiling and running the corresponding algorithms in the following environment:

```
> uname -v 4.0 18.04.1-Ubuntu SMP Thu Nov 14 12:06:39 UTC 2019
> lshw -short H/W path Device Class Description =====
system VC65-C1 /0 bus VC65-C1 /0/0 memory 64KiB BIOS /0/2f memory 16GiB System Memory /0/2f/0
memory [empty] /0/2f/1 memory 16GiB SODIMM DDR4 Synchronous 2400 MHz (0.4 ns) /0/39 memory 384KiB
L1 cache /0/3a memory 1536KiB L2 cache /0/3b memory 12MiB L3 cache /0/3c processor Intel(R) Core(TM)
i7-8700T CPU @ 2.40GHz /0/100 bridge 8th Gen Core Processor Host Bridge/DRAM Registers /0/100/2
display Intel Corporation /0/100/12 generic Cannon Lake PCH Thermal Controller /0/100/14 bus
Cannon Lake PCH USB 3.1 xHCI Host Controller /0/100/14/0 usb1 bus xHCI Host Controller /0/100/14/0/5
input ELECOM Wired Keyboard /0/100/14/0/6 input PTZ-630 /0/100/14/0/7 generic USB2.0-CRW /0/100/14/0/e
communication Bluetooth wireless interface /0/100/14/1 usb2 bus xHCI Host Controller /0/100/14.2
memory RAM memory /0/100/14.3 wlo1 network Wireless-AC 9560 [Jefferson Peak] /0/100/16 communication
Cannon Lake PCH HECI Controller /0/100/17 storage Cannon Lake PCH SATA AHCI Controller /0/100/1f
bridge Intel Corporation /0/100/1f.3 multimedia Cannon Lake PCH cAVS /0/100/1f.4 bus Cannon Lake
PCH SMBus Controller /0/100/1f.5 bus Cannon Lake PCH SPI Controller /0/100/1f.6 eno2 network
Ethernet Connection (7) I219-V /0/1 scsi0 storage /0/1/0.0.0 /dev/sda disk 128GB HFS128G39TND-N21
/0/1/0.0.0/1 volume 99MiB Windows FAT volume /0/1/0.0.0/2 /dev/sda2 volume 15MiB reserved partition
/0/1/0.0.0/3 /dev/sda3 volume 83GiB Windows NTFS volume /0/1/0.0.0/4 /dev/sda4 volume 499MiB
Windows NTFS volume /0/1/0.0.0/5 /dev/sda5 volume 35GiB EXT4 volume /0/2 scsi2 storage /0/2/0.0.0
```

```

/dev/sdb disk 500GB ST500LM034-2GH17 /0/2/0.0.0/1 /dev/sdb1 volume 463GiB EXT4 volume /0/2/0.0.0/2
/dev/sdb2 volume 499MiB Windows FAT volume /0/3 scsi5 storage /0/3/0.0.0 /dev/cdrom disk BD-RE
BU50N /1 power To Be Filled By O.E.M.
> lscpu Architecture: x86_64CPUop-mode(s): 32-bit, 64-bitByteOrder: LittleEndianCPU(s):
12On-lineCPU(s)list: 0-11Thread(s)percore: 2Core(s)persocket: 6Socket(s): 1NUMAnode(s):
1VendorID: GenuineIntelCPUfamily: 6Model: 158Modelname: Intel(R)Core(TM)i7-8700TCPU@2.40GHzStepping:
10CPUMHz: 1380.998CPUMaxMHz: 4000.0000CPUMinMHz: 800.0000BogoMIPS: 4800.00Virtualization:
VT-xL1dcache: 32KL1icache: 32KL2cache: 256KL3cache: 12288KNUMAnode0CPU(s): 0-
11Flags: fpuvmedepsetscmsrpaemcecx8apicsepmtrrpgemcasmovpatpse36clflushdtsacpimmxfsrssesse2sshttmptesyscallnxpdp
> gcc -v Using built-in specs. COLLECT_GCC = gccCOLLECT_LTO_WRAPPER = /usr/lib/gcc/x86_64-
linux-gnu/7/lto-wrapperOFFLOAD_TARGET_NAMES = nvptx-noneOFFLOAD_TARGET_DEFAULT =
1Target: x86_64-linux-gnuConfigured with: ../src/configure-v--with-pkgversion='Ubuntu7.4.0-
1ubuntu1 18.04.1'--with-bugurl=file:///usr/share/doc/gcc-7/README.Bugs--enable-
languages=c,ada,c++,go,brig,d,fortran,objc,obj-c++--prefix=/usr--with-gcc-major-
version-only--program-suffix=-7--program-prefix=x86_64-linux-gnu--enable-
shared--enable-linker-build-id--libexecdir=/usr/lib--without-included-gettext--enable-
threads=posix--libdir=/usr/lib--enable-nls--with-sysroot=/--enable-clocale=
gnu--enable-libstdcxx-debug--enable-libstdcxx-time=yes--with-default-libstdcxx-abi=
new--enable-gnu-unique-object--disable-vtable-verify--enable-libmpx--enable-plugin-
--enable-default-pie--with-system-zlib--with-target-system-zlib--enable-objc-gc=
auto--enable-multiarch--disable-werror--with-arch=32=i686--with-abi=m64-
--with-multilib-list=m32,m64,mx32--enable-multilib--with-tune=generic--enable-
offload-targets=nvptx-none--without-cuda-driver--enable-checking=release--build=
x86_64-linux-gnu--host=x86_64-linux-gnu--target=x86_64-linux-gnuThreadmodel:
posixgccversion7.4.0(Ubuntu7.4.0-1ubuntu1 18.04.1)

```

10.2 SAT implementation

In this section I introduce the code of the implementation of the SAT algorithm, used to validate and qualify the FMB algorithm.

10.2.1 Header

```

#ifndef __SAT_H_
#define __SAT_H_

#include <stdbool.h>
#include <string.h>
#include "frame.h"

// ----- Functions declaration -----

// Test for intersection between 2D Frame 'that' and 2D Frame 'tho'
// Return true if the two Frames are intersecting, else false
bool SATTestIntersection2D(
    const Frame2D* const that,
    const Frame2D* const tho);

```

```

// Test for intersection between moving 2D Frame 'that' and 2D
// Frame 'tho'
// Return true if the two Frames are intersecting, else false
bool SATTestIntersection2DTime(
    const Frame2DTime* const that,
    const Frame2DTime* const tho);

// Test for intersection between 3D Frame 'that' and 3D Frame 'tho'
// Return true if the two Frames are intersecting, else false
bool SATTestIntersection3D(
    const Frame3D* const that,
    const Frame3D* const tho);

// Test for intersection between moving 3D Frame 'that' and 3D
// Frame 'tho'
// Return true if the two Frames are intersecting, else false
bool SATTestIntersection3DTime(
    const Frame3DTime* const that,
    const Frame3DTime* const tho);

#endif

```

10.2.2 Body

```

#include "sat.h"

// ----- Macros -----

#define EPSILON 0.0000001

// ----- Functions declaration -----

// Check the intersection constraint along one axis
bool CheckAxis3D(
    const Frame3D* const that,
    const Frame3D* const tho,
    const double* const axis);

// Check the intersection constraint along one axis
bool CheckAxis3DTime(
    const Frame3DTime* const that,
    const Frame3DTime* const tho,
    const double* const axis,
    const double* const relSpeed);

// ----- Functions implementation -----

// Test for intersection between 2D Frame 'that' and 2D Frame 'tho'
// Return true if the two Frames are intersecting, else false
bool SATTestIntersection2D(
    const Frame2D* const that,
    const Frame2D* const tho) {

    // Declare a variable to loop on Frames and commonalize code
    const Frame2D* frameEdge = that;

    // Loop to commonalize code when checking SAT based on that's edges
    // and then tho's edges
    for (int iFrame = 2;
        iFrame--;) {

```

```

// Shortcuts
FrameType frameEdgeType = frameEdge->type;
const double* frameEdgeCompA = frameEdge->comp[0];
const double* frameEdgeCompB = frameEdge->comp[1];

// Declare a variable to memorize the number of edges, by default 2
int nbEdges = 2;

// Declare a variable to memorize the third edge in case of
// tetrahedron
double thirdEdge[2];

// If the frame is a tetrahedron
if (frameEdgeType == FrameTetrahedron) {

    // Initialise the third edge
    thirdEdge[0] = frameEdgeCompB[0] - frameEdgeCompA[0];
    thirdEdge[1] = frameEdgeCompB[1] - frameEdgeCompA[1];

    // Correct the number of edges
    nbEdges = 3;

}

// Loop on the frame's edges
for (int iEdge = nbEdges;
     iEdge--;) {

    // Get the current edge
    const double* edge =
        (iEdge == 2 ? thirdEdge : frameEdge->comp[iEdge]);

    // Declare variables to memorize the boundaries of projection
    // of the two frames on the current edge
    double bdgBoxA[2];
    double bdgBoxB[2];

    // Declare two variables to loop on Frames and commonalize code
    const Frame2D* frame = that;
    double* bdgBox = bdgBoxA;

    // Loop on Frames
    for (int iFrame = 2;
         iFrame--;) {

        // Shortcuts
        const double* frameOrig = frame->orig;
        const double* frameCompA = frame->comp[0];
        const double* frameCompB = frame->comp[1];
        FrameType frameType = frame->type;

        // Get the number of vertices of frame
        int nbVertices = (frameType == FrameTetrahedron ? 3 : 4);

        // Declare a variable to memorize if the current vertex is
        // the first in the loop, used to initialize the boundaries
        bool firstVertex = true;

        // Loop on vertices of the frame
        for (int iVertex = nbVertices;
             iVertex--;) {

```

```

// Get the vertex
double vertex[2];
vertex[0] = frameOrig[0];
vertex[1] = frameOrig[1];
switch (iVertex) {
    case 3:
        vertex[0] += frameCompA[0] + frameCompB[0];
        vertex[1] += frameCompA[1] + frameCompB[1];
        break;
    case 2:
        vertex[0] += frameCompA[0];
        vertex[1] += frameCompA[1];
        break;
    case 1:
        vertex[0] += frameCompB[0];
        vertex[1] += frameCompB[1];
        break;
    default:
        break;
}

// Get the projection of the vertex on the normal of the edge
// Orientation of the normal doesn't matter, so we
// use arbitrarily the normal (edge[1], -edge[0])
double proj = vertex[0] * edge[1] - vertex[1] * edge[0];

// If it's the first vertex
if (firstVertex == true) {

    // Initialize the boundaries of the projection of the
    // Frame on the edge
    bdgBox[0] = proj;
    bdgBox[1] = proj;

    // Update the flag to memorize we did the first vertex
    firstVertex = false;

// Else, it's not the first vertex
} else {

    // Update the boundaries of the projection of the Frame on
    // the edge
    if (bdgBox[0] > proj)
        bdgBox[0] = proj;

    if (bdgBox[1] < proj)
        bdgBox[1] = proj;

}

}

// Switch the frame to check the vertices of the second Frame
frame = tho;
bdgBox = bdgBoxB;

}

// If the projections of the two frames on the edge are
// not intersecting
if (bdgBoxB[1] < bdgBoxA[0] ||
    bdgBoxA[1] < bdgBoxB[0]) {

```

```

        // There exists an axis which separates the Frames,
        // thus they are not in intersection
        return false;

    }

}

// Switch the frames to test against the second Frame's edges
frameEdge = tho;

}

// If we reaches here, it means the two Frames are intersecting
return true;

}

// Test for intersection between moving 2D Frame 'that' and 2D
// Frame 'tho'
// Return true if the two Frames are intersecting, else false
bool SATTestIntersection2DTime(
    const Frame2DTime* const that,
    const Frame2DTime* const tho) {

    // Declare a variable to loop on Frames and commonalize code
    const Frame2DTime* frameEdge = that;

    // Declare a variable to memorize the speed of tho relative to that
    double relSpeed[2];
    relSpeed[0] = tho->speed[0] - that->speed[0];
    relSpeed[1] = tho->speed[1] - that->speed[1];

    // Loop to commonalize code when checking SAT based on that's edges
    // and then tho's edges
    for (int iFrame = 2;
        iFrame--;) {

        // Shortcuts
        FrameType frameEdgeType = frameEdge->type;
        const double* frameEdgeCompA = frameEdge->comp[0];
        const double* frameEdgeCompB = frameEdge->comp[1];

        // Declare a variable to memorize the number of edges, by default 2
        int nbEdges = 2;

        // Declare a variable to memorize the third edge in case of
        // tetrahedron
        double thirdEdge[2];

        // If the frame is a tetrahedron
        if (frameEdgeType == FrameTetrahedron) {

            // Initialise the third edge
            thirdEdge[0] = frameEdgeCompB[0] - frameEdgeCompA[0];
            thirdEdge[1] = frameEdgeCompB[1] - frameEdgeCompA[1];

            // Correct the number of edges
            nbEdges = 3;

        }

    }
}

```

```

// If the current frame is the second frame
if (iFrame == 1) {

    // Add one more edge to take into account the movement
    // of the relative to that
    ++nbEdges;

}

// Loop on the frame's edges
for (int iEdge = nbEdges;
     iEdge--;) {

    // Get the current edge
    const double* edge =
        (iEdge == 3 ? relSpeed :
         (iEdge == 2 ?
          (frameEdgeType == FrameTetrahedron ? thirdEdge : relSpeed) :
          frameEdge->comp[iEdge]));

    // Declare variables to memorize the boundaries of projection
    // of the two frames on the current edge
    double bdgBoxA[2];
    double bdgBoxB[2];

    // Declare two variables to loop on Frames and commonalize code
    const Frame2DTime* frame = that;
    double* bdgBox = bdgBoxA;

    // Loop on Frames
    for (int iFrame = 2;
         iFrame--;) {

        // Shortcuts
        const double* frameOrig = frame->orig;
        const double* frameCompA = frame->comp[0];
        const double* frameCompB = frame->comp[1];
        FrameType frameType = frame->type;

        // Get the number of vertices of frame
        int nbVertices = (frameType == FrameTetrahedron ? 3 : 4);

        // Declare a variable to memorize if the current vertex is
        // the first in the loop, used to initialize the boundaries
        bool firstVertex = true;

        // Loop on vertices of the frame
        for (int iVertex = nbVertices;
             iVertex--;) {

            // Get the vertex
            double vertex[2];
            vertex[0] = frameOrig[0];
            vertex[1] = frameOrig[1];
            switch (iVertex) {
                case 3:
                    vertex[0] += frameCompA[0] + frameCompB[0];
                    vertex[1] += frameCompA[1] + frameCompB[1];
                    break;
                case 2:
                    vertex[0] += frameCompA[0];

```



```

        vertex[1] += frameCompA[1];
        break;
    case 1:
        vertex[0] += frameCompB[0];
        vertex[1] += frameCompB[1];
        break;
    default:
        break;
}

// Get the projection of the vertex on the normal of the edge
// Orientation of the normal doesn't matter, so we
// use arbitrarily the normal (edge[1], -edge[0])
double proj = vertex[0] * edge[1] - vertex[1] * edge[0];

// If it's the first vertex
if (firstVertex == true) {

    // Initialize the boundaries of the projection of the
    // Frame on the edge
    bdgBox[0] = proj;
    bdgBox[1] = proj;

    // Update the flag to memorize we did the first vertex
    firstVertex = false;

// Else, it's not the first vertex
} else {

    // Update the boundaries of the projection of the Frame on
    // the edge
    if (bdgBox[0] > proj)
        bdgBox[0] = proj;

    if (bdgBox[1] < proj)
        bdgBox[1] = proj;

}

// If we are checking the second frame's vertices
if (frame == tho) {

    // Check also the vertices moved by the relative speed
    vertex[0] += relSpeed[0];
    vertex[1] += relSpeed[1];

    proj = vertex[0] * edge[1] - vertex[1] * edge[0];

    if (bdgBox[0] > proj)
        bdgBox[0] = proj;

    if (bdgBox[1] < proj)
        bdgBox[1] = proj;

}

}

// Switch the frame to check the vertices of the second Frame
frame = tho;
bdgBox = bdgBoxB;

```

```

    }

    // If the projections of the two frames on the edge are
    // not intersecting
    if (bdgBoxB[1] < bdgBoxA[0] ||
        bdgBoxA[1] < bdgBoxB[0]) {

        // There exists an axis which separates the Frames,
        // thus they are not in intersection
        return false;

    }

}

// Switch the frames to test against the second Frame's edges
frameEdge = tho;

}

// If we reaches here, it means the two Frames are intersecting
return true;

}

// Test for intersection between 3D Frame 'that' and 3D Frame 'tho'
// Return true if the two Frames are intersecting, else false
bool SATTestIntersection3D(
    const Frame3D* const that,
    const Frame3D* const tho) {

    // Declare two variables to memorize the opposite edges in case
    // of tetrahedron
    double oppEdgesThat[3][3];
    double oppEdgesTho[3][3];

    // Declare two variables to memorize the number of edges, by default 3
    int nbEdgesThat = 3;
    int nbEdgesTho = 3;

    // If the first Frame is a tetrahedron
    if (that->type == FrameTetrahedron) {

        // Shortcuts
        const double* frameCompA = that->comp[0];
        const double* frameCompB = that->comp[1];
        const double* frameCompC = that->comp[2];

        // Initialise the opposite edges
        oppEdgesThat[0][0] = frameCompB[0] - frameCompA[0];
        oppEdgesThat[0][1] = frameCompB[1] - frameCompA[1];
        oppEdgesThat[0][2] = frameCompB[2] - frameCompA[2];

        oppEdgesThat[1][0] = frameCompB[0] - frameCompC[0];
        oppEdgesThat[1][1] = frameCompB[1] - frameCompC[1];
        oppEdgesThat[1][2] = frameCompB[2] - frameCompC[2];

        oppEdgesThat[2][0] = frameCompC[0] - frameCompA[0];
        oppEdgesThat[2][1] = frameCompC[1] - frameCompA[1];
        oppEdgesThat[2][2] = frameCompC[2] - frameCompA[2];

        // Correct the number of edges

```

```

    nbEdgesThat = 6;
}

// If the second Frame is a tetrahedron
if (tho->type == FrameTetrahedron) {

    // Shortcuts
    const double* frameCompA = tho->comp[0];
    const double* frameCompB = tho->comp[1];
    const double* frameCompC = tho->comp[2];

    // Initialise the opposite edges
    oppEdgesTho[0][0] = frameCompB[0] - frameCompA[0];
    oppEdgesTho[0][1] = frameCompB[1] - frameCompA[1];
    oppEdgesTho[0][2] = frameCompB[2] - frameCompA[2];

    oppEdgesTho[1][0] = frameCompB[0] - frameCompC[0];
    oppEdgesTho[1][1] = frameCompB[1] - frameCompC[1];
    oppEdgesTho[1][2] = frameCompB[2] - frameCompC[2];

    oppEdgesTho[2][0] = frameCompC[0] - frameCompA[0];
    oppEdgesTho[2][1] = frameCompC[1] - frameCompA[1];
    oppEdgesTho[2][2] = frameCompC[2] - frameCompA[2];

    // Correct the number of edges
    nbEdgesTho = 6;
}

// Declare variables to loop on Frames and commonalize code
const Frame3D* frame = that;
const double (*oppEdgesA)[3] = oppEdgesThat;

// Loop to commonalize code when checking SAT based on that's edges
// and then tho's edges
for (int iFrame = 2;
     iFrame--;) {

    // Shortcuts
    FrameType frameType = frame->type;
    const double* frameCompA = frame->comp[0];
    const double* frameCompB = frame->comp[1];
    const double* frameCompC = frame->comp[2];

    // Declare a variable to memorize the number of faces, by default 3
    int nbFaces = 3;

    // Declare a variable to memorize the normal to faces
    // Arrangement is normFaces[iFace][iAxis]
    double normFaces[4][3];

    // Initialise the normal to faces
    normFaces[0][0] =
        frameCompA[1] * frameCompB[2] -
        frameCompA[2] * frameCompB[1];
    normFaces[0][1] =
        frameCompA[2] * frameCompB[0] -
        frameCompA[0] * frameCompB[2];
    normFaces[0][2] =
        frameCompA[0] * frameCompB[1] -
        frameCompA[1] * frameCompB[0];

```

```

normFaces[1][0] =
    frameCompA[1] * frameCompC[2] -
    frameCompA[2] * frameCompC[1];
normFaces[1][1] =
    frameCompA[2] * frameCompC[0] -
    frameCompA[0] * frameCompC[2];
normFaces[1][2] =
    frameCompA[0] * frameCompC[1] -
    frameCompA[1] * frameCompC[0];

normFaces[2][0] =
    frameCompC[1] * frameCompB[2] -
    frameCompC[2] * frameCompB[1];
normFaces[2][1] =
    frameCompC[2] * frameCompB[0] -
    frameCompC[0] * frameCompB[2];
normFaces[2][2] =
    frameCompC[0] * frameCompB[1] -
    frameCompC[1] * frameCompB[0];

// If the frame is a tetrahedron
if (frameType == FrameTetrahedron) {

    // Shortcuts
    const double* oppEdgeA = oppEdgesA[0];
    const double* oppEdgeB = oppEdgesA[1];

    // Initialise the normal to the opposite face
    normFaces[3][0] =
        oppEdgeA[1] * oppEdgeB[2] -
        oppEdgeA[2] * oppEdgeB[1];
    normFaces[3][1] =
        oppEdgeA[2] * oppEdgeB[0] -
        oppEdgeA[0] * oppEdgeB[2];
    normFaces[3][2] =
        oppEdgeA[0] * oppEdgeB[1] -
        oppEdgeA[1] * oppEdgeB[0];

    // Correct the number of faces
    nbFaces = 4;
}

// Loop on the frame's faces
for (int iFace = nbFaces;
     iFace--;) {

    // Check against the current face's normal
    bool isIntersection =
        CheckAxis3D(
            that,
            tho,
            normFaces[iFace]);

    // If the axis is separating the Frames
    if (isIntersection == false) {

        // The Frames are not in intersection,
        // terminate the test
        return false;
    }
}

```

```

    }

}

// Switch the frame to test against the second Frame
frame = tho;
oppEdgesA = oppEdgesTho;

}

// Loop on the pair of edges between the two frames
for (int iEdgeThat = nbEdgesThat;
     iEdgeThat--;) {

    // Get the first edge
    const double* edgeThat =
        (iEdgeThat < 3 ?
         that->comp[iEdgeThat] :
         oppEdgesThat[iEdgeThat - 3]);

    for (int iEdgeTho = nbEdgesTho;
         iEdgeTho--;) {

        // Get the second edge
        const double* edgeTho =
            (iEdgeTho < 3 ?
             tho->comp[iEdgeTho] :
             oppEdgesTho[iEdgeTho - 3]);

        // Get the cross product of the two edges
        double axis[3];
        axis[0] = edgeThat[1] * edgeTho[2] - edgeThat[2] * edgeTho[1];
        axis[1] = edgeThat[2] * edgeTho[0] - edgeThat[0] * edgeTho[2];
        axis[2] = edgeThat[0] * edgeTho[1] - edgeThat[1] * edgeTho[0];

        // Check against the cross product of the two edges
        bool isIntersection =
            CheckAxis3D(
                that,
                tho,
                axis);

        // If the axis is separating the Frames
        if (isIntersection == false) {

            // The Frames are not in intersection,
            // terminate the test
            return false;

        }

    }

}

}

// If we reaches here, it means the two Frames are intersecting
return true;

}

// Test for intersection between moving 3D Frame 'that' and 3D
// Frame 'tho'

```

```

// Return true if the two Frames are intersecting, else false
bool SATTestIntersection3DTime(
    const Frame3DTime* const that,
    const Frame3DTime* const tho) {

    // Declare two variables to memorize the opposite edges in case
    // of tetrahedron
    double oppEdgesThat[3][3];
    double oppEdgesTho[3][3];

    // Declare a variable to memorize the speed of tho relative to that
    double relSpeed[3];
    relSpeed[0] = tho->speed[0] - that->speed[0];
    relSpeed[1] = tho->speed[1] - that->speed[1];
    relSpeed[2] = tho->speed[2] - that->speed[2];

    // Declare two variables to memorize the number of edges, by default 3
    int nbEdgesThat = 3;
    int nbEdgesTho = 3;

    // If the first Frame is a tetrahedron
    if (that->type == FrameTetrahedron) {

        // Shortcuts
        const double* frameCompA = that->comp[0];
        const double* frameCompB = that->comp[1];
        const double* frameCompC = that->comp[2];

        // Initialise the opposite edges
        oppEdgesThat[0][0] = frameCompB[0] - frameCompA[0];
        oppEdgesThat[0][1] = frameCompB[1] - frameCompA[1];
        oppEdgesThat[0][2] = frameCompB[2] - frameCompA[2];

        oppEdgesThat[1][0] = frameCompB[0] - frameCompC[0];
        oppEdgesThat[1][1] = frameCompB[1] - frameCompC[1];
        oppEdgesThat[1][2] = frameCompB[2] - frameCompC[2];

        oppEdgesThat[2][0] = frameCompC[0] - frameCompA[0];
        oppEdgesThat[2][1] = frameCompC[1] - frameCompA[1];
        oppEdgesThat[2][2] = frameCompC[2] - frameCompA[2];

        // Correct the number of edges
        nbEdgesThat = 6;
    }

    // If the second Frame is a tetrahedron
    if (tho->type == FrameTetrahedron) {

        // Shortcuts
        const double* frameCompA = tho->comp[0];
        const double* frameCompB = tho->comp[1];
        const double* frameCompC = tho->comp[2];

        // Initialise the opposite edges
        oppEdgesTho[0][0] = frameCompB[0] - frameCompA[0];
        oppEdgesTho[0][1] = frameCompB[1] - frameCompA[1];
        oppEdgesTho[0][2] = frameCompB[2] - frameCompA[2];

        oppEdgesTho[1][0] = frameCompB[0] - frameCompC[0];
        oppEdgesTho[1][1] = frameCompB[1] - frameCompC[1];
        oppEdgesTho[1][2] = frameCompB[2] - frameCompC[2];
    }
}

```

```

    oppEdgesTho[2][0] = frameCompC[0] - frameCompA[0];
    oppEdgesTho[2][1] = frameCompC[1] - frameCompA[1];
    oppEdgesTho[2][2] = frameCompC[2] - frameCompA[2];

    // Correct the number of edges
    nbEdgesTho = 6;
}

// Declare variables to loop on Frames and commonalize code
const Frame3DTime* frame = that;
const double (*oppEdgesA)[3] = oppEdgesThat;

// Loop to commonalize code when checking SAT based on that's edges
// and then tho's edges
for (int iFrame = 2;
     iFrame--;) {

    // Shortcuts
    FrameType frameType = frame->type;
    const double* frameCompA = frame->comp[0];
    const double* frameCompB = frame->comp[1];
    const double* frameCompC = frame->comp[2];

    // Declare a variable to memorize the number of faces, by default 3
    int nbFaces = 3;

    // Declare a variable to memorize the normal to faces
    // Arrangement is normFaces[iFace][iAxis]
    double normFaces[10][3];

    // Initialise the normal to faces
    normFaces[0][0] =
        frameCompA[1] * frameCompB[2] -
        frameCompA[2] * frameCompB[1];
    normFaces[0][1] =
        frameCompA[2] * frameCompB[0] -
        frameCompA[0] * frameCompB[2];
    normFaces[0][2] =
        frameCompA[0] * frameCompB[1] -
        frameCompA[1] * frameCompB[0];

    normFaces[1][0] =
        frameCompA[1] * frameCompC[2] -
        frameCompA[2] * frameCompC[1];
    normFaces[1][1] =
        frameCompA[2] * frameCompC[0] -
        frameCompA[0] * frameCompC[2];
    normFaces[1][2] =
        frameCompA[0] * frameCompC[1] -
        frameCompA[1] * frameCompC[0];

    normFaces[2][0] =
        frameCompC[1] * frameCompB[2] -
        frameCompC[2] * frameCompB[1];
    normFaces[2][1] =
        frameCompC[2] * frameCompB[0] -
        frameCompC[0] * frameCompB[2];
    normFaces[2][2] =
        frameCompC[0] * frameCompB[1] -
        frameCompC[1] * frameCompB[0];
}

```

```

// If the frame is a tetrahedron
if (frameType == FrameTetrahedron) {

    // Shortcuts
    const double* oppEdgeA = oppEdgesA[0];
    const double* oppEdgeB = oppEdgesA[1];

    // Initialise the normal to the opposite face
    normFaces[3][0] =
        oppEdgeA[1] * oppEdgeB[2] -
        oppEdgeA[2] * oppEdgeB[1];
    normFaces[3][1] =
        oppEdgeA[2] * oppEdgeB[0] -
        oppEdgeA[0] * oppEdgeB[2];
    normFaces[3][2] =
        oppEdgeA[0] * oppEdgeB[1] -
        oppEdgeA[1] * oppEdgeB[0];

    // Correct the number of faces
    nbFaces = 4;
}

// If we are checking the frame 'tho'
if (frame == tho) {

    // Add the normal to the virtual faces created by the speed
    // of tho relative to that

    normFaces[nbFaces][0] =
        relSpeed[1] * frameCompA[2] -
        relSpeed[2] * frameCompA[1];
    normFaces[nbFaces][1] =
        relSpeed[2] * frameCompA[0] -
        relSpeed[0] * frameCompA[2];
    normFaces[nbFaces][2] =
        relSpeed[0] * frameCompA[1] -
        relSpeed[1] * frameCompA[0];
    if (fabs(normFaces[nbFaces][0]) > EPSILON ||
        fabs(normFaces[nbFaces][1]) > EPSILON ||
        fabs(normFaces[nbFaces][2]) > EPSILON)
        ++nbFaces;

    normFaces[nbFaces][0] =
        relSpeed[1] * frameCompB[2] -
        relSpeed[2] * frameCompB[1];
    normFaces[nbFaces][1] =
        relSpeed[2] * frameCompB[0] -
        relSpeed[0] * frameCompB[2];
    normFaces[nbFaces][2] =
        relSpeed[0] * frameCompB[1] -
        relSpeed[1] * frameCompB[0];
    if (fabs(normFaces[nbFaces][0]) > EPSILON ||
        fabs(normFaces[nbFaces][1]) > EPSILON ||
        fabs(normFaces[nbFaces][2]) > EPSILON)
        ++nbFaces;

    normFaces[nbFaces][0] =
        relSpeed[1] * frameCompC[2] -
        relSpeed[2] * frameCompC[1];
    normFaces[nbFaces][1] =

```



```

        relSpeed[2] * frameCompC[0] -
        relSpeed[0] * frameCompC[2];
    normFaces[nbFaces][2] =
        relSpeed[0] * frameCompC[1] -
        relSpeed[1] * frameCompC[0];
    if (fabs(normFaces[nbFaces][0]) > EPSILON ||
        fabs(normFaces[nbFaces][1]) > EPSILON ||
        fabs(normFaces[nbFaces][2]) > EPSILON)
        ++nbFaces;

    if (frameType == FrameTetrahedron) {

        const double* oppEdgeA = oppEdgesA[0];
        const double* oppEdgeB = oppEdgesA[1];
        const double* oppEdgeC = oppEdgesA[2];

        normFaces[nbFaces][0] =
            relSpeed[1] * oppEdgeA[2] -
            relSpeed[2] * oppEdgeA[1];
        normFaces[nbFaces][1] =
            relSpeed[2] * oppEdgeA[0] -
            relSpeed[0] * oppEdgeA[2];
        normFaces[nbFaces][2] =
            relSpeed[0] * oppEdgeA[1] -
            relSpeed[1] * oppEdgeA[0];
        if (fabs(normFaces[nbFaces][0]) > EPSILON ||
            fabs(normFaces[nbFaces][1]) > EPSILON ||
            fabs(normFaces[nbFaces][2]) > EPSILON)
            ++nbFaces;

        normFaces[nbFaces][0] =
            relSpeed[1] * oppEdgeB[2] -
            relSpeed[2] * oppEdgeB[1];
        normFaces[nbFaces][1] =
            relSpeed[2] * oppEdgeB[0] -
            relSpeed[0] * oppEdgeB[2];
        normFaces[nbFaces][2] =
            relSpeed[0] * oppEdgeB[1] -
            relSpeed[1] * oppEdgeB[0];
        if (fabs(normFaces[nbFaces][0]) > EPSILON ||
            fabs(normFaces[nbFaces][1]) > EPSILON ||
            fabs(normFaces[nbFaces][2]) > EPSILON)
            ++nbFaces;

        normFaces[nbFaces][0] =
            relSpeed[1] * oppEdgeC[2] -
            relSpeed[2] * oppEdgeC[1];
        normFaces[nbFaces][1] =
            relSpeed[2] * oppEdgeC[0] -
            relSpeed[0] * oppEdgeC[2];
        normFaces[nbFaces][2] =
            relSpeed[0] * oppEdgeC[1] -
            relSpeed[1] * oppEdgeC[0];
        if (fabs(normFaces[nbFaces][0]) > EPSILON ||
            fabs(normFaces[nbFaces][1]) > EPSILON ||
            fabs(normFaces[nbFaces][2]) > EPSILON)
            ++nbFaces;

    }
}

// Loop on the frame's faces

```

```

for (int iFace = nbFaces;
    iFace--;) {

    // Check against the current face's normal
    bool isIntersection =
        CheckAxis3DTime(
            that,
            tho,
            normFaces[iFace],
            relSpeed);

    // If the axis is separating the Frames
    if (isIntersection == false) {

        // The Frames are not in intersection,
        // terminate the test
        return false;

    }

}

// Switch the frame to test against the second Frame
frame = tho;
oppEdgesA = oppEdgesTho;

}

// Loop on the pair of edges between the two frames
for (int iEdgeThat = nbEdgesThat;
    iEdgeThat--;) {

    // Get the first edge
    const double* edgeThat =
        (iEdgeThat < 3 ?
         that->comp[iEdgeThat] :
         oppEdgesThat[iEdgeThat - 3]);

    for (int iEdgeTho = nbEdgesTho + 1;
        iEdgeTho--;) {

        // Get the second edge
        const double* edgeTho =
            (iEdgeTho == nbEdgesTho ?
             relSpeed :
             (iEdgeTho < 3 ?
              tho->comp[iEdgeTho] :
              oppEdgesTho[iEdgeTho - 3]));

        // Get the cross product of the two edges
        double axis[3];
        axis[0] = edgeThat[1] * edgeTho[2] - edgeThat[2] * edgeTho[1];
        axis[1] = edgeThat[2] * edgeTho[0] - edgeThat[0] * edgeTho[2];
        axis[2] = edgeThat[0] * edgeTho[1] - edgeThat[1] * edgeTho[0];

        // Check against the cross product of the two edges
        bool isIntersection =
            CheckAxis3DTime(
                that,
                tho,
                axis,
                relSpeed);
    }
}

```

```

        // If the axis is separating the Frames
        if (isIntersection == false) {

            // The Frames are not in intersection,
            // terminate the test
            return false;

        }

    }

}

// If we reaches here, it means the two Frames are intersecting
return true;

}

// Check the intersection constraint for Frames 'that' and 'tho'
// relatively to 'axis'
bool CheckAxis3D(
    const Frame3D* const that,
    const Frame3D* const tho,
    const double* const axis) {

    // Declare variables to memorize the boundaries of projection
    // of the two frames on the current edge
    double bdgBoxA[2];
    double bdgBoxB[2];

    // Declare two variables to loop on Frames and commonalize code
    const Frame3D* frame = that;
    double* bdgBox = bdgBoxA;

    // Loop on Frames
    for (int iFrame = 2;
        iFrame--;) {

        // Shortcuts
        const double* frameOrig = frame->orig;
        const double* frameCompA = frame->comp[0];
        const double* frameCompB = frame->comp[1];
        const double* frameCompC = frame->comp[2];
        FrameType frameType = frame->type;

        // Get the number of vertices of frame
        int nbVertices = (frameType == FrameTetrahedron ? 4 : 8);

        // Declare a variable to memorize if the current vertex is
        // the first in the loop, used to initialize the boundaries
        bool firstVertex = true;

        // Loop on vertices of the frame
        for (int iVertex = nbVertices;
            iVertex--;) {

            // Get the vertex
            double vertex[3];
            vertex[0] = frameOrig[0];
            vertex[1] = frameOrig[1];
            vertex[2] = frameOrig[2];

```

```

switch (iVertex) {
    case 7:
        vertex[0] +=
            frameCompA[0] + frameCompB[0] + frameCompC[0];
        vertex[1] +=
            frameCompA[1] + frameCompB[1] + frameCompC[1];
        vertex[2] +=
            frameCompA[2] + frameCompB[2] + frameCompC[2];
        break;
    case 6:
        vertex[0] += frameCompB[0] + frameCompC[0];
        vertex[1] += frameCompB[1] + frameCompC[1];
        vertex[2] += frameCompB[2] + frameCompC[2];
        break;
    case 5:
        vertex[0] += frameCompA[0] + frameCompC[0];
        vertex[1] += frameCompA[1] + frameCompC[1];
        vertex[2] += frameCompA[2] + frameCompC[2];
        break;
    case 4:
        vertex[0] += frameCompA[0] + frameCompB[0];
        vertex[1] += frameCompA[1] + frameCompB[1];
        vertex[2] += frameCompA[2] + frameCompB[2];
        break;
    case 3:
        vertex[0] += frameCompC[0];
        vertex[1] += frameCompC[1];
        vertex[2] += frameCompC[2];
        break;
    case 2:
        vertex[0] += frameCompB[0];
        vertex[1] += frameCompB[1];
        vertex[2] += frameCompB[2];
        break;
    case 1:
        vertex[0] += frameCompA[0];
        vertex[1] += frameCompA[1];
        vertex[2] += frameCompA[2];
        break;
    default:
        break;
}

// Get the projection of the vertex on the axis
double proj =
    vertex[0] * axis[0] +
    vertex[1] * axis[1] +
    vertex[2] * axis[2];

// If it's the first vertex
if (firstVertex == true) {

    // Initialize the boundaries of the projection of the
    // Frame on the edge
    bdgBox[0] = proj;
    bdgBox[1] = proj;

    // Update the flag to memorize we did the first vertex
    firstVertex = false;

} else {

```

```

        // Update the boundaries of the projection of the Frame on
        // the edge
        if (bdgBox[0] > proj)
            bdgBox[0] = proj;

        if (bdgBox[1] < proj)
            bdgBox[1] = proj;
    }

}

// Switch the frame to check the vertices of the second Frame
frame = tho;
bdgBox = bdgBoxB;

}

// If the projections of the two frames on the edge are
// not intersecting
if (bdgBoxB[1] < bdgBoxA[0] ||
    bdgBoxA[1] < bdgBoxB[0]) {

    // There exists an axis which separates the Frames,
    // thus they are not in intersection
    return false;

}

// If we reaches here the two Frames are in intersection
return true;

}

// Check the intersection constraint for Frames 'that' and 'tho'
// relatively to 'axis'
bool CheckAxis3DTime(
    const Frame3DTime* const that,
    const Frame3DTime* const tho,
    const double* const axis,
    const double* const relSpeed) {

    // Declare variables to memorize the boundaries of projection
    // of the two frames on the current edge
    double bdgBoxA[2];
    double bdgBoxB[2];

    // Declare two variables to loop on Frames and commonalize code
    const Frame3DTime* frame = that;
    double* bdgBox = bdgBoxA;

    // Loop on Frames
    for (int iFrame = 2;
        iFrame--;) {

        // Shortcuts
        const double* frameOrig = frame->orig;
        const double* frameCompA = frame->comp[0];
        const double* frameCompB = frame->comp[1];
        const double* frameCompC = frame->comp[2];
        FrameType frameType = frame->type;
    }
}

```

```

// Get the number of vertices of frame
int nbVertices = (frameType == FrameTetrahedron ? 4 : 8);

// Declare a variable to memorize if the current vertex is
// the first in the loop, used to initialize the boundaries
bool firstVertex = true;

// Loop on vertices of the frame
for (int iVertex = nbVertices;
     iVertex--;) {

    // Get the vertex
    double vertex[3];
    vertex[0] = frameOrig[0];
    vertex[1] = frameOrig[1];
    vertex[2] = frameOrig[2];
    switch (iVertex) {
        case 7:
            vertex[0] +=
                frameCompA[0] + frameCompB[0] + frameCompC[0];
            vertex[1] +=
                frameCompA[1] + frameCompB[1] + frameCompC[1];
            vertex[2] +=
                frameCompA[2] + frameCompB[2] + frameCompC[2];
            break;
        case 6:
            vertex[0] += frameCompB[0] + frameCompC[0];
            vertex[1] += frameCompB[1] + frameCompC[1];
            vertex[2] += frameCompB[2] + frameCompC[2];
            break;
        case 5:
            vertex[0] += frameCompA[0] + frameCompC[0];
            vertex[1] += frameCompA[1] + frameCompC[1];
            vertex[2] += frameCompA[2] + frameCompC[2];
            break;
        case 4:
            vertex[0] += frameCompA[0] + frameCompB[0];
            vertex[1] += frameCompA[1] + frameCompB[1];
            vertex[2] += frameCompA[2] + frameCompB[2];
            break;
        case 3:
            vertex[0] += frameCompC[0];
            vertex[1] += frameCompC[1];
            vertex[2] += frameCompC[2];
            break;
        case 2:
            vertex[0] += frameCompB[0];
            vertex[1] += frameCompB[1];
            vertex[2] += frameCompB[2];
            break;
        case 1:
            vertex[0] += frameCompA[0];
            vertex[1] += frameCompA[1];
            vertex[2] += frameCompA[2];
            break;
        default:
            break;
    }

    // Get the projection of the vertex on the axis
    double proj =

```

```

    vertex[0] * axis[0] +
    vertex[1] * axis[1] +
    vertex[2] * axis[2];

// If it's the first vertex
if (firstVertex == true) {

    // Initialize the boundaries of the projection of the
    // Frame on the edge
    bdgBox[0] = proj;
    bdgBox[1] = proj;

    // Update the flag to memorize we did the first vertex
    firstVertex = false;

// Else, it's not the first vertex
} else {

    // Update the boundaries of the projection of the Frame on
    // the edge
    if (bdgBox[0] > proj)
        bdgBox[0] = proj;

    if (bdgBox[1] < proj)
        bdgBox[1] = proj;

}

// If we are checking the second frame's vertices
if (frame == tho) {

    // Check also the vertices moved by the relative speed
    vertex[0] += relSpeed[0];
    vertex[1] += relSpeed[1];
    vertex[2] += relSpeed[2];

    proj =
    vertex[0] * axis[0] +
    vertex[1] * axis[1] +
    vertex[2] * axis[2];

    if (bdgBox[0] > proj)
        bdgBox[0] = proj;

    if (bdgBox[1] < proj)
        bdgBox[1] = proj;

}

}

// Switch the frame to check the vertices of the second Frame
frame = tho;
bdgBox = bdgBoxB;

}

// If the projections of the two frames on the edge are
// not intersecting
if (bdgBoxB[1] < bdgBoxA[0] ||
    bdgBoxA[1] < bdgBoxB[0]) {

```

```

        // There exists an axis which separates the Frames,
        // thus they are not in intersection
        return false;

    }

    // If we reaches here the two Frames are in intersection
    return true;

}

```

10.3 Makefile

In this section I introduce the Makefile used to compile the code given in the previous sections.

```

COMPILER=gcc
OPTIMIZATION=-O3

all : compile run plot doc

install :
    sudo apt-get install gnuplot

compile : main unitTests validation qualification

main : main2D main2DTime main3D main3DTime

main2D:
    cd 2D; make main; cd -

main2DTime:
    cd 2DTime; make main; cd -

main3D:
    cd 3D; make main; cd -

main3DTime:
    cd 3DTime; make main; cd -

unitTests : unitTests2D unitTests2DTime unitTests3D unitTests3DTime

unitTests2D:
    cd 2D; make unitTests; cd -

unitTests2DTime:
    cd 2DTime; make unitTests; cd -

unitTests3D:
    cd 3D; make unitTests; cd -

unitTests3DTime:
    cd 3DTime; make unitTests; cd -

validation : validation2D validation2DTime validation3D validation3DTime

validation2D:
    cd 2D; make validation; cd -

```



```

validation2DTime:
    cd 2DTime; make validation; cd -

validation3D:
    cd 3D; make validation; cd -

validation3DTime:
    cd 3DTime; make validation; cd -

qualification : qualification2D qualification2DTime qualification3D
               qualification3DTime

qualification2D:
    cd 2D; make qualification; cd -

qualification2DTime:
    cd 2DTime; make qualification; cd -

qualification3D:
    cd 3D; make qualification; cd -

qualification3DTime:
    cd 3DTime; make qualification; cd -

clean : clean2D clean2DTime clean3D clean3DTime

clean2D:
    cd 2D; make clean; cd -

clean2DTime:
    cd 2DTime; make clean; cd -

clean3D:
    cd 3D; make clean; cd -

clean3DTime:
    cd 3DTime; make clean; cd -

valgrind : valgrind2D valgrind2DTime valgrind3D valgrind3DTime

valgrind2D:
    cd 2D; make valgrind; cd -

valgrind2DTime:
    cd 2DTime; make valgrind; cd -

valgrind3D:
    cd 3D; make valgrind; cd -

valgrind3DTime:
    cd 3DTime; make valgrind; cd -

run : run2D run2DTime run3D run3DTime

run2D:
    cd 2D; ./main > ../Results/main2D.txt; ./unitTests > ../Results/
    unitTests2D.txt; ./validation > ../Results/validation2D.txt;
    grep failed ../Results/validation2D.txt; ./qualification > ../
    Results/qualification2D.txt; grep failed ../Results/
    qualification2D.txt; cd -

run3D:

```

```

cd 3D; ./main > ../Results/main3D.txt; ./unitTests > ../Results/
unitTests3D.txt; ./validation > ../Results/validation3D.txt;
grep failed ../Results/validation3D.txt; ./qualification > ../
Results/qualification3D.txt; grep failed ../Results/
qualification3D.txt; cd -

run2DTime:
cd 2DTime; ./main > ../Results/main2DTime.txt; ./unitTests > ../
Results/unitTests2DTime.txt; ./validation > ../Results/
validation2DTime.txt; grep failed ../Results/validation2DTime.
txt; ./qualification > ../Results/qualification2DTime.txt; grep
failed ../Results/qualification2DTime.txt; cd -

run3DTime:
cd 3DTime; ./main > ../Results/main3DTime.txt; ./unitTests > ../
Results/unitTests3DTime.txt; ./validation > ../Results/
validation3DTime.txt; grep failed ../Results/validation3DTime.
txt; ./qualification > ../Results/qualification3DTime.txt; grep
failed ../Results/qualification3DTime.txt; cd -

plot: cleanPlot plot2D plot2DTime plot3D plot3DTime

cleanPlot:
rm Results/*.png

plot2D:
cd Results; gnuplot qualification2D.gnu < qualification2D.txt; cd -

plot2DTime:
cd Results; gnuplot qualification2DTime.gnu < qualification2DTime.
txt; cd -

plot3D:
cd Results; gnuplot qualification3D.gnu < qualification3D.txt; cd -

plot3DTime:
cd Results; gnuplot qualification3DTime.gnu < qualification3DTime.
txt; cd -

doc:
cd Doc; make latex; cd -

```

10.3.1 2D static

```

all : main unitTests validation qualification

COMPILER?=gcc
OPTIMIZATION?=-O3
BUILD_ARG=$(OPTIMIZATION) -I../SAT -I../Frame

main : main.o fmb2d.o frame.o Makefile
$(COMPILER) -o main main.o fmb2d.o frame.o

main.o : main.c fmb2d.h ../Frame/frame.h Makefile
$(COMPILER) -c main.c $(BUILD_ARG)

unitTests : unitTests.o fmb2d.o frame.o Makefile
$(COMPILER) -o unitTests unitTests.o fmb2d.o frame.o $(LINK_ARG)

```

```

unitTests.o : unitTests.c fmb2d.h ../Frame/frame.h Makefile
               $(COMPILER) -c unitTests.c $(BUILD_ARG)

validation : validation.o fmb2d.o sat.o frame.o Makefile
               $(COMPILER) -o validation validation.o fmb2d.o sat.o frame.o

validation.o : validation.c fmb2d.h ../SAT/sat.h ../Frame/frame.h Makefile
               $(COMPILER) -c validation.c $(BUILD_ARG)

qualification : qualification.o fmb2d.o sat.o frame.o Makefile
               $(COMPILER) -o qualification qualification.o fmb2d.o sat.o frame.o $
               (LINK_ARG)

qualification.o : qualification.c fmb2d.h ../SAT/sat.h ../Frame/frame.h
               Makefile
               $(COMPILER) -c qualification.c $(BUILD_ARG)

fmb2d.o : fmb2d.c fmb2d.h ../Frame/frame.h Makefile
               $(COMPILER) -c fmb2d.c $(BUILD_ARG)

sat.o : ../SAT/sat.c ../SAT/sat.h ../Frame/frame.h Makefile
               $(COMPILER) -c ../SAT/sat.c $(BUILD_ARG)

frame.o : ../Frame/frame.c ../Frame/frame.h Makefile
               $(COMPILER) -c ../Frame/frame.c $(BUILD_ARG)

clean :
        rm -f *.o main unitTests validation qualification

valgrind :
        valgrind -v --track-origins=yes --leak-check=full \
        --gen-suppressions=yes --show-leak-kinds=all ./main

```

10.3.2 3D static

```

all : main unitTests validation qualification

COMPILER?=gcc
OPTIMIZATION?=-O3
BUILD_ARG=$(OPTIMIZATION) -I../SAT -I../Frame

main : main.o fmb3d.o frame.o Makefile
               $(COMPILER) -o main main.o fmb3d.o frame.o

main.o : main.c fmb3d.h ../Frame/frame.h Makefile
               $(COMPILER) -c main.c $(BUILD_ARG)

unitTests : unitTests.o fmb3d.o frame.o Makefile
               $(COMPILER) -o unitTests unitTests.o fmb3d.o frame.o $(LINK_ARG)

unitTests.o : unitTests.c fmb3d.h ../Frame/frame.h Makefile
               $(COMPILER) -c unitTests.c $(BUILD_ARG)

validation : validation.o fmb3d.o sat.o frame.o Makefile
               $(COMPILER) -o validation validation.o fmb3d.o sat.o frame.o

validation.o : validation.c fmb3d.h ../SAT/sat.h ../Frame/frame.h Makefile
               $(COMPILER) -c validation.c $(BUILD_ARG)

qualification : qualification.o fmb3d.o sat.o frame.o Makefile
               $(COMPILER) -o qualification qualification.o fmb3d.o sat.o frame.o $

```

```

        (LINK_ARG)

qualification.o : qualification.c fmb3d.h ../SAT/sat.h ../Frame/frame.h
    Makefile
    $(COMPILER) -c qualification.c $(BUILD_ARG)

fmb3d.o : fmb3d.c fmb3d.h ../Frame/frame.h Makefile
    $(COMPILER) -c fmb3d.c $(BUILD_ARG)

sat.o : ../SAT/sat.c ../SAT/sat.h ../Frame/frame.h Makefile
    $(COMPILER) -c ../SAT/sat.c $(BUILD_ARG)

frame.o : ../Frame/frame.c ../Frame/frame.h Makefile
    $(COMPILER) -c ../Frame/frame.c $(BUILD_ARG)

clean :
    rm -f *.o main unitTests validation qualification

valgrind :
    valgrind -v --track-origins=yes --leak-check=full \
    --gen-suppressions=yes --show-leak-kinds=all ./main

```

10.3.3 2D dynamic

```

all : main unitTests validation qualification

COMPILER?=gcc
OPTIMIZATION?=-O3
BUILD_ARG=$(OPTIMIZATION) -I../SAT -I../Frame

main : main.o fmb2dt.o frame.o Makefile
    $(COMPILER) -o main main.o fmb2dt.o frame.o

main.o : main.c fmb2dt.h ../Frame/frame.h Makefile
    $(COMPILER) -c main.c $(BUILD_ARG)

unitTests : unitTests.o fmb2dt.o frame.o Makefile
    $(COMPILER) -o unitTests unitTests.o fmb2dt.o frame.o $(LINK_ARG)

unitTests.o : unitTests.c fmb2dt.h ../Frame/frame.h Makefile
    $(COMPILER) -c unitTests.c $(BUILD_ARG)

validation : validation.o fmb2dt.o sat.o frame.o Makefile
    $(COMPILER) -o validation validation.o fmb2dt.o sat.o frame.o

validation.o : validation.c fmb2dt.h ../SAT/sat.h ../Frame/frame.h Makefile
    $(COMPILER) -c validation.c $(BUILD_ARG)

qualification : qualification.o fmb2dt.o sat.o frame.o Makefile
    $(COMPILER) -o qualification qualification.o fmb2dt.o sat.o frame.o
    $(LINK_ARG)

qualification.o : qualification.c fmb2dt.h ../SAT/sat.h ../Frame/frame.h
    Makefile
    $(COMPILER) -c qualification.c $(BUILD_ARG)

fmb2dt.o : fmb2dt.c fmb2dt.h ../Frame/frame.h Makefile
    $(COMPILER) -c fmb2dt.c $(BUILD_ARG)

sat.o : ../SAT/sat.c ../SAT/sat.h ../Frame/frame.h Makefile
    $(COMPILER) -c ../SAT/sat.c $(BUILD_ARG)

```

```

frame.o : ../Frame/frame.c ../Frame/frame.h Makefile
          $(COMPILER) -c ../Frame/frame.c $(BUILD_ARG)

clean :
        rm -f *.o main unitTests validation qualification

valgrind :
        valgrind -v --track-origins=yes --leak-check=full \
        --gen-suppressions=yes --show-leak-kinds=all ./main

```

10.3.4 3D dynamic

```

all : main unitTests validation qualification

COMPILER?=gcc
OPTIMIZATION?=-O3
BUILD_ARG=$(OPTIMIZATION) -I../SAT -I../Frame

main : main.o fmb3dt.o frame.o Makefile
      $(COMPILER) -o main main.o fmb3dt.o frame.o

main.o : main.c fmb3dt.h ../Frame/frame.h Makefile
        $(COMPILER) -c main.c $(BUILD_ARG)

unitTests : unitTests.o fmb3dt.o frame.o Makefile
            $(COMPILER) -o unitTests unitTests.o fmb3dt.o frame.o $(LINK_ARG)

unitTests.o : unitTests.c fmb3dt.h ../Frame/frame.h Makefile
              $(COMPILER) -c unitTests.c $(BUILD_ARG)

validation : validation.o fmb3dt.o sat.o frame.o Makefile
              $(COMPILER) -o validation validation.o fmb3dt.o sat.o frame.o

validation.o : validation.c fmb3dt.h ../SAT/sat.h ../Frame/frame.h Makefile
                $(COMPILER) -c validation.c $(BUILD_ARG)

qualification : qualification.o fmb3dt.o sat.o frame.o Makefile
                $(COMPILER) -o qualification qualification.o fmb3dt.o sat.o frame.o
                $(LINK_ARG)

qualification.o : qualification.c fmb3dt.h ../SAT/sat.h ../Frame/frame.h
                  Makefile
                  $(COMPILER) -c qualification.c $(BUILD_ARG)

fmb3dt.o : fmb3dt.c fmb3dt.h ../Frame/frame.h Makefile
            $(COMPILER) -c fmb3dt.c $(BUILD_ARG)

sat.o : ../SAT/sat.c ../SAT/sat.h ../Frame/frame.h Makefile
        $(COMPILER) -c ../SAT/sat.c $(BUILD_ARG)

frame.o : ../Frame/frame.c ../Frame/frame.h Makefile
          $(COMPILER) -c ../Frame/frame.c $(BUILD_ARG)

clean :
        rm -f *.o main unitTests validation qualification

valgrind :
        valgrind -v --track-origins=yes --leak-check=full \
        --gen-suppressions=yes --show-leak-kinds=all ./main

```

References

- [1] J.J.-B. Fourier. Oeuvres II. Paris, 1890
- [2] T.S. Motzkin. *Beiträge zur Theorie der linearen Ungleichungen*. Thesis, 1936. Reprinted in: *Theodore S. Motzkin: selected papers* (D.Cantor et al., eds,), Birkhäuser, Boston, 1983.