

# GDataSet

P. Baillehache

April 22, 2019

## Contents

<b>1</b>	<b>Interface</b>	<b>2</b>
<b>2</b>	<b>Code</b>	<b>9</b>
2.1	gdataset.c . . . . .	9
2.2	gdataset-inline.c . . . . .	21
<b>3</b>	<b>Makefile</b>	<b>27</b>
<b>4</b>	<b>Dataset configuration file</b>	<b>28</b>
4.1	VecFloat . . . . .	28
4.2	Pair of GenBrush . . . . .	29
<b>5</b>	<b>Unit tests</b>	<b>30</b>
<b>6</b>	<b>Unit test output</b>	<b>35</b>

## Introduction

GDataSet is a C library to manipulate generic data sets.

It offers the following functionalities:

- loading a data set from its description file
- splitting the data set into user defined categories (e.g. training, validation, test)
- shuffling the data set

- looping through the samples of the data set.
- centering on the mean, normalizing, getting the covariance of two variables, getting the covariance matrix for dataset of type VecFloat

It provides an unique interface to several implementation supporting various types of dataset. Supported types are: VecFloat and pair of GenBrush (img/mask).

The GDataSet library uses the PBErr, GSet, PBJson, PBMath and PBFileSys libraries.

## 1 Interface

```
// ===== GDATASET_H =====

#ifndef GDATASET_H
#define GDATASET_H

// ===== Include =====

#include <stdlib.h>
#include <stdio.h>
#include <stdbool.h>
#include <execinfo.h>
#include <errno.h>
#include <string.h>
#include "pberr.h"
#include "gset.h"
#include "pbmath.h"
#include "pbjson.h"
#include "pbfilesys.h"

// Define locally the needed types and functions for libraries that were
// not included to allow the user to include only what's needed for her
// application
#ifndef GENBRUSH_H
typedef struct GenBrush GenBrush;
typedef enum GBScaleMethod {GBScaleMethod_Default} GBScaleMethod;
GenBrush* GBCreateFromFile(const char* const fileName);
GenBrush* GBScale(const GenBrush* const that,
    const VecShort2D* const dim, const GBScaleMethod scaleMethod);
void GBFree(GenBrush** that);
VecShort2D* GBDim(const GenBrush* const that);
#endif

// ===== Define =====

typedef enum GDataSetType {
    GDataSetType_VecFloat, GDataSetType_GenBrushPair
} GDataSetType;

// ===== Data structures =====
```

```

typedef struct GDataSet {
    // Path to the config file of the data set
    char* _cfgFilePath;
    // Data in the config file encoded as JSON object
    JSONNode* _json;
    // Name of the data set
    char* _name;
    // Description of the data set
    char* _desc;
    // Type of set
    GDataSetType _type;
    // Nb of samples
    int _nbSample;
    // Set of samples
    GSet _samples;
    // Dimensions of each sample, they must have all the same dimension
    // e.g.:
    // if samples are VecFloat<3> then _dim = VecShort<1>[3]
    // if samples are GenBrush then _dim = VecShort<2>[width, height]
    VecShort* _sampleDim;
    // Splitting of samples
    VecShort* _split;
    // Sets of splitted samples
    GSet* _categories;
    // Iterators on the sets of splitted samples
    GSetIterForward* _iterators;
} GDataSet;

typedef struct GDataSetVecFloat {
    // Generic GDataSet
    GDataSet _dataSet;
} GDataSetVecFloat;

typedef struct GDataSetGenBrushPair {
    // Generic GDataSet
    GDataSet _dataSet;
    // Format of images
    char* _format;
    // Dimensions of images
    VecShort2D _dim;
    // Nb of mask per img
    int _nbMask;
} GDataSetGenBrushPair;

#define GDS_NBMAXMASK 100
typedef struct GDSFilePathPair {
    char* _path[1 + GDS_NBMAXMASK];
} GDSFilePathPair;

typedef struct GDSGenBrushPair {
    GenBrush* _img;
    GenBrush* _mask[GDS_NBMAXMASK];
} GDSGenBrushPair;

// ===== Functions declaration =====

// Create a new GDataSet defined by the file at 'cfgFilePath'
GDataSet GDataSetCreateStatic(const char* const cfgFilePath);

// Free the memory used by a GDataSet
void GDataSetFreeStatic(GDataSet* const that);

```

```

// Create a new GDataSetVecFloat defined by the file at 'cfgFilePath'
GDataSetVecFloat GDataSetVecFloatCreateStatic(
    const char* const cfgFilePath);

// Free the memory used by a GDataSetVecFloat
void GDataSetVecFloatFreeStatic(GDataSetVecFloat* const that);

// Create a new GDataSetGenBrushPair defined by the file at 'cfgFilePath'
GDataSetGenBrushPair GDataSetGenBrushPairCreateStatic(
    const char* const cfgFilePath);

// Free the memory used by a GDataSetGenBrushPair
void GDataSetGenBrushPairFreeStatic(GDataSetGenBrushPair* const that);

// Get the total number of samples in the GDataSet 'that'
#if BUILDMODE != 0
inline
#endif
long _GDSGetSize(const GDataSet* const that);

// Get the number of masks in the GDataSet 'that'
int _GDSGetNbMask(const GDataSet* const that);

// Get the number of masks in the GDataSetGenBrushPair 'that'
#if BUILDMODE != 0
inline
#endif
int GDSGetNbMaskGenBrushPair(const GDataSetGenBrushPair* const that);

// Get the total number of samples in the GDataSet 'that' for the
// category 'iCat'. Return 0 if the category doesn't exists
#if BUILDMODE != 0
inline
#endif
long _GDSGetSizeCat(const GDataSet* const that, const long iCat);

// Split the samples of the GDataSet 'that' into several categories
// defined by 'cat'. The dimension of 'cat' gives the number of
// categories and the value for each dimension of 'cat' gives the
// number of samples in the corresponding category. For example <3,4>
// would mean 2 categories with 3 samples in the first one and 4
// samples in the second one. There must be at least as many samples
// in the data set as the sum of samples in 'cat'.
// Each category must have at least one sample. Samples are allocated // randomly to the categories.
// If 'that' was already splitted the previous splitting is discarded.
void _GDSSplit(GDataSet* const that, const VecShort* const cat);

// Unsplit the GDataSet 'that', i.e. after calling GDataSetUnsplit 'that'
// has only one category containing all the samples
#if BUILDMODE != 0
inline
#endif
void _GDSUnsplit(GDataSet* const that);

// Shuffle the samples of the category 'iCat' of the GDataSet 'that'.
// Reset the iterator of the category
#if BUILDMODE != 0
inline
#endif
void _GDSShuffle(GDataSet* const that, const long iCat);

// Shuffle the samples of all the categories of the GDataSet 'that'.

```

```

// Reset the iterator of the categories
#if BUILDMODE != 0
inline
#endif
void _GDSShuffleAll(GDataSet* const that);

// Get the name of the GDataSet 'that'
#if BUILDMODE != 0
inline
#endif
const char* _GDSName(const GDataSet* const that);

// Get the description of the GDataSet 'that'
#if BUILDMODE != 0
inline
#endif
const char* _GDSDesc(const GDataSet* const that);

// Get the path of the config file of the GDataSet 'that'
#if BUILDMODE != 0
inline
#endif
const char* _GDSCfgFilePath(const GDataSet* const that);

// Get a copy of the path of the config file of the GDataSet 'that'
#if BUILDMODE != 0
inline
#endif
char* _GDSGetCfgFilePath(const GDataSet* const that);

// Get the path of the folder of the config file of the GDataSet 'that'
#if BUILDMODE != 0
inline
#endif
char* _GDSGetCfgFolderPath(const GDataSet* const that);

// Get the type of the GDataSet 'that'
#if BUILDMODE != 0
inline
#endif
GDataSetType _GDSGetType(const GDataSet* const that);

// Get the number of categories of the GDataSet 'that'
#if BUILDMODE != 0
inline
#endif
long _GDSGetNbCat(const GDataSet* const that);

// If there is a next sample move to the next sample of the category
// 'iCat' and return true, else return false
#if BUILDMODE != 0
inline
#endif
bool _GDSStepSample(const GDataSet* const that, const long iCat);

// Reset the iterator on category 'iCat' of the GDataSet 'that', i.e.
// the next call to GDataSetGetNextSample will give the first sample of
// the category 'iCat'
#if BUILDMODE != 0
inline
#endif
void _GDSReset(GDataSet* const that, const long iCat);

```

```

// Reset the iterator on all categories of the GDataSet 'that'
#if BUILDMODE != 0
inline
#endif
void _GDSResetAll(GDataSet* const that);

// Get the current sample in the category 'iCat' of the GDataSet 'that'
void* _GDSGetSample(
    const GDataSet* const that, const int iCat);
VecFloat* GDSGetSampleVecFloat(
    const GDataSetVecFloat* const that, const int iCat);
GDSGenBrushPair* GDSGetSampleGenBrushPair(
    const GDataSetGenBrushPair* const that, const int iCat);

// Release the memory used by the FilePathPair 'that'
void GDSFilePathPairFree(GDSFilePathPair** const that);
#ifdef GENBRUSH_H
// Release the memory used by the GenBrushPair 'that'
void GDSGenBrushPairFree(GDSGenBrushPair** const that);
#endif

// Get the dimensions of the samples of GDataSet 'that'
#if BUILDMODE != 0
inline
#endif
const VecShort* _GDSSampleDim(const GDataSet* const that);

// Get the samples of the GDataSet 'that'
#if BUILDMODE != 0
inline
#endif
const GSetVecFloat* _GDSVecFloatSamples(
    const GDataSetVecFloat* const that);
#if BUILDMODE != 0
inline
#endif
const GSet* _GDSGenBrushPairSamples(
    const GDataSetGenBrushPair* const that);

// Center the GDataSet 'that' on its mean
void GDSMeanCenter(GDataSetVecFloat* const that);

// Normalize the GDataSet 'that', ie normalize each of its vectors
void GDSNormalize(GDataSetVecFloat* const that);

// Get the mean of the GDataSet 'that'
VecFloat* GDSGetMean(const GDataSetVecFloat* const that);

// Get a clone of the GDataSet 'that'
// All the data in the GDataSet are cloned except for the splitting
// categories which are reset to one category made of the original data
GDataSetVecFloat GDSClone(const GDataSetVecFloat* const that);

// Get the covariance matrix of the GDataSetVecFloat 'that'
MatFloat* GDSGetCovarianceMatrix(const GDataSetVecFloat* const that);

// Get the covariance of the variables at 'indices' in the
// GDataSetVecFloat 'that'
float GDSGetCovariance(const GDataSetVecFloat* const that,
    const VecShort2D* const indices);

```

```

// ===== Polymorphism =====

#define GDSCfgFilePath(DataSet) _Generic(DataSet, \
    GDataSet*: _GDSCfgFilePath, \
    const GDataSet*: _GDSCfgFilePath, \
    GDataSetVecFloat*: _GDSCfgFilePath, \
    const GDataSetVecFloat*: _GDSCfgFilePath, \
    GDataSetGenBrushPair*: _GDSCfgFilePath, \
    const GDataSetGenBrushPair*: _GDSCfgFilePath, \
    default: PBErrInvalidPolymorphism)((const GDataSet*)DataSet)

#define GDSGetCfgFilePath(DataSet) _Generic(DataSet, \
    GDataSet*: _GDSGetCfgFilePath, \
    const GDataSet*: _GDSGetCfgFilePath, \
    GDataSetVecFloat*: _GDSGetCfgFilePath, \
    const GDataSetVecFloat*: _GDSGetCfgFilePath, \
    GDataSetGenBrushPair*: _GDSGetCfgFilePath, \
    const GDataSetGenBrushPair*: _GDSGetCfgFilePath, \
    default: PBErrInvalidPolymorphism)((const GDataSet*)DataSet)

#define GDSGetCfgFolderPath(DataSet) _Generic(DataSet, \
    GDataSet*: _GDSGetCfgFolderPath, \
    const GDataSet*: _GDSGetCfgFolderPath, \
    GDataSetVecFloat*: _GDSGetCfgFolderPath, \
    const GDataSetVecFloat*: _GDSGetCfgFolderPath, \
    GDataSetGenBrushPair*: _GDSGetCfgFolderPath, \
    const GDataSetGenBrushPair*: _GDSGetCfgFolderPath, \
    default: PBErrInvalidPolymorphism)((const GDataSet*)DataSet)

#define GDSDesc(DataSet) _Generic(DataSet, \
    GDataSet*: _GDSDesc, \
    const GDataSet*: _GDSDesc, \
    GDataSetVecFloat*: _GDSDesc, \
    const GDataSetVecFloat*: _GDSDesc, \
    GDataSetGenBrushPair*: _GDSDesc, \
    const GDataSetGenBrushPair*: _GDSDesc, \
    default: PBErrInvalidPolymorphism)((const GDataSet*)DataSet)

#define GDSGetNbCat(DataSet) _Generic(DataSet, \
    GDataSet*: _GDSGetNbCat, \
    const GDataSet*: _GDSGetNbCat, \
    GDataSetVecFloat*: _GDSGetNbCat, \
    const GDataSetVecFloat*: _GDSGetNbCat, \
    GDataSetGenBrushPair*: _GDSGetNbCat, \
    const GDataSetGenBrushPair*: _GDSGetNbCat, \
    default: PBErrInvalidPolymorphism)((const GDataSet*)DataSet)

#define GDSGetSample(DataSet, ICat) _Generic(DataSet, \
    GDataSet*: _GDSGetSample, \
    const GDataSet*: _GDSGetSample, \
    GDataSetVecFloat*: GDSGetSampleVecFloat, \
    const GDataSetVecFloat*: GDSGetSampleVecFloat, \
    GDataSetGenBrushPair*: GDSGetSampleGenBrushPair, \
    const GDataSetGenBrushPair*: GDSGetSampleGenBrushPair, \
    default: PBErrInvalidPolymorphism)(DataSet, ICat)

#define GDSGetSize(DataSet) _Generic(DataSet, \
    GDataSet*: _GDSGetSize, \
    const GDataSet*: _GDSGetSize, \
    GDataSetVecFloat*: _GDSGetSize, \
    const GDataSetVecFloat*: _GDSGetSize, \
    GDataSetGenBrushPair*: _GDSGetSize, \

```

```

    const GDataSetGenBrushPair*: _GDSGetSize, \
    default: PBErrInvalidPolymorphism)((const GDataSet*)DataSet)

#define GDSGetSizeCat(DataSet, ICat) _Generic(DataSet, \
    GDataSet*: _GDSGetSizeCat, \
    const GDataSet*: _GDSGetSizeCat, \
    GDataSetVecFloat*: _GDSGetSizeCat, \
    const GDataSetVecFloat*: _GDSGetSizeCat, \
    GDataSetGenBrushPair*: _GDSGetSizeCat, \
    const GDataSetGenBrushPair*: _GDSGetSizeCat, \
    default: PBErrInvalidPolymorphism)((const GDataSet*)DataSet, ICat)

#define GDSGetType(DataSet) _Generic(DataSet, \
    GDataSet*: _GDSGetType, \
    const GDataSet*: _GDSGetType, \
    GDataSetVecFloat*: _GDSGetType, \
    const GDataSetVecFloat*: _GDSGetType, \
    GDataSetGenBrushPair*: _GDSGetType, \
    const GDataSetGenBrushPair*: _GDSGetType, \
    default: PBErrInvalidPolymorphism)((const GDataSet*)DataSet)

#define GDSName(DataSet) _Generic(DataSet, \
    GDataSet*: _GDSName, \
    const GDataSet*: _GDSName, \
    GDataSetVecFloat*: _GDSName, \
    const GDataSetVecFloat*: _GDSName, \
    GDataSetGenBrushPair*: _GDSName, \
    const GDataSetGenBrushPair*: _GDSName, \
    default: PBErrInvalidPolymorphism)((const GDataSet*)DataSet)

#define GDSGetNbMask(DataSet) _Generic(DataSet, \
    GDataSet*: _GDSGetNbMask, \
    const GDataSet*: _GDSGetNbMask, \
    GDataSetGenBrushPair*: GDSGetNbMaskGenBrushPair, \
    const GDataSetGenBrushPair*: GDSGetNbMaskGenBrushPair, \
    default: PBErrInvalidPolymorphism)(DataSet)

#define GDSReset(DataSet, ICat) _Generic(DataSet, \
    GDataSet*: _GDSReset, \
    const GDataSet*: _GDSReset, \
    GDataSetVecFloat*: _GDSReset, \
    const GDataSetVecFloat*: _GDSReset, \
    GDataSetGenBrushPair*: _GDSReset, \
    const GDataSetGenBrushPair*: _GDSReset, \
    default: PBErrInvalidPolymorphism)((GDataSet*)DataSet, ICat)

#define GDSResetAll(DataSet) _Generic(DataSet, \
    GDataSet*: _GDSResetAll, \
    const GDataSet*: _GDSResetAll, \
    GDataSetVecFloat*: _GDSResetAll, \
    const GDataSetVecFloat*: _GDSResetAll, \
    GDataSetGenBrushPair*: _GDSResetAll, \
    const GDataSetGenBrushPair*: _GDSResetAll, \
    default: PBErrInvalidPolymorphism)((const GDataSet*)DataSet)

#define GDSSampleDim(DataSet) _Generic(DataSet, \
    GDataSet*: _GDSSampleDim, \
    const GDataSet*: _GDSSampleDim, \
    GDataSetVecFloat*: _GDSSampleDim, \
    const GDataSetVecFloat*: _GDSSampleDim, \
    GDataSetGenBrushPair*: _GDSSampleDim, \
    const GDataSetGenBrushPair*: _GDSSampleDim, \

```



```

    default: PBErrInvalidPolymorphism)((const GDataSet*)DataSet)

#define GDSShuffle(DataSet, ICat) _Generic(DataSet, \
    GDataSet*: _GDSShuffle, \
    GDataSetVecFloat*: _GDSShuffle, \
    GDataSetGenBrushPair*: _GDSShuffle, \
    default: PBErrInvalidPolymorphism)((GDataSet*)DataSet, ICat)

#define GDSShuffleAll(DataSet) _Generic(DataSet, \
    GDataSet*: _GDSShuffleAll, \
    GDataSetVecFloat*: _GDSShuffleAll, \
    GDataSetGenBrushPair*: _GDSShuffleAll, \
    default: PBErrInvalidPolymorphism)((GDataSet*)DataSet)

#define GDSSplit(DataSet, Cat) _Generic(DataSet, \
    GDataSet*: _GDSSplit, \
    GDataSetVecFloat*: _GDSSplit, \
    GDataSetGenBrushPair*: _GDSSplit, \
    default: PBErrInvalidPolymorphism)((GDataSet*)DataSet, Cat)

#define GDSSStepSample(DataSet, ICat) _Generic(DataSet, \
    GDataSet*: _GDSSStepSample, \
    const GDataSet*: _GDSSStepSample, \
    GDataSetVecFloat*: _GDSSStepSample, \
    const GDataSetVecFloat*: _GDSSStepSample, \
    GDataSetGenBrushPair*: _GDSSStepSample, \
    const GDataSetGenBrushPair*: _GDSSStepSample, \
    default: PBErrInvalidPolymorphism)((const GDataSet*)DataSet, ICat)

#define GDSUnsplit(DataSet) _Generic(DataSet, \
    GDataSet*: _GDSUnsplit, \
    GDataSetVecFloat*: _GDSUnsplit, \
    GDataSetGenBrushPair*: _GDSUnsplit, \
    default: PBErrInvalidPolymorphism)((GDataSet*)DataSet)

#define GDSSamples(DataSet) _Generic(DataSet, \
    GDataSetVecFloat*: _GDSVecFloatSamples, \
    const GDataSetVecFloat*: _GDSVecFloatSamples, \
    GDataSetGenBrushPair*: _GDSGenBrushPairSamples, \
    const GDataSetGenBrushPair*: _GDSGenBrushPairSamples, \
    default: PBErrInvalidPolymorphism)(DataSet)

// ===== Inliner =====

#if BUILDMODE != 0
#include "gdataset-inline.c"
#endif

#endif

```

## 2 Code

### 2.1 gdataset.c

```

// ===== GDATASET_C =====

// ===== Include =====

```

```

#include "gdataset.h"
#if BUILDMODE == 0
#include "gdataset-inline.c"
#endif

// ===== Functions implementation =====

// Create a new GDataSet defined by the file at 'cfgFilePath'
GDataSet GDataSetCreateStatic(const char* const cfgFilePath) {
#if BUILDMODE == 0
    if (cfgFilePath == NULL) {
        GDataSetErr->_type = PBErrTypeNullPointer;
        sprintf(PBImgAnalysisErr->_msg, "'cfgFilePath' is null");
        PBErrCatch(PBImgAnalysisErr);
    }
#endif
    // Declare the new GDataSet
    GDataSet that;
    // Copy the file path
    that._cfgFilePath = PBErrMalloc(GDataSetErr, strlen(cfgFilePath) + 1);
    strcpy(that._cfgFilePath, cfgFilePath);
    // Open the description file
    FILE* cfgFile = fopen(cfgFilePath, "r");
    // If the description file doesn't exist
    if (cfgFile == NULL) {
        GDataSetErr->_type = PBErrTypeInvalidArg;
        sprintf(GDataSetErr->_msg, "Can't open the configuration file %s",
            cfgFilePath);
        PBErrCatch(GDataSetErr);
    }
    // Load the encoded data
    that._json = JSONCreate();
    // Load the whole encoded data
    if (JSONLoad(that._json, cfgFile) == false) {
        printf("%s\n", GDataSetErr->_msg);
        GDataSetErr->_type = PBErrTypeInvalidData;
        sprintf(GDataSetErr->_msg, "Can't load the configuration file");
        PBErrCatch(GDataSetErr);
    }
    // Decode dataSet
    JSONNode* prop = JSONProperty(that._json, "dataSet");
    if (prop == NULL) {
        GDataSetErr->_type = PBErrTypeInvalidData;
        sprintf(GDataSetErr->_msg,
            "Invalid description file (dataSet missing)");
        PBErrCatch(GDataSetErr);
    }
    JSONNode* val = JSONValue(prop, 0);
    that._name = PBErrMalloc(GDataSetErr,
        sizeof(char) * (strlen(JSONLabel(val)) + 1));
    strcpy(that._name, JSONLabel(val));
    // Decode desc
    prop = JSONProperty(that._json, "desc");
    if (prop == NULL) {
        GDataSetErr->_type = PBErrTypeInvalidData;
        sprintf(GDataSetErr->_msg,
            "Invalid description file (desc missing)");
        PBErrCatch(GDataSetErr);
    }
    val = JSONValue(prop, 0);
    that._desc = PBErrMalloc(GDataSetErr,
        sizeof(char) * (strlen(JSONLabel(val)) + 1));

```

```

strcpy(that._desc, JSONLabel(val));
// Decode dataSetType
prop = JSONProperty(that._json, "dataSetType");
if (prop == NULL) {
    GDataSetErr->_type = PErrTypeInvalidData;
    sprintf(GDataSetErr->_msg,
        "Invalid description file (dataSetType missing)");
    PErrCatch(GDataSetErr);
}
val = JSONValue(prop, 0);
that._type = atoi(JSONLabel(val));
// Decode dim
prop = JSONProperty(that._json, "dim");
if (prop == NULL) {
    GDataSetErr->_type = PErrTypeInvalidData;
    sprintf(GDataSetErr->_msg,
        "Invalid description file (dim missing)");
    PErrCatch(GDataSetErr);
}
that._sampleDim = NULL;
VecDecodeAsJSON(&(that._sampleDim), prop);
// Decode nbSample
prop = JSONProperty(that._json, "nbSample");
if (prop == NULL) {
    GDataSetErr->_type = PErrTypeInvalidData;
    sprintf(GDataSetErr->_msg,
        "Invalid description file (nbSample missing)");
    PErrCatch(GDataSetErr);
}
val = JSONValue(prop, 0);
that._nbSample = atoi(JSONLabel(val));
// Init the splits and iterators
that._split = NULL;
that._categories = NULL;
that._iterators = NULL;

// Close the description file
fclose(cfgFile);

// Return the new GDataSet
return that;
}

// Free the memory used by a GDataSet
void GDataSetFreeStatic(GDataSet* const that) {
    if (that == NULL)
        return;
    // Free memory
    JSONFree(&(that->_json));
    free(that->_name);
    free(that->_desc);
    free(that->_cfgFilePath);
    for (int iCat = GDSGetNbCat(that); iCat--;) {
        GSetFlush(that->_categories + iCat);
    }
    free(that->_categories);
    free(that->_iterators);
    VecFree(&(that->_split));
    VecFree(&(that->_sampleDim));
}

// Create a new GDataSetVecFloat defined by the file at 'cfgFilePath'

```

```

GDataSetVecFloat GDataSetVecFloatCreateStatic(
    const char* const cfgFilePath) {
    #if BUILDMODE == 0
        if (cfgFilePath == NULL) {
            GDataSetErr->_type = PBErrTypeNullPointer;
            sprintf(PBImgAnalysisErr->_msg, "'cfgFilePath' is null");
            PBErrCatch(PBImgAnalysisErr);
        }
    #endif
    // Declare the new GDataSetVecFloat
    GDataSetVecFloat that;
    // Create the generic GDataSet
    that._dataSet = GDataSetCreateStatic(cfgFilePath);
    // Check the type
    if (GDSGetType(&that) != GDataSetType_VecFloat) {
        GDataSetErr->_type = PBErrTypeInvalidData;
        sprintf(GDataSetErr->_msg, "Invalid type");
        PBErrCatch(GDataSetErr);
    }
    // Check the samples' dimension
    if (VecGetDim(GDSSampleDim(&that)) != 1) {
        GDataSetErr->_type = PBErrTypeInvalidData;
        sprintf(GDataSetErr->_msg, "Invalid sample dimension");
        PBErrCatch(GDataSetErr);
    }
    // Load the samples
    JSONNode* prop = JSONProperty(that._dataSet._json, "samples");
    if (prop == NULL) {
        GDataSetErr->_type = PBErrTypeInvalidData;
        sprintf(GDataSetErr->_msg,
            "Invalid description file (samples missing)");
        PBErrCatch(GDataSetErr);
    }
    if (JSONGetNbValue(prop) != that._dataSet._nbSample) {
        GDataSetErr->_type = PBErrTypeInvalidData;
        sprintf(GDataSetErr->_msg,
            "Invalid description file (samples's number != nbSample)");
        PBErrCatch(GDataSetErr);
    }
    that._dataSet._samples = GSetCreateStatic();
    for (int iSample = 0; iSample < that._dataSet._nbSample; ++iSample) {
        JSONNode* val = JSONValue(prop, iSample);
        VecFloat* v = NULL;
        VecDecodeAsJSON(&v, val);
        GSetAppend(&(that._dataSet._samples), v);
    }
    // Create the initial category
    that._dataSet._split = VecShortCreate(1);
    VecSet(that._dataSet._split, 0, that._dataSet._nbSample);
    that._dataSet._categories = PBErrMalloc(GDataSetErr, sizeof(GSet));
    that._dataSet._categories[0] = GSetCreateStatic();
    GSetIterForward iter =
        GSetIterForwardCreateStatic(&(that._dataSet._samples));
    do {
        void* sample = GSetIterGet(&iter);
        GSetAppend(that._dataSet._categories, sample);
    } while (GSetIterStep(&iter));
    that._dataSet._iterators =
        PBErrMalloc(GDataSetErr, sizeof(GSetIterForward));
    that._dataSet._iterators[0] =
        GSetIterForwardCreateStatic(that._dataSet._categories);
    // Return the new GDataSetVecFloat

```

```

    return that;
}

// Free the memory used by a GDataSetVecFloat
void GDataSetVecFloatFreeStatic(GDataSetVecFloat* const that) {
    if (that == NULL)
        return;
    // Free memory
    GDataSetFreeStatic((GDataSet*)that);
    while (GSetNbElem(&(((GDataSet*)that)->_samples)) > 0) {
        VecFloat* sample = GSetPop(&(((GDataSet*)that)->_samples));
        VecFree(&sample);
    }
}

// Create a new GDataSetGenBrushPair defined by the file at 'cfgFilePath'
// The random generator must have been initialized before calling
// this function
GDataSetGenBrushPair GDataSetGenBrushPairCreateStatic(
    const char* const cfgFilePath) {
    #if BUILDMODE == 0
        if (cfgFilePath == NULL) {
            GDataSetErr->_type = PBErrTypeNullPointer;
            sprintf(PBImgAnalysisErr->_msg, "'cfgFilePath' is null");
            PBErrCatch(PBImgAnalysisErr);
        }
    #endif
    // Declare the new GDataSetVecFloat
    GDataSetGenBrushPair that;
    // Create the generic GDataSet
    that._dataSet = GDataSetCreateStatic(cfgFilePath);
    // Check the type
    if (GDSGetType(&that) != GDataSetType_GenBrushPair) {
        GDataSetErr->_type = PBErrTypeInvalidData;
        sprintf(GDataSetErr->_msg, "Invalid type");
        PBErrCatch(GDataSetErr);
    }
    // Check the samples' dimension
    if (VecGetDim(GDSSampleDim(&that)) != 2) {
        GDataSetErr->_type = PBErrTypeInvalidData;
        sprintf(GDataSetErr->_msg, "Invalid sample dimension (%ld=2)",
            VecGetDim(GDSSampleDim(&that)));
        PBErrCatch(GDataSetErr);
    }
    // Get the nb of mask
    JSONNode* prop = JSONProperty(that._dataSet._json, "nbMask");
    if (prop == NULL) {
        GDataSetErr->_type = PBErrTypeInvalidData;
        sprintf(GDataSetErr->_msg,
            "Invalid description file (nbMask missing)");
        PBErrCatch(GDataSetErr);
    }
    that._nbMask = atoi(JSONLabel(JSONValue(prop), 0));
    if (that._nbMask >= GDS_NBMAXMASK) {
        GDataSetErr->_type = PBErrTypeInvalidData;
        sprintf(GDataSetErr->_msg,
            "Invalid description file (invalid nbMask %d>=%d)",
            that._nbMask, GDS_NBMAXMASK);
        PBErrCatch(GDataSetErr);
    }
    // Load the samples
    prop = JSONProperty(that._dataSet._json, "samples");

```

```

if (prop == NULL) {
    GDataSetErr->_type = PBErrTypeInvalidData;
    sprintf(GDataSetErr->_msg,
        "Invalid description file (samples missing)");
    PBErrCatch(GDataSetErr);
}
if (JSONGetNbValue(prop) != that._dataSet._nbSample) {
    GDataSetErr->_type = PBErrTypeInvalidData;
    sprintf(GDataSetErr->_msg,
        "Invalid description file (samples's number != nbSample)");
    PBErrCatch(GDataSetErr);
}
that._dataSet._samples = GSetCreateStatic();
for (int iSample = 0; iSample < that._dataSet._nbSample; ++iSample) {
    JSONNode* val = JSONValue(prop, iSample);
    // Allocate memory for the pair image/mask
    GDSFilePathPair* pair = PBErrMalloc(GDataSetErr,
        sizeof(GDSFilePathPair));
    pair->_path[0] = NULL;
    for (int iMask = GDS_NBMAXMASK; iMask--;)
        pair->_path[1 + iMask] = NULL;
    // Decode img
    JSONNode* subProp = JSONProperty(val, "img");
    if (subProp == NULL) {
        GDataSetErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GDataSetErr->_msg,
            "Invalid description file (samples.img missing)");
        PBErrCatch(GDataSetErr);
    }
    JSONNode* subVal = JSONValue(subProp, 0);
    pair->_path[0] = PBErrMalloc(GDataSetErr,
        sizeof(char) * (strlen(JSONLabel(subVal)) + 1));
    strcpy(pair->_path[0], JSONLabel(subVal));
    // Decode mask
    subProp = JSONProperty(val, "mask");
    if (subProp == NULL) {
        GDataSetErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GDataSetErr->_msg,
            "Invalid description file (samples.mask missing)");
        PBErrCatch(GDataSetErr);
    }
    for (int iMask = 0; iMask < that._nbMask; ++iMask) {
        subVal = JSONValue(subProp, iMask);
        pair->_path[1 + iMask] = PBErrMalloc(GDataSetErr,
            sizeof(char) * (strlen(JSONLabel(subVal)) + 1));
        strcpy(pair->_path[1 + iMask], JSONLabel(subVal));
    }
    // Add the pair to the samples
    GSetAppend(&(that._dataSet._samples), pair);
}
// Create the initial category
that._dataSet._split = VecShortCreate(1);
VecSet(that._dataSet._split, 0, that._dataSet._nbSample);
that._dataSet._categories = PBErrMalloc(GDataSetErr, sizeof(GSet));
that._dataSet._categories[0] = GSetCreateStatic();
GSetIterForward iter =
    GSetIterForwardCreateStatic(&(that._dataSet._samples));
do {
    void* sample = GSetIterGet(&iter);
    GSetAppend(that._dataSet._categories, sample);
} while (GSetIterStep(&iter));
that._dataSet._iterators =

```

```

    PBErrMalloc(GDataSetErr, sizeof(GSetIterForward));
    that->_dataSet._iterators[0] =
        GSetIterForwardCreateStatic(that->_dataSet._categories);
    // Return the new GDataSetVecFloat
    return that;
}

// Free the memory used by a GDataSetGenBrushPair
void GDataSetGenBrushPairFreeStatic(GDataSetGenBrushPair* const that) {
    if (that == NULL)
        return;
    // Free memory
    GDataSetFreeStatic((GDataSet*)that);
    while (GSetNbElem(&((GDataSet*)that)->_samples) > 0) {
        GDSFilePathPair* sample = GSetPop(&((GDataSet*)that)->_samples);
        GDSFilePathPairFree(&sample);
    }
}

// Split the samples of the GDataSet 'that' into several categories
// defined by 'cat'. The dimension of 'cat' gives the number of
// categories and the value for each dimension of 'cat' gives the
// number of samples in the corresponding category. For example <3,4>
// would mean 2 categories with 3 samples in the first one and 4
// samples in the second one. There must be at least as many samples
// in the data set as the sum of samples in 'cat'.
// Each category must have at least one sample. Samples are allocated // randomly to the categories.
// If 'that' was already splitted the previous splitting is discarded.
void _GDSSplit(GDataSet* const that, const VecShort* const cat) {
#ifdef BUILDMODE == 0
    if (that == NULL) {
        GDataSetErr->_type = PBErrTypeNullPointer;
        sprintf(PBImgAnalysisErr->_msg, "'that' is null");
        PBErrCatch(PBImgAnalysisErr);
    }
    long nb = 0;
    for (long iCat = VecGetDim(cat); iCat--;)
        nb += VecGet(cat, iCat);
    if (nb > GDSGetSize(that)) {
        GDataSetErr->_type = PBErrTypeInvalidArg;
        sprintf(PBImgAnalysisErr->_msg,
            "Not enough samples for the requested splitting (%ld<%ld)",
            nb, GDSGetSize(that));
        PBErrCatch(PBImgAnalysisErr);
    }
#endif
    // Free the current splitting if necessary
    if (that->_categories != NULL) {
        if (that->_split != NULL) {
            for (int iCat = GDSGetNbCat(that); iCat--;) {
                GSetFlush(that->_categories + iCat);
            }
        }
        free(that->_categories);
    }
    if (that->_iterators)
        free(that->_iterators);
    VecFree(&(that->_split));
    // Get the number of categories
    long nbCat = VecGetDim(cat);
    // Allocate memory for the categories
    that->_categories = PBErrMalloc(GDataSetErr, sizeof(GSet) * nbCat);

```

```

for (long iCat = nbCat; iCat--;) {
    that->_categories[iCat] = GSetCreateStatic();
}
// Copy the splitting
that->_split = VecClone(cat);
// Shuffle the samples
GSetShuffle(&(amp;that->_samples));
// Declare an iterator on the samples
GSetIterForward iter = GSetIterForwardCreateStatic(&(amp;that->_samples));
// Loop on categories
for (long iCat = nbCat; iCat--;) {
    // Get the nb of samples for this category
    long nbSample = VecGet(cat, iCat);
    // Loop on the sample
    for (long iSample = nbSample; iSample--; GSetIterStep(&iter)) {
        // Get the next sample
        void* sample = GSetIterGet(&iter);
        // Add the sample to the category
        GSetAppend(that->_categories + iCat, sample);
    }
}
// Allocate memory for the iterators
that->_iterators = PBErrMalloc(GDataSetErr,
    sizeof(GSetIterForward) * nbCat);
for (long iCat = nbCat; iCat--;) {
    that->_iterators[iCat] =
        GSetIterForwardCreateStatic(that->_categories + iCat);
}
}

// Get the current sample in the category 'iCat' of the GDataSet 'that'
void* _GDSGetSample(
    const GDataSet* const that, const int iCat) {
    // Call the appropriate function according to the type
    switch (GDSGetType(that)) {
        case GDataSetType_VecFloat:
            return GDSGetSampleVecFloat((GDataSetVecFloat*)that, iCat);
            break;
        case GDataSetType_GenBrushPair:
            return GDSGetSampleGenBrushPair((GDataSetGenBrushPair*)that, iCat);
            break;
        default:
            return NULL;
            break;
    }
}

// Get the number of masks in the GDataSet 'that'
int _GDSGetNbMask(const GDataSet* const that) {
    // Call the appropriate function according to the type
    switch (GDSGetType(that)) {
        case GDataSetType_GenBrushPair:
            return GDSGetNbMaskGenBrushPair((GDataSetGenBrushPair*)that);
            break;
        default:
            return 0;
            break;
    }
}

VecFloat* GDSGetSampleVecFloat(
    const GDataSetVecFloat* const that, const int iCat) {

```



```

#if BUILDMODE == 0
    if (that == NULL) {
        GDataSetErr->_type = PErrTypeNullPointer;
        sprintf(PBImgAnalysisErr->_msg, "'that' is null");
        PErrCatch(PBImgAnalysisErr);
    }
    if (iCat < 0 || iCat >= GDSGetNbCat(that)) {
        GDataSetErr->_type = PErrTypeInvalidArg;
        sprintf(PBImgAnalysisErr->_msg, "'iCat' is invalid (0<=%d<%ld)",
            iCat, GDSGetNbCat(that));
        PErrCatch(PBImgAnalysisErr);
    }
#endif
    VecFloat* sample = GSetIterGet(((GDataSet*)that)->_iterators + iCat);
    return VecClone(sample);
}

GDSGenBrushPair* GDSGetSampleGenBrushPair(
    const GDataSetGenBrushPair* const that, const int iCat) {
#if BUILDMODE == 0
    if (that == NULL) {
        GDataSetErr->_type = PErrTypeNullPointer;
        sprintf(PBImgAnalysisErr->_msg, "'that' is null");
        PErrCatch(PBImgAnalysisErr);
    }
    if (iCat < 0 || iCat >= GDSGetNbCat(that)) {
        GDataSetErr->_type = PErrTypeInvalidArg;
        sprintf(PBImgAnalysisErr->_msg, "'iCat' is invalid (0<=%d<%ld)",
            iCat, GDSGetNbCat(that));
        PErrCatch(PBImgAnalysisErr);
    }
#endif
    GDSFilePathPair* pairFile =
        GSetIterGet(((GDataSet*)that)->_iterators + iCat);
    GDSGenBrushPair* pairSample = PErrMalloc(GDataSetErr,
        sizeof(GDSGenBrushPair));
    for (int iMask = 0; iMask < GDS_NBMAXMASK; ++iMask)
        pairSample->_mask[iMask] = NULL;
    char* root = GDSGetCfgFolderPath(that);
    char* path = PBFSJoinPath(root, pairFile->_path[0]);
    GenBrush* gb = GBCreateFromFile(path);
    // Rescale the sample if needed to always provide to the user
    // the dimensions defined in the configuration file of the data set
    if (gb != NULL && !VecIsEqual(GBDim(gb), GDSSampleDim(that))) {
        pairSample->_img = GBScale(gb,
            (const VecShort2D*)GDSSampleDim(that), GBScaleMethod_Default);
        GBFree(&gb);
    } else {
        pairSample->_img = gb;
    }
    free(path);
    for (int iMask = 0; iMask < GDSGetNbMask(that); ++iMask) {
        path = PBFSJoinPath(root, pairFile->_path[1 + iMask]);
        gb = GBCreateFromFile(path);
        if (gb != NULL && !VecIsEqual(GBDim(gb), GDSSampleDim(that))) {
            pairSample->_mask[iMask] = GBScale(gb,
                (const VecShort2D*)GDSSampleDim(that), GBScaleMethod_Default);
            GBFree(&gb);
        } else {
            pairSample->_mask[iMask] = gb;
        }
    }
    free(path);
}

```

```

    }
    free(root);
    return pairSample;
}

// Release the memory used by the FilePathPair 'that'
void GDSFilePathPairFree(GDSFilePathPair** const that) {
    if (that == NULL || *that == NULL)
        return;
    for (int iMask = GDS_NBMAXMASK + 1; iMask--;)
        if ((*that)->_path[iMask] != NULL)
            free((*that)->_path[iMask]);
    free(*that);
    *that = NULL;
}

// Release the memory used by the GenBrushPair 'that'
void GDSGenBrushPairFree(GDSGenBrushPair** const that) {
    if (that == NULL || *that == NULL)
        return;
    GBFree(&((*that)->_img));
    for (int iMask = GDS_NBMAXMASK; iMask--;)
        GBFree(&((*that)->_mask[iMask]));
    free(*that);
    *that = NULL;
}

// Center the GDataSet 'that' on its mean
void GDSMeanCenter(GDataSetVecFloat* const that) {
    #if BUILDMODE == 0
        if (that == NULL) {
            GDataSetErr->_type = PBErrTypeNullPointer;
            sprintf(PBImgAnalysisErr->_msg, "'that' is null");
            PBErrCatch(PBImgAnalysisErr);
        }
    #endif
    // Get the mean of the dataset
    VecFloat* mean = GDSGetMean(that);
    // Translate all the data by the mean of the data set
    if (GDSGetSize(that) > 0) {
        GSetIterForward iter = GSetIterForwardCreateStatic(GDSSamples(that));
        do {
            VecFloat* sample = GSetIterGet(&iter);
            VecOp(sample, 1.0, mean, -1.0);
        } while (GSetIterStep(&iter));
    }
    // Free memory
    VecFree(&mean);
}

// Normalize the GDataSet 'that', ie normalize each of its vectors
void GDSNormalize(GDataSetVecFloat* const that) {
    #if BUILDMODE == 0
        if (that == NULL) {
            GDataSetErr->_type = PBErrTypeNullPointer;
            sprintf(PBImgAnalysisErr->_msg, "'that' is null");
            PBErrCatch(PBImgAnalysisErr);
        }
    #endif
    // Normalize all the data of the data set
    if (GDSGetSize(that) > 0) {
        GSetIterForward iter = GSetIterForwardCreateStatic(GDSSamples(that));

```

```

        do {
            VecFloat* sample = GSetIterGet(&iter);
            VecNormalise(sample);
        } while (GSetIterStep(&iter));
    }
}

// Get the mean of the GDataSet 'that'
VecFloat* GDSGetMean(const GDataSetVecFloat* const that) {
    #if BUILDMODE == 0
        if (that == NULL) {
            GDataSetErr->_type = PBErrTypeNullPointer;
            sprintf(PBImgAnalysisErr->_msg, "'that' is null");
            PBErrCatch(PBImgAnalysisErr);
        }
    #endif
    // Get the dimension of the samples
    const VecShort* dim = GDSSampleDim(that);
    // Create a vector to calculate the mean
    VecFloat* mean = VecFloatCreate(VecGet(dim, 0));
    // Calculate the mean
    if (GDSGetSize(that) > 0) {
        GSetIterForward iter =
            GSetIterForwardCreateStatic(GDSSamples(that));
        do {
            VecFloat* v = GSetIterGet(&iter);
            VecOp(mean, 1.0, v, 1.0);
        } while(GSetIterStep(&iter));
        VecScale(mean, 1.0 / (float)GDSGetSize(that));
    }
    // Return the result
    return mean;
}

// Get a clone of the GDataSet 'that'
// All the data in the GDataSet are cloned except for the splitting
// categories which are reset to one category made of the original data
GDataSetVecFloat GDSClone(const GDataSetVecFloat* const that) {
    #if BUILDMODE == 0
        if (that == NULL) {
            GDataSetErr->_type = PBErrTypeNullPointer;
            sprintf(PBImgAnalysisErr->_msg, "'that' is null");
            PBErrCatch(PBImgAnalysisErr);
        }
    #endif
    // Declare the result dataset
    GDataSetVecFloat dataset;
    // Create a pointer to the GDataSet for convenience
    GDataSet* tho = &(dataset._dataSet);
    // Clone or initialize the properties
    tho->_json = NULL;
    tho->_cfgFilePath = PBErrMalloc(GDataSetErr,
        sizeof(char) * (1 + strlen(that->_dataSet._cfgFilePath)));
    strcpy(tho->_cfgFilePath, that->_dataSet._cfgFilePath);
    tho->_name = PBErrMalloc(GDataSetErr,
        sizeof(char) * (1 + strlen(that->_dataSet._name)));
    strcpy(tho->_name, that->_dataSet._name);
    tho->_desc = PBErrMalloc(GDataSetErr,
        sizeof(char) * (1 + strlen(that->_dataSet._desc)));
    strcpy(tho->_desc, that->_dataSet._desc);
    tho->_type = that->_dataSet._type;
    tho->_nbSample = that->_dataSet._nbSample;
}

```

```

tho->_sampleDim = VecClone(that->_dataSet._sampleDim);
tho->_samples = GSetCreateStatic();
if (GDSGetSize(that) > 0) {
    GSetIterForward iter = GSetIterForwardCreateStatic(GDSSamples(that));
    do {
        VecFloat* v = GSetIterGet(&iter);
        GSetAppend(&(tho->_samples), VecClone(v));
    } while (GSetIterStep(&iter));
}
tho->_split = NULL;
tho->_categories = NULL;
tho->_iterators = NULL;
tho->_split = VecShortCreate(1);
VecSet(tho->_split, 0, tho->_nbSample);
tho->_categories = PBErrMalloc(GDataSetErr, sizeof(GSet));
tho->_categories[0] = GSetCreateStatic();
if (GDSGetSize(that) > 0) {
    GSetIterForward iter =
        GSetIterForwardCreateStatic(&(tho->_samples));
    do {
        void* sample = GSetIterGet(&iter);
        GSetAppend(tho->_categories, sample);
    } while (GSetIterStep(&iter));
}
tho->_iterators =
    PBErrMalloc(GDataSetErr, sizeof(GSetIterForward));
tho->_iterators[0] =
    GSetIterForwardCreateStatic(tho->_categories);
// Return the result dataset
return dataset;
}

// Get the covariance matrix of the GDataSetVecFloat 'that'
MatFloat* GDSGetCovarianceMatrix(const GDataSetVecFloat* const that) {
#ifdef BUILDMODE == 0
    if (that == NULL) {
        GDataSetErr->_type = PBErrTypeNullPointer;
        sprintf(PBImgAnalysisErr->_msg, "'that' is null");
        PBErrCatch(PBImgAnalysisErr);
    }
#endif
    // Get the dimension of the samples
    const VecShort* dim = GDSSampleDim(that);
    // Allocate memory for the covariance matrix;
    VecShort2D dimMat = VecShortCreateStatic2D();
    VecSet(&dimMat, 0, VecGet(dim, 0));
    VecSet(&dimMat, 1, VecGet(dim, 0));
    MatFloat* res = MatFloatCreate(&dimMat);
    // Loop on the matrix to set the covariances
    VecShort2D i = VecShortCreateStatic2D();
    do {
        // The matrix is symmetric, avoid calculating twice the same value
        if (VecGet(&i, 0) > VecGet(&i, 1)) {
            VecShort2D j = VecShortCreateStatic2D();
            VecSet(&j, 0, VecGet(&i, 1));
            VecSet(&j, 1, VecGet(&i, 0));
            MatSet(res, &i, MatGet(res, &j));
        } else {
            float covar = GDSGetCovariance(that, &i);
            MatSet(res, &i, covar);
        }
    } while(VecStep(&i, &dimMat));
}

```

```

    // Return the covariance matrix
    return res;
}

// Get the covariance of the variables at 'indices' in the
// GDataSetVecFloat 'that'
float GDSGetCovariance(const GDataSetVecFloat* const that,
    const VecShort2D* const indices) {
    #if BUILDMODE == 0
        if (that == NULL) {
            GDataSetErr->_type = PBErrTypeNullPointer;
            sprintf(PBImgAnalysisErr->_msg, "'that' is null");
            PBErrCatch(PBImgAnalysisErr);
        }
        if (indices == NULL) {
            GDataSetErr->_type = PBErrTypeNullPointer;
            sprintf(PBImgAnalysisErr->_msg, "'indices' is null");
            PBErrCatch(PBImgAnalysisErr);
        }
    #endif
    // Declare a variable to memorize the result
    float res = 0.0;
    if (GDSGetSize(that) > 0) {
        // Get the means of the dataset
        VecFloat* means = GDSGetMean(that);
        // Calculate the covariance
        GSetIterForward iter = GSetIterForwardCreateStatic(GDSSamples(that));
        do {
            VecFloat* sample = GSetIterGet(&iter);
            res += (VecGet(sample, VecGet(indices, 0)) -
                VecGet(means, VecGet(indices, 0))) *
                (VecGet(sample, VecGet(indices, 1)) -
                VecGet(means, VecGet(indices, 1)));
        } while (GSetIterStep(&iter));
        res /= (float)GDSGetSize(that);
        // Free memory
        VecFree(&means);
    }
    // Return the covariance
    return res;
}

```

## 2.2 gdataset-inline.c

```

// ===== GDATASET_INLINE.C =====

// ===== Functions implementation =====

// Get the total number of samples in the GDataSet 'that'
#if BUILDMODE != 0
inline
#endif
long _GDSGetSize(const GDataSet* const that) {
    #if BUILDMODE == 0
        if (that == NULL) {
            GDataSetErr->_type = PBErrTypeNullPointer;
            sprintf(PBImgAnalysisErr->_msg, "'that' is null");
            PBErrCatch(PBImgAnalysisErr);
        }
    #endif
}

```

```

#endif
    return that->_nbSample;
}

// Get the total number of samples in the GDataSet 'that' for the
// category 'iCat'. Return 0 if the category doesn't exists
#if BUILDMODE != 0
inline
#endif
long _GDSGetSizeCat(const GDataSet* const that, const long iCat) {
#if BUILDMODE == 0
    if (that == NULL) {
        GDataSetErr->_type = PErrTypeNullPointer;
        sprintf(PBImgAnalysisErr->_msg, "'that' is null");
        PErrCatch(PBImgAnalysisErr);
    }
    if (that->_split == NULL) {
        GDataSetErr->_type = PErrTypeNullPointer;
        sprintf(PBImgAnalysisErr->_msg, "'that->_split' is null");
        PErrCatch(PBImgAnalysisErr);
    }
    if (iCat < 0 || iCat >= GDSGetNbCat(that)) {
        GDataSetErr->_type = PErrTypeInvalidArg;
        sprintf(PBImgAnalysisErr->_msg, "'iCat' is invalid (0<=%ld<%ld)",
            iCat, GDSGetNbCat(that));
        PErrCatch(PBImgAnalysisErr);
    }
#endif
    return VecGet(that->_split, iCat);
}

// Unsplit the GDataSet 'that', i.e. after calling GDataSetUnsplit 'that'
// has only one category containing all the samples
#if BUILDMODE != 0
inline
#endif
void _GDSUnsplit(GDataSet* const that) {
#if BUILDMODE == 0
    if (that == NULL) {
        GDataSetErr->_type = PErrTypeNullPointer;
        sprintf(PBImgAnalysisErr->_msg, "'that' is null");
        PErrCatch(PBImgAnalysisErr);
    }
#endif
    // Unsplitting is equivalent to splitting in one category with all the
    // samples
    VecShort* split = VecShortCreate(1);
    VecSet(split, 0, GDSGetSize(that));
    GDSSplit(that, split);
    VecFree(&split);
}

// Shuffle the samples of the category 'iCat' of the GDataSet 'that'.
// Reset the iterator of the category
#if BUILDMODE != 0
inline
#endif
void _GDSShuffle(GDataSet* const that, const long iCat) {
#if BUILDMODE == 0
    if (that == NULL) {
        GDataSetErr->_type = PErrTypeNullPointer;
        sprintf(PBImgAnalysisErr->_msg, "'that' is null");
    }
#endif
}

```

```

        PBErCatch(PBImgAnalysisErr);
    }
    if (that->_categories == NULL) {
        GDataSetErr->_type = PBErTypeNullPointer;
        sprintf(PBImgAnalysisErr->_msg, "'that->_categories' is null");
        PBErCatch(PBImgAnalysisErr);
    }
    if (iCat < 0 || iCat >= GDSGetNbCat(that)) {
        GDataSetErr->_type = PBErTypeInvalidArg;
        sprintf(PBImgAnalysisErr->_msg, "'iCat' is invalid (0<=%ld<%ld)",
            iCat, GDSGetNbCat(that));
        PBErCatch(PBImgAnalysisErr);
    }
}
#endif
// Shuffle the GSet of the category
GSetShuffle(that->_categories + iCat);
// Reset the iterator
GDSReset(that, iCat);
}

// Shuffle the samples of all the categories of the GDataSet 'that'.
// Reset the iterator of the categories
#if BUILDMODE != 0
inline
#endif
void _GDSShuffleAll(GDataSet* const that) {
    if BUILDMODE == 0
        if (that == NULL) {
            GDataSetErr->_type = PBErTypeNullPointer;
            sprintf(PBImgAnalysisErr->_msg, "'that' is null");
            PBErCatch(PBImgAnalysisErr);
        }
    #endif
    // Loop on categories
    for (int iCat = GDSGetNbCat(that); iCat--;)
        // Shuffle the category
        GDSShuffle(that, iCat);
}

// Get the name of the GDataSet 'that'
#if BUILDMODE != 0
inline
#endif
const char* _GDSName(const GDataSet* const that) {
    if BUILDMODE == 0
        if (that == NULL) {
            GDataSetErr->_type = PBErTypeNullPointer;
            sprintf(PBImgAnalysisErr->_msg, "'that' is null");
            PBErCatch(PBImgAnalysisErr);
        }
    #endif
    return that->_name;
}

// Get the description of the GDataSet 'that'
#if BUILDMODE != 0
inline
#endif
const char* _GDSDesc(const GDataSet* const that) {
    if BUILDMODE == 0
        if (that == NULL) {
            GDataSetErr->_type = PBErTypeNullPointer;

```

```

        sprintf(PBImgAnalysisErr->_msg, "'that' is null");
        PBErCatch(PBImgAnalysisErr);
    }
#endif
    return that->_desc;
}

// Get the path of the config file of the GDataSet 'that'
#if BUILDMODE != 0
inline
#endif
const char* _GDSCfgFilePath(const GDataSet* const that) {
    #if BUILDMODE == 0
        if (that == NULL) {
            GDataSetErr->_type = PBErTypeNullPointer;
            sprintf(PBImgAnalysisErr->_msg, "'that' is null");
            PBErCatch(PBImgAnalysisErr);
        }
    #endif
    return that->_cfgFilePath;
}

// Get a copy of the path of the config file of the GDataSet 'that'
#if BUILDMODE != 0
inline
#endif
char* _GDSGetCfgFilePath(const GDataSet* const that) {
    #if BUILDMODE == 0
        if (that == NULL) {
            GDataSetErr->_type = PBErTypeNullPointer;
            sprintf(PBImgAnalysisErr->_msg, "'that' is null");
            PBErCatch(PBImgAnalysisErr);
        }
    #endif
    char* ret = malloc(strlen(that->_cfgFilePath) + 1);
    strcpy(ret, that->_cfgFilePath);
    return ret;
}

// Get the path of the folder of the config file of the GDataSet 'that'
#if BUILDMODE != 0
inline
#endif
char* _GDSGetCfgFolderPath(const GDataSet* const that) {
    #if BUILDMODE == 0
        if (that == NULL) {
            GDataSetErr->_type = PBErTypeNullPointer;
            sprintf(PBImgAnalysisErr->_msg, "'that' is null");
            PBErCatch(PBImgAnalysisErr);
        }
    #endif
    return PBFSGetRootPath(that->_cfgFilePath);
}

// Get the type of the GDataSet 'that'
#if BUILDMODE != 0
inline
#endif
GDataSetType _GDSGetType(const GDataSet* const that) {
    #if BUILDMODE == 0
        if (that == NULL) {
            GDataSetErr->_type = PBErTypeNullPointer;

```



```

        sprintf(PBImgAnalysisErr->_msg, "'that' is null");
        PBErCatch(PBImgAnalysisErr);
    }
#endif
    return that->_type;
}

// Get the number of categories of the GDataSet 'that'
#if BUILDMODE != 0
inline
#endif
long _GDSGetNbCat(const GDataSet* const that) {
    if BUILDMODE == 0
        if (that == NULL) {
            GDataSetErr->_type = PBErTypeNullPointer;
            sprintf(PBImgAnalysisErr->_msg, "'that' is null");
            PBErCatch(PBImgAnalysisErr);
        }
    #endif
    return VecGetDim(that->_split);
}

// If there is a next sample move to the next sample of the category
// 'iCat' and return true, else return false
#if BUILDMODE != 0
inline
#endif
bool _GDSStepSample(const GDataSet* const that, const long iCat) {
    if BUILDMODE == 0
        if (that == NULL) {
            GDataSetErr->_type = PBErTypeNullPointer;
            sprintf(PBImgAnalysisErr->_msg, "'that' is null");
            PBErCatch(PBImgAnalysisErr);
        }
        if (that->_iterators == NULL) {
            GDataSetErr->_type = PBErTypeNullPointer;
            sprintf(PBImgAnalysisErr->_msg, "'that->_iterators' is null");
            PBErCatch(PBImgAnalysisErr);
        }
        if (iCat < 0 || iCat >= GDSGetNbCat(that)) {
            GDataSetErr->_type = PBErTypeInvalidArg;
            sprintf(PBImgAnalysisErr->_msg, "'iCat' is invalid (0<=%ld<%ld)",
                iCat, GDSGetNbCat(that));
            PBErCatch(PBImgAnalysisErr);
        }
    #endif
    return GSetIterStep(that->_iterators + iCat);
}

// Reset the iterator on category 'iCat' of the GDataSet 'that', i.e.
// the next call to GDataSetGetNextSample will give the first sample of
// the category 'iCat'
#if BUILDMODE != 0
inline
#endif
void _GDSReset(GDataSet* const that, const long iCat) {
    if BUILDMODE == 0
        if (that == NULL) {
            GDataSetErr->_type = PBErTypeNullPointer;
            sprintf(PBImgAnalysisErr->_msg, "'that' is null");
            PBErCatch(PBImgAnalysisErr);
        }
}

```

```

    if (that->_iterators == NULL) {
        GDataSetErr->_type = PBErrTypeNullPointer;
        sprintf(PBImgAnalysisErr->_msg, "'that->_iterators' is null");
        PBErrCatch(PBImgAnalysisErr);
    }
    if (iCat < 0 || iCat >= GDSGetNbCat(that)) {
        GDataSetErr->_type = PBErrTypeInvalidArg;
        sprintf(PBImgAnalysisErr->_msg, "'iCat' is invalid (0<=%ld<%ld)",
            iCat, GDSGetNbCat(that));
        PBErrCatch(PBImgAnalysisErr);
    }
}
#endif
GSetIterReset(that->_iterators + iCat);
}

// Reset the iterator on all categories of the GDataSet 'that'
#if BUILDMODE != 0
inline
#endif
void _GDSResetAll(GDataSet* const that) {
    #if BUILDMODE == 0
        if (that == NULL) {
            GDataSetErr->_type = PBErrTypeNullPointer;
            sprintf(PBImgAnalysisErr->_msg, "'that' is null");
            PBErrCatch(PBImgAnalysisErr);
        }
    #endif
    // Loop on categories
    for (int iCat = GDSGetNbCat(that); iCat--;)
        // Shuffle the category
        GDSReset(that, iCat);
}

// Get the dimensions of the samples of GDataSet 'that'
#if BUILDMODE != 0
inline
#endif
const VecShort* _GDSSampleDim(const GDataSet* const that) {
    #if BUILDMODE == 0
        if (that == NULL) {
            GDataSetErr->_type = PBErrTypeNullPointer;
            sprintf(PBImgAnalysisErr->_msg, "'that' is null");
            PBErrCatch(PBImgAnalysisErr);
        }
    #endif
    return that->_sampleDim;
}

// Get the number of masks in the GDataSetGenBrushPair 'that'
#if BUILDMODE != 0
inline
#endif
int GDSGetNbMaskGenBrushPair(const GDataSetGenBrushPair* const that) {
    #if BUILDMODE == 0
        if (that == NULL) {
            GDataSetErr->_type = PBErrTypeNullPointer;
            sprintf(PBImgAnalysisErr->_msg, "'that' is null");
            PBErrCatch(PBImgAnalysisErr);
        }
    #endif
    return that->_nbMask;
}

```

```

// Get the samples of the GDataSet 'that'
#if BUILDMODE != 0
inline
#endif
const GSetVecFloat* _GDSVecFloatSamples(
    const GDataSetVecFloat* const that) {
#if BUILDMODE == 0
    if (that == NULL) {
        GDataSetErr->_type = PBErrTypeNullPointer;
        sprintf(PBImgAnalysisErr->_msg, "'that' is null");
        PBErrCatch(PBImgAnalysisErr);
    }
#endif
    return (GSetVecFloat*)&(that->_dataSet._samples);
}
#if BUILDMODE != 0
inline
#endif
const GSet* _GDSGenBrushPairSamples(
    const GDataSetGenBrushPair* const that) {
#if BUILDMODE == 0
    if (that == NULL) {
        GDataSetErr->_type = PBErrTypeNullPointer;
        sprintf(PBImgAnalysisErr->_msg, "'that' is null");
        PBErrCatch(PBImgAnalysisErr);
    }
#endif
    return &(that->_dataSet._samples);
}

```

### 3 Makefile

```

# Build mode
# 0: development (max safety, no optimisation)
# 1: release (min safety, optimisation)
# 2: fast and furious (no safety, optimisation)
BUILD_MODE?=1

all: pbmake_wget main

# Automatic installation of the repository PBMake in the parent folder
pbmake_wget:
if [ ! -d ../PBMake ]; then wget https://github.com/BayashiPascal/PBMake/archive/master.zip; unzip master.zip; rm -f

# Makefile definitions
MAKEFILE_INC=../PBMake/Makefile.inc
include $(MAKEFILE_INC)

# Rules to make the executable
repo=gdataset
$(repo)_EXENAME: \
$(repo)_EXENAME.o \
$(repo)_EXE_DEP \
$(repo)_DEP
$(COMPILER) 'echo "$(repo)_EXE_DEP $(repo)_EXENAME.o" | tr ' ' '\n' | sort -u' $(LINK_ARG) $(repo)_LINK_ARG

```

```

$$($(repo)_EXENAME).o: \
$$($(repo)_DIR)/$$($(repo)_EXENAME).c \
$$($(repo)_INC_H_EXE) \
$$($(repo)_EXE_DEP)
$(COMPILER) $(BUILD_ARG) $$($(repo)_BUILD_ARG) 'echo "$$(repo)_INC_DIR" | tr ' ' '\n' | sort -u' -c $$($(repo)_DIR)/

```

## 4 Dataset configuration file

### 4.1 VecFloat

testGDataSetVecFloat.json:

```

{
  "dataSet": "testGDataSet",
  "dataSetType": "0",
  "desc": "UnitTestGDataSetCreateFree",
  "dim": {
    "_dim": "1",
    "_val": ["2"]
  },
  "nbSample": "3",
  "samples": [
    {
      "_dim": "2",
      "_val": ["0.0", "1.0"]
    },
    {
      "_dim": "2",
      "_val": ["2.0", "3.0"]
    },
    {
      "_dim": "2",
      "_val": ["4.0", "5.0"]
    }
  ]
}

```

testGDataSetVecFloatCovariance.json:

```

{
  "dataSet": "testGDataSet",
  "dataSetType": "0",
  "desc": "UnitTestGDataSetVecFloatCovariance",
  "dim": {
    "_dim": "1",
    "_val": ["3"]
  },
  "nbSample": "3",
  "samples": [
    {
      "_dim": "3",
      "_val": ["1.0", "2.0", "3.0"]
    },
    {
      "_dim": "3",
      "_val": ["6.0", "5.0", "4.0"]
    },
    {

```

```

        "_dim": "3",
        "_val": ["7.0", "8.0", "9.0"]
    }
]
}

```

testGDataSetVecFloat.json:

```

{
  "dataSet": "testGDataSet",
  "dataSetType": "0",
  "desc": "UnitTestGDataSetVecFloatNormalize",
  "dim": {
    "_dim": "1",
    "_val": ["3"]
  },
  "nbSample": "3",
  "samples": [
    {
      "_dim": "3",
      "_val": ["1.0", "2.0", "3.0"]
    },
    {
      "_dim": "3",
      "_val": ["6.0", "5.0", "4.0"]
    },
    {
      "_dim": "3",
      "_val": ["7.0", "8.0", "9.0"]
    }
  ]
}

```

## 4.2 Pair of GenBrush

```

{
  "dataSet": "dataset-002-001",
  "dataSetType": "1",
  "desc": "unitTest",
  "dim": {
    "_dim": "2",
    "_val": [
      "10",
      "20"
    ]
  },
  "format": "tga",
  "nbMask": "2",
  "nbSample": "3",
  "samples": [
    {
      "bounding": [],
      "img": "img000.tga",
      "mask": [
        "mask000-000.tga",
        "mask000-001.tga"
      ]
    },
    {
      "bounding": [],

```

```

        "img": "img001.tga",
        "mask": [
            "mask001-000.tga",
            "mask001-001.tga"
        ]
    },
    {
        "bounding": [],
        "img": "img002.tga",
        "mask": [
            "mask002-000.tga",
            "mask002-001.tga"
        ]
    }
]
}
}

```

## 5 Unit tests

```

#include <stdlib.h>
#include <stdio.h>
#include <time.h>
#include <string.h>
#include <math.h>
#include "genbrush.h"
#include "gdataset.h"

void UnitTestGDataSetVecFloatCreateFreeClone() {
    srand(1);
    char* cfgFilePath = "testGDataSetVecFloat.json";
    GDataSetVecFloat gdataset = GDataSetVecFloatCreateStatic(cfgFilePath);
    if (strcmp(gdataset._dataSet._cfgFilePath, cfgFilePath) != 0) {
        GDataSetErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GDataSetErr->_msg, "GDataSetCreateStatic failed");
        PBErrCatch(GDataSetErr);
    }
    GDataSet* g = (GDataSet*)&gdataset;
    if (GSetGet(g->_categories, 0) != GSetGet(&(g->_samples), 0) ||
        GSetGet(g->_categories, 1) != GSetGet(&(g->_samples), 1) ||
        GSetGet(g->_categories, 2) != GSetGet(&(g->_samples), 2)) {
        GDataSetErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GDataSetErr->_msg, "GDataSetCreateStatic failed");
        PBErrCatch(GDataSetErr);
    }
    GDataSetVecFloat clone = GDSClone(&gdataset);
    if (strcmp(clone._dataSet._cfgFilePath, cfgFilePath) != 0) {
        GDataSetErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GDataSetErr->_msg, "GDSClone failed");
        PBErrCatch(GDataSetErr);
    }
    GDataSet* f = (GDataSet*)&clone;
    if (GSetGet(f->_categories, 0) != GSetGet(&(f->_samples), 0) ||
        GSetGet(f->_categories, 1) != GSetGet(&(f->_samples), 1) ||
        GSetGet(f->_categories, 2) != GSetGet(&(f->_samples), 2)) {
        GDataSetErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GDataSetErr->_msg, "GDSClone failed");
        PBErrCatch(GDataSetErr);
    }
}

```

```

GDataSetVecFloatFreeStatic(&clone);
GDataSetVecFloatFreeStatic(&gdataset);
printf("UnitTestGDataSetVecFloatCreateFreeClone OK\n");
}

void UnitTestGDataSetVecFloatGet() {
    srand(1);
    char* cfgFilePath = "testGDataSetVecFloat.json";
    GDataSetVecFloat gdataset = GDataSetVecFloatCreateStatic(cfgFilePath);
    if (strcmp(GDSCfgFilePath(&gdataset), cfgFilePath) != 0) {
        GDataSetErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GDataSetErr->_msg, "GDSCfgFilePath failed");
        PBErrCatch(GDataSetErr);
    }
    char* str = GDSGetCfgFilePath(&gdataset);
    if (strcmp(str, cfgFilePath) != 0) {
        GDataSetErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GDataSetErr->_msg, "GDSGetCfgFilePath failed");
        PBErrCatch(GDataSetErr);
    }
    free(str);
    str = GDSGetCfgFolderPath(&gdataset);
    if (strcmp(str, "") != 0) {
        GDataSetErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GDataSetErr->_msg, "GDSGetCfgFolderPath failed");
        PBErrCatch(GDataSetErr);
    }
    free(str);
    if (strcmp(GDSDesc(&gdataset), "UnitTestGDataSetCreateFree") != 0) {
        GDataSetErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GDataSetErr->_msg, "GDSDesc failed");
        PBErrCatch(GDataSetErr);
    }
    if (strcmp(GDSName(&gdataset), "testGDataSet") != 0) {
        GDataSetErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GDataSetErr->_msg, "GDSName failed");
        PBErrCatch(GDataSetErr);
    }
    if (GDSGetType(&gdataset) != GDataSetType_VecFloat) {
        GDataSetErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GDataSetErr->_msg, "GDSGetType failed");
        PBErrCatch(GDataSetErr);
    }
    if (GDSGetNbCat(&gdataset) != 1) {
        GDataSetErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GDataSetErr->_msg, "GDSGetNbCat failed");
        PBErrCatch(GDataSetErr);
    }
    if (GDSGetSize(&gdataset) != 3) {
        GDataSetErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GDataSetErr->_msg, "GDSGetSize failed");
        PBErrCatch(GDataSetErr);
    }
    if (GDSGetSizeCat(&gdataset, 0) != 3) {
        GDataSetErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GDataSetErr->_msg, "GDSGetSizeCat failed");
        PBErrCatch(GDataSetErr);
    }
    if ((GSet*)GDSSamples(&gdataset) != &(gdataset._dataSet._samples)) {
        GDataSetErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GDataSetErr->_msg, "GDSSamples failed");
        PBErrCatch(GDataSetErr);
    }
}

```

```

}
VecShort* dim = VecShortCreate(1);
VecSet(dim, 0, 2);
if (VecIsEqual(GDSSampleDim(&gdataset), dim) != true) {
    GDataSetErr->_type = PBErrTypeUnitTestFailed;
    sprintf(GDataSetErr->_msg, "GDSSampleDim failed");
    PBErrCatch(GDataSetErr);
}
VecFree(&dim);
VecFloat* mean = GDSGetMean(&gdataset);
VecFloat2D checkMean = VecFloatCreateStatic2D();
VecSet(&checkMean, 0, 2.0);
VecSet(&checkMean, 1, 3.0);
if (!VecIsEqual(mean, &checkMean)) {
    GDataSetErr->_type = PBErrTypeUnitTestFailed;
    sprintf(GDataSetErr->_msg, "GDSGetMean failed");
    PBErrCatch(GDataSetErr);
}
VecFree(&mean);
GDSMeanCenter(&gdataset);
VecFloat2D checkMeanCenter[3];
for (int i = 0; i < GDSGetSize(&gdataset); ++i) {
    checkMeanCenter[i] = VecFloatCreateStatic2D();
    VecSet(checkMeanCenter + i, 0, -2.0 + (float)i * 2.0);
    VecSet(checkMeanCenter + i, 1, -2.0 + (float)i * 2.0);
}
GSetIterForward iter = GSetIterForwardCreateStatic(
    GDSSamples(&gdataset));
int i = 0;
do {
    VecFloat* sample = GSetIterGet(&iter);
    if (!VecIsEqual(sample, checkMeanCenter + i)) {
        GDataSetErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GDataSetErr->_msg, "GDSMeanCenter failed");
        PBErrCatch(GDataSetErr);
    }
} while (GSetIterStep(&iter) && ++i);

GDataSetVecFloatFreeStatic(&gdataset);
printf("UnitTestGDataSetVecFloatGet OK\n");
}

void UnitTestGDataSetVecFloatSplitUnsplit() {
    srand(1);
    char* cfgFilePath = "testGDataSetVecFloat.json";
    GDataSetVecFloat gdataset = GDataSetVecFloatCreateStatic(cfgFilePath);
    VecShort* split = VecShortCreate(2);
    VecSet(split, 0, 1);
    VecSet(split, 1, 2);
    GDSSplit(&gdataset, split);
    if (GDSGetNbCat(&gdataset) != 2) {
        GDataSetErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GDataSetErr->_msg, "GDSSplit failed");
        PBErrCatch(GDataSetErr);
    }
    if (GDSGetSizeCat(&gdataset, 0) != 1 ||
        GDSGetSizeCat(&gdataset, 1) != 2) {
        GDataSetErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GDataSetErr->_msg, "GDSSplit failed");
        PBErrCatch(GDataSetErr);
    }
    GDSUnsplit(&gdataset);
}

```



```

    if (GDSGetNbCat(&gdataset) != 1) {
        GDataSetErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GDataSetErr->_msg, "GDSUnsplit failed");
        PBErrCatch(GDataSetErr);
    }
    VecFree(&split);
    GDataSetVecFloatFreeStatic(&gdataset);
    printf("UnitTestGDataSetVecFloatSplitUnsplit OK\n");
}

void UnitTestGDataSetVecFloatShuffle() {
    srand(1);
    char* cfgFilePath = "testGDataSetVecFloat.json";
    GDataSetVecFloat gdataset = GDataSetVecFloatCreateStatic(cfgFilePath);
    GDSShuffle(&gdataset, 0);
    GDataSet* g = (GDataSet*)(&gdataset);
    if (GSetGet(g->_categories, 0) != GSetGet(&(g->_samples), 1)/* ||
        GSetGet(g->_categories, 1) != GSetGet(&(g->_samples), 0) ||
        GSetGet(g->_categories, 2) != GSetGet(&(g->_samples), 1)*/) {
        GDataSetErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GDataSetErr->_msg, "GDSShuffle failed");
        PBErrCatch(GDataSetErr);
    }
    GDataSetVecFloatFreeStatic(&gdataset);
    printf("UnitTestGDataSetVecFloatShuffle OK\n");
}

void UnitTestGDataSetVecFloatStepSampleGetSample() {
    srand(1);
    char* cfgFilePath = "testGDataSetVecFloat.json";
    GDataSetVecFloat gdataset = GDataSetVecFloatCreateStatic(cfgFilePath);
    int iSample = 0;
    float check[6] = {0.0, 1.0, 2.0, 3.0, 4.0, 5.0};
    do {
        VecFloat* sample = GDSGetSample(&gdataset, 0);
        if (ISEQUALF(VecGet(sample, 0), check[iSample * 2]) == false ||
            ISEQUALF(VecGet(sample, 1), check[iSample * 2 + 1]) == false) {
            GDataSetErr->_type = PBErrTypeUnitTestFailed;
            sprintf(GDataSetErr->_msg, "GDSGetSample failed");
            PBErrCatch(GDataSetErr);
        }
        VecFree(&sample);
        ++iSample;
    } while (GDSSample(&gdataset, 0));
    GDataSetVecFloatFreeStatic(&gdataset);
    printf("UnitTestGDataSetVecFloatStepSampleGetSample OK\n");
}

void UnitTestGDataSetVecFloatCovariance() {
    srand(1);
    char* cfgFilePath = "testGDataSetVecFloatCovariance.json";
    GDataSetVecFloat gdataset = GDataSetVecFloatCreateStatic(cfgFilePath);
    MatFloat* covariance = GDSGetCovarianceMatrix(&gdataset);
    float v[9] = {
        6.888888, 6.0, 5.111111,
        6.0, 6.0, 6.0,
        5.111111, 6.0, 6.888888};
    VecShort2D i = VecShortCreateStatic2D();
    VecShort2D dim = VecShortCreateStatic2D();
    VecSet(&dim, 0, 3);
    VecSet(&dim, 1, 3);
    int j = 0;

```

```

do {
    if (!ISEQUALF(MatGet(covariance, &i), v[j])) {
        GDataSetErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GDataSetErr->_msg, "GDSGetCovarianceMatrix failed");
        PBErrCatch(GDataSetErr);
    }
    ++j;
} while (VecStep(&i, &dim));
MatFree(&covariance);
GDataSetVecFloatFreeStatic(&gdataset);
printf("UnitTestGDataSetVecFloatCovariance OK\n");
}

void UnitTestGDataSetVecFloatNormalize() {
    srand(1);
    char* cfgFilePath = "testGDataSetVecFloatNormalize.json";
    GDataSetVecFloat gdataset = GDataSetVecFloatCreateStatic(cfgFilePath);
    GDSNormalize(&gdataset);
    GSetIterForward iter =
        GSetIterForwardCreateStatic(GDSSamples(&gdataset));
    float check[9] = {
        0.267261, 0.534522, 0.801784,
        0.683763, 0.569803, 0.455842,
        0.502571, 0.574367, 0.646162
    };
    int i = 0;
    do {
        VecFloat* v = GSetIterGet(&iter);
        if (!ISEQUALF(VecGet(v, 0), check[i * 3]) ||
            !ISEQUALF(VecGet(v, 1), check[i * 3 + 1]) ||
            !ISEQUALF(VecGet(v, 2), check[i * 3 + 2])) {
            GDataSetErr->_type = PBErrTypeUnitTestFailed;
            sprintf(GDataSetErr->_msg, "GDSNormalize failed");
            PBErrCatch(GDataSetErr);
        }
        ++i;
    } while(GSetIterStep(&iter));
    GDataSetVecFloatFreeStatic(&gdataset);
    printf("UnitTestGDataSetVecFloatNormalize OK\n");
}

void UnitTestGDataSetVecFloat() {
    UnitTestGDataSetVecFloatCreateFreeClone();
    UnitTestGDataSetVecFloatGet();
    UnitTestGDataSetVecFloatSplitUnsplit();
    UnitTestGDataSetVecFloatShuffle();
    UnitTestGDataSetVecFloatStepSampleGetSample();
    UnitTestGDataSetVecFloatCovariance();
    UnitTestGDataSetVecFloatNormalize();
}

void UnitTestGDataSetGenBrushPair() {
    srand(1);
    char* cfgFilePath = "testGDataSetGenBrushPair.json";
    GDataSetGenBrushPair gdataset =
        GDataSetGenBrushPairCreateStatic(cfgFilePath);
    if (GDSGetNbMask(&gdataset) != 2) {
        GDataSetErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GDataSetErr->_msg, "GDSGetSample<GenBrushPair> failed");
        PBErrCatch(GDataSetErr);
    }
    int iCat = 0;

```

```

do {
    GDSSGenBrushPair* sample = GDSGetSample(&gdataset, iCat);
    if (VecIsEqual(GBDim(sample->_img),
        GDSSampleDim(&gdataset)) == false ||
        VecIsEqual(GBDim(sample->_mask[0]),
            GDSSampleDim(&gdataset)) == false ||
        VecIsEqual(GBDim(sample->_mask[1]),
            GDSSampleDim(&gdataset)) == false) {
        GDataSetErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GDataSetErr->_msg, "GDSGetSample<GenBrushPair> failed");
        PBErrCatch(GDataSetErr);
    }
    GDSSGenBrushPairFree(&sample);
} while (GDSSStepSample(&gdataset, iCat));
GDataSetGenBrushPairFreeStatic(&gdataset);
printf("UnitTestGDataSetGenBrushPair OK\n");
}

void UnitTestSDSIA() {
    srandom(1);
    char* cfgFilePath = "../SDSIA/UnitTestOut/002/001/dataset.json";
    GDataSetGenBrushPair gdataset =
        GDataSetGenBrushPairCreateStatic(cfgFilePath);
    int iCat = 0;
    do {
        GDSSGenBrushPair* sample = GDSGetSample(&gdataset, iCat);
        if (VecIsEqual(GBDim(sample->_img),
            GDSSampleDim(&gdataset)) == false ||
            VecIsEqual(GBDim(sample->_mask[0]),
                GDSSampleDim(&gdataset)) == false ||
            VecIsEqual(GBDim(sample->_mask[1]),
                GDSSampleDim(&gdataset)) == false) {
            GDataSetErr->_type = PBErrTypeUnitTestFailed;
            sprintf(GDataSetErr->_msg, "GDSGetSample<GenBrushPair> failed");
            PBErrCatch(GDataSetErr);
        }
        GDSSGenBrushPairFree(&sample);
    } while (GDSSStepSample(&gdataset, iCat));
    GDataSetGenBrushPairFreeStatic(&gdataset);
    printf("UnitTestSDSIA OK\n");
}

void UnitTestAll() {
    UnitTestGDataSetVecFloat();
    UnitTestGDataSetGenBrushPair();
    UnitTestSDSIA();
}

int main(void) {
    UnitTestAll();
    return 0;
}

```

## 6 Unit test output

```

UnitTestGDataSetVecFloatCreateFreeClone OK
UnitTestGDataSetVecFloatGet OK
UnitTestGDataSetVecFloatSplitUnsplit OK

```

UnitTestGDataSetVecFloatShuffle OK  
UnitTestGDataSetVecFloatStepSampleGetSample OK  
UnitTestGDataSetVecFloatCovariance OK  
UnitTestGDataSetVecFloatNormalize OK  
UnitTestGDataSetGenBrushPair OK  
UnitTestSDSIA OK