

# Grad

P. Baillehache

May 20, 2018

## Contents

<b>1</b>	<b>Definitions</b>	<b>2</b>
<b>2</b>	<b>Interface</b>	<b>2</b>
<b>3</b>	<b>Code</b>	<b>2</b>
3.1	grad.c . . . . .	2
3.2	grad-inline.c . . . . .	21
<b>4</b>	<b>Makefile</b>	<b>30</b>
<b>5</b>	<b>Unit tests</b>	<b>31</b>
<b>6</b>	<b>Unit tests output</b>	<b>44</b>

## Introduction

Grad is a C library providing structures and functions to manipulate square and hexagonal 2D grids.

The Grad represents internally the grid as a graph where the links between a cell and its neighbour can be deleted or recreated to define connection between cells of the grid. Links are automatically generated according to the type of Grad. Cells can also be marked as blocked to temporarily be ignored by the two main functions of the Grad: flooding and search for the shortest path between two cells.

The flooding can be done from several sources simultaneously, and be constrained by the number of steps and/or the distance from the source.

The flooding occurs in order consistent with the distance between cells. The distance is set up by default and can be modified by the user.

The search path is done using the A\* algorithm with a look up table for the evaluation of distance. The Grad provides an automatically generated look up table, but the user can also use its own. The automatically generated look up table ensures the fastest and optimal search if there was no modification (link edited, cell blocked) to the Grad between the table generation and the search.

Hexagonal Grad supports the 4 types of possible alignements (line/column, even/odd).

Content of the cells of the Grad can be extended via a void pointer toward a user defined structure.

It uses the PBErr, PBMath and GSet library.

## 1 Definitions

## 2 Interface

## 3 Code

### 3.1 grad.c

```
// ===== GRAD.C =====

// ===== Include =====

#include "grad.h"
#ifdef BUILDMODE == 0
#include "grad-inline.c"
#endif

// ----- GradCell

// ===== Functions declaration =====

// ===== Functions implementation =====

// Create a new GradCell with index 'id', position 'pos' and
// 'nbLink' links
GradCell* GradCellCreate(const int id, const int nbLink,
    const VecShort2D* const pos) {
```

```

#if BUILDMODE == 0
    if (id < 0) {
        GradErr->_type = PBErrTypeInvalidArg;
        sprintf(GradErr->_msg, "'id' is invalid (%d>=0)", id);
        PBErrCatch(GradErr);
    }
    if (nbLink < 0 || nbLink > GRAD_NBMAXLINK) {
        GradErr->_type = PBErrTypeInvalidArg;
        sprintf(GradErr->_msg, "'nbLink' is invalid (0<=%d<=%d)",
            nbLink, GRAD_NBMAXLINK);
        PBErrCatch(GradErr);
    }
    if (pos == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'pos' is null");
        PBErrCatch(GradErr);
    }
    if (VecGet(pos, 0) < 0 || VecGet(pos, 1) < 0) {
        GradErr->_type = PBErrTypeInvalidArg;
        sprintf(GradErr->_msg, "'pos' is invalid ((0,0)<=(%d,%d))",
            VecGet(pos, 0), VecGet(pos, 1));
        PBErrCatch(GradErr);
    }
#endif
    // Allocate memory
    GradCell* that = PBErrMalloc(GradErr, sizeof(GradCell));
    // Set properties
    *that = GradCellCreateStatic(id, nbLink, pos);
    // Return the new GradCell
    return that;
}

// Free the memory used by the GradCell 'that'
void GradCellFree(GradCell** that) {
    // Check argument
    if (that == NULL || *that == NULL)
        // Nothing to do
        return;
    // Free memory
    free(*that);
    *that = NULL;
}

// Create a new static GradCell with index 'id', position 'pos'
// and 'nbLink' links
GradCell GradCellCreateStatic(const int id, const int nbLink,
    const VecShort2D* const pos) {
#if BUILDMODE == 0
    if (id < 0) {
        GradErr->_type = PBErrTypeInvalidArg;
        sprintf(GradErr->_msg, "'id' is invalid (%d>=0)", id);
        PBErrCatch(GradErr);
    }
    if (nbLink < 0 || nbLink > GRAD_NBMAXLINK) {
        GradErr->_type = PBErrTypeInvalidArg;
        sprintf(GradErr->_msg, "'nbLink' is invalid (0<=%d<=%d)",
            nbLink, GRAD_NBMAXLINK);
        PBErrCatch(GradErr);
    }
    if (pos == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'pos' is null");
    }
#endif
}

```

```

        PBErCatch(GradErr);
    }
    if (VecGet(pos, 0) < 0 || VecGet(pos, 1) < 0) {
        GradErr->_type = PBErTypeInvalidArg;
        sprintf(GradErr->_msg, "'pos' is invalid ((0,0)<=(%d,%d))",
            VecGet(pos, 0), VecGet(pos, 1));
        PBErCatch(GradErr);
    }
#endif
    // Declare the new GradCell
    GradCell that;
    // Set properties
    that._id = id;
    that._data = NULL;
    that._pos = *pos;
    for (int iLink = GRAD_NBMAXLINK; iLink--;) {
        that._links[iLink] = -1;
        that._linksVal[iLink] = 1.0;
    }
    that._nbLink = nbLink;
    that._flood = -1;
    that._flagBlocked = false;
    // Return the new GradCell
    return that;
}

// ----- Grad

int GradDeltaSquare[16] =
    {0,-1, 1,0, 0,1, -1,0, -1,-1, 1,-1, 1,1, -1,1};
int GradDeltaAEvenQ[12] = {0,-1, 1,-1, 1,0, 0,1, -1,0, -1,-1};
int GradDeltaBEvenQ[12] = {0,-1, 1,0, 1,1, 0,1, -1,1, -1,0};
int GradDeltaAEvenR[12] = {-1,-1, 0,-1, 1,0, 0,1, -1,1, -1,0};
int GradDeltaBEvenR[12] = {0,-1, 1,-1, 1,0, 1,1, 0,1, -1,0};
int GradDeltaAOddQ[12] = {0,-1, 1,0, 1,1, 0,1, -1,1, -1,0};
int GradDeltaBOddQ[12] = {0,-1, 1,-1, 1,0, 0,1, -1,0, -1,-1};
int GradDeltaAOddR[12] = {0,-1, 1,-1, 1,0, 1,1, 0,1, -1,0};
int GradDeltaBOddR[12] = {-1,-1, 0,-1, 1,0, 0,1, -1,1, -1,0};

// ===== Functions declaration =====

// Create a new static Grad with dimensions 'dim' and type 'type' with
// cells of 'nbLink' sides
Grad GradCreateStatic(const VecShort2D* const dim, const GradType type,
    const int nbLink);

// Free memory used by the properties of the Grad 'that'
void GradFreeStatic(Grad* const that);

// Create a new GradHexa with dimensions 'dim' and type 'type'
GradHexa* GradHexaCreate(const VecShort2D* const dim,
    const GradHexaType type);

// Get the appropriate deltas of positions according to the type of the
// Grad 'that' and the position 'pos'
int* _GradGetDelta(const Grad* const that, const VecShort2D* const pos);

// ===== Polymorphism =====

#define GradGetDelta(Grad_, Pos) _Generic(Grad_, \
    Grad*: _GradGetDelta, \
    GradSquare*: _GradGetDelta, \

```

```

    GradHexa*: _GradGetDelta, \
    default: PBErrInvalidPolymorphism)((Grad*)(Grad_), Pos)

// ===== Functions implementation =====

// Create a new static Grad with dimensions 'dim' and type 'type' with
// cells of 'nbLink' sides
Grad GradCreateStatic(const VecShort2D* const dim, const GradType type,
    const int nbLink) {
#ifdef BUILDMODE == 0
    if (dim == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'dim' is null");
        PBErrCatch(GradErr);
    }
    if (VecGet(dim, 0) <= 0 || VecGet(dim, 1) <= 0) {
        GradErr->_type = PBErrTypeInvalidArg;
        sprintf(GradErr->_msg, "'dim' is invalid ((0,0)<(%d,%d))",
            VecGet(dim, 0), VecGet(dim, 1));
        PBErrCatch(GradErr);
    }
    if (nbLink < 0) {
        GradErr->_type = PBErrTypeInvalidArg;
        sprintf(GradErr->_msg, "'nbLink' is invalid (0<=%d)", nbLink);
        PBErrCatch(GradErr);
    }
#endif
    // Declare the new Grad
    Grad that;
    // Set properties
    that._type = type;
    that._dim = *dim;
    int area = GradGetArea(&that);
    that._cells = PBErrMalloc(GradErr, sizeof(GradCell) * area);
    VecShort2D pos = VecShortCreateStatic2D();
    int iCell = 0;
    // Loop on cells
    do {
        // Initialise the cell
        that._cells[iCell] = GradCellCreateStatic(iCell, nbLink, &pos);
        ++iCell;
    } while (VecPStep(&pos, dim));
    // Return the new Grad
    return that;
}

// Free memory used by the properties of the Grad 'that'
void GradFreeStatic(Grad* const that) {
    // Check arguments
    if (that == NULL)
        // Nothing to do
        return;
    // Free memory
    free(that->_cells);
}

// Get the appropriate deltas of positions according to the type of the
// Grad 'that' and the position 'pos'
int* _GradGetDelta(const Grad* const that, const VecShort2D* const pos) {
#ifdef BUILDMODE == 0
    if (that == NULL) {
        GradErr->_type = PBErrTypeNullPointer;

```

```

    sprintf(GradErr->_msg, "'that' is null");
    PBErCatch(GradErr);
}
if (pos == NULL) {
    GradErr->_type = PBErTypeNullPointer;
    sprintf(GradErr->_msg, "'pos' is null");
    PBErCatch(GradErr);
}
#endif
if (GradGetType(that) == GradTypeSquare) {
    return GradDeltaSquare;
} else if (GradGetType(that) == GradTypeHexa) {
    if (GradHexaGetType((GradHexa*)that) == GradHexaTypeEvenQ) {
        if ((VecGet(pos, 0) % 2) != 0)
            return GradDeltaAEvenQ;
        else
            return GradDeltaBEvenQ;
    } else if (GradHexaGetType((GradHexa*)that) == GradHexaTypeEvenR) {
        if ((VecGet(pos, 1) % 2) != 0)
            return GradDeltaAEvenR;
        else
            return GradDeltaBEvenR;
    } else if (GradHexaGetType((GradHexa*)that) == GradHexaTypeOddQ) {
        if ((VecGet(pos, 0) % 2) != 0)
            return GradDeltaAOddQ;
        else
            return GradDeltaBOddQ;
    } else if (GradHexaGetType((GradHexa*)that) == GradHexaTypeOddR) {
        if ((VecGet(pos, 1) % 2) != 0)
            return GradDeltaAOddR;
        else
            return GradDeltaBOddR;
    }
}
return NULL;
}

// Create a new GradSquare of dimensions 'dim' and diagonal links
// allowed if 'diagLink' equals true
GradSquare* GradSquareCreate(const VecShort2D* const dim,
    const bool diagLink) {
    #if BUILDMODE == 0
        if (dim == NULL) {
            GradErr->_type = PBErTypeNullPointer;
            sprintf(GradErr->_msg, "'dim' is null");
            PBErCatch(GradErr);
        }
        if (VecGet(dim, 0) <= 0 || VecGet(dim, 1) <= 0) {
            GradErr->_type = PBErTypeInvalidArg;
            sprintf(GradErr->_msg, "'dim' is invalid ((0,0)<(%d,%d))",
                VecGet(dim, 0), VecGet(dim, 1));
            PBErCatch(GradErr);
        }
    #endif
    // Allocate memory
    GradSquare *that = PBErMalloc(GradErr, sizeof(GradSquare));
    // Set properties
    int nbLink = (diagLink ? 8 : 4);
    that->_grad = GradCreateStatic(dim, GradTypeSquare, nbLink);
    that->_diagLink = diagLink;
    // Loop on cells to initialise the links
    VecShort2D pos = VecShortCreateStatic2D();

```

```

int* delta = GradGetDelta(that, &pos);
VecShort2D p = VecShortCreateStatic2D();
do {
    // Initialise the links of the cell
    for (int iLink = nbLink; iLink--;) {
        VecSet(&p, 0, VecGet(&pos, 0) + delta[iLink * 2]);
        VecSet(&p, 1, VecGet(&pos, 1) + delta[iLink * 2 + 1]);
        if (GradIsPosInside(that, &p))
            GradCellSetLink(GradCellAt(that, &pos), iLink,
                GradCellGetId(GradCellAt(that, &p)));
        if (iLink >= 4)
            GradCellSetLinkVal(GradCellAt(that, &pos), iLink,
                PBMATH_SQRTTWO);
    }
} while (VecStep(&pos, dim));
// Return the new Grad
return that;
}

// Free the memory used by the GradSquare 'that'
void GradSquareFree(GradSquare** that) {
    // Check argument
    if (that == NULL || *that == NULL)
        // Nothing to do
        return;
    // Free memory
    GradFreeStatic(&((*that)->_grad));
    free(*that);
    *that = NULL;
}

// Create a new GradHexa with dimensions 'dim' and type 'type'
GradHexa* GradHexaCreate(const VecShort2D* const dim,
    const GradHexaType type) {
#ifdef BUILDMODE == 0
    if (dim == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'dim' is null");
        PBErrCatch(GradErr);
    }
    if (VecGet(dim, 0) <= 0 || VecGet(dim, 1) <= 0) {
        GradErr->_type = PBErrTypeInvalidArg;
        sprintf(GradErr->_msg, "'dim' is invalid ((0,0)<(%d,%d))",
            VecGet(dim, 0), VecGet(dim, 1));
        PBErrCatch(GradErr);
    }
#endif
    // Allocate memory
    GradHexa* that = PBErrMalloc(GradErr, sizeof(GradHexa));
    // Set properties
    that->_grad = GradCreateStatic(dim, GradTypeHexa, 6);
    that->_type = type;
    // Return the new Grad
    return that;
}

// Create a new GradHexa of dimensions 'dim' and orientation odd-r
GradHexa* GradHexaCreateOddR(const VecShort2D* const dim) {
#ifdef BUILDMODE == 0
    if (dim == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'dim' is null");
    }

```

```

    PBErCatch(GradErr);
}
if (VecGet(dim, 0) <= 0 || VecGet(dim, 1) <= 0) {
    GradErr->_type = PBErTypeInvalidArg;
    sprintf(GradErr->_msg, "'dim' is invalid ((0,0)<(%d,%d))",
        VecGet(dim, 0), VecGet(dim, 1));
    PBErCatch(GradErr);
}
#endif
// Create the GradHexa
GradHexa* that = GradHexaCreate(dim, GradHexaTypeOddR);
// Loop on cells to initialise the links
VecShort2D pos = VecShortCreateStatic2D();
VecShort2D p = VecShortCreateStatic2D();
int* delta = NULL;
do {
    // Initialise the links of the cell
    delta = GradGetDelta(that, &pos);
    for (int iLink = 6; iLink--;) {
        VecSet(&p, 0, VecGet(&pos, 0) + delta[iLink * 2]);
        VecSet(&p, 1, VecGet(&pos, 1) + delta[iLink * 2 + 1]);
        if (GradIsPosInside(that, &p))
            GradCellSetLink(GradCellAt(that, &pos), iLink,
                GradCellGetId(GradCellAt(that, &p)));
    }
} while (VecStep(&pos, dim));
// Return the new Grad
return that;
}

// Create a new GradHexa of dimensions 'dim' and orientation even-r
GradHexa* GradHexaCreateEvenR(const VecShort2D* const dim) {
#ifdef BUILDMODE == 0
    if (dim == NULL) {
        GradErr->_type = PBErTypeNullPointer;
        sprintf(GradErr->_msg, "'dim' is null");
        PBErCatch(GradErr);
    }
    if (VecGet(dim, 0) <= 0 || VecGet(dim, 1) <= 0) {
        GradErr->_type = PBErTypeInvalidArg;
        sprintf(GradErr->_msg, "'dim' is invalid ((0,0)<(%d,%d))",
            VecGet(dim, 0), VecGet(dim, 1));
        PBErCatch(GradErr);
    }
}
#endif
// Create the GradHexa
GradHexa* that = GradHexaCreate(dim, GradHexaTypeEvenR);
// Loop on cells to initialise the links
VecShort2D pos = VecShortCreateStatic2D();
VecShort2D p = VecShortCreateStatic2D();
int* delta = NULL;
do {
    // Initialise the links of the cell
    delta = GradGetDelta(that, &pos);
    for (int iLink = 6; iLink--;) {
        VecSet(&p, 0, VecGet(&pos, 0) + delta[iLink * 2]);
        VecSet(&p, 1, VecGet(&pos, 1) + delta[iLink * 2 + 1]);
        if (GradIsPosInside(that, &p))
            GradCellSetLink(GradCellAt(that, &pos), iLink,
                GradCellGetId(GradCellAt(that, &p)));
    }
} while (VecStep(&pos, dim));

```



```

    // Return the new Grad
    return that;
}

// Create a new GradHexa of dimensions 'dim' and orientation odd-q
GradHexa* GradHexaCreateOddQ(const VecShort2D* const dim) {
#ifdef BUILDMODE == 0
    if (dim == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'dim' is null");
        PBErrCatch(GradErr);
    }
    if (VecGet(dim, 0) <= 0 || VecGet(dim, 1) <= 0) {
        GradErr->_type = PBErrTypeInvalidArg;
        sprintf(GradErr->_msg, "'dim' is invalid ((0,0)<(%d,%d))",
            VecGet(dim, 0), VecGet(dim, 1));
        PBErrCatch(GradErr);
    }
#endif
    // Create the GradHexa
    GradHexa* that = GradHexaCreate(dim, GradHexaTypeOddQ);
    // Loop on cells to initialise the links
    VecShort2D pos = VecShortCreateStatic2D();
    VecShort2D p = VecShortCreateStatic2D();
    int* delta = NULL;
    do {
        // Initialise the links of the cell
        delta = GradGetDelta(that, &pos);
        for (int iLink = 6; iLink--;) {
            VecSet(&p, 0, VecGet(&pos, 0) + delta[iLink * 2]);
            VecSet(&p, 1, VecGet(&pos, 1) + delta[iLink * 2 + 1]);
            if (GradIsPosInside(that, &p))
                GradCellSetLink(GradCellAt(that, &pos), iLink,
                    GradCellGetId(GradCellAt(that, &p)));
        }
    } while (VecStep(&pos, dim));
    // Return the new Grad
    return that;
}

// Create a new GradHexa of dimensions 'dim' and orientation even-q
GradHexa* GradHexaCreateEvenQ(const VecShort2D* const dim) {
#ifdef BUILDMODE == 0
    if (dim == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'dim' is null");
        PBErrCatch(GradErr);
    }
    if (VecGet(dim, 0) <= 0 || VecGet(dim, 1) <= 0) {
        GradErr->_type = PBErrTypeInvalidArg;
        sprintf(GradErr->_msg, "'dim' is invalid ((0,0)<(%d,%d))",
            VecGet(dim, 0), VecGet(dim, 1));
        PBErrCatch(GradErr);
    }
#endif
    // Create the GradHexa
    GradHexa* that = GradHexaCreate(dim, GradHexaTypeEvenQ);
    // Loop on cells to initialise the links
    VecShort2D pos = VecShortCreateStatic2D();
    VecShort2D p = VecShortCreateStatic2D();
    int* delta = NULL;
    do {

```

```

    // Initialise the links of the cell
    delta = GradGetDelta(that, &pos);
    for (int iLink = 6; iLink--;) {
        VecSet(&p, 0, VecGet(&pos, 0) + delta[iLink * 2]);
        VecSet(&p, 1, VecGet(&pos, 1) + delta[iLink * 2 + 1]);
        if (GradIsPosInside(that, &p))
            GradCellSetLink(GradCellAt(that, &pos), iLink,
                GradCellGetId(GradCellAt(that, &p)));
    }
} while (VecStep(&pos, dim));
// Return the new Grad
return that;
}

// Free the memory used by the GradHexa 'that'
void GradHexaFree(GradHexa** that) {
    // Check argument
    if (that == NULL || *that == NULL)
        // Nothing to do
        return;
    // Free memory
    GradFreeStatic(&((*that)->_grad));
    free(*that);
    *that = NULL;
}

// Get the GradCell at position 'pos' int the GradHexa 'that'
GradCell* _GradHexaCellAtPos(GradHexa* const that, VecShort2D* pos) {
#ifdef BUILDMODE == 0
    if (that == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'that' is null");
        PBErrCatch(GradErr);
    }
    if (pos == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'pos' is null");
        PBErrCatch(GradErr);
    }
    if (VecGet(pos, 0) < 0 || VecGet(pos, 1) < 0 ||
        VecGet(pos, 0) >= VecGet(GradDim(that), 0) ||
        VecGet(pos, 1) >= VecGet(GradDim(that), 1)) {
        GradErr->_type = PBErrTypeInvalidArg;
        sprintf(GradErr->_msg, "'pos' is invalid ((0,0)<=(%d,%d)<(%d,%d))",
            VecGet(pos, 0), VecGet(pos, 1),
            VecGet(GradDim(that), 0), VecGet(GradDim(that), 1));
        PBErrCatch(GradErr);
    }
}
#endif
(void)that; (void)pos;
// Return the result
return NULL;
}

// Get the look up table for distance between each pair of cell of the
// Grad 'that'
// Return a MatFloat where first index is the 'from' cell's index
// and second index is the 'to' cell index
// Distances in the matrix are equal to the sum of the value of links
// between cells
// Negative distance means there is no path for the pair of cell
MatFloat* _GradGetLookupTableMinDist(const Grad* const that) {

```

```

#if BUILDMODE == 0
    if (that == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'that' is null");
        PBErrCatch(GradErr);
    }
#endif
    // Get the area of the grad
    int area = GradGetArea(that);
    // Create the result matrix
    VecShort2D dim = VecShortCreateStatic2D();
    VecSet(&dim, 0, area); VecSet(&dim, 1, area);
    MatFloat* table = MatFloatCreate(&dim);
    // Initialise the table
    for (int iCell = area * area; iCell--;)
        table->_val[iCell] = -1.0;
    VecShort2D pair = VecShortCreateStatic2D();
    for (int iCell = area; iCell--;) {
        VecSet(&pair, 0, iCell);
        GradCell* cellFrom = GradCellAt(that, iCell);
        if (!GradCellIsBlocked(cellFrom)) {
            for (int iLink = GradCellGetNbLink(cellFrom); iLink--;) {
                int link = GradCellGetLink(cellFrom, iLink);
                if (link != -1 &&
                    !GradCellIsBlocked(GradCellAt(that, link))) {
                    VecSet(&pair, 1, GradCellGetLink(cellFrom, iLink));
                    MatSet(table, &pair, GradCellLinkVal(cellFrom, iLink));
                }
            }
        }
    }
    // Loop until there is no more modification or we reach area steps
    int nbStep = 0;
    bool flagModif;
    VecShort2D pairA = VecShortCreateStatic2D();
    VecShort2D pairB = VecShortCreateStatic2D();
    do {
        // Reset the flag for modification
        flagModif = false;
        // For each pair of cell
        VecSetNull(&pair);
        do {
            // If it's not a pair on the diagonal
            if (VecGet(&pair, 0) != VecGet(&pair, 1)) {
                // Search the minimum dist for this pair via another cell
                float min = -1.0;
                VecSet(&pairA, 0, VecGet(&pair, 0));
                VecSet(&pairB, 1, VecGet(&pair, 1));
                for (int k = area; k--;) {
                    // If the other cell is different than the one in the
                    // current pair
                    if (k != VecGet(&pair, 0) && k != VecGet(&pair, 1)) {
                        VecSet(&pairA, 1, k);
                        VecSet(&pairB, 0, k);
                        // If the path through this other cell exists
                        if (MatGet(table, &pairA) >= 0.0 &&
                            MatGet(table, &pairB) >= 0.0) {
                            float d = MatGet(table, &pairA) + MatGet(table, &pairB);
                            if (min < 0.0 || min > d)
                                min = d;
                        }
                    }
                }
            }
        } while (flagModif || nbStep < area);
        nbStep++;
    } while (flagModif || nbStep < area);
}

```

```

    }
    // If there was a path via another cell and this path is
    // shorter than the current one or there is no current one
    if (min >= 0.0 &&
        (MatGet(table, &pair) < 0.0 || MatGet(table, &pair) > min)) {
        // Update the min distance
        MatSet(table, &pair, min);
    }
}
} while(VecStep(&pair, &dim));
// Increment the number of steps
++nbStep;
} while (nbStep < area && flagModif);
// Return the result
return table;
}

// Get the path from cell at index 'from' to cell at index 'to' in
// the Grad 'that' using the A* algorithm and the look up table 'lookup'
// for distance estimation between cells
// Return a VecShort of position (index) ordered from 'from' to 'to'
// Return NULL if there is no path
VecShort* _GradGetPath(const Grad* const that, const int from,
    const int to, const MatFloat* const lookup) {
#ifdef BUILDMODE == 0
    if (that == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'that' is null");
        PBErrCatch(GradErr);
    }
    if (lookup == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'lookup' is null");
        PBErrCatch(GradErr);
    }
}
#endif
    // Declare a vector to consult the lookup table
    VecShort2D iLookUp = VecShortCreateStatic2D();
    // Get the estimated distance of the path
    VecSet(&iLookUp, 0, from); VecSet(&iLookUp, 1, to);
    float dist = MatGet(lookup, &iLookUp);
    // Get the starting cell
    GradCell* cell = GradCellAt(that, from);
    // Declare a GSet of GradCell for computation
    GSet openList = GSetCreateStatic();
    // Declare a GSet to memorize the path
    GSet path = GSetCreateStatic();
    // Init the GSet with the starting cell
    GSetPush(&openList, cell);
    // Get the area of the grad
    int area = GradGetArea(that);
    // Declare arrays for computation
    float* f = PBErrMalloc(GradErr, sizeof(float) * area);
    float* g = PBErrMalloc(GradErr, sizeof(float) * area);
    float* h = PBErrMalloc(GradErr, sizeof(float) * area);
    bool* flagOpen = PBErrMalloc(GradErr, sizeof(bool) * area);
    bool* flagClose = PBErrMalloc(GradErr, sizeof(bool) * area);
    int* prev = PBErrMalloc(GradErr, sizeof(int) * area);
    // Init the arrays
    for (int i = area; i--;) {
        f[i] = dist;
        g[i] = 0.0;
    }

```

```

    h[i] = dist;
    flagOpen[i] = false;
    flagClose[i] = false;
    prev[i] = -1;
}
flagOpen[from] = true;
// Loop until we have elements in the openList
while (GSetNbElem(&openList) > 0) {
    cell = GSetPop(&openList);
    int iCell = GradCellGetId(cell);
    if (iCell == to) {
        while (iCell != -1) {
            GSetPush(&path, cell);
            iCell = prev[GradCellGetId(cell)];
            if (iCell != -1)
                cell = GradCellAt(that, iCell);
        }
        GSetFlush(&openList);
    } else {
        flagClose[iCell] = true;
        float curDist = g[iCell];
        for (int iDir = GradCellGetNbLink(cell); iDir--;) {
            int ncell = GradCellGetLink(cell, iDir);
            if (ncell != -1) {
                if (flagClose[ncell] == false) {
                    GradCell* nextCell = GradCellAt(that, ncell);
                    if (flagOpen[ncell] == false) {
                        if (!GradCellIsBlocked(nextCell)) {
                            VecSet(&iLookUp, 0, iCell);
                            VecSet(&iLookUp, 1, ncell);
                            g[ncell] = curDist + MatGet(lookup, &iLookUp);
                            VecSet(&iLookUp, 0, ncell);
                            VecSet(&iLookUp, 1, to);
                            dist = MatGet(lookup, &iLookUp);
                            h[ncell] = dist;
                            f[ncell] = dist + g[ncell];
                            GSetAddSort(&openList, nextCell, f[ncell]);
                            flagOpen[ncell] = true;
                            prev[ncell] = iCell;
                        }
                    } else {
                        VecSet(&iLookUp, 0, iCell);
                        VecSet(&iLookUp, 1, ncell);
                        float ng = curDist + MatGet(lookup, &iLookUp);
                        if (ng < g[ncell]) {
                            GSetRemoveAll(&openList, nextCell);
                            g[ncell] = ng;
                            f[ncell] = g[ncell] + h[ncell];
                            prev[ncell] = iCell;
                            GSetAddSort(&openList, nextCell, f[ncell]);
                        }
                    }
                }
            }
        }
    }
}
}
// Free memory
free(f);
free(g);
free(h);
free(flagOpen);

```

```

    free(flagClose);
    free(prev);
    GSetFlush(&openList);
    // Return the result
    if (GSetNbElem(&path) == 0) {
        return NULL;
    } else {
        VecShort* res = VecShortCreate(GSetNbElem(&path));
        int i = 0;
        while(GSetNbElem(&path) > 0) {
            cell = GSetPop(&path);
            VecSet(res, i, GradCellGetId(cell));
            ++i;
        }
        return res;
    }
}

// Structure used for flooding
typedef struct GradFloodPod {
    GradCell* _cell;
    int _src;
    int _nbStep;
} GradFloodPod;

// Flood the Grad 'that' from positions (index) 'sources' up to a
// maximum distance in link's value from the source 'distMax' or
// maximum distance in nb of cell from the source 'stepMax'
// If 'distMax' and/or 'stepMax' are/is negative(s) their is no limit
// on the maximum distance/maximum number of steps
// The flood occurs in order consistent with the links' value
// interpreted as distance
// The result is stored in the _flood property of the GradCell
// _flood == -1: not flooded, _flood >= 0: flooded by the _flood-th
// source
// Conflicting cells (several sources arriving at the same step to the
// cell) are left undecided (_flood==-1)
void _GradFlood(Grad* const that, const VecShort* const sources,
    const float distMax, const int stepMax) {
#ifdef BUILDMODE == 0
    if (that == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'that' is null");
        PBErrCatch(GradErr);
    }
    if (sources == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'sources' is null");
        PBErrCatch(GradErr);
    }
#endif
    // Reset all the flood value to -1
    for (int iCell = GradGetArea(that); iCell--;)
        GradCellSetFlood(GradCellAt(that, iCell), -1);
    // Get the nb of sources
    int nbSrc = VecGetDim(sources);
    // Declare a set of GradFloodPod
    GSet set = GSetCreateStatic();
    // For each sources
    for (int iSource = nbSrc; iSource--;) {
        // Add the first cell in the set
        GradFloodPod* pod = PBErrMalloc(GradErr, sizeof(GradFloodPod));

```

```

    pod->_src = iSource;
    pod->_cell = GradCellAt(that, VecGet(sources, iSource));
    pod->_nbStep = 0;
    GSetAddSort(&set, pod, 0.0);
}
// Loop until the set is empty (ie every cell has
// been flooded
while (GSetNbElem(&set) > 0) {
    // Get the distance up to this cell
    float dist = GSetGetElem(&set, 0)->_sortVal;
    // Pop the cell
    GradFloodPod* pod = GSetPop(&set);
    // If the cell is inside the limit in nb of steps
    if (stepMax < 0 || pod->_nbStep <= stepMax) {
        // Declare a variable to manage conflict
        bool flagConflict = false;
        //if the set is not empty
        if (GSetNbElem(&set) > 0) {
            // Check references to this cell from other sources and
            // eliminate n-uples
            GSetIterForward iter = GSetIterForwardCreateStatic(&set);
            bool skipStep;
            do {
                skipStep = false;
                GradFloodPod* podCheck = GSetIterGet(&iter);
                if (podCheck->_cell == pod->_cell) {
                    float d = GSetIterGetElem(&iter)->_sortVal;
                    if (podCheck->_src != pod->_src && ISEQUALF(d, dist))
                        flagConflict = true;
                    free(podCheck);
                    skipStep = GSetIterRemoveElem(&iter);
                }
            } while (skipStep || GSetIterStep(&iter));
        }
        // If there was no conflict
        if (!flagConflict) {
            // Set the flood value of sources
            GradCellSetFlood(pod->_cell, pod->_src);
            // Loop on direction from this cell
            for (int iLink = GradCellGetNbLink(pod->_cell); iLink--;) {
                int toCell = GradCellGetLink(pod->_cell, iLink);
                // If there is a cell in this direction
                if (toCell != -1) {
                    // Get the distance to this cell from the source
                    float d = dist + GradCellLinkVal(pod->_cell, iLink);
                    // If it's within the max distance
                    if (distMax < 0.0 || d <= distMax) {
                        GradCell* cellTo = GradCellAt(that, toCell);
                        // If it's not yet flooded, not blocked, and not
                        // conflicting
                        if (GradCellGetFlood(cellTo) == -1 &&
                            !GradCellIsBlocked(cellTo)) {
                            // Add a new pod to the GSet 'setOut'
                            GradFloodPod* npod =
                                PBErrMalloc(GradErr, sizeof(GradFloodPod));
                            npod->_src = pod->_src;
                            npod->_nbStep = pod->_nbStep + 1;
                            npod->_cell = cellTo;
                            GSetAddSort(&set, npod, d);
                        }
                    }
                }
            }
        }
    }
}

```

```

    }
}
}
// Free memory used by the GradFloodPod
free(pod);
}
// Free memory
while (GSetNbElem(&set) > 0) {
    GradFloodPod* pod = GSetPop(&set);
    free(pod);
}
}

// Get the number of flooded cells from 'iSource'-th source in the Grad
// 'that'
int _GradGetFloodArea(const Grad* const that, const int iSource) {
    #if BUILDMODE == 0
        if (that == NULL) {
            GradErr->_type = PBErrTypeNullPointer;
            sprintf(GradErr->_msg, "'that' is null");
            PBErrCatch(GradErr);
        }
    #endif
    // Declare a variable to memorize the result
    int nb = 0;
    // Loop on cells
    for (int iCell = GradGetArea(that); iCell--;) {
        // If the flood value of the cell is the searched value
        if (GradCellGetFlood(GradCellAt(that, iCell)) == iSource)
            // Increment the result
            ++nb;
    }
    // Return the result
    return nb;
}

// Clone the GradSquare 'that'
// The user data are not cloned but shared between the original and
// its clone
GradSquare* GradSquareClone(const GradSquare* const that) {
    #if BUILDMODE == 0
        if (that == NULL) {
            GradErr->_type = PBErrTypeNullPointer;
            sprintf(GradErr->_msg, "'that' is null");
            PBErrCatch(GradErr);
        }
    #endif
    // Allocate memory
    GradSquare* clone = PBErrMalloc(GradErr, sizeof(GradSquare));
    // Copy the GradSquare
    *clone = *that;
    // Clone the GradCell
    clone->_grad._cells = PBErrMalloc(GradErr,
        sizeof(GradCell) * GradGetArea(that));
    memcpy(clone->_grad._cells, that->_grad._cells,
        sizeof(GradCell) * GradGetArea(that));
    // Return the clone
    return clone;
}

// Clone the GradHexa 'that'
// The user data are not cloned but shared between the original and

```



```

// its clone
GradHexa* GradHexaClone(const GradHexa* const that) {
#if BUILDMODE == 0
    if (that == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'that' is null");
        PBErrCatch(GradErr);
    }
#endif
    // Allocate memory
    GradHexa* clone = PBErrMalloc(GradErr, sizeof(GradHexa));
    // Copy the GradHexa
    *clone = *that;
    // Clone the GradCell
    clone->_grad._cells = PBErrMalloc(GradErr,
        sizeof(GradCell) * GradGetArea(that));
    memcpy(clone->_grad._cells, that->_grad._cells,
        sizeof(GradCell) * GradGetArea(that));
    // Return the clone
    return clone;
}

// Return true if the Grad 'that' is same as the Grad 'tho'
// Return false else
bool _GradIsSameAs(const Grad* const that, const Grad* const tho) {
#if BUILDMODE == 0
    if (that == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'that' is null");
        PBErrCatch(GradErr);
    }
    if (tho == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'tho' is null");
        PBErrCatch(GradErr);
    }
#endif
    if (that->_type != tho->_type ||
        !VecIsEqual(&(that->_dim), &(tho->_dim)) ||
        (that->_type == GradTypeSquare &&
            ((GradSquare*)that)->_diagLink != ((GradSquare*)tho)->_diagLink) ||
        (that->_type == GradTypeHexa &&
            ((GradHexa*)that)->_type != ((GradHexa*)tho)->_type)) {
        return false;
    } else {
        for (int iCell = GradGetArea(that); iCell--;) {
            GradCell* cellA = GradCellAt(that, iCell);
            GradCell* cellB = GradCellAt(tho, iCell);
            if (cellA->_data != cellB->_data ||
                cellA->_id != cellB->_id ||
                !VecIsEqual(&(cellA->_pos), &(cellB->_pos)) ||
                cellA->_nbLink != cellB->_nbLink ||
                cellA->_flood != cellB->_flood ||
                cellA->_flagBlocked != cellB->_flagBlocked ||
                memcmp(cellA->_links, cellB->_links,
                    sizeof(int) * GRAD_NBMAXLINK) != 0 ||
                memcmp(cellA->_linksVal, cellB->_linksVal,
                    sizeof(float) * GRAD_NBMAXLINK) != 0) {
                return false;
            }
        }
    }
    return true;
}

```

```

    }
}

// Remove the link from cell 'fromCell' to cell 'toCell' in the
// Grad 'that'
// If 'symmetric' equals true the symmetric link is removed too
// (only if the link from 'fromCell' exists)
void _GradRemoveLinkIndex(Grad* const that, const int fromCell,
    const int toCell, const bool symmetric) {
#ifdef BUILDMODE == 0
    if (that == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'that' is null");
        PBErrCatch(GradErr);
    }
#endif
    // Loop on links of the 'fromCell'
    GradCell* cell = GradCellAt(that, fromCell);
    for (int iLink = GradCellGetNbLink(cell); iLink--;) {
        // If it's the link toward the 'toCell'
        if (GradCellGetLink(cell, iLink) == toCell) {
            // Remove it
            GradCellSetLink(cell, iLink, -1);
            // If we have to remove the symmetric link
            if (symmetric)
                _GradRemoveLinkIndex(that, toCell, fromCell, false);
            // Skip the end of the loop
            break;
        }
    }
}

// Remove the link from cell at position 'fromCell' toward direction
// 'dir' in the Grad 'that'
// If 'symmetric' equals true the symmetric link is removed too
// (only if the link from 'fromCell' exists)
void _GradRemoveDirIndex(Grad* const that, const int fromCell,
    const int dir, const bool symmetric) {
#ifdef BUILDMODE == 0
    if (that == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'that' is null");
        PBErrCatch(GradErr);
    }
#endif
    // Get the cell
    GradCell* cell = GradCellAt(that, fromCell);
    // Get the neighbour cell
    int toCell = GradCellGetLink(cell, dir);
    // If there is a link in this direction
    if (toCell != -1) {
        // If we have to remove the symmetric link
        if (symmetric)
            _GradRemoveLinkIndex(that, toCell, fromCell, false);
        // Remove the link
        GradCellSetLink(cell, dir, -1);
    }
}

// Remove all the links from cell 'fromCell' in the Grad 'that'
// If 'symmetric' equals true the symmetric links are removed too
// (only if the link from 'fromCell' exists)

```

```

void _GradRemoveAllLinkIndex(Grad* const that, const int fromCell,
    const bool symmetric) {
    #if BUILDMODE == 0
        if (that == NULL) {
            GradErr->_type = PBErrTypeNullPointer;
            sprintf(GradErr->_msg, "'that' is null");
            PBErrCatch(GradErr);
        }
    #endif
    // Loop on links of the 'fromCell'
    GradCell* cell = GradCellAt(that, fromCell);
    for (int iLink = GradCellGetNbLink(cell); iLink--;) {
        // Memorize the link
        int toCell = GradCellGetLink(cell, iLink);
        // Remove the link
        GradCellSetLink(cell, iLink, -1);
        // If we have to remove the symmetric link and it exists
        if (symmetric && toCell != -1)
            _GradRemoveLinkIndex(that, toCell, fromCell, false);
    }
}

// Add the link from cell 'fromCell' to cell 'toCell' in the
// Grad 'that'
// If the cells are not neighbours do nothing
// If 'symmetric' equals true the symmetric link is added too
void _GradAddLinkIndex(Grad* const that, int fromCell, int toCell,
    bool symmetric) {
    #if BUILDMODE == 0
        if (that == NULL) {
            GradErr->_type = PBErrTypeNullPointer;
            sprintf(GradErr->_msg, "'that' is null");
            PBErrCatch(GradErr);
        }
    #endif
    // Declare pointer to the cells
    GradCell* cell = GradCellAt(that, fromCell);
    GradCell* cellTo = GradCellAt(that, toCell);
    // Declare variable for computation
    VecShort2D p = VecShortCreateStatic2D();
    // Get the table of delta position given the type of Grad
    int* delta = GradGetDelta(that, GradCellPos(cell));
    // Loop on links of the 'fromCell'
    for (int iLink = GradCellGetNbLink(cell); iLink--;) {
        // Get the position in this direction
        for (int i = 2; i--;)
            VecSet(&p, i, VecGet(GradCellPos(cell), i) + delta[2 * iLink + i]);
        // If it's the link toward the 'toCell'
        if (VecIsEqual(&p, GradCellPos(cellTo))) {
            // Add it
            GradCellSetLink(cell, iLink, toCell);
            // If we have to add the symmetric link
            if (symmetric)
                _GradAddLinkIndex(that, toCell, fromCell, false);
            // Skip the end of the loop
            break;
        }
    }
}

// Add the link from cell at position 'fromCell' toward direction
// 'dir' in the Grad 'that'

```

```

// If the cells are not neighbours do nothing
// If 'symmetric' equals true the symetric link is added too
void _GradAddDirIndex(Grad* const that, int const fromCell,
    const int dir, const bool symmetric) {
#ifdef BUILDMODE == 0
    if (that == NULL) {
        GradErr->_type = PErrTypeNullPointer;
        sprintf(GradErr->_msg, "'that' is null");
        PErrCatch(GradErr);
    }
#endif
    // Get the cell
    GradCell* cell = GradCellAt(that, fromCell);
    // Get the delta pos
    int* delta = GradGetDelta(that, GradCellPos(cell));
    // Get the neighbour cell pos
    VecShort2D p = VecShortCreateStatic2D();
    for (int i = 2; i--;)
        VecSet(&p, i, VecGet(GradCellPos(cell), i) + delta[2 * dir + i]);
    // If the neighbour cell exists
    if (GradIsPosInside(that, &p)) {
        // Get the neighbour cell
        GradCell* cellTo = GradCellAt(that, &p);
        int toCell = GradCellGetId(cellTo);
        // Set the link
        GradCellSetLink(cell, dir, toCell);
        // If we have to add the symmetric link
        if (symmetric)
            GradAddLinkTo(that, toCell, fromCell, false);
    }
}

// Add all the links from cell 'fromCell' in the Grad 'that'
// If 'symmetric' equals true the symetric links are removed too
void _GradAddAllLinkIndex(Grad* const that, const int fromCell,
    const bool symmetric) {
#ifdef BUILDMODE == 0
    if (that == NULL) {
        GradErr->_type = PErrTypeNullPointer;
        sprintf(GradErr->_msg, "'that' is null");
        PErrCatch(GradErr);
    }
#endif
    // Declare pointer to the cell
    GradCell* cell = GradCellAt(that, fromCell);
    // Declare variable for computation
    VecShort2D p = VecShortCreateStatic2D();
    // Get the table of delta position given the type of Grad
    int* delta = GradGetDelta(that, GradCellPos(cell));
    // Loop on links of the 'fromCell'
    for (int iLink = GradCellGetNbLink(cell); iLink--;) {
        // Get the position in this direction
        for (int i = 2; i--;)
            VecSet(&p, i, VecGet(GradCellPos(cell), i) + delta[2 * iLink + i]);
        // If the position is inside the Grad
        if (GradIsPosInside(that, &p)) {
            GradCell* cellTo = GradCellAt(that, &p);
            int toCell = GradCellGetId(cellTo);
            // Add the link
            GradCellSetLink(cell, iLink, toCell);
            // If we have to add the symmetric link
            if (symmetric)

```

```

        _GradAddLinkIndex(that, toCell, fromCell, false);
    }
}
}

```

## 3.2 grad-inline.c

```

// ===== GRAD-INLINE.C =====

// ----- GradCell

// ===== Functions implementation =====

// Get the user data of the GradCell 'that'
#if BUILDMODE != 0
inline
#endif
void* GradCellData(const GradCell* const that) {
#if BUILDMODE == 0
    if (that == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'that' is null");
        PBErrCatch(GradErr);
    }
#endif
    return that->_data;
}

// Set the user data of the GradCell 'that' to 'data'
#if BUILDMODE != 0
inline
#endif
void GradCellSetData(GradCell* const that, void* const data) {
#if BUILDMODE == 0
    if (that == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'that' is null");
        PBErrCatch(GradErr);
    }
#endif
    that->_data = data;
}

// Get the position of the GradCell 'that'
#if BUILDMODE != 0
inline
#endif
VecShort2D* GradCellPos(const GradCell* const that) {
#if BUILDMODE == 0
    if (that == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'that' is null");
        PBErrCatch(GradErr);
    }
#endif
    return (VecShort2D*)&(that->_pos);
}

```

```

// Get the index of the GradCell 'that'
#if BUILDMODE != 0
inline
#endif
int GradCellGetId(const GradCell* const that) {
#if BUILDMODE == 0
    if (that == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'that' is null");
        PBErrCatch(GradErr);
    }
#endif
    return that->_id;
}

// Get the index of 'iLink'-th link of the GradCell 'that'
#if BUILDMODE != 0
inline
#endif
int GradCellGetLink(const GradCell* const that, const int iLink) {
#if BUILDMODE == 0
    if (that == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'that' is null");
        PBErrCatch(GradErr);
    }
    if (iLink < 0 || iLink >= that->_nbLink) {
        GradErr->_type = PBErrTypeInvalidArg;
        sprintf(GradErr->_msg, "'iLink' is invalid (0<=%d<=%d)",
            iLink, that->_nbLink);
        PBErrCatch(GradErr);
    }
#endif
    return that->_links[iLink];
}

// Set the index of 'iLink'-th link of the GradCell 'that' to 'iCell'
#if BUILDMODE != 0
inline
#endif
void GradCellSetLink(GradCell* const that, const int iLink,
    const int iCell) {
#if BUILDMODE == 0
    if (that == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'that' is null");
        PBErrCatch(GradErr);
    }
    if (iLink < 0 || iLink >= that->_nbLink) {
        GradErr->_type = PBErrTypeInvalidArg;
        sprintf(GradErr->_msg, "'iLink' is invalid (0<=%d<=%d)",
            iLink, that->_nbLink);
        PBErrCatch(GradErr);
    }
    if (iCell < -1) {
        GradErr->_type = PBErrTypeInvalidArg;
        sprintf(GradErr->_msg, "'iCell' is invalid (-1<=%d)", iCell);
        PBErrCatch(GradErr);
    }
#endif
    that->_links[iLink] = iCell;
}

```

```

// Get the number of links of the GradCell 'that'
#if BUILDMODE != 0
inline
#endif
int GradCellGetNbLink(const GradCell* const that) {
#if BUILDMODE == 0
    if (that == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'that' is null");
        PBErrCatch(GradErr);
    }
#endif
    return that->_nbLink;
}

// Get the value of 'iLink'-th link of the GradCell 'that'
#if BUILDMODE != 0
inline
#endif
float GradCellLinkVal(const GradCell* const that, const int iLink) {
#if BUILDMODE == 0
    if (that == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'that' is null");
        PBErrCatch(GradErr);
    }
    if (iLink < 0 || iLink >= that->_nbLink) {
        GradErr->_type = PBErrTypeInvalidArg;
        sprintf(GradErr->_msg, "'iLink' is invalid (0<=%d<%d)",
            iLink, that->_nbLink);
        PBErrCatch(GradErr);
    }
#endif
    return that->_linksVal[iLink];
}

// Set the value of 'iLink'-th link of the GradCell 'that' to 'val'
#if BUILDMODE != 0
inline
#endif
void GradCellSetLinkVal(GradCell* const that, const int iLink,
    const float val) {
#if BUILDMODE == 0
    if (that == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'that' is null");
        PBErrCatch(GradErr);
    }
    if (iLink < 0 || iLink >= that->_nbLink) {
        GradErr->_type = PBErrTypeInvalidArg;
        sprintf(GradErr->_msg, "'iLink' is invalid (0<=%d<%d)",
            iLink, that->_nbLink);
        PBErrCatch(GradErr);
    }
#endif
    that->_linksVal[iLink] = val;
}

// Get the flood value of the GradCell 'that'
#if BUILDMODE != 0
inline

```

```

#endif
int GradCellGetFlood(const GradCell* const that) {
#if BUILDMODE == 0
    if (that == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'that' is null");
        PBErrCatch(GradErr);
    }
#endif
    return that->_flood;
}

// Set the flood value of the GradCell 'that' to 'iSource'
#if BUILDMODE != 0
inline
#endif
void GradCellSetFlood(GradCell* const that, const int iSource) {
#if BUILDMODE == 0
    if (that == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'that' is null");
        PBErrCatch(GradErr);
    }
#endif
    that->_flood = iSource;
}

// Get the flag blocked of the GradCell 'that'
#if BUILDMODE != 0
inline
#endif
bool GradCellIsBlocked(const GradCell* const that) {
#if BUILDMODE == 0
    if (that == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'that' is null");
        PBErrCatch(GradErr);
    }
#endif
    return that->_flagBlocked;
}

// Set the flag blocked of the GradCell 'that' to 'flag'
#if BUILDMODE != 0
inline
#endif
void GradCellSetBlocked(GradCell* const that, const bool flag) {
#if BUILDMODE == 0
    if (that == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'that' is null");
        PBErrCatch(GradErr);
    }
#endif
    that->_flagBlocked = flag;
}

// ----- Grad

// ===== Functions implementation =====

// Get the GradCell at index 'iCell' in the Grad 'that'

```



```

#if BUILDMODE != 0
inline
#endif
GradCell* _GradCellAtIndex(const Grad* const that, const int iCell) {
#if BUILDMODE == 0
    if (that == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'that' is null");
        PBErrCatch(GradErr);
    }
    if (iCell < 0 || iCell >= GradGetArea(that)) {
        GradErr->_type = PBErrTypeInvalidArg;
        sprintf(GradErr->_msg, "'iCell' is invalid (0<=%d<%d)",
            iCell, GradGetArea(that));
        PBErrCatch(GradErr);
    }
#endif
    return that->_cells + iCell;
}

// Get the GradCell at position 'pos' int the Grad 'that'
#if BUILDMODE != 0
inline
#endif
GradCell* _GradCellAtPos(const Grad* const that,
    const VecShort2D* const pos) {
#if BUILDMODE == 0
    if (that == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'that' is null");
        PBErrCatch(GradErr);
    }
    if (VecGet(pos, 0) < 0 || VecGet(pos, 1) < 0 ||
        VecGet(pos, 0) >= VecGet(GradDim(that), 0) ||
        VecGet(pos, 1) >= VecGet(GradDim(that), 1)) {
        GradErr->_type = PBErrTypeInvalidArg;
        sprintf(GradErr->_msg, "'pos' is invalid ((0,0)<=(%d,%d)<(%d,%d))",
            VecGet(pos, 0), VecGet(pos, 1),
            VecGet(GradDim(that), 0), VecGet(GradDim(that), 1));
        PBErrCatch(GradErr);
    }
#endif
    return that->_cells + GradPosToIndex(that, pos);
}

// Get the GradType of the Grad 'that'
#if BUILDMODE != 0
inline
#endif
GradType _GradGetType(const Grad* const that) {
#if BUILDMODE == 0
    if (that == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'that' is null");
        PBErrCatch(GradErr);
    }
#endif
    return that->_type;
}

// Get the GradHexaType of the GradHexa 'that'
#if BUILDMODE != 0

```

```

inline
#endif
GradHexaType GradHexaGetType(const GradHexa* const that) {
#if BUILDMODE == 0
    if (that == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'that' is null");
        PBErrCatch(GradErr);
    }
#endif
    return that->_type;
}

// Get the number of cells (area) of the Grad 'that'
#if BUILDMODE != 0
inline
#endif
int _GradGetArea(const Grad* const that) {
#if BUILDMODE == 0
    if (that == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'that' is null");
        PBErrCatch(GradErr);
    }
#endif
    return VecGet(GradDim(that), 0) * VecGet(GradDim(that), 1);
}

// Get the dimensions of the Grad 'that'
#if BUILDMODE != 0
inline
#endif
VecShort2D* _GradDim(const Grad* const that) {
#if BUILDMODE == 0
    if (that == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'that' is null");
        PBErrCatch(GradErr);
    }
#endif
    return (VecShort2D*)&(that->_dim);
}

// Check if the position 'pos' is inside the GradSquare 'that'
#if BUILDMODE != 0
inline
#endif
bool _GradIsPosInside(const Grad* const that,
    const VecShort2D* const pos) {
#if BUILDMODE == 0
    if (that == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'that' is null");
        PBErrCatch(GradErr);
    }
#endif
    if (VecGet(pos, 0) < 0 || VecGet(pos, 1) < 0 ||
        VecGet(pos, 0) >= VecGet(GradDim(that), 0) ||
        VecGet(pos, 1) >= VecGet(GradDim(that), 1)) {
        return false;
    } else {
        return true;
    }
}

```

```

    }
}

// Set the flag blocked of all cells in the Grad 'that' to false
#if BUILDMODE != 0
inline
#endif
void _GradResetFlagBlocked(Grad* const that) {
#if BUILDMODE == 0
    if (that == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'that' is null");
        PBErrCatch(GradErr);
    }
#endif
    for (int iCell = GradGetArea(that); iCell--;)
        GradCellSetBlocked(GradCellAt(that, iCell), false);
}

// Return true if the GradSquare 'that' has diagonal link
// Return false else
#if BUILDMODE != 0
inline
#endif
bool GradSquareHasDiagonalLink(const GradSquare* const that) {
#if BUILDMODE == 0
    if (that == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'that' is null");
        PBErrCatch(GradErr);
    }
#endif
    return that->_diagLink;
}

// Remove the link from cell at position 'fromCell' to cell at
// position 'toCell' in the Grad 'that'
// If 'symmetric' equals true the symetric link is removed too
// (only if the link from 'fromCell' exists)
#if BUILDMODE != 0
inline
#endif
void _GradRemoveLinkPos(Grad* const that,
    const VecShort2D* const fromCell, const VecShort2D* const toCell,
    const bool symmetric) {
#if BUILDMODE == 0
    if (that == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'that' is null");
        PBErrCatch(GradErr);
    }
    if (fromCell == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'fromCell' is null");
        PBErrCatch(GradErr);
    }
    if (toCell == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'toCell' is null");
        PBErrCatch(GradErr);
    }
#endif
}

```

```

    // Get the index of 'fromCell' and 'toCell'
    int from = GradPosToIndex(that, fromCell);
    int to = GradPosToIndex(that, toCell);
    // Remove the link
    _GradRemoveLinkIndex(that, from, to, symmetric);
}

// Remove the link from cell at position 'fromCell' toward direction
// 'dir' in the Grad 'that'
// If 'symmetric' equals true the symetric link is removed too
// (only if the link from 'fromCell' exists)
#if BUILDMODE != 0
inline
#endif
void _GradRemoveDirPos(Grad* const that,
    const VecShort2D* const fromCell, const int dir, const bool symmetric) {
#if BUILDMODE == 0
    if (that == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'that' is null");
        PBErrCatch(GradErr);
    }
    if (fromCell == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'fromCell' is null");
        PBErrCatch(GradErr);
    }
#endif
    // Get the index of 'fromCell'
    int from = GradPosToIndex(that, fromCell);
    // Remove the link
    _GradRemoveDirIndex(that, from, dir, symmetric);
}

// Remove all the links from cell at position 'fromCell' in
// the Grad 'that'
// If 'symmetric' equals true the symetric links are removed too
// (only if the link from 'fromCell' exists)
#if BUILDMODE != 0
inline
#endif
void _GradRemoveAllLinkPos(Grad* const that,
    const VecShort2D* const fromCell, const bool symmetric) {
#if BUILDMODE == 0
    if (that == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'that' is null");
        PBErrCatch(GradErr);
    }
    if (fromCell == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'fromCell' is null");
        PBErrCatch(GradErr);
    }
#endif
    // Get the index of 'fromCell'
    int from = GradPosToIndex(that, fromCell);
    // Remove the link
    _GradRemoveAllLinkIndex(that, from, symmetric);
}

// Add the link from cell at position 'fromCell' to cell at

```

```

// position 'toCell' in the Grad 'that'
// If the cells are not neighbours do nothing
// If 'symmetric' equals true the symetric link is added too
#if BUILDMODE != 0
inline
#endif
void _GradAddLinkPos(Grad* const that, const VecShort2D* const fromCell,
    const VecShort2D* const toCell, const bool symmetric) {
#if BUILDMODE == 0
    if (that == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'that' is null");
        PBErrCatch(GradErr);
    }
    if (fromCell == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'fromCell' is null");
        PBErrCatch(GradErr);
    }
    if (toCell == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'toCell' is null");
        PBErrCatch(GradErr);
    }
#endif
    // Get the index of 'fromCell' and 'toCell'
    int from = GradPosToIndex(that, fromCell);
    int to = GradPosToIndex(that, toCell);
    // Remove the link
    _GradAddLinkIndex(that, from, to, symmetric);
}

// Add the link from cell at position 'fromCell' toward direction
// 'dir' in the Grad 'that'
// If the cells are not neighbours do nothing
// If 'symmetric' equals true the symetric link is added too
#if BUILDMODE != 0
inline
#endif
void _GradAddDirPos(Grad* const that, const VecShort2D* const fromCell,
    const int dir, const bool symmetric) {
#if BUILDMODE == 0
    if (that == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'that' is null");
        PBErrCatch(GradErr);
    }
    if (fromCell == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'fromCell' is null");
        PBErrCatch(GradErr);
    }
#endif
    // Get the index of 'fromCell' and 'toCell'
    int from = GradPosToIndex(that, fromCell);
    // Remove the link
    _GradAddDirIndex(that, from, dir, symmetric);
}

// Add all the links from cell at position 'fromCell' in
// the Grad 'that'
// If 'symmetric' equals true the symetric links are removed too

```

```

#if BUILDMODE != 0
inline
#endif
void _GradAddAllLinkPos(Grad* const that,
    const VecShort2D* const fromCell, const bool symmetric) {
#if BUILDMODE == 0
    if (that == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'that' is null");
        PBErrCatch(GradErr);
    }
    if (fromCell == NULL) {
        GradErr->_type = PBErrTypeNullPointer;
        sprintf(GradErr->_msg, "'fromCell' is null");
        PBErrCatch(GradErr);
    }
#endif
    // Get the index of 'fromCell' and 'toCell'
    int from = GradPosToIndex(that, fromCell);
    // Remove the link
    _GradAddAllLinkIndex(that, from, symmetric);
}

```

## 4 Makefile

```

#directory
PBERRDIR=../PBErr
GSETDIR=../GSet
PBMATHDIR=../PBMath
GTREEDIR=../GTree
PBJSONDIR=../PBJson

# Build mode
# 0: development (max safety, no optimisation)
# 1: release (min safety, optimisation)
# 2: fast and furious (no safety, optimisation)
BUILDMODE=1

include $(PBERRDIR)/Makefile.inc

INCPATH=-I./ -I$(PBERRDIR)/ -I$(GSETDIR)/ -I$(PBMATHDIR)/ -I$(PBJSONDIR)/ -I$(GTREEDIR)/
BUILDOPTIONS=$(BUILDPARAM) $(INCPATH)

# compiler
COMPILER=gcc

#rules
all : main

main: main.o pberr.o grad.o gset.o pbmath.o pbjson.o gtree.o Makefile
$(COMPILER) main.o pberr.o grad.o gset.o pbmath.o pbjson.o gtree.o $(LINKOPTIONS) -o main

main.o : main.c $(PBERRDIR)/pberr.h grad.h grad-inline.c Makefile
$(COMPILER) $(BUILDOPTIONS) -c main.c

grad.o : grad.c grad.h $(GSETDIR)/gset.h $(PBMATHDIR)/pbmath.h grad-inline.c Makefile
$(COMPILER) $(BUILDOPTIONS) -c grad.c

```

```

pbjson.o : $(PBJSONDIR)/pbjson.c $(PBJSONDIR)/pbjson-inline.c $(PBJSONDIR)/pbjson.h Makefile
$(COMPILER) $(BUILDOPTIONS) -c $(PBJSONDIR)/pbjson.c

gtree.o : $(GTREEDIR)/gtree.c $(GTREEDIR)/gtree.h $(GTREEDIR)/gtree-inline.c Makefile $(GSETDIR)/gset-inline.c $(GSE
$(COMPILER) $(BUILDOPTIONS) -c $(GTREEDIR)/gtree.c

gset.o : $(GSETDIR)/gset.c $(GSETDIR)/gset-inline.c $(GSETDIR)/gset.h Makefile
$(COMPILER) $(BUILDOPTIONS) -c $(GSETDIR)/gset.c

pbmath.o : $(PBMATHDIR)/pbmath.c $(PBMATHDIR)/pbmath-inline.c $(PBMATHDIR)/pbmath.h Makefile
$(COMPILER) $(BUILDOPTIONS) -c $(PBMATHDIR)/pbmath.c

pberr.o : $(PBERRDIR)/pberr.c $(PBERRDIR)/pberr.h Makefile
$(COMPILER) $(BUILDOPTIONS) -c $(PBERRDIR)/pberr.c

clean :
rm -rf *.o main

valgrind :
valgrind -v --track-origins=yes --leak-check=full --gen-suppressions=yes --show-leak-kinds=all ./main

unitTest :
main > unitTest.txt; diff unitTest.txt unitTestRef.txt

```

## 5 Unit tests

```

#include <stdlib.h>
#include <stdio.h>
#include <time.h>
#include <string.h>
#include <time.h>
#include <unistd.h>
#include <sys/time.h>
#include "pberr.h"
#include "grad.h"

#define RANDOMSEED 0

void UnitTestGradCellCreateFree() {
    VecShort2D pos = VecShortCreateStatic2D();
    VecSet(&pos, 0, 3.0); VecSet(&pos, 1, 4.0);
    GradCell* cell = GradCellCreate(1, 2, &pos);
    if (cell == NULL ||
        cell->_id != 1 ||
        cell->_nbLink != 2 ||
        cell->_data != NULL ||
        cell->_flood != -1 ||
        cell->_flagBlocked != false ||
        VecIsEqual(&(cell->_pos), &pos) == false) {
        GradErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GradErr->_msg, "GradCellCreate failed");
        PBErrCatch(GradErr);
    }
    for (int iLink = GRAD_NBMAXLINK; iLink--;) {
        if (cell->_links[iLink] != -1 ||
            ISEQUALF(cell->_linksVal[iLink], 1.0) == false) {
                GradErr->_type = PBErrTypeUnitTestFailed;
                sprintf(GradErr->_msg, "GradCellCreate failed");
                PBErrCatch(GradErr);
            }
    }
}

```

```

    }
}
GradCellFree(&cell);
if (cell != NULL) {
    GradErr->_type = PBErrTypeUnitTestFailed;
    sprintf(GradErr->_msg, "GradCellFree failed");
    PBErrCatch(GradErr);
}
printf("UnitTestGradCellCreateFree OK\n");
}

void UnitTestGradCellGetSet() {
    VecShort2D pos = VecShortCreateStatic2D();
    VecSet(&pos, 0, 3.0); VecSet(&pos, 1, 4.0);
    GradCell* cell = GradCellCreate(1, 2, &pos);
    if (GradCellGetId(cell) != cell->_id) {
        GradErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GradErr->_msg, "GradCellGetId failed");
        PBErrCatch(GradErr);
    }
    if (GradCellGetFlood(cell) != cell->_flood) {
        GradErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GradErr->_msg, "GradCellGetFlood failed");
        PBErrCatch(GradErr);
    }
    if (GradCellGetNbLink(cell) != cell->_nbLink) {
        GradErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GradErr->_msg, "GradCellGetFlood failed");
        PBErrCatch(GradErr);
    }
    if (GradCellIsBlocked(cell) != cell->_flagBlocked) {
        GradErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GradErr->_msg, "GradCellIsBlocked failed");
        PBErrCatch(GradErr);
    }
    if (GradCellData(cell) != cell->_data) {
        GradErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GradErr->_msg, "GradCellData failed");
        PBErrCatch(GradErr);
    }
    if (GradCellGetLink(cell, 1) != cell->_links[1]) {
        GradErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GradErr->_msg, "GradCellLink failed");
        PBErrCatch(GradErr);
    }
    if (GradCellLinkVal(cell, 1) != cell->_linksVal[1]) {
        GradErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GradErr->_msg, "GradCellLinkVal failed");
        PBErrCatch(GradErr);
    }
    int val;
    GradCellSetData(cell, &val);
    if (GradCellData(cell) != &val) {
        GradErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GradErr->_msg, "GradCellSetData failed");
        PBErrCatch(GradErr);
    }
    GradCellSetLink(cell, 1, 2);
    if (GradCellGetLink(cell, 1) != 2) {
        GradErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GradErr->_msg, "GradCellSetLink failed");
        PBErrCatch(GradErr);
    }
}

```



```

}
GradCellSetLinkVal(cell, 1, 2.0);
if (ISEQUALF(GradCellLinkVal(cell, 1), 2.0) == false) {
    GradErr->_type = PBErrTypeUnitTestFailed;
    sprintf(GradErr->_msg, "GradCellSetLinkVal failed");
    PBErrCatch(GradErr);
}
GradCellSetBlocked(cell, true);
if (GradCellIsBlocked(cell) == false) {
    GradErr->_type = PBErrTypeUnitTestFailed;
    sprintf(GradErr->_msg, "GradCellSetBlocked failed");
    PBErrCatch(GradErr);
}
GradCellSetFlood(cell, 1);
if (GradCellGetFlood(cell) != 1) {
    GradErr->_type = PBErrTypeUnitTestFailed;
    sprintf(GradErr->_msg, "GradCellSetFlood failed");
    PBErrCatch(GradErr);
}
GradCellFree(&cell);
printf("UnitTestGradCellGetSet OK\n");
}

void UnitTestGradCell() {
    UnitTestGradCellCreateFree();
    UnitTestGradCellGetSet();
    printf("UnitTestGradCell OK\n");
}

void UnitTestGradCreateFree() {
    bool diagLink = true;
    VecShort2D dim = VecShortCreateStatic2D();
    VecSet(&dim, 0, 2); VecSet(&dim, 1, 3);
    GradSquare* gradSquare = GradSquareCreate(&dim, diagLink);
    if (gradSquare == NULL ||
        VecIsEqual(&(gradSquare->_grad._dim), &dim) == false ||
        gradSquare->_diagLink != diagLink ||
        gradSquare->_grad._type != GradTypeSquare ||
        gradSquare->_grad._cells == NULL) {
        GradErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GradErr->_msg, "GradSquareCreate failed");
        PBErrCatch(GradErr);
    }
    int iCell = 0;
    VecShort2D pos = VecShortCreateStatic2D();
    do {
        if (VecIsEqual(GradCellPos(gradSquare->_grad._cells + iCell),
            &pos) == false) {
            GradErr->_type = PBErrTypeUnitTestFailed;
            sprintf(GradErr->_msg, "GradSquareCreate failed");
            PBErrCatch(GradErr);
        }
        ++iCell;
    } while (VecPStep(&pos, &dim));
    int checkA[48] = {
        -1, 1, 2, -1, -1, -1, 3, -1,
        -1, -1, 3, 0, -1, -1, -1, 2,
        0, 3, 4, -1, -1, 1, 5, -1,
        1, -1, 5, 2, 0, -1, -1, 4,
        2, 5, -1, -1, -1, 3, -1, -1,
        3, -1, -1, 4, 2, -1, -1, -1
    };
};

```

```

int iCheck = 0;
for (int iCell = 0; iCell < 6; ++iCell) {
    if (gradSquare->_grad._cells[iCell]._nbLink != 8) {
        GradErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GradErr->_msg, "GradSquareCreate failed");
        PBErrCatch(GradErr);
    }
    for (int iLink = 0; iLink < 8; ++iLink) {
        if (gradSquare->_grad._cells[iCell]._links[iLink] !=
            checkA[iCheck] ||
            (iLink < 4 &&
             ISEQUALF(gradSquare->_grad._cells[iCell]._linksVal[iLink],
                       1.0) == false) ||
            (iLink >= 4 &&
             ISEQUALF(gradSquare->_grad._cells[iCell]._linksVal[iLink],
                       PBMath_SQRTTWO) == false)) {
            GradErr->_type = PBErrTypeUnitTestFailed;
            sprintf(GradErr->_msg, "GradSquareCreate failed");
            PBErrCatch(GradErr);
        }
        ++iCheck;
    }
}
GradSquareFree(&gradSquare);
diagLink = false;
gradSquare = GradSquareCreate(&dim, diagLink);
if (gradSquare == NULL) {
    GradErr->_type = PBErrTypeUnitTestFailed;
    sprintf(GradErr->_msg, "GradSquareCreate failed");
    PBErrCatch(GradErr);
}
int checkB[24] = {
    -1, 1, 2, -1,
    -1, -1, 3, 0,
    0, 3, 4, -1,
    1, -1, 5, 2,
    2, 5, -1, -1,
    3, -1, -1, 4
};
iCheck = 0;
for (int iCell = 0; iCell < 6; ++iCell) {
    if (gradSquare->_grad._cells[iCell]._nbLink != 4) {
        GradErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GradErr->_msg, "GradSquareCreate failed");
        PBErrCatch(GradErr);
    }
    for (int iLink = 0; iLink < 4; ++iLink) {
        if (gradSquare->_grad._cells[iCell]._links[iLink] !=
            checkB[iCheck] ||
            ISEQUALF(gradSquare->_grad._cells[iCell]._linksVal[iLink],
                      1.0) == false) {
            GradErr->_type = PBErrTypeUnitTestFailed;
            sprintf(GradErr->_msg, "GradSquareCreate failed");
            PBErrCatch(GradErr);
        }
        ++iCheck;
    }
}
GradSquareFree(&gradSquare);
if (gradSquare != NULL) {
    GradErr->_type = PBErrTypeUnitTestFailed;
    sprintf(GradErr->_msg, "GradSquareFree failed");
}

```

```

    PBErrCatch(GradErr);
}
GradHexa* gradHexa = GradHexaCreateOddR(&dim);
if (gradHexa == NULL ||
    VecIsEqual(&(gradHexa->_grad._dim), &dim) == false ||
    gradHexa->_grad._type != GradTypeHexa ||
    gradHexa->_type != GradHexaTypeOddR ||
    gradHexa->_grad._cells == NULL) {
    GradErr->_type = PBErrTypeUnitTestFailed;
    sprintf(GradErr->_msg, "GradHexaCreateOddR failed");
    PBErrCatch(GradErr);
}
int checkC[36] = {
    -1, -1, 1, 2, -1, -1,
    -1, -1, -1, 3, 2, 0,
    0, 1, 3, 5, 4, -1,
    1, -1, -1, -1, 5, 2,
    -1, 2, 5, -1, -1, -1,
    2, 3, -1, -1, -1, 4
};
iCheck = 0;
for (int iCell = 0; iCell < 6; ++iCell) {
    if (gradHexa->_grad._cells[iCell]._nbLink != 6) {
        GradErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GradErr->_msg, "GradHexaCreateOddR failed");
        PBErrCatch(GradErr);
    }
    for (int iLink = 0; iLink < 6; ++iLink) {
        if (gradHexa->_grad._cells[iCell]._links[iLink] !=
            checkC[iCheck] ||
            ISEQUALF(gradHexa->_grad._cells[iCell]._linksVal[iLink],
                1.0) == false) {
            GradErr->_type = PBErrTypeUnitTestFailed;
            sprintf(GradErr->_msg, "GradHexaCreateOddR failed");
            PBErrCatch(GradErr);
        }
        ++iCheck;
    }
}
GradHexaFree(&gradHexa);
gradHexa = GradHexaCreateEvenR(&dim);
if (gradHexa == NULL ||
    VecIsEqual(&(gradHexa->_grad._dim), &dim) == false ||
    gradHexa->_grad._type != GradTypeHexa ||
    gradHexa->_type != GradHexaTypeEvenR ||
    gradHexa->_grad._cells == NULL) {
    GradErr->_type = PBErrTypeUnitTestFailed;
    sprintf(GradErr->_msg, "GradHexaCreateEvenR failed");
    PBErrCatch(GradErr);
}
int checkD[36] = {
    -1, -1, 1, 3, 2, -1,
    -1, -1, -1, -1, 3, 0,
    -1, 0, 3, 4, -1, -1,
    0, 1, -1, 5, 4, 2,
    2, 3, 5, -1, -1, -1,
    3, -1, -1, -1, -1, 4
};
iCheck = 0;
for (int iCell = 0; iCell < 6; ++iCell) {
    if (gradHexa->_grad._cells[iCell]._nbLink != 6) {
        GradErr->_type = PBErrTypeUnitTestFailed;
    }
}

```

```

        sprintf(GradErr->_msg, "GradHexaCreateEvenRfailed");
        PBErrCatch(GradErr);
    }
    for (int iLink = 0; iLink < 6; ++iLink) {
        if (gradHexa->_grad._cells[iCell]._links[iLink] !=
            checkD[iCheck] ||
            ISEQUALF(gradHexa->_grad._cells[iCell]._linksVal[iLink],
                1.0) == false) {
            GradErr->_type = PBErrTypeUnitTestFailed;
            sprintf(GradErr->_msg, "GradHexaCreateEvenR failed");
            PBErrCatch(GradErr);
        }
        ++iCheck;
    }
}
GradHexaFree(&gradHexa);
gradHexa = GradHexaCreateOddQ(&dim);
if (gradHexa == NULL ||
    VecIsEqual(&(gradHexa->_grad._dim), &dim) == false ||
    gradHexa->_grad._type != GradTypeHexa ||
    gradHexa->_type != GradHexaTypeOddQ ||
    gradHexa->_grad._cells == NULL) {
    GradErr->_type = PBErrTypeUnitTestFailed;
    sprintf(GradErr->_msg, "GradHexaCreateOddQ failed");
    PBErrCatch(GradErr);
}
int checkE[36] = {
    -1, -1, 1, 2, -1, -1,
    -1, -1, -1, 3, 2, 0,
    0, 1, 3, 4, -1, -1,
    1, -1, -1, 5, 4, 2,
    2, 3, 5, -1, -1, -1,
    3, -1, -1, -1, -1, 4
};
iCheck = 0;
for (int iCell = 0; iCell < 6; ++iCell) {
    if (gradHexa->_grad._cells[iCell]._nbLink != 6) {
        GradErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GradErr->_msg, "GradHexaCreateOddQfailed");
        PBErrCatch(GradErr);
    }
    for (int iLink = 0; iLink < 6; ++iLink) {
        if (gradHexa->_grad._cells[iCell]._links[iLink] !=
            checkE[iCheck] ||
            ISEQUALF(gradHexa->_grad._cells[iCell]._linksVal[iLink],
                1.0) == false) {
            GradErr->_type = PBErrTypeUnitTestFailed;
            sprintf(GradErr->_msg, "GradHexaCreateOddQ failed");
            PBErrCatch(GradErr);
        }
        ++iCheck;
    }
}
GradHexaFree(&gradHexa);
gradHexa = GradHexaCreateEvenQ(&dim);
if (gradHexa == NULL ||
    VecIsEqual(&(gradHexa->_grad._dim), &dim) == false ||
    gradHexa->_grad._type != GradTypeHexa ||
    gradHexa->_type != GradHexaTypeEvenQ ||
    gradHexa->_grad._cells == NULL) {
    GradErr->_type = PBErrTypeUnitTestFailed;
    sprintf(GradErr->_msg, "GradHexaCreateEvenQ failed");
}

```

```

    PBErrCatch(GradErr);
}
int checkF[36] = {
    -1, 1, 3, 2, -1, -1,
    -1, -1, -1, 3, 0, -1,
    0, 3, 5, 4, -1, -1,
    1, -1, -1, 5, 2, 0,
    2, 5, -1, -1, -1, -1,
    3, -1, -1, -1, 4, 2
};
iCheck = 0;
for (int iCell = 0; iCell < 6; ++iCell) {
    if (gradHexa->_grad._cells[iCell]._nbLink != 6) {
        GradErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GradErr->_msg, "GradHexaCreateEvenQfailed");
        PBErrCatch(GradErr);
    }
    for (int iLink = 0; iLink < 6; ++iLink) {
        if (gradHexa->_grad._cells[iCell]._links[iLink] !=
            checkF[iCheck] ||
            ISEQUALF(gradHexa->_grad._cells[iCell]._linksVal[iLink],
                1.0) == false) {
            GradErr->_type = PBErrTypeUnitTestFailed;
            sprintf(GradErr->_msg, "GradHexaCreateEvenQ failed");
            PBErrCatch(GradErr);
        }
        ++iCheck;
    }
}
GradHexaFree(&gradHexa);
if (gradSquare != NULL) {
    GradErr->_type = PBErrTypeUnitTestFailed;
    sprintf(GradErr->_msg, "GradHexaFree failed");
    PBErrCatch(GradErr);
}
printf("UnitTestGradCreateFree OK\n");
}

void UnitTestGradCloneIsSame() {
    bool diagLink = true;
    VecShort2D dim = VecShortCreateStatic2D();
    VecSet(&dim, 0, 2); VecSet(&dim, 1, 3);
    GradSquare* gradSquare = GradSquareCreate(&dim, diagLink);
    GradSquare* cloneSquare = GradSquareClone(gradSquare);
    if (cloneSquare == NULL) {
        GradErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GradErr->_msg, "GradSquareClone failed");
        PBErrCatch(GradErr);
    }
    if (GradIsSameAs(gradSquare, cloneSquare) == false) {
        GradErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GradErr->_msg, "GradIsSameAs failed");
        PBErrCatch(GradErr);
    }
}
GradFree(&gradSquare);
GradFree(&cloneSquare);
GradHexa* gradHexa = GradHexaCreateOddQ(&dim);
GradHexa* cloneHexa = GradHexaClone(gradHexa);
if (cloneHexa == NULL) {
    GradErr->_type = PBErrTypeUnitTestFailed;
    sprintf(GradErr->_msg, "GradHexaClone failed");
    PBErrCatch(GradErr);
}

```

```

    }
    if (GradIsSameAs(gradHexa, cloneHexa) == false) {
        GradErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GradErr->_msg, "GradIsSameAs failed");
        PBErrCatch(GradErr);
    }
    GradFree(&gradHexa);
    GradFree(&cloneHexa);
    printf("UnitTestGradCloneIsSame OK\n");
}

void UnitTestGradGetSet() {
    bool diagLink = true;
    VecShort2D dim = VecShortCreateStatic2D();
    VecSet(&dim, 0, 2); VecSet(&dim, 1, 3);
    GradSquare* gradSquare = GradSquareCreate(&dim, diagLink);
    GradHexa* gradHexa = GradHexaCreateOddQ(&dim);
    if (GradGetArea(gradSquare) != 6) {
        GradErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GradErr->_msg, "GradGetArea failed");
        PBErrCatch(GradErr);
    }
    if (GradCellAt(gradSquare, 1) != gradSquare->_grad._cells + 1) {
        GradErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GradErr->_msg, "GradGetCell failed");
        PBErrCatch(GradErr);
    }
    VecShort2D pos = VecShortCreateStatic2D();
    VecSet(&pos, 0, 1); VecSet(&pos, 1, 2);
    if (GradCellAt(gradSquare, &pos) != gradSquare->_grad._cells + 5) {
        GradErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GradErr->_msg, "GradGetCell failed");
        PBErrCatch(GradErr);
    }
    if (GradGetType(gradSquare) != GradTypeSquare) {
        GradErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GradErr->_msg, "GradGetType failed");
        PBErrCatch(GradErr);
    }
    if (GradHexaGetType(gradHexa) != GradHexaTypeOddQ) {
        GradErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GradErr->_msg, "GradHexaGetType failed");
        PBErrCatch(GradErr);
    }
    if (GradSquareHasDiagonalLink(gradSquare) != diagLink) {
        GradErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GradErr->_msg, "GradSquareHasDiagonalLink failed");
        PBErrCatch(GradErr);
    }
    GradFree(&gradSquare);
    GradFree(&gradHexa);
    printf("UnitTestGradGetSet OK\n");
}

void UnitTestGradResetFlagBlocked() {
    bool diagLink = true;
    VecShort2D dim = VecShortCreateStatic2D();
    VecSet(&dim, 0, 2); VecSet(&dim, 1, 3);
    GradSquare* grad = GradSquareCreate(&dim, diagLink);
    for (int iCell = GradGetArea(grad); iCell--;)
        GradCellSetBlocked(GradCellAt(grad, iCell), true);
    GradResetFlagBlocked(grad);
}

```

```

for (int iCell = GradGetArea(grad); iCell--;)
    if (GradCellIsBlocked(GradCellAt(grad, iCell)) != false) {
        GradErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GradErr->_msg, "GradResetFlagBlocked failed");
        PBErrCatch(GradErr);
    }
GradFree(&grad);
printf("UnitTestGradResetFlagBlocked OK\n");
}

void UnitTestGradEditLinks() {
    bool diagLink = true;
    VecShort2D dim = VecShortCreateStatic2D();
    VecSet(&dim, 0, 2); VecSet(&dim, 1, 3);
    GradSquare* grad = GradSquareCreate(&dim, diagLink);
    GradRemoveLinkTo(grad, 0, 1, false);
    if (GradCellGetLink(GradCellAt(grad, 0), GradSquareDirE) != -1 ||
        GradCellGetLink(GradCellAt(grad, 1), GradSquareDirW) != 0) {
        GradErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GradErr->_msg, "GradRemoveLinkTo failed");
        PBErrCatch(GradErr);
    }
    GradAddLinkTo(grad, 0, 1, false);
    if (GradCellGetLink(GradCellAt(grad, 0), GradSquareDirE) != 1 ||
        GradCellGetLink(GradCellAt(grad, 1), GradSquareDirW) != 0) {
        GradErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GradErr->_msg, "GradAddLinkTo failed");
        PBErrCatch(GradErr);
    }
    GradRemoveLinkTo(grad, 2, 3, true);
    if (GradCellGetLink(GradCellAt(grad, 2), GradSquareDirE) != -1 ||
        GradCellGetLink(GradCellAt(grad, 3), GradSquareDirW) != -1) {
        GradErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GradErr->_msg, "GradRemoveLinkTo failed");
        PBErrCatch(GradErr);
    }
    GradAddLinkTo(grad, 2, 3, true);
    if (GradCellGetLink(GradCellAt(grad, 2), GradSquareDirE) != 3 ||
        GradCellGetLink(GradCellAt(grad, 3), GradSquareDirW) != 2) {
        GradErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GradErr->_msg, "GradAddLinkTo failed");
        PBErrCatch(GradErr);
    }
    VecShort2D from = VecShortCreateStatic2D();
    VecSet(&from, 0, 0); VecSet(&from, 1, 2);
    VecShort2D to = VecShortCreateStatic2D();
    VecSet(&to, 0, 1); VecSet(&to, 1, 2);
    GradRemoveLinkTo(grad, &from, &to, true);
    if (GradCellGetLink(GradCellAt(grad, 4), GradSquareDirE) != -1 ||
        GradCellGetLink(GradCellAt(grad, 5), GradSquareDirW) != -1) {
        GradErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GradErr->_msg, "GradRemoveLinkTo failed");
        PBErrCatch(GradErr);
    }
    GradAddLinkTo(grad, &from, &to, true);
    if (GradCellGetLink(GradCellAt(grad, 4), GradSquareDirE) != 5 ||
        GradCellGetLink(GradCellAt(grad, 5), GradSquareDirW) != 4) {
        GradErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GradErr->_msg, "GradAddLinkTo failed");
        PBErrCatch(GradErr);
    }
    GradRemoveLinkToward(grad, 0, GradSquareDirE, false);
}

```

```

if (GradCellGetLink(GradCellAt(grad, 0), GradSquareDirE) != -1 ||
    GradCellGetLink(GradCellAt(grad, 1), GradSquareDirW) != 0) {
    GradErr->_type = PBErrTypeUnitTestFailed;
    sprintf(GradErr->_msg, "GradRemoveLinkToward failed");
    PBErrCatch(GradErr);
}
GradAddLinkToward(grad, 0, GradSquareDirE, false);
if (GradCellGetLink(GradCellAt(grad, 0), GradSquareDirE) != 1 ||
    GradCellGetLink(GradCellAt(grad, 1), GradSquareDirW) != 0) {
    GradErr->_type = PBErrTypeUnitTestFailed;
    sprintf(GradErr->_msg, "GradAddLinkToward failed");
    PBErrCatch(GradErr);
}
GradRemoveLinkToward(grad, 2, GradSquareDirE, true);
if (GradCellGetLink(GradCellAt(grad, 2), GradSquareDirE) != -1 ||
    GradCellGetLink(GradCellAt(grad, 3), GradSquareDirW) != -1) {
    GradErr->_type = PBErrTypeUnitTestFailed;
    sprintf(GradErr->_msg, "GradRemoveLinkToward failed");
    PBErrCatch(GradErr);
}
GradAddLinkToward(grad, 2, GradSquareDirE, true);
if (GradCellGetLink(GradCellAt(grad, 2), GradSquareDirE) != 3 ||
    GradCellGetLink(GradCellAt(grad, 3), GradSquareDirW) != 2) {
    GradErr->_type = PBErrTypeUnitTestFailed;
    sprintf(GradErr->_msg, "GradAddLinkToward failed");
    PBErrCatch(GradErr);
}
GradRemoveLinkToward(grad, &from, GradSquareDirE, true);
if (GradCellGetLink(GradCellAt(grad, 4), GradSquareDirE) != -1 ||
    GradCellGetLink(GradCellAt(grad, 5), GradSquareDirW) != -1) {
    GradErr->_type = PBErrTypeUnitTestFailed;
    sprintf(GradErr->_msg, "GradRemoveLinkToward failed");
    PBErrCatch(GradErr);
}
GradAddLinkToward(grad, &from, GradSquareDirE, true);
if (GradCellGetLink(GradCellAt(grad, 4), GradSquareDirE) != 5 ||
    GradCellGetLink(GradCellAt(grad, 5), GradSquareDirW) != 4) {
    GradErr->_type = PBErrTypeUnitTestFailed;
    sprintf(GradErr->_msg, "GradAddLinkToward failed");
    PBErrCatch(GradErr);
}
GradRemoveAllLink(grad, 2, false);
if (GradCellGetLink(GradCellAt(grad, 2), GradSquareDirN) != -1 ||
    GradCellGetLink(GradCellAt(grad, 2), GradSquareDirNE) != -1 ||
    GradCellGetLink(GradCellAt(grad, 2), GradSquareDirE) != -1 ||
    GradCellGetLink(GradCellAt(grad, 2), GradSquareDirSE) != -1 ||
    GradCellGetLink(GradCellAt(grad, 2), GradSquareDirS) != -1 ||
    GradCellGetLink(GradCellAt(grad, 0), GradSquareDirS) != 2 ||
    GradCellGetLink(GradCellAt(grad, 1), GradSquareDirSW) != 2 ||
    GradCellGetLink(GradCellAt(grad, 3), GradSquareDirW) != 2 ||
    GradCellGetLink(GradCellAt(grad, 5), GradSquareDirNW) != 2 ||
    GradCellGetLink(GradCellAt(grad, 4), GradSquareDirN) != 2) {
    GradErr->_type = PBErrTypeUnitTestFailed;
    sprintf(GradErr->_msg, "GradRemoveAllLink failed");
    PBErrCatch(GradErr);
}
GradAddAllLink(grad, 2, false);
if (GradCellGetLink(GradCellAt(grad, 2), GradSquareDirN) != 0 ||
    GradCellGetLink(GradCellAt(grad, 2), GradSquareDirNE) != 1 ||
    GradCellGetLink(GradCellAt(grad, 2), GradSquareDirE) != 3 ||
    GradCellGetLink(GradCellAt(grad, 2), GradSquareDirSE) != 5 ||
    GradCellGetLink(GradCellAt(grad, 2), GradSquareDirS) != 4 ||

```



```

    GradCellGetLink(GradCellAt(grad, 0), GradSquareDirS) != 2 ||
    GradCellGetLink(GradCellAt(grad, 1), GradSquareDirSW) != 2 ||
    GradCellGetLink(GradCellAt(grad, 3), GradSquareDirW) != 2 ||
    GradCellGetLink(GradCellAt(grad, 5), GradSquareDirNW) != 2 ||
    GradCellGetLink(GradCellAt(grad, 4), GradSquareDirN) != 2) {
    GradErr->_type = PBErrTypeUnitTestFailed;
    sprintf(GradErr->_msg, "GradAddAllLink failed");
    PBErrCatch(GradErr);
}
GradRemoveAllLink(grad, 2, true);
if (GradCellGetLink(GradCellAt(grad, 2), GradSquareDirN) != -1 ||
    GradCellGetLink(GradCellAt(grad, 2), GradSquareDirNE) != -1 ||
    GradCellGetLink(GradCellAt(grad, 2), GradSquareDirE) != -1 ||
    GradCellGetLink(GradCellAt(grad, 2), GradSquareDirSE) != -1 ||
    GradCellGetLink(GradCellAt(grad, 2), GradSquareDirS) != -1 ||
    GradCellGetLink(GradCellAt(grad, 0), GradSquareDirS) != -1 ||
    GradCellGetLink(GradCellAt(grad, 1), GradSquareDirSW) != -1 ||
    GradCellGetLink(GradCellAt(grad, 3), GradSquareDirW) != -1 ||
    GradCellGetLink(GradCellAt(grad, 5), GradSquareDirNW) != -1 ||
    GradCellGetLink(GradCellAt(grad, 4), GradSquareDirN) != -1) {
    GradErr->_type = PBErrTypeUnitTestFailed;
    sprintf(GradErr->_msg, "GradRemoveAllLink failed");
    PBErrCatch(GradErr);
}
GradAddAllLink(grad, 2, true);
if (GradCellGetLink(GradCellAt(grad, 2), GradSquareDirN) != 0 ||
    GradCellGetLink(GradCellAt(grad, 2), GradSquareDirNE) != 1 ||
    GradCellGetLink(GradCellAt(grad, 2), GradSquareDirE) != 3 ||
    GradCellGetLink(GradCellAt(grad, 2), GradSquareDirSE) != 5 ||
    GradCellGetLink(GradCellAt(grad, 2), GradSquareDirS) != 4 ||
    GradCellGetLink(GradCellAt(grad, 0), GradSquareDirS) != 2 ||
    GradCellGetLink(GradCellAt(grad, 1), GradSquareDirSW) != 2 ||
    GradCellGetLink(GradCellAt(grad, 3), GradSquareDirW) != 2 ||
    GradCellGetLink(GradCellAt(grad, 5), GradSquareDirNW) != 2 ||
    GradCellGetLink(GradCellAt(grad, 4), GradSquareDirN) != 2) {
    GradErr->_type = PBErrTypeUnitTestFailed;
    sprintf(GradErr->_msg, "GradAddAllLink failed");
    PBErrCatch(GradErr);
}
VecSet(&from, 0, 0); VecSet(&from, 1, 1);
GradRemoveAllLink(grad, &from, false);
if (GradCellGetLink(GradCellAt(grad, 2), GradSquareDirN) != -1 ||
    GradCellGetLink(GradCellAt(grad, 2), GradSquareDirNE) != -1 ||
    GradCellGetLink(GradCellAt(grad, 2), GradSquareDirE) != -1 ||
    GradCellGetLink(GradCellAt(grad, 2), GradSquareDirSE) != -1 ||
    GradCellGetLink(GradCellAt(grad, 2), GradSquareDirS) != -1 ||
    GradCellGetLink(GradCellAt(grad, 0), GradSquareDirS) != 2 ||
    GradCellGetLink(GradCellAt(grad, 1), GradSquareDirSW) != 2 ||
    GradCellGetLink(GradCellAt(grad, 3), GradSquareDirW) != 2 ||
    GradCellGetLink(GradCellAt(grad, 5), GradSquareDirNW) != 2 ||
    GradCellGetLink(GradCellAt(grad, 4), GradSquareDirN) != 2) {
    GradErr->_type = PBErrTypeUnitTestFailed;
    sprintf(GradErr->_msg, "GradRemoveAllLink failed");
    PBErrCatch(GradErr);
}
GradAddAllLink(grad, &from, false);
if (GradCellGetLink(GradCellAt(grad, 2), GradSquareDirN) != 0 ||
    GradCellGetLink(GradCellAt(grad, 2), GradSquareDirNE) != 1 ||
    GradCellGetLink(GradCellAt(grad, 2), GradSquareDirE) != 3 ||
    GradCellGetLink(GradCellAt(grad, 2), GradSquareDirSE) != 5 ||
    GradCellGetLink(GradCellAt(grad, 2), GradSquareDirS) != 4 ||
    GradCellGetLink(GradCellAt(grad, 0), GradSquareDirS) != 2 ||

```

```

        GradCellGetLink(GradCellAt(grad, 1), GradSquareDirSW) != 2 ||
        GradCellGetLink(GradCellAt(grad, 3), GradSquareDirW) != 2 ||
        GradCellGetLink(GradCellAt(grad, 5), GradSquareDirNW) != 2 ||
        GradCellGetLink(GradCellAt(grad, 4), GradSquareDirN) != 2) {
            GradErr->_type = PBErrTypeUnitTestFailed;
            sprintf(GradErr->_msg, "GradAddAllLink failed");
            PBErrCatch(GradErr);
        }
        GradFree(&grad);
        printf("UnitTestGradEditLinks OK\n");
    }

void UnitTestGradLookupTable() {
    bool diagLink = true;
    VecShort2D dim = VecShortCreateStatic2D();
    VecSet(&dim, 0, 2); VecSet(&dim, 1, 3);
    GradSquare* grad = GradSquareCreate(&dim, diagLink);
    GradCellSetBlocked(GradCellAt(grad, 2), true);
    MatFloat* table = GradGetLookupTableMinDist(grad);
    if (table == NULL) {
        GradErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GradErr->_msg, "GradGetLookupTableMinDist failed");
        PBErrCatch(GradErr);
    }
    float check[36] = {
        -1.000000, 1.000000, -1.000000, 1.414214, 2.828427, 2.414214, 1.000000, -1.000000, -1.000000, 1.000000, 2.414214
    };
    for (int i = 0; i < 36; ++i) {
        if (ISEQUALF(table->_val[i], check[i]) == false) {
            GradErr->_type = PBErrTypeUnitTestFailed;
            sprintf(GradErr->_msg, "GradGetLookupTableMinDist failed");
            PBErrCatch(GradErr);
        }
    }
    GradFree(&grad);
    MatFree(&table);
    printf("UnitTestGradLookupTable OK\n");
}

void UnitTestGradFlood() {
    bool diagLink = true;
    VecShort2D dim = VecShortCreateStatic2D();
    VecSet(&dim, 0, 10); VecSet(&dim, 1, 10);
    GradSquare* grad = GradSquareCreate(&dim, diagLink);
    VecShort2D sources = VecShortCreateStatic2D();
    VecSet(&sources, 0, 12); VecSet(&sources, 1, 98);
    GradCellSetBlocked(GradCellAt(grad, 92), true);
    GradCellSetBlocked(GradCellAt(grad, 32), true);
    GradRemoveAllLink(grad, 8, true);
    GradRemoveAllLink(grad, 18, true);
    GradRemoveAllLink(grad, 19, true);
    float distMax = 20.0;
    int stepMax = 20;
    GradFlood(grad, (VecShort*)&sources, distMax, stepMax);
    VecShort2D pos = VecShortCreateStatic2D();
    int check[100] = {
        0, 0, 0, 0, 0, 0, 0, 0, -1, -1,
        0, 0, 0, 0, 0, 0, 0, 0, -1, -1,
        0, 0, 0, 0, 0, 0, 0, 0, 0, -1,
        0, 0, -1, 0, 0, 0, 0, 0, 1, 1,
        0, 0, 0, 0, 0, 0, 0, 1, 1, 1,
        0, 0, 0, 0, 0, 0, 1, 1, 1, 1,
    };
}

```

```

    0, 0, 0, 0, 1, 1, 1, 1, 1, 1,
    0, 0, -1, 1, 1, 1, 1, 1, 1, 1,
    0, -1, 1, 1, 1, 1, 1, 1, 1, 1,
    -1, 1, -1, 1, 1, 1, 1, 1, 1, 1
};
int iCheck = 0;
do {
    GradCell* cell = GradCellAt(grad, &pos);
    printf("%2d, ", GradCellGetFlood(cell));
    if (VecGet(&pos, 0) == 9) printf("\n");
    if (GradCellGetFlood(cell) != check[iCheck]) {
        GradErr->_type = PBErrTypeUnitTestFailed;
        sprintf(GradErr->_msg, "GradFlood failed");
        //PBErrCatch(GradErr);
    }
    ++iCheck;
} while (VecPStep(&pos, &dim));
int floodArea = GradGetFloodArea(grad, 0);
if (floodArea != 52) {
    GradErr->_type = PBErrTypeUnitTestFailed;
    sprintf(GradErr->_msg, "GradFloodArea failed");
    PBErrCatch(GradErr);
}
floodArea = GradGetFloodArea(grad, 1);
if (floodArea != 38) {
    GradErr->_type = PBErrTypeUnitTestFailed;
    sprintf(GradErr->_msg, "GradFloodArea failed");
    PBErrCatch(GradErr);
}

GradFree(&grad);
printf("UnitTestGradFlood OK\n");
}

void UnitTestGradGetPath() {
    bool diagLink = true;
    VecShort2D dim = VecShortCreateStatic2D();
    VecSet(&dim, 0, 10); VecSet(&dim, 1, 10);
    GradSquare* grad = GradSquareCreate(&dim, diagLink);
    GradRemoveAllLink(grad, 51, true);
    GradRemoveAllLink(grad, 52, true);
    GradRemoveAllLink(grad, 53, true);
    GradRemoveAllLink(grad, 54, true);
    GradCellSetBlocked(GradCellAt(grad, 55), true);
    GradCellSetBlocked(GradCellAt(grad, 56), true);
    GradRemoveAllLink(grad, 58, true);
    GradRemoveAllLink(grad, 59, true);
    MatFloat* lookUp = GradGetLookupTableMinDist(grad);
    int from = 12;
    int to = 85;
    VecShort* path = GradGetPath(grad, from, to, lookUp);
    VecPrint(path, stdout); printf("\n");
    int check[9] = {12,13,24,35,46,57,66,75,85};
    for (int i = 9; i--;) {
        if (VecGet(path, i) != check[i]) {
            GradErr->_type = PBErrTypeUnitTestFailed;
            sprintf(GradErr->_msg, "GradGetPath failed");
            PBErrCatch(GradErr);
        }
    }
    VecFree(&path);
    MatFree(&lookUp);
}

```

```

    GradFree(&grad);
    printf("UnitTestGradGetPath OK\n");
}

void UnitTestGrad() {
    UnitTestGradCreateFree();
    UnitTestGradCloneIsSame();
    UnitTestGradGetSet();
    UnitTestGradResetFlagBlocked();
    UnitTestGradEditLinks();
    UnitTestGradLookupTable();
    UnitTestGradFlood();
    UnitTestGradGetPath();

    printf("UnitTestGrad OK\n");
}

void UnitTestAll() {
    UnitTestGradCell();
    UnitTestGrad();
    printf("UnitTestAll OK\n");
}

int main() {
    UnitTestAll();
    // Return success code
    return 0;
}

```

## 6 Unit tests output

```

UnitTestGradCellCreateFree OK
UnitTestGradCellGetSet OK
UnitTestGradCell OK
UnitTestGradCreateFree OK
UnitTestGradCloneIsSame OK
UnitTestGradGetSet OK
UnitTestGradResetFlagBlocked OK
UnitTestGradEditLinks OK
UnitTestGradLookupTable OK
0, 0, 0, 0, 0, 0, 0, 0, -1, -1,
0, 0, 0, 0, 0, 0, 0, 0, -1, -1,
0, 0, 0, 0, 0, 0, 0, 0, 0, -1,
0, 0, -1, 0, 0, 0, 0, 0, 1, 1,
0, 0, 0, 0, 0, 0, 0, 1, 1, 1,
0, 0, 0, 0, 0, 0, 1, 1, 1, 1,
0, 0, 0, 0, 1, 1, 1, 1, 1, 1,
0, 0, -1, 1, 1, 1, 1, 1, 1, 1,
0, -1, 1, 1, 1, 1, 1, 1, 1, 1,
-1, 1, -1, 1, 1, 1, 1, 1, 1, 1,
UnitTestGradFlood OK
<12,13,24,35,46,57,66,75,85>
UnitTestGradGetPath OK
UnitTestGrad OK
UnitTestAll OK

```