

NeuraMorph

Validation results

P. Baillehache

October 6, 2020

Contents

1	Breast Cancer Wisconsin (Diagnostic) Data Set	4
1.1	NeuraMorph results	4
1.2	Concurrent results	4
1.2.1	Multisurface method	4
1.2.2	Additive logistic regression	5
2	Iris Data Set	6
2.1	NeuraMorph results	6
2.2	Concurrent results	6
2.2.1	Additive logistic regression	6
2.2.2	Neural networks	6
3	Annealing Data Set	8
3.1	NeuraMorph results	8
3.2	Concurrent results	8
3.2.1	Additive logistic regression	8
3.2.2	Rule based classifier	9
4	Arrhythmia Data Set	10
4.1	NeuraMorph results	10
4.2	Concurrent results	10
4.2.1	Additive logistic regression	10
4.2.2	Ensemble classifier, support vector machine and random forest with random sampling	10
4.2.3	Support vector machine	10
5	Agaricus Lepiota Data Set	11
5.1	NeuraMorph results	11
5.2	Concurrent results	11
5.2.1	Additive logistic regression	11
5.2.2	Decision tree	11

6	Solar Flare Data Set	12
6.1	NeuraMorph results	12
6.1.1	Accuracy +/- 0.5	12
6.1.2	Accuracy +/- 1.0	12
6.2	Concurrent results	13
6.2.1	Additive logistic regression	13
7	Abalone Data Set	14
7.1	NeuraMorph results	14
7.1.1	Accuracy +/- 0.5	14
7.1.2	Accuracy +/- 1.0	14
7.2	Concurrent results	15
7.2.1	Additive logistic regression	15
7.2.2	Feed-forward supervised artificial neural networks	15
8	Tic-Tac-Toe Data Set	16
8.1	NeuraMorph results	16
8.2	Concurrent results	16
8.2.1	Additive logistic regression	16
9	Pen Digits Data Set	17
9.1	NeuraMorph results	17
9.2	Concurrent results	18
9.2.1	Additive logistic regression	18
9.2.2	MLP	18
10	Image Segmentation Data Set	19
10.1	NeuraMorph results	19
10.2	Concurrent results	19
10.2.1	Additive logistic regression	19
11	Dermatology Data Set	21
11.1	NeuraMorph results	21
11.2	Concurrent results	21
11.2.1	Additive logistic regression	21
12	Page Blocks Data Set	22
12.1	NeuraMorph results	22
12.2	Concurrent results	22
12.2.1	Additive logistic regression	22
13	Balance Scale Data Set	23
13.1	NeuraMorph results	23
13.2	Concurrent results	23
13.2.1	Additive logistic regression	23
14	Vote Data Set	24
14.1	NeuraMorph results	24
14.2	Concurrent results	24
14.2.1	Additive logistic regression	24

15		25
15.1	NeuraMorph results	25
15.2	Concurrent results	25
15.2.1	Additive logistic regression	25
15.3	Validation result	25

Introduction

This document introduces the validation results of the NeuraMorph algorithm.

Validation has been performed by using NeuraMorph on data sets publicly available on Internet, and comparing the accuracy of prediction made by NeuraMorph with the publicly available results achieved by other algorithms.

To avoid "lucky strike", results introduced here are produced with an instance of the NeuraMorph model selected amongst models produced with a systematic exploration of hyper parameters of the model, and based on its average of prediction accuracy over 5 different random splits of training/test samples.

1 Breast Cancer Wisconsin (Diagnostic) Data Set

Source:

[https://archive.ics.uci.edu/ml/datasets/Breast+Cancer+Wisconsin+\(Diagnostic\)](https://archive.ics.uci.edu/ml/datasets/Breast+Cancer+Wisconsin+(Diagnostic))

1.1 NeuraMorph results

Training parameters:

Nb inputs/outputs	30/2
Nb samples	569
Percentage of training samples	90%
weakUnitThreshold	0.900000
precAcc	0.000010
depth	5
maxLvlDiv	1
nbMaxInputsUnit	2
nbMaxUnitDepth	21
order	2
pca	1
oneHot	1
allHot	0
Time training	16.4s

Results:

Bias prediction (min/avg/sigma/max) and accuracy	c.00	[0.000,0.000,0.000,0.000]	100.00%
	c.01	[0.000,0.000,0.000,0.000]	100.00%
	[0.000,0.000,0.000,0.000]	100.00%
Bias training (min/avg/sigma/max) and accuracy	c.00	[0.000,0.008,0.062,2.000]	99.61%
	c.01	[0.000,0.008,0.062,2.000]	99.61%
	[0.000,0.011,0.062,2.828]	99.61%

1.2 Concurrent results

1.2.1 Multisurface method

”Dr. Wolberg [...] in collaboration with Prof. Mangasarian and two of his graduate students, Rudy Setiono and Kristin Bennett, [developped] a classifier [...] using the multisurface method (MSM) of pattern separation [...] that successfully diagnosed 97% of new cases.”

Source:

<http://pages.cs.wisc.edu/~olvi/uwmp/cancer.html>

1.2.2 Additive logistic regression

”J. Friedman, T. Hastie, R. Tibshirani (1998). Additive Logistic Regression: a Statistical View of Boosting. Stanford University.”

Predictive accuracy: 96.28%

Source:

<https://www.openml.org/f/77> <https://projecteuclid.org/euclid.aos/1016218223>

2 Iris Data Set

Source:

<http://archive.ics.uci.edu/ml/datasets/Iris/>

2.1 NeuraMorph results

Training parameters:

Nb inputs/outputs	4/3
Nb samples	150
Percentage of training samples	90%
weakUnitThreshold	0.975000
precAcc	0.000010
depth	2
maxLvlDiv	1
nbMaxInputsUnit	2
nbMaxUnitDepth	11
order	1
pca	1
oneHot	1
allHot	0
Time training	0.0s

Results:

Bias prediction (min/avg/sigma/max) and accuracy	c.00 [0.000,0.000,0.000,0.000]	100.00%
	c.01 [0.000,0.000,0.000,0.000]	100.00%
	c.02 [0.000,0.000,0.000,0.000]	100.00%
 [0.000,0.000,0.000,0.000]	100.00%
Bias training (min/avg/sigma/max) and accuracy	c.00 [0.000,0.000,0.000,0.000]	100.00%
	c.01 [0.000,0.015,0.086,2.000]	99.26%
	c.02 [0.000,0.015,0.086,2.000]	99.26%
 [0.000,0.021,0.000,2.828]	99.26%

2.2 Concurrent results

2.2.1 Additive logistic regression

”J. Friedman, T. Hastie, R. Tibshirani (1998). Additive Logistic Regression: a Statistical View of Boosting. Stanford University.”

Predictive accuracy: 94.67%

Source:

<https://www.openml.org/f/77> <https://projecteuclid.org/euclid.aos/1016218223>

2.2.2 Neural networks

”Classification of Iris data set, Primož Potocnik, Vitaly Borovinskiy”

Predictive accuracy:
Multilayer perceptron: 96.825% Radial basis function network: 96.825% Probabilistic neural network: 95.238%

Source:

http://lab.fs.uni-lj.si/lasin/wp/IMIT_files/neural/doc/seminar8.pdf

3 Annealing Data Set

Source:

<https://archive.ics.uci.edu/ml/datasets/Annealing>

3.1 NeuraMorph results

Training parameters:

Nb inputs/outputs	77/5
Nb samples	798
Percentage of training samples	90%
weakUnitThreshold	0.800000
precAcc	0.000010
depth	4
maxLvlDiv	3
nbMaxInputsUnit	2
nbMaxUnitDepth	3
order	2
pca	1
oneHot	1
allHot	0
Time training	44.3s

Results:

Bias prediction (min/avg/sigma/max) and accuracy	c.00	[0.000,0.051,0.160,2.000]	97.47%
	c.01	[0.000,0.051,0.160,2.000]	97.47%
	c.02	[0.000,0.000,0.000,0.000]	100.00%
	c.03	[0.000,0.051,0.160,2.000]	97.47%
	c.04	[0.000,0.000,0.000,0.000]	100.00%
	[0.000,0.107,0.160,2.828]	96.20%
Bias training (min/avg/sigma/max) and accuracy	c.00	[0.000,0.028,0.118,2.000]	98.61%
	c.01	[0.000,0.022,0.106,2.000]	98.89%
	c.02	[0.000,0.003,0.037,2.000]	99.86%
	c.03	[0.000,0.003,0.037,2.000]	99.86%
	c.04	[0.000,0.000,0.000,0.000]	100.00%
	[0.000,0.039,0.118,2.828]	98.61%

3.2 Concurrent results

3.2.1 Additive logistic regression

”J. Friedman, T. Hastie, R. Tibshirani (1998). Additive Logistic Regression: a Statistical View of Boosting. Stanford University.”

Predictive accuracy: 99.67%

Source:

<https://www.openml.org/f/77> <https://projecteuclid.org/euclid.aos/1016218223>

3.2.2 Rule based classifier

”Analysis of Different Classification Algorithms Applied to Anneal Dataset Using Data Mining Techniques, V.Kamalakkannan, Dr.D. Ramyachitra, Computer Science Department, Bharathiar University, Coimbatore, Tamil Nadu, India”

Predictive accuracy:

Naive Bayes: 97.66%

SMO: 97.01%

OneR: 83.65%

J48: 95.88%

Source:

http://www.istpublications.com/temp/16_V_Kamalakkannan_Et_al_.pdf

4 Arrhythmia Data Set

Source:

<https://archive.ics.uci.edu/ml/datasets/arrhythmia>

4.1 NeuraMorph results

4.2 Concurrent results

4.2.1 Additive logistic regression

”J. Friedman, T. Hastie, R. Tibshirani (1998). Additive Logistic Regression: a Statistical View of Boosting. Stanford University.”

Predictive accuracy: 74.12%

Source:

<https://www.openml.org/f/77> <https://projecteuclid.org/euclid.aos/1016218223>

4.2.2 Ensemble classifier, support vector machine and random forest with random sampling

”Arrhythmia Disease Classification and Mobile Based System Design, Soha Samir AbdElMoneem, Hany Hanafy Said, and Amani Anwar Saad, Computer Engineering Department, Arab Academy for Science, Technology and Maritime Transport Abukir, Alexandria, Egypt”

Predictive accuracy: 98.18%

Source:

<https://iopscience.iop.org/article/10.1088/1742-6596/1447/1/012014/pdf>

4.2.3 Support vector machine

”Multiclass Classification of Cardiac Arrhythmia Using Improved Feature Selection and SVM Invariants Anam Mustaqeem, Syed Muhammad Anwar, and Muahammad Majid, University of Engineering and Technology, Taxila, Pakistan”

Predictive accuracy: 92.07%

Source:

<https://alendar.google.com/calendar/r/customday/2020/7/14?pli=1>

5 Agaricus Lepiota Data Set

Source:

<https://archive.ics.uci.edu/ml/datasets/mushroom>

5.1 NeuraMorph results

Training parameters:

Nb inputs/outputs	111/1
Nb samples	8124
Percentage of training samples	90%
weakUnitThreshold	0.800000
precAcc	0.000010
depth	6
maxLvlDiv	1
nbMaxInputsUnit	2
nbMaxUnitDepth	3
order	1
pca	0
oneHot	1
allHot	0
Time training	42.8s

Results:

Bias prediction (min/avg/sigma/max) and accuracy	c.00 [0.000,0.002,0.035,2.000] 99.88%
Bias training (min/avg/sigma/max) and accuracy	c.00 [0.000,0.002,0.031,2.000] 99.90%

5.2 Concurrent results

5.2.1 Additive logistic regression

”J. Friedman, T. Hastie, R. Tibshirani (1998). Additive Logistic Regression: a Statistical View of Boosting. Stanford University.”

Predictive accuracy: 100.0%

Source:

<https://www.openml.org/f/77> <https://projecteuclid.org/euclid.aos/1016218223>

5.2.2 Decision tree

”Agaricus Lepiota Analysis, Manikanda Prabhu M and Jerin Stanley Daniel J”

Predictive accuracy: 99.0%

Source:

<https://rpubs.com/ManikandaPrabhuM/JerinDaniel-agaricuslepiota>

6 Solar Flare Data Set

Source:

https://www.openml.org/data/get_csv/3597/dataset_116_solar-flare_2.arff

6.1 NeuraMorph results

6.1.1 Accuracy +/- 0.5

Training parameters:

Nb inputs/outputs	24/3
Nb samples	1066
Percentage of training samples	90%
weakUnitThreshold	0.800000
precAcc	0.500000
depth	2
maxLvlDiv	2
nbMaxInputsUnit	2
nbMaxUnitDepth	3
order	2
pca	1
oneHot	0
allHot	0
Time training	1.9s

Results:

Bias prediction (min/avg/sigma/max) and accuracy	c.00	[0.056,0.593,0.900,5.856]	75.47%
	c.01	[0.032,0.105,0.138,2.018]	94.34%
	c.02	[0.000,0.009,0.000,1.000]	99.06%
	[0.065,0.649,0.828,5.856]	89.62%
Bias training (min/avg/sigma/max) and accuracy	c.00	[0.031,0.392,0.461,6.940]	80.21%
	c.01	[0.000,0.073,0.177,5.018]	96.98%
	c.02	[0.000,0.004,0.000,0.751]	99.69%
	[0.065,0.422,0.500,6.940]	92.29%

6.1.2 Accuracy +/- 1.0

Training parameters:

Nb inputs/outputs	24/3
Nb samples	1066
Percentage of training samples	90%
weakUnitThreshold	0.800000
precAcc	1.000000
depth	2
maxLvlDiv	2
nbMaxInputsUnit	2
nbMaxUnitDepth	3
order	2
pca	1
oneHot	0
allHot	0
Time training	1.9s

Results:

Bias prediction (min/avg/sigma/max) and accuracy	c.00	[0.056,0.593,0.900,5.856]	87.74%
	c.01	[0.032,0.105,0.138,2.018]	98.11%
	c.02	[0.000,0.009,0.000,1.000]	99.06%
	[0.065,0.649,0.828,5.856]	94.97%
Bias training (min/avg/sigma/max) and accuracy	c.00	[0.031,0.392,0.461,6.940]	91.67%
	c.01	[0.000,0.073,0.177,5.018]	99.58%
	c.02	[0.000,0.004,0.000,0.751]	100.00%
	[0.065,0.422,0.500,6.940]	97.08%

6.2 Concurrent results

6.2.1 Additive logistic regression

”J. Friedman, T. Hastie, R. Tibshirani (1998). Additive Logistic Regression: a Statistical View of Boosting. Stanford University.”

Predictive accuracy: 99.15%

Source:

<https://www.openml.org/f/77> <https://projecteuclid.org/euclid.aos/1016218223>

7 Abalone Data Set

Source:

<http://archive.ics.uci.edu/ml/datasets/Abalone>

7.1 NeuraMorph results

7.1.1 Accuracy +/- 0.5

Training parameters:

Nb inputs/outputs	10/1
Nb samples	4177
Percentage of training samples	90%
weakUnitThreshold	0.800000
precAcc	0.500000
depth	2
maxLvlDiv	0
nbMaxInputsUnit	2
nbMaxUnitDepth	3
order	1
pca	1
oneHot	0
allHot	0
Time training	0.2s

Results:

Bias prediction (min/avg/sigma/max) and accuracy	c.00 [0.004,1.488,1.155,12.157] 24.94%
Bias training (min/avg/sigma/max) and accuracy	c.00 [0.001,1.636,1.295,15.673] 23.24%

7.1.2 Accuracy +/- 1.0

Training parameters:

Nb inputs/outputs	10/1
Nb samples	4177
Percentage of training samples	90%
weakUnitThreshold	0.800000
precAcc	1.000000
depth	2
maxLvlDiv	0
nbMaxInputsUnit	2
nbMaxUnitDepth	3
order	1
pca	1
oneHot	0
allHot	0
Time training	0.2s

Results:

Bias prediction (min/avg/sigma/max) and accuracy	c.00 [0.004,1.488,1.155,12.157] 45.32%
Bias training (min/avg/sigma/max) and accuracy	c.00 [0.001,1.636,1.295,15.673] 42.45%

7.2 Concurrent results

7.2.1 Additive logistic regression

”J. Friedman, T. Hastie, R. Tibshirani (1998). Additive Logistic Regression: a Statistical View of Boosting. Stanford University.”

Predictive accuracy: 26.45%

Source:

<https://www.openml.org/f/77> <https://projecteuclid.org/euclid.aos/1016218223>

7.2.2 Feed-forward supervised artificial neural networks

”Extensions to the Cascade-Correlation architecture and benchmarking of feed-forward supervised artificial neural networks, Samuel George Waugh, BSc (Hons), Submitted in fulfilment of the requirements for the degree of Doctor of Philosophy, University of Tasmania, August, 1995”

Predictive accuracy: 26.25%

Source:

https://eprints.utas.edu.au/21965/1/wholeWaughSamuelGeorge1997_thesis.pdf

8 Tic-Tac-Toe Data Set

Source:

<https://archive.ics.uci.edu/ml/datasets/Tic-Tac-Toe+Endgame>

8.1 NeuraMorph results

Training parameters:

Nb inputs/outputs	9/1
Nb samples	958
Percentage of training samples	90%
weakUnitThreshold	0.800000
precAcc	0.000010
depth	7
maxLvlDiv	0
nbMaxInputsUnit	2
nbMaxUnitDepth	3
order	2
pca	1
oneHot	1
allHot	0
Time training	0.3s

Results:

Bias prediction (min/avg/sigma/max) and accuracy	c.00 [0.000,0.000,0.000,0.000] 100.00%
Bias training (min/avg/sigma/max) and accuracy	c.00 [0.000,0.007,0.059,2.000] 99.65%

8.2 Concurrent results

8.2.1 Additive logistic regression

”J. Friedman, T. Hastie, R. Tibshirani (1998). Additive Logistic Regression: a Statistical View of Boosting. Stanford University.”

Predictive accuracy: 98.23%

Source:

<https://www.openml.org/f/77> <https://projecteuclid.org/euclid.aos/1016218223>

9 Pen Digits Data Set

Source:

<https://archive.ics.uci.edu/ml/datasets/Pen-Based+Recognition+of+Handwritten+Digits>

9.1 NeuraMorph results

Training parameters:

Nb inputs/outputs	16/10
Nb samples	7494
Percentage of training samples	90%
weakUnitThreshold	0.800000
precAcc	0.000010
depth	4
maxLvlDiv	2
nbMaxInputsUnit	2
nbMaxUnitDepth	3
order	2
pca	1
oneHot	1
allHot	0
Time training	361.6s

Results:

Bias prediction (min/avg/sigma/max) and accuracy	c.00	[0.000,0.043,0.146,2.000]	97.86%
	c.01	[0.000,0.013,0.082,2.000]	99.33%
	c.02	[0.000,0.051,0.159,2.000]	97.46%
	c.03	[0.000,0.029,0.121,2.000]	98.53%
	c.04	[0.000,0.051,0.159,2.000]	97.46%
	c.05	[0.000,0.016,0.090,2.000]	99.20%
	c.06	[0.000,0.027,0.116,2.000]	98.66%
	c.07	[0.000,0.061,0.175,2.000]	96.93%
	c.08	[0.000,0.077,0.197,2.000]	96.13%
	c.09	[0.000,0.043,0.146,2.000]	97.86%
	[0.000,0.291,0.146,2.828]	89.72%
Bias training (min/avg/sigma/max) and accuracy	c.00	[0.000,0.013,0.082,2.000]	99.33%
	c.01	[0.000,0.001,0.024,2.000]	99.94%
	c.02	[0.000,0.016,0.089,2.000]	99.20%
	c.03	[0.000,0.017,0.092,2.000]	99.15%
	c.04	[0.000,0.021,0.103,2.000]	98.93%
	c.05	[0.000,0.003,0.037,2.000]	99.87%
	c.06	[0.000,0.006,0.054,2.000]	99.70%
	c.07	[0.000,0.023,0.108,2.000]	98.83%
	c.08	[0.000,0.038,0.137,2.000]	98.12%
	c.09	[0.000,0.006,0.056,2.000]	99.69%
	[0.000,0.102,0.082,2.828]	96.38%

9.2 Concurrent results

9.2.1 Additive logistic regression

”J. Friedman, T. Hastie, R. Tibshirani (1998). Additive Logistic Regression: a Statistical View of Boosting. Stanford University.”

Predictive accuracy: 98.17%

Source:

<https://www.openml.org/f/77> <https://projecteuclid.org/euclid.aos/1016218223>

9.2.2 MLP

”COMBINING MULTIPLE CLASSIFIERS FOR PEN-BASED HAND-WRITTEN DIGIT RECOGNITION by Fevzi Alimoglu, B.S. in Computer Engineering, Bogazici University, 1994”

Predictive accuracy: 97.03%

Source:

<http://citeseerx.ist.psu.edu/viewdoc/download?doi=10.1.1.25.6299rep=rep1type=pdf>

10 Image Segmentation Data Set

Source:

<http://archive.ics.uci.edu/ml/datasets/image+segmentation>

10.1 NeuraMorph results

Training parameters:

Nb inputs/outputs	18/7
Nb samples	2100
Percentage of training samples	90%
weakUnitThreshold	0.800000
precAcc	0.000010
depth	1
maxLvlDiv	3
nbMaxInputsUnit	2
nbMaxUnitDepth	3
order	2
pca	1
oneHot	1
allHot	0
Time training	5.9s

Results:

Bias prediction (min/avg/sigma/max) and accuracy	c.00	[0.000,0.029,0.120,2.000]	98.57%
	c.01	[0.000,0.076,0.196,2.000]	96.19%
	c.02	[0.000,0.038,0.138,2.000]	98.10%
	c.03	[0.000,0.095,0.219,2.000]	95.24%
	c.04	[0.000,0.000,0.000,0.000]	100.00%
	c.05	[0.000,0.133,0.259,2.000]	93.33%
	c.06	[0.000,0.010,0.069,2.000]	99.52%
	[0.000,0.269,0.120,2.828]	90.48%
Bias training (min/avg/sigma/max) and accuracy	c.00	[0.000,0.034,0.130,2.000]	98.31%
	c.01	[0.000,0.056,0.168,2.000]	97.20%
	c.02	[0.000,0.004,0.046,2.000]	99.79%
	c.03	[0.000,0.061,0.175,2.000]	96.93%
	c.04	[0.000,0.001,0.023,2.000]	99.95%
	c.05	[0.000,0.068,0.184,2.000]	96.61%
	c.06	[0.000,0.000,0.000,0.000]	100.00%
	[0.000,0.159,0.130,2.828]	94.39%

10.2 Concurrent results

10.2.1 Additive logistic regression

”J. Friedman, T. Hastie, R. Tibshirani (1998). Additive Logistic Regression: a Statistical View of Boosting. Stanford University.”

Predictive accuracy: 97.58%

Source:

<https://www.openml.org/f/77> <https://projecteuclid.org/euclid.aos/1016218223>

11 Dermatology Data Set

Source:

<https://www.openml.org/d/35>

11.1 NeuraMorph results

Training parameters:

Nb inputs/outputs	34/6
Nb samples	358
Percentage of training samples	90%
weakUnitThreshold	0.800000
precAcc	0.000010
depth	1
maxLvlDiv	2
nbMaxInputsUnit	2
nbMaxUnitDepth	3
order	2
pca	1
oneHot	1
allHot	0
Time training	2.2s

Results:

Bias prediction (min/avg/sigma/max) and accuracy	c.00	[0.000,0.000,0.000,0.000]	100.00%
	c.01	[0.000,0.000,0.000,0.000]	100.00%
	c.02	[0.000,0.171,0.297,2.000]	91.43%
	c.03	[0.000,0.171,0.297,2.000]	91.43%
	c.04	[0.000,0.114,0.243,2.000]	94.29%
	c.05	[0.000,0.000,0.000,0.000]	100.00%
	[0.000,0.323,0.000,2.828]	88.57%
Bias training (min/avg/sigma/max) and accuracy	c.00	[0.000,0.025,0.111,2.000]	98.76%
	c.01	[0.000,0.000,0.000,0.000]	100.00%
	c.02	[0.000,0.074,0.193,2.000]	96.28%
	c.03	[0.000,0.056,0.167,2.000]	97.21%
	c.04	[0.000,0.012,0.079,2.000]	99.38%
	c.05	[0.000,0.006,0.056,2.000]	99.69%
	[0.000,0.123,0.111,2.828]	95.67%

11.2 Concurrent results

11.2.1 Additive logistic regression

”J. Friedman, T. Hastie, R. Tibshirani (1998). Additive Logistic Regression: a Statistical View of Boosting. Stanford University.”

Predictive accuracy: 97.27%

Source:

<https://www.openml.org/f/77> <https://projecteuclid.org/euclid.aos/1016218223>

12 Page Blocks Data Set

Source:

<https://www.openml.org/d/30>

12.1 NeuraMorph results

Training parameters:

Nb inputs/outputs	10/5
Nb samples	5473
Percentage of training samples	90%
weakUnitThreshold	0.800000
precAcc	0.000010
depth	1
maxLvlDiv	2
nbMaxInputsUnit	2
nbMaxUnitDepth	3
order	3
pca	1
oneHot	1
allHot	0
Time training	4.1s

Results:

Bias prediction (min/avg/sigma/max) and accuracy	c.00	[0.000,0.037,0.135,2.000]	98.17%
	c.01	[0.000,0.029,0.121,2.000]	98.54%
	c.02	[0.000,0.004,0.043,2.000]	99.82%
	c.03	[0.000,0.066,0.182,2.000]	96.71%
	c.04	[0.000,0.011,0.074,2.000]	99.45%
	[0.000,0.103,0.135,2.828]	96.34%
Bias training (min/avg/sigma/max) and accuracy	c.00	[0.000,0.028,0.118,2.000]	98.60%
	c.01	[0.000,0.017,0.093,2.000]	99.13%
	c.02	[0.000,0.005,0.051,2.000]	99.74%
	c.03	[0.000,0.052,0.161,2.000]	97.40%
	c.04	[0.000,0.005,0.051,2.000]	99.74%
	[0.000,0.076,0.118,2.828]	97.30%

12.2 Concurrent results

12.2.1 Additive logistic regression

”J. Friedman, T. Hastie, R. Tibshirani (1998). Additive Logistic Regression: a Statistical View of Boosting. Stanford University.”

Predictive accuracy: 97.27%

Source:

<https://www.openml.org/f/77> <https://projecteuclid.org/euclid.aos/1016218223>

13 Balance Scale Data Set

Source:

<http://archive.ics.uci.edu/ml/datasets/balance+scale>

13.1 NeuraMorph results

Training parameters:

Nb inputs/outputs	4/3
Nb samples	625
Percentage of training samples	90%
weakUnitThreshold	0.800000
precAcc	0.000010
depth	4
maxLvlDiv	3
nbMaxInputsUnit	2
nbMaxUnitDepth	3
order	1
pca	1
oneHot	1
allHot	0
Time training	0.6s

Results:

Bias prediction (min/avg/sigma/max) and accuracy	c.00	[0.000,0.129,0.256,2.000]	93.55%
	c.01	[0.000,0.032,0.128,2.000]	98.39%
	c.02	[0.000,0.161,0.286,2.000]	91.94%
	[0.000,0.228,0.256,2.828]	91.94%
Bias training (min/avg/sigma/max) and accuracy	c.00	[0.000,0.000,0.000,0.000]	100.00%
	c.01	[0.000,0.000,0.000,0.000]	100.00%
	c.02	[0.000,0.000,0.000,0.000]	100.00%
	[0.000,0.000,0.000,0.000]	100.00%

13.2 Concurrent results

13.2.1 Additive logistic regression

”J. Friedman, T. Hastie, R. Tibshirani (1998). Additive Logistic Regression: a Statistical View of Boosting. Stanford University.”

Predictive accuracy: 96.48%

Source:

<https://www.openml.org/f/77> <https://projecteuclid.org/euclid.aos/1016218223>

14 Vote Data Set

Source:

<https://www.openml.org/d/56>

14.1 NeuraMorph results

Training parameters:

Nb inputs/outputs	48/1
Nb samples	435
Percentage of training samples	90%
weakUnitThreshold	0.800000
precAcc	0.000010
depth	1
maxLvlDiv	0
nbMaxInputsUnit	2
nbMaxUnitDepth	3
order	1
pca	1
oneHot	1
allHot	0
Time training	0.3s

Results:

Bias prediction (min/avg/sigma/max) and accuracy	c.00 [0.000,0.093,0.218,2.000] 95.35%
Bias training (min/avg/sigma/max) and accuracy	c.00 [0.000,0.087,0.209,2.000] 95.66%

14.2 Concurrent results

14.2.1 Additive logistic regression

”J. Friedman, T. Hastie, R. Tibshirani (1998). Additive Logistic Regression: a Statistical View of Boosting. Stanford University.”

Predictive accuracy: 95.86%

Source:

<https://www.openml.org/f/77> <https://projecteuclid.org/euclid.aos/1016218223>

15

Source:

<https://>

15.1 NeuraMorph results

15.2 Concurrent results

15.2.1 Additive logistic regression

””

Source:

<http://>

15.3 Validation result

NeuraMorph performs as well as the concurrent algorithm(s) on this data set.