

NeuraMorph

P. Baillehache

September 16, 2020

Contents

1	Definitions	1
2	Interface	1
3	Code	10
3.1	neuramorph.c	10
3.2	neuramorph-inline.c	41
4	Makefile	59
5	Unit tests	60
6	Unit tests output	84

Introduction

NeuraMorph is a C library providing structures and functions to implement a neural network.

It uses the PBErr, PBMath, GSet library.

1 Definitions

2 Interface

```
// ===== NEURAMORPH.H =====
```

```

#ifndef NEURAMORPH_H
#define NEURAMORPH_H

// ===== Include =====

#include <stdlib.h>
#include <stdio.h>
#include <math.h>
#include <string.h>
#include <stdbool.h>
#include "pberr.h"
#include "pbmath.h"
#include "gset.h"
#include "gdataset.h"
#include "bcurve.h"

// ---- NeuraMorphUnit

// ===== Data structure =====

typedef struct NeuraMorphUnit {

    // Input indices in parent NeuraMorph
    VecLong* iInputs;

    // Output indices in parent NeuraMorph
    VecLong* iOutputs;

    // Lowest and highest values for filtering inputs
    VecFloat* lowFilters;
    VecFloat* highFilters;

    // Lowest and highest values of outputs
    VecFloat* lowOutputs;
    VecFloat* highOutputs;

    // Vector to memorize the output values
    VecFloat* outputs;

    // Transfer function
    BBody* transfer;

    // Working variable to avoid reallocation of memory at each Evaluate()
    VecFloat* unitInputs;

    // Variable to memorize the value of the unit during training
    float value;

    long nbTrainingSample;

} NeuraMorphUnit;

// ===== Functions declaration =====

// Create a new NeuraMorphUnit between the input 'iInputs' and the
// outputs 'iOutputs'
NeuraMorphUnit* NeuraMorphUnitCreate(
    const VecLong* iInputs,
    const VecLong* iOutputs);

// Free the memory used by the NeuraMorphUnit 'that'
void NeuraMorphUnitFree(NeuraMorphUnit** that);

```

```

// Get the input indices of the NeuraMorphUnit 'that'
#if BUILDMODE != 0
static inline
#endif
const VecLong* NMUnitIInputs(const NeuraMorphUnit* that);

// Get the output indices of the NeuraMorphUnit 'that'
#if BUILDMODE != 0
static inline
#endif
const VecLong* NMUnitIOutputs(const NeuraMorphUnit* that);

// Get the output values of the NeuraMorphUnit 'that'
#if BUILDMODE != 0
static inline
#endif
const VecFloat* NMUnitOutputs(const NeuraMorphUnit* that);

// Calculate the outputs for the 'inputs' with the NeuraMorphUnit 'that'
// Update 'that->outputs'
void NMUnitEvaluate(
    NeuraMorphUnit* that,
    const VecFloat* inputs);

// Get the number of input values of the NeuraMorphUnit 'that'
#if BUILDMODE != 0
static inline
#endif
long NMUnitGetNbInputs(const NeuraMorphUnit* that);

// Get the number of output values of the NeuraMorphUnit 'that'
#if BUILDMODE != 0
static inline
#endif
long NMUnitGetNbOutputs(const NeuraMorphUnit* that);

// Get the number of coefficients in the transfer function of
// the NeuraMorphUnit 'that'
#if BUILDMODE != 0
static inline
#endif
long NMUnitGetNbCoeffs(const NeuraMorphUnit* that);

// Get the value of the NeuraMorphUnit 'that'
#if BUILDMODE != 0
static inline
#endif
float NMUnitGetValue(const NeuraMorphUnit* that);

// Set the value of the NeuraMorphUnit 'that' to 'val'
#if BUILDMODE != 0
static inline
#endif
void NMUnitSetValue(
    NeuraMorphUnit* that,
    float val);

// Print the NeuraMorphUnit 'that' on the 'stream'
void NMUnitPrint(
    const NeuraMorphUnit* that,
    FILE* stream);

```

```

#define NMUnitPrintln(T, S) \
    do {NMUnitPrint(T, S);fprintf(S, "\n");} while (false)

// ----- NeuraMorph

// ===== Data structure =====

typedef struct NeuraMorph {

    // Number of inputs and outputs
    long nbInput;
    long nbOutput;

    // Inputs and outputs values
    VecFloat* inputs;
    VecFloat* outputs;

    // Internal values
    VecFloat* hiddens;

    // Lowest and highest values for internal values
    VecFloat* lowHiddens;
    VecFloat* highHiddens;

    // Flag to memorize if the outputs are to be seen as one hot encoding
    bool flagOneHot;

    // GSet of NeuraMorphUnit
    GSet units;

} NeuraMorph;

// ===== Functions declaration =====

// Create a new NeuraMorph with 'nbInput' inputs and 'nbOutput' outputs
NeuraMorph* NeuraMorphCreate(
    long nbInput,
    long nbOutput);

// Free the memory used by the NeuraMorph 'that'
void NeuraMorphFree(NeuraMorph** that);

// Get the number of input values of the NeuraMorph 'that'
#if BUILDMODE != 0
static inline
#endif
long NMGetNbInput(const NeuraMorph* that);

// Get the number of output values of the NeuraMorph 'that'
#if BUILDMODE != 0
static inline
#endif
long NMGetNbOutput(const NeuraMorph* that);

// Get the input values of the NeuraMorph 'that'
#if BUILDMODE != 0
static inline
#endif
VecFloat* NMInputs(NeuraMorph* that);

// Get the output values of the NeuraMorph 'that'
#if BUILDMODE != 0

```

```

static inline
#endif
const VecFloat* NMOutputs(const NeuraMorph* that);

// Get the hidden values of the NeuraMorph 'that'
#if BUILDMODE != 0
static inline
#endif
const VecFloat* NMHiddens(const NeuraMorph* that);

// Get the lowest bound of hidden values of the NeuraMorph 'that'
#if BUILDMODE != 0
static inline
#endif
const VecFloat* NMLowHiddens(const NeuraMorph* that);

// Get the highest bound of hidden values of the NeuraMorph 'that'
#if BUILDMODE != 0
static inline
#endif
const VecFloat* NMHighHiddens(const NeuraMorph* that);

// Get the number of hidden values of the NeuraMorph 'that'
#if BUILDMODE != 0
static inline
#endif
long NMGetNbHidden(const NeuraMorph* that);

// Set the number of hidden values of the NeuraMorph 'that' to 'nb'
#if BUILDMODE != 0
static inline
#endif
void NMSetNbHidden(
    NeuraMorph* that,
    long nb);

// Get the flag for one hot encoding of the NeuraMorph 'that'
#if BUILDMODE != 0
static inline
#endif
bool NMGetFlagOneHot(const NeuraMorph* that);

// Set the flag for one hot encoding of the NeuraMorph 'that' to 'flag'
#if BUILDMODE != 0
static inline
#endif
void NMSetFlagOneHot(
    NeuraMorph* that,
    bool flag);

// Add one NeuraMorphUnit with input and output indices 'iInputs'
// and 'iOutputs' to the NeuraMorph 'that'
// Return the created NeuraMorphUnit
NeuraMorphUnit* NMAddUnit(
    NeuraMorph* that,
    const VecLong* iInputs,
    const VecLong* iOutputs);

// Remove the NeuraMorphUnit 'unit' from the NeuraMorph 'that'
// The NeuraMorphUnit is not freed
void NMRemoveUnit(
    NeuraMorph* that,

```

```

    NeuroMorphUnit* unit);

// Burry the NeuroMorphUnits in the 'units' set into the
// NeuroMorph 'that'
// 'units' is empty after calling this function
// The NeuroMorphUnits iOutputs must point toward the NeuroMorph
// outputs
// NeuroMorphUnits' iOutputs are redirected toward new hidden values
// 'that->hiddens' is resized as necessary
void NMBurryUnits(
    NeuroMorph* that,
    GSet* units);

// Get a new vector with indices of the outputs in the NeuroMorph 'that'
VecLong* NMGetVecIOutputs(const NeuroMorph* that);

// Evaluate the NeuroMorph 'that' on the 'inputs' values
void NMEvaluate(
    NeuroMorph* that,
    VecFloat* inputs);

// ----- NeuroMorphTrainer

// ===== Data structure =====

typedef struct NeuroMorphTrainer {

    // Trained NeuroMorph
    NeuroMorph* neuroMorph;

    // Training dataset
    GDataSetVecFloat* dataset;

    // Index of the dataset's category used for training and evaluation
    unsigned int iCatTraining;
    unsigned int iCatEval;

    // Depth of the training
    short depth;

    // Order of the transfer function of NeuroMorphUnit
    int order;

    // Maximum number of inputs per NeuroMorphUnit
    int nbMaxInputsUnit;

    // Threshold used to discard weakest units during training
    // in [0.0,1.0]
    float weakUnitThreshold;

    // Maximum number of unit kept at each depth
    int nbMaxUnitDepth;

    // Max level of division of values' range
    short maxLvlDiv;

    // Precomputed values to train the NeuroMorphUnit
    VecFloat** preCompInp;
    VecFloat** preCompOut;

    // Lowest and highest values for input values in the training
    // dataset

```

```

VecFloat* lowInputs;
VecFloat* highInputs;

// Variable to store the result of the last evaluation
// min/avg/sigma/max
VecFloat* resEval;
long nbCorrect;

// Stream to output info during training and evaluation
FILE* streamInfo;

} NeuraMorphTrainer;

// ===== Functions declaration =====

// Create a static NeuraMorphTrainer for the NeuraMorph 'neuraMorph' and the
// GDataSet 'dataset'
// Default depth: 2
// Default iCatTraining: 0
// Default weakUnitThreshold: 0.9
NeuraMorphTrainer NeuraMorphTrainerCreateStatic(
    NeuraMorph* neuraMorph,
    GDataSetVecFloat* dataset);

// Free the memory used by the static NeuraMorphTrainer 'that'
void NeuraMorphTrainerFreeStatic(NeuraMorphTrainer* that);

// Run the training process for the NeuraMorphTrainer 'that'
void NMTrainerRun(NeuraMorphTrainer* that);

// Run the evaluation process for the NeuraMorphTrainer 'that'
void NMTrainerEval(NeuraMorphTrainer* that);

// Get the depth of the NeuraMorphTrainer 'that'
#if BUILDMODE != 0
static inline
#endif
short NMTrainerGetDepth(const NeuraMorphTrainer* that);

// Set the depth of the NeuraMorphTrainer 'that' to 'depth'
#if BUILDMODE != 0
static inline
#endif
void NMTrainerSetDepth(
    NeuraMorphTrainer* that,
    short depth);

// Get the streamInfo of the NeuraMorphTrainer 'that'
#if BUILDMODE != 0
static inline
#endif
FILE* NMTrainerStreamInfo(const NeuraMorphTrainer* that);

// Set the streamInfo of the NeuraMorphTrainer 'that' to 'streamInfo'
#if BUILDMODE != 0
static inline
#endif
void NMTrainerSetStreamInfo(
    NeuraMorphTrainer* that,
    FILE* streamInfo);

// Get the maxLvlDiv of the NeuraMorphTrainer 'that'

```

```

#if BUILDMODE != 0
static inline
#endif
short NMTrainerGetMaxLvlDiv(const NeuraMorphTrainer* that);

// Set the maxLvlDiv of the NeuraMorphTrainer 'that' to 'lvl'
#if BUILDMODE != 0
static inline
#endif
void NMTrainerSetMaxLvlDiv(
    NeuraMorphTrainer* that,
    short lvl);

// Get the order of the NeuraMorphTrainer 'that'
#if BUILDMODE != 0
static inline
#endif
int NMTrainerGetOrder(const NeuraMorphTrainer* that);

// Set the order of the NeuraMorphTrainer 'that' to 'order'
#if BUILDMODE != 0
static inline
#endif
void NMTrainerSetOrder(
    NeuraMorphTrainer* that,
    int order);

// Get the nbMaxUnitDepth of the NeuraMorphTrainer 'that'
#if BUILDMODE != 0
static inline
#endif
int NMTrainerGetNbMaxUnitDepth(const NeuraMorphTrainer* that);

// Set the nbMaxUnitDepth of the NeuraMorphTrainer 'that' to 'nbMaxUnitDepth'
#if BUILDMODE != 0
static inline
#endif
void NMTrainerSetNbMaxUnitDepth(
    NeuraMorphTrainer* that,
    int nbMaxUnitDepth);

// Get the nbMaxInputsUnit of the NeuraMorphTrainer 'that'
#if BUILDMODE != 0
static inline
#endif
int NMTrainerGetNbMaxInputsUnit(const NeuraMorphTrainer* that);

// Set the nbMaxInputsUnit of the NeuraMorphTrainer 'that' to 'order'
#if BUILDMODE != 0
static inline
#endif
void NMTrainerSetNbMaxInputsUnit(
    NeuraMorphTrainer* that,
    int nbMaxInputsUnit);

// Get the weakness threshold of the NeuraMorphTrainer 'that'
#if BUILDMODE != 0
static inline
#endif
float NMTrainerGetWeakThreshold(const NeuraMorphTrainer* that);

// Set the weakness threshold of the NeuraMorphTrainer 'that'

```



```

// to 'iCat'
#if BUILDMODE != 0
static inline
#endif
void NMTrainerSetWeakThreshold(
    NeuraMorphTrainer* that,
    float weakUnitThreshold);

// Get the index of the training category of the NeuraMorphTrainer 'that'
#if BUILDMODE != 0
static inline
#endif
unsigned int NMTrainerGetICatTraining(const NeuraMorphTrainer* that);

// Set the index of the training category of the NeuraMorphTrainer 'that'
// to 'iCat'
#if BUILDMODE != 0
static inline
#endif
void NMTrainerSetICatTraining(
    NeuraMorphTrainer* that,
    unsigned int iCatTraining);

// Get the index of the evaluation category of the NeuraMorphTrainer 'that'
#if BUILDMODE != 0
static inline
#endif
unsigned int NMTrainerGetICatEval(const NeuraMorphTrainer* that);

// Set the index of the evaluation category of the NeuraMorphTrainer 'that'
// to 'iCat'
#if BUILDMODE != 0
static inline
#endif
void NMTrainerSetICatEval(
    NeuraMorphTrainer* that,
    unsigned int iCatEval);

// Get the NeuraMorph of the NeuraMorphTrainer 'that'
#if BUILDMODE != 0
static inline
#endif
NeuraMorph* NMTrainerNeuraMorph(const NeuraMorphTrainer* that);

// Get the GDataSet of the NeuraMorphTrainer 'that'
#if BUILDMODE != 0
static inline
#endif
GDataSetVecFloat* NMTrainerDataset(const NeuraMorphTrainer* that);

// Get the result of the last evaluation of the NeuraMorphTrainer 'that'
#if BUILDMODE != 0
static inline
#endif
const VecFloat* NMTrainerResEval(const NeuraMorphTrainer* that);

// Get the number of correct output in the last evaluation of the
// NeuraMorphTrainer 'that'
#if BUILDMODE != 0
static inline
#endif
long NMTrainerGetNbCorrect(const NeuraMorphTrainer* that);

```

```
// ===== static inline =====

#ifdef BUILDMODE != 0
#include "neuramorph-inline.c"
#endif

#endif
```

3 Code

3.1 neuramorph.c

```
// ===== NEURAMORPH.C =====

// ===== Include =====

#include "neuramorph.h"
#ifdef BUILDMODE == 0
#include "neuramorph-inline.c"
#endif

// ----- NeuraMorphUnit

// ===== Functions declaration =====

// Update the low and high of the hiddens of the NeuraMorph 'that' with
// the low and high of its units
void NMUpdateLowHighHiddens(NeuraMorph* that);

// ===== Functions implementation =====

// Create a new NeuraMorphUnit between the input 'iInputs' and the
// outputs 'iOutputs'
NeuraMorphUnit* NeuraMorphUnitCreate(
    const VecLong* iInputs,
    const VecLong* iOutputs) {

#ifdef BUILDMODE == 0

    if (iInputs == NULL) {

        NeuraMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'iInputs' is null");
        PBErrCatch(NeuraMorphErr);

    }

    if (iOutputs == NULL) {

        NeuraMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'iOutputs' is null");
        PBErrCatch(NeuraMorphErr);

    }

#endif

}
```

```

    }

#endif

// Allocate memory for the NeuraMorphUnit
NeuraMorphUnit* that =
    PBErrMalloc(
        NeuraMorphErr,
        sizeof(NeuraMorphUnit));

// Get the number of inputs (including the constant) and outputs
long nbIn = VecGetDim(iInputs);
long nbOut = VecGetDim(iOutputs);

// Init properties
that->iInputs = VecClone(iInputs);
that->iOutputs = VecClone(iOutputs);
that->lowFilters = VecFloatCreate(nbIn);
that->highFilters = VecFloatCreate(nbIn);
that->lowOutputs = NULL;
that->highOutputs = NULL;
that->outputs = VecFloatCreate(nbOut);
VecShort2D dim = VecShortCreateStatic2D();
VecSet(
    &dim,
    0,
    nbIn);
VecSet(
    &dim,
    1,
    nbOut);
that->transfer = NULL;
that->unitInputs = VecFloatCreate(nbIn);
that->value = 0.0;

// Return the new NeuraMorphUnit
return that;
}

// Free the memory used by the NeuraMorphUnit 'that'
void NeuraMorphUnitFree(NeuraMorphUnit** that) {

    // Check the input
    if (that == NULL || *that == NULL) {

        return;
    }

    // Free memory
    VecFree(&((*that)->iInputs));
    VecFree(&((*that)->iOutputs));
    VecFree(&((*that)->lowFilters));
    VecFree(&((*that)->highFilters));
    if ((*that)->lowOutputs != NULL) {

        VecFree(&((*that)->lowOutputs));
    }

    if ((*that)->highOutputs != NULL) {

```

```

    VecFree(&((*that)->highOutputs));

}

VecFree(&((*that)->outputs));
BBodyFree(&((*that)->transfer));
VecFree(&((*that)->unitInputs));
free(*that);
*that = NULL;

}

// Calculate the outputs for the 'inputs' with the NeuraMorphUnit 'that'
// Update 'that->outputs'
void NMUnitEvaluate(
    NeuraMorphUnit* that,
    const VecFloat* inputs) {

#ifdef BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PErrCatch(NeuraMorphErr);

    }

    if (VecGetDim(inputs) != VecGetDim(that->iInputs)) {

        NeuraMorphErr->_type = PErrTypeInvalidArg;
        sprintf(
            NeuraMorphErr->_msg,
            "'inputs' has invalid dimension (%ld!=%ld)",
            VecGetDim(inputs),
            VecGetDim(that->iInputs));
        PErrCatch(NeuraMorphErr);

    }

#endif

    // Reset the outputs
    VecFree(&(that->outputs));

    // Update the scaled inputs
    for (
        long iInput = 0;
        iInput < VecGetDim(that->unitInputs);
        ++iInput) {

        // Get the input value and its low/high filters
        float val =
            VecGet(
                inputs,
                iInput);
        float low =
            VecGet(
                that->lowFilters,

```

```

        iInput);
float high =
    VecGet(
        that->highFilters,
        iInput);

// Set the value in the unit inputs
VecSet(
    that->unitInputs,
    iInput,
    (val - low) / (high - low));
}

// Apply the transfer function
that->outputs =
    BBodyGet(
        that->transfer,
        that->unitInputs);

// If the low and high values for outputs don't exist yet
if (that->lowOutputs == NULL) {

    // Create the low and high values by cloning the current output
    that->lowOutputs = VecClone(that->outputs);
    that->highOutputs = VecClone(that->outputs);

// Else, the low and high values for outputs exist
} else {

    // Loop on the outputs
    for (
        long iOutput = 0;
        iOutput < VecGetDim(that->outputs);
        ++iOutput) {

        // Update the low and high values for this output
        float val =
            VecGet(
                that->outputs,
                iOutput);

        float curLow =
            VecGet(
                that->lowOutputs,
                iOutput);
        if (curLow > val) {

            VecSet(
                that->lowOutputs,
                iOutput,
                val);

        }

        float curHigh =
            VecGet(
                that->highOutputs,
                iOutput);
        if (curHigh < val) {

            VecSet(

```

```

        that->highOutputs,
        iOutput,
        val);

    }

}

}

}

// Print the NeuraMorphUnit 'that' on the 'stream'
void NMUnitPrint(
    const NeuraMorphUnit* that,
    FILE* stream) {

#ifdef BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PBErrCatch(NeuraMorphErr);

    }

    if (stream == NULL) {

        NeuraMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'stream' is null");
        PBErrCatch(NeuraMorphErr);

    }

#endif

    VecPrint(
        NMUnitIInputs(that),
        stream);
    fprintf(
        stream,
        " val(%.6f)",
        NMUnitGetValue(that));
    fprintf(
        stream,
        " nbSample(%ld)",
        that->nbTrainingSample);

}

// ----- NeuraMorph

// ===== Functions implementation =====

// Create a new NeuraMorph with 'nbInput' inputs and 'nbOutput' outputs
NeuraMorph* NeuraMorphCreate(
    long nbInput,

```

```

long nbOutput) {

// Allocate memory for the NeuraMorph
NeuraMorph* that =
    PBErrMalloc(
        NeuraMorphErr,
        sizeof(NeuraMorph));

// Init properties
that->nbInput = nbInput;
that->nbOutput = nbOutput;
that->inputs = VecFloatCreate(nbInput);
that->outputs = VecFloatCreate(nbOutput);
that->hiddens = NULL;
that->lowHiddens = NULL;
that->highHiddens = NULL;
that->units = GSetCreateStatic();
that->flagOneHot = false;

// Return the NeuraMorph
return that;
}

// Free the memory used by the NeuraMorph 'that'
void NeuraMorphFree(NeuraMorph** that) {

// Check the input
if (that == NULL || *that == NULL) {

    return;
}

// Free memory
VecFree(&((*that)->inputs));
VecFree(&((*that)->outputs));
if ((*that)->hiddens != NULL) {

    VecFree(&((*that)->hiddens));
    VecFree(&((*that)->lowHiddens));
    VecFree(&((*that)->highHiddens));
}

while (GSetNbElem(&((*that)->units)) > 0) {

    NeuraMorphUnit* unit = GSetPop(&((*that)->units));
    NeuraMorphUnitFree(&unit);
}

free(*that);
*that = NULL;
}

// Add one NeuraMorphUnit with input and output indices 'iInputs'
// and 'iOutputs' to the NeuraMorph 'that'
// Return the created NeuraMorphUnit
NeuraMorphUnit* NMAddUnit(
    NeuraMorph* that,

```

```

    const VecLong* iInputs,
    const VecLong* iOutputs) {

#ifdef BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PBErrCatch(NeuraMorphErr);

    }

    if (iInputs == NULL) {

        NeuraMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'iInputs' is null");
        PBErrCatch(NeuraMorphErr);

    }

    if (iOutputs == NULL) {

        NeuraMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'iOutputs' is null");
        PBErrCatch(NeuraMorphErr);

    }

#endif

    // Create the NeuraMorphUnit
    NeuraMorphUnit* unit =
        NeuraMorphUnitCreate(
            iInputs,
            iOutputs);

    // Append the new NeuraorphUnit to the set of NeuraMorphUnit
    GSetAppend(
        &(that->units),
        unit);

    // Return the new unit
    return unit;

}

// Remove the NeuraMorphUnit 'unit' from the NeuraMorph 'that'
// The NeuraMorphUnit is not freed
void NMRemoveUnit(
    NeuraMorph* that,
    NeuraMorphUnit* unit) {

#ifdef BUILDMODE == 0

    if (that == NULL) {

```



```

        NeuraMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PBErrCatch(NeuraMorphErr);

    }

#endif

    // Remove the NeuraMorphUnit from the set of NeuraMorphUnit
    GSetRemoveAll(
        &(that->units),
        unit);

}

// Burry the NeuraMorphUnits in the 'units' set into the
// NeuraMorph 'that'
// 'units' is empty after calling this function
// The NeuraMorphUnits iOutputs must point toward the NeuraMorph
// outputs
// NeuraMorphUnits' iOutputs are redirected toward new hidden values
// 'that->hiddens' is resized as necessary
void NMBurryUnits(
    NeuraMorph* that,
    GSet* units) {

#if BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PBErrCatch(NeuraMorphErr);

    }

#endif

    // Declare a variable to memorize the number of hidden values
    // to add
    long nbHiddenValues = 0;

    // While there are units to burry
    while (GSetNbElem(units) > 0) {

        // Get the unit
        NeuraMorphUnit* unit = GSetPop(units);

        // Loop on the iOutputs of the unit
        for (
            long iOutput = 0;
            iOutput < VecGetDim(NMUnitIOutputs(unit));
            ++iOutput) {

            long indice =
                VecGet(
                    NMUnitIOutputs(unit),

```

```

        iOutput);
    VecSet(
        unit->iOutputs,
        iOutput,
        indice + nbHiddenValues);
}

// Append the unit to the set of NeuraMorphUnit
GSetAppend(
    &(that->units),
    unit);

// Update the number of new hidden values
nbHiddenValues += VecGetDim(NMUnitIOutputs(unit));
}

// If there is already hidden values
if (that->hiddens != NULL) {

    // Add the previous number of hidden values
    nbHiddenValues += VecGetDim(that->hiddens);

    // Free memory
    VecFree(&(that->hiddens));
    VecFree(&(that->lowHiddens));
    VecFree(&(that->highHiddens));
}

// If there are hidden values after burrying
if (nbHiddenValues > 0) {

    // Resize the hiddens value vector
    that->hiddens = VecFloatCreate(nbHiddenValues);
    that->lowHiddens = VecFloatCreate(nbHiddenValues);
    that->highHiddens = VecFloatCreate(nbHiddenValues);

    // Update the low and high of the hiddens with the low and high
    // of the units
    NMUpdateLowHighHiddens(that);
}
}

// Get a new vector with indices of the outputs in the NeuraMorph 'that'
VecLong* NMGetVecIOutputs(const NeuraMorph* that) {

#ifdef BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PBErrCatch(NeuraMorphErr);
    }
}

```

```

#endif

// Allocate memory for the result
VecLong* iOutputs = VecLongCreate(NMGetNbOutput(that));

// Loop on indices
for (
    long iOutput = 0;
    iOutput < NMGetNbOutput(that);
    ++iOutput) {

    // Set the indice of this output
    VecSet(
        iOutputs,
        iOutput,
        iOutput + NMGetNbHidden(that));

}

// Return the result
return iOutputs;

}

// Update the low and high of the hiddens of the NeuraMorph 'that' with
// the low and high of its units
void NMUpdateLowHighHiddens(NeuraMorph* that) {

#if BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PBErrCatch(NeuraMorphErr);

    }

#endif

// Loop on the units
GSetIterForward iter =
    GSetIterForwardCreateStatic(&(that->units));
do {

    // Get the unit
    NeuraMorphUnit* unit = GSetIterGet(&iter);

    // Loop on the iOutputs of the unit
    for (
        long iOutput = 0;
        iOutput < VecGetDim(NMUnitIOutputs(unit));
        ++iOutput) {

        // Get the indice
        long indice =
            VecGet(
                NMUnitIOutputs(unit),
                iOutput);
    }
}

```

```

// If the indice points to a hidden value
if (indice < NMGetNbHidden(that)) {

    // If the low and high exist
    if (
        unit->lowOutputs != NULL &&
        unit->highOutputs != NULL) {

        // Update the low and high
        float low =
            VecGet(
                unit->lowOutputs,
                iOutput);
        float high =
            VecGet(
                unit->highOutputs,
                iOutput);
        VecSet(
            that->lowHiddens,
            indice,
            low);
        VecSet(
            that->highHiddens,
            indice,
            high);

    }

}

}

} while (GSetIterStep(&iter));
}

// Evaluate the NeuraMorph 'that' on the 'inputs' values
void NMEvaluate(
    NeuraMorph* that,
    VecFloat* inputs) {

#ifdef BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PBErrCatch(NeuraMorphErr);

    }

    if (inputs == NULL) {

        NeuraMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'inputs' is null");
        PBErrCatch(NeuraMorphErr);

    }

}

```

```

if (VecGetDim(inputs) != VecGetDim(that->inputs)) {

    NeuraMorphErr->_type = PErrTypeInvalidArg;
    sprintf(
        NeuraMorphErr->_msg,
        "'inputs' has invalid size (%ld==%ld)",
        VecGetDim(inputs),
        VecGetDim(that->inputs));
    PErrCatch(NeuraMorphErr);

}

#endif

// Copy the inputs into the internal inputs
VecCopy(
    that->inputs,
    inputs);

// Reset the internal outputs
VecSetNull(that->outputs);

// If there are no units
if (GSetNbElem(&(that->units)) == 0) {

    // Nothing else to do
    return;

}

// Loop on the units
GSetIterForward iter = GSetIterForwardCreateStatic(&(that->units));
do {

    // Get the unit
    NeuraMorphUnit* unit = GSetIterGet(&iter);

    // Allocate memory for inputs sent to the unit
    VecFloat* unitInputs = VecFloatCreate(NMUnitGetNbInputs(unit));

    // Loop on the input indices of the unit
    for (
        long iInput = 0;
        iInput < NMUnitGetNbInputs(unit);
        ++iInput) {

        // Get the input indice
        long indiceInput =
            VecGet(
                NMUnitIInputs(unit),
                iInput);

        // Declare a variable to memorize the input value
        float val = 0.0;

        // If this indice points toward an input
        if (indiceInput < NMGetNbInput(that)) {

            // Get the input value of the NeuraMorph for this indice
            val =
                VecGet(

```

```

        NMInputs(that),
        indiceInput);

// Else, the indice points toward a hidden value
} else {

    // Get the hidden value of the NeuraMorph for this indice
    val =
        VecGet(
            that->hiddens,
            indiceInput - NMGetNbInput(that));

}

// Set the input value for the unit for this indice
VecSet(
    unitInputs,
    iInput,
    val);

}

// Evaluate the unit
NMUnitEvaluate(
    unit,
    unitInputs);

// Free the memory used by the unit input
VecFree(&unitInputs);

// Loop on the output indices of the unit
for (
    long iOutput = 0;
    iOutput < NMUnitGetNbOutputs(unit);
    ++iOutput) {

    // Get the output value of the unit for this indice
    float val =
        VecGet(
            NMUnitOutputs(unit),
            iOutput);

    // Get the output indice
    long indiceOutput =
        VecGet(
            NMUnitIOutputs(unit),
            iOutput);

    // If the indice points toward a hidden
    if (indiceOutput < NMGetNbHidden(that)) {

        // Set the hidden value of the NeuraMorph for this indice
        VecSet(
            that->hiddens,
            indiceOutput,
            val);

    }

    // Else, the indice points toward an output
} else {

    // Set the output value of the NeuraMorph for this indice
    VecSet(

```

```

        that->outputs,
        indiceOutput - NMGetNbHidden(that),
        val);

    }

}

} while (GSetIterStep(&iter));

// If the NeuraMorph is a one hot encoder
if (NMGetFlagOneHot(that) == true) {

    // Get the one hot
    long oneHot = VecGetIMaxVal(that->outputs);

    // Convert the output values
    VecSetAll(
        that->outputs,
        -1.0);
    VecSet(
        that->outputs,
        oneHot,
        1.0);

}

}

// ----- NeuraMorphTrainer

// ===== Functions declaration =====

// Return true if the vector 'v' is a valid indices configuration
// i.e. v[i]<v[j] for all i<j
bool NMTrainerIsValidInputConfig(
    const VecLong* v,
    long iMinInput);

// Train a new NeuraMorphUnit with the interface defined by 'iInputs'
// and 'iOutputs', and add it to the set, sorted on its value
// If 'lastUnit' is true, the NeuraMorphUnit will be the last one in
// its NeuraMorph
void NMTrainerTrainUnit(
    NeuraMorphTrainer* that,
    GSet* trainedUnits,
    const VecLong* iInputs,
    const VecLong* iOutputs,
    bool lastUnit);

// Precompute the values of the NeuraMorph for each sample of the
// GDataset for the NeuraMorphTrainer 'that'
void NMTrainerPrecomputeValues(NeuraMorphTrainer* that);

// Free the precomputed values of the NeuraMorphTrainer 'that'
void NMTrainerFreePrecomputed(NeuraMorphTrainer* that);

// ===== Functions implemetation =====

// Create a static NeuraMorphTrainer for the NeuraMorph 'neuraMorph' and the
// GDataSet 'dataset'
// Default depth: 2

```

```

// Default iCatTraining: 0
// Default weakUnitThreshold: 0.9
NeuraMorphTrainer NeuraMorphTrainerCreateStatic(
    NeuraMorph* neuraMorph,
    GDataSetVecFloat* dataset) {

#ifdef BUILDMODE == 0

    if (neuraMorph == NULL) {

        NeuraMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'neuraMorph' is null");
        PBErrCatch(NeuraMorphErr);

    }

    if (dataset == NULL) {

        NeuraMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'dataset' is null");
        PBErrCatch(NeuraMorphErr);

    }

#endif

    // Declare the new NeuraMorphTrainer
    NeuraMorphTrainer that;

    // Init properties
    that.neuraMorph = neuraMorph;
    that.dataset = dataset;
    that.depth = 2;
    that.order = 1;
    that.nbMaxUnitDepth = 2;
    that.maxLvlDiv = 2;
    that.nbMaxInputsUnit =
        MAX(
            GDSGetNbOutputs(dataset),
            2);
    that.iCatTraining = 0;
    that.iCatEval = 1;
    that.weakUnitThreshold = 0.9;
    that.preCompInp = NULL;
    that.lowInputs = NULL;
    that.highInputs = NULL;
    that.streamInfo = NULL;
    that.resEval = VecFloatCreate(4);
    that.nbCorrect = 0;

    // Return the NeuraMorphTrainer
    return that;

}

// Free the memory used by the static NeuraMorphTrainer 'that'
void NeuraMorphTrainerFreeStatic(NeuraMorphTrainer* that) {

```



```

#if BUILDMODE == 0

    if (that == NULL) {

        NeuroMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuroMorphErr->_msg,
            "'that' is null");
        PBErrCatch(NeuroMorphErr);

    }

#endif

    VecFree(&(that->lowInputs));
    VecFree(&(that->highInputs));
    VecFree(&(that->resEval));

}

// Run the training process for the NeuroMorphTrainer 'that'
void NMTrainerRun(NeuroMorphTrainer* that) {

#if BUILDMODE == 0

    if (that == NULL) {

        NeuroMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuroMorphErr->_msg,
            "'that' is null");
        PBErrCatch(NeuroMorphErr);

    }

#endif

    // Declare a variable to memorize the minimum index needed in the
    // inputs of the new unit to ensure we do not train twice the same
    // unit
    long iMinInput = 0;

    // Loop on training depth
    for (
        short iDepth = 1;
        iDepth <= NMTrainerGetDepth(that);
        ++iDepth) {

        printf(
            "Depth %d/%d...\n",
            iDepth,
            NMTrainerGetDepth(that));

        // Get the number of available inputs for the new unit
        long nbAvailInputs =
            MMGetNbInput(NMTrainerNeuraMorph(that)) +
            MMGetNbHidden(NMTrainerNeuraMorph(that));

        printf(
            "Nb available inputs: %ld\n",
            nbAvailInputs);
    }
}

```

```

// Precompute the values to speed up the training
NMTrainerPrecomputeValues(that);

// Get the output indices
VecLong* iOutputs = NMGetVecIOutputs(NMTrainerNeuraMorph(that));

// Declare a set to memorize the trained units
GSet trainedUnits = GSetCreateStatic();

// Set a flag to memorize if we are at the last depth
bool isLastDepth = (iDepth == NMTrainerGetDepth(that));

// Get the number of inputs per unit
long nbMaxInputsUnit =
    MIN(
        nbAvailInputs,
        NMTrainerGetNbMaxInputsUnit(that));

// Loop on the number of inputs for the new unit
for (
    long nbUnitInputs = 1;
    nbUnitInputs <= nbMaxInputsUnit;
    ++nbUnitInputs) {

    printf(
        "Train units with %04ld input(s)\n",
        nbUnitInputs);

    // Loop on the possible input configurations for the new units
    VecLong* iInputs = VecLongCreate(nbUnitInputs);
    VecLong* iInputsBound = VecLongCreate(nbUnitInputs);
    VecSetAll(
        iInputsBound,
        nbAvailInputs);
    bool hasStepped = true;
    do {

        bool isValidInputConfig =
            NMTrainerIsValidInputConfig(
                iInputs,
                iMinInput);
        if (isValidInputConfig == true) {
            if (GSetTail(&trainedUnits)){
                VecPrint(iInputs,stderr);fprintf(stderr, " %f    \r", NMUnitGetValue(GSetTail(&trainedUnits)));
            }

            // Train the unit
            NMTrainerTrainUnit(
                that,
                &trainedUnits,
                iInputs,
                iOutputs,
                (iDepth != 1));
            //isLastDepth);

        }

        // Step to the next input configuration
        hasStepped =
            VecStep(
                iInputs,
                iInputsBound);
    } while (hasStepped);
}

```

```

    } while (hasStepped);

    // Free memory
    VecFree(&iInputs);
    VecFree(&iInputsBound);
}

// If this is the last depth
if (isLastDepth == true) {

    // Add the best of all units to the NeuraMorph
    NeuraMorphUnit* bestUnit = GSetDrop(&trainedUnits);
    GSetAppend(
        &(NMTrainerNeuraMorph(that)->units),
        bestUnit);

    printf("Add the last unit\n");
    NMUnitPrintln(
        bestUnit,
        stdout);

    // Discard all other units
    while (GSetNbElem(&trainedUnits) > 0) {

        NeuraMorphUnit* unit = GSetPop(&trainedUnits);
        NeuraMorphUnitFree(&unit);

    }

    // Else, this is not the last depth
} else {

    // Get the value of the weakest and strongest units
    float weakVal = GSetElemGetSortVal(GSetHeadElem(&trainedUnits));
    float strongVal = GSetElemGetSortVal(GSetTailElem(&trainedUnits));

    // Get the threshold to discard the weakest units
    float threshold =
        weakVal + (strongVal - weakVal) *
        NMTrainerGetWeakThreshold(that);

    // Discard the weakest units
    long nbTrainedUnits = GSetNbElem(&trainedUnits);
    while (
        GSetElemGetSortVal(GSetHeadElem(&trainedUnits)) < threshold
        || GSetNbElem(&trainedUnits) > NMTrainerGetNbMaxUnitDepth(that)) {

        NeuraMorphUnit* unit = GSetPop(&trainedUnits);
        NeuraMorphUnitFree(&unit);

    }

    // Displayed the burried units
    printf(
        "Burry %ld out of %ld unit(s)\n",
        GSetNbElem(&trainedUnits),
        nbTrainedUnits);
    GSetIterForward iter = GSetIterForwardCreateStatic(&trainedUnits);
    do {

        NeuraMorphUnit* unit = GSetIterGet(&iter);

```

```

        NMUnitPrintln(
            unit,
            stdout);

    } while (GSetIterStep(&iter));

    // Burry the remaining units
    NMBurryUnits(
        NMTrainerNeuraMorph(that),
        &trainedUnits);

}

// Update the minimum index of a valid configuration
iMinInput = nbAvailInputs;

// Free memory
VecFree(&iOutputs);
NMTrainerFreePrecomputed(that);

}

}

// Return true if the vector 'v' is a valid indices configuration
// i.e. v[i]<v[j] for all i<j and there exists i such as
// v[i]>=iMinInput
bool NMTrainerIsValidInputConfig(
    const VecLong* v,
    long iMinInput) {

#ifdef BUILDMODE == 0

    if (v == NULL) {

        NeuraMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'v' is null");
        PBErrCatch(NeuraMorphErr);

    }

#endif

    bool noveltyCond = false;
    long a =
        VecGet(
            v,
            0);
    if (a >= iMinInput) {

        noveltyCond = true;

    }

    for (
        long i = 1;
        i < VecGetDim(v);
        ++i) {

        long b =

```

```

        VecGet(
            v,
            i);
    if (a >= b) {

        return false;
    }

    a = b;

    if (a >= iMinInput) {

        noveltyCond = true;
    }
}

return noveltyCond;
}

// Train a new NeuroMorphUnit with the interface defined by 'iInputs'
// and 'iOutputs', and add it to the set, sorted on its value
// If 'lastUnit' is true, the NeuroMorphUnit will be the last one in
// its NeuroMorph
void NMTrainerTrainUnit(
    NeuroMorphTrainer* that,
        GSet* trainedUnits,
        const VecLong* iInputs,
        const VecLong* iOutputs,
        bool lastUnit) {

#ifdef BUILDMODE == 0

    if (that == NULL) {

        NeuroMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuroMorphErr->_msg,
            "'that' is null");
        PBErrCatch(NeuroMorphErr);
    }

    if (trainedUnits == NULL) {

        NeuroMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuroMorphErr->_msg,
            "'trainedUnits' is null");
        PBErrCatch(NeuroMorphErr);
    }

    if (iInputs == NULL) {

        NeuroMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuroMorphErr->_msg,
            "'iInputs' is null");

```

```

        PBErCatch(NeuraMorphErr);
    }

    if (iOutputs == NULL) {

        NeuraMorphErr->_type = PBErTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'iOutputs' is null");
        PBErCatch(NeuraMorphErr);
    }

#endif

    // Get the number of inputs
    long nbInputs = VecGetDim(iInputs);

    // Loop on the division levels
    // (None for the last unit)
    VecShort* curDivLvl = VecShortCreate(nbInputs);
    VecShort* divLvlBound = VecShortCreate(nbInputs);
    if (lastUnit == true) {

        VecSetAll(
            divLvlBound,
            0);

    } else {

        VecSetAll(
            divLvlBound,
            NMTrainerGetMaxLvlDiv(that));
    }

    bool flagStepDivLvl = true;
    do {

        // Get the bounds for the number of division for each input
        // at current levels
        VecShort* divBound = VecShortCreate(nbInputs);
        for (
            long iInput = nbInputs;
            iInput--;) {

            short lvl =
                VecGet(
                    curDivLvl,
                    iInput);
            short bound =
                powi(
                    2,
                    lvl);
            VecSet(
                divBound,
                iInput,
                bound);
        }
    }

```

```

// Loop on the combination of divisions
VecShort* curDiv = VecShortCreate(nbInputs);
bool flagStepDiv = true;
do {

    // Create the unit
    NeuraMorphUnit* unit =
        NeuraMorphUnitCreate(
            iInputs,
            iOutputs);

unit->nbTrainingSample = 0;

    // Loop on the inputs of the unit
    for (
        long iInput = nbInputs;
        iInput--;) {

        // Get the indice of this input in the NeuraMorph
        short jInput =
            VecGet(
                NMUnitIInputs(unit),
                iInput);

        // Declare variables to memorize the lowest and highest
        // values for this input
        float low = 0.0;
        float high = 0.0;

        // If this input is an input in the NeuraMorph
        if (jInput < NMGetNbInput(NMTrainerNeuraMorph(that))) {

            low =
                VecGet(
                    that->lowInputs,
                    jInput);
            high =
                VecGet(
                    that->highInputs,
                    jInput);

            // Else, this input is an hidden value in the NeuraMorph
        } else {

            low =
                VecGet(
                    NMLowHiddens(NMTrainerNeuraMorph(that)),
                    jInput - NMGetNbInput(NMTrainerNeuraMorph(that)));
            high =
                VecGet(
                    NMHighHiddens(NMTrainerNeuraMorph(that)),
                    jInput - NMGetNbInput(NMTrainerNeuraMorph(that)));

        }

        // Get the filter values for the current division
        float lowFilter =
            low + (high - low) *
            (float)VecGet(
                curDiv,
                iInput) /
            (float)VecGet(

```

```

        divBound,
        iInput);
float highFilter =
    low + (high - low) *
    (float)(VecGet(
        curDiv,
        iInput) + 1) /
    (float)VecGet(
        divBound,
        iInput);

// Set the filter values in the unit
VecSet(
    unit->lowFilters,
    iInput,
    lowFilter);
VecSet(
    unit->highFilters,
    iInput,
    highFilter);
}

// Declare two GSets to extract the filtered samples
GSetVecFloat trainingInputs = GSetVecFloatCreateStatic();
GSetVecFloat trainingOutputs = GSetVecFloatCreateStatic();

// Loop on the samples of the dataset
long nbSample =
    GDSGetSizeCat(
        NMTrainerDataset(that),
        NMTrainerGetICatTraining(that));
for (
    long iSample = 0;
    iSample < nbSample;
    ++iSample) {

    // Create the sample's inputs for this unit
    VecFloat* sampleInputs = VecFloatCreate(nbInputs);

    // If all the input values are within the bound of the unit
    bool flag = true;
    for (
        long iInput = nbInputs;
        flag && iInput--;) {

        float low =
            VecGet(
                unit->lowFilters,
                iInput);
        float high =
            VecGet(
                unit->highFilters,
                iInput);

        if (high - low < PBMath_EPSILON) {

            low -= 1.0;
            high += 1.0;
            VecSet(
                unit->lowFilters,
                iInput,

```



```

        low);
    VecSet(
        unit->highFilters,
        iInput,
        high);

}

short jInput =
    VecGet(
        iInputs,
        iInput);
float val =
    VecGet(
        that->preCompInp[iSample],
        jInput);
if (
    val < low - PBMath_EPSILON ||
    val > high + PBMath_EPSILON) {

    flag = false;

}

// Simultaneously, scale the inputs values toward the unit
// input space
val = (val - low) / (high - low);
VecSet(
    sampleInputs,
    iInput,
    val);

}

if (flag) {

    // Add this sample to the training set for the current unit
    GSetAppend(
        &trainingInputs,
        sampleInputs);
    GSetAppend(
        &trainingOutputs,
        that->preCompOut[iSample]);

} else {

    // Free memory
    VecFree(&sampleInputs);

}

}

// If we have enough samples to train the unit on the current
// combination of divisions
long nbMinSample =
    powi(
        NMTrainerGetOrder(that) + 2,
        NMUnitGetNbInputs(unit) + 1);
nbMinSample =
    MIN(
        nbMinSample,

```

```

        nbSample);
    if (GSetNbElem(&trainingInputs) >= nbMinSample) {

        // Calculate the transfer function
        float bias = 0.0;
        unit->transfer =
            BBodyFromPointCloud(
                NMTrainerGetOrder(that),
                &trainingInputs,
                &trainingOutputs,
                &bias);

        // If we could calculate the transfer function
        if (unit->transfer != NULL) {

            // Set the value of the unit
            float corrRange =
                (float)GSetNbElem(&trainingInputs) /
                (float)GDSGetSizeCat(
                    NMTrainerDataset(that),
                    NMTrainerGetICatTraining(that));
            NMUnitSetValue(
                unit,
                -1.0 * bias / corrRange);

            unit->nbTrainingSample += GSetNbElem(&trainingInputs);

            // Add the unit to the set of trained units
            GSetAddSort(
                trainedUnits,
                unit,
                NMUnitGetValue(unit));

            // Else, we couldn't calculate the transfer function
        } else {

            // Free memory
            NeuraMorphUnitFree(&unit);

        }

    }

    // Free memory
    while (GSetNbElem(&trainingInputs) > 0) {

        VecFloat* v = GSetPop(&trainingInputs);
        VecFree(&v);

    }

    GSetFlush(&trainingOutputs);

    // Move to the next combination of divisions
    flagStepDiv =
        VecStep(
            curDiv,
            divBound);

} while (flagStepDiv);

// Free memory

```

```

    VecFree(&curDiv);
    VecFree(&divBound);

    // Move to the next division level
    flagStepDivLvl =
        VecStep(
            curDivLvl,
            divLvlBound);

} while (flagStepDivLvl);

// Free memory
VecFree(&curDivLvl);
VecFree(&divLvlBound);

}

// Precompute the values of the NeuraMorph for each sample of the
// GDataset for the NeuraMorphTrainer 'that'
void NMTrainerPrecomputeValues(NeuraMorphTrainer* that) {

#ifdef BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PBErrCatch(NeuraMorphErr);

    }

#endif

    // Get the number of samples
    long nbSample =
        GDSGetSizeCat(
            NMTrainerDataset(that),
            NMTrainerGetICatTraining(that));

    // Allocate memory
    that->preCompInp =
        PBErrMalloc(
            NeuraMorphErr,
            nbSample * sizeof(VecFloat*));
    that->preCompOut =
        PBErrMalloc(
            NeuraMorphErr,
            nbSample * sizeof(VecFloat*));

    // Reset the low and high values for input
    VecFree(&(that->lowInputs));
    VecFree(&(that->highInputs));

    // Get the size of the precomputed vector
    long sizeInp =
        NMGetNbInput(NMTrainerNeuraMorph(that)) +
        NMGetNbHidden(NMTrainerNeuraMorph(that));

    // Loop on the samples
    long iSample = 0;

```

```

bool flagStep = true;
GDSReset(
    NMTrainerDataset(that),
    NMTrainerGetICatTraining(that));
do {

    // Get a clone of the sample's inputs
    VecFloat* inputs =
        GDSGetSampleInputs(
            NMTrainerDataset(that),
            NMTrainerGetICatTraining(that));

    // Update the low and high input values
    if (that->lowInputs == NULL) {

        that->lowInputs = VecClone(inputs);
        that->highInputs = VecClone(inputs);

    } else {

        for (
            long iInput = 0;
            iInput < VecGetDim(inputs);
            ++iInput) {

            float val =
                VecGet(
                    inputs,
                    iInput);

            float curLow =
                VecGet(
                    that->lowInputs,
                    iInput);
            if (curLow > val) {

                VecSet(
                    that->lowInputs,
                    iInput,
                    val);

            }

            float curHigh =
                VecGet(
                    that->highInputs,
                    iInput);
            if (curHigh < val) {

                VecSet(
                    that->highInputs,
                    iInput,
                    val);

            }

        }

    }

    // Get a clone of the sample's outputs
    that->preCompOut[iSample] =

```

```

    GDSGetSampleOutputs(
        NMTrainerDataset(that),
        NMTrainerGetICatTraining(that));

// Run the NeuraMorph on the sample
NMEvaluate(
    NMTrainerNeuraMorph(that),
    inputs);

// Allocate memory for the precomputed vector
that->preCompInp[iSample] = VecFloatCreate(sizeInp);

// Copy the inputs and hidden values into the precomputed vector
for (
    long i = NMGetNbInput(NMTrainerNeuraMorph(that));
    i--;) {

    float val =
        VecGet(
            NMInputs(NMTrainerNeuraMorph(that)),
            i);
    VecSet(
        that->preCompInp[iSample],
        i,
        val);

}

for (
    long i = NMGetNbHidden(NMTrainerNeuraMorph(that));
    i--;) {

    float val =
        VecGet(
            NMHiddens(NMTrainerNeuraMorph(that)),
            i);
    VecSet(
        that->preCompInp[iSample],
        i + NMGetNbInput(NMTrainerNeuraMorph(that)),
        val);

}

// Free memory
VecFree(&inputs);

// Move to the next sample
++iSample;
flagStep =
    GDSStepSample(
        NMTrainerDataset(that),
        NMTrainerGetICatTraining(that));

} while (flagStep);

// Finally, update the hiddens bound if any
if (NMGetNbHidden(NMTrainerNeuraMorph(that)) > 0) {

    NMUpdateLowHighHiddens(NMTrainerNeuraMorph(that));

}

```

```

}

// Free the precomputed hidden values of the NeuraMorphTrainer 'that'
void NMTrainerFreePrecomputed(NeuraMorphTrainer* that) {

#ifdef BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PBErrCatch(NeuraMorphErr);

    }

#endif

    // If the hidden values are not precomputed
    if (that->preCompInp == NULL) {

        // Stop here
        return;

    }

    // Get the number of samples
    long nbSample =
        GDSGetSizeCat(
            NMTrainerDataset(that),
            NMTrainerGetICatTraining(that));

    // Free memory
    for (
        long iSample = nbSample;
        iSample--;) {

        VecFree(that->preCompInp + iSample);
        VecFree(that->preCompOut + iSample);

    }

    free(that->preCompInp);
    that->preCompInp = NULL;
    free(that->preCompOut);
    that->preCompOut = NULL;

}

// Run the evaluation process for the NeuraMorphTrainer 'that'
void NMTrainerEval(NeuraMorphTrainer* that) {

#ifdef BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PBErrCatch(NeuraMorphErr);

    }

#endif

```

```

    }

#endif

    // Declare variables to calculate the result of evaluation
    float minBias = 0.0;
    float avgBias = 0.0;
    float maxBias = 0.0;
    float sigmaBias = 0.0;
    that->nbCorrect = 0;
    long nbSample =
        GDSGetSizeCat(
            NMTrainerDataset(that),
            NMTrainerGetICatEval(that));
    float* biases =
        PBErrMalloc(
            NeuraMorphErr,
            sizeof(float) * nbSample);

    // Loop on the evaluation samples
    long iSample = 0;
    bool flagStep = true;
    GDSReset(
        NMTrainerDataset(that),
        NMTrainerGetICatEval(that));
    do {

        // Get a clone of the sample's inputs and outputs
        VecFloat* inputs =
            GDSGetSampleInputs(
                NMTrainerDataset(that),
                NMTrainerGetICatEval(that));
        VecFloat* outputs =
            GDSGetSampleOutputs(
                NMTrainerDataset(that),
                NMTrainerGetICatEval(that));

        // Run the NeuraMorph on the sample
        NMEvaluate(
            NMTrainerNeuraMorph(that),
            inputs);

        // Update the result of evaluation
        float bias =
            VecDist(
                outputs,
                NMOutputs(NMTrainerNeuraMorph(that)));
        avgBias += bias;
        biases[iSample] = bias;
        if (iSample == 0) {

            minBias = bias;
            maxBias = bias;

        } else {

            minBias =
                MIN(
                    bias,
                    minBias);
            maxBias =

```

```

        MAX(
            bias,
            maxBias);
    }
    if (fabs(bias) < PBMath_EPSILON) {

        ++(that->nbCorrect);
    }

    // Display the result
    /* if (NMTrainerStreamInfo(that) != NULL) {

        fprintf(
            NMTrainerStreamInfo(that),
            "%02ld ",
            iSample);
        VecPrint(
            inputs,
            NMTrainerStreamInfo(that));
        fprintf(
            NMTrainerStreamInfo(that),
            " -> ");
        VecPrint(
            outputs,
            NMTrainerStreamInfo(that));
        fprintf(
            NMTrainerStreamInfo(that),
            " : ");
        VecPrint(
            NMOutputs(NMTrainerNeuraMorph(that)),
            NMTrainerStreamInfo(that));
        fprintf(
            NMTrainerStreamInfo(that),
            " ");
        fprintf(
            NMTrainerStreamInfo(that),
            "%f\n",
            bias);
    } */

    // Free memory
    VecFree(&inputs);
    VecFree(&outputs);

    // Move to the next sample
    ++iSample;
    flagStep =
        GDSSStepSample(
            NMTrainerDataset(that),
            NMTrainerGetICatEval(that));
} while (flagStep);

// Calculate the mean and standard deviation
avgBias /= (float)nbSample;
for (
    iSample = nbSample;
    iSample--;) {

```



```

        sigmaBias +=
            powi(
                biases[iSample] - avgBias,
                2);
    }
    sigmaBias /= (float)(nbSample - 1);
    sigmaBias = sqrt(sigmaBias);

    // Memorize the result of evaluation
    VecSet(
        that->resEval,
        0,
        minBias);
    VecSet(
        that->resEval,
        1,
        avgBias);
    VecSet(
        that->resEval,
        2,
        sigmaBias);
    VecSet(
        that->resEval,
        3,
        maxBias);

    // Free memory
    free(biases);
}

```

3.2 neuramorph-inline.c

```

// ===== NEURAMORPH-INLINE.C =====

// ---- NeuraMorphUnit

// ===== Functions implementation =====

// Get the input indices of the NeuraMorphUnit 'that'
#if BUILDMODE != 0
static inline
#endif
const VecLong* NMUnitIInputs(const NeuraMorphUnit* that) {

    #if BUILDMODE == 0

        if (that == NULL) {

            NeuraMorphErr->_type = PBErrTypeNullPointer;
            sprintf(
                NeuraMorphErr->_msg,
                "'that' is null");
            PBErrCatch(NeuraMorphErr);

        }

    #endif
}

```

```

    return that->iInputs;
}

// Get the output indices of the NeuraMorphUnit 'that'
#if BUILDMODE != 0
static inline
#endif
const VecLong* NMUnitIOutputs(const NeuraMorphUnit* that) {

#if BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PBErrCatch(NeuraMorphErr);

    }

#endif

    return that->iOutputs;
}

// Get the output values of the NeuraMorphUnit 'that'
#if BUILDMODE != 0
static inline
#endif
const VecFloat* NMUnitOutputs(const NeuraMorphUnit* that) {

#if BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PBErrCatch(NeuraMorphErr);

    }

#endif

    return that->outputs;
}

// Get the number of input values of the NeuraMorphUnit 'that'
#if BUILDMODE != 0
static inline
#endif
long NMUnitGetNbInputs(const NeuraMorphUnit* that) {

#if BUILDMODE == 0

    if (that == NULL) {

```

```

        NeuraMorphErr->_type = PErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PErrCatch(NeuraMorphErr);
    }

#endif

    return VecGetDim(that->iInputs);
}

// Get the number of output values of the NeuraMorphUnit 'that'
#if BUILDMODE != 0
static inline
#endif
long NMUnitGetNbOutputs(const NeuraMorphUnit* that) {

#if BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PErrCatch(NeuraMorphErr);
    }

#endif

    return VecGetDim(that->iOutputs);
}

// Get the number of coefficients in the transfer function of
// the NeuraMorphUnit 'that'
#if BUILDMODE != 0
static inline
#endif
long NMUnitGetNbCoeffs(const NeuraMorphUnit* that) {

#if BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PErrCatch(NeuraMorphErr);
    }

#endif

    return BBodyGetNbCtrl(that->transfer);
}

```

```

// Get the value of the NeuraMorphUnit 'that'
#if BUILDMODE != 0
static inline
#endif
float NMUnitGetValue(const NeuraMorphUnit* that) {

#if BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PBErrCatch(NeuraMorphErr);

    }

#endif

    return that->value;

}

// Set the value of the NeuraMorphUnit 'that' to 'val'
#if BUILDMODE != 0
static inline
#endif
void NMUnitSetValue(
    NeuraMorphUnit* that,
    float val) {

#if BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PBErrCatch(NeuraMorphErr);

    }

#endif

    that->value = val;

}

// ----- NeuraMorph

// ===== Functions implementation =====

// Get the number of input values of the NeuraMorph 'that'
#if BUILDMODE != 0
static inline
#endif
long NMGetNbInput(const NeuraMorph* that) {

#if BUILDMODE == 0

```

```

    if (that == NULL) {

        NeuroMorphErr->_type = PErrTypeNullPointer;
        sprintf(
            NeuroMorphErr->_msg,
            "'that' is null");
        PErrCatch(NeuroMorphErr);

    }

#endif

    return that->nbInput;

}

// Get the number of output values of the NeuroMorph 'that'
#if BUILDMODE != 0
static inline
#endif
long NMGetNbOutput(const NeuroMorph* that) {

#if BUILDMODE == 0

    if (that == NULL) {

        NeuroMorphErr->_type = PErrTypeNullPointer;
        sprintf(
            NeuroMorphErr->_msg,
            "'that' is null");
        PErrCatch(NeuroMorphErr);

    }

#endif

    return that->nbOutput;

}

// Get the input values of the NeuroMorph 'that'
#if BUILDMODE != 0
static inline
#endif
VecFloat* NMInputs(NeuroMorph* that) {

#if BUILDMODE == 0

    if (that == NULL) {

        NeuroMorphErr->_type = PErrTypeNullPointer;
        sprintf(
            NeuroMorphErr->_msg,
            "'that' is null");
        PErrCatch(NeuroMorphErr);

    }

#endif

    return that->inputs;

```

```

}

// Get the output values of the NeuraMorph 'that'
#if BUILDMODE != 0
static inline
#endif
const VecFloat* NMOutputs(const NeuraMorph* that) {

#if BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PErrCatch(NeuraMorphErr);

    }

#endif

    return that->outputs;

}

// Get the hidden values of the NeuraMorph 'that'
#if BUILDMODE != 0
static inline
#endif
const VecFloat* NMHiddens(const NeuraMorph* that) {

#if BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PErrCatch(NeuraMorphErr);

    }

#endif

    return that->hiddens;

}

// Get the number of hidden values of the NeuraMorph 'that'
#if BUILDMODE != 0
static inline
#endif
long NMGetNbHidden(const NeuraMorph* that) {

#if BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PErrTypeNullPointer;

```

```

        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PBErCatch(NeuraMorphErr);
    }

#endif

    long nb = 0;
    if (that->hiddens != NULL) {

        nb = VecGetDim(that->hiddens);
    }

    return nb;
}

// Set the number of hidden values of the NeuraMorph 'that' to 'nb'
#if BUILDMODE != 0
static inline
#endif
void NMSetNbHidden(
    NeuraMorph* that,
    long nb) {

#if BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PBErTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PBErCatch(NeuraMorphErr);
    }

    if (nb <= 0) {

        NeuraMorphErr->_type = PBErTypeInvalidArg;
        sprintf(
            NeuraMorphErr->_msg,
            "'nb' is invalid (%ld>0)",
            nb);
        PBErCatch(NeuraMorphErr);
    }

#endif

    if (that->hiddens != NULL) {

        VecFree(&(that->hiddens));
    }

    that->hiddens = VecFloatCreate(nb);
}

```

```

// Get the lowest bound of hidden values of the NeuraMorph 'that'
#if BUILDMODE != 0
static inline
#endif
const VecFloat* NMLowHiddens(const NeuraMorph* that) {

#if BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PBErrCatch(NeuraMorphErr);

    }

#endif

    return that->lowHiddens;

}

// Get the highest bound of hidden values of the NeuraMorph 'that'
#if BUILDMODE != 0
static inline
#endif
const VecFloat* NMHighHiddens(const NeuraMorph* that) {

#if BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PBErrCatch(NeuraMorphErr);

    }

#endif

    return that->highHiddens;

}

// Get the flag for one hot encoding of the NeuraMorph 'that'
#if BUILDMODE != 0
static inline
#endif
bool NMGetFlagOneHot(const NeuraMorph* that) {

#if BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,

```



```

        "'that' is null");
        PBErCatch(NeuraMorphErr);

    }

#endif

    return that->flagOneHot;

}

// Set the flag for one hot encoding of the NeuraMorph 'that' to 'flag'
#if BUILDMODE != 0
static inline
#endif
void NMSetFlagOneHot(
    NeuraMorph* that,
    bool flag) {

#if BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PBErTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PBErCatch(NeuraMorphErr);

    }

#endif

    that->flagOneHot = flag;

}

// ----- NeuraMorphTrainer

// ===== Functions implementation =====

// Get the depth of the NeuraMorphTrainer 'that'
#if BUILDMODE != 0
static inline
#endif
short NMTrainerGetDepth(const NeuraMorphTrainer* that) {

#if BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PBErTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PBErCatch(NeuraMorphErr);

    }

#endif

    return that->depth;
}

```

```

}

// Set the depth of the NeuraMorphTrainer 'that' to 'depth'
#if BUILDMODE != 0
static inline
#endif
void NMTrainerSetDepth(
    NeuraMorphTrainer* that,
    short depth) {

#if BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PBErrCatch(NeuraMorphErr);

    }

    if (depth < 1) {

        NeuraMorphErr->_type = PBErrTypeInvalidArg;
        sprintf(
            NeuraMorphErr->_msg,
            "'depth' is invalid (%d>=1)",
            depth);
        PBErrCatch(NeuraMorphErr);

    }

#endif

    that->depth = depth;

}

// Get the maxLv1Div of the NeuraMorphTrainer 'that'
#if BUILDMODE != 0
static inline
#endif
short NMTrainerGetMaxLv1Div(const NeuraMorphTrainer* that) {

#if BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PBErrCatch(NeuraMorphErr);

    }

#endif

    return that->maxLv1Div;
}

```

```

}

// Set the maxLvlDiv of the NeuraMorphTrainer 'that' to 'lvl'
#if BUILDMODE != 0
static inline
#endif
void NMTrainerSetMaxLvlDiv(
    NeuraMorphTrainer* that,
    short lvl) {

#if BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PBErrCatch(NeuraMorphErr);

    }

    if (lvl < 0) {

        NeuraMorphErr->_type = PBErrTypeInvalidArg;
        sprintf(
            NeuraMorphErr->_msg,
            "'lvl' is invalid (%d>=0)",
            lvl);
        PBErrCatch(NeuraMorphErr);

    }

#endif

    that->maxLvlDiv = lvl;

}

// Get the order of the NeuraMorphTrainer 'that'
#if BUILDMODE != 0
static inline
#endif
int NMTrainerGetOrder(const NeuraMorphTrainer* that) {

#if BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PBErrCatch(NeuraMorphErr);

    }

#endif

    return that->order;

}

```

```

// Set the order of the NeuraMorphTrainer 'that' to 'order'
#if BUILDMODE != 0
static inline
#endif
void NMTrainerSetOrder(
    NeuraMorphTrainer* that,
    int order) {

#if BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PBErrCatch(NeuraMorphErr);

    }

    if (order < 1) {

        NeuraMorphErr->_type = PBErrTypeInvalidArg;
        sprintf(
            NeuraMorphErr->_msg,
            "'order' is invalid (%d>=1)",
            order);
        PBErrCatch(NeuraMorphErr);

    }

#endif

    that->order = order;

}

// Get the nbMaxInputsUnit of the NeuraMorphTrainer 'that'
#if BUILDMODE != 0
static inline
#endif
int NMTrainerGetNbMaxInputsUnit(const NeuraMorphTrainer* that) {

#if BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PBErrCatch(NeuraMorphErr);

    }

#endif

    return that->nbMaxInputsUnit;

}

```

```

// Set the nbMaxInputsUnit of the NeuraMorphTrainer 'that' to 'order'
#if BUILDMODE != 0
static inline
#endif
void NMTrainerSetNbMaxInputsUnit(
    NeuraMorphTrainer* that,
    int nbMaxInputsUnit) {

#if BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PErrCatch(NeuraMorphErr);

    }

    if (nbMaxInputsUnit < 2) {

        NeuraMorphErr->_type = PErrTypeInvalidArg;
        sprintf(
            NeuraMorphErr->_msg,
            "'nbMaxInputsUnit' is invalid (%d>=2)",
            nbMaxInputsUnit);
        PErrCatch(NeuraMorphErr);

    }

#endif

    that->nbMaxInputsUnit = nbMaxInputsUnit;

}

// Get the NeuraMorph of the NeuraMorphTrainer 'that'
#if BUILDMODE != 0
static inline
#endif
NeuraMorph* NMTrainerNeuraMorph(const NeuraMorphTrainer* that) {

#if BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PErrCatch(NeuraMorphErr);

    }

#endif

    return that->neuraMorph;

}

// Get the GDataSet of the NeuraMorphTrainer 'that'

```

```

#if BUILDMODE != 0
static inline
#endif
GDataSetVecFloat* NMTrainerDataset(const NeuraMorphTrainer* that) {

#if BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PErrCatch(NeuraMorphErr);

    }

#endif

    return that->dataset;

}

// Get the index of the training category of the NeuraMorphTrainer 'that'
#if BUILDMODE != 0
static inline
#endif
unsigned int NMTrainerGetICatTraining(const NeuraMorphTrainer* that) {

#if BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PErrCatch(NeuraMorphErr);

    }

#endif

    return that->iCatTraining;

}

// Set the index of the training category of the NeuraMorphTrainer 'that'
// to 'iCat'
#if BUILDMODE != 0
static inline
#endif
void NMTrainerSetICatTraining(
    NeuraMorphTrainer* that,
    unsigned int iCatTraining) {

#if BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PErrTypeNullPointer;
        sprintf(

```

```

        NeuraMorphErr->_msg,
        "'that' is null");
        PBErCatch(NeuraMorphErr);
    }

#endif

    that->iCatTraining = iCatTraining;
}

// Get the index of the evaluation category of the NeuraMorphTrainer 'that'
#if BUILDMODE != 0
static inline
#endif
unsigned int NMTrainerGetICatEval(const NeuraMorphTrainer* that) {

#if BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PBErTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PBErCatch(NeuraMorphErr);
    }

#endif

    return that->iCatEval;
}

// Set the index of the evaluation category of the NeuraMorphTrainer 'that'
// to 'iCat'
#if BUILDMODE != 0
static inline
#endif
void NMTrainerSetICatEval(
    NeuraMorphTrainer* that,
    unsigned int iCatEval) {

#if BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PBErTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PBErCatch(NeuraMorphErr);
    }

#endif

    that->iCatEval = iCatEval;
}

```

```

// Get the weakness threshold of the NeuraMorphTrainer 'that'
#if BUILDMODE != 0
static inline
#endif
float NMTrainerGetWeakThreshold(const NeuraMorphTrainer* that) {

#if BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PBErrCatch(NeuraMorphErr);

    }

#endif

    return that->weakUnitThreshold;

}

// Set the weakness threshold of the NeuraMorphTrainer 'that'
// to 'iCat'
#if BUILDMODE != 0
static inline
#endif
void NMTrainerSetWeakThreshold(
    NeuraMorphTrainer* that,
    float weakUnitThreshold) {

#if BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PBErrCatch(NeuraMorphErr);

    }

#endif

    that->weakUnitThreshold = weakUnitThreshold;

}

// Get the nbMaxUnitDepth of the NeuraMorphTrainer 'that'
#if BUILDMODE != 0
static inline
#endif
int NMTrainerGetNbMaxUnitDepth(const NeuraMorphTrainer* that) {

#if BUILDMODE == 0

    if (that == NULL) {

```



```

        NeuraMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PBErrCatch(NeuraMorphErr);
    }

#endif

    return that->nbMaxUnitDepth;
}

// Set the nbMaxUnitDepth of the NeuraMorphTrainer 'that' to 'nbMaxUnitDepth'
#if BUILDMODE != 0
static inline
#endif
void NMTrainerSetNbMaxUnitDepth(
    NeuraMorphTrainer* that,
    int nbMaxUnitDepth) {

#if BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PBErrCatch(NeuraMorphErr);
    }

#endif

    that->nbMaxUnitDepth = nbMaxUnitDepth;
}

// Get the result of the last evaluation of the NeuraMorphTrainer 'that'
#if BUILDMODE != 0
static inline
#endif
const VecFloat* NMTrainerResEval(const NeuraMorphTrainer* that) {

#if BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PBErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PBErrCatch(NeuraMorphErr);
    }

#endif

    return that->resEval;
}

```

```

}

// Get the streamInfo of the NeuraMorphTrainer 'that'
#if BUILDMODE != 0
static inline
#endif
FILE* NMTrainerStreamInfo(const NeuraMorphTrainer* that) {

#if BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PErrCatch(NeuraMorphErr);

    }

#endif

    return that->streamInfo;

}

// Set the streamInfo of the NeuraMorphTrainer 'that' to 'streamInfo'
#if BUILDMODE != 0
static inline
#endif
void NMTrainerSetStreamInfo(
    NeuraMorphTrainer* that,
    FILE* streamInfo) {

#if BUILDMODE == 0

    if (that == NULL) {

        NeuraMorphErr->_type = PErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PErrCatch(NeuraMorphErr);

    }

#endif

    that->streamInfo = streamInfo;

}

// Get the number of correct output in the last evaluation of the
// NeuraMorphTrainer 'that'
#if BUILDMODE != 0
static inline
#endif
long NMTrainerGetNbCorrect(const NeuraMorphTrainer* that) {

#if BUILDMODE == 0

    if (that == NULL) {

```

```

        NeuraMorphErr->_type = PErrTypeNullPointer;
        sprintf(
            NeuraMorphErr->_msg,
            "'that' is null");
        PErrCatch(NeuraMorphErr);

    }

#endif

    return that->nbCorrect;

}

```

4 Makefile

```

# Build mode
# 0: development (max safety, no optimisation)
# 1: release (min safety, optimisation)
# 2: fast and furious (no safety, optimisation)
BUILD_MODE?=1

all: pbmake_wget main validation

# Automatic installation of the repository PBMake in the parent folder
pbmake_wget:
if [ ! -d ../PBMake ]; then wget https://github.com/BayashiPascal/PBMake/archive/master.zip; unzip master.zip; rm -f

# Makefile definitions
MAKEFILE_INC=../PBMake/Makefile.inc
include $(MAKEFILE_INC)

# Rules to make the executable
repo=neuramorph
$(repo)_EXENAME: \
$(repo)_EXENAME.o \
$(repo)_EXE_DEP \
$(repo)_DEP
$(COMPILER) 'echo "$(repo)_EXE_DEP $(repo)_EXENAME.o" | tr ' ' '\n' | sort -u' $(LINK_ARG) $(repo)_LINK_ARG

$(repo)_EXENAME.o: \
$(repo)_DIR/$(repo)_EXENAME.c \
$(repo)_INC_H_EXE \
$(repo)_EXE_DEP
$(COMPILER) $(BUILD_ARG) $(repo)_BUILD_ARG 'echo "$(repo)_INC_DIR" | tr ' ' '\n' | sort -u' -c $(repo)_DIR)/

validation: \
validation.o \
$(repo)_EXE_DEP \
$(repo)_DEP
$(COMPILER) 'echo "$(repo)_EXE_DEP validation.o" | tr ' ' '\n' | sort -u' $(LINK_ARG) $(repo)_LINK_ARG -o vali

validation.o: \
$(repo)_DIR/validation.c \
$(repo)_INC_H_EXE \
$(repo)_EXE_DEP
$(COMPILER) $(BUILD_ARG) $(repo)_BUILD_ARG 'echo "$(repo)_INC_DIR" | tr ' ' '\n' | sort -u' -c $(repo)_DIR)/

```

5 Unit tests

```
#include <stdlib.h>
#include <stdio.h>
#include <time.h>
#include <string.h>
#include <time.h>
#include <unistd.h>
#include <sys/time.h>
#include "neuramorph.h"

void UnitTestNeuraMorphUnitCreateFree() {

    VecLong* iIn = VecLongCreate(3);
    VecSet(
        iIn,
        0,
        0);
    VecSet(
        iIn,
        1,
        1);
    VecSet(
        iIn,
        2,
        2);
    VecLong* iOut = VecLongCreate(2);
    VecSet(
        iOut,
        0,
        0);
    VecSet(
        iOut,
        1,
        1);
    NeuraMorphUnit* unit =
        NeuraMorphUnitCreate(
            iIn,
            iOut);
    bool isSame =
        ISEQUALF(
            unit->value,
            0.0);
    if (
        VecGetDim(unit->outputs) != 2 ||
        VecGetDim(unit->lowFilters) != 3 ||
        VecGetDim(unit->highFilters) != 3 ||
        VecGetDim(unit->unitInputs) != 3 ||
        isSame != true ||
        unit->lowOutputs != NULL ||
        unit->highOutputs != NULL) {

        NeuraMorphErr->_type = PBErrTypeUnitTestFailed;
        sprintf(
            NeuraMorphErr->_msg,
            "NeuraMorphUnitCreate failed (1)");
        PBErrCatch(NeuraMorphErr);

    }

    isSame =
```

```

        VecIsEqual(
            unit->iInputs,
            iIn);
    if (isSame == false) {

        NeuraMorphErr->_type = PBErrTypeUnitTestFailed;
        sprintf(
            NeuraMorphErr->_msg,
            "NeuraMorphUnitCreate failed (2)");
        PBErrCatch(NeuraMorphErr);

    }

    isSame =
        VecIsEqual(
            unit->iOutputs,
            iOut);
    if (isSame == false) {

        NeuraMorphErr->_type = PBErrTypeUnitTestFailed;
        sprintf(
            NeuraMorphErr->_msg,
            "NeuraMorphUnitCreate failed (3)");
        PBErrCatch(NeuraMorphErr);

    }

    NeuraMorphUnitFree(&unit);
    if (unit != NULL) {

        NeuraMorphErr->_type = PBErrTypeUnitTestFailed;
        sprintf(
            NeuraMorphErr->_msg,
            "NeuraMorphUnitFree failed");
        PBErrCatch(NeuraMorphErr);

    }

    VecFree(&iIn);
    VecFree(&iOut);
    printf("UnitTestNeuraMorphUnitCreateFree OK\n");

}

void UnitTestNeuraMorphUnitGetSetPrint() {

    VecLong* iIn = VecLongCreate(3);
    VecLong* iOut = VecLongCreate(2);
    NeuraMorphUnit* unit =
        NeuraMorphUnitCreate(
            iIn,
            iOut);

    if (NMUnitIInputs(unit) != unit->iInputs) {

        NeuraMorphErr->_type = PBErrTypeUnitTestFailed;
        sprintf(
            NeuraMorphErr->_msg,
            "NMUnitIInputs failed");
        PBErrCatch(NeuraMorphErr);

    }

}

```

```

if (NMUnitIOOutputs(unit) != unit->iOutputs) {

    NeuroMorphErr->_type = PBErrTypeUnitTestFailed;
    sprintf(
        NeuroMorphErr->_msg,
        "NMUnitIOOutputs failed");
    PBErrCatch(NeuroMorphErr);

}

if (NMUnitOutputs(unit) != unit->outputs) {

    NeuroMorphErr->_type = PBErrTypeUnitTestFailed;
    sprintf(
        NeuroMorphErr->_msg,
        "NMUnitOutputs failed");
    PBErrCatch(NeuroMorphErr);

}

if (NMUnitGetNbInputs(unit) != 3) {

    NeuroMorphErr->_type = PBErrTypeUnitTestFailed;
    sprintf(
        NeuroMorphErr->_msg,
        "NMUnitGetNbInputs failed");
    PBErrCatch(NeuroMorphErr);

}

if (NMUnitGetNbOutputs(unit) != 2) {

    NeuroMorphErr->_type = PBErrTypeUnitTestFailed;
    sprintf(
        NeuroMorphErr->_msg,
        "NMUnitGetNbOutputs failed");
    PBErrCatch(NeuroMorphErr);

}

bool isSame =
    ISEQUALF(
        NMUnitGetValue(unit),
        0.0);
if (isSame != true) {

    NeuroMorphErr->_type = PBErrTypeUnitTestFailed;
    sprintf(
        NeuroMorphErr->_msg,
        "NMUnitGetValue failed");
    PBErrCatch(NeuroMorphErr);

}

NMUnitSetValue(
    unit,
    0.5);
isSame =
    ISEQUALF(
        NMUnitGetValue(unit),
        0.5);

```

```

if (isSame != true) {

    NeuraMorphErr->_type = PBErrTypeUnitTestFailed;
    sprintf(
        NeuraMorphErr->_msg,
        "NMUnitSetValue failed");
    PBErrCatch(NeuraMorphErr);

}

NMUnitPrintln(
    unit,
    stdout);

NeuraMorphUnitFree(&unit);
VecFree(&iIn);
VecFree(&iOut);
printf("UnitTestNeuraMorphUnitGetSetPrint OK\n");

}

void UnitTestNeuraMorphUnitEvaluate() {

    VecLong* iIn = VecLongCreate(3);
    VecLong* iOut = VecLongCreate(2);
    NeuraMorphUnit* unit =
        NeuraMorphUnitCreate(
            iIn,
            iOut);

    for (
        long iInput = 3;
        iInput--;) {

        VecSet(
            unit->lowFilters,
            iInput,
            0.0);
        VecSet(
            unit->highFilters,
            iInput,
            2.0);

    }

    VecShort2D dim = VecShortCreateStatic2D();
    VecSet(
        &dim,
        0,
        3);
    VecSet(
        &dim,
        1,
        2);
    unit->transfer =
        BBodyCreate(
            1,
            &dim);
    unit->transfer->_ctrl[0]->_val[0] = 1.0;
    unit->transfer->_ctrl[0]->_val[1] = 2.0;

    VecFloat* inputs = VecFloatCreate(3);

```

```

VecSet(
    inputs,
    0,
    1.0);
VecSet(
    inputs,
    1,
    3.0);
VecSet(
    inputs,
    2,
    1.5);

NMUnitEvaluate(
    unit,
    inputs);

float check[2];
check[0] = -0.0625;
check[1] = -0.125;
VecFloat2D checkHigh = VecFloatCreateStatic2D();
VecSet(
    &checkHigh,
    0,
    check[0]);
VecSet(
    &checkHigh,
    1,
    check[1]);
VecFloat2D checkLow = checkHigh;
for (
    long iOutput = 2;
    iOutput--;) {

    float v =
        VecGet(
            unit->outputs,
            iOutput);
    bool same =
        ISEQUALF(
            v,
            check[iOutput]);
    if (same == false) {

        NeuraMorphErr->_type = PBErrTypeUnitTestFailed;
        sprintf(
            NeuraMorphErr->_msg,
            "NMUnitEvaluate failed (1)");
        PBErrCatch(NeuraMorphErr);

    }

}

bool sameLow =
    VecIsEqual(
        &checkLow,
        unit->lowOutputs);
bool sameHigh =
    VecIsEqual(
        &checkHigh,
        unit->highOutputs);

```



```

if (
    sameLow == false ||
    sameHigh == false) {

    NeuroMorphErr->_type = PBErrTypeUnitTestFailed;
    sprintf(
        NeuroMorphErr->_msg,
        "NMUnitEvaluate failed (2)");
    PBErrCatch(NeuroMorphErr);

}

NeuroMorphUnitFree(&unit);
VecFree(&iIn);
VecFree(&iOut);
VecFree(&inputs);
printf("UnitTestNeuroMorphUnitEvaluate OK\n");

}

void UnitTestNeuroMorphUnit() {

    UnitTestNeuroMorphUnitCreateFree();
    UnitTestNeuroMorphUnitGetSetPrint();
    UnitTestNeuroMorphUnitEvaluate();
    printf("UnitTestNeuroMorphUnit OK\n");

}

void UnitTestNeuroMorphCreateFree() {

    NeuroMorph* nm =
        NeuroMorphCreate(
            3,
            2);
    if (
        nm->nbInput != 3 ||
        nm->nbOutput != 2 ||
        nm->flagOneHot != false ||
        VecGetDim(nm->inputs) != 3 ||
        VecGetDim(nm->outputs) != 2 ||
        nm->hiddens != NULL ||
        GSetNbElem(&(nm->units)) != 0) {

        NeuroMorphErr->_type = PBErrTypeUnitTestFailed;
        sprintf(
            NeuroMorphErr->_msg,
            "NeuroMorphCreate failed");
        PBErrCatch(NeuroMorphErr);

    }

    NeuroMorphFree(&nm);
    if (nm != NULL) {

        NeuroMorphErr->_type = PBErrTypeUnitTestFailed;
        sprintf(
            NeuroMorphErr->_msg,
            "NeuroMorphFree failed");
        PBErrCatch(NeuroMorphErr);

    }

}

```

```

    printf("UnitTestNeuraMorphCreateFree OK\n");
}

void UnitTestNeuraMorphGetSet() {

    NeuraMorph* nm =
        NeuraMorphCreate(
            3,
            2);
    if (NMGetNbInput(nm) != 3) {

        NeuraMorphErr->_type = PBErrTypeUnitTestFailed;
        sprintf(
            NeuraMorphErr->_msg,
            "NMGetNbInput failed");
        PBErrCatch(NeuraMorphErr);

    }

    if (NMGetNbOutput(nm) != 2) {

        NeuraMorphErr->_type = PBErrTypeUnitTestFailed;
        sprintf(
            NeuraMorphErr->_msg,
            "NMGetNbOutput failed");
        PBErrCatch(NeuraMorphErr);

    }

    if (NMGetNbHidden(nm) != 0) {

        NeuraMorphErr->_type = PBErrTypeUnitTestFailed;
        sprintf(
            NeuraMorphErr->_msg,
            "NMGetNbHidden failed");
        PBErrCatch(NeuraMorphErr);

    }

    if (NMGetFlagOneHot(nm) != false) {

        NeuraMorphErr->_type = PBErrTypeUnitTestFailed;
        sprintf(
            NeuraMorphErr->_msg,
            "NMGetFlagOneHot failed");
        PBErrCatch(NeuraMorphErr);

    }

    NMSetNbHidden(
        nm,
        5);
    if (NMGetNbHidden(nm) != 5) {

        NeuraMorphErr->_type = PBErrTypeUnitTestFailed;
        sprintf(
            NeuraMorphErr->_msg,
            "NMSetNbHidden failed");
        PBErrCatch(NeuraMorphErr);

    }
}

```

```

}

NMSetFlagOneHot(
    nm,
    true);
if (NMGetFlagOneHot(nm) != true) {

    NeuraMorphErr->_type = PBErrTypeUnitTestFailed;
    sprintf(
        NeuraMorphErr->_msg,
        "NMSetFlagOneHot failed");
    PBErrCatch(NeuraMorphErr);

}

VecLong* iOuts = NMGetVecIOutputs(nm);
VecLong2D checkOuts =
    VecLongCreateStatic2D();
VecSet(
    &checkOuts,
    0,
    5);
VecSet(
    &checkOuts,
    1,
    6);
bool isSame =
    VecIsEqual(
        &checkOuts,
        iOuts);
if (isSame == false) {

    NeuraMorphErr->_type = PBErrTypeUnitTestFailed;
    sprintf(
        NeuraMorphErr->_msg,
        "NMGetVecIOutputs failed");
    PBErrCatch(NeuraMorphErr);

}

VecFree(&iOuts);

if (NMInputs(nm) != nm->inputs) {

    NeuraMorphErr->_type = PBErrTypeUnitTestFailed;
    sprintf(
        NeuraMorphErr->_msg,
        "NMInputs failed");
    PBErrCatch(NeuraMorphErr);

}

if (NMOutputs(nm) != nm->outputs) {

    NeuraMorphErr->_type = PBErrTypeUnitTestFailed;
    sprintf(
        NeuraMorphErr->_msg,
        "NMOutputs failed");
    PBErrCatch(NeuraMorphErr);

}

```

```

if (NMHiddens(nm) != nm->hiddens) {

    NeuraMorphErr->_type = PBErrTypeUnitTestFailed;
    sprintf(
        NeuraMorphErr->_msg,
        "NMHiddens failed");
    PBErrCatch(NeuraMorphErr);

}

if (NMLowHiddens(nm) != nm->lowHiddens) {

    NeuraMorphErr->_type = PBErrTypeUnitTestFailed;
    sprintf(
        NeuraMorphErr->_msg,
        "NMLowHiddens failed");
    PBErrCatch(NeuraMorphErr);

}

if (NMHighHiddens(nm) != nm->highHiddens) {

    NeuraMorphErr->_type = PBErrTypeUnitTestFailed;
    sprintf(
        NeuraMorphErr->_msg,
        "NMHighHiddens failed");
    PBErrCatch(NeuraMorphErr);

}

NeuraMorphFree(&nm);

printf("UnitTestNeuraMorphGetSet OK\n");

}

void UnitTestNeuraMorphAddRemoveUnit() {

    VecLong3D iInputs = VecLongCreateStatic3D();
    VecSet(
        &iInputs,
        0,
        0);
    VecSet(
        &iInputs,
        1,
        1);
    VecSet(
        &iInputs,
        2,
        2);
    VecLong2D iOutputs = VecLongCreateStatic2D();
    VecSet(
        &iOutputs,
        0,
        0);
    VecSet(
        &iOutputs,
        1,
        1);

    NeuraMorph* nm =

```

```

NeuraMorphCreate(
    3,
    2);

NeuraMorphUnit* unit =
    NMAddUnit(
        nm,
        (VecLong*)&iInputs,
        (VecLong*)&iOutputs);

bool isSameA =
    VecIsEqual(
        &iInputs,
        unit->iInputs);
bool isSameB =
    VecIsEqual(
        &iOutputs,
        unit->iOutputs);
if (
    GSetNbElem(&(nm->units)) != 1 ||
    GSetHead(&(nm->units)) != unit ||
    isSameA == false ||
    isSameB == false) {

    NeuraMorphErr->_type = PBErrTypeUnitTestFailed;
    sprintf(
        NeuraMorphErr->_msg,
        "NMAddUnit failed");
    PBErrCatch(NeuraMorphErr);

}

NeuraMorphFree(&nm);

nm =
    NeuraMorphCreate(
        3,
        2);

unit =
    NMAddUnit(
        nm,
        (VecLong*)&iInputs,
        (VecLong*)&iOutputs);

NMRemoveUnit(
    nm,
    unit);

if (GSetNbElem(&(nm->units)) != 0) {

    NeuraMorphErr->_type = PBErrTypeUnitTestFailed;
    sprintf(
        NeuraMorphErr->_msg,
        "NMRemoveUnit failed");
    PBErrCatch(NeuraMorphErr);

}

NeuraMorphUnitFree(&unit);
NeuraMorphFree(&nm);

```

```

    printf("UnitTestNeuraMorphAddRemoveUnit OK\n");
}

void UnitTestNeuraMorphBurryUnitsEvaluate() {

    VecLong3D iInputs = VecLongCreateStatic3D();
    VecSet(
        &iInputs,
        0,
        0);
    VecSet(
        &iInputs,
        1,
        1);
    VecSet(
        &iInputs,
        2,
        2);
    VecLong2D iOutputs = VecLongCreateStatic2D();
    VecSet(
        &iOutputs,
        0,
        0);
    VecSet(
        &iOutputs,
        1,
        1);

    NeuraMorph* nm =
        NeuraMorphCreate(
            3,
            2);

    NeuraMorphUnit* unitA =
        NeuraMorphUnitCreate(
            (VecLong*)&iInputs,
            (VecLong*)&iOutputs);

    NeuraMorphUnit* unitB =
        NeuraMorphUnitCreate(
            (VecLong*)&iInputs,
            (VecLong*)&iOutputs);

    for (
        long iInput = 3;
        iInput--;) {

        VecSet(
            unitA->lowFilters,
            iInput,
            0.0);
        VecSet(
            unitA->highFilters,
            iInput,
            2.0);
        VecSet(
            unitB->lowFilters,
            iInput,
            0.0);
        VecSet(
            unitB->highFilters,

```

```

        iInput,
        2.0);
}

VecShort2D dim = VecShortCreateStatic2D();
VecSet(
    &dim,
    0,
    3);
VecSet(
    &dim,
    1,
    2);
unitA->transfer =
    BBodyCreate(
        1,
        &dim);
unitA->transfer->_ctrl[0]->_val[0] = 1.0;
unitA->transfer->_ctrl[0]->_val[1] = 2.0;
unitB->transfer =
    BBodyCreate(
        1,
        &dim);
unitB->transfer->_ctrl[0]->_val[0] = 2.0;
unitB->transfer->_ctrl[0]->_val[1] = 1.0;

float x = 1.0;
float y = 0.5;
float z = 1.5;
VecFloat* evalInputs = VecFloatCreate(3);
VecSet(
    evalInputs,
    0,
    x);
VecSet(
    evalInputs,
    1,
    y);
VecSet(
    evalInputs,
    2,
    z);

NMUnitEvaluate(
    unitA,
    evalInputs);
NMUnitEvaluate(
    unitB,
    evalInputs);

GSet units = GSetCreateStatic();
GSetAppend(
    &units,
    unitA);
GSetAppend(
    &units,
    unitB);

NMBurryUnits(
    nm,
    &units);

```

```

if (
    GSetNbElem(&units) != 0 ||
    nm->hiddens == NULL ||
    VecGetDim(nm->hiddens) != 4) {

    NeuraMorphErr->_type = PErrTypeUnitTestFailed;
    sprintf(
        NeuraMorphErr->_msg,
        "NMBurryUnits failed (1)");
    PErrCatch(NeuraMorphErr);

}

VecLong2D checkA = VecLongCreateStatic2D();
VecSet(
    &checkA,
    0,
    0);
VecSet(
    &checkA,
    1,
    1);
VecLong2D checkB = VecLongCreateStatic2D();
VecSet(
    &checkB,
    0,
    2);
VecSet(
    &checkB,
    1,
    3);

bool isSameA =
    VecIsEqual(
        &checkA,
        unitA->iOutputs);
bool isSameB =
    VecIsEqual(
        &checkB,
        unitB->iOutputs);
if (
    isSameA == false ||
    isSameB == false) {

    NeuraMorphErr->_type = PErrTypeUnitTestFailed;
    sprintf(
        NeuraMorphErr->_msg,
        "NMBurryUnits failed (2)");
    PErrCatch(NeuraMorphErr);

}

float checkLowAa =
    VecGet(
        unitA->lowOutputs,
        0);
checkLowAa -=
    VecGet(
        nm->lowHiddens,
        0);
bool isSameLowAa =

```



```

ISEQUALF(
    checkLowAa,
    0.0);
float checkLowAb =
    VecGet(
        unitA->lowOutputs,
        1);
checkLowAb -=
    VecGet(
        nm->lowHiddens,
        1);
bool isSameLowAb =
    ISEQUALF(
        checkLowAb,
        0.0);
float checkLowBa =
    VecGet(
        unitB->lowOutputs,
        0);
checkLowBa -=
    VecGet(
        nm->lowHiddens,
        2);
bool isSameLowBa =
    ISEQUALF(
        checkLowBa,
        0.0);
float checkLowBb =
    VecGet(
        unitB->lowOutputs,
        1);
checkLowBb -=
    VecGet(
        nm->lowHiddens,
        3);
bool isSameLowBb =
    ISEQUALF(
        checkLowBb,
        0.0);
float checkHighAa =
    VecGet(
        unitA->lowOutputs,
        0);
checkHighAa -=
    VecGet(
        nm->lowHiddens,
        0);
bool isSameHighAa =
    ISEQUALF(
        checkHighAa,
        0.0);
float checkHighAb =
    VecGet(
        unitA->lowOutputs,
        1);
checkHighAb -=
    VecGet(
        nm->lowHiddens,
        1);
bool isSameHighAb =
    ISEQUALF(
        checkHighAb,

```

```

    0.0);
float checkHighBa =
    VecGet(
        unitB->lowOutputs,
        0);
checkHighBa -=
    VecGet(
        nm->lowHiddens,
        2);
bool isSameHighBa =
    ISEQUALF(
        checkHighBa,
        0.0);
float checkHighBb =
    VecGet(
        unitB->lowOutputs,
        1);
checkHighBb -=
    VecGet(
        nm->lowHiddens,
        3);
bool isSameHighBb =
    ISEQUALF(
        checkHighBb,
        0.0);
if (
    isSameLowAa == false ||
    isSameLowAb == false ||
    isSameLowBa == false ||
    isSameLowBb == false ||
    isSameHighAa == false ||
    isSameHighAb == false ||
    isSameHighBa == false ||
    isSameHighBb == false) {

    NeuraMorphErr->_type = PBErrTypeUnitTestFailed;
    sprintf(
        NeuraMorphErr->_msg,
        "NMBurryUnits failed (3)");
    PBErrCatch(NeuraMorphErr);

}

VecSet(
    &iInputs,
    0,
    3);
VecSet(
    &iInputs,
    1,
    4);
VecSet(
    &iInputs,
    2,
    5);
VecSet(
    &iOutputs,
    0,
    4);
VecSet(
    &iOutputs,
    1,

```

```

5);
NeuraMorphUnit* unitC =
    NMAddUnit(
        nm,
        (VecLong*)&iInputs,
        (VecLong*)&iOutputs);

for (
    long iInput = 3;
    iInput--;) {

    VecSet(
        unitC->lowFilters,
        iInput,
        0.0);
    VecSet(
        unitC->highFilters,
        iInput,
        20.0);

}

unitC->transfer =
    BBodyCreate(
        1,
        &dim);
unitC->transfer->_ctrl[0]->_val[0] = -1.0;
unitC->transfer->_ctrl[0]->_val[1] = -2.0;

NMEvaluate(
    nm,
    evalInputs);
float checkAout[2];
checkAout[0] =
    0.09375 -
    VecGet(
        nm->hiddens,
        0);
checkAout[1] =
    0.1875 -
    VecGet(
        nm->hiddens,
        1);
float checkBout[2];
checkBout[0] =
    0.1875 -
    VecGet(
        nm->hiddens,
        2);
checkBout[1] =
    0.09375 -
    VecGet(
        nm->hiddens,
        3);

bool isSameAa =
    ISEQUALF(
        checkAout[0],
        0.0);
bool isSameAb =
    ISEQUALF(
        checkAout[1],

```

```

    0.0);
bool isSameBa =
    ISEQUALF(
        checkBout[0],
        0.0);
bool isSameBb =
    ISEQUALF(
        checkBout[1],
        0.0);
if (
    isSameAa == false ||
    isSameAb == false ||
    isSameBa == false ||
    isSameBb == false) {

    NeuraMorphErr->_type = PErrTypeUnitTestFailed;
    sprintf(
        NeuraMorphErr->_msg,
        "NMEvaluate failed (1)");
    PErrCatch(NeuraMorphErr);

}

x =
    VecGet(
        nm->hiddens,
        0);
y =
    VecGet(
        nm->hiddens,
        1);
z =
    VecGet(
        nm->hiddens,
        2);
float checkCout[2];
checkCout[0] =
    -0.976738 -
    VecGet(
        unitC->outputs,
        0);
checkCout[1] =
    -1.953476 -
    VecGet(
        unitC->outputs,
        1);

bool isSameCa =
    ISEQUALF(
        checkCout[0],
        0.0);
bool isSameCb =
    ISEQUALF(
        checkCout[1],
        0.0);
bool isSameCc =
    VecIsEqual(
        unitC->outputs,
        nm->outputs);
if (
    isSameCa == false ||
    isSameCb == false ||

```

```

        isSameCc == false) {

    NeuraMorphErr->_type = PBErrTypeUnitTestFailed;
    sprintf(
        NeuraMorphErr->_msg,
        "NMEvaluate failed (2)");
    PBErrCatch(NeuraMorphErr);

}

VecFree(&evalInputs);
NeuraMorphFree(&nm);

printf("UnitTestNeuraMorphBurryUnitsEvaluate OK\n");

}

void UnitTestNeuraMorph() {

    UnitTestNeuraMorphCreateFree();
    UnitTestNeuraMorphGetSet();
    UnitTestNeuraMorphAddRemoveUnit();
    UnitTestNeuraMorphBurryUnitsEvaluate();
    printf("UnitTestNeuraMorph OK\n");

}

void UnitTestNeuraMorphTrainerCreateFree() {

    GDataSetVecFloat dataset =
        GDataSetVecFloatCreateStaticFromFile("./Datasets/iris.json");
    NeuraMorph* nm =
        NeuraMorphCreate(
            GDSGetNbInputs(&dataset),
            GDSGetNbOutputs(&dataset));
    NeuraMorphTrainer trainer =
        NeuraMorphTrainerCreateStatic(
            nm,
            &dataset);
    bool isSame =
        ISEQUALF(
            trainer.weakUnitThreshold,
            0.9);
    if (
        trainer.neuraMorph != nm ||
        trainer.depth != 2 ||
        trainer.order != 1 ||
        trainer.nbCorrect != 0 ||
        trainer.nbMaxUnitDepth != 2 ||
        trainer.streamInfo != NULL ||
        trainer.maxLvlDiv != 2 ||
        trainer.nbMaxInputsUnit != GDSGetNbOutputs(&dataset) ||
        isSame != true ||
        trainer.iCatTraining != 0 ||
        trainer.iCatEval != 1 ||
        trainer.dataset != &dataset) {

        NeuraMorphErr->_type = PBErrTypeUnitTestFailed;
        sprintf(
            NeuraMorphErr->_msg,
            "NeuraMorphTrainerCreateStatic failed");
        PBErrCatch(NeuraMorphErr);
    }
}

```

```

    }

    NeuraMorphTrainerFreeStatic(&trainer);
    NeuraMorphFree(&nm);
    GDataSetVecFloatFreeStatic(&dataset);

    printf("UnitTestNeuraMorphTrainerCreateFree OK\n");
}

void UnitTestNeuraMorphTrainerGetSet() {

    GDataSetVecFloat dataset =
        GDataSetVecFloatCreateStaticFromFile("./Datasets/iris.json");
    NeuraMorph* nm =
        NeuraMorphCreate(
            GDSGetNbInputs(&dataset),
            GDSGetNbOutputs(&dataset));
    NeuraMorphTrainer trainer =
        NeuraMorphTrainerCreateStatic(
            nm,
            &dataset);
    if (NMTrainerGetDepth(&trainer) != 2) {

        NeuraMorphErr->_type = PBErrTypeUnitTestFailed;
        sprintf(
            NeuraMorphErr->_msg,
            "NeuraMorphTrainerGetDepth failed");
        PBErrCatch(NeuraMorphErr);
    }

    if (NMTrainerGetOrder(&trainer) != 1) {

        NeuraMorphErr->_type = PBErrTypeUnitTestFailed;
        sprintf(
            NeuraMorphErr->_msg,
            "NeuraMorphTrainerGetOrder failed");
        PBErrCatch(NeuraMorphErr);
    }

    if (NMTrainerStreamInfo(&trainer) != NULL) {

        NeuraMorphErr->_type = PBErrTypeUnitTestFailed;
        sprintf(
            NeuraMorphErr->_msg,
            "NeuraMorphTrainerStreamInfo failed");
        PBErrCatch(NeuraMorphErr);
    }

    if (NMTrainerGetNbMaxUnitDepth(&trainer) != 2) {

        NeuraMorphErr->_type = PBErrTypeUnitTestFailed;
        sprintf(
            NeuraMorphErr->_msg,
            "NeuraMorphTrainerGetNbMaxUnitDepth failed");
        PBErrCatch(NeuraMorphErr);
    }
}

```

```

if (NMTrainerGetMaxLvlDiv(&trainer) != 2) {

    NeuroMorphErr->_type = PBErrTypeUnitTestFailed;
    sprintf(
        NeuroMorphErr->_msg,
        "NeuraMorphTrainerGetMaxLvlDiv failed");
    PBErrCatch(NeuroMorphErr);

}

if (NMTrainerGetNbMaxInputsUnit(&trainer) != GDSGetNbOutputs(&dataset)) {

    NeuroMorphErr->_type = PBErrTypeUnitTestFailed;
    sprintf(
        NeuroMorphErr->_msg,
        "NeuraMorphTrainerGetNbMaxInputsUnit failed");
    PBErrCatch(NeuroMorphErr);

}

if (NMTrainerGetICatTraining(&trainer) != 0) {

    NeuroMorphErr->_type = PBErrTypeUnitTestFailed;
    sprintf(
        NeuroMorphErr->_msg,
        "NeuraMorphTrainerGetICatTraining failed");
    PBErrCatch(NeuroMorphErr);

}

if (NMTrainerGetICatEval(&trainer) != 1) {

    NeuroMorphErr->_type = PBErrTypeUnitTestFailed;
    sprintf(
        NeuroMorphErr->_msg,
        "NeuraMorphTrainerGetICatEval failed");
    PBErrCatch(NeuroMorphErr);

}

bool isSame =
    ISEQUALF(
        NMTrainerGetWeakThreshold(&trainer),
        0.9);
if (isSame != true) {

    NeuroMorphErr->_type = PBErrTypeUnitTestFailed;
    sprintf(
        NeuroMorphErr->_msg,
        "NeuraMorphTrainerGetWeakThreshold failed");
    PBErrCatch(NeuroMorphErr);

}

NMTrainerSetDepth(
    &trainer,
    3);
if (NMTrainerGetDepth(&trainer) != 3) {

    NeuroMorphErr->_type = PBErrTypeUnitTestFailed;
    sprintf(

```

```

        NeuraMorphErr->_msg,
        "NeuraMorphTrainerSetDepth failed");
    PBErrCatch(NeuraMorphErr);
}

trainer.nbCorrect = 1;
if (NMTrainerGetNbCorrect(&trainer) != 1) {

    NeuraMorphErr->_type = PBErrTypeUnitTestFailed;
    sprintf(
        NeuraMorphErr->_msg,
        "NeuraMorphTrainerGetNbCorrect failed");
    PBErrCatch(NeuraMorphErr);
}

NMTrainerSetStreamInfo(
    &trainer,
    stdout);
if (NMTrainerStreamInfo(&trainer) != stdout) {

    NeuraMorphErr->_type = PBErrTypeUnitTestFailed;
    sprintf(
        NeuraMorphErr->_msg,
        "NeuraMorphTrainerSetStreamInfo failed");
    PBErrCatch(NeuraMorphErr);
}

NMTrainerSetNbMaxUnitDepth(
    &trainer,
    3);
if (NMTrainerGetNbMaxUnitDepth(&trainer) != 3) {

    NeuraMorphErr->_type = PBErrTypeUnitTestFailed;
    sprintf(
        NeuraMorphErr->_msg,
        "NeuraMorphTrainerSetNbMaxUnitDepth failed");
    PBErrCatch(NeuraMorphErr);
}

NMTrainerSetOrder(
    &trainer,
    3);
if (NMTrainerGetOrder(&trainer) != 3) {

    NeuraMorphErr->_type = PBErrTypeUnitTestFailed;
    sprintf(
        NeuraMorphErr->_msg,
        "NeuraMorphTrainerSetOrder failed");
    PBErrCatch(NeuraMorphErr);
}

NMTrainerSetNbMaxInputsUnit(
    &trainer,
    GDSGetNbOutputs(&dataset) + 1);
if (NMTrainerGetNbMaxInputsUnit(&trainer) != GDSGetNbOutputs(&dataset) + 1) {

    NeuraMorphErr->_type = PBErrTypeUnitTestFailed;

```



```

    sprintf(
        NeuraMorphErr->_msg,
        "NeuraMorphTrainerSetNbMaxInputsUnit failed");
    PBErrCatch(NeuraMorphErr);
}

NMTrainerSetICatTraining(
    &trainer,
    3);
if (NMTrainerGetICatTraining(&trainer) != 3) {

    NeuraMorphErr->_type = PBErrTypeUnitTestFailed;
    sprintf(
        NeuraMorphErr->_msg,
        "NeuraMorphTrainerSetICatTraining failed");
    PBErrCatch(NeuraMorphErr);
}

NMTrainerSetICatEval(
    &trainer,
    4);
if (NMTrainerGetICatEval(&trainer) != 4) {

    NeuraMorphErr->_type = PBErrTypeUnitTestFailed;
    sprintf(
        NeuraMorphErr->_msg,
        "NeuraMorphTrainerSetICatEval failed");
    PBErrCatch(NeuraMorphErr);
}

NMTrainerSetMaxLvlDiv(
    &trainer,
    3);
if (NMTrainerGetMaxLvlDiv(&trainer) != 3) {

    NeuraMorphErr->_type = PBErrTypeUnitTestFailed;
    sprintf(
        NeuraMorphErr->_msg,
        "NeuraMorphTrainerSetMaxLvlDiv failed");
    PBErrCatch(NeuraMorphErr);
}

NMTrainerSetWeakThreshold(
    &trainer,
    0.5);
isSame =
    ISEQUALF(
        NMTrainerGetWeakThreshold(&trainer),
        0.5);
if (isSame != true) {

    NeuraMorphErr->_type = PBErrTypeUnitTestFailed;
    sprintf(
        NeuraMorphErr->_msg,
        "NeuraMorphTrainerSetWeakThreshold failed");
    PBErrCatch(NeuraMorphErr);
}

```

```

NeuraMorphTrainerFreeStatic(&trainer);
NeuraMorphFree(&nm);
GDataSetVecFloatFreeStatic(&dataset);

printf("UnitTestNeuraMorphTrainerGetSet OK\n");
}

void UnitTestNeuraMorphTrainerRun() {

    srand(2);
    GDataSetVecFloat dataset =
        GDataSetVecFloatCreateStaticFromFile("./Datasets/iris.json");
    GDSShuffle(&dataset);
    VecShort2D split = VecShortCreateStatic2D();
    VecSet(
        &split,
        0,
        130);
    VecSet(
        &split,
        1,
        20);
    GDSSplit(
        &dataset,
        (VecShort*)&split);
    NeuraMorph* nm =
        NeuraMorphCreate(
            GDSGetNbInputs(&dataset),
            GDSGetNbOutputs(&dataset));
    NMSetFlagOneHot(
        nm,
        true);
    NeuraMorphTrainer trainer =
        NeuraMorphTrainerCreateStatic(
            nm,
            &dataset);

    NMTrainerSetWeakThreshold(
        &trainer,
        0.99);
    NMTrainerSetDepth(
        &trainer,
        3);
    NMTrainerSetMaxLvlDiv(
        &trainer,
        1);
    NMTrainerSetNbMaxInputsUnit(
        &trainer,
        GDSGetNbInputs(&dataset));
    NMTrainerSetOrder(
        &trainer,
        1);
    NMTrainerRun(&trainer);
    NMTrainerSetStreamInfo(
        &trainer,
        stdout);
    NMTrainerEval(&trainer);
    printf("Bias (min/avg/max): ");
    VecPrint(
        NMTrainerResEval(&trainer),

```

```

        stdout);
float percCorrect =
    (float)NMTrainerGetNbCorrect(&trainer) /
    (float)VecGet(
        &split,
        1);
printf(
    " %f\n",
    percCorrect);
NMTrainerSetICatEval(
    &trainer,
    0);
NMTrainerSetStreamInfo(
    &trainer,
    NULL);
NMTrainerEval(&trainer);
printf("Bias training (min/avg/max): ");
VecPrint(
    NMTrainerResEval(&trainer),
    stdout);
percCorrect =
    (float)NMTrainerGetNbCorrect(&trainer) /
    (float)VecGet(
        &split,
        0);
printf(
    " %f\n",
    percCorrect);

NeuraMorphTrainerFreeStatic(&trainer);
NeuraMorphFree(&nm);
GDataSetVecFloatFreeStatic(&dataset);

printf("UnitTestNeuraMorphTrainerRun OK\n");
}

void UnitTestNeuraMorphTrainer() {

    UnitTestNeuraMorphTrainerCreateFree();
    UnitTestNeuraMorphTrainerGetSet();
    UnitTestNeuraMorphTrainerRun();
    printf("UnitTestNeuraMorphTrainer OK\n");
}

void UnitTestAll() {

    UnitTestNeuraMorphUnit();
    UnitTestNeuraMorph();
    UnitTestNeuraMorphTrainer();
    printf("UnitTestAll OK\n");
}

int main() {

    UnitTestAll();

    // Return success code
    return 0;
}

```

}

6 Unit tests output

```
UnitTestNeuraMorphUnitCreateFree OK
<0,0,0> -> <0,0> (0.500000)
UnitTestNeuraMorphUnitGetSetPrint OK
UnitTestNeuraMorphUnitEvaluate OK
UnitTestNeuraMorphUnit OK
UnitTestNeuraMorphCreateFree OK
UnitTestNeuraMorphGetSet OK
UnitTestNeuraMorphAddRemoveUnit OK
UnitTestNeuraMorphBurryUnitsEvaluate OK
UnitTestNeuraMorph OK
UnitTestNeuraMorphTrainerCreateFree OK
UnitTestNeuraMorphTrainerGetSet OK
Depth 1/3...
Nb available inputs: 4
Train units with 0001 input(s)
Train units with 0002 input(s)
Train units with 0003 input(s)
Train units with 0004 input(s)
Burry 1 out of 15 unit(s)
<0,1,2,3> -> <0,1,2> (-3.347140)
Depth 2/3...
Nb available inputs: 7
Train units with 0001 input(s)
Train units with 0002 input(s)
Train units with 0003 input(s)
Train units with 0004 input(s)
Burry 1 out of 78 unit(s)
<2,3,5,6> -> <3,4,5> (-2.053272)
Depth 3/3...
Nb available inputs: 10
Train units with 0001 input(s)
Train units with 0002 input(s)
Train units with 0003 input(s)
Train units with 0004 input(s)
Add the last unit
<4,6,8,9> -> <6,7,8> (-1.552779)
00 <4.900,2.500,4.500,1.700> -> <-1.000,-1.000,1.000> : <-1.000,-1.000,1.000> 0.000000
01 <5.100,3.800,1.600,0.200> -> <1.000,-1.000,-1.000> : <1.000,-1.000,-1.000> 0.000000
02 <5.400,3.000,4.500,1.500> -> <-1.000,1.000,-1.000> : <-1.000,1.000,-1.000> 0.000000
03 <4.900,3.100,1.500,0.200> -> <1.000,-1.000,-1.000> : <1.000,-1.000,-1.000> 0.000000
04 <7.000,3.200,4.700,1.400> -> <-1.000,1.000,-1.000> : <-1.000,1.000,-1.000> 0.000000
05 <5.000,2.300,3.300,1.000> -> <-1.000,1.000,-1.000> : <-1.000,1.000,-1.000> 0.000000
06 <6.400,2.900,4.300,1.300> -> <-1.000,1.000,-1.000> : <-1.000,1.000,-1.000> 0.000000
07 <7.700,3.800,6.700,2.200> -> <-1.000,-1.000,1.000> : <-1.000,-1.000,1.000> 0.000000
08 <6.000,2.700,5.100,1.600> -> <-1.000,1.000,-1.000> : <-1.000,-1.000,1.000> 2.828427
09 <7.100,3.000,5.900,2.100> -> <-1.000,-1.000,1.000> : <-1.000,-1.000,1.000> 0.000000
10 <6.400,2.800,5.600,2.100> -> <-1.000,-1.000,1.000> : <-1.000,-1.000,1.000> 0.000000
11 <5.800,4.000,1.200,0.200> -> <1.000,-1.000,-1.000> : <1.000,-1.000,-1.000> 0.000000
12 <5.800,2.700,5.100,1.900> -> <-1.000,-1.000,1.000> : <-1.000,-1.000,1.000> 0.000000
13 <5.300,3.700,1.500,0.200> -> <1.000,-1.000,-1.000> : <1.000,-1.000,-1.000> 0.000000
14 <5.600,2.500,3.900,1.100> -> <-1.000,1.000,-1.000> : <-1.000,1.000,-1.000> 0.000000
15 <6.300,2.500,5.000,1.900> -> <-1.000,-1.000,1.000> : <-1.000,-1.000,1.000> 0.000000
16 <5.100,3.500,1.400,0.300> -> <1.000,-1.000,-1.000> : <1.000,-1.000,-1.000> 0.000000
17 <4.800,3.000,1.400,0.300> -> <1.000,-1.000,-1.000> : <1.000,-1.000,-1.000> 0.000000
18 <5.400,3.700,1.500,0.200> -> <1.000,-1.000,-1.000> : <1.000,-1.000,-1.000> 0.000000
```

```
19 <6.300,2.700,4.900,1.800> -> <-1.000,-1.000,1.000> : <-1.000,-1.000,1.000> 0.000000  
Bias (min/avg/max): <0.000,0.141,2.828>  
UnitTestNeuraMorphTrainerRun OK  
UnitTestNeuraMorphTrainer OK  
UnitTestAll OK
```