

PBImgAnalysis

P. Baillehache

March 2, 2019

Contents

1	Interface	2
2	Code	9
2.1	pbimganalysis.c	9
3	Makefile	29
4	Unit tests	30
5	Unit tests output	34
5.1	K-Means clustering on RGBA space	37

Introduction

PBImgAnalysis is a C library providing structures and functions to perform various data analysis on images.

It implements the following algorithms:

- K-means clustering on the RGBA space of pixels in a user defined radius
- Intersection over Union (aka Jaccard index)

It uses the `PBErr`, `PBDataAnalysis`, `GenBrush` libraries.

1 Interface

```
// ===== PBIMGANALYSIS.H =====

#ifndef PBIMGANALYSIS_H
#define PBIMGANALYSIS_H

// ===== Include =====

#include <stdlib.h>
#include <stdio.h>
#include <stdbool.h>
#include <execinfo.h>
#include <errno.h>
#include <string.h>
#include "pberr.h"
#include "pbdataanalysis.h"
#include "genbrush.h"
#include "genalg.h"
#include "neuranet.h"
#include "gdataset.h"

// ----- ImgKMeansClusters -----

// ===== Define =====

// ===== Data structure =====

typedef struct ImgKMeansClusters {
    // Image on which the clustering is applied
    // Uses the GBSurfaceFinalPixels
    const GenBrush* _img;
    // Clusters result of the search
    KMeansClusters _kmeansClusters;
    // Size of the considered cell in the image around a given position
    // is equal to (_size * 2 + 1)
    int _size;
} ImgKMeansClusters;

// ===== Functions declaration =====

// Create a new ImgKMeansClusters for the image 'img' and with seed 'seed'
// and type 'type' and a cell size equal to 2*'size'+1
ImgKMeansClusters ImgKMeansClustersCreateStatic(
    const GenBrush* const img, const KMeansClustersSeed seed,
    const int size);

// Free the memory used by a ImgKMeansClusters
void ImgKMeansClustersFreeStatic(ImgKMeansClusters* const that);

// Get the GenBrush of the ImgKMeansClusters 'that'
#if BUILDMODE != 0
inline
#endif
const GenBrush* IKMCImg(const ImgKMeansClusters* const that);

// Set the GenBrush of the ImgKMeansClusters 'that' to 'img'
#if BUILDMODE != 0
inline
#endif
void IKMCSetImg(ImgKMeansClusters* const that, const GenBrush* const img);
```

```

// Set the size of the cells of the ImgKMeansClusters 'that' to
// 2*'size'+1
#if BUILDMODE != 0
inline
#endif
void IKMCSetSizeCell(ImgKMeansClusters* const that, const int size);

// Get the number of cluster of the ImgKMeansClusters 'that'
#if BUILDMODE != 0
inline
#endif
int IKMCGetK(const ImgKMeansClusters* const that);

// Get the size of the cells of the ImgKMeansClusters 'that'
#if BUILDMODE != 0
inline
#endif
int IKMCGetSizeCell(const ImgKMeansClusters* const that);

// Get the KMeansClusters of the ImgKMeansClusters 'that'
#if BUILDMODE != 0
inline
#endif
const KMeansClusters* IKMCKMeansClusters(
    const ImgKMeansClusters* const that);

// Search for the 'K' clusters in the image of the
// ImgKMeansClusters 'that'
void IKMCSearch(ImgKMeansClusters* const that, const int K);

// Print the ImgKMeansClusters 'that' on the stream 'stream'
void IKMCPrintln(const ImgKMeansClusters* const that,
    FILE* const stream);

// Get the index of the cluster at position 'pos' for the
// ImgKMeansClusters 'that'
int IKMCGetId(const ImgKMeansClusters* const that,
    const VecShort2D* const pos);

// Get the GBPixel equivalent to the cluster at position 'pos'
// for the ImgKMeansClusters 'that'
GBPixel IKMCGetPixel(const ImgKMeansClusters* const that,
    const VecShort2D* const pos);

// Convert the image of the ImageKMeansClusters 'that' to its clustered
// version
// IKMCSearch must have been called previously
void IKMCCluster(const ImgKMeansClusters* const that);

// Load the IKMC 'that' from the stream 'stream'
// There is no associated GenBrush object saved
// Return true upon success else false
bool IKMCLoad(ImgKMeansClusters* that, FILE* const stream);

// Save the IKMC 'that' to the stream 'stream'
// If 'compact' equals true it saves in compact form, else it saves in
// readable form
// There is no associated GenBrush object saved
// Return true upon success else false
bool IKMCSave(const ImgKMeansClusters* const that,
    FILE* const stream, const bool compact);

```

```

// Function which return the JSON encoding of 'that'
JSONNode* IKMCEncodeAsJSON(const ImgKMeansClusters* const that);

// Function which decode from JSON encoding 'json' to 'that'
bool IKMCDecodeAsJSON(ImgKMeansClusters* that,
    const JSONNode* const json);

// ===== Polymorphism =====

// ----- General functions -----

// Return the Jaccard index (aka intersection over union) of the
// image 'that' and 'tho' for pixels of color 'rgba'
// 'that' and 'tho' must have same dimensions
float IntersectionOverUnion(const GenBrush* const that,
    const GenBrush* const tho, const GBPixel* const rgba);

// ----- ImgSegmentor -----

// ===== Define =====

// ===== Data structure =====

typedef struct ImgSegmentor {
    // Set of criterion
    GSet _criteria;
    // Number of segmentation class
    int _nbClass;
    // Flag to apply or not the binarization on result of prediction
    // false by default
    bool _flagBinaryResult;
    // Threshold value for the binarization of result of prediction
    // If the result of prediction is above the threshold then
    // the result is considered equal to 1.0 else it is considered equal
    // to -1.0
    // 0.5 by default
    float _thresholdBinaryResult;
    // Nb of epoch for training, 1 by default
    unsigned int _nbEpoch;
    // Size pool for training
    // By default GENALG_NBENTITIES
    int _sizePool;
    // Nb elite for training
    // By default GENALG_NBELITES
    int _nbElite;
    // Threshold to stop the training once
    float _targetBestValue;
} ImgSegmentor;

typedef struct ImgSegmentorPerf {
    // Accuracy
    float _accuracy;
} ImgSegmentorPerf;

typedef struct ImgSegmentorTrainParam {
    // Nb of epochs
    int _nbEpoch;
} ImgSegmentorParam;

typedef enum ISCType {
    ISCType_RGB

```

```

} ISCType;

typedef struct ImgSegmentorCriterion {
    // Type of criteriion
    ISCType _type;
    // Nb of class
    int _nbClass;
} ImgSegmentorCriterion;

typedef struct ImgSegmentorCriterionRGB {
    // ImgSegmentorCriterion
    ImgSegmentorCriterion _criterion;
    // NeuraNet model
    NeuraNet* _nn;
} ImgSegmentorCriterionRGB;

// ===== Functions declaration =====

// Create a new static ImgSegmentor with 'nbClass' output
ImgSegmentor ImgSegmentorCreateStatic(int nbClass);

// Free the memory used by the static ImgSegmentor 'that'
void ImgSegmentorFreeStatic(ImgSegmentor* that);

// Return the nb of criterion of the ImgSegmentor 'that'
#if BUILDMODE != 0
inline
#endif
long ISGetNbCriterion(const ImgSegmentor* const that);

// Add a new ImageSegmentorCriterionRGB to the ImgSegmentor 'that'
#if BUILDMODE != 0
inline
#endif
void ISAddCriterionRGB(ImgSegmentor* const that);

// Return the nb of classes of the ImgSegmentor 'that'
#if BUILDMODE != 0
inline
#endif
int ISGetNbClass(const ImgSegmentor* const that);

// Return the flag controlling the binarization of the result of
// prediction of the ImgSegmentor 'that'
#if BUILDMODE != 0
inline
#endif
bool ISGetFlagBinaryResult(const ImgSegmentor* const that);

// Return the threshold controlling the binarization of the result of
// prediction of the ImgSegmentor 'that'
#if BUILDMODE != 0
inline
#endif
float ISGetThresholdBinaryResult(const ImgSegmentor* const that);

// Return the threshold controlling the stop of the training
#if BUILDMODE != 0
inline
#endif
float ISGetTargetBestValue(const ImgSegmentor* const that);

```

```

// Set the threshold controlling the stop of the training to 'val'
// Clip the value to [0.0, 1.0]
#if BUILDMODE != 0
inline
#endif
void ISSetTargetBestValue(ImgSegmentor* const that, const float val);

// Set the flag controlling the binarization of the result of
// prediction of the ImgSegmentor 'that' to 'flag'
#if BUILDMODE != 0
inline
#endif
void ISSetFlagBinaryResult(ImgSegmentor* const that,
    const bool flag);

// Return the number of epoch for training the ImgSegmentor 'that'
#if BUILDMODE != 0
inline
#endif
unsigned int ISGetNbEpoch(const ImgSegmentor* const that);

// Set the number of epoch for training the ImgSegmentor 'that' to 'nb'
#if BUILDMODE != 0
inline
#endif
void ISSetNbEpoch(ImgSegmentor* const that, unsigned int nb);

// Return the size of the pool for training the ImgSegmentor 'that'
#if BUILDMODE != 0
inline
#endif
int ISGetSizePool(const ImgSegmentor* const that);

// Set the size of the pool for training the ImgSegmentor 'that' to 'nb'
#if BUILDMODE != 0
inline
#endif
void ISSetSizePool(ImgSegmentor* const that, int nb);

// Return the nb of elites for training the ImgSegmentor 'that'
#if BUILDMODE != 0
inline
#endif
int ISGetNbElite(const ImgSegmentor* const that);

// Set the nb of elites for training the ImgSegmentor 'that' to 'nb'
#if BUILDMODE != 0
inline
#endif
void ISSetNbElite(ImgSegmentor* const that, int nb);

// Set the threshold controlling the binarization of the result of
// prediction of the ImgSegmentor 'that' to 'threshold'
#if BUILDMODE != 0
inline
#endif
void ISSetThresholdBinaryResult(ImgSegmentor* const that,
    const float threshold);

// Make a prediction on the GenBrush 'img' with the ImgSegmentor 'that'
// Return an array of pointer to GenBrush, one per output class, in
// greyscale, where the color of each pixel indicates the detection of

```

```

// the corresponding class at the given pixel, white equals no
// detection, black equals detection, 50% grey equals "don't know"
GenBrush** ISPredict(const ImgSegmentor* const that,
    const GenBrush* const img);

// Return the nb of criterion of the ImgSegmentor 'that'
#if BUILDMODE != 0
inline
#endif
const GSet* ISCriteria(const ImgSegmentor* const that);

// Train the ImageSegmentor 'that' on the data set 'dataSet' using
// the data of the first category in 'dataSet'
// srandom must have been called before calling ISTrain
void ISTrain(ImgSegmentor* const that,
    const GDataSetGenBrushPair* const dataset);

// Create a new static ImgSegmentorCriterion with 'nbClass' output
// and the type of criterion 'type'
ImgSegmentorCriterion ImgSegmentorCriterionCreateStatic(int nbClass,
    ISCType type);

// Free the memory used by the static ImgSegmentorCriterion 'that'
void ImgSegmentorCriterionFreeStatic(ImgSegmentorCriterion* that);

// Make the prediction on the 'input' values by calling the appropriate
// function according to the type of criterion
// 'input' 's format is width*height*3, values in [0.0, 1.0]
// Return values are width*height*nbClass, values in [-1.0, 1.0]
VecFloat* ISCPredict(const ImgSegmentorCriterion* const that,
    const VecFloat* input, const VecShort2D* const dim);

// Return the nb of class of the ImgSegmentorCriterion 'that'
#if BUILDMODE != 0
inline
#endif
int _ISCGetNbClass(const ImgSegmentorCriterion* const that);

// Return the number of int parameters for the criterion 'that'
long _ISCGetNbParamInt(const ImgSegmentorCriterion* const that);

// Return the number of float parameters for the criterion 'that'
long _ISCGetNbParamFloat(const ImgSegmentorCriterion* const that);

// Set the bounds of int parameters for training of the criterion 'that'
void _ISCSetBoundsAdnInt(const ImgSegmentorCriterion* const that,
    GenAlg* const ga, const long shift);

// Set the bounds of float parameters for training of the criterion 'that'
void _ISCSetBoundsAdnFloat(const ImgSegmentorCriterion* const that,
    GenAlg* const ga, const long shift);

// Set the values of int parameters for training of the criterion 'that'
void _ISCSetAdnInt(const ImgSegmentorCriterion* const that,
    const GenAlgAdn* const adn, const long shift);

// Set the values of float parameters for training of the criterion 'that'
void _ISCSetAdnFloat(const ImgSegmentorCriterion* const that,
    const GenAlgAdn* const adn, const long shift);

// Create a new ImgSegmentorCriterionRGB with 'nbClass' output
ImgSegmentorCriterionRGB* ImgSegmentorCriterionRGBCreate(int nbClass);

```

```

// Free the memory used by the ImgSegmentorCriterionRGB 'that'
void ImgSegmentorCriterionRGBFree(ImgSegmentorCriterionRGB* that);

// Make the prediction on the 'input' values with the
// ImgSegmentorCriterionRGB that
// 'input' 's format is width*height*3, values in [0.0, 1.0]
// Return values are width*height*nbClass, values in [-1.0, 1.0]
VecFloat* ISCRGBPredict(const ImgSegmentorCriterionRGB* const that,
    const VecFloat* input, const VecShort2D* const dim);

// Return the number of int parameters for the criterion 'that'
long ISCRGBGetNbParamInt(const ImgSegmentorCriterionRGB* const that);

// Return the number of float parameters for the criterion 'that'
long ISCRGBGetNbParamFloat(const ImgSegmentorCriterionRGB* const that);

// Set the bounds of int parameters for training of the criterion 'that'
void ISCRGBSetBoundsAdnInt(const ImgSegmentorCriterionRGB* const that,
    GenAlg* const ga, const long shift);

// Set the bounds of float parameters for training of the criterion 'that'
void ISCRGBSetBoundsAdnFloat(const ImgSegmentorCriterionRGB* const that,
    GenAlg* const ga, const long shift);

// Set the values of int parameters for training of the criterion 'that'
void ISCRGBSetAdnInt(const ImgSegmentorCriterionRGB* const that,
    const GenAlgAdn* const adn, const long shift);

// Set the values of float parameters for training of the criterion 'that'
void ISCRGBSetAdnFloat(const ImgSegmentorCriterionRGB* const that,
    const GenAlgAdn* const adn, const long shift);

// Return the NeuraNet of the ImgSegmentorCriterionRGB 'that'
#if BUILDMODE != 0
inline
#endif
const NeuraNet* ISCRGBNeuraNet(
    const ImgSegmentorCriterionRGB* const that);

// ===== Polymorphism =====

#define ISCGetNbClass(That) _Generic(That, \
    ImgSegmentorCriterion*: _ISCGetNbClass, \
    const ImgSegmentorCriterion*: _ISCGetNbClass, \
    ImgSegmentorCriterionRGB*: _ISCGetNbClass, \
    const ImgSegmentorCriterionRGB*: _ISCGetNbClass, \
    default: PBErrInvalidPolymorphism) ((const ImgSegmentorCriterion*)That)

#define ISCGetNbParamInt(That) _Generic(That, \
    ImgSegmentorCriterion*: _ISCGetNbParamInt, \
    const ImgSegmentorCriterion*: _ISCGetNbParamInt, \
    ImgSegmentorCriterionRGB*: ISCRGBGetNbParamInt, \
    const ImgSegmentorCriterionRGB*: ISCRGBGetNbParamInt, \
    default: PBErrInvalidPolymorphism) ((const ImgSegmentorCriterion*)That)

#define ISCGetNbParamFloat(That) _Generic(That, \
    ImgSegmentorCriterion*: _ISCGetNbParamFloat, \
    const ImgSegmentorCriterion*: _ISCGetNbParamFloat, \
    ImgSegmentorCriterionRGB*: ISCRGBGetNbParamFloat, \
    const ImgSegmentorCriterionRGB*: ISCRGBGetNbParamFloat, \
    default: PBErrInvalidPolymorphism) ((const ImgSegmentorCriterion*)That)

```



```

#define ISCSetBoundsAdnInt(That, GenAlg, Shift) _Generic(That, \
    ImgSegmentorCriterion*: _ISCSetBoundsAdnInt, \
    const ImgSegmentorCriterion*: _ISCSetBoundsAdnInt, \
    ImgSegmentorCriterionRGB*: ISCRGBSetBoundsAdnInt, \
    const ImgSegmentorCriterionRGB*: ISCRGBSetBoundsAdnInt, \
    default: PBErrInvalidPolymorphism) ( \
    (const ImgSegmentorCriterion*)That, GenAlg, Shift)

#define ISCSetBoundsAdnFloat(That, GenAlg, Shift) _Generic(That, \
    ImgSegmentorCriterion*: _ISCSetBoundsAdnFloat, \
    const ImgSegmentorCriterion*: _ISCSetBoundsAdnFloat, \
    ImgSegmentorCriterionRGB*: ISCRGBSetBoundsAdnFloat, \
    const ImgSegmentorCriterionRGB*: ISCRGBSetBoundsAdnFloat, \
    default: PBErrInvalidPolymorphism) ( \
    (const ImgSegmentorCriterion*)That, GenAlg, Shift)

#define ISCSetAdnInt(That, Adn, Shift) _Generic(That, \
    ImgSegmentorCriterion*: _ISCSetAdnInt, \
    const ImgSegmentorCriterion*: _ISCSetAdnInt, \
    ImgSegmentorCriterionRGB*: ISCRGBSetAdnInt, \
    const ImgSegmentorCriterionRGB*: ISCRGBSetAdnInt, \
    default: PBErrInvalidPolymorphism) ( \
    (const ImgSegmentorCriterion*)That, Adn, Shift)

#define ISCSetAdnFloat(That, Adn, Shift) _Generic(That, \
    ImgSegmentorCriterion*: _ISCSetAdnFloat, \
    const ImgSegmentorCriterion*: _ISCSetAdnFloat, \
    ImgSegmentorCriterionRGB*: ISCRGBSetAdnFloat, \
    const ImgSegmentorCriterionRGB*: ISCRGBSetAdnFloat, \
    default: PBErrInvalidPolymorphism) ( \
    (const ImgSegmentorCriterion*)That, Adn, Shift)

// ===== Inliner =====

#if BUILDMODE != 0
#include "pbimganalysis-inline.c"
#endif

#endif

```

2 Code

2.1 pbimganalysis.c

```

// ===== PBIMGANALYSIS.C =====

// ===== Include =====

#include "pbimganalysis.h"
#if BUILDMODE == 0
#include "pbimganalysis-inline.c"
#endif

// ----- ImgKMeansClusters -----

// ===== Define =====

```

```

// ===== Functions declaration =====

// Get the input values for the pixel at position 'pos' according to
// the cell size of the ImgKMeansClusters 'that'
// The return is a VecFloat made of the sizeCell^2 pixels' value
// around pos ordered by ((r*256+g)*256+b)*256+a)
VecFloat* IKMCGetInputOverCell(const ImgKMeansClusters* const that,
    const VecShort2D* const pos);

// ===== Functions implementation =====

// Create a new ImgKMeansClusters for the image 'img' and with seed 'seed'
// and type 'type' and a cell size equal to 2*'size'+1
ImgKMeansClusters ImgKMeansClustersCreateStatic(
    const GenBrush* const img, const KMeansClustersSeed seed,
    const int size) {
    #if BUILDMODE == 0
        if (img == NULL) {
            PImgAnalysisErr->_type = PErrTypeNullPointer;
            sprintf(PImgAnalysisErr->_msg, "'img' is null");
            PErrCatch(PImgAnalysisErr);
        }
        if (size < 0) {
            PImgAnalysisErr->_type = PErrTypeInvalidArg;
            sprintf(PImgAnalysisErr->_msg, "'size' is invalid (%d>=0)", size);
            PErrCatch(PImgAnalysisErr);
        }
    #endif
    // Declare the new ImgKMeansClusters
    ImgKMeansClusters that;
    // Set properties
    that._img = img;
    that._kmeansClusters = KMeansClustersCreateStatic(seed);
    that._size = size;
    // Return the new ImgKMeansClusters
    return that;
}

// Free the memory used by a ImgKMeansClusters
void ImgKMeansClustersFreeStatic(ImgKMeansClusters* const that) {
    #if BUILDMODE == 0
        if (that == NULL) {
            PImgAnalysisErr->_type = PErrTypeNullPointer;
            sprintf(PImgAnalysisErr->_msg, "'that' is null");
            PErrCatch(PImgAnalysisErr);
        }
    #endif
    // Reset the GenBrush associated to the IKMC
    that->_img = NULL;
    // Free the memory used by the KMeansClusters
    KMeansClustersFreeStatic((KMeansClusters*)IKMCKMeansClusters(that));
}

// Search for the 'K' clusters in the image of the
// ImgKMeansClusters 'that'
void IKMCSearch(ImgKMeansClusters* const that, const int K) {
    #if BUILDMODE == 0
        if (that == NULL) {
            PImgAnalysisErr->_type = PErrTypeNullPointer;
            sprintf(PImgAnalysisErr->_msg, "'that' is null");
            PErrCatch(PImgAnalysisErr);
        }
    #endif
}

```

```

if (K < 1) {
    PBIImgAnalysisErr->_type = PBErrTypeInvalidArg;
    sprintf(PBIImgAnalysisErr->_msg, "'K' is invalid (%d>0)", K);
    PBErrCatch(PBIImgAnalysisErr);
}
#endif
// Create a set to memorize the input over cells
GSetVecFloat inputOverCells = GSetVecFloatCreateStatic();
// Get the dimension of the image
VecShort2D dim = GBGetDim(IKMCImg(that));
// Loop on pixels
VecShort2D pos = VecShortCreateStatic2D();
do {
    // Get the KMeansClusters input over the cell
    VecFloat* inputOverCell = IKMCGetInputOverCell(that, &pos);
    // Add it to the inputs for the search
    GSetAppend(&inputOverCells, inputOverCell);
} while (VecStep(&pos, &dim));
// Search the clusters
KMeansClustersSearch((KMeansClusters*)IKMCKMeansClusters(that),
    &inputOverCells, K);
// Free the memory used by the input
while (GSetNbElem(&inputOverCells) > 0) {
    VecFloat* v = GSetPop(&inputOverCells);
    VecFree(&v);
}
}

// Print the ImgKMeansClusters 'that' on the stream 'stream'
void IKMCPrintln(const ImgKMeansClusters* const that,
    FILE* const stream) {
    #if BUILDMODE == 0
        if (that == NULL) {
            PBIImgAnalysisErr->_type = PBErrTypeNullPointer;
            sprintf(PBIImgAnalysisErr->_msg, "'that' is null");
            PBErrCatch(PBIImgAnalysisErr);
        }
        if (stream == NULL) {
            PBIImgAnalysisErr->_type = PBErrTypeNullPointer;
            sprintf(PBIImgAnalysisErr->_msg, "'stream' is null");
            PBErrCatch(PBIImgAnalysisErr);
        }
    #endif
    // Print the KMeansClusters of 'that'
    KMeansClustersPrintln(IKMCKMeansClusters(that), stream);
}

// Get the index of the cluster at position 'pos' for the
// ImgKMeansClusters 'that'
int IKMCGetId(const ImgKMeansClusters* const that,
    const VecShort2D* const pos) {
    #if BUILDMODE == 0
        if (that == NULL) {
            PBIImgAnalysisErr->_type = PBErrTypeNullPointer;
            sprintf(PBIImgAnalysisErr->_msg, "'that' is null");
            PBErrCatch(PBIImgAnalysisErr);
        }
        if (pos == NULL) {
            PBIImgAnalysisErr->_type = PBErrTypeNullPointer;
            sprintf(PBIImgAnalysisErr->_msg, "'pos' is null");
            PBErrCatch(PBIImgAnalysisErr);
        }
    #endif
}

```

```

#endif
    // Get the KMeansClusters input over the cell
    VecFloat* inputOverCell = IKMCGetInputOverCell(that, pos);
    // Get the index of the cluster for this pixel
    int id = KMeansClustersGetId(IKMCKMeansClusters(that), inputOverCell);
    // Free memory
    VecFree(&inputOverCell);
    // Return the id
    return id;
}

// Get the GBPixel equivalent to the cluster at position 'pos'
// for the ImgKMeansClusters 'that'
// This is the average pixel over the pixel in the cell of the cluster
GBPixel IKMCGetPixel(const ImgKMeansClusters* const that,
    const VecShort2D* const pos) {
    #if BUILDMODE == 0
        if (that == NULL) {
            PBImpAnalysisErr->_type = PBErrTypeNullPointer;
            sprintf(PBImpAnalysisErr->_msg, "'that' is null");
            PBErrCatch(PBImpAnalysisErr);
        }
        if (pos == NULL) {
            PBImpAnalysisErr->_type = PBErrTypeNullPointer;
            sprintf(PBImpAnalysisErr->_msg, "'pos' is null");
            PBErrCatch(PBImpAnalysisErr);
        }
    #endif
    // Declare the result pixel
    GBPixel pix;
    // Get the id of the cluster for the input pixel
    int id = IKMCGetId(that, pos);
    // Get the 'id'-th cluster's center
    const VecFloat* center =
        KMeansClustersCenter(IKMCKMeansClusters(that), id);
    // Declare a variable to calculate the average pixel
    VecFloat* avgPix = VecFloatCreate(4);
    // Calculate the average pixel
    for (int i = 0; i < VecGetDim(center); i += 4) {
        for (int j = 4; j--;) {
            VecSet(avgPix, j, VecGet(avgPix, j) + VecGet(center, i + j));
        }
    }
    VecScale(avgPix, 1.0 / round((float)VecGetDim(center) / 4.0));
    // Update the returned pixel values and ensure the converted value
    // from float to char is valid
    for (int i = 4; i--;) {
        float v = VecGet(avgPix, i);
        if (v < 0.0)
            v = 0.0;
        else if (v > 255.0)
            v = 255.0;
        pix._rgba[i] = (unsigned char)v;
    }
    // Free memory
    VecFree(&avgPix);
    // Return the result pixel
    return pix;
}

// Convert the image of the ImageKMeansClusters 'that' to its clustered
// version

```

```

// IKMCSearch must have been called previously
void IKMCCluster(const ImgKMeansClusters* const that) {
#if BUILDMODE == 0
    if (that == NULL) {
        PBIImgAnalysisErr->_type = PBErrTypeNullPointer;
        sprintf(PBIImgAnalysisErr->_msg, "'that' is null");
        PBErrCatch(PBIImgAnalysisErr);
    }
#endif
    // Get the dimension of the image
    VecShort2D dim = GBGetDim(IKMCImg(that));
    // Loop on pixels
    VecShort2D pos = VecShortCreateStatic2D();
    do {
        // Get the clustered pixel for this pixel
        GBPixel clustered = IKMCGetPixel(that, &pos);
        // Replace the original pixel
        GBSetFinalPixel((GenBrush*)IKMCImg(that), &pos, &clustered);
    } while (VecStep(&pos, &dim));
}

// Get the input values for the pixel at position 'pos' according to
// the cell size of the ImgKMeansClusters 'that'
// The return is a VecFloat made of the sizeCell^2 pixels' value
// around pos ordered by ((r*256+g)*256+b)*256+a
VecFloat* IKMCGetInputOverCell(const ImgKMeansClusters* const that,
    const VecShort2D* const pos) {
#if BUILDMODE == 0
    if (that == NULL) {
        PBIImgAnalysisErr->_type = PBErrTypeNullPointer;
        sprintf(PBIImgAnalysisErr->_msg, "'that' is null");
        PBErrCatch(PBIImgAnalysisErr);
    }
    if (pos == NULL) {
        PBIImgAnalysisErr->_type = PBErrTypeNullPointer;
        sprintf(PBIImgAnalysisErr->_msg, "'pos' is null");
        PBErrCatch(PBIImgAnalysisErr);
    }
#endif
    // Create two vectors to loop on the cell
    VecShort2D from = VecShortCreateStatic2D();
    VecSet(&from, 0, -that->_size);
    VecSet(&from, 1, -that->_size);
    VecShort2D to = VecShortCreateStatic2D();
    VecSet(&to, 0, that->_size + 1);
    VecSet(&to, 1, that->_size + 1);
    // Get the pixel at the center of the cell, will be used as default
    // if the cell goes over the border of the image
    const GBPixel* defaultPixel = GBFinalPixel(IKMCImg(that), pos);
    // Declare a set to memorize the pixels in the cell
    GSet pixels = GSetCreateStatic();
    // Loop over the pixels of the cell
    VecShort2D posCell = from;
    VecShort2D posImg = VecShortCreateStatic2D();
    do {
        // If the position in the cell is inside the radius of the cell
        VecFloat2D posCellFloat = VecShortToFloat2D(&posCell);
        if ((int)round(VecNorm(&posCellFloat)) <= that->_size) {
            // Get the position in the image
            posImg = VecGetOp(pos, 1, &posCell, 1);
            // Get the pixel at this position
            const GBPixel* pix = GBFinalPixelSafe(IKMCImg(that), &posImg);

```

```

        if (pix == NULL)
            pix = defaultPixel;
        // Get the value to sort this pixel
        float valPix = 0.0;
        for (int iRgba = 4; iRgba--;)
            valPix += 256.0 * valPix + (float)(pix->rgba[iRgba]);
        // Add the pixel to the set of pixels in the cell
        GSetAddSort(&pixels, pix, valPix);
    }
} while (VecShiftStep(&posCell, &from, &to));
// Declare the result vector
VecFloat* res = VecFloatCreate(GSetNbElem(&pixels) * 4);
// Loop over the sorted pixels of the cell
int iPix = 0;
while (GSetNbElem(&pixels)) {
    const GPixel* pix = GSetDrop(&pixels);
    // Set the result value
    for (int i = 0; i < 4; ++i)
        VecSet(res, iPix * 4 + i, (float)(pix->rgba[i]));
    ++iPix;
}
// Return the result
return res;
}

// Load the IKMC 'that' from the stream 'stream'
// There is no associated GenBrush object saved
// Return true upon success else false
bool IKMCLoad(ImgKMeansClusters* that, FILE* const stream) {
#ifdef BUILDMODE == 0
    if (that == NULL) {
        PBImpAnalysisErr->_type = PBErrTypeNullPointer;
        sprintf(PBImpAnalysisErr->_msg, "'that' is null");
        PBErrCatch(PBImpAnalysisErr);
    }
    if (stream == NULL) {
        PBImpAnalysisErr->_type = PBErrTypeNullPointer;
        sprintf(PBImpAnalysisErr->_msg, "'stream' is null");
        PBErrCatch(PBImpAnalysisErr);
    }
}
#endif
// Declare a json to load the encoded data
JSONNode* json = JSONCreate();
// Load the whole encoded data
if (!JSONLoad(json, stream)) {
    return false;
}
// Decode the data from the JSON
if (!IKMCDecodeAsJSON(that, json)) {
    return false;
}
// Free the memory used by the JSON
JSONFree(&json);
// Return success code
return true;
}

// Save the IKMC 'that' to the stream 'stream'
// If 'compact' equals true it saves in compact form, else it saves in
// readable form
// There is no associated GenBrush object saved
// Return true upon success else false

```

```

bool IKMCSave(const ImgKMeansClusters* const that,
FILE* const stream, const bool compact) {
#if BUILDMODE == 0
    if (that == NULL) {
        PImgAnalysisErr->_type = PErrTypeNullPointer;
        sprintf(PImgAnalysisErr->_msg, "'that' is null");
        PErrCatch(PImgAnalysisErr);
    }
    if (stream == NULL) {
        PImgAnalysisErr->_type = PErrTypeNullPointer;
        sprintf(PImgAnalysisErr->_msg, "'stream' is null");
        PErrCatch(PImgAnalysisErr);
    }
#endif
    // Get the JSON encoding
    JSONNode* json = IKMCEncodeAsJSON(that);
    // Save the JSON
    if (!JSONSave(json, stream, compact)) {
        return false;
    }
    // Free memory
    JSONFree(&json);
    // Return success code
    return true;
}

// Function which return the JSON encoding of 'that'
JSONNode* IKMCEncodeAsJSON(const ImgKMeansClusters* const that) {
#if BUILDMODE == 0
    if (that == NULL) {
        PImgAnalysisErr->_type = PErrTypeNullPointer;
        sprintf(PImgAnalysisErr->_msg, "'that' is null");
        PErrCatch(PImgAnalysisErr);
    }
#endif
    // Create the JSON structure
    JSONNode* json = JSONCreate();
    // Declare a buffer to convert value into string
    char val[100];
    // Encode the size
    sprintf(val, "%d", that->_size);
    JSONAddProp(json, "_size", val);
    // Encode the KMeansClusters
    JSONAddProp(json, "_clusters",
        KMeansClustersEncodeAsJSON(IKMCKMeansClusters(that)));
    // Return the created JSON
    return json;
}

// Function which decode from JSON encoding 'json' to 'that'
bool IKMCDecodeAsJSON(ImgKMeansClusters* that,
const JSONNode* const json) {
#if BUILDMODE == 0
    if (that == NULL) {
        PImgAnalysisErr->_type = PErrTypeNullPointer;
        sprintf(PImgAnalysisErr->_msg, "'that' is null");
        PErrCatch(PImgAnalysisErr);
    }
    if (json == NULL) {
        PImgAnalysisErr->_type = PErrTypeNullPointer;
        sprintf(PImgAnalysisErr->_msg, "'json' is null");
        PErrCatch(PImgAnalysisErr);
    }
#endif
}

```

```

    }
#endif
    // Free the memory eventually used by the IKMC
    ImgKMeansClustersFreeStatic(that);
    // Get the size from the JSON
    JSONNode* prop = JSONProperty(json, "_size");
    if (prop == NULL) {
        return false;
    }
    that->_size = atoi(JSONLabel(JSONValue(prop, 0)));
    if (that->_size < 0) {
        return false;
    }
    // Decode the KMeansClusters
    prop = JSONProperty(json, "_clusters");
    if (!KMeansClustersDecodeAsJSON(
        (KMeansClusters*)IKMCKMeansClusters(that), prop)) {
        return false;
    }
    // Return the success code
    return true;
}

// ----- ImgSegmentor -----

// ===== Functions implementation =====

// Create a new static ImgSegmentor with 'nbClass' output
ImgSegmentor ImgSegmentorCreateStatic(int nbClass) {
#if BUILDMODE == 0
    if (nbClass <= 0) {
        PBImpAnalysisErr->_type = PBErrTypeInvalidArg;
        sprintf(PBImpAnalysisErr->_msg, "'nbClass' is invalid (%d>0)",
            nbClass);
        PBErrCatch(PBImpAnalysisErr);
    }
#endif
    // Declare the new ImgSegmentor
    ImgSegmentor that;
    // Init properties
    that._nbClass = nbClass;
    that._criteria = GSetCreateStatic();
    that._flagBinaryResult = false;
    that._thresholdBinaryResult = 0.5;
    that._nbEpoch = 1;
    that._sizePool = GENALG_NBENTITIES;
    that._nbElite = GENALG_NBELITES;
    that._targetBestValue = 0.9999;
    // Return the new ImgSegmentor
    return that;
}

// Free the memory used by the static ImgSegmentor 'that'
void ImgSegmentorFreeStatic(ImgSegmentor* that) {
    if (that == NULL)
        return;
    while (ISGetNbCriterion(that) > 0) {
        ImgSegmentorCriterion* criterion = GSetPop(&(that->_criteria));
        switch (criterion->_type) {
            case ISCType_RGB:
                ImgSegmentorCriterionRGBFree(
                    (ImgSegmentorCriterionRGB*)&criterion);

```



```

        break;
    default:
        PBIImgAnalysisErr->_type = PBErrTypeNotYetImplemented;
        sprintf(PBIImgAnalysisErr->_msg,
            "Not yet implemented type of criterion");
        PBErrCatch(PBIImgAnalysisErr);
        break;
    }
}
}

// Make a prediction on the GenBrush 'img' with the ImgSegmentor 'that'
// Return an array of pointer to GenBrush, one per output class, in
// greyscale, where the color of each pixel indicates the detection of
// the corresponding class at the given pixel, white equals no
// detection, black equals detection, 50% grey equals "don't know"
GenBrush** ISPredict(const ImgSegmentor* const that,
    const GenBrush* const img) {
#ifdef BUILDMODE == 0
    if (that == NULL) {
        PBIImgAnalysisErr->_type = PBErrTypeNullPointer;
        sprintf(PBIImgAnalysisErr->_msg, "'that' is null");
        PBErrCatch(PBIImgAnalysisErr);
    }
    if (img == NULL) {
        PBIImgAnalysisErr->_type = PBErrTypeNullPointer;
        sprintf(PBIImgAnalysisErr->_msg, "'img' is null");
        PBErrCatch(PBIImgAnalysisErr);
    }
#endif
    // Get the dimension of the input image
    VecShort2D dim = GBGetDim(img);
    // Calculate the area of the image
    long area = VecGet(&dim, 0) * VecGet(&dim, 1);
    // Create a temporary vector to convert the image into the input
    // of a criterion
    VecFloat* input = VecFloatCreate(area * 3);
    // Declare a vector to loop on position in the image
    VecShort2D pos = VecShortCreateStatic2D();
    // Convert the image's pixels into the input VecFloat
    do {
        GBPixel pix = GBGetFinalPixel(img, &pos);
        long iPos = GBPosIndex(&pos, &dim);
        for (int iRGB = 3; iRGB--;)
            VecSet(input, iPos * 3 + iRGB, (float)(pix._rgba[iRGB]) / 255.0);
    } while (VecStep(&pos, &dim));
    // Create temporary vectors to memorize the prediction of each criterion
    VecFloat** pred = PBErrMalloc(PBIImgAnalysisErr,
        sizeof(VecFloat*) * ISGetNbCriterion(that));
    // Loop on criteria
    int iCrit = 0;
    GSetIterForward iter = GSetIterForwardCreateStatic(ISCriteria(that));
    do {
        ImgSegmentorCriterion* criterion = GSetIterGet(&iter);
        pred[iCrit] = ISCPredict(criterion, input, &dim);
        ++iCrit;
    } while (GSetIterStep(&iter));
    // Create temporary vectors to memorize the combined predictions
    VecFloat* combPred = VecFloatCreate(area * ISGetNbClass(that));
    VecFloat* finalPred = VecFloatCreate(area * ISGetNbClass(that));
    // Combine the predictions over criteria
    // The combination is the weighted average of prediction over criteria

```

```

// where the weight is the absolute value of the prediction
for (long i = area * (long)ISGetNbClass(that); i--;) {
    float sumWeight = 0.0;
    for (iCrit = ISGetNbCriterion(that); iCrit--;) {
        float v = VecGet(pred[iCrit], i);
        VecSetAdd(combPred, i, v * fabs(v));
        sumWeight += fabs(v);
    }
    if (sumWeight > PBMath_EPSILON)
        VecSet(combPred, i, VecGet(combPred, i) / sumWeight);
    else
        VecSet(combPred, i, 0.0);
}
// Combine the predictions over classes
// The combination is calculated as follow:
// finalPred(i) = (pred(i)*abs(combPred(i) - sum_{j!=i}
//   combPred(j)*abs(combPred(j)) / (sum_i abs(combPred(i))
VecSetNull(&pos);
do {
    for (long iClass = ISGetNbClass(that); iClass--;) {
        float sumWeight = 0.0;
        long iPos = GBPosIndex(&pos, &dim) * ISGetNbClass(that) + iClass;
        for (long jClass = ISGetNbClass(that); jClass--;) {
            long jPos = GBPosIndex(&pos, &dim) * ISGetNbClass(that) + jClass;
            float v = VecGet(combPred, jPos);
            if (iClass == jClass) {
                VecSetAdd(finalPred, iPos, v * fabs(v));
            } else {
                VecSetAdd(finalPred, iPos, -1.0 * v * fabs(v));
            }
            sumWeight += fabs(v);
        }
        if (sumWeight > PBMath_EPSILON)
            VecSet(finalPred, iPos, VecGet(finalPred, iPos) / sumWeight);
        else
            VecSet(finalPred, iPos, 0.0);
    }
} while(VecStep(&pos, &dim));
// Allocate memory for the results
GenBrush** res = PBErrMalloc(PBImgAnalysisErr,
    sizeof(GenBrush*) * ISGetNbClass(that));
// Declare a variable to convert the prediction into pixel
GBPixel pix = GBColorWhite;
// Loop on classes
for (int iClass = ISGetNbClass(that); iClass--;) {
    // Create the result GenBrush
    res[iClass] = GBCreateImage(&dim);
    // Loop on position in the image
    VecSetNull(&pos);
    do {
        // Get the prediction value for this class and this position
        // and convert it to rgb value
        long iPos = GBPosIndex(&pos, &dim);
        float p = VecGet(finalPred, iPos * ISGetNbClass(that) + iClass);
        if (ISGetFlagBinaryResult(that)) {
            if (p > ISGetThresholdBinaryResult(that))
                p = 1.0;
            else
                p = -1.0;
        }
        unsigned char pChar = 255 -
            (unsigned char)round(255.0 * (p * 0.5 + 0.5));
    } while(VecStep(&pos, &dim));
}

```

```

        // Convert the prediction to a pixel
        pix._rgba[GBPixelRed] = pix._rgba[GBPixelGreen] =
            pix._rgba[GBPixelBlue] = pChar;
        // Set the pixel in the result image
        GBSetFinalPixel(res[iClass], &pos, &pix);
    } while (VecStep(&pos, &dim));
}
// Free memory
for (int iCrit = ISGetNbCriterion(that); iCrit--;) {
    VecFree(pred + iCrit);
}
free(pred);
VecFree(&input);
VecFree(&finalPred);
// Return the result
return res;
}

// Train the ImageSegmentor 'that' on the data set 'dataSet' using
// the data of the first category in 'dataSet'
// srandom must have been called before calling ISTrain
void ISTrain(ImgSegmentor* const that,
             const GDataSetGenBrushPair* const dataset) {
#ifdef BUILDMODE == 0
    if (that == NULL) {
        PBIImgAnalysisErr->_type = PBErrTypeNullPointer;
        sprintf(PBIImgAnalysisErr->_msg, "'that' is null");
        PBErrCatch(PBIImgAnalysisErr);
    }
    if (dataset == NULL) {
        PBIImgAnalysisErr->_type = PBErrTypeNullPointer;
        sprintf(PBIImgAnalysisErr->_msg, "'dataset' is null");
        PBErrCatch(PBIImgAnalysisErr);
    }
    if (ISGetNbClass(that) > GDSGetNbMask(dataset)) {
        PBIImgAnalysisErr->_type = PBErrTypeInvalidData;
        sprintf(PBIImgAnalysisErr->_msg,
            "Not enough masks in the dataset (%d<=%d)",
            ISGetNbClass(that), GDSGetNbMask(dataset));
        PBErrCatch(PBIImgAnalysisErr);
    }
#endif
    // If there is no criterion, nothing to do
    if (ISGetNbCriterion(that) == 0)
        return;
    // Memorize the current flag for binarization of results
    bool curFlagBinary = ISGetFlagBinaryResult(that);
    // Turn on the binarization
    ISSetFlagBinaryResult(that, true);
    // Create two vectors to memorize the number of int and float
    // parameters for each criterion
    VecLong* nbParamInt = VecLongCreate(ISGetNbCriterion(that));
    VecLong* nbParamFloat = VecLongCreate(ISGetNbCriterion(that));
    // Declare two variables to memorize the total number of int and
    // float parameters
    long nbTotalParamInt = 0;
    long nbTotalParamFloat = 0;
    // Declare a variable to memorize the color of the mask
    const GBPixel rgbaMask = GBColorBlack;
    // Get the number of int and float parameters for each criterion
    int iCrit = 0;
    GSetIterForward iter = GSetIterForwardCreateStatic(ISCriteria(that));

```

```

do {
    ImgSegmentorCriterion* crit = GSetIterGet(&iter);
    long nb = ISCGetNbParamInt(crit);
    VecSet(nbParamInt, iCrit, nb);
    nbTotalParamInt += nb;
    nb = ISCGetNbParamFloat(crit);
    VecSet(nbParamFloat, iCrit, nb);
    nbTotalParamFloat += nb;
    ++iCrit;
} while (GSetIterStep(&iter));
// If there are parameters
if (nbTotalParamInt > 0 || nbTotalParamFloat > 0) {
    // Create the GenAlg to search parameters' value
    GenAlg* ga = GenAlgCreate(ISGetSizePool(that), ISGetNbElite(that),
        nbTotalParamFloat, nbTotalParamInt);
    // Loop on the criterion to initialise the parameters bound
    GSetIterReset(&iter);
    long shiftParamInt = 0;
    long shiftParamFloat = 0;
    do {
        ImgSegmentorCriterion* crit = GSetIterGet(&iter);
        ISCSetsAdnInt(crit, ga, shiftParamInt);
        shiftParamInt += ISCGetNbParamInt(crit);
        ISCSetsAdnFloat(crit, ga, shiftParamFloat);
        shiftParamFloat += ISCGetNbParamFloat(crit);
    } while (GSetIterStep(&iter));
    // Initialise the GenAlg
    GAINit(ga);
    // Declare a variable to memorize the current best value
    float bestValue = 0.0;
    // Loop over epochs
    do {
        // Loop over the GenAlg entities
        for (int iEnt = 0; iEnt < GAGetNbAdns(ga); ++iEnt) {
            // If this entity is a new one
            if (GAAdnIsNew(GAAdn(ga, iEnt))) {
                // Loop on the criterion to set the criteria parameters with
                // this entity's adn
                GSetIterReset(&iter);
                shiftParamInt = 0;
                shiftParamFloat = 0;
                do {
                    ImgSegmentorCriterion* crit = GSetIterGet(&iter);
                    ISCSetsAdnInt(crit, GAAdn(ga, iEnt), shiftParamInt);
                    shiftParamInt += ISCGetNbParamInt(crit);
                    ISCSetsAdnFloat(crit, GAAdn(ga, iEnt), shiftParamFloat);
                    shiftParamFloat += ISCGetNbParamFloat(crit);
                } while (GSetIterStep(&iter));
                // Evaluate the ImgSegmentor for this entity's adn on the
                // dataset
                float value = 0.0;
                const int iCatTraining = 0;
                // Reset the iterator of the GDataSet
                GDSReset(dataset, iCatTraining);
                // Loop on the samples
                long iSample = 0;
                do {
                    printf("Epoch %05ld/%05u ",
                        GAGetCurEpoch(ga) + 1, ISGetNbEpoch(that));
                    printf("Entity %03d/%03d ",
                        iEnt + 1, GAGetNbAdns(ga));
                    printf("Sample %05ld/%05ld ",

```

```

        iSample + 1, GDSGetSizeCat(dataset, iCatTraining));
    // Get the next sample
    GDSGenBrushPair* sample = GDSGetSample(dataset, iCatTraining);
    // Do the prediction on the sample
    GenBrush** pred = ISPredict(that, sample->_img);
    // Check the prediction against the masks
    float valMask = 0.0;
    for (int iMask = ISGetNbClass(that); iMask--;) {
        valMask += IntersectionOverUnion(
            sample->_mask[iMask], pred[iMask], &rgbaMask);
    }
    value += valMask / (float)GDSGetNbMask(dataset);
    // Free memory
    for (int iClass = ISGetNbClass(that); iClass--;)
        GFree(pred + iClass);
    free(pred);
    GDSGenBrushPairFree(&sample);
    if (iSample + 1 < GDSGetSizeCat(dataset, iCatTraining))
        printf("\n");
    fflush(stdout);
    ++iSample;
} while (GDSStepSample(dataset, iCatTraining));
// Get the average value over all samples
value /= (float)GDSGetSizeCat(dataset, iCatTraining);
// Update the adn value of this entity
GASetAdnValue(ga, GAAdn(ga, iEnt), value);
// If the value is the best value
if (value - bestValue > PBMath_EPSILON) {
    bestValue = value;
}
printf("BestValue %f/%f\n", bestValue,
    ISGetTargetBestValue(that));
}
}
// Step the GenAlg
GAStep(ga);
} while (GAGetCurEpoch(ga) < ISGetNbEpoch(that) &&
    bestValue < ISGetTargetBestValue(that));
// Loop on the criterion to set the criteria to the best one
GSetIterReset(&iter);
shiftParamInt = 0;
shiftParamFloat = 0;
do {
    ImgSegmentorCriterion* crit = GSetIterGet(&iter);
    ISCSetsAdnInt(crit, GABestAdn(ga), shiftParamInt);
    shiftParamInt += ISCSetsNbParamInt(crit);
    ISCSetsAdnFloat(crit, GABestAdn(ga), shiftParamFloat);
    shiftParamFloat += ISCSetsNbParamFloat(crit);
} while (GSetIterStep(&iter));
// Free memory
GenAlgFree(&ga);
}
// Free memory
VecFree(&nbParamInt);
VecFree(&nbParamFloat);
// Put back the flag for binarization in its original state
ISSetFlagBinaryResult(that, curFlagBinary);
}

// Create a new static ImgSegmentorCriterion with 'nbClass' output
// and the type of criteria 'type'
ImgSegmentorCriterion ImgSegmentorCriterionCreateStatic(int nbClass,

```

```

    ISCType type) {
#ifdef BUILDMODE == 0
    if (nbClass <= 0) {
        PBIImgAnalysisErr->_type = PBErrTypeInvalidArg;
        sprintf(PBIImgAnalysisErr->_msg, "'nbClass' is invalid (%d>0)",
            nbClass);
        PBErrCatch(PBIImgAnalysisErr);
    }
#endif
    // Declare the new ImgSegmentorCriterion
    ImgSegmentorCriterion that;
    // Set the properties
    that._nbClass = nbClass;
    that._type = type;
    // Return the new ImgSegmentorCriterion
    return that;
}

// Free the memory used by the static ImgSegmentorCriterion 'that'
void ImgSegmentorCriterionFreeStatic(ImgSegmentorCriterion* that) {
    if (that == NULL)
        return;
    // Nothing to do
}

// Make the prediction on the 'input' values by calling the appropriate
// function according to the type of criteria
// 'input' 's format is width*height*3, values in [0.0, 1.0]
// Return values are width*height*nbClass, values in [-1.0, 1.0]
VecFloat* ISCPredict(const ImgSegmentorCriterion* const that,
    const VecFloat* input, const VecShort2D* const dim) {
#ifdef BUILDMODE == 0
    if (that == NULL) {
        PBIImgAnalysisErr->_type = PBErrTypeNullPointer;
        sprintf(PBIImgAnalysisErr->_msg, "'that' is null");
        PBErrCatch(PBIImgAnalysisErr);
    }
    if (input == NULL) {
        PBIImgAnalysisErr->_type = PBErrTypeNullPointer;
        sprintf(PBIImgAnalysisErr->_msg, "'input' is null");
        PBErrCatch(PBIImgAnalysisErr);
    }
#endif
    // Declare a variable to memorize the result
    VecFloat* res = NULL;
    // Call the appropriate function based on the type
    switch(that->_type) {
        case ISCType_RGB:
            res = ISCRGBPredict((const ImgSegmentorCriterionRGB*)that,
                input, dim);
            break;
        default:
            break;
    }
    // Return the result
    return res;
}

// Return the number of int parameters for the criterion 'that'
long _ISCGetNbParamInt(const ImgSegmentorCriterion* const that) {
#ifdef BUILDMODE == 0
    if (that == NULL) {

```

```

    PBIImgAnalysisErr->_type = PBErrTypeNullPointer;
    sprintf(PBIImgAnalysisErr->_msg, "'that' is null");
    PBErrCatch(PBIImgAnalysisErr);
}
#endif
// Declare a variable to memorize the result
long res = 0;
// Call the appropriate function based on the type
switch(that->_type) {
    case ISCType_RGB:
        res = ISCRGBGetNbParamInt((const ImgSegmentorCriterionRGB*)that);
        break;
    default:
        break;
}
// Return the result
return res;
}

// Return the number of float parameters for the criterion 'that'
long _ISCGetNbParamFloat(const ImgSegmentorCriterion* const that) {
    #if BUILDMODE == 0
        if (that == NULL) {
            PBIImgAnalysisErr->_type = PBErrTypeNullPointer;
            sprintf(PBIImgAnalysisErr->_msg, "'that' is null");
            PBErrCatch(PBIImgAnalysisErr);
        }
    #endif
    // Declare a variable to memorize the result
    long res = 0;
    // Call the appropriate function based on the type
    switch(that->_type) {
        case ISCType_RGB:
            res = ISCRGBGetNbParamFloat((const ImgSegmentorCriterionRGB*)that);
            break;
        default:
            break;
    }
    // Return the result
    return res;
}

// Create a new ImgSegmentorCriterionRGB with 'nbClass' output
ImgSegmentorCriterionRGB* ImgSegmentorCriterionRGBCreate(int nbClass) {
    #if BUILDMODE == 0
        if (nbClass <= 0) {
            PBIImgAnalysisErr->_type = PBErrTypeInvalidArg;
            sprintf(PBIImgAnalysisErr->_msg, "'nbClass' is invalid (%d>0)",
                nbClass);
            PBErrCatch(PBIImgAnalysisErr);
        }
    #endif
    // Allocate memory for the new ImgSegmentorCriterionRGB
    ImgSegmentorCriterionRGB* that = PBErrMalloc(PBIImgAnalysisErr,
        sizeof(ImgSegmentorCriterionRGB));
    // Create the parent ImgSegmentorCriterion
    that->_criterion = ImgSegmentorCriterionCreateStatic(nbClass,
        ISCType_RGB);
    // Create the NeuraNet
    const int nbInput = 3;
    const int nbHidden = fsquare(nbInput) * nbClass;
    VecLong* hidden = VecLongCreate(1);

```

```

    VecSet(hidden, 0, nbHidden);
    that->_nn = NeuraNetCreateFullyConnected(nbInput, nbClass, hidden);
    VecFree(&hidden);
    // Return the new ImgSegmentorCriterionRGB
    return that;
}

// Free the memory used by the ImgSegmentorCriterionRGB 'that'
void ImgSegmentorCriterionRGBFree(ImgSegmentorCriterionRGB** that) {
    if (that == NULL || *that == NULL)
        return;
    // Free memory
    ImgSegmentorCriterionFreeStatic((ImgSegmentorCriterion*)(*that));
    NeuraNetFree(&((*that)->_nn));
    free(*that);
}

// Make the prediction on the 'input' values with the
// ImgSegmentorCriterionRGB that
// 'input' 's format is width*height*3, values in [0.0, 1.0]
// Return values are width*height*nbClass, values in [-1.0, 1.0]
VecFloat* ISCRGBPredict(const ImgSegmentorCriterionRGB* const that,
    const VecFloat* input, const VecShort2D* const dim) {
#ifdef BUILDMODE == 0
    if (that == NULL) {
        PBImpAnalysisErr->_type = PBErrTypeNullPointer;
        sprintf(PBImpAnalysisErr->_msg, "'that' is null");
        PBErrCatch(PBImpAnalysisErr);
    }
    if (input == NULL) {
        PBImpAnalysisErr->_type = PBErrTypeNullPointer;
        sprintf(PBImpAnalysisErr->_msg, "'input' is null");
        PBErrCatch(PBImpAnalysisErr);
    }
    if ((VecGetDim(input) % 3) != 0) {
        PBImpAnalysisErr->_type = PBErrTypeInvalidArg;
        sprintf(PBImpAnalysisErr->_msg,
            "'input' 's dim is not multiple of 3 (%ld)", VecGetDim(input));
        PBErrCatch(PBImpAnalysisErr);
    }
#endif
    // Calculate the area of the input image
    long area = VecGet(dim, 0) * VecGet(dim, 1);
    // Allocate memory for the result
    VecFloat* res = VecFloatCreate(area * (long)ISCGetNbClass(that));
    // Declare variables to memorize the input/output of the NeuraNet
    VecFloat3D in = VecFloatCreateStatic3D();
    VecFloat* out = VecFloatCreate(ISCGetNbClass(that));
    // Apply the NeuraNet on inputs
    for (long iInput = area; iInput--;) {
        for (long i = 3; i--;)
            VecSet(&in, i, VecGet(input, iInput * 3L + i));
        NNEval(that->_nn, (VecFloat*)&in, out);
        for (long i = ISCGetNbClass(that); i--;)
            VecSet(res, iInput * (long)ISCGetNbClass(that) + i,
                VecGet(out, i));
    }
    // Free memory
    VecFree(&out);
    // Return the result
    return res;
}

```



```

// Return the number of int parameters for the criterion 'that'
long ISCRGBGetNbParamInt(const ImgSegmentorCriterionRGB* const that) {
#ifdef BUILDMODE == 0
    if (that == NULL) {
        PBIImgAnalysisErr->_type = PBErrTypeNullPointer;
        sprintf(PBIImgAnalysisErr->_msg, "'that' is null");
        PBErrCatch(PBIImgAnalysisErr);
    }
#endif
    (void)that;
    return 0;
}

// Return the number of float parameters for the criterion 'that'
long ISCRGBGetNbParamFloat(const ImgSegmentorCriterionRGB* const that) {
#ifdef BUILDMODE == 0
    if (that == NULL) {
        PBIImgAnalysisErr->_type = PBErrTypeNullPointer;
        sprintf(PBIImgAnalysisErr->_msg, "'that' is null");
        PBErrCatch(PBIImgAnalysisErr);
    }
#endif
    return NNGetGAAdnFloatLength(that->_nn);
}

// Set the bounds of int parameters for training of the criterion 'that'
void _ISCSetsBoundsAdnInt(const ImgSegmentorCriterion* const that,
    GenAlg* const ga, const long shift) {
#ifdef BUILDMODE == 0
    if (that == NULL) {
        PBIImgAnalysisErr->_type = PBErrTypeNullPointer;
        sprintf(PBIImgAnalysisErr->_msg, "'that' is null");
        PBErrCatch(PBIImgAnalysisErr);
    }
    if (ga == NULL) {
        PBIImgAnalysisErr->_type = PBErrTypeNullPointer;
        sprintf(PBIImgAnalysisErr->_msg, "'ga' is null");
        PBErrCatch(PBIImgAnalysisErr);
    }
#endif
    // Call the appropriate function based on the type
    switch(that->_type) {
        case ISCType_RGB:
            ISCRGBSetBoundsAdnInt((const ImgSegmentorCriterionRGB*)that,
                ga, shift);
            break;
        default:
            break;
    }
}

// Set the bounds of float parameters for training of the criterion
// 'that'
void _ISCSetsBoundsAdnFloat(const ImgSegmentorCriterion* const that,
    GenAlg* const ga, const long shift) {
#ifdef BUILDMODE == 0
    if (that == NULL) {
        PBIImgAnalysisErr->_type = PBErrTypeNullPointer;
        sprintf(PBIImgAnalysisErr->_msg, "'that' is null");
        PBErrCatch(PBIImgAnalysisErr);
    }
}

```

```

    if (ga == NULL) {
        PBIImgAnalysisErr->_type = PBErrTypeNullPointer;
        sprintf(PBIImgAnalysisErr->_msg, "'ga' is null");
        PBErrCatch(PBIImgAnalysisErr);
    }
#endif
    // Call the appropriate function based on the type
    switch(that->_type) {
        case ISCRType_RGB:
            ISCRGBSetBoundsAdnFloat((const ImgSegmentorCriterionRGB*)that,
                ga, shift);
            break;
        default:
            break;
    }
}

// Set the bounds of int parameters for training of the criterion 'that'
void ISCRGBSetBoundsAdnInt(const ImgSegmentorCriterionRGB* const that,
    GenAlg* const ga, const long shift) {
    #if BUILDMODE == 0
        if (that == NULL) {
            PBIImgAnalysisErr->_type = PBErrTypeNullPointer;
            sprintf(PBIImgAnalysisErr->_msg, "'that' is null");
            PBErrCatch(PBIImgAnalysisErr);
        }
        if (ga == NULL) {
            PBIImgAnalysisErr->_type = PBErrTypeNullPointer;
            sprintf(PBIImgAnalysisErr->_msg, "'ga' is null");
            PBErrCatch(PBIImgAnalysisErr);
        }
    #endif
    // Nothing to do
    (void)that; (void)ga; (void)shift;
}

// Set the bounds of float parameters for training of the criterion
// 'that'
void ISCRGBSetBoundsAdnFloat(const ImgSegmentorCriterionRGB* const that,
    GenAlg* const ga, const long shift) {
    #if BUILDMODE == 0
        if (that == NULL) {
            PBIImgAnalysisErr->_type = PBErrTypeNullPointer;
            sprintf(PBIImgAnalysisErr->_msg, "'that' is null");
            PBErrCatch(PBIImgAnalysisErr);
        }
        if (ga == NULL) {
            PBIImgAnalysisErr->_type = PBErrTypeNullPointer;
            sprintf(PBIImgAnalysisErr->_msg, "'ga' is null");
            PBErrCatch(PBIImgAnalysisErr);
        }
    #endif
    VecFloat2D bounds = VecFloatCreateStatic2D();
    VecSet(&bounds, 0, -1.0);
    VecSet(&bounds, 1, 1.0);
    for (long iParam = ISCRGBGetNbParamFloat(that); iParam--;) {
        GASetBoundsAdnFloat(ga, iParam + shift, &bounds);
    }
}

// Set the values of int parameters for training of the criterion 'that'
void _ISCSetAdnInt(const ImgSegmentorCriterion* const that,

```

```

    const GenAlgAdn* const adn, const long shift) {
#ifdef BUILDMODE == 0
    if (that == NULL) {
        PBIImgAnalysisErr->_type = PBErrTypeNullPointer;
        sprintf(PBIImgAnalysisErr->_msg, "'that' is null");
        PBErrCatch(PBIImgAnalysisErr);
    }
    if (adn == NULL) {
        PBIImgAnalysisErr->_type = PBErrTypeNullPointer;
        sprintf(PBIImgAnalysisErr->_msg, "'ga' is null");
        PBErrCatch(PBIImgAnalysisErr);
    }
#endif
    // Call the appropriate function based on the type
    switch(that->_type) {
        case ISCType_RGB:
            ISCRGBSetAdnInt((const ImgSegmentorCriterionRGB*)that,
                adn, shift);
            break;
        default:
            break;
    }
}

// Set the values of float parameters for training of the criterion
// 'that'
void _ISCSetAdnFloat(const ImgSegmentorCriterion* const that,
    const GenAlgAdn* const adn, const long shift) {
#ifdef BUILDMODE == 0
    if (that == NULL) {
        PBIImgAnalysisErr->_type = PBErrTypeNullPointer;
        sprintf(PBIImgAnalysisErr->_msg, "'that' is null");
        PBErrCatch(PBIImgAnalysisErr);
    }
    if (adn == NULL) {
        PBIImgAnalysisErr->_type = PBErrTypeNullPointer;
        sprintf(PBIImgAnalysisErr->_msg, "'ga' is null");
        PBErrCatch(PBIImgAnalysisErr);
    }
#endif
    // Call the appropriate function based on the type
    switch(that->_type) {
        case ISCType_RGB:
            ISCRGBSetAdnFloat((const ImgSegmentorCriterionRGB*)that,
                adn, shift);
            break;
        default:
            break;
    }
}

// Set the values of int parameters for training of the criterion 'that'
void ISCRGBSetAdnInt(const ImgSegmentorCriterionRGB* const that,
    const GenAlgAdn* const adn, const long shift) {
#ifdef BUILDMODE == 0
    if (that == NULL) {
        PBIImgAnalysisErr->_type = PBErrTypeNullPointer;
        sprintf(PBIImgAnalysisErr->_msg, "'that' is null");
        PBErrCatch(PBIImgAnalysisErr);
    }
    if (adn == NULL) {
        PBIImgAnalysisErr->_type = PBErrTypeNullPointer;
    }
#endif
}

```

```

        sprintf(PBImgAnalysisErr->_msg, "'ga' is null");
        PBErCatch(PBImgAnalysisErr);
    }
#endif
    // Nothing to do
    (void)that; (void)adn; (void)shift;
}

// Set the values of float parameters for training of the criterion
// 'that'
void ISCRGBSetAdnFloat(const ImgSegmentorCriterionRGB* const that,
    const GenAlgAdn* const adn, const long shift) {
    #if BUILDMODE == 0
        if (that == NULL) {
            PBImgAnalysisErr->_type = PBErrTypeNullPointer;
            sprintf(PBImgAnalysisErr->_msg, "'that' is null");
            PBErCatch(PBImgAnalysisErr);
        }
        if (adn == NULL) {
            PBImgAnalysisErr->_type = PBErrTypeNullPointer;
            sprintf(PBImgAnalysisErr->_msg, "'ga' is null");
            PBErCatch(PBImgAnalysisErr);
        }
    #endif
    const VecFloat* adnF = GAAdnAdnF(adn);
    VecFloat* bases = VecFloatCreate(ISCRGBGetNbParamFloat(that));
    for (int i = ISCRGBGetNbParamFloat(that); i--;)
        VecSet(bases, i, VecGet(adnF, shift + i));
    NNSetBases((NeuraNet*)ISCRGBNeuraNet(that), bases);
    VecFree(&bases);
}

// ----- General functions -----

// ===== Functions implementation =====

// Return the Jaccard index (aka intersection over union) of the
// image 'that' and 'tho' for pixels of color 'rgba'
// 'that' and 'tho' must have same dimensions
float IntersectionOverUnion(const GenBrush* const that,
    const GenBrush* const tho, const GBPixel* const rgba) {
    #if BUILDMODE == 0
        if (that == NULL) {
            PBImgAnalysisErr->_type = PBErrTypeNullPointer;
            sprintf(PBImgAnalysisErr->_msg, "'that' is null");
            PBErCatch(PBImgAnalysisErr);
        }
        if (tho == NULL) {
            PBImgAnalysisErr->_type = PBErrTypeNullPointer;
            sprintf(PBImgAnalysisErr->_msg, "'tho' is null");
            PBErCatch(PBImgAnalysisErr);
        }
        if (rgba == NULL) {
            PBImgAnalysisErr->_type = PBErrTypeNullPointer;
            sprintf(PBImgAnalysisErr->_msg, "'rgba' is null");
            PBErCatch(PBImgAnalysisErr);
        }
        if (!VecIsEqual(GBDim(that), GBDim(tho))) {
            PBImgAnalysisErr->_type = PBErrTypeInvalidArg;
            sprintf(PBImgAnalysisErr->_msg,
                "'that' and 'tho' have different dimensions");
            PBErCatch(PBImgAnalysisErr);
        }
    #endif
}

```

```

    }
#endif
    // Declare two variables to count the number of pixels in
    // intersection and union
    long nbUnion = 0;
    long nbInter = 0;
    // Declare a variable to loop through pixels
    VecShort2D pos = VecShortCreateStatic2D();
    // Loop through pixels
    do {
        // If the pixel is in the intersection
        if (GBPixelIsSame(GBFinalPixel(that, &pos), rgba) &&
            GBPixelIsSame(GBFinalPixel(tho, &pos), rgba)) {
            // Increment the number of pixels in intersection
            ++nbInter;
        }
        // If the pixel is in the union
        if (GBPixelIsSame(GBFinalPixel(that, &pos), rgba) ||
            GBPixelIsSame(GBFinalPixel(tho, &pos), rgba)) {
            // Increment the number of pixels in union
            ++nbUnion;
        }
    } while (VecStep(&pos, GBDim(that)));
    // Calcaulte the intersection over union
    float iou = (float)nbInter / (float)nbUnion;
    // Return the result
    return iou;
}

```

3 Makefile

```

# Build mode
# 0: development (max safety, no optimisation)
# 1: release (min safety, optimisation)
# 2: fast and furious (no safety, optimisation)
BUILD_MODE?=1

all: pbmake_wget main

# Automatic installation of the repository PBMake in the parent folder
pbmake_wget:
if [ ! -d ../PBMake ]; then wget https://github.com/BayashiPascal/PBMake/archive/master.zip; unzip master.zip; rm -f

# Makefile definitions
MAKEFILE_INC=../PBMake/Makefile.inc
include $(MAKEFILE_INC)

# Rules to make the executable
repo=pbimganalysis
${$(repo)_EXENAME}: \
${$(repo)_EXENAME}.o \
${$(repo)_EXE_DEP} \
${$(repo)_DEP}
$(COMPILER) 'echo "${$(repo)_EXE_DEP} ${$(repo)_EXENAME}.o" | tr ' ' '\n' | sort -u' $(LINK_ARG) ${$(repo)_LINK_ARG}

${$(repo)_EXENAME}.o: \
${$(repo)_DIR}/${$(repo)_EXENAME}.c \
${$(repo)_INC_H_EXE} \

```

```

$$($(repo)_EXE_DEP)
$(COMPILER) $(BUILD_ARG) $$($(repo)_BUILD_ARG) 'echo "$$(repo)_INC_DIR" | tr ' ' '\n' | sort -u' -c $$($(repo)_DIR)/

```

4 Unit tests

```

#include <stdlib.h>
#include <stdio.h>
#include <time.h>
#include <string.h>
#include <math.h>
#include "pbimganalysis.h"

void UnitTestImgKMeansClusters() {
    srandom(1);
    for (int size = 0; size < 6; ++size) {
        for (int K = 2; K <= 6; ++K) {
            char* fileName = "./ImgKMeansClustersTest/imgkmeanscluster.tga";
            GenBrush* img = GBCreateFromFile(fileName);
            ImgKMeansClusters clusters = ImgKMeansClustersCreateStatic(
                img, KMeansClustersSeed_Forgy, size);
            IKMCSearch(&clusters, K);

            FILE* fd = fopen("./imgkmeanscluster.txt", "w");
            if (!IKMCSave(&clusters, fd, false)) {
                PBIImgAnalysisErr->_type = PBErrTypeUnitTestFailed;
                sprintf(PBIImgAnalysisErr->_msg, "IKMCSave NOK");
                PBErrCatch(PBIImgAnalysisErr);
            }
            fclose(fd);
            fd = fopen("./imgkmeanscluster.txt", "r");
            if (!IKMCLoad(&clusters, fd)) {
                PBIImgAnalysisErr->_type = PBErrTypeUnitTestFailed;
                sprintf(PBIImgAnalysisErr->_msg, "IKMCLoad NOK");
                PBErrCatch(PBIImgAnalysisErr);
            }
            IKMCSetImg(&clusters, img);
            fclose(fd);

            printf("%s size K=%d cell=%d:\n",
                fileName, K, IKMCGetSizeCell(&clusters));
            IKMCPrintln(&clusters, stdout);
            IKMCCLuster(&clusters);
            char fileNameOut[50] = {'\0'};
            sprintf(fileNameOut,
                "./ImgKMeansClustersTest/imgkmeanscluster%02d-%02d.tga", K, size);
            GBSetFileName(img, fileNameOut);
            GBRender(img);
            GBFree(&img);
            ImgKMeansClustersFreeStatic(&clusters);
        }
    }
    printf("UnitTestImgKMeansClusters OK\n");
}

void UnitTestIntersectionOverUnion() {
    char* fileNameA = "./iou1.tga";
    GenBrush* imgA = GBCreateFromFile(fileNameA);
    char* fileNameB = "./iou2.tga";

```

```

    GenBrush* imgB = GBCreateFromFile(fileNameB);
    GBPixel rgba = GBColorBlack;
    float iou = IntersectionOverUnion(imgA, imgB, &rgba);
    if (!ISEQUALF(iou, 6.0 / 10.0)) {
        PBIImgAnalysisErr->_type = PBErrTypeUnitTestFailed;
        sprintf(PBIImgAnalysisErr->_msg, "IntersectionOverUnion failed");
        PBErrCatch(PBIImgAnalysisErr);
    }
    GBFree(&imgA);
    GBFree(&imgB);
    printf("UnitTestIntersectionOverUnion OK\n");
}

void UnitTestImgSegmentorRGB() {
    int nbClass = 2;
    ImgSegmentorCriterionRGB* criterion =
        ImgSegmentorCriterionRGBCreate(nbClass);
    if (ISCGetNbClass(criterion) != nbClass) {
        PBIImgAnalysisErr->_type = PBErrTypeUnitTestFailed;
        sprintf(PBIImgAnalysisErr->_msg,
            "ImgSegmentorCriterionRGBCreate failed");
        PBErrCatch(PBIImgAnalysisErr);
    }
    int imgArea = 4;
    VecFloat* input = VecFloatCreate(imgArea * 3);
    VecShort2D dim = VecShortCreateStatic2D();
    VecSet(&dim, 0, 2);
    VecSet(&dim, 1, 2);
    VecFloat* output = ISCRGBPredict(criterion, input, &dim);
    if (VecGetDim(output) != imgArea * nbClass) {
        PBIImgAnalysisErr->_type = PBErrTypeUnitTestFailed;
        sprintf(PBIImgAnalysisErr->_msg, "ISCRGBPredict failed");
        PBErrCatch(PBIImgAnalysisErr);
    }
    VecFree(&input);
    VecFree(&output);
    ImgSegmentorCriterionRGBFree(&criterion);
    printf("UnitTestImgSegmentorRGB OK\n");
}

void UnitTestImgSegmentorCreateFree() {
    int nbClass = 2;
    ImgSegmentor segmentor = ImgSegmentorCreateStatic(nbClass);
    if (segmentor._nbClass != nbClass ||
        segmentor._flagBinaryResult != false ||
        segmentor._nbEpoch != 1 ||
        !ISEQUALF(segmentor._thresholdBinaryResult, 0.5) ||
        !ISEQUALF(segmentor._targetBestValue, 0.9999)) {
        PBIImgAnalysisErr->_type = PBErrTypeUnitTestFailed;
        sprintf(PBIImgAnalysisErr->_msg, "ImgSegmentorCreateStatic failed");
        PBErrCatch(PBIImgAnalysisErr);
    }
    ImgSegmentorFreeStatic(&segmentor);
    printf("UnitTestImgSegmentorCreateFree OK\n");
}

void UnitTestImgSegmentorAddCriterionGetSet() {
    int nbClass = 2;
    ImgSegmentor segmentor = ImgSegmentorCreateStatic(nbClass);
    if (ISCriteria(&segmentor) != &(segmentor._criteria)) {
        PBIImgAnalysisErr->_type = PBErrTypeUnitTestFailed;
        sprintf(PBIImgAnalysisErr->_msg, "ISCriteria failed");
    }
}

```

```

    PBErCatch(PBImgAnalysisErr);
}
if (ISGetNbClass(&segmentor) != nbClass) {
    PBImgAnalysisErr->_type = PBErrTypeUnitTestFailed;
    sprintf(PBImgAnalysisErr->_msg, "ISGetNbClass failed");
    PBErCatch(PBImgAnalysisErr);
}
if (ISGetNbCriterion(&segmentor) != 0) {
    PBImgAnalysisErr->_type = PBErrTypeUnitTestFailed;
    sprintf(PBImgAnalysisErr->_msg, "ISGetNbCriterion failed");
    PBErCatch(PBImgAnalysisErr);
}
ISAddCriterionRGB(&segmentor);
if (GSetNbElem(&(segmentor._criteria)) != 1 ||
    ((ImgSegmentorCriterion*)GSetGet(&(segmentor._criteria),
    0))->_type != ISCType_RGB) {
    PBImgAnalysisErr->_type = PBErrTypeUnitTestFailed;
    sprintf(PBImgAnalysisErr->_msg, "ISAddCriterion failed");
    PBErCatch(PBImgAnalysisErr);
}
if (ISGetNbCriterion(&segmentor) != 1) {
    PBImgAnalysisErr->_type = PBErrTypeUnitTestFailed;
    sprintf(PBImgAnalysisErr->_msg, "ISGetNbCriterion failed");
    PBErCatch(PBImgAnalysisErr);
}
ISSetFlagBinaryResult(&segmentor, true);
if (segmentor._flagBinaryResult != true) {
    PBImgAnalysisErr->_type = PBErrTypeUnitTestFailed;
    sprintf(PBImgAnalysisErr->_msg, "ISSetFlagBinaryResult failed");
    PBErCatch(PBImgAnalysisErr);
}
if (ISGetFlagBinaryResult(&segmentor) != true) {
    PBImgAnalysisErr->_type = PBErrTypeUnitTestFailed;
    sprintf(PBImgAnalysisErr->_msg, "ISGetFlagBinaryResult failed");
    PBErCatch(PBImgAnalysisErr);
}
ISSetThresholdBinaryResult(&segmentor, 1.0);
if (!ISEQUALF(segmentor._thresholdBinaryResult, 1.0)) {
    PBImgAnalysisErr->_type = PBErrTypeUnitTestFailed;
    sprintf(PBImgAnalysisErr->_msg, "ISSetThrehsoldBinaryResult failed");
    PBErCatch(PBImgAnalysisErr);
}
if (!ISEQUALF(ISGetThresholdBinaryResult(&segmentor), 1.0)) {
    PBImgAnalysisErr->_type = PBErrTypeUnitTestFailed;
    sprintf(PBImgAnalysisErr->_msg, "ISGetThresholdBinaryResult failed");
    PBErCatch(PBImgAnalysisErr);
}
if (ISGetSizePool(&segmentor) != GENALG_NBENTITIES) {
    PBImgAnalysisErr->_type = PBErrTypeUnitTestFailed;
    sprintf(PBImgAnalysisErr->_msg, "ISGetSizePool failed");
    PBErCatch(PBImgAnalysisErr);
}
ISSetSizePool(&segmentor, GENALG_NBENTITIES + 100);
if (ISGetSizePool(&segmentor) != GENALG_NBENTITIES + 100) {
    PBImgAnalysisErr->_type = PBErrTypeUnitTestFailed;
    sprintf(PBImgAnalysisErr->_msg, "ISSetSizePool failed");
    PBErCatch(PBImgAnalysisErr);
}
if (ISGetNbElite(&segmentor) != GENALG_NBELITES) {
    PBImgAnalysisErr->_type = PBErrTypeUnitTestFailed;
    sprintf(PBImgAnalysisErr->_msg, "ISGetNbElite failed");
    PBErCatch(PBImgAnalysisErr);
}

```



```

    }
    ISSetNbElite(&segmentor, GENALG_NBELITES + 10);
    if (ISGetNbElite(&segmentor) != GENALG_NBELITES + 10) {
        PBIImgAnalysisErr->_type = PBErrTypeUnitTestFailed;
        sprintf(PBIImgAnalysisErr->_msg, "ISSetNbElite failed");
        PBErrCatch(PBIImgAnalysisErr);
    }
    if (!ISEQUALF(ISGetTargetBestValue(&segmentor), 0.9999)) {
        PBIImgAnalysisErr->_type = PBErrTypeUnitTestFailed;
        sprintf(PBIImgAnalysisErr->_msg, "ISGetTargetBestValue failed");
        PBErrCatch(PBIImgAnalysisErr);
    }
    ISSetTargetBestValue(&segmentor, 0.5);
    if (!ISEQUALF(ISGetTargetBestValue(&segmentor), 0.5)) {
        PBIImgAnalysisErr->_type = PBErrTypeUnitTestFailed;
        sprintf(PBIImgAnalysisErr->_msg, "ISSetTargetBestValue failed");
        PBErrCatch(PBIImgAnalysisErr);
    }
    ImgSegmentorFreeStatic(&segmentor);
    printf("UnitTestImgSegmentorAddCriterionGetSet OK\n");
}

void UnitTestImgSegmentorPredict() {
    int nbClass = 2;
    ImgSegmentor segmentor = ImgSegmentorCreateStatic(nbClass);
    ISAddCriterionRGB(&segmentor);
    char* fileNameIn = "ISPredict-in.tga";
    char fileNameOut[20];
    GenBrush* img = GBCreateFromFile(fileNameIn);
    GenBrush** res = ISPredict(&segmentor, img);
    for (int iClass = nbClass; iClass--;) {
        sprintf(fileNameOut, "ISPredict-out%02d.tga", iClass);
        GBSetFileName(res[iClass], fileNameOut);
        GBRender(res[iClass]);
    }
    ImgSegmentorFreeStatic(&segmentor);
    for (int iClass = nbClass; iClass--;)
        GBFree(res + iClass);
    free(res);
    GBFree(&img);
    printf("UnitTestImgSegmentorPredict OK\n");
}

void UnitTestImgSegmentorTrain() {
    srand(0);
    int nbClass = 2;
    ImgSegmentor segmentor = ImgSegmentorCreateStatic(nbClass);
    ISAddCriterionRGB(&segmentor);
    char* cfgFilePath = PBFSJoinPath(
        ".", "UnitTestImgSegmentorTrain", "dataset.json");
    GDataSetGenBrushPair dataSet =
        GDataSetGenBrushPairCreateStatic(cfgFilePath);
    ISSetSizePool(&segmentor, 20);
    ISSetNbElite(&segmentor, 5);
    ISSetNbEpoch(&segmentor, 100);
    ISSetTargetBestValue(&segmentor, 0.9);
    ITrain(&segmentor, &dataSet);
    char* imgFilePath = PBFSJoinPath(
        ".", "UnitTestImgSegmentorTrain", "img000.tga");
    GenBrush* img = GBCreateFromFile(imgFilePath);
    GenBrush** pred = ISPredict(&segmentor, img);
    for (int iClass = nbClass; iClass--;) {

```

```

    char outPath[100];
    sprintf(outPath, "pred000-%03d.tga", iClass);
    char* predFilePath = PBFSJoinPath(
        ".", "UnitTestImgSegmentorTrain", outPath);
    GBSetFileName(pred[iClass], predFilePath);
    GBRender(pred[iClass]);
    GBFree(pred + iClass);
    free(predFilePath);
}
free(pred);
GBFree(&img);
free(cfgFilePath);
free(imgFilePath);
GDataSetGenBrushPairFreeStatic(&dataSet);
ImgSegmentorFreeStatic(&segmentor);
printf("UnitTestImgSegmentorTrain OK\n");
}

void UnitTestImgSegmentor() {
    UnitTestImgSegmentorCreateFree();
    UnitTestImgSegmentorAddCriterionGetSet();
    UnitTestImgSegmentorPredict();
    UnitTestImgSegmentorTrain();
    printf("UnitTestImgSegmentor OK\n");
}

void UnitTestAll() {
    UnitTestImgKMeansClusters();
    UnitTestIntersectionOverUnion();
    UnitTestImgSegmentorRGB();
    UnitTestImgSegmentor();
}

int main(void) {
    //UnitTestAll();
    UnitTestImgSegmentorTrain();
    return 0;
}

```

5 Unit tests output

```

./ImgKMeansClustersTest/imgkmeanscluster.tga size K=2 cell=1:
<190.271,188.622,189.519,255.874>
<57.922,71.614,92.852,255.544>
./ImgKMeansClustersTest/imgkmeanscluster.tga size K=3 cell=1:
<197.903,195.060,194.940,255.852>
<46.857,55.700,72.989,255.384>
<129.141,141.318,156.154,255.440>
./ImgKMeansClustersTest/imgkmeanscluster.tga size K=4 cell=1:
<49.314,59.658,46.134,255.156>
<156.342,159.087,163.036,255.568>
<56.903,76.562,152.418,255.000>
<201.616,198.516,198.111,255.828>
./ImgKMeansClustersTest/imgkmeanscluster.tga size K=5 cell=1:
<42.357,54.043,156.886,255.000>
<47.936,59.604,46.270,255.149>
<119.585,133.399,145.312,255.076>
<177.630,176.173,177.662,255.664>

```

35

[illegible]

```

<193.738,192.354,194.603,255.624,191.464,190.109,192.329,255.624,190.082,188.651,190.943,255.624,189.102,187.653,189
<215.627,212.985,212.171,255.789,214.132,211.474,210.659,255.789,213.254,210.560,209.729,255.789,212.604,209.874,209
./ImgKMeansClustersTest/imgkmeanscluster.tga size K=6 cell=11:
<196.962,195.091,196.314,255.637,194.823,192.955,194.140,255.637,193.509,191.580,192.825,255.637,192.583,190.634,191
<216.604,213.962,213.103,255.769,215.146,212.500,211.632,255.769,214.297,211.606,210.719,255.769,213.659,210.932,210
<70.341,82.140,181.645,255.000,66.122,78.006,178.974,255.000,63.550,75.585,177.268,255.000,61.513,73.710,176.053,255
<168.407,174.211,187.354,255.172,165.483,171.246,184.447,255.172,163.417,169.211,182.599,255.172,161.927,167.772,181
<62.493,77.283,91.390,255.000,58.906,73.770,87.228,255.000,56.700,71.607,84.403,255.000,55.019,70.037,82.114,255.000
<158.205,157.647,153.292,255.000,154.523,153.677,149.119,255.000,151.883,151.184,146.267,255.000,149.633,149.100,143
UnitTestImgKMeansClusters OK
UnitTestIntersectionOverUnion OK


```




5.1 K-Means clustering on RGBA space

imgkmeanscluster.tga:








clustering for K equals 2 to 6 and radius equals 0 to 5:
K=2:







K=3:





K=4:






K=5:





K=6:





imgkmeanscluster.txt:

```
{
  "_size": "5",
  "_clusters": {
    "_seed": "1",
    "_centers": [
      {
        "_dim": "388",
        "_val": ["196.962387", "195.091156", "196.313553", "255.637268", "194.823151", "192.954971", "194.140289", "255.637268"],
      },
      {
        "_dim": "388",
        "_val": ["216.603745", "213.961731", "213.103195", "255.768936", "215.145920", "212.499786", "211.631653", "255.768936"],
      },
      {
        "_dim": "388",
        "_val": ["70.341324", "82.139534", "181.645172", "255.000000", "66.121559", "78.005623", "178.973862", "255.000000"],
      },
      {
        "_dim": "388",
        "_val": ["168.406982", "174.211227", "187.353622", "255.172226", "165.482742", "171.246460", "184.447128", "255.172226"],
      },
      {
        "_dim": "388",
        "_val": ["62.493431", "77.282890", "91.389877", "255.000000", "58.905697", "73.769623", "87.228317", "255.000000"],
      },
    ],
  },
}
```

```
{
  "_dim": "388",
  "_val": ["158.205353", "157.647125", "153.291733", "255.000000", "154.523422", "153.677002", "149.119064", "255.000000"]
}
```