

RAJSHAHI UNIVERSITY OF ENGINEERING & TECHNOLOGY

**DEPARTMENT OF ELECTRICAL AND ELECTRONIC
ENGINEERING**

LABORATORY REPORT

Course No: EEE 3102

Course Title: Digital Signal Processing Sessional

Experiment No: 02

Name of the Experiment:
Analyzing TRIAC Characteristics

Submitted by:

John Doe

Roll: 1901000

Section: A, Group: 1

Submitted to:

Dr. Jane Smith

Professor

Mr. Bob Brown

Lecturer

Date of Performance: October 07, 2026

Date of Submission: October 14, 2026

Experiment No: 02

Name of the Experiment: Analyzing TRIAC Characteristics

1 Introduction

A TRIAC (Triode for Alternating Current) is a three-terminal electronic component that conducts current in either direction when triggered. It is equivalent to two SCRs connected in inverse parallel with a common gate. The V-I characteristic shows forward and reverse blocking regions until the breakover voltage is reached, or a gate pulse is applied. A TRIAC (Triode for Alternating Current) is a three-terminal electronic component that conducts current in either direction when triggered. It is equivalent to two SCRs connected in inverse parallel with a common gate. The V-I characteristic shows forward and reverse blocking regions until the breakover voltage is reached, or a gate pulse is applied. A TRIAC (Triode for Alternating Current) is a three-terminal electronic component that conducts current in either direction when triggered. It is equivalent to two SCRs connected in inverse parallel with a common gate. The V-I characteristic shows forward and reverse blocking regions until the breakover voltage is reached, or a gate pulse is applied. A TRIAC (Triode for Alternating Current) is a three-terminal electronic component that conducts current in either direction when triggered. It is equivalent to two SCRs connected in inverse parallel with a common gate. The V-I characteristic shows forward and reverse blocking regions until the breakover voltage is reached, or a gate pulse is applied. A TRIAC (Triode for Alternating Current) is a three-terminal electronic component that conducts current in either direction when triggered. It is equivalent to two SCRs connected in inverse parallel with a common gate. The V-I characteristic shows forward and reverse blocking regions until the breakover voltage is reached, or a gate pulse is applied. A TRIAC (Triode for Alternating Current) is a three-terminal electronic component that conducts current in either direction when triggered. It is equivalent to two SCRs connected in inverse parallel with a common gate. The V-I characteristic shows forward and reverse blocking regions until the breakover voltage is reached, or a gate pulse is applied. A TRIAC (Triode for Alternating Current) is a three-terminal electronic component that conducts current in either direction when triggered. It is equivalent to two SCRs connected in inverse parallel with a common gate. The V-I characteristic shows forward and reverse blocking regions until the breakover voltage is reached, or a gate pulse is applied.

2 Circuit Design

A variable DC voltage source is connected across the main terminals of the TRIAC through a current-limiting resistor. A gate current is provided to trigger the device. The voltage is swept from negative to positive values to observe both quadrants of operation.




Figure 1: Experimental Circuit Diagram

3 Required Apparatus

- DC Power Supply (Variable) (Quantity: 1)
- TRIAC (e.g., BT136) (Quantity: 1)
- Resistor ($1k\Omega$) (Quantity: 1)
- Multimeter (Quantity: 2)

4 Procedure

1. Connect the circuit as per the experimental circuit diagram.
2. Apply a constant gate current I_G .
3. Vary the supply voltage from -15V to 15V.
4. Record the voltage across the TRIAC (V_{MT}) and the current flowing through it (I_{MT}).
5. Plot the V-I characteristics.

5 Result

V_{MT} (V)	I_{MT} (mA)
-1.5	-50.0
-0.8	-0.1
0.0	0.0
0.8	0.1
1.5	50.0

Table 1: Simulated TRIAC Data (Sample Points)




Figure 2: Simulated TRIAC V-I Curve

6 Discussion

The simulation results show the symmetrical conduction characteristics of the TRIAC. The device triggered into conduction in both the first and third quadrants when the voltage exceeded the threshold. The simulation results show the symmetrical conduction characteristics of the TRIAC. The device triggered into conduction in both the first and third quadrants when the voltage exceeded the threshold. The simulation results show the symmetrical conduction characteristics of the TRIAC. The device triggered into conduction in both the first and third quadrants when the voltage exceeded the threshold. The simulation results show the symmetrical conduction characteristics of the TRIAC. The device triggered into conduction in both the first and third quadrants when the voltage exceeded the threshold. The simulation results show the symmetrical conduction characteristics of the TRIAC. The device triggered into conduction in both the first and third

quadrants when the voltage exceeded the threshold. The simulation results show the symmetrical conduction characteristics of the TRIAC. The device triggered into conduction in both the first and third quadrants when the voltage exceeded the threshold.

7 Conclusion

The V-I characteristics of the TRIAC were successfully analyzed, demonstrating its bidirectional current control capabilities. The graphical results matched the theoretical expectations for a thyristor operating in AC environments. The V-I characteristics of the TRIAC were successfully analyzed, demonstrating its bidirectional current control capabilities. The graphical results matched the theoretical expectations for a thyristor operating in AC environments. The V-I characteristics of the TRIAC were successfully analyzed, demonstrating its bidirectional current control capabilities. The graphical results matched the theoretical expectations for a thyristor operating in AC environments. The V-I characteristics of the TRIAC were successfully analyzed, demonstrating its bidirectional current control capabilities. The graphical results matched the theoretical expectations for a thyristor operating in AC environments. The V-I characteristics of the TRIAC were successfully analyzed, demonstrating its bidirectional current control capabilities. The graphical results matched the theoretical expectations for a thyristor operating in AC environments. The V-I characteristics of the TRIAC were successfully analyzed, demonstrating its bidirectional current control capabilities. The graphical results matched the theoretical expectations for a thyristor operating in AC environments.

8 References

1. Boylestad, R. L., & Nashelsky, L. (2012). *Electronic Devices and Circuit Theory*.
2. Ngspice Simulation Data.