

CL1002 <i>Programming Fundamentals Lab</i>	Lab 04 Basic Decision Structures
---	---

NATIONAL UNIVERSITY OF COMPUTER AND EMERGING SCIENCES

Fall 2024.

AIMS AND OBJECTIVES

Aim:

The aim of learning basic decision structures in C is to understand and implement logical decision-making in programs. This involves using conditions to control the flow of execution, allowing programs to make choices based on different criteria, enhancing their interactivity, functionality, and responsiveness.

Objectives:

1. Understand the Concept of Decision Structures:

- Grasp the importance of decision-making in programming and how it helps in controlling the flow of a program.

2. Learn Basic Decision-Making Statements:

- Familiarize yourself with the primary decision structures in C, such as if, if-else, and switch statements.

3. Implement if and if-else Statements:

- Learn how to use if statements to execute code blocks based on a condition.
- Use if-else statements to handle multiple branches, allowing different actions based on whether a condition is true or false.

4. Use switch Statements for Multiple Choices:

- Learn how to use switch statements for scenarios involving multiple possible cases, improving code readability and organization over multiple if-else conditions.

5. Understand Relational and Logical Operators:

- Gain proficiency in using relational (==, !=, <, >, <=, >=) and logical operators (&&, ||, !) to form complex conditions within decision structures.

INTRODUCTION

Decision structures are fundamental building blocks in programming that allow programs to make choices based on certain conditions. In C, decision structures enable you to control the flow of execution, making your programs dynamic and responsive to different inputs and scenarios.

At the core of decision-making in C are statements like if, if-else, and switch, which provide mechanisms to execute specific blocks of code depending on whether certain conditions are true or false. These structures allow the program to "decide" what actions to take, making them essential for building interactive applications, performing calculations based on user input, managing error handling, and much more.

Understanding and effectively using decision structures is a critical skill for any programmer. They form the basis for writing logical, efficient, and flexible code that can adapt to varying requirements. Whether you are developing simple applications or complex systems, mastering decision structures will enhance your ability to create programs that can intelligently respond to different situations.

CONDITIONAL STATEMENTS

In C programming there are decision making statements, we need these kinds of statements because while programming we often need to make a lot of decisions. Let's take an example of a traffic signal management as show below




Figure 1. Example of a 4-Way smart traffic signal

In most countries there are vehicle sensors embedded in the road that detect how many cars are present in that lane. In the above-mentioned example these sensors are represented via black circles. If both circles are occupied by cars in that lane the time would be reduced to allow a smoother flow of traffic else if only one of the sensors is covered in that lane, then the timer would engage normally and start counting downwards until the counter value hits zero. Otherwise, if no sensors detects a vehicle then the signal would remain red.

EXAMPLE 1

In some cases, we need to execute this block of code

```
1  If the number is odd
2  {
3      //Execute some code if both sensors are detecting a vehicle
4  }
5  else
6  {
7      //Execute some code
8  }
```

Otherwise, we want to execute this block

```
1  If the number is odd
2  {
3      //Execute some code
4  }
5  Else
6  {
7      //Execute some code
8  }
```

In C, an if/else statement specifies that one block of code should be executed if a condition is true, and another block should be executed if that condition is false.

To write meaningful if/else statements, it is important to know operators which allow us to compare two expressions and produce a Boolean outcome.

In C, however, there are no distinct values for true or false, instead a false condition is denoted by a number 0 and anything which is non-zero is considered true.

<code>expr1 == expr 2</code>	This condition checks if expr1 is equal to expr2
<code>expr1 != expr 2</code>	This condition checks if expr1 is not equal to expr2
<code>expr1 < expr 2</code>	This condition checks if expr1 is less than expr2
<code>expr1 <= expr 2</code>	This condition checks if expr1 is less than or equal to expr2
<code>expr1 > expr 2</code>	This condition checks if expr1 is greater than expr2
<code>expr1 >= expr 2</code>	This condition checks if expr1 is greater than or equal to expr2
<code>!expr1</code>	This condition checks the logical NOT of expr1
<code>expr1 && expr 2</code>	This condition checks the logical AND of expr1 and expr2
<code>expr1 expr 2</code>	This condition checks the logical OR of expr1 and expr2

Figure 2. Use cases for if-else if- else statement

In 'C' programming conditional statements are possible with the help of the following two constructs:

1. If statement
2. If-else statement


It is also called branching as a program decides which statement to execute based on the result of the evaluated condition.

IF-STATEMENT

An if statement consists of a conditional expression followed by one or more statements.

If the conditional expression evaluates to true, then the block of code inside the if statement will be executed. If the conditional expression evaluates to false, then the first set of code after the end of the if statement (after the closing curly brace) will be executed.

Syntax: The syntax of an if statement in C programming language is:



```
If (condition)
```

```
{
```

```
//stateme
```

```
}
```

Example: Checking if the number input by user is 0 or not. If it's 0 then print Zero else print non-zero

```
#include <stdio.h>
int main() {
    int num;
    printf ("Enter any number\n");
    scanf("%d", &num);
    if (num==0)
        printf("Zero");
    else
        printf("Non-zero");
    return 0;
}
```


1. If else statement

An if statement can be followed by an optional else statement, which executes when the Boolean expression is false.

Syntax: The syntax of an if...else statement in C programming language is:

```
If (condition)
{
    //statements;
}
else
{
    //statements;
}
```

Flowchart:



Example: In FAST University 80% attendance is required for students to appear in the examination otherwise you won't be able to sit in an exam.

C Code

```
#include <stdio.h>
int main() {
    int attendance;
    printf ("Enter Attendance of your semeseter:\n");
    scanf ("%d", &attendance);
    if (attendance>80)
        printf ("You are eligible for the Examination");
    else
        printf ("Sorry! You are not for the Examination");
}
```

If - else if statement

An if statement can be followed by an optional else if...else statement, which is very useful to test various conditions using single if...else if statement.

When using if, else if, else statements there are few points to keep in mind:

1. An if can have zero or one else's and it must come after any else if's.
2. An if can have zero to many else if's and they must come before the else.
3. Once an else if succeeds, none of the remaining else if's or else's will be tested.

Syntax: The syntax of an if...else statement in C programming language is:

```

If (condition)
    {
        //statements;
    }
else if (condition)
    {
        //statements;
    }
else if (condition)
    {
        //statements;
    }
else
    {
        //statements;
    }

```

Example: FAST University wants to assign a grade to every PhD student according to the obtained marks. The grading criteria for PhD students is given below.

Ph.D.	Equivalent %
A+	90 & above
A	86
A-	82
B+	78
B	74
F	70
	66
	62
	58
	54
	50

Write a program to assign the grade to each student according to his marks.

```
#include<stdio.h>
void main()
{
    int marks;
    printf("Enter your marks ");
    scanf("%d",&marks);
    if(marks<0 || marks>100) {
        printf("Wrong Entry");
    }
    else if(marks>=90) {
        printf("Grade A+");
    }
    else if(marks>=86 && marks<90){
        printf("Grade A");
    }
    else if(marks>=82 && marks<86){
        printf("Grade A-");
    }
    else if(marks>=78 && marks<82){
        printf("Grade B+");
    }
    else if(marks>=74 && marks<78){
        printf("Grade B");
    }
    else{
        printf("Grade ");
    }
}
```

~~Nested If-else Statement~~

A nested if in C is an if statement that is the target of another if statement. Nested if statements mean an if statement inside another if statement.

Syntax: The syntax of a Nested if...else statement in C programming language is:

```
//check if the first condition holds
```

```
if (condition 1) {
```

```
    //if the second condition holds
```

```
    if (condition 2) {do something}
```

```
    //if the second condition does not hold
```

```
    else {do something else}
```

```
}
```

```
// if the first condition does not hold
```

```
else {
```

```
    //if the third condition holds
```


```
    if (condition 3) {do something}
```

```
    //if the third condition does not hold
```

```
    else {do something else}
```

```
}
```

Flowchart



Example: Write c program to analyze if the number is even or odd, and then if it is even, whether it is divisible by 4 or not, and if it is odd, whether it is divisible by 3 or not will be:

```
#include <stdio.h>
int main() {
    int n;
    printf("Enter The Number ");
    scanf("%d", &n);
    if (n % 2 == 0)
    {
        printf("Even ");
        if (n % 4 == 0) {
            printf("and divisible by 4");
        } else {
            printf("and not divisible by 4");
        }
    }
    else
    {
        printf("Odd ");
        if (n % 3 == 0) {
            printf("and divisible by 3");
        } else {
            printf("and not divisible by 3");
        }
    }
}
```

Ternary Operator

We use the ternary operator in C to run one code when the condition is true and another code when the condition is false.

Syntax.

The testCondition is a boolean expression that results in either true or false. If the condition is

true - expression1 (before the colon) is executed

false - expression2 (after the colon) is executed

The ternary operator takes 3 operands (condition, expression1 and expression2). Hence, the name ternary operator.

Example: Write a C program that takes a user's age as input and uses a ternary operator to print 'You can vote' if the age is 18 or older, and 'You cannot vote' otherwise.

```
#include <stdio.h>

int main() {
    int age;
    printf("Enter your age: ");
    scanf("%d", &age);

    // ternary operator to find if a person can vote or not
    (age >= 18) ? printf("You can vote") : printf("You cannot vote");

    return 0;
}
```

Switch Statement

Another way that programs can make decisions is to use switch/case. The syntax of switch/case is shown in the figure below.

Syntax:

```
switch (selection expression) {
    case 1:
        //statement
        break;
    case 2:
        //statement
        break;
    // ...
}
```

Here, when the execution arrow reaches the switch statement, the selection expression—in parenthesis after the keyword switch—is evaluated to a value.

This value is then used to determine which case to enter. The execution arrow then jumps to the corresponding case—the one whose label (the constant immediately after the keyword case) matches the selection expression's value. If no label matches, then the execution arrow jumps to the default case if there is one, and to the closing curly brace of the switch if not.

The following rules apply to a switch statement:


The expression used in a switch statement must have an integral or enumerated type, or be of a class type in which the class has a single conversion function to an integral or enumerated type.

You can have any number of case statements within a switch. Each case is followed by the value to be compared to and a colon.


Switch statement is better than if else statement.

A switch statement is usually more efficient than a set of nested ifs

Switch statement acts as a substitute for a long if-else-if ladder that is used to test a list of cases.



Flowchart




Example: Calculator using numbers to choose operators, if 1 is pressed then addition is performed, if 2 is pressed then subtraction if 3 is pressed then multiplication, if 4 is pressed then division otherwise print invalid choice.

```
#include <stdio.h>
int main() {
    int num1, num2, choice;
    printf ("Enter two numbers\n");
    scanf ("%d%d", &num1, &num2);

    printf("Press \n 1 for sum \n 2 for sub \n 3 for mul \n 4 for div\n");
    scanf ("%d", &choice);

    switch (choice) {
        case 1:
            printf("Sum = %d\n", num1 + num2);
            break;
        case 2:
            printf("Subtraction = %d\n", num1 - num2);
            break;
        case 3:
            printf("Multiplication = %d\n", num1 * num2);
            break;
        case 4:
            printf("Division = %d\n", num1 / num2);
            break;
        default:
            printf("Enter valid choice\n");
    }
}
```

Output:



```
E:\CPrograms\switch.exe
Enter two numbers
100
50
Press
 1 for sum
 2 for sub
 3 for mul
 4 for div
2
Subtraction = 50

-----
Process exited after 12.01 seconds with return value 17
Press any key to continue . . .
```

Nested-Switch Statement:

Nested-Switch statements refers to Switch statements inside of another Switch Statements.

Syntax

The syntax for a **nested switch** statement is as follows -

```
switch(ch1) {  
  
    case 'A':  
        printf("This A is part of outer switch");  
  
        switch(ch2) {  
            case 'A':  
                printf("This A is part of inner switch");  
                break;  
            case 'B': /* case code */  
            }  
  
            break;  
            case 'B': /* case code */  
        }  
}
```

Example

C program that simulates a weekly schedule for a person. The program should take inputs for the day (1-7) and activity (1 for working from home, 2 for the office, 3 for the gym) and display the corresponding activity for that day. Use switch-case statements for the logic.

```
#include <stdio.h>
int main() {
    int day = 1; // Assuming it's Wednesday
    int activity = 3; // 1: Work from home, 2: Office, 3: Gym
    switch (day) {
        case 1:
            printf("Monday: ");
            switch (activity) {
                case 1:
                    printf("Working from home\n");
                    break;
                case 2:
                    printf("Office\n");
                    break;
                case 3:
                    printf("Gym in the evening\n");
                    break;
                default:
                    printf("Invalid input\n");
            }
            break;
        case 2:
            printf("Tuesday: ");
            switch (activity) {
                case 1:
                    printf("Working from home\n");
                    break;
                case 2:
                    printf("Office\n");
                    break;
                case 3:
                    printf("Gym in the evening\n");
                    break;
                default:
                    printf("Invalid input\n");
            }
            break;
        // Add cases for the remaining days here

        default:
            printf("Other day\n");
    }

    return 0;
}
```

LAB Tasks

Q1. Write a program to see greetings according to time using a 24-hour format. If the time between is 5 to 11 it should greet "Good Morning", if time is between 12 to 18 it should greet "Good Evening", if time between 18 to 24 it should greet "Good Night".

Q2. Write a C program to find maximum between three numbers.

Q3. Using IF and Switch statement, write a program that displays the following menu for the food items available to take order from the customer:

- a. B= Burger (Rs. 200)
- b. F= French Fries (Rs. 50)
- c. P= Pizza (Rs. 500)
- d. S= Sandwiches (Rs. 150)

The costumer can order any combination of available food. The program first asks to enter the no of types of snacks i.e. 1 or 2, then it ask to enter the choice i.e. B for Burger and then for quantity. The program should finally display the total charges for the order.

```
ABC Restaurant Online Order Placement
WELCOME!

Please select from the following Menu
B= Burger
F= French Fries
P= Pizza
S= Sandwiches
How many types of snacks you need to order: 2
Enter first Snack you want to order: B
Please provide quantity: 2
Enter second Snack you want to order: P
Please provide quantity: 3
-----
You have ordered!
2 Burger (s) value 400 PKR
3 pizza (s) value 1500 PKR
Total: 1900 PKR
Thank you for your order... have a nice day.
```

Q4. Write a program to control a coffee machine. Allow the user to input the type of coffee as B for Black and W for White. Ask the user if the cup size is double and if the coffee is manual. The following table details the time chart for the machine for each coffee type. Display a statement for each step. If the coffee size is double, increase the baking time by 50 percent. Use functions to display instructions to the user and to compute the coffee time.

Operation	White Coffee	Black Coffee
Put Water	15 mins	20 mins
Sugar	15 mins	20 mins
Mix Well	20 mins	25 mins
Add Coffee	2 mins	15 mins
Add Milk	4 mins	-
Mix Well	20mins	25 mins

Note: Use switch structure to solve this problem.

Q5. Write a C program to input electricity unit charges and calculate total electricity bill according to the given condition:

- For first 50 units Rs. 0.50/unit
- For next 100 units Rs. 0.75/unit
- For next 100 units Rs. 1.20/unit
- For unit above 250 Rs. 1.50/unit

An additional surcharge of 20% is added to the bill

Q6. An online shopping store is providing discounts on the items due to the Eid. If the cost of items is less than 2000 it will give a discount up to 5%. If the cost of shopping is 2000 to 4000, a 10% discount will be applied. If the cost of

shopping is 4000 to 6000, a 20% discount will be applied. If it's more than 6000 then a 35% discount will be applied to the cost of shopping. Print the actual

amount, saved amount and the amount after discount. The Minimum amount eligible for a discount is 500.

Q7. Given a positive integer denoting n, do the following:

- If $1 \leq n \leq 9$, print lowercase English words corresponding to the numbers e.g. (one for 1, two for 2)
- If $n > 9$ print greater than 9