

Neighborhood Cognition Consistent Multi-Agent Reinforcement Learning

Hangyu Mao,^{1,2} Wulong Liu,² Jianye Hao,^{3,2} Jun Luo²
Dong Li,² Zhengchao Zhang,¹ Jun Wang,⁴ Zhen Xiao¹

¹Peking University, ²Noah's Ark Lab, Huawei

³Tianjin University, ⁴University College London

{hy.mao, zhengchaozhang, xiaozhen}@pku.edu.cn

{liuwulong, haojianye, jun.luo1, lidong106}@huawei.com
jun.wang@cs.ucl.ac.uk



北京大学
PEKING UNIVERSITY



HUAWEI
华为技术有限公司



诺亚方舟实验室
Noah's Ark Lab



天津大学
TIANJIN UNIVERSITY



UCL

英国伦敦大学学院
University College London



北京大学



Learning Agent Communication under Limited Bandwidth by Message Pruning


Hangyu Mao,¹ Zhengchao Zhang,¹ Zhen Xiao,¹ Zhibo Gong,² Yan Ni¹

¹Peking University, ²Huawei Technologies Co., Ltd.

{hy.mao, zhengchaozhang, xiaozhen, niyan.ny}@pku.edu.cn, gongzhibo@huawei.com



北京大学
PEKING UNIVERSITY



HUAWEI
华为技术有限公司



北京大学




Outline

- **Motivation**
- Design
- Evaluation
- Conclusion



北京大学




Many Stories of DRL



Win the best human
Go → Go Zero → Zero



Reduce data center
cooling bill by 40%



Playing Atari games




Berkeley helicopter

Alibaba Group | 阿里技术

从虚拟世界走进现实应用
**强化学习在阿里的
技术演进与业务创新**
Reinforcement Learning Beyond Games:
To Make a Difference in Alibaba



北京大学



Relatively Backward of MARL


five
decentralized
cooperative
agents

only
one
centralized
agent

*what
is
the
next
one*



北京大學



Focus of This Research


more agents in real systems



Abilene/Internet2 Network



Unmanned Aerial Vehicle




Smart Grid/WiFi Network



Autopilot/Unmanned Warship

**possible
answer:

more
agents**




Focus of This Research

But how to coordinate more agents?
Communication

But real applications has limited bandwidth!
Message pruning



北京大学




Focus of This Research

**We focus on addressing
the **limited bandwidth** problem
in multi-agent communication
by message pruning.**



北京大学




Outline

- Motivation
- **Design**
- Evaluation
- Conclusion



北京大学



ACML (w/o Comm.)

- ACML combines the merits of the existing methods.




Figure 1. The proposed ACML. For clarity, we illustrate this model with a two-agent example. All components are implemented by DNN. The red arrows indicate the message exchange process.


However,

the agents have to send messages continuously (in order to generate one action),

regardless of whether the messages are beneficial to the performance of the agent team.




北京大学



Gated-ACML

- Gated-ACML applies a gating mechanism to adaptively identify less beneficial messages (for the agent team) and thus to adaptively prune these messages.


Figure 2: The actor part of Gated-ACML. For clarity, we only show one agent's structure; we do not show the critic part because it is the same as that of ACML.



- To make the above design work, **a suitable p must be trained for each observation**, otherwise Gated-ACML may degenerate to ACML in the extreme case where $I(p > 0.5) \equiv 1$.
- However, as the indicator function $g \leftarrow I(p > 0.5)$ is **non-differentiable**, it makes the end-to-end backpropagation method inapplicable.
- To bypass the training of the non-differentiable indicator function, **we train the input p directly by the auxiliary task technique** (ICLR 2016), which provides training signal for p explicitly.



北京大学



Gated-ACML

➤ Because we want to prune the messages on the premise of maintaining the performance (), we design the following auxiliary task.

- ① Let p indicate the probability that $\Delta Q(o) = Q(o, a^C) - Q(o, a^I)$ is larger than T .
- ② In this setting, the true label of this auxiliary task can be formulated as:

$$Y(o_i) = \mathbb{I}(Q(\langle o_i, \vec{a}_i^C \rangle, \langle \vec{o}_{-i}, \vec{a}_{-i}^C \rangle) - Q(\langle o_i, \vec{a}_i^I \rangle, \langle \vec{o}_{-i}, \vec{a}_{-i}^C \rangle) > T)$$


- ③ Then we can train p by minimizing the following loss function:

$$L_{\theta_{op}}(o_i) = -E_{o_i}[Y(o_i)\log p(o_i|\theta_{op}) + (1 - Y(o_i))\log(1 - p(o_i|\theta_{op}))]$$

The insight: If $\Delta Q(o)$ is really larger than T (i.e., a^C can obtain at least T Q-values that a^I , and $Y(o) = 1$), the network should try to generate a probability p that is larger than $T_p = 0.5$ to encourage communication.



北京大学



Key Implementation

- The training method relies on correct labels of the auxiliary task.

$$Y(o_i) = \mathbb{I}(Q(\langle o_i, \mathbf{a}_i^C \rangle, \langle \vec{o}_{-i}, \vec{\mathbf{a}}_{-i}^C \rangle) - Q(\langle o_i, \mathbf{a}_i^I \rangle, \langle \vec{o}_{-i}, \vec{\mathbf{a}}_{-i}^C \rangle) > T)$$

- $Q(o, \mathbf{a}^C)$ and $Q(o, \mathbf{a}^I)$ can be estimated by setting $g=1$ and $g=0$, respectively.

- For T , we propose two methods to set a fixed T and a dynamic T .

- The moving average to set a **dynamic** T :

- $T_t = (1 - \beta)T_{t-1} + \beta \left(Q_t(\langle o_i, \mathbf{a}_i^C \rangle, \langle \vec{o}_{-i}, \vec{\mathbf{a}}_{-i}^C \rangle) - Q_t(\langle o_i, \mathbf{a}_i^I \rangle, \langle \vec{o}_{-i}, \vec{\mathbf{a}}_{-i}^C \rangle) \right)$

- **Advantage:** $Y(o)$ becomes an adaptive training label even for the same observation o . This is very important for the dynamically changing environments.

- Pre-calculating to set a fixed T :


- First, sort the $\Delta Q(o)$ of the latest K observations encountered during training, resulting in $L_{\Delta Q(o)}$.

- Then, set T by splitting $L_{\Delta Q(o)}$ **in terms of the index**. For example, if we want to prune $T_m\%$ messages, we set $T = L_{\Delta Q(o)}[K \times T_m\%]$.

- **Advantage:** the actual number of pruned messages is ensured to be close to the desired $T_m\%$.



北京大学




Outline







- Motivation
- Design
- **Evaluation**
- Conclusion




北京大学



Environments



北京大学



Results


Table 2: The average results of 10 experiments on packet routing and wifi access point configuration tasks. For models named as Gated-*, we adopt dynamic thresholds with $\beta = 0.8$. The “WAPC.” is the abbreviation of Wifi Access Point Configuration.

	Simple Routing		Moderate Routing		Complex Routing		Simple WAPC.		Complex WAPC.	
	reward	message	reward	message	reward	message	reward	message	reward	message
CommNet	0.264	100.0%	0.164	100.0%	-	100.0%	0.652	100.0%	0.441	100.0%
AMP	0.266	100.0%	0.185	100.0%	-	100.0%	0.627	100.0%	0.418	100.0%
ACML	0.317	100.0%	0.263	100.0%	-	100.0%	0.665	100.0%	0.480	100.0%
ACML-mean	0.321	100.0%	0.267	100.0%	-	100.0%	0.673	100.0%	0.493	100.0%
ACML-attention	0.329	100.0%	0.271	100.0%	-	100.0%	0.689	100.0%	0.506	100.0%

ACML (i.e., w/o message pruning) works better than baselines.



北京大学



Results


Table 2: The average results of 10 experiments on packet routing and wifi access point configuration tasks. For models named as Gated-*, we adopt dynamic thresholds with $\beta = 0.8$. The “WAPC.” is the abbreviation of Wifi Access Point Configuration.

	Simple Routing		Moderate Routing		Complex Routing		Simple WAPC.		Complex WAPC.	
	reward	message	reward	message	reward	message	reward	message	reward	message
CommNet	0.264	100.0%	0.164	100.0%	-	100.0%	0.652	100.0%	0.441	100.0%
AMP	0.266	100.0%	0.185	100.0%	-	100.0%	0.627	100.0%	0.418	100.0%
ACML	0.317	100.0%	0.263	100.0%	-	100.0%	0.665	100.0%	0.480	100.0%
ACML-mean	0.321	100.0%	0.267	100.0%	-	100.0%	0.673	100.0%	0.493	100.0%
ACML-attention	0.329	100.0%	0.271	100.0%	-	100.0%	0.689	100.0%	0.506	100.0%
Gated-CommNet	0.232	35.2%	0.144	21.7%	-	19.8%	0.595	53.1%	0.386	41.8%
Gated-AMP	0.241	46.7%	0.170	35.0%	-	81.7%	0.539	57.2%	0.350	32.3%
Gated-ACML	0.288	33.6%	0.239	27.9%	-	22.6%	0.610	41.9%	0.411	37.7%
ATOC	0.297	73.7%	0.102	104.6%	-	326.1%	0.418	136.5%	0.231	393.4%

Gated-ACML (w/ dynamic T) can prune a lot of messages with little impact on performance.



北京大学



Results

Table 2: The average results of 10 experiments on packet routing and wifi access point configuration tasks. For models named as Gated-*, we adopt dynamic thresholds with $\beta = 0.8$. The “WAPC.” is the abbreviation of Wifi Access Point Configuration.

	Simple Routing		Moderate Routing		Complex Routing		Simple WAPC.		Complex WAPC.	
	reward	message	reward	message	reward	message	reward	message	reward	message
CommNet	0.264	100.0%	0.164	100.0%	-	100.0%	0.652	100.0%	0.441	100.0%
AMP	0.266	100.0%	0.185	100.0%	-	100.0%	0.627	100.0%	0.418	100.0%
ACML	0.317	100.0%	0.263	100.0%	-	100.0%	0.665	100.0%	0.480	100.0%
ACML-mean	0.321	100.0%	0.267	100.0%	-	100.0%	0.673	100.0%	0.493	100.0%
ACML-attention	0.329	100.0%	0.271	100.0%	-	100.0%	0.689	100.0%	0.506	100.0%
Gated-CommNet	0.232	35.2%	0.144	21.7%	-	19.8%	0.595	53.1%	0.386	41.8%
Gated-AMP	0.241	46.7%	0.170	35.0%	-	81.7%	0.539	57.2%	0.350	32.3%
Gated-ACML	0.288	33.6%	0.239	27.9%	-	22.6%	0.610	41.9%	0.411	37.7%
ATOC	0.297	73.7%	0.102	104.6%	-	326.1%	0.418	136.5%	0.231	393.4%


Table 3: The results of Gated-ACML in packet routing scenarios. We adopt a fixed threshold $T = L_{\Delta Q_{(o_i)}}[K \times T_m \%]$.

$T_m \%$	Simple Routing		Moderate Routing	
	pruned message	reward decrease	pruned message	reward decrease
10.0%	12.19%	-8.46%	11.60%	-7.03%
20.0%	24.07%	-13.59%	22.77%	-12.14%
30.0%	27.65%	-4.88%	29.98%	-3.25%
70.0%	66.73%	9.27%	68.54%	10.06%
80.0%	79.14%	14.01%	76.81%	13.25%
90.0%	87.22%	18.60%	85.11%	19.50%
100.0%	100.00%	59.35%	100.00%	65.42%

Gated-ACML (w/ fixed T) can ensure the number of prune messages is close to the desired $T_m \%$.



北京大学




Results

Table 2: The average results of 10 experiments on packet routing and wifi access point configuration tasks. For models named as Gated-*, we adopt dynamic thresholds with $\beta = 0.8$. The “WAPC.” is the abbreviation of Wifi Access Point Configuration.

	Simple Routing		Moderate Routing		Complex Routing		Simple WAPC.		Complex WAPC.	
	reward	message	reward	message	reward	message	reward	message	reward	message
CommNet	0.264	100.0%	0.164	100.0%	-	100.0%	0.652	100.0%	0.441	100.0%
AMP	0.266	100.0%	0.185	100.0%	-	100.0%	0.627	100.0%	0.418	100.0%
ACML	0.317	100.0%	0.263	100.0%	-	100.0%	0.665	100.0%	0.480	100.0%
ACML-mean	0.321	100.0%	0.267	100.0%	-	100.0%	0.673	100.0%	0.493	100.0%
ACML-attention	0.329	100.0%	0.271	100.0%	-	100.0%	0.689	100.0%	0.506	100.0%
Gated-CommNet	0.232	35.2%	0.144	21.7%	-	19.8%	0.595	53.1%	0.386	41.8%
Gated-AMP	0.241	46.7%	0.170	35.0%	-	81.7%	0.539	57.2%	0.350	32.3%
Gated-ACML	0.288	33.6%	0.239	27.9%	-	22.6%	0.610	41.9%	0.411	37.7%
ATOC	0.297	73.7%	0.102	104.6%	-	326.1%	0.418	136.5%	0.231	393.4%

Table 3: The results of Gated-ACML in packet routing scenarios. We adopt a fixed threshold $T = L_{\Delta Q_{(o_i)}}[K \times T_m\%]$.


$T_m\%$	Simple Routing		Moderate Routing	
	pruned message	reward decrease	pruned message	reward decrease
10.0%	12.19%	-8.46%	11.60%	-7.03%
20.0%	24.07%	-13.59%	22.77%	-12.14%
30.0%	27.65%	-4.88%	29.98%	-3.25%
70.0%	66.73%	9.27%	68.54%	10.06%
80.0%	79.14%	14.01%	76.81%	13.25%
90.0%	87.22%	18.60%	85.11%	19.50%
100.0%	100.00%	59.35%	100.00%	65.42%



The messages are distributed near the junction where communication is critical for safety deriving.



北京大学




Outline

- Motivation
- Design
- Evaluation
- **Conclusion**



北京大学




Conclusion

- We have proposed a gating mechanism, which consists of several key designs like auxiliary task with appropriate training signal, dynamic and fixed thresholds, to address the limited bandwidth that has been largely ignored by previous DRL methods.
- The gating mechanism prunes less beneficial messages in an adaptive manner, so that the performance can be maintained or even improved with much fewer messages. (as shown by the experiments on three tasks developed based on eight real-world scenarios.)
- Furthermore, it is applicable to several previous methods and multi-agent scenarios with good performance.
- To the best of our knowledge, it is the first method to achieve these in the multi-agent reinforcement learning community.



北京大学



Thanks for Listening!

Question?



北京大學