

ReDISchool

Introduction to Programming - Fall 2026

Classes and files

Keep data and actions together. Keep data for next time.

Write your own classes, then read and write text files.

What we'll learn today

1. **Classes and objects:** keep a thing's data and its actions together.
2. **Files:** read a text file, write a new one, and add lines to it.
3. **Your project:** start thinking about your own project idea.

Part 1: Classes and objects

Keep a thing's data and its actions together.

01	Quick recap
02	What is an object?
03	Where do objects live?
04	Making our own objects - Class
05	Your first class
06	`__init__` and `self`
07	Methods
08	When to use a class?

Practice: a wallet.

01 - Quick recap

Last week, we could store a dog in a dictionary and write functions for it.

```
dog = {"name": "Rex", "age": 3, "hungry": True}

def describe(dog):
    print(f"{dog['name']} is {dog['age']} years old")

def feed(dog):
    dog["hungry"] = False

describe(dog)          # Rex is 3 years old
feed(dog)
print(dog["hungry"])   # False
```

The data is in the dictionary. The actions are separate functions. The data and the actions live apart.

02 - What is an object?

A dog **has** things and **does** things.

A dog has: a name, an age, hungry or not
A dog does: bark, eat

Word	Meaning
Object	A value in your program that holds data and can do actions
Attribute	Something the object **has**, such as its name
Method	Something the object **does**, such as bark
State	The values of its attributes right now. After the dog eats, it is no longer hungry.

Objects in code

You have already used objects.

```
name = "rex"
print(name.upper())   # REX
print(type(name))     # <class 'str'>
```

```
dogs = ["Rex"]
dogs.append("Bella")
print(dogs)           # ['Rex', 'Bella']
print(type(dogs))     # <class 'list'>
```

`.upper()` and `.append()` are **methods**. `str` and `list` are **classes**.

`type()` tells you which class an object was made from. Today you will write your own class.

An object has state

State means the values an object holds right now. Its methods can change them.

```
import turtle

tina = turtle.Turtle()        # a new turtle object
tina.shape("turtle")
tina.shapesize(3)             # 3 times bigger
print(tina.position())        # (0.00,0.00)
print(tina.heading())         # 0.0

tina.forward(100)             # moves and draws a line
tina.left(90)                 # turns left
print(tina.position())        # (100.00,0.00)
print(tina.heading())         # 90.0

print(type(tina))             # <class 'turtle.Turtle'>
turtle.done()                 # keeps the window open
```

`Turtle` is a class from the `turtle` library.

The state of `tina` is her position and her direction.

- `forward()` changes her position.
- `left()` changes her direction.


`tina` remembers her new state, so later code sees it.

03 - Where do objects live?

```
tina = turtle.Turtle()
leo = turtle.Turtle()
print(tina)
```

```
<turtle.Turtle object at 0x10a3f2b50>
```

Each `turtle.Turtle()` makes a new object on the **heap**. `0x10a3f2b50` is its **address**.



A variable does not hold the object. It holds the object's **address**.

0x10a3f2b30	0x10a3f2b40	0x10a3f2b50	0x10a3f2b60	0x10a3f2b70	0x10a3f2b80
empty	empty	tina's Turtle	empty	empty	leo's Turtle

Memory is a long row of boxes, and each box has a number: its **address**. The heap is the part of memory where Python keeps objects.


Two names, one object

```
tina = turtle.Turtle()
tom = tina        # no new turtle is made

tom.forward(100)
print(tina.position())
```

```
(100.00,0.00)
```

`tom = tina` copies the **address**, not the turtle. Both names point to the same object, so when `tom` moves, `tina` moves too.



Want a second turtle? Call `turtle.Turtle()` again.

04 - Making our own objects - Class

A **class** is a template for making objects. It says what every object of that kind **has** and **does**.

Think of a **cookie cutter**. The cutter is not a cookie, but every cookie you press out with it has the same shape. Each cookie is its own cookie, and you can decorate each one differently.



Idea	Cookies	Python
Class: what every object has and does	the cutter	`Dog` : a name, an age, can bark
Instance: an object made from the class	one cookie	`rex` : Rex, age 3
Another **instance**	another cookie	`bella` : Bella, age 5

One class, many objects. They have the same parts, but each one has its own values.

05 - Your first class

```
class Dog:
    pass

rex = Dog()
bella = Dog()

rex.name = "Rex"
rex.age = 3
bella.name = "Bella"

print(rex.name)      # Rex
print(bella.age)     # crashes!
```


```
AttributeError: 'Dog' object has no attribute 'age'
```

- `class Dog:` creates a class. Class names start with a capital letter.
- `pass` means "nothing here yet". `Dog()` creates a new object.
- We forgot Bella's age. We need a way to fill in every box when we create a dog.

06 - `__init__` and `self`

```python
class Dog:
    def __init__(self, name, age):
        self.name = name
        self.age = age

rex = Dog("Rex", 3)
```



`self` and `rex` hold the same **address**, so they are two names for the same dog.

`__init__` : the setup method

Python runs it **automatically** every time you create an object, for example `Dog("Rex", 3)`. It gives the new object its starting **attributes**. It has **two underscores** on each side.

`self` : the object itself

`self` is the object being set up. When we create Rex, `self` is Rex.

`self.name = name` means "save the name we were given inside this object".

What happens on `Dog("Rex", 3)`?

```
rex = Dog("Rex", 3)
bella = Dog("Bella", 5)

print(rex.name, rex.age)        # Rex 3
print(bella.name, bella.age)    # Bella 5
```

1. Python creates a new, empty `Dog` object.
2. It runs `__init__`: `self` is the new object, `name` is `"Rex"`, `age` is `3`.
3. `self.name = name` saves `"Rex"` in the object.
4. The new object is stored in `rex`.

We never pass `self` ourselves. Python does it for us.

Predict the output

```
class Dog:
    def __init__(self, name, age):
        self.name = name
        self.age = age

rex = Dog("Rex", 3)
bella = Dog("Bella", 5)
bella.age = 6

print(rex.age)
print(bella.name, bella.age)
```

What two lines are printed?

Exercise: Wallet · 10 min

You are building a wallet. Every wallet has an owner and an amount of money in Danish Kroner.

1. Write a class `Wallet`. It should be initialized with an `owner` (string) and `money` (a number) and saves them as attributes.
2. Create a wallet for "Ana" with 200 DKK and a wallet for "Ben" with 125 DKK.
3. Print each wallet's owner and money.
4. **(Advanced)** Put both wallets in a list and use a loop to print every owner and their money.

Expected input and output

Code	Output
`ana = Wallet("Ana", 200)` `print(ana.owner)`	`Ana`
`print(ana.money)`	`200`
`ben = Wallet("Ben", 125)`	`125`

Help

```python
class Dog:
    def __init__(self, name, age):
        self.name = name
        self.age = age

rex = Dog("Rex", 3)
print(rex.name)
```

Starter: exercises/09-classes-and-files/wallet/

07 - Methods

A **method** is a function inside a class. Its first parameter is `self`.

```
class Dog:
    def __init__(self, name):
        self.name = name
        self.hungry = True

    def bark(self):
        print(f"{self.name} says Woof!")

    def eat(self):
        self.hungry = False

rex = Dog("Rex")
bella = Dog("Bella")
rex.bark()             # Rex says Woof!
rex.eat()
print(rex.hungry)      # False
print(bella.hungry)    # True
```

In `rex.eat()`, `self` is `rex`. So `self` gives the method access to **this** object's attributes.

Return a value or change an attribute

```
class Dog:
    # __init__, bark and eat as before

    def is_hungry(self):
        return self.hungry

    def feed_if_hungry(self):
        if self.is_hungry():
            self.eat()
```

Method	What it does
`is_hungry()`	**Returns** a value. It changes nothing.
`eat()`	**Changes** an attribute. It returns nothing.
`feed_if_hungry()`	Calls other methods of the same object with `self.`

```
rex = Dog("Rex")
rex.feed_if_hungry()
print(rex.is_hungry())    # False
```

Exercise: Wallet methods · 15 min

Copy the code from the starter if you need it: wallet-methods/exercise.py

Our wallet is not useful yet. Let's allow it to receive money and pay for things.

1. Add a method `receive(amount)` that adds `amount` to `money`.
2. Add a method `has_enough_money(price)` that returns `True` if `money` is at least `price`, otherwise `False`.
3. Add a method `pay(price)`. If `money` is at least `price`, it subtracts `price` from `money` and returns `True`. Otherwise it returns `False` and does not change `money`.
4. **(Advanced)** Add a method `pay_all(prices)` that calls `pay` for each price in the list and returns how many prices were paid.

Expected input and output

```
wallet = Wallet("Ana", 200)
wallet.receive(50)              # money 250
wallet.has_enough_money(300)    # False
wallet.pay(100)                 # True, money 150
wallet.pay(400)                 # False, money 150
wallet.pay_all([50, 200, 30])   # 2, money 70
```

Help

```
class Dog:
    def eat(self):          # changes an attribute
        self.hungry = False

    def is_hungry(self):    # returns a value
        return self.hungry
```

08 - When to use a class?

	Dictionary	Class
Create	`dog = {"name": "Rex", "age": 3}`	`rex = Dog("Rex", 3)`
Read a value	`dog["name"]`	`rex.name`
Actions	Separate functions: `feed(dog)`	Methods: `rex.eat()`
Same boxes every time?	Not checked	`__init__` fills them in

- Use a **dictionary** for simple data that you look up by key.
- Use a **class** when the data and the actions belong together, or when you create many things of the same kind.

Break

15 minutes

Part 2: Working with files

Keep data after the program ends.

09	Why files?
10	Opening and closing a file
11	Reading a file
12	Writing
13	Adding to a file

Practice: a shopping list file.

09 - Why files?

Variables disappear when the program ends.

A **file** keeps data for next time: a shopping list that is still there tomorrow.

We can also share data with someone else by giving them a file.

A **text file** is just lines of text (strings), like a `.txt` or `.py` file in VS Code.

```
bread
milk
eggs
```

Files and folders reminder

Every file lives inside a folder. A **path** says where the file is.

	Path
Windows	`C:\Users\ana\redi\shopping.txt`
macOS	`/Users/ana/redi/shopping.txt`

A plain name like `"shopping.txt"` means "the file in the folder my terminal is in".

1. In VS Code, open the exercise folder with `Open Folder...`.
2. Put the file next to `exercise.py`.
3. Open **Terminal → New Terminal** and run the program there:

```
python3 exercise.py    # macOS
py exercise.py         # Windows
```

10 - Opening and closing a file

```
file = open("shopping.txt", "r")
text = file.read()
print(text)
file.close()
```

`open` gives back a **file object**. Like the objects in Part 1, it has methods: `.read()`, `.write()` and `.close()`.

Mode	Meaning
`"r"`	**Read** the file
`"w"`	**Write** a new file (erases what was there first)
`"a"`	**Add** to the end of the file

The file must be **closed** with `file.close()`. Until then, Python keeps it open, and what you wrote may not be saved to the disk yet.

The `with` block

```
with open("shopping.txt", "r") as file:
    text = file.read()
    print(text)

print("The file is closed now")
```

With this pattern, Python makes sure the file is **closed** when the indented block ends.

From now on, we always use `with`.

11 - Reading a whole file

```
with open("shopping.txt", "r") as file:
    text = file.read()  # "bread\nmilk\neggs\n"
```

The file `shopping.txt`

```
bread
milk
eggs
```

`file.read()`



The string in `text`

```
"bread\nmilk\neggs\n"
```

`"\n"` means **new line**. When we `print(text)`, each `"\n"` becomes a line break again.

Reading line by line

```
with open("shopping.txt", "r") as file:
    for line in file:
        print(line)
```

```
bread

milk

eggs
```

```
with open("shopping.txt", "r") as file:
    for line in file:
        print(line.strip())
```

```
bread
milk
eggs
```

`for line in file:` gives one line at a time. Each line still ends with `"\n"`, and `print` adds another new line.

`.strip()` (from lesson 04) removes the `"\n"`.

Trace the loop

```
with open("shopping.txt", "r") as file:
    for line in file:
        print(line.strip())
```

Round	`line`	`line.strip()`
1	`"bread\n"`	`"bread"`
2	`"milk\n"`	`"milk"`
3	`"eggs\n"`	`"eggs"`

The loop stops after the last line.

Building a list from a file

```
items = []
with open("shopping.txt", "r") as file:
    for line in file:
        item = line.strip()
        if item != "":
            items.append(item)

print(items)    # ['bread', 'milk', 'eggs']
```

- Start with an empty list `[]`.
- Add each line, without its `"\n"`, to the list.
- An empty line becomes `""` after `.strip()`, so we skip it.

Exercise: Shopping list · 10 min

You keep your shopping list in a file, one item per line. Write code that reads it.

1. In VS Code, make a new file `shopping_list.txt` next to your `exercise.py`. Type a few items into it by hand, one per line, and save it (see the example below).
2. Write the function `print_list(filename)`: **prints** every item, with no empty lines.
3. **(Advanced)** Write the function `has_item(filename, item)`: **returns** `True` if `item` is in the file, otherwise `False`.

Expected input and output

shopping_list.txt

```
bread
milk
eggs
```

```
print_list("shopping_list.txt")  # prints:
# bread
# milk
# eggs
has_item("shopping_list.txt", "milk")    # True
has_item("shopping_list.txt", "cheese")  # False
```

Help

```
with open(filename, "r") as file:
    for line in file:
        print(line.strip())
```

`.strip()` removes the `"\n"` at the end of a line.

For `has_item`, check `line.strip() == item`.

Starter: exercises/09-classes-and-files/shopping-list/

12 - Writing

`"w"` opens a file for **writing**. `file.write()` puts text into the file.

```
with open("shopping.txt", "w") as file:
    file.write("bread\n")
    file.write("milk\n")
```

Before: shopping.txt

```
tea
```

`"w"`



After: shopping.txt

```
bread
milk
```

- `"w"` **erases** the old text first. If the file does not exist yet, `"w"` creates it.
- `.write()` does not start a new line by itself. Without `"\n"` we get `breadmilk`.

13 - Adding to a file

`"a"` opens a file for **adding** (a = append). New text goes at the **end**, and the old lines stay.

```
with open("shopping.txt", "a") as file:
    file.write("eggs\n")
```

Before: shopping.txt

```
bread
milk
```

`"a"`



After: shopping.txt

```
bread
milk
eggs
```

- Use `"a"` when you want to **keep** what is already in the file.
- If the file does not exist yet, `"a"` creates it.

What is in `shopping.txt`?

```
with open("shopping.txt", "w") as file:
    file.write("tea\n")

with open("shopping.txt", "a") as file:
    file.write("milk\n")

with open("shopping.txt", "w") as file:
    file.write("bread\n")

with open("shopping.txt", "a") as file:
    file.write("eggs\n")
```

What is in the file after these lines run?

Exercise: Add to the shopping list · 10 min

Now you want to change your shopping list from Python. Write code that saves a new list and adds items to it.

1. Write the function `save_list(filename, items)`: `filename` is the name of the file, such as `"shopping.txt"`. `items` is a list of strings. It **writes** each item into the file, one per line. Anything already in the file is **replaced**.
2. Write the function `add_item(filename, item)`: `item` is one string. It **adds** `item` to the end of the file. The old items **stay**.
3. **(Advanced)** Write the function `add_items(filename, items)`: `items` is a list of strings. It **adds** each item to the end of the file. Use `add_item`.

Expected input and output

```
save_list("shopping.txt", ["bread", "milk"])
add_item("shopping.txt", "eggs")
add_items("shopping.txt", ["cheese", "apples"])
```

shopping.txt afterwards

```
bread
milk
eggs
```

Help

```
with open(filename, "w") as file:
    file.write(item + "\n")
```

`"w"` replaces the file. `"a"` adds to the end.

Use a `for` loop to write every item in a list.

Starter: exercises/09-classes-and-files/shopping-list-write/

Common mistakes

Mistake	What you see	Fix
The file is not in the terminal's folder	`FileNotFoundError: [Errno 2] No such file or directory: 'shopping.txt'`	Read the message. Check the file name and the folder your terminal is in
Forgetting `"\n"`	All items on one line: `breadmilk`	Add `"\n"` after each item
Using `"w"` when you meant `"a"`	The old lines are gone	Use `"a"` to add to the end

The main ideas

- A **class** is like a cookie cutter. Each **object** is one cookie made with it.
- `__init__` fills in the **attributes** when an object is created. `self` is the object itself.
- **Methods** are functions inside a class: `rex.eat()`.
- Objects live on the **heap**. A variable holds an object's address, so `b = a` makes two names for the same object.
- Open files with `with open(name, mode) as file:`. The file closes by itself.
- `"r"` reads, `"w"` writes a new file (erases first), `"a"` adds to the end.
- `for line in file:` reads one line at a time. `.strip()` removes the `"\n"`.

Part 3: Your project

Build a small program of your own, using what we've learned.

TODAY

Pick an idea

Think of your own project, based on the topics we've discussed.

WEEK 11

Start building

Start writing your project in class. We will be there to help.

WEEK 12

Present

Show your work to the class. 5 minutes each.

Everyone works on their own project.

Project ideas

BEST IDEA

Something from the field you work in, or want to work in. Think of a small task there that a program could do for you.

Some other ideas:

Virtual pet

Feed, play with and put your pet to bed. It gets hungry over time. Saved in a file.

class · methods · files

Secret code

Turn a message into a secret code by swapping letters, and back again.

strings · loops · dict

Job application tracker

Companies you applied to, the status and the next step. Saved in a file.

class · files · lists

More ideas at the end of the slides.

Questions?

More project ideas

- **Quiz game:** asks questions, keeps a score, says if you passed. (input, conditionals, loops, dict)
- **Shopping budget:** add items with prices, warns when you go over budget. (lists, functions, Wallet class)
- **Flashcards:** practise words in another language, repeats the ones you got wrong. (dict, loops, lists)
- **Recipe book:** store recipes and search by ingredient. (dict of lists, functions)
- **To-do list:** add, finish and list tasks, saved in a file. (lists, files, class)
- **Habit tracker:** tick off habits each day and see your streak. (dict, loops, files)
- **Split the bill:** who paid what and who owes whom after a trip with friends. (dict, functions)
- **Hangman+ / guess the number:** extend a game from class with levels and a high score file. (loops, random, files)
- **Outfit picker:** picks a random outfit from your tops, bottoms and shoes, depending on the weather. (lists, random, conditionals)
- **Movie night:** friends vote on movies; shows the winner. (dict, loops, input)
- **Song lyrics stats:** read lyrics from a file; count lines, words and the most used word. (files, dict, loops)