

DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

A18EA
Revision 13

2T-1A
2T-1A-1
2T-1A-2

November 10, 2020

TYPE CERTIFICATE DATA SHEET A18EA

This data sheet which is a part of Type Certificate No. A18EA prescribes conditions and limitations under which the product for which the Type Certificate was issued meets the airworthiness requirements of the Federal Aviation Regulations.

Type Certificate Holder: WACO Classic Aircraft Corporation
15955 S. Airport Road
Battle Creek, Michigan 49015

Type Certificate Ownership Record:

A18EA Issued to Windward Aviation, Inc. on January 14, 1972

Reissued to Windward Aviation, Inc. on February 17, 1972

Reissued to Great Lakes Aircraft Company on September 5, 1972 to add
Models 2T-1A-1 and 2T-1A-2.

Reissued to Great Lakes Aircraft Company (Russel Dean Franklin, Jr.) on September
6, 1979

Great Lakes Aircraft Company (Russel Dean Franklin, Jr) transferred ownership of
Type Certificate A18EA to Chaparral Motors, Inc. on January 17, 1989.

Chaparral Motors, Inc. (John Duncan) changes to name and address on September 27,
2000.

Great Lakes Aircraft Company, LLC (John Duncan) transferred ownership of Type
Certificate A18EA to Waco Classic Aircraft Corporation on October 21, 2011.

I - Model 2T-1A, 1 or 2 POLB, Approved 1/14/72

Engine	American Cirrus Mark III
Fuel	73 minimum octane aviation gas
Engine limits	Takeoff 2100 r.p.m. (100 hp.) Maximum Continuous 2100 r.p.m. (100 hp.)
Propeller and propeller limits	Fixed pitch wood or adjustable metal (Hamilton Standard 7020 hub, 25V2 blades) See NOTE 4
Airspeed limits (CAS)	Maximum speed (S.L.) 100 m.p.h.. (95.5 knots) Landing speed 40 m.p.h. (34.8 knots) Cruising speed 90 m.p.h. (78.2 knots)

Page No.	1	2	3	4	5	6
Rev No.	12	11	11	13	12	13

M.A.C.	45.75 in. (L.E. of MAC is 10 in. forward of leading edge of lower wing)			
Maximum weight	1618 lb.			
Minimum Crew	1 (pilot)			
No. of seats	Two			
Maximum baggage	13 lb. as 2-place 200 lb. as 1-place (Pay load includes 2 parachutes, 20 lb. each)			
Fuel capacity	26 gal. (+60.5)			
Oil capacity	8 qt. (+22.5)			
Control surface movements	Aileron	($\pm 1^\circ$)	Up 24°	Down 22°
	Stabilizer	($\pm 1/2^\circ$)	Up 7-1/4°	Up 1/4°
	Elevator	($\pm 1^\circ$)	Up 21°	Down 29°
	Rudder	($\pm 1^\circ$)	Left 35°	Right 35°
Serial Nos. eligible	0501 and 0502 See NOTE 5			

II - Model 2T-1A-1, 1 or 2 POLB (Acrobatic Category) (See NOTE 6), Approved 12/17/73

Engine	Lycoming O-320-E2A installed per Great Lakes Dwg. 50123; or Lycoming IO-360-B1F6 or AEIO-360-B1G6 installed per Great Lakes Dwg. 50148		
Fuel	Lycoming O-320-E2A, 80/87 minimum grade aviation fuel		
	Lycoming IO-360-B1F6 and AEIO-360-B1G6, 91/96 minimum grade aviation fuel		
Engine limits	Lycoming O-320-E2A		
	Takeoff	2450 r.p.m. (140 hp.)	
	Maximum Continuous	2450 r.p.m. (140 hp.)	
	Lycoming IO-360-B1F6 and AEIO-360-B1G6		
	Takeoff	2700 r.p.m. (180 hp.)	
	Maximum continuous	2700 r.p.m. (180 hp.)	
Propeller and propeller limits	Lycoming O-320-E2A		
	McCauley 1C160-EGM 7654		
	Diameter: Not over 76 in., not under 74.5 in.		
	Static r.p.m. at maximum permissible throttle setting:		
	Not over 2350 r.p.m., not under 2250 r.p.m.		
	No additional tolerance permitted.		
	Lycoming IO-360-B1F6 and AEIO-360-B1G6,		
	(a)	Hartzell HC-C2YK-4F/FC7666A-2	
		Diameter: 74.0 in.	
		No reduction allowed	
		Pitch settings at 30 in. sta.:	
		low 12.5°, high 26.8°	
	(b)	Hartzell Spinner P/N 835-41	
	(c)	Hartzell Hydraulic Governor No. F6-31	

Airspeed limits (CAS)	<u>Landplane</u> Never exceed 142 m.p.h. (124 knots) Max. structural cruise 120 m.p.h. (105 knots) Maneuvering 120 m.p.h. (105 knots)
M.A.C.	46.0 in. (L.E. of MAC is Sta. 9.0)
C.G. Range	(15.7) at 1600 lb. or less (18.9 to 23.0) at 1750 lb. Straight line variation between points given
Empty Wt. C.G.	None
Maximum weight	1750 lb.
No. of seats	2 (1 at 27.5, 1 at 61.5)
Maximum baggage	40 lb. (+92.0)
Fuel capacity	27.4 gal. (+26.7 gal. usable, one 26.0 gal. tank in top wing at +13.0 and one 1.4 gal. header tank in fuselage at +5.0). (Lycoming IO-360-B1F6 and AEIO-360-B1G6) See NOTE 1 for data on unusable fuel 26 gal. (26.0 gal. usable, one 26 gal. tank in top wing at +13.0) (Lycoming O-320-E2A) See NOTE 1 for data on unusable fuel
Oil capacity	8 qt. (-24.0) (4 qt. usable) Lycoming IO-360-B1F6 and AEIO-360-B1G6 8 qt. (-24.0) (6 qt. usable) Lycoming O-320-E2A See NOTE 1 for data on oil system
Control surface movements	Aileron (±1°) Up 24° Down 22° for both 2-aileron and 4-aileron configuration Stabilizer (±1/2°) Up 7-1/4° Up 1/4° Elevator (±1°) Up 21° Down 29° Rudder (±1°) Left 35° Right 35°
Serial Nos. eligible	0503 and 0699 See NOTE 5
<u>III - Model 2T-1A-2, 1 or 2 POLB (Acrobatic Category) (See NOTE 6) Approved 7/25/74</u>	
Engine	Lycoming IO-360-B1F6 or AEIO-360-B1G6 installed per Great Lakes Dwg. 50148 or Lycoming O-320-E2A installed per Great Lakes Dwg. 50123
Fuel	Lycoming IO-360-B1F6 and AEIO-360-B1G6, 91/96 minimum grade aviation fuel Lycoming O-320-E2A, 80/87 minimum grade aviation fuel
Engine limits	Lycoming IO-360-B1F6 and AEIO-360-B1G6 Takeoff 2700 r.p.m. (180 hp.) Maximum Continuous 2700 r.p.m. (180 hp.) Lycoming O-320-E2A Takeoff 2450 r.p.m. (140 hp.) Maximum continuous 2450 r.p.m. (140 hp.)

Propeller and
propeller limits

Lycoming IO-360-B1F6 and AEIO-360-B1G6,
(a) Hartzell HC-C2YK-4F/FC7666A-2
Diameter: 74.0 in.
No reduction allowed
Pitch settings at 30 in. sta.:
low 12.5°, high 26.8°
Hartzell Spinner P/N 835-41
Hartzell Hydraulic Governor No. F6-31 or Hartzell Hydraulic Governor No. S-4-5
(b) MT Propeller Model MTV-15-B-C/C-188-34
Diameter 188 cm (74 in) +/- .5 cm (.2 in)
Pitch Settings at 70.5 cm (27.75 in) sta.
Low 9° +/- .2°, High 34° +/- 1°
MT Spinner Assembly Part Number P-277-B
Hartzell Hydraulic Governor No. S-4-5
(c) MT Propeller Model MTV-9-B-C/C188-18b (See NOTE 7)
Diameter 188 cm (74 in) +0cm, -5cm
Pitch Settings at 70.5 cm (27.75 in) sta.
Low 9° +/- .2° High 30° +/- 1°
MT Spinner Assembly Part Number P-208-C
Hartzell Hydraulic Governor No. S-4-5

Lycoming O-320-E2A
McCauley 1C160-EGM 7654
Diameter: Not over 76 in., not under 74-5 in.
Static r.p.m. at maximum permissible throttle setting:
Not over 2350 r.p.m., not under 2250 r.p.m.
No additional tolerance permitted.

Airspeed limits

Landplane

Never exceed 153 m.p.h. (133 knots)
Max. structural cruise 120 m.p.h. (105 knots)
Maneuvering 120 m.p.h. (105 knots)

C. G. range

(+15.7) at 1600 lb. or less
(+20.0) to (+23.8) at 1800 lb.
Straight line variation between points given

Empty Wt. C.G.

None

Maximum weight

1800 lb.

No. of seats

2 (1 at 27.5, 1 at 61.5)

Maximum baggage

(a) 40 lb. (+92.0) Serial No. 701 to 1199
(b) 10 lb (+84.0) Serial No. 1200 and up

Fuel capacity

27.4 gal. (26.7 gal. usable, one 26.0 gal. tank in top wing at +13.0
and one 1.4 gal. header tank in fuselage at +5.0). (Lycoming IO- 360-B1F6
and AEIO-360-B1G6) See NOTE 1 for data on unusable fuel

26 gal. (26.0 gal. usable, one 26 gal. tank in top wing at +13.0)
(Lycoming O-320-E2A) See NOTE 1 for data on unusable fuel

Oil capacity

8 qt. (-24.0) (4 qt. usable)
Lycoming IO-360-B1F6 and AEIO-360-B1G6
See NOTE 1 for data on oil system 8 qt. (-24.0)
(6 qt. usable (Lycoming O-320-E2A)

Control surface movements

Aileron	(±1°)	Up	24°	Down	22°
Stabilizer	(±1/2°)	Up	7-1/4°	Up	1/4°
Elevator	(±1°)	Up	21°	Down	29°
Rudder	(±1°)	Left	35°	Right	35°

Serial Nos. eligible 0701 and up

Data Pertinent to all Models

Datum Fuselage Sta. (00) is center of most forward lateral fuselage tube.
A pin is located on the lower side of landing gear streamline tube
to indicate datum.

Leveling means Upper Longerons at cockpit

Certification basis Aeronautics Bulletin No. 7-A dated October 1, 1934; FAR 23 dated
February 1, 1967, Amendments 23-1 through 23-7 for powerplant
installation; Type Certificate A18EA issued January 14, 1972. Great
Lakes Company obtained Exemption No. 1163 which granted an
exemption from Section 21.17 of the FAR to permit the issuance of
the Type Certificate incorporating the type design portion of ATC-228.

Production basis Production Certificate Number 328CE

Equipment The basic required equipment as prescribed in the applicable airworthiness
regulations (see Certification Basis) must be installed in the aircraft for
certification.

In addition, the following items of equipment are required:

1. FAA approved Airplane Flight Manual as follows:
 - a. Serial Nos. 0501 and 0502, approval date July 13, 1973, or
later FAA approved revision as required by STC SA941CE.
 - b. Serial Nos. 0503 through 0699; approval date Nov. 9, 1973,
or later FAA approved revision.
 - c. Serial Nos. 0701 through 1199; approval date July 25, 1974, or
later FAA approved revision.
 - d. Serial Nos. 1200 and up; approval date March 20, 2014 or later FAA approved
revision

NOTE 1. Current weight and balance report together with list of equipment included in certificated empty weight must
be provided for each aircraft at time of original certification. The certificated empty weight and
corresponding center of gravity location must include unusable fuel of 0.0 lb. at (+13.0) and system oil of 1.0
lb. at (-4.0) for airplanes with Lycoming O-320-E2A engines. Certificated empty weight and corresponding
center of gravity location must include unusable fuel of 4.0 lb. at (+5.0) and system oil of 1.0 lb. at (-4.0) for
airplanes with Lycoming IO-360-B1F6 and AEIO-360-B1G6 engines.

NOTE 2. All placards specified in FAA Approved Airplane Flight Manual must be displayed in the airplane.

NOTE 3. Reserved.

NOTE 4. Reference CAR 04.61 Dated May 31, 1938, to determine propeller diameter and static r.p.m. limits.

NOTE 5. Serial Nos. 0501 and 0502 are modified by installation of the Lycoming O-320-E2A engine per STC
SA941CE; and Cleveland 20-80 wheels and brakes, Cleveland IO-5 master cylinders, and Scott tail wheel
per STC SA942CE. These airplanes eligible for certification as 2T- 1A-1 airplanes when Identification Plate
00120-1 and FAA Approved Airplane Flight Manual for the 2T-1A-1 dated November 9, 1973 with Rev. "B"
dated April 22, 1975, or later FAA approved revision are installed.

NOTE 6. The certification basis for these airplanes does not contain operating categories, i.e., normal, utility or acrobatic, as listed in current certification regulations. However, since certain of these models were designed to perform and have demonstrated the capability to perform the acrobatic maneuvers listed in the approved airplane flight manual plus those maneuvers not exceeding the load factors listed below, the words "acrobatic category" are included so that those persons concerned with these airplanes understand their capacity in terms of current practices. Maneuvering load factors are as follows:

- | | | |
|----|---------|----------------|
| A. | 2T-1A-1 | +5.05 to -2.05 |
| B. | 2T-1A-2 | +5.40 to -4.00 |

For the above reasons, the airworthiness certificate for 2T-1A-1 and 2T-1A-2 airplanes are to be issued in the acrobatic category.

| NOTE 7. Installation of MTV-9-B-C/C188-18b propeller limited to Serial Numbers 1200 and up.

...END...