

```
(kali@kali)-[~]
```

```
$ ls
```

```
Desktop      Music          nmap-assignment Public      Videos
Documents    nikto_results.txt.txt  nmap_recon.txt  sample.txt  wapiti_report.txt
Downloads    nikto_scan.txt.txt    nmap_web.txt    Templates
fruits.txt   nikto_testphp_report.html.htm Pictures
gobuster_output.txt  nikto_web.txt.txt    Projects        testphp_tuned.txt.txt
                                                username.txt
```

```
(kali@kali)-[~]
```

```
$ cat >username.txt
```

```
dinesh
kiran
admin
kali
^C
```

```
(kali@kali)-[~]
```

```
$ cat >password.txt
```

```
dinesh@123
kiran@123
admin@123
kali
^C
```

```
(kali@kali)-[~]
```

```
$ hydra -h
```

Hydra v9.7 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in military or secret service organizations, or for illegal purposes (this is non-binding, these *** ignore laws and ethics anyway).

Syntax: hydra [[[-l LOGIN|-L FILE] [-p PASS|-P FILE]] | [-C FILE]] [-e nsr] [-o FILE] [-t TASKS] [-M FILE] [-T TASKS]] [-w TIME] [-W TIME] [-f] [-s PORT] [-x MIN:MAX:CHARSET] [-c TIME] [-ISOUvVd46] [-m MODULE_OPT] [service://server[:PORT][:OPT]]

Options:

- R restore a previous aborted/crashed session
- I ignore an existing restore file (don't wait 10 seconds)
- S perform an SSL connect
- s PORT if the service is on a different default port, define it here
- l LOGIN or -L FILE login with LOGIN name, or load several logins from FILE
- p PASS or -P FILE try password PASS, or load several passwords from FILE
- x MIN:MAX:CHARSET password bruteforce generation, type "-x -h" to get help
- y disable use of symbols in bruteforce, see above
- r use a non-random shuffling method for option -x
- e nsr try "n" null password, "s" login as pass and/or "n" reversed login
- u loop around users, not passwords (effective! implied with -x)
- C FILE colon separated "login:pass" format, instead of -L/-P options
- M FILE list of servers to attack, one entry per line, ':' to specify port
- D XoFY Divide wordlist into Y segments and use the Xth segment.
- o FILE write found login/password pairs to FILE instead of stdout

Session Actions Edit View Help

```
-m OPT    options specific for a module, see -U output for information
-h        more command line options (COMPLETE HELP)
server    the target: DNS, IP or 192.168.0.0/24 (this OR the -M option)
service   the service to crack (see below for supported protocols)
OPT       some service modules support additional input (-U for module help)
```

wordlist_report.txt

Supported services: adam6500 asterisk cisco cisco-enable cobaltstrike cvs firebird ftp[s] http[s]-{head|get|post} h
tftp[s]-{get|post}-form http-proxy http-proxy-urlenum icq imap[s] irc ldap2[s] ldap3[-{cram|digest}md5][s] memcached
mongodb mssql mysql nntp oracle-listener oracle-sid pcanywhere pcnfs pop3[s] postgres radmin2 rdp redis rexec rlog
in rpcap rsh rtsp s7-300 sip smb smb2 smtp[s] smtp-enum snmp socks5 ssh sshkey svn teamspeak telnet[s] vmauthd vnc
xmpp

Hydra is a tool to guess/crack valid login/password pairs.
Licensed under AGPL v3.0. The newest version is always available at;
<https://github.com/vanhauser-thc/thc-hydra>
Please don't use in military or secret service organizations, or for illegal
purposes. (This is a wish and non-binding - most such people do not care about
laws and ethics anyway - and tell themselves they are one of the good ones.)
These services were not compiled in: afp ncp oracle sapr3.

Use HYDRA_PROXY_HTTP or HYDRA_PROXY environment variables for a proxy setup.
E.g. % export HYDRA_PROXY=socks5://l:p@127.0.0.1:9150 (or: socks4:// connect://)
% export HYDRA_PROXY=connect_and_socks_proxylist.txt (up to 64 entries)
% export HYDRA_PROXY_HTTP=http://login:pass@proxy:8080
% export HYDRA_PROXY_HTTP=proxylist.txt (up to 64 entries)

Examples:

```
hydra -l user -P passlist.txt ftp://192.168.0.1
hydra -L userlist.txt -p defaultpw imap://192.168.0.1/PLAIN
hydra -C defaults.txt -6 pop3s://[2001:db8::1]:143/TLS:DIGEST-MD5
hydra -l admin -p password ftp://[192.168.0.0/24]/
hydra -L logins.txt -P pws.txt -M targets.txt ssh
```

(kali@kali)-[~]

\$ nmap 10.0.2.15/24

Starting Nmap 7.99 (<https://nmap.org>) at 2026-08-19 13:52 -0400

Nmap scan report for 10.0.2.2

Host is up (0.0015s latency).

Not shown: 993 filtered tcp ports (no-response)

PORT STATE SERVICE

135/tcp open msrpc

445/tcp open microsoft-ds

902/tcp open iss-realsecure

912/tcp open apex-mesh

3000/tcp open ppp

3580/tcp open nati-svrloc

5000/tcp open upnp

MAC Address: 52:54:00:12:35:00 (QEMU virtual NIC)

Nmap scan report for 10.0.2.3

Host is up (0.00047s latency).

Session Actions Edit View Help

Not shown: 999 filtered tcp ports (net-unreach)

PORT STATE SERVICE

53/tcp open domain

MAC Address: 52:54:00:12:35:00 (QEMU virtual NIC)

(kali@kali)-[~]

\$ hydra -l username.txt -p password.txt -f ssh://10.0.2.1 -v

Hydra v9.7 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in military or secret service organizations, or for illegal purposes (this is non-binding, these *** ignore laws and ethics anyway).

Hydra (https://github.com/vanhauser-thc/thc-hydra) starting at 2026-08-19 13:54:59

[WARNING] Many SSH configurations limit the number of parallel tasks, it is recommended to reduce the tasks: use -t 4

[DATA] max 1 task per 1 server, overall 1 task, 1 login try (l:1/p:1), ~1 try per task

[DATA] attacking ssh://10.0.2.1:22/

[VERBOSE] Resolving addresses ... [VERBOSE] resolving done

[INFO] Testing if password authentication is supported by ssh://username.txt@10.0.2.1:22

[ERROR] could not connect to ssh://10.0.2.1:22 - No route to host

(kali@kali)-[~]

\$ hydra -l username.txt -p password.txt -f ssh://10.0.2.15 -v

Hydra v9.7 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in military or secret service organizations, or for illegal purposes (this is non-binding, these *** ignore laws and ethics anyway).

Hydra (https://github.com/vanhauser-thc/thc-hydra) starting at 2026-08-19 13:59:24

[WARNING] Many SSH configurations limit the number of parallel tasks, it is recommended to reduce the tasks: use -t 4

[DATA] max 1 task per 1 server, overall 1 task, 1 login try (l:1/p:1), ~1 try per task

[DATA] attacking ssh://10.0.2.15:22/

[VERBOSE] Resolving addresses ... [VERBOSE] resolving done

[INFO] Testing if password authentication is supported by ssh://username.txt@10.0.2.15:22

[ERROR] could not connect to ssh://10.0.2.15:22 - Connection refused

(kali@kali)-[~]

\$ hydra -l kali -p password.txt -f ssh://10.0.2.15 -v

Hydra v9.7 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in military or secret service organizations, or for illegal purposes (this is non-binding, these *** ignore laws and ethics anyway).

Hydra (https://github.com/vanhauser-thc/thc-hydra) starting at 2026-08-19 14:00:31

[WARNING] Many SSH configurations limit the number of parallel tasks, it is recommended to reduce the tasks: use -t 4

[DATA] max 1 task per 1 server, overall 1 task, 1 login try (l:1/p:1), ~1 try per task

[DATA] attacking ssh://10.0.2.15:22/

[VERBOSE] Resolving addresses ... [VERBOSE] resolving done

[INFO] Testing if password authentication is supported by ssh://kali@10.0.2.15:22

[ERROR] could not connect to ssh://10.0.2.15:22 - Connection refused

(kali@kali)-[~]

\$