

Display Lists



Oregon State
University

Mike Bailey

mjb@cs.oregonstate.edu



This work is licensed under a [Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License](https://creativecommons.org/licenses/by-nc-nd/4.0/)



Oregon State
University

Computer Graphics

Drawing a Sphere – Notice a lot of time-consuming Trig Function Calls!

```

void
Sphere( float radius, int slices, int stacks )
{
    struct point top, bot;      // top, bottom points
    struct point *p;
    NumLngs = slices;
    NumLats = stacks;

    Pts = new struct point[ NumLngs * NumLats ];
    for( int ilat = 0; ilat < NumLats; ilat++ )
    {
        float lat = M_PI/2. + M_PI * (float)ilat / (float)(NumLats-1);
        float xz = cos( lat );
        float y = sin( lat );
        for( int ilng = 0; ilng < NumLngs; ilng++ )
        {
            float lng = -M_PI + 2 * M_PI * (float)ilng / (float)(NumLngs-1);
            float x = xz * cos( lng );
            float z = -xz * sin( lng );
            p = PtsPointer( ilat, ilng );
            p->x = radius * x;
            p->y = radius * y;
            p->z = radius * z;
            p->nx = x;
            p->ny = y;
            p->nz = z;
            p->s = ( lng + M_PI ) / ( 2.*M_PI );
            p->t = ( lat + M_PI/2. ) / M_PI;
        }
    }
}

```

```

top.x = 0.;    top.y = radius;    top.z = 0.;
top.nx = 0.;   top.ny = 1.;       top.nz = 0.;
top.s = 0.;    top.t = 1.;
bot.x = 0.;    bot.y = -radius;    bot.z = 0.;
bot.nx = 0.;   bot.ny = -1.;       bot.nz = 0.;
bot.s = 0.;    bot.t = 0.;

```

```

glBegin( GL_QUADS );
for( int ilng = 0; ilng < NumLngs-1; ilng++ )
{
    p = PtsPointer( NumLats-1, ilng );
    DrawPoint( p );
    p = PtsPointer( NumLats-2, ilng );
    DrawPoint( p );
    p = PtsPointer( NumLats-2, ilng+1 );
    DrawPoint( p );
    p = PtsPointer( NumLats-1, ilng+1 );
    DrawPoint( p );
}
glEnd( );

```

```

glBegin( GL_QUADS );
for( int ilng = 0; ilng < NumLngs-1; ilng++ )
{
    p = PtsPointer( 0, ilng );
    DrawPoint( p );
    p = PtsPointer( 0, ilng+1 );
    DrawPoint( p );
    p = PtsPointer( 1, ilng+1 );
    DrawPoint( p );
    p = PtsPointer( 1, ilng );
    DrawPoint( p );
}
glEnd( );

```



```
glBegin( GL_QUADS );  
for( int ilat = 2; ilat < NumLats-1; ilat++ )  
{  
    for( int ilng = 0; ilng < NumLngs-1; ilng++ )  
    {  
        p = PtsPointer( ilat-1, ilng );  
        DrawPoint( p );  
        p = PtsPointer( ilat-1, ilng+1 );  
        DrawPoint( p );  
        p = PtsPointer( ilat, ilng+1 );  
        DrawPoint( p );  
        p = PtsPointer( ilat, ilng );  
        DrawPoint( p );  
    }  
}  
glEnd( );
```



You don't want to execute all that code every time you want to redraw the scene, so draw it once, store the numbers in GPU memory, and call them back up later

The solution is to incur the sphere-creation overhead *once*, and whenever the sphere needs to be re-drawn, just draw the saved numbers, not the equations. This is a **Display List**.

1 How many unique, unused, consecutive DL identifiers to give back to you

2 The ID of the first DL in the unique, unused list

Creating the Display List in InitLists():

// a global GLuint variable:

SphereList = glGenLists(1);
glNewList(SphereList, GL_COMPILE);

3 Open up a display list in (GPU) memory

Sphere(5., 30, 30);

4 The coordinates, etc. end up in memory instead of being sent to the display

glEndList();

5 Stop storing the numbers in the DL

Calling up the Display List in Display():

glCallList(SphereList);

6 Pull all the coordinates, etc. from memory, just as if the code to generate them had been executed here

