

lecture00_python_tutorial_exercises

September 13, 2016

```
In [ ]: #-----#
        # PYTHON EXERCISES
        # September 12, 2016 #
        # EECS 445: Machine Learning #
        # Author: Valliappa Chockalingam (valli@umich.edu)
        # -----#
```

1 Question 1: Numbers and Data Structures

- Example: If we list all the natural numbers below 10 that are multiples of 3 or 5, we get 3, 5, 6 and 9. The sum of these multiples is 23.
- **Question:** Find the sum of all the multiples of 3 or 5 below 1000 in 3 ways.
- **Hint 1:** Loop through all the possible numbers, i.e., $x \in \mathbb{N} \wedge x < 1000$ and simply add up the multiples as you go through them. Use two loops first and then try making your code more concise.
- **Bonus:** Use the inclusion-exclusion principle. Write a function that calculates the sum of the first n numbers in an arithmetic series. Hint: $S_n = \frac{n}{2}(u_1 + u_n) = \frac{n}{2}(2u_1 + (n - 1) \cdot d)$

```
In [415]: # Open Ended, No Skeleton Code for this question.
```

2 Question 2: Strings and Data Structures

Note: You are free to use any functions and libraries that come with Python. The aim is not to necessarily implement code from scratch, but to get familiar with Python (specifically the syntax and data structures) and, to some extent, write concise readable working code.

- ***** (a):** Given a non-empty string like “Code” return a string like “CCoCodCode”. *******
- ***** (b):** Given strings a, b and c, write a function that will replace all occurrences of a in b with c. *******
- ***** (c):** Given a string s that has been Caesar enciphered with a numeric shift n. Return the deciphered string. ******* For example, s = “vjku ku c eqfg” and n = -2, returns “this is a code”
Note: You can assume the string is all in lowercase without any special characters.

- ***** (d):** Given a string *s*, return whether *s* is a palindrome, i.e, it is spelt the same when read from either direction. ******* Note: Ignore case, special characters and spacing.
- ***** (e):** Using the higher order function `filter()`, define a function `filter_long_words()` that takes a list of words and an integer *n* and returns the list of words that are longer than *n* (in the same order). *******
- ***** (f):** Given a string *s* and a number *n*, return a list of size *n* consisting of tuples with two elements, the first being the correct string in the look-and-say-sequence and the second being a dictionary of character: count pairs that is sorted (Hint: Use Ordered Dictionaries and `sorted()`). ******* For example, if *s* = "1" and *n* = 5, the look-and-say-sequence is as follows:

```
1 ("1", {"1" : 1}) 11 ("11", {"1" : 2}) 21 ("21", {"1" : 1, "2" : 1}) 1211 ("1211", {"1" : 3, "2" : 1}) 111221 ("111221", {"1" : 4, "2" : 2}) correct output: [("1", {"1" : 1}), ("11", {"1" : 2}), ("21", {"1" : 1, "2" : 1}), ("1211", {"1" : 3, "2" : 1}), ("111221", {"1" : 4, "2" : 2})]
```

```
In [64]: # Implement part (a) below
```

```
def string_repeater(s):
    pass
```

```
# Implement part (b) below
```

```
def string_occurrence_remover(a, b, c):
    pass
```

```
# Implement part (c) below
```

```
def caesar_decipher(s, n):
    pass
```

```
# Implement part (d) below
```

```
def is_palindrome(s):
    pass
```

```
# Implement part (e) below
```

```
def filter_long_words(l, n):
    pass
```

```
# Implement part (f) below
```

```
def look_and_say(s, n):
    pass
```

```
In [67]: # Simple Tests for part (a)
```

```
assert(string_repeater("Code") == "CCoCodCode")
```

```
assert(string_repeater("EECS445") == "EEEECEECSEECs4EECS44EECS445")
```

```
# Simple Tests for part (b)
```

```
assert(string_occurrence_remover("Boring", "PythonIsBoring", "Fun") == "Pyt
```

```
assert(string_occurrence_remover("12", "Today is September 12 and 12 is my
    "Today is September 9 and 9 is my favorite number.")
```

```

# Simple Tests for part (c)
assert(caesar_decipher("vjku ku eqfg", -2) == "this is code")
assert(caesar_decipher("h khjd bnlotdqr", 1) == "i like computers")

# Simple Tests for part (d)
assert(is_palindrome("Rats live on no evil star."))
assert(is_palindrome("On a clover, if alive, erupts a vast pure evil; a fi
assert(not is_palindrome("Hello, this is Jupyter Notebook speaking."))
assert(not is_palindrome("I am currently in a hands-on lecture."))

# Simple Tests for part (e)
assert(filter_long_words(['a', '', '0', 'a0', 'a0b02030', 'ee', 'cs', 'ee
assert(filter_long_words(['1', '2'], 0) == ['1', '2'])

# Simple Test for part (f)
from collections import OrderedDict
assert(look_and_say("aabbcc", 5) == [('aabbcc', OrderedDict([('a', 2), ('b', 2), ('c', 2)])),
('2a2b2c', OrderedDict([('2', 3), ('a', 1), ('b', 1), ('c', 1)])),
('121a121b121c',
OrderedDict([('1', 6), ('2', 3), ('a', 1), ('b', 1), ('c', 1)])),
('1112111a1112111b1112111c',
OrderedDict([('1', 18), ('2', 3), ('a', 1), ('b', 1), ('c', 1)])),
('3112311a3112311b3112311c',
OrderedDict([('1', 12), ('2', 3), ('3', 6), ('a', 1), ('b', 1), ('c', 1)]))

```

3 Question 3: Classes and Interactive I/O

*** (a) Define a class which has at least two methods, getString: to get a string from console input and printString: to print the string in upper case. Also write a simple test to check the functionality class methods. ***

In [416]: # Open Ended. No Skeleton Code here.

*** (b) Write a program able to play the “Guess the number”-game, where the number to be guessed is randomly chosen between 1 and 20.***

(Source: <http://inventwithpython.com>) This is how it should work when run in a terminal:

```

Hello! What is your name?
Valli
Well, Valli, I am thinking of a number between 1 and 20.
Take a guess.
10
Your guess is too low.
Take a guess.
15
Your guess is too low.
Take a guess.

```

18

Good job, Valli! You guessed my number in 3 guesses!

```
In [102]: import random
          class GuessTheNumber(object):
              # Create a constructor here (__init__ function) that takes two numbers
              # the range that guesses can take. Save these in variable min_guess and max_guess
              # initialize a Boolean called incorrect to be true. (Note: Python booleans are capitalized)

              def play(self):
                  # Change the following line of code to get input from the user and store it in a variable
                  print("Hello! What is your name? ")
                  name = input()
                  print("Well, " + name + ", I am thinking of a number between " +
                        str(self.min_guess) + " and " + str(self.max_guess) + ".\n")
                  answer = random.randrange(self.min_guess, self.max_guess + 1)
                  # Write the main loop to collect guesses and check whether they are correct
                  # Additionally, if the guess is out of range or input is unexpected,
                  # simply print an error message and break from the loop.

In [ ]: # Test out your game!
        g = GuessTheNumber(1, 20)
        g.play()
```

4 Question 4: Pandas and Data Exploration

```
In [6]: # Generate some Data for analysis
        from sklearn.datasets import make_classification
        X, y = make_classification(1000, n_features=5, n_informative=2,
                                   n_redundant=2, n_classes=2, random_state=0)

In [417]: # (a) Get a glimpse of the data by making a Pandas DataFrame from the data
          # few rows.

In [418]: # (b) Plot a boxplot of each column to visualize the distribution of the data

In [419]: # (c) Try using the describe() function of the DataFrame.

In [420]: # (d) Install Seaborn if it is not already installed and import it below.

In [421]: # (e) Now try Seaborn's correlation plot (Heatmap).

In [422]: # (Optional) Using the first 70% of the data as a training set and the last 30%
          # as a test set, fit a logistic regression model to the training set
          # and see how well it performs. You will be certainly able to do this at the end of the course.
```

5 Question 5: Numpy Exercises

```
In [423]: # (a) Write a function that takes in a tuple and a string that can either
          # be 'zero', 'one' or 'gaussian' and correspondingly return a NumPy array
          # assume sampling with mean = 0, std = 1.
```

```

In [424]: # (b) Write a function that returns a n x n identity matrix with n as a p
In [425]: # (c) Write a function that normalizes a matrix to [0, 1] and returns the
In [426]: # (d) Write code that creates a NumPy array and makes it immutable.
In [427]: # (e) Write a function that finds the closest value to a given scalar s.
In [428]: # (f) Write a function that subtracts the mean of each row from a matrix
In [429]: # (g) Write a function that sorts an array by the nth column and returns

```

6 Question 6: Numpy + First ML algorithm!

```

In [3]: # (a) Write a function that implements Ordinary Least Squares given an input
        # We will go over the method in the forthcoming lecture, but the equation is
        # https://en.wikipedia.org/wiki/Linear\_regression#Estimation\_methods
        # Note: Use NumPy here, but do NOT make use of library functions that do the
In [ ]:
In [370]: from sklearn.datasets import make_regression
        X, y = make_regression(1000, n_features=1, noise=20, random_state=0)
In [371]: # (b) Run your function on the above data and plot the data as well as the
        # generated by your classifier using matplotlib.
In [ ]:

```