

1-

Zone Records - bea.dual.edu

Zone Editor

15 records

Name	Type	Status	TTL	Data
@	A	Active	60	192.168.100.100
dns	A	Active	60	192.168.22.2
mail	A	Active	60	15.15.15.15
web	A	Active	60	192.168.100.100
@	MX	Active	60	15 mail.bea.dual.edu.
@	NS	Active	60	dns.bea.dual.edu.

Showing 1 to 6 of 6 entries

2-

```
daw2fpddaw@a24eq113: ~/Documentos/dns-webadmin/dns-we
root@c2a7cbf0d6d0:/# nslookup bea.dual.edu
;; Got recursion not available from 127.0.0.11
Server:      127.0.0.11
Address:     127.0.0.11#53

Name:   bea.dual.edu
Address: 192.168.100.100
;; Got recursion not available from 127.0.0.11
root@c2a7cbf0d6d0:/#
```

3-

```
web.bea.dual.edu has address 192.168.100.100
root@c2a7cbf0d6d0:/# host web.bea.dual.edu
web.bea.dual.edu has address 192.168.100.100
root@c2a7cbf0d6d0:/#
```

4-

```
root@c2a7cbf0d6d0:/# host -t MX bea.dual.edu
bea.dual.edu mail is handled by 15 mail.bea.dual.edu.
root@c2a7cbf0d6d0:/# host mail.bea.dual.edu
mail.bea.dual.edu has address 15.15.15.15
root@c2a7cbf0d6d0:/#
```

5 -

```
root@c2a7cbf0d6d0:/# dig NS bea.dual.edu

; <<>> DiG 9.18.33-1~deb12u2-Debian <<>> NS bea.dual.edu
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 26896
;; flags: qr aa rd; QUERY: 1, ANSWER: 1, AUTHORITY: 0, ADDITIONAL: 2
;; WARNING: recursion requested but not available

;; OPT PSEUDOSECTION:
; EDNS: version: 0, flags:; udp: 1232
;; QUESTION SECTION:
;bea.dual.edu.                IN      NS

;; ANSWER SECTION:
bea.dual.edu.                 60      IN      NS      dns.bea.dual.edu.

;; ADDITIONAL SECTION:
dns.bea.dual.edu.            60      IN      A        192.168.22.2

;; Query time: 0 msec
;; SERVER: 127.0.0.11#53(127.0.0.11) (UDP)
;; WHEN: Fri Mar 07 09:55:31 UTC 2025
;; MSG SIZE rcvd: 75
```