

# Data Science for Economists

## Lecture 5: Data cleaning & wrangling: (1) Tidyverse

---

Grant McDermott

University of Oregon | EC 607

# Table of contents

1. Prologue
2. Tidyverse basics
3. Data wrangling with dplyr
  - filter
  - arrange
  - select
  - mutate
  - summarise
  - joins
4. Data tidying with tidyr
  - pivot\_longer / pivot\_wider
  - separate
  - unite
5. Summary

# Prologue

---

# What is "tidy" data?

## Resources:

- [Vignette](#) (from the **tidyr** package)
- [Original paper](#) (Hadley Wickham, 2014 JSS)

# What is "tidy" data?

## Resources:

- [Vignette](#) (from the **tidyr** package)
- [Original paper](#) (Hadley Wickham, 2014 JSS)

## Key points:

1. Each variable forms a column.
2. Each observation forms a row.
3. Each type of observational unit forms a table.

# What is "tidy" data?

## Resources:

- [Vignette](#) (from the **tidyr** package)
- [Original paper](#) (Hadley Wickham, 2014 JSS)

## Key points:

1. Each variable forms a column.
2. Each observation forms a row.
3. Each type of observational unit forms a table.

Basically, tidy data is more likely to be [long \(i.e. narrow\) format](#) than wide format.

# Checklist

R packages you'll need today

☑ **tidyverse**

☑ **nycflights13**

# Checklist

## R packages you'll need today

☑ **tidyverse**

☑ **nycflights13**

I'll hold off loading these libraries for now. But you can install/update them both with the following command.

```
install.packages(c('tidyverse', 'nycflights13'), repos = 'https://cran.rstudio.com', c
```

**Tip:** If you're on Linux, then I *strongly* recommend installing the pre-compiled binary versions of these packages from **RSPM** instead of CRAN. The exact repo mirror varies by distro (see the link). But on Ubuntu 20.04, for example, you'd use:

```
install.packages(c('tidyverse', 'nycflights13'), repos = 'https://packagemanager.rstu
```



# Tidyverse basics

---

# Tidyverse vs. base R

Much digital ink has been spilled over the "tidyverse vs. base R" debate.

# Tidyverse vs. base R

Much digital ink has been spilled over the "tidyverse vs. base R" debate.

I won't delve into this debate here, because I think the answer is **clear**: We should teach the tidyverse first (or, at least, early).

- The documentation and community support are outstanding.
- Having a consistent philosophy and syntax makes it easier to learn.
- Provides a convenient "front-end" to big data tools that we'll use later in the course.
- For data cleaning, wrangling, and plotting, the tidyverse really is a no-brainer.<sup>1</sup>

<sup>1</sup> I'm also a huge fan of **data.table**. This package will be the subject of our next lecture.

# Tidyverse vs. base R

Much digital ink has been spilled over the "tidyverse vs. base R" debate.

I won't delve into this debate here, because I think the answer is **clear**: We should teach the tidyverse first (or, at least, early).

- The documentation and community support are outstanding.
- Having a consistent philosophy and syntax makes it easier to learn.
- Provides a convenient "front-end" to big data tools that we'll use later in the course.
- For data cleaning, wrangling, and plotting, the tidyverse really is a no-brainer.<sup>1</sup>

**But...** this certainly shouldn't put you off learning base R alternatives.

- Base R is extremely flexible and powerful (and stable).
- There are some things that you'll have to venture outside of the tidyverse for.
- A combination of tidyverse and base R is often the best solution to a problem.
- Excellent base R data manipulation tutorials: [here](#) and [here](#).

<sup>1</sup> I'm also a huge fan of **data.table**. This package will be the subject of our next lecture.

# Tidyverse vs. base R (cont.)

One point of convenience is that there is often a direct correspondence between a tidyverse command and its base R equivalent.

These generally follow a `tidyverse::snake_case` vs `base::period.case` rule. E.g. Compare:

tidyverse	base
<code>?readr::read_csv</code>	<code>?utils::read.csv</code>
<code>?dplyr::if_else</code>	<code>?base::ifelse</code>
<code>?tibble::tibble</code>	<code>?base::data.frame</code>

Etcetera.

If you call up the above examples, you'll see that the tidyverse alternative typically offers some enhancements or other useful options (and sometimes restrictions) over its base counterpart.

# Tidyverse vs. base R (cont.)

One point of convenience is that there is often a direct correspondence between a tidyverse command and its base R equivalent.

These generally follow a `tidyverse::snake_case` vs `base::period.case` rule. E.g. Compare:

tidyverse	base
<code>?readr::read_csv</code>	<code>?utils::read.csv</code>
<code>?dplyr::if_else</code>	<code>?base::ifelse</code>
<code>?tibble::tibble</code>	<code>?base::data.frame</code>

Etcetera.

If you call up the above examples, you'll see that the tidyverse alternative typically offers some enhancements or other useful options (and sometimes restrictions) over its base counterpart.

**Remember:** There are (almost) always multiple ways to achieve a single goal in R.

# Tidyverse packages

Let's load the tidyverse meta-package and check the output.

```
library(tidyverse)
```

```
## — Attaching packages ————— tidyverse 1.3.1 —
```

```
## ✓ ggplot2 3.3.3      ✓ purrr  0.3.4
```

```
## ✓ tibble  3.1.1      ✓ dplyr  1.0.5
```

```
## ✓ tidyr   1.1.3      ✓ stringr 1.4.0
```

```
## ✓ readr   1.4.0      ✓ forcats 0.5.1
```

```
## — Conflicts ————— tidyverse_conflicts() —
```

```
## x dplyr::filter() masks stats::filter()
```

```
## x dplyr::lag()    masks stats::lag()
```

# Tidyverse packages

Let's load the tidyverse meta-package and check the output.

```
library(tidyverse)
```

```
## — Attaching packages ————— tidyverse 1.3.1 —
```

```
## ✓ ggplot2 3.3.3      ✓ purrr  0.3.4
```

```
## ✓ tibble  3.1.1      ✓ dplyr  1.0.5
```

```
## ✓ tidyr   1.1.3      ✓ stringr 1.4.0
```

```
## ✓ readr   1.4.0      ✓ forcats 0.5.1
```

```
## — Conflicts ————— tidyverse_conflicts() —
```

```
## x dplyr::filter() masks stats::filter()
```

```
## x dplyr::lag()     masks stats::lag()
```

We see that we have actually loaded a number of packages (which could also be loaded individually): **ggplot2**, **tibble**, **dplyr**, etc.

- We can also see information about the package versions and some namespace conflicts.



# Tidyverse packages (cont.)

The tidyverse actually comes with a lot more packages than those that are just loaded automatically.<sup>1</sup>

```
tidyverse_packages()
```

```
## [1] "broom"      "cli"        "crayon"     "dbplyr"     "dplyr"
## [6] "forcats"    "ggplot2"    "haven"      "hms"        "httr"
## [11] "jsonlite"   "lubridate"  "magrittr"   "modelr"     "pillar"
## [16] "purrr"      "readr"      "readxl"     "reprex"     "rlang"
## [21] "rstudioapi" "rvest"      "stringr"    "tibble"     "tidyr"
## [26] "xml2"       "tidyverse"
```

We'll use several of these additional packages during the remainder of this course.

- E.g. The **lubridate** package for working with dates and the **rvest** package for webscraping.
- However, bear in mind that these packages will have to be loaded separately.

<sup>1</sup> It also includes a *lot* of dependencies upon installation. This is a matter of some **controversy**.

# Tidyverse packages (cont.)

I hope to cover most of the tidyverse packages over the length of this course.

Today, however, I'm only really going to focus on two packages:

1. **dplyr**
2. **tidyr**

These are the workhorse packages for cleaning and wrangling data. They are thus the ones that you will likely make the most use of (alongside **ggplot2**, which we already met back in Lecture 1).

- Data cleaning and wrangling occupies an inordinate amount of time, no matter where you are in your research career.

# An aside on pipes: %>%

We already learned about pipes in our [lecture](#) on the bash shell. The tidyverse loads its own pipe operator, denoted `%>%`.

I want to reiterate how cool pipes are, and how using them can dramatically improve the experience of reading and writing code. Compare:

*## These next two lines of code do exactly the same thing.*

```
mpg %>% filter(manufacturer="audi") %>% group_by(model) %>% summarise(hwy_mean = mean(hwy))  
summarise(group_by(filter(mpg, manufacturer="audi"), model), hwy_mean = mean(hwy))
```

# An aside on pipes: %>%

We already learned about pipes in our [lecture](#) on the bash shell. The tidyverse loads its own pipe operator, denoted `%>%`.

I want to reiterate how cool pipes are, and how using them can dramatically improve the experience of reading and writing code. Compare:

*## These next two lines of code do exactly the same thing.*

```
mpg %>% filter(manufacturer="audi") %>% group_by(model) %>% summarise(hwy_mean = mean(hwy))  
summarise(group_by(filter(mpg, manufacturer="audi"), model), hwy_mean = mean(hwy))
```

The first line reads from left to right, exactly how I thought of the operations in my head.

- Take this object (`mpg`), do this (`filter`), then do this (`group_by`), etc.

The second line totally inverts this logical order (the final operation comes first!)

- Who wants to read things inside out?

# An aside on pipes: %>% (cont.)

The piped version of the code is even more readable if we write it over several lines. Here it is again and, this time, I'll run it for good measure so you can see the output:

```
mpg %>%  
  filter(manufacturer=="audi") %>%  
  group_by(model) %>%  
  summarise(hwy_mean = mean(hwy))
```

```
## # A tibble: 3 x 2  
##   model      hwy_mean  
##   <chr>      <dbl>  
## 1 a4         28.3  
## 2 a4 quattro  25.8  
## 3 a6 quattro  24
```

Remember: Using vertical space costs nothing and makes for much more readable/writeable code than cramming things horizontally.

# An aside on pipes: %>% (cont.)

The piped version of the code is even more readable if we write it over several lines. Here it is again and, this time, I'll run it for good measure so you can see the output:

```
mpg %>%  
  filter(manufacturer=="audi") %>%  
  group_by(model) %>%  
  summarise(hwy_mean = mean(hwy))
```

```
## # A tibble: 3 x 2  
##   model      hwy_mean  
##   <chr>      <dbl>  
## 1 a4         28.3  
## 2 a4 quattro 25.8  
## 3 a6 quattro 24
```

Remember: Using vertical space costs nothing and makes for much more readable/writeable code than cramming things horizontally.

PS — The pipe is originally from the **magrittr** package ([geddit?](#)), which can do some other cool things if you're inclined to explore.

# A further aside on the base R pipe: |>

The magrittr pipe has proven so successful and popular, that the R core team **recently announced** a "native" pipe would be coming to base R, denoted `▷`.<sup>1</sup> For example:

```
mtcars ▷ subset(cyl=4) ▷ head()  
mtcars ▷ subset(cyl=4) ▷ d ⇒ lm(mpg ~ disp, data = d)
```

<sup>1</sup> That's actually a `|` followed by a `>`. The default font on these slides just makes it look extra fancy.

# A further aside on the base R pipe: |>

The magrittr pipe has proven so successful and popular, that the R core team **recently announced** a "native" pipe would be coming to base R, denoted `|>`.<sup>1</sup> For example:

```
mtcars |> subset(cyl=4) |> head()
mtcars |> subset(cyl=4) |> d => lm(mpg ~ disp, data = d)
```

At the time of writing this native pipe is only available in the **development** version of R. (I'll show an in-class demo.)

This native pipe complements some other new cool features, like support for **"lambda" functions** in R.

- So, worth watching this space.

<sup>1</sup> That's actually a `|` followed by a `>`. The default font on these slides just makes it look extra fancy.



# dplyr

---

# Aside: dplyr 1.0.0 release

Some of the **dplyr** features that we'll cover today were introduced in **version 1.0.0** of the package.

- Version 1.0.0 is a big deal since it marks a stable code base for the package going forward. However, at the time of writing these slides, it had only come out very recently.
- Please make sure that you are running at least **dplyr** 1.0.0 before continuing.

```
packageVersion('dplyr')
```

```
## [1] '1.0.5'
```

```
# install.packages('dplyr') ## install updated version if < 1.0.0
```

# Aside: dplyr 1.0.0 release

Some of the **dplyr** features that we'll cover today were introduced in **version 1.0.0** of the package.

- Version 1.0.0 is a big deal since it marks a stable code base for the package going forward. However, at the time of writing these slides, it had only come out very recently.
- Please make sure that you are running at least **dplyr** 1.0.0 before continuing.

```
packageVersion('dplyr')
```

```
## [1] '1.0.5'
```

```
# install.packages('dplyr') ## install updated version if < 1.0.0
```

**Note:** **dplyr** 1.0.0 also notifies you about grouping variables every time you do operations on or with them. YMMV, but, personally, I find these messages annoying and so prefer to **switch them off**.

```
options(dplyr.summarise.inform = FALSE) ## Add to .Rprofile to make permanent
```

# Key dplyr verbs

There are five key dplyr verbs that you need to learn.

1. `filter`: Filter (i.e. subset) rows based on their values.
2. `arrange`: Arrange (i.e. reorder) rows based on their values.
3. `select`: Select (i.e. subset) columns by their names:
4. `mutate`: Create new columns.
5. `summarise`: Collapse multiple rows into a single summary value.<sup>1</sup>

<sup>1</sup> `summarize` with a "z" works too. R doesn't discriminate against uncivilised nations of the world.

# Key dplyr verbs

There are five key dplyr verbs that you need to learn.

1. `filter`: Filter (i.e. subset) rows based on their values.
2. `arrange`: Arrange (i.e. reorder) rows based on their values.
3. `select`: Select (i.e. subset) columns by their names:
4. `mutate`: Create new columns.
5. `summarise`: Collapse multiple rows into a single summary value.<sup>1</sup>

Let's practice these commands together using the `starwars` data frame that comes pre-packaged with dplyr.

<sup>1</sup> `summarize` with a "z" works too. R doesn't discriminate against uncivilised nations of the world.

# 1) dplyr::filter

We can chain multiple filter commands with the pipe (`%>%`), or just separate them within a single filter command using commas.

```
starwars %>%  
  filter(  
    species = "Human",  
    height ≥ 190  
  )
```

```
## # A tibble: 4 x 14  
##   name    height  mass hair_color skin_color eye_color birth_year sex  gender  
##   <chr>   <int> <dbl> <chr>      <chr>      <chr>      <dbl> <chr> <chr>  
## 1 Dart...    202   136 none      white      yellow      41.9 male  mascu...  
## 2 Qui-...    193    89 brown     fair       blue        92  male  mascu...  
## 3 Dooku     193    80 white     fair       brown       102  male  mascu...  
## 4 Bail...   191    NA black     tan        brown        67  male  mascu...  
## # ... with 5 more variables: homeworld <chr>, species <chr>, films <list>,  
## #   vehicles <list>, starships <list>
```

# 1) dplyr::filter cont.

Regular expressions work well too.

```
starwars %>%  
  filter(grepl("Skywalker", name))
```

```
## # A tibble: 3 x 14  
##   name    height  mass hair_color skin_color eye_color birth_year sex   gender  
##   <chr>   <int> <dbl> <chr>      <chr>      <chr>      <dbl> <chr> <chr>  
## 1 Luke...   172    77 blond      fair        blue        19   male masculi...  
## 2 Anak...   188    84 blond      fair        blue       41.9  male masculi...  
## 3 Shmi...   163    NA black      fair        brown       72   fema... feminin...  
## # ... with 5 more variables: homeworld <chr>, species <chr>, films <list>,  
## #   vehicles <list>, starships <list>
```

# 1) dplyr::filter cont.

A very common `filter` use case is identifying (or removing) missing data cases.

```
starwars %>%  
  filter(is.na(height))
```

```
## # A tibble: 6 x 14  
##   name   height  mass hair_color skin_color eye_color birth_year sex   gender  
##   <chr>  <int> <dbl> <chr>      <chr>      <chr>      <dbl> <chr> <chr>  
## 1 Arve...    NA    NA brown      fair        brown        NA male  mascu...  
## 2 Finn      NA    NA black     dark        dark        NA male  mascu...  
## 3 Rey       NA    NA brown     light       hazel        NA fema... femin...  
## 4 Poe ...   NA    NA brown     light       brown        NA male  mascu...  
## 5 BB8       NA    NA none      none        black        NA none  mascu...  
## 6 Capt...   NA    NA unknown  unknown     unknown     NA <NA>  <NA>  
## # ... with 5 more variables: homeworld <chr>, species <chr>, films <list>,  
## #   vehicles <list>, starships <list>
```



# 1) dplyr::filter cont.

A very common `filter` use case is identifying (or removing) missing data cases.

```
starwars %>%  
  filter(is.na(height))
```

```
## # A tibble: 6 x 14  
##   name    height    mass hair_color skin_color eye_color birth_year sex    gender  
##   <chr>   <int> <dbl> <chr>      <chr>      <chr>      <dbl> <chr> <chr>  
## 1 Arve...     NA     NA brown      fair        brown          NA male  mascu...  
## 2 Finn        NA     NA black      dark        dark          NA male  mascu...  
## 3 Rey         NA     NA brown      light       hazel          NA fema... femin...  
## 4 Poe ...     NA     NA brown      light       brown          NA male  mascu...  
## 5 BB8         NA     NA none       none        black          NA none  mascu...  
## 6 Capt...     NA     NA unknown   unknown    unknown          NA <NA>  <NA>  
## # ... with 5 more variables: homeworld <chr>, species <chr>, films <list>,  
## #   vehicles <list>, starships <list>
```

To remove missing observations, simply use negation: `filter(!is.na(height))`. Try this yourself.

## 2) dplyr::arrange

```
starwars %>%  
  arrange(birth_year)
```

```
## # A tibble: 87 x 14
```

```
##   name    height  mass hair_color skin_color eye_color birth_year sex   gender  
##   <chr>   <int> <dbl> <chr>      <chr>      <chr>      <dbl> <chr> <chr>  
## 1 Wick...    88   20  brown     brown     brown         8  male  masculi  
## 2 IG-88    200  140  none      metal     red          15  none  masculi  
## 3 Luke...   172   77  blond     fair      blue         19  male  masculi  
## 4 Leia...   150   49  brown     light     brown        19  fema... feminin  
## 5 Wedg...   170   77  brown     fair      hazel        21  male  masculi  
## 6 Plo ...   188   80  none      orange    black        22  male  masculi  
## 7 Bigg...   183   84  black     light     brown        24  male  masculi  
## 8 Han ...   180   80  brown     fair      brown        29  male  masculi  
## 9 Land...   177   79  black     dark      brown        31  male  masculi  
## 10 Boba...  183  78.2  black     fair      brown       31.5  male  masculi  
## # ... with 77 more rows, and 5 more variables: homeworld <chr>, species <chr>,  
## #   films <list>, vehicles <list>, starships <list>
```

## 2) dplyr::arrange

```
starwars %>%  
  arrange(birth_year)
```

```
## # A tibble: 87 x 14  
##   name      height  mass hair_color skin_color eye_color birth_year sex   gender  
##   <chr>    <int> <dbl> <chr>      <chr>      <chr>      <dbl> <chr> <chr>  
## 1 Wick...      88   20  brown      brown      brown         8  male  mascu...  
## 2 IG-88      200  140  none       metal      red          15  none  mascu...  
## 3 Luke...     172   77  blond      fair       blue         19  male  mascu...  
## 4 Leia...     150   49  brown      light      brown        19  fema... femin...  
## 5 Wedg...     170   77  brown      fair       hazel        21  male  mascu...  
## 6 Plo ...     188   80  none       orange     black        22  male  mascu...  
## 7 Bigg...     183   84  black      light      brown        24  male  mascu...  
## 8 Han ...     180   80  brown      fair       brown        29  male  mascu...  
## 9 Land...     177   79  black      dark       brown        31  male  mascu...  
## 10 Boba...     183  78.2  black      fair       brown       31.5  male  mascu...  
## # ... with 77 more rows, and 5 more variables: homeworld <chr>, species <chr>,  
## #   films <list>, vehicles <list>, starships <list>
```

Note: Arranging on a character-based column (i.e. strings) will sort alphabetically. Try this yourself by arranging according to the "name" column.

## 2) dplyr::arrange cont.

We can also arrange items in descending order using `arrange(desc())`.

```
starwars %>%  
  arrange(desc(birth_year))
```

```
## # A tibble: 87 x 14  
##   name      height  mass hair_color skin_color eye_color birth_year sex  gender  
##   <chr>    <int> <dbl> <chr>      <chr>      <chr>      <dbl> <chr> <chr>  
## 1 Yoda        66    17 white      green      brown        896 male  mascu...  
## 2 Jabb...     175   1358 <NA>      green-tan... orange        600 herm... mascu...  
## 3 Chew...     228    112 brown      unknown    blue         200 male  mascu...  
## 4 C-3PO      167     75 <NA>      gold        yellow        112 none  mascu...  
## 5 Dooku       193     80 white      fair        brown        102 male  mascu...  
## 6 Qui-...     193     89 brown      fair        blue          92 male  mascu...  
## 7 Ki-A...     198     82 white      pale        yellow         92 male  mascu...  
## 8 Fini...     170     NA blond      fair        blue          91 male  mascu...  
## 9 Palp...     170     75 grey      pale        yellow         82 male  mascu...  
## 10 Clie...     183     NA brown      fair        blue          82 male  mascu...  
## # ... with 77 more rows, and 5 more variables: homeworld <chr>, species <chr>,  
## #   films <list>, vehicles <list>, starships <list>
```

### 3) dplyr::select

Use commas to select multiple columns out of a data frame. (You can also use "first:last" for consecutive columns). Deselect a column with "-".

```
starwars %>%  
  select(name:skin_color, species, -height)
```

```
## # A tibble: 87 x 5  
##   name                mass hair_color  skin_color species  
##   <chr>              <dbl> <chr>      <chr>      <chr>  
## 1 Luke Skywalker      77 blond     fair       Human  
## 2 C-3PO                75 <NA>      gold       Droid  
## 3 R2-D2                32 <NA>      white, blue Droid  
## 4 Darth Vader         136 none      white      Human  
## 5 Leia Organa          49 brown     light      Human  
## 6 Owen Lars           120 brown, grey light      Human  
## 7 Beru Whitesun lars   75 brown     light      Human  
## 8 R5-D4                32 <NA>      white, red  Droid  
## 9 Biggs Darklighter   84 black     light      Human  
## 10 Obi-Wan Kenobi      77 auburn, white fair       Human  
## # ... with 77 more rows
```

### 3) dplyr::select *cont.*

You can also rename some (or all) of your selected variables in place.

```
starwars %>%  
  select(alias=name, crib=homeworld, sex=gender)
```

```
## # A tibble: 87 x 3  
##   alias          crib      sex  
##   <chr>         <chr>   <chr>  
## 1 Luke Skywalker Tatooine masculine  
## 2 C-3PO         Tatooine masculine  
## 3 R2-D2         Naboo    masculine  
## 4 Darth Vader   Tatooine masculine  
## 5 Leia Organa   Alderaan feminine  
## 6 Owen Lars     Tatooine masculine  
## 7 Beru Whitesun lars Tatooine feminine  
## 8 R5-D4         Tatooine masculine  
## 9 Biggs Darklighter Tatooine masculine  
## 10 Obi-Wan Kenobi Stewjon  masculine  
## # ... with 77 more rows
```

### 3) dplyr::select *cont.*

You can also rename some (or all) of your selected variables in place.

```
starwars %>%  
  select(alias=name, crib=homeworld, sex=gender)
```

```
## # A tibble: 87 x 3  
##   alias          crib      sex  
##   <chr>         <chr>   <chr>  
## 1 Luke Skywalker Tatooine masculine  
## 2 C-3PO          Tatooine masculine  
## 3 R2-D2          Naboo    masculine  
## 4 Darth Vader    Tatooine masculine  
## 5 Leia Organa    Alderaan feminine  
## 6 Owen Lars      Tatooine masculine  
## 7 Beru Whitesun lars Tatooine feminine  
## 8 R5-D4          Tatooine masculine  
## 9 Biggs Darklighter Tatooine masculine  
## 10 Obi-Wan Kenobi Stewjon  masculine  
## # ... with 77 more rows
```

If you just want to rename columns without subsetting them, you can use `rename`. Try this now by replacing `select( ... )` in the above code chunk with `rename( ... )`.

### 3) dplyr::select *cont.*

The `select(contains(PATTERN))` option provides a nice shortcut in relevant cases.

```
starwars %>%  
  select(name, contains("color"))
```

```
## # A tibble: 87 x 4  
##   name                hair_color  skin_color eye_color  
##   <chr>              <chr>      <chr>      <chr>  
## 1 Luke Skywalker    blond      fair       blue  
## 2 C-3PO             <NA>      gold       yellow  
## 3 R2-D2             <NA>      white, blue red  
## 4 Darth Vader       none       white      yellow  
## 5 Leia Organa       brown      light      brown  
## 6 Owen Lars         brown, grey light      blue  
## 7 Beru Whitesun lars brown      light      blue  
## 8 R5-D4             <NA>      white, red red  
## 9 Biggs Darklighter black       light      brown  
## 10 Obi-Wan Kenobi    auburn, white fair       blue-gray  
## # ... with 77 more rows
```



### 3) dplyr::select *cont.*

The `select( ... , everything())` option is another useful shortcut if you only want to bring some variable(s) to the "front" of a data frame.

```
starwars %>%  
  select(species, homeworld, everything()) %>%  
  head(5)
```

```
## # A tibble: 5 x 14  
##   species homeworld name    height  mass hair_color skin_color eye_color  
##   <chr>    <chr>    <chr>   <int> <dbl> <chr>      <chr>    <chr>  
## 1 Human   Tatooine  Luke...   172    77 blond      fair      blue  
## 2 Droid   Tatooine  C-3PO    167    75 <NA>      gold      yellow  
## 3 Droid   Naboo     R2-D2     96    32 <NA>      white, bl... red  
## 4 Human   Tatooine  Dart...  202   136 none       white      yellow  
## 5 Human   Alderaan  Leia...  150    49 brown      light      brown  
## # ... with 6 more variables: birth_year <dbl>, sex <chr>, gender <chr>,  
## #   films <list>, vehicles <list>, starships <list>
```

### 3) dplyr::select *cont.*

The `select( ... , everything())` option is another useful shortcut if you only want to bring some variable(s) to the "front" of a data frame.

```
starwars %>%
  select(species, homeworld, everything()) %>%
  head(5)
```

  

```
## # A tibble: 5 x 14
##   species homeworld name    height  mass hair_color skin_color eye_color
##   <chr>    <chr>    <chr>   <int> <dbl> <chr>      <chr>    <chr>
## 1 Human   Tatooine  Luke...   172    77 blond      fair      blue
## 2 Droid   Tatooine  C-3PO    167    75 <NA>      gold      yellow
## 3 Droid   Naboo     R2-D2     96    32 <NA>      white, bl... red
## 4 Human   Tatooine  Dart...  202   136 none       white      yellow
## 5 Human   Alderaan  Leia...  150    49 brown      light      brown
## # ... with 6 more variables: birth_year <dbl>, sex <chr>, gender <chr>,
## #   films <list>, vehicles <list>, starships <list>
```

*Note:* The new `relocate` function available in dplyr 1.0.0 has brought a lot more functionality to ordering of columns. See [here](#).

## 4) dplyr::mutate

You can create new columns from scratch, or (more commonly) as transformations of existing columns.

```
starwars %>%  
  select(name, birth_year) %>%  
  mutate(dog_years = birth_year * 7) %>%  
  mutate(comment = paste0(name, " is ", dog_years, " in dog years."))
```

```
## # A tibble: 87 x 4  
##   name                birth_year dog_years comment  
##   <chr>                <dbl>     <dbl> <chr>  
## 1 Luke Skywalker         19        133 Luke Skywalker is 133 in dog years.  
## 2 C-3PO                 112        784 C-3PO is 784 in dog years.  
## 3 R2-D2                  33        231 R2-D2 is 231 in dog years.  
## 4 Darth Vader           41.9       293.3 Darth Vader is 293.3 in dog years.  
## 5 Leia Organa           19        133 Leia Organa is 133 in dog years.  
## 6 Owen Lars              52        364 Owen Lars is 364 in dog years.  
## 7 Beru Whitesun lars     47        329 Beru Whitesun lars is 329 in dog yea...  
## 8 R5-D4                  NA         NA R5-D4 is NA in dog years.  
## 9 Biggs Darklighter     24        168 Biggs Darklighter is 168 in dog year...  
## 10 Obi-Wan Kenobi        57        399 Obi-Wan Kenobi is 399 in dog years.  
## # ... with 77 more rows
```

## 4) dplyr::mutate cont.

Note: `mutate` is order aware. So you can chain multiple mutates in a single call.

```
starwars %>%
  select(name, birth_year) %>%
  mutate(
    dog_years = birth_year * 7, ## Separate with a comma
    comment = paste0(name, " is ", dog_years, " in dog years.")
  )
```

```
## # A tibble: 87 x 4
```

```
##   name                birth_year dog_years comment
##   <chr>                <dbl>     <dbl> <chr>
## 1 Luke Skywalker      19         133 Luke Skywalker is 133 in dog years.
## 2 C-3PO               112         784 C-3PO is 784 in dog years.
## 3 R2-D2               33         231 R2-D2 is 231 in dog years.
## 4 Darth Vader        41.9        293.3 Darth Vader is 293.3 in dog years.
## 5 Leia Organa         19         133 Leia Organa is 133 in dog years.
## 6 Owen Lars           52         364 Owen Lars is 364 in dog years.
## 7 Beru Whitesun lars  47         329 Beru Whitesun lars is 329 in dog yea...
## 8 R5-D4              NA          NA   R5-D4 is NA in dog years.
## 9 Biggs Darklighter  24         168 Biggs Darklighter is 168 in dog year...
## 10 Obi-Wan Kenobi     57         399 Obi-Wan Kenobi is 399 in dog years.
## # ... with 77 more rows
```

## 4) dplyr::mutate cont.

Boolean, logical and conditional operators all work well with `mutate` too.

```
starwars %>%  
  select(name, height) %>%  
  filter(name %in% c("Luke Skywalker", "Anakin Skywalker")) %>%  
  mutate(tall1 = height > 180) %>%  
  mutate(tall2 = ifelse(height > 180, "Tall", "Short")) ## Same effect, but can choose
```

```
## # A tibble: 2 x 4  
##   name          height tall1 tall2  
##   <chr>          <int> <lgl> <chr>  
## 1 Luke Skywalker    172 FALSE Short  
## 2 Anakin Skywalker    188  TRUE  Tall
```

## 4) dplyr::mutate *cont.*

Lastly, combining `mutate` with the new `across` feature in dplyr 1.0.0+ allows you to easily work on a subset of variables. For example:

```
starwars %>%  
  select(name:eye_color) %>%  
  mutate(across(where(is.character), toupper)) %>%  
  head(5)
```

```
## # A tibble: 5 x 6  
##   name          height  mass hair_color skin_color eye_color  
##   <chr>         <int> <dbl> <chr>      <chr>      <chr>  
## 1 LUKE SKYWALKER    172    77 BLOND      FAIR        BLUE  
## 2 C-3PO             167    75 <NA>      GOLD        YELLOW  
## 3 R2-D2             96    32 <NA>      WHITE, BLUE RED  
## 4 DARTH VADER      202   136 NONE      WHITE        YELLOW  
## 5 LEIA ORGANA      150    49 BROWN     LIGHT        BROWN
```

## 4) dplyr::mutate *cont.*

Lastly, combining `mutate` with the new `across` feature in dplyr 1.0.0+ allows you to easily work on a subset of variables. For example:

```
starwars %>%  
  select(name:eye_color) %>%  
  mutate(across(where(is.character), toupper)) %>%  
  head(5)
```

```
## # A tibble: 5 x 6  
##   name          height  mass hair_color skin_color eye_color  
##   <chr>         <int> <dbl> <chr>      <chr>      <chr>  
## 1 LUKE SKYWALKER   172    77 BLOND      FAIR        BLUE  
## 2 C-3PO           167    75 <NA>      GOLD        YELLOW  
## 3 R2-D2           96     32 <NA>      WHITE, BLUE RED  
## 4 DARTH VADER     202   136 NONE      WHITE        YELLOW  
## 5 LEIA ORGANA     150    49 BROWN     LIGHT        BROWN
```

*Note:* This workflow (i.e. combining `mutate` and `across`) supersedes the old "scoped" variants of `mutate` that you might have used previously. More details [here](#) and [here](#).

# 5) dplyr::summarise

Particularly useful in combination with the `group_by` command.

```
starwars %>%  
  group_by(species, gender) %>%  
  summarise(mean_height = mean(height, na.rm = TRUE))
```

```
## # A tibble: 42 x 3  
## # Groups:   species [38]  
##   species    gender  mean_height  
##   <chr>      <chr>      <dbl>  
## 1 Aleena    masculine      79  
## 2 Besalisk  masculine     198  
## 3 Cerean    masculine     198  
## 4 Chagrian  masculine     196  
## 5 Clawdite  feminine     168  
## 6 Droid     feminine      96  
## 7 Droid     masculine     140  
## 8 Dug       masculine     112  
## 9 Ewok      masculine      88  
## 10 Geonosian masculine     183  
## # ... with 32 more rows
```



## 5) dplyr::summarise *cont.*

Note that including "na.rm = TRUE" (or, its alias "na.rm = T") is usually a good idea with summarise functions. Otherwise, any missing value will propagate to the summarised value too.

```
## Probably not what we want
```

```
starwars %>%  
  summarise(mean_height = mean(height))
```

```
## # A tibble: 1 x 1  
##   mean_height  
##         <dbl>  
## 1         NA
```

```
## Much better
```

```
starwars %>%  
  summarise(mean_height = mean(height, na.rm = TRUE))
```

```
## # A tibble: 1 x 1  
##   mean_height  
##         <dbl>  
## 1       174.
```

## 5) dplyr::summarise *cont.*

The same `across`-based workflow that we saw with `mutate` a few slides back also works with `summarise`. For example:

```
starwars %>%  
  group_by(species) %>%  
  summarise(across(where(is.numeric), mean, na.rm=T)) %>%  
  head(5)
```

```
## # A tibble: 5 x 4  
##   species height  mass birth_year  
##   <chr>    <dbl> <dbl>      <dbl>  
## 1 Aleena      79     15         NaN  
## 2 Besalisk    198    102         NaN  
## 3 Cerean     198     82          92  
## 4 Chagrian    196    NaN         NaN  
## 5 Clawdite    168     55         NaN
```

## 5) dplyr::summarise *cont.*

The same `across`-based workflow that we saw with `mutate` a few slides back also works with `summarise`. For example:

```
starwars %>%  
  group_by(species) %>%  
  summarise(across(where(is.numeric), mean, na.rm=T)) %>%  
  head(5)
```

```
## # A tibble: 5 x 4  
##   species height mass birth_year  
##   <chr>    <dbl> <dbl>    <dbl>  
## 1 Aleena      79     15      NaN  
## 2 Besalisk    198    102      NaN  
## 3 Cerean      198     82      92  
## 4 Chagrian    196     NA      NaN  
## 5 Clawdite    168     55      NaN
```

*Note:* Again, this functionality supersedes the old "scoped" variants of `summarise` that you used prior to dplyr 1.0.0. Details [here](#) and [here](#).

# Other dplyr goodies

`group_by` and `ungroup`: For (un)grouping.

- Particularly useful with the `summarise` and `mutate` commands, as we've already seen.

# Other dplyr goodies

`group_by` and `ungroup`: For (un)grouping.

- Particularly useful with the `summarise` and `mutate` commands, as we've already seen.

`slice`: Subset rows by position rather than filtering by values.

- E.g. `starwars %>% slice(c(1, 5))`

# Other dplyr goodies

`group_by` and `ungroup`: For (un)grouping.

- Particularly useful with the `summarise` and `mutate` commands, as we've already seen.

`slice`: Subset rows by position rather than filtering by values.

- E.g. `starwars %>% slice(c(1, 5))`

`pull`: Extract a column from a data frame as a vector or scalar.

- E.g. `starwars %>% filter(gender="female") %>% pull(height)`

# Other dplyr goodies

`group_by` and `ungroup`: For (un)grouping.

- Particularly useful with the `summarise` and `mutate` commands, as we've already seen.

`slice`: Subset rows by position rather than filtering by values.

- E.g. `starwars %>% slice(c(1, 5))`

`pull`: Extract a column from a data frame as a vector or scalar.

- E.g. `starwars %>% filter(gender="female") %>% pull(height)`

`count` and `distinct`: Number and isolate unique observations.

- E.g. `starwars %>% count(species)`, or `starwars %>% distinct(species)`
- You could also use a combination of `mutate`, `group_by`, and `n()`, e.g. `starwars %>% group_by(species) %>% mutate(num = n())`.

# Other dplyr goodies (cont.)

There are also a whole class of **window functions** for getting leads and lags, ranking, creating cumulative aggregates, etc.

- See `vignette("window-functions")`.



# Other dplyr goodies (cont.)

There are also a whole class of **window functions** for getting leads and lags, ranking, creating cumulative aggregates, etc.

- See `vignette("window-functions")`.

The final set of dplyr "goodies" are the family of join operations. However, these are important enough that I want to go over some concepts in a bit more depth...

- We will encounter and practice these many more times as the course progresses.

# Joins

One of the mainstays of the dplyr package is merging data with the family [join operations](#).

- `inner_join(df1, df2)`
- `left_join(df1, df2)`
- `right_join(df1, df2)`
- `full_join(df1, df2)`
- `semi_join(df1, df2)`
- `anti_join(df1, df2)`

(You find find it helpful to to see visual depictions of the different join operations [here](#).)

# Joins

One of the mainstays of the dplyr package is merging data with the family [join operations](#).

- `inner_join(df1, df2)`
- `left_join(df1, df2)`
- `right_join(df1, df2)`
- `full_join(df1, df2)`
- `semi_join(df1, df2)`
- `anti_join(df1, df2)`

(You find find it helpful to to see visual depictions of the different join operations [here](#).)

For the simple examples that I'm going to show here, we'll need some data sets that come bundled with the [nycflights13](#) package.

- Load it now and then inspect these data frames in your own console.

```
library(nycflights13)
flights
planes
```

# Joins (cont.)

Let's perform a **left join** on the flights and planes datasets.

- *Note:* I'm going subset columns after the join, but only to keep text on the slide.

# Joins (cont.)

Let's perform a **left join** on the flights and planes datasets.

- *Note:* I'm going subset columns after the join, but only to keep text on the slide.

```
left_join(flights, planes) %>%
  select(year, month, day, dep_time, arr_time, carrier, flight, tailnum, type, model)

## Joining, by = c("year", "tailnum")

## # A tibble: 336,776 x 10
##   year month   day dep_time arr_time carrier flight tailnum type  model
##   <int> <int> <int>   <int>   <int>   <chr>   <int> <chr>   <chr> <chr>
## 1  2013     1     1     517     830 UA      1545 N14228 <NA> <NA>
## 2  2013     1     1     533     850 UA      1714 N24211 <NA> <NA>
## 3  2013     1     1     542     923 AA      1141 N619AA <NA> <NA>
## 4  2013     1     1     544    1004 B6       725 N804JB <NA> <NA>
## 5  2013     1     1     554     812 DL       461 N668DN <NA> <NA>
## 6  2013     1     1     554     740 UA      1696 N39463 <NA> <NA>
## 7  2013     1     1     555     913 B6       507 N516JB <NA> <NA>
## 8  2013     1     1     557     709 EV      5708 N829AS <NA> <NA>
## 9  2013     1     1     557     838 B6        79 N593JB <NA> <NA>
## 10 2013     1     1     558     753 AA       301 N3ALAA <NA> <NA>
## # ... with 336,766 more rows
```

# Joins (cont.)

*(continued from previous slide)*

Note that dplyr made a reasonable guess about which columns to join on (i.e. columns that share the same name). It also told us its choices:

```
## Joining, by = c("year", "tailnum")
```

However, there's an obvious problem here: the variable "year" does not have a consistent meaning across our joining datasets!

- In one it refers to the *year of flight*, in the other it refers to *year of construction*.

# Joins (cont.)

*(continued from previous slide)*

Note that dplyr made a reasonable guess about which columns to join on (i.e. columns that share the same name). It also told us its choices:

```
## Joining, by = c("year", "tailnum")
```

However, there's an obvious problem here: the variable "year" does not have a consistent meaning across our joining datasets!

- In one it refers to the *year of flight*, in the other it refers to *year of construction*.

Luckily, there's an easy way to avoid this problem.

- See if you can figure it out before turning to the next slide.
- Try `?dplyr::join`.

# Joins (cont.)

(continued from previous slide)

You just need to be more explicit in your join call by using the `by =` argument.

- You can also rename any ambiguous columns to avoid confusion.

```
left_join(
  flights,
  planes %>% rename(year_built = year), ## Not necessary w/ below line, but helpful
  by = "tailnum" ## Be specific about the joining column
) %>%
select(year, month, day, dep_time, arr_time, carrier, flight, tailnum, year_built, 1
head(3) ## Just to save vertical space on the slide
```

```
## # A tibble: 3 x 11
##   year month   day dep_time arr_time carrier flight tailnum year_built type
##   <int> <int> <int>   <int>   <int> <chr>   <int> <chr>      <int> <chr>
## 1  2013     1     1     517     830 UA      1545 N14228     1999 Fixe...
## 2  2013     1     1     533     850 UA      1714 N24211     1998 Fixe...
## 3  2013     1     1     542     923 AA      1141 N619AA     1990 Fixe...
## # ... with 1 more variable: model <chr>
```



# Joins (cont.)

(continued from previous slide)

Last thing I'll mention for now; note what happens if we again specify the join column... but don't rename the ambiguous "year" column in at least one of the given data frames.

```
left_join(
  flights,
  planes, ## Not renaming "year" to "year_built" this time
  by = "tailnum"
) %>%
select(contains("year"), month, day, dep_time, arr_time, carrier, flight, tailnum, 1
head(3)
```

```
## # A tibble: 3 x 11
##   year.x year.y month   day dep_time arr_time carrier flight tailnum type  model
##   <int>  <int> <int> <int>   <int>   <int> <chr>    <int> <chr>  <chr> <chr>
## 1  2013    1999     1     1     517     830 UA       1545 N14228  Fixe... 737-...
## 2  2013    1998     1     1     533     850 UA       1714 N24211  Fixe... 737-...
## 3  2013    1990     1     1     542     923 AA       1141 N619AA  Fixe... 757-...
```

# Joins (cont.)

(continued from previous slide)

Last thing I'll mention for now; note what happens if we again specify the join column... but don't rename the ambiguous "year" column in at least one of the given data frames.

```
left_join(
  flights,
  planes, ## Not renaming "year" to "year_built" this time
  by = "tailnum"
) %>%
select(contains("year"), month, day, dep_time, arr_time, carrier, flight, tailnum, 1
head(3)
```

```
## # A tibble: 3 x 11
##   year.x year.y month   day dep_time arr_time carrier flight tailnum type  model
##   <int>  <int> <int> <int>   <int>   <int> <chr>    <int> <chr>  <chr> <chr>
## 1   2013   1999     1     1     517     830 UA       1545 N14228  Fixe... 737-...
## 2   2013   1998     1     1     533     850 UA       1714 N24211  Fixe... 737-...
## 3   2013   1990     1     1     542     923 AA       1141 N619AA  Fixe... 757-...
```

Make sure you know what "year.x" and "year.y" are. Again, it pays to be specific.

# tidyr

---

# Key tidyr verbs

1. `pivot_longer`: Pivot wide data into long format (i.e. "melt").<sup>1</sup>
2. `pivot_wider`: Pivot long data into wide format (i.e. "cast").<sup>2</sup>
3. `separate`: Separate (i.e. split) one column into multiple columns.
4. `unite`: Unite (i.e. combine) multiple columns into one.

<sup>1</sup> Updated version of `tidyr::gather`.

<sup>2</sup> Updated version of `tidyr::spread`.

# Key tidyr verbs

1. `pivot_longer`: Pivot wide data into long format (i.e. "melt").<sup>1</sup>
2. `pivot_wider`: Pivot long data into wide format (i.e. "cast").<sup>2</sup>
3. `separate`: Separate (i.e. split) one column into multiple columns.
4. `unite`: Unite (i.e. combine) multiple columns into one.

Let's practice these verbs together in class.

- Side question: Which of `pivot_longer` vs `pivot_wider` produces "tidy" data?

<sup>1</sup> Updated version of `tidyr::gather`.

<sup>2</sup> Updated version of `tidyr::spread`.

# 1) tidyr::pivot\_longer

```
stocks = data.frame( ## Could use "tibble" instead of "data.frame" if you prefer
  time = as.Date('2009-01-01') + 0:1,
  X = rnorm(2, 0, 1),
  Y = rnorm(2, 0, 2),
  Z = rnorm(2, 0, 4)
)
stocks
```

```
##           time           X           Y           Z
## 1 2009-01-01  0.7630456 -0.7002949 -3.417682
## 2 2009-01-02 -0.4579186 -0.7498116 -6.052036
```

```
stocks %>% pivot_longer(-time, names_to="stock", values_to="price")
```

```
## # A tibble: 6 x 3
##   time      stock price
##   <date>   <chr> <dbl>
## 1 2009-01-01 X      0.763
## 2 2009-01-01 Y     -0.700
## 3 2009-01-01 Z     -3.42
## 4 2009-01-02 X     -0.458
## 5 2009-01-02 Y     -0.750
## 6 2009-01-02 Z     -6.05
```

# 1) tidyr::pivot\_longer cont.

Let's quickly save the "tidy" (i.e. long) stocks data frame for use on the next slide.

```
## Write out the argument names this time: i.e. "names_to=" and "values_to="  
tidy_stocks =  
  stocks %>%  
  pivot_longer(-time, names_to="stock", values_to="price")
```

## 2) tidyr::pivot\_wider

```
tidy_stocks %>% pivot_wider(names_from=stock, values_from=price)
```

```
## # A tibble: 2 x 4
##   time          X      Y      Z
##   <date>      <dbl> <dbl> <dbl>
## 1 2009-01-01  0.763 -0.700 -3.42
## 2 2009-01-02 -0.458 -0.750 -6.05
```

```
tidy_stocks %>% pivot_wider(names_from=time, values_from=price)
```

```
## # A tibble: 3 x 3
##   stock 2009-01-01 2009-01-02
##   <chr>      <dbl>      <dbl>
## 1 X          0.763      -0.458
## 2 Y         -0.700      -0.750
## 3 Z         -3.42       -6.05
```



## 2) tidyr::pivot\_wider

```
tidy_stocks %>% pivot_wider(names_from=stock, values_from=price)
```

```
## # A tibble: 2 x 4
##   time          X          Y          Z
##   <date>      <dbl>   <dbl>   <dbl>
## 1 2009-01-01  0.763 -0.700 -3.42
## 2 2009-01-02 -0.458 -0.750 -6.05
```

```
tidy_stocks %>% pivot_wider(names_from=time, values_from=price)
```

```
## # A tibble: 3 x 3
##   stock 2009-01-01 2009-01-02
##   <chr>   <dbl>   <dbl>
## 1 X      0.763   -0.458
## 2 Y     -0.700   -0.750
## 3 Z     -3.42   -6.05
```

Note that the second example — which has combined different pivoting arguments — has effectively transposed the data.

# Aside: Remembering the `pivot_*` syntax

There's a long-running joke about no-one being able to remember Stata's "reshape" command. ([Exhibit A](#).)

It's easy to see this happening with the `pivot_*` functions too. However, I find that I never forget the commands as long as I remember the argument order is *"names"* then *"values"*.

### 3) tidyr::separate

```
economists = data.frame(name = c("Adam.Smith", "Paul.Samuelson", "Milton.Friedman"))  
economists
```

```
##           name  
## 1   Adam.Smith  
## 2 Paul.Samuelson  
## 3 Milton.Friedman
```

```
economists %>% separate(name, c("first_name", "last_name"))
```

```
## first_name last_name  
## 1      Adam      Smith  
## 2      Paul Samuelson  
## 3     Milton  Friedman
```

### 3) tidyr::separate

```
economists = data.frame(name = c("Adam.Smith", "Paul.Samuelson", "Milton.Friedman"))  
economists
```

```
##           name  
## 1   Adam.Smith  
## 2 Paul.Samuelson  
## 3 Milton.Friedman
```

```
economists %>% separate(name, c("first_name", "last_name"))
```

```
## first_name last_name  
## 1      Adam      Smith  
## 2      Paul Samuelson  
## 3      Milton  Friedman
```

This command is pretty smart. But to avoid ambiguity, you can also specify the separation character with `separate( ... , sep=".")`.

### 3) tidyr::separate cont.

A related function is `separate_rows`, for splitting up cells that contain multiple fields or observations (a frustratingly common occurrence with survey data).

```
jobs = data.frame(  
  name = c("Jack", "Jill"),  
  occupation = c("Homemaker", "Philosopher, Philanthropist, Troublemaker")  
)  
jobs
```

```
##   name                occupation  
## 1 Jack                Homemaker  
## 2 Jill Philosopher, Philanthropist, Troublemaker
```

```
## Now split out Jill's various occupations into different rows  
jobs %>% separate_rows(occupation)
```

```
## # A tibble: 4 x 2  
##   name  occupation  
##   <chr> <chr>  
## 1 Jack  Homemaker  
## 2 Jill  Philosopher  
## 3 Jill  Philanthropist  
## 4 Jill  Troublemaker
```

## 4) tidyr::unite

```
gdp = data.frame(  
  yr = rep(2016, times = 4),  
  mnth = rep(1, times = 4),  
  dy = 1:4,  
  gdp = rnorm(4, mean = 100, sd = 2)  
)  
gdp
```

```
##      yr mnth dy      gdp  
## 1 2016     1   1 101.6175  
## 2 2016     1   2 100.4228  
## 3 2016     1   3 102.3959  
## 4 2016     1   4 101.8645
```

```
## Combine "yr", "mnth", and "dy" into one "date" column  
gdp %>% unite(date, c("yr", "mnth", "dy"), sep = "-")
```

```
##      date      gdp  
## 1 2016-1-1 101.6175  
## 2 2016-1-2 100.4228  
## 3 2016-1-3 102.3959  
## 4 2016-1-4 101.8645
```

## 4) tidyr::unite *cont.*

Note that `unite` will automatically create a character variable. You can see this better if we convert it to a tibble.

```
gdp_u = gdp %>% unite(date, c("yr", "mnth", "dy"), sep = "-") %>% as_tibble()
gdp_u
```

```
## # A tibble: 4 x 2
##   date      gdp
##   <chr>    <dbl>
## 1 2016-1-1  102.
## 2 2016-1-2  100.
## 3 2016-1-3  102.
## 4 2016-1-4  102.
```

## 4) tidyr::unite cont.

Note that `unite` will automatically create a character variable. You can see this better if we convert it to a tibble.

```
gdp_u = gdp %>% unite(date, c("yr", "mnth", "dy"), sep = "-") %>% as_tibble()
gdp_u
```

```
## # A tibble: 4 x 2
##   date      gdp
##   <chr>    <dbl>
## 1 2016-1-1  102.
## 2 2016-1-2  100.
## 3 2016-1-3  102.
## 4 2016-1-4  102.
```

If you want to convert it to something else (e.g. date or numeric) then you will need to modify it using `mutate`. See the next slide for an example, using the `lubridate` package's super helpful date conversion functions.



## 4) tidyr::unite cont.

*(continued from previous slide)*

```
library(lubridate)
gdp_u %>% mutate(date = ymd(date))
```

```
## # A tibble: 4 x 2
##   date      gdp
##   <date>    <dbl>
## 1 2016-01-01  98.5
## 2 2016-01-02 102.
## 3 2016-01-03 101.
## 4 2016-01-04 101.
```

# Other tidyr goodies

Use `crossing` to get the full combination of a group of variables.<sup>1</sup>

```
crossing(side=c("left", "right"), height=c("top", "bottom"))
```

```
## # A tibble: 4 x 2
##   side  height
##   <chr> <chr>
## 1 left  bottom
## 2 left  top
## 3 right bottom
## 4 right top
```

<sup>1</sup> Base R alternative: `expand.grid`.

# Other tidyr goodies

Use `crossing` to get the full combination of a group of variables.<sup>1</sup>

```
crossing(side=c("left", "right"), height=c("top", "bottom"))
```

```
## # A tibble: 4 x 2
##   side  height
##   <chr> <chr>
## 1 left  bottom
## 2 left  top
## 3 right bottom
## 4 right top
```

See `?expand` and `?complete` for more specialised functions that allow you to fill in (implicit) missing data or variable combinations in existing data frames.

- You'll encounter this during your next assignment.

<sup>1</sup> Base R alternative: `expand.grid`.

# Summary

---

# Key verbs

## dplyr

1. `filter`
2. `arrange`
3. `select`
4. `mutate`
5. `summarise`

## tidyr

1. `pivot_longer`
2. `pivot_wider`
3. `separate`
4. `unite`

# Key verbs

## dplyr

1. `filter`
2. `arrange`
3. `select`
4. `mutate`
5. `summarise`

## tidyr

1. `pivot_longer`
2. `pivot_wider`
3. `separate`
4. `unite`

Other useful items include: pipes (`%>%`), grouping (`group_by`), joining functions (`left_join`, `inner_join`, etc.).

Next lecture: Data cleaning and  
wrangling: (2) data.table

---