NAME

ibus - command line utility for ibus

SYNOPSIS

ibus COMMAND [OPTION]...

DESCRIPTION

IBus is an Intelligent Input Bus. It is a new input framework for Linux OS. It provides full featured and user friendly input method user interface. It also may help developers to develop input method easily.

ibus is a command line utility which can restart or exit ibus-daemon, get or set the current ibus engine or list the ibus engines.

Homepage: https://github.com/ibus/wiki

COMMAND

help Show the commands list.

engine [ENGINE_NAME]

Show the curent ibus engine when **ENGINE_NAME** is not given. Set **ENGINE_NAME** to the current ibus engine.

exit Exit ibus-daemon.

list-engine

Show ibus engines list.

restart Restart ibus-daemon.

version

Show the ibus version.

read-cache [--system|--file=FILE]

Show the content of the user registry cache if —-system is not given. Show the content of the system registry cache if —-system is given. Show the content of the custom registry cache **FILE** if —-file=FILE is given.

write-cache [--system|--file=FILE]

Save the user registry cache if **—-system** is not given. Save the system registry cache if **—-system** is given. Save the custom registry cache **FILE** if **—-file=FILE** is given.

By default, it reads the component XML files from the standard component directory (/usr/share/ibus/component), you can set IBUS_COMPONENT_PATH environment variable for custom component directories, separated by ':'.

address

Show the D-Bus address of ibus-daemon.

read-config

Print the setting values in a gsettings configuration file.

reset-config

Reset the user setting values to the default ones in a gsettings configuration file.

watch Under construction.

emoji [--font=FONT|--lang=LANG|--help|--partial-match]

Launch IBus Emojier (**ibus-emoji** (1)) and save the selected emoji to your clipboard. Can choose an emoji font with **—-font** option. Can choose a language of emoji annotations with **—-lang** option. If LANG="en", IBus Emojier loads /usr/share/ibus/dicts/emoji-en.dict . **—-partial-match**

option enables to match annotations with a partial string. These settings are available with **ibus-setup** (1) utility.

BUGS

If you find a bug, please report it at https://github.com/ibus/ibus/issues

SEE ALSO

ibus-emoji(7)