

NAME

`a2enconf`, `a2disconf` – enable or disable an apache2 configuration file

SYNOPSIS

a2enconf [`[-q|--quiet]` *configuration*]

a2disconf [`[-q|--quiet]` *configuration*]

DESCRIPTION

This manual page documents briefly the **a2enconf** and **a2disconf** commands.

a2enconf is a script that enables the specified configuration file within the **apache2** configuration. It does this by creating symlinks within **/etc/apache2/conf-enabled**. Likewise, **a2disconf** disables a specific configuration part by removing those symlinks. It is not an error to enable a configuration which is already enabled, or to disable one which is already disabled.

Note that many configuration file may have a dependency to specific modules. Unlike module dependencies, these are not resolved automatically. Configuration fragments stored in the **conf-available** directory are considered non-essential or being installed and managed by reverse dependencies (e.g. web scripts).

OPTIONS

-q, --quiet

Don't show informative messages.

-m, --maintmode

Enables the maintainer mode, that is the program invocation is effectuated automatically by a maintainer script. This switch should not be used by end users.

-p, --purge

When disabling a module, purge all traces of the module in the internal state data base.

EXIT STATUS

a2enconf and **a2disconf** exit with status 0 if all *configurations* are processed successfully, 1 if errors occur, 2 if an invalid option was used.

EXAMPLES

a2enconf security

a2disconf charset

Enables Apache security directives stored in the **security** configuration files, and disables the **charset** configuration.

FILES

/etc/apache2/conf-available

Directory with files giving information on available configuration files.

/etc/apache2/conf-enabled

Directory with links to the files in **conf-available** for enabled configuration files.

SEE ALSO

apache2ctl(8), **a2enmod(8)**, **a2dismod(8)**.

AUTHOR

This manual page was written by Arno Toell <debian@toell.net> for the Debian GNU/Linux distribution, as it is a Debian-specific script with the package.