

NAME

rtnetlink – macros to manipulate rtnetlink messages

SYNOPSIS

```
#include <asm/types.h>
#include <linux/netlink.h>
#include <linux/rtnetlink.h>
#include <sys/socket.h>

rtnetlink_socket = socket(AF_NETLINK, int socket_type, NETLINK_ROUTE);

int RTA_OK(struct rtattr *rta, int rtabuflen);

void *RTA_DATA(struct rtattr *rta);

unsigned int RTA_PAYLOAD(struct rtattr *rta);

struct rtattr *RTA_NEXT(struct rtattr *rta, unsigned int rtabuflen);

unsigned int RTA_LENGTH(unsigned int length);

unsigned int RTA_SPACE(unsigned int length);
```

DESCRIPTION

All **rtnetlink**(7) messages consist of a **netlink**(7) message header and appended attributes. The attributes should be manipulated only using the macros provided here.

RTA_OK(*rta*, *attrlen*) returns true if *rta* points to a valid routing attribute; *attrlen* is the running length of the attribute buffer. When not true then you must assume there are no more attributes in the message, even if *attrlen* is nonzero.

RTA_DATA(*rta*) returns a pointer to the start of this attribute's data.

RTA_PAYLOAD(*rta*) returns the length of this attribute's data.

RTA_NEXT(*rta*, *attrlen*) gets the next attribute after *rta*. Calling this macro will update *attrlen*. You should use **RTA_OK** to check the validity of the returned pointer.

RTA_LENGTH(*len*) returns the length which is required for *len* bytes of data plus the header.

RTA_SPACE(*len*) returns the amount of space which will be needed in a message with *len* bytes of data.

CONFORMING TO

These macros are nonstandard Linux extensions.

BUGS

This manual page is incomplete.

EXAMPLE

Creating a rtnetlink message to set the MTU of a device:

```
#include <linux/rtnetlink.h>

...

struct {
    struct nlmsgghdr  nh;
    struct ifinfomsg if;
    char              attrbuf[512];
} req;

struct rtattr *rta;
unsigned int mtu = 1000;

int rtnetlink_sk = socket(AF_NETLINK, SOCK_DGRAM, NETLINK_ROUTE);
```

```
memset(&req, 0, sizeof(req));
req.nh.nlmsg_len = NLMSG_LENGTH(sizeof(struct ifinfomsg));
req.nh.nlmsg_flags = NLM_F_REQUEST;
req.nh.nlmsg_type = RTM_NEWLINK;
req.if_ifi_family = AF_UNSPEC;
req.if_ifi_index = INTERFACE_INDEX;
req.if_ifi_change = 0xffffffff; /* ??? */
rta = (struct rtattr *)(((char *) &req) +
                        NLMSG_ALIGN(req.nh.nlmsg_len));
rta->rta_type = IFLA_MTU;
rta->rta_len = RTA_LENGTH(sizeof(unsigned int));
req.nh.nlmsg_len = NLMSG_ALIGN(req.nh.nlmsg_len) +
                  RTA_LENGTH(sizeof(mtu));
memcpy(RTA_DATA(rta), &mtu, sizeof(mtu));
send(rtnetlink_sk, &req, req.nh.nlmsg_len, 0);
```

SEE ALSO

netlink(3), netlink(7), rtnetlink(7)

COLOPHON

This page is part of release 5.02 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.