NAME

floor, floorf, floorl - largest integral value not greater than argument

SYNOPSIS

DESCRIPTION

These functions return the largest integral value that is not greater than x.

For example, floor(0.5) is 0.0, and floor(-0.5) is -1.0.

RETURN VALUE

These functions return the floor of x.

If x is integral, +0, -0, NaN, or an infinity, x itself is returned.

ERRORS

No errors occur. POSIX.1-2001 documents a range error for overflows, but see NOTES.

ATTRIBUTES

For an explanation of the terms used in this section, see **attributes**(7).

Interface	Attribute	Value
$\boldsymbol{floor}(), \boldsymbol{floorf}(), \boldsymbol{floorl}()$	Thread safety	MT-Safe

CONFORMING TO

C99, POSIX.1-2001, POSIX.1-2008.

The variant returning double also conforms to SVr4, 4.3BSD, C89.

NOTES

SUSv2 and POSIX.1-2001 contain text about overflow (which might set *errno* to **ERANGE**, or raise an **FE_OVERFLOW** exception). In practice, the result cannot overflow on any current machine, so this error-handling stuff is just nonsense. (More precisely, overflow can happen only when the maximum value of the exponent is smaller than the number of mantissa bits. For the IEEE-754 standard 32-bit and 64-bit floating-point numbers the maximum value of the exponent is 128 (respectively, 1024), and the number of mantissa bits is 24 (respectively, 53).)

SEE ALSO

```
\boldsymbol{ceil}(3), \boldsymbol{lrint}(3), \boldsymbol{nearbyint}(3), \boldsymbol{rint}(3), \boldsymbol{round}(3), \boldsymbol{trunc}(3)
```

COLOPHON

This page is part of release 5.02 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at https://www.kernel.org/doc/man-pages/.

2017-09-15