

NAME

encguess – guess character encodings of files

VERSION

\$Id: encguess,v 0.2 2016/08/04 03:15:58 dankogai Exp \$

SYNOPSIS

```
encguess [switches] filename...
```

SWITCHES

- h**
show this message and exit.
- s**
specify a list of “suspect encoding types” to test, separated by either : or ,
- S**
output a list of all acceptable encoding types that can be used with the **-s** param
- u**
suppress display of unidentified types

EXAMPLES:

- Guess encoding of a file named `test.txt`, using only the default suspect types.

```
encguess test.txt
```
- Guess the encoding type of a file named `test.txt`, using the suspect types `euc-jp, shiftjis, 7bit-jis`.

```
encguess -s euc-jp,shiftjis,7bit-jis test.txt  
encguess -s euc-jp:shiftjis:7bit-jis test.txt
```
- Guess the encoding type of several files, do not display results for unidentified files.

```
encguess -us euc-jp,shiftjis,7bit-jis test*.txt
```

DESCRIPTION

The encoding identification is done by checking one encoding type at a time until all but the right type are eliminated. The set of encoding types to try is defined by the **-s** parameter and defaults to `ascii, utf8` and `UTF-16/32 with BOM`. This can be overridden by passing one or more encoding types via the **-s** parameter. If you need to pass in multiple suspect encoding types, use a quoted string with the a space separating each value.

SEE ALSO

Encode::Guess, Encode::Detect

LICENSE AND COPYRIGHT

Copyright 2015 Michael LaGrasta and Dan Kogai.

This program is free software; you can redistribute it and/or modify it under the terms of the the Artistic License (2.0). You may obtain a copy of the full license at:

<http://www.perlfoundation.org/artistic_license_2_0>