

NAME

`opal_wrapper` - Back-end Open MPI wrapper command

SYNOPSIS

`opal_wrapper` [**options**]

DESCRIPTION

opal_wrapper is not meant to be called directly by end users. It is automatically invoked as the back-end by the Open MPI wrapper commands such as: **mpicc**, **mpiCC**, **mpic++**, and **mpifort** (and its legacy/deprecated names **mpif77** and **mpif90**).

Some Open MPI installations may have additional wrapper commands, and/or have renamed the wrapper compilers listed above to avoid executable name conflicts with other MPI implementations. Hence, you may also have wrapper compilers installed including the following names: **mpifort.openmpi** (and the legacy/deprecated names **mpif90.openmpi** and **mpif77.openmpi**), **mpicxx.openmpi**, **mpiCC.openmpi**, **mpicc.openmpi**, **mpic++.openmpi**, **opalcc**, **opalc++**, **ortecc**, and **ortec++**,

SEE ALSO

The following may exist depending on your particular Open MPI installation: **mpicc**(1), **mpiCC**(1), **mpic++**(1), **mpifort**(1), **mpifort.openmpi**(1), **mpicxx.openmpi**(1), **mpiCC.openmpi**(1), **mpicc.openmpi**(1), **mpic++.openmpi**(1), **ortecc**(1), **ortec++**(1), **opalccc**(1), and the website at <http://www.openmpi.org/>.

AUTHORS

The Open MPI maintainers -- see <http://www.openmpi.org/> or the file *AUTHORS*.

This manual page was originally contributed by Dirk Eddelbuettel <edd@debian.org>, one of the Debian GNU/Linux maintainers for Open MPI, and may be used by others.