NAME
> devlink-region − devlink address region access

SYNOPSIS
> **devlink** [*OPTIONS*] **region** { *COMMAND* | **help** }

> *OPTIONS* := { **−V**[*ersion*] | **−n**[*no-nice-names*] }

> **devlink region show** [*DEV/REGION*]

> **devlink region del** *DEV/REGION* **snapshot** *SNAPSHOT_ID*

> **devlink region dump** *DEV/REGION* **snapshot** *SNAPSHOT_ID*

> **devlink region read** *DEV/REGION* **[snapshot** *SNAPSHOT_ID* **] address** *ADDRESS* **length** *LENGTH*

> **devlink region help**

DESCRIPTION
> **devlink region show - Show all supported address regions names, snapshots and sizes**
> > *DEV/REGION* - specifies the devlink device and address-region to query.

> **devlink region del - Delete a snapshot specified by address-region name and snapshot ID**
> > *DEV/REGION* - specifies the devlink device and address-region to delete the snapshot from

> > snapshot *SNAPSHOT_ID* - specifies the snapshot ID to delete

> **devlink region dump - Dump all the available data from a region or from snapshot of a region**
> > *DEV/REGION* - specifies the device and address-region to dump from.

> > snapshot *SNAPSHOT_ID* - specifies the snapshot-id of the region to dump.

> **devlink region read - Read from a specific region address for a given length**
> > *DEV/REGION* - specifies the device and address-region to read from.

> > snapshot *SNAPSHOT_ID* - specifies the snapshot-id of the region to read.

> > address *ADDRESS* - specifies the address to read from.

> > length *LENGTH* - specifies the length of data to read.

EXAMPLES
> devlink region show
> > List available address regions and snapshot.

> devlink region del pci/0000:00:05.0/cr-space snapshot 1
> > Delete snapshot id 1 from cr-space address region from device pci/0000:00:05.0.

> devlink region dump pci/0000:00:05.0/cr-space snapshot 1
> > Dump the snapshot taken from cr-space address region with ID 1

> devlink region read pci/0000:00:05.0/cr-space snapshot 1 address 0x10 legth 16

Read from address 0x10, 16 Bytes of snapshot ID 1 taken from cr-space address region

SEE ALSO
    devlink(8), **devlink-dev**(8), **devlink-port**(8), **devlink-monitor**(8),

AUTHOR
    Alex Vesker <valex@mellanox.com>