

NAME

autoconf – Generate configuration scripts

SYNOPSIS

autoconf [*OPTION*]... [*TEMPLATE-FILE*]

DESCRIPTION

Generate a configuration script from a *TEMPLATE-FILE* if given, or ‘configure.ac’ if present, or else ‘configure.in’. Output is sent to the standard output if *TEMPLATE-FILE* is given, else into ‘configure’.

Operation modes:

- h, --help**
print this help, then exit
- V, --version**
print version number, then exit
- v, --verbose**
verbosely report processing
- d, --debug**
don’t remove temporary files
- f, --force**
consider all files obsolete
- o, --output=FILE**
save output in FILE (stdout is the default)
- W, --warnings=CATEGORY**
report the warnings falling in CATEGORY [syntax]

Warning categories include:

- ‘cross’ cross compilation issues
 - ‘obsolete’
obsolete constructs
 - ‘syntax’
dubious syntactic constructs
 - ‘all’ all the warnings
 - ‘no-CATEGORY’
turn off the warnings on CATEGORY
 - ‘none’ turn off all the warnings
 - ‘error’ warnings are error
- The environment variables ‘M4’ and ‘WARNINGS’ are honored.

Library directories:

- B, --prepend-include=DIR**
prepend directory DIR to search path
- I, --include=DIR**
append directory DIR to search path

Tracing:

- t, --trace=MACRO[:FORMAT]**
report the list of calls to MACRO
- i, --initialization**
also trace Autoconf’s initialization process

In tracing mode, no configuration script is created. *FORMAT* defaults to ‘\$f:\$l:\$n:\$%’; see ‘autom4te --help’ for information about *FORMAT*.

AUTHOR

Written by David J. MacKenzie and Akim Demaille.

REPORTING BUGS

Report bugs to <bug-autoconf@gnu.org>.

GNU Autoconf home page: <<http://www.gnu.org/software/autoconf/>>.

General help using GNU software: <<http://www.gnu.org/gethelp/>>.

COPYRIGHT

Copyright © 2012 Free Software Foundation, Inc. License GPLv3+/Autoconf: GNU GPL version 3 or later <<http://gnu.org/licenses/gpl.html>>, <<http://gnu.org/licenses/exceptions.html>>

This is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

autoconf(1), **automake**(1), **autoreconf**(1), **autoupdate**(1), **autoheader**(1), **autoscan**(1), **config.guess**(1), **config.sub**(1), **ifnames**(1), **libtool**(1).

The full documentation for **autoconf** is maintained as a Texinfo manual. If the **info** and **autoconf** programs are properly installed at your site, the command

info autoconf

should give you access to the complete manual.