

NAME

cvs-debuild – build a Debian package using **cvs-buildpackage** and **debuild**

SYNOPSIS

cvs-debuild [*debuild options*] [*cvs-buildpackage options*] [**--lintian-opts** *lintian options*]

DESCRIPTION

cvs-debuild is a wrapper around **cvs-buildpackage** to run it with **debuild** as the package-building program. (This cannot simply be accomplished using the **-C** option of **cvs-buildpackage**, as it does not know how to handle all of the special **debuild** options.)

The program simply stashes the **debuild** and **lintian** options, and passes them to **debuild** when it is called by **cvs-buildpackage**. All of the standard **debuild** options may be used (as listed below), but note that the root command specified by any **--rootcmd** or **-r** command-line option will be passed as an option to **cvs-buildpackage**. The first non-**debuild** option detected will signal the start of the **cvs-buildpackage** options.

The selection of the root command is slightly subtle: if there are any command-line options, these will be used. If not, then if **cvs-buildpackage** is set up to use a default root command, that will be used. Finally, if neither of these are the case, then **debuild** will use its procedures to determine an appropriate command, as described in its documentation.

See the manpages for **debuild**(1) and **cvs-buildpackage** for more information about the behaviour of each.

OPTIONS

The following are the **debuild** options recognised by **cvs-debuild**. All **cvs-buildpackage** and **lintian** options are simply passed to the appropriate program. For explanations of the meanings of these variables, see **debuild**(1).

--no-conf, **--noconf**

--rootcmd=*gain-root-command*, **-r***gain-root-command*

--preserve-env

--preserve-envvar=*var*, **-e***var*

--set-envvar=*var=value*, **-e***var=value*

--lintian, **--no-lintian**

--ignore-dirname, **--check-dirname**

These should not be needed, but it is provided nevertheless.

SEE ALSO

cvs-buildpackage(1), **debuild**(1), **dpkg-buildpackage**(1), **lintian**(1)

AUTHOR

This program was written by Julian Gilbey <jdg@debian.org>.