

NAME

xdelta-config - script to get information about the installed version of Xdelta

SYNOPSIS

xdelta-config [**--prefix**[=*DIR*]] [**--exec-prefix**[=*DIR*]] [**--version**] [**--libs**] [**--cflags**] [**LIBRARIES**]

DESCRIPTION

xdelta-config is a tool that is used to configure to determine the compiler and linker flags that should be used to compile and link programs that use *xdelta*. It is also used internally to the .m4 macros for GNU autoconf that are included with *xdelta*.

OPTIONS

xdelta-config accepts the following options:

LIBRARIES

xdelta has one library 'xdelta'.

--version

Print the currently installed version of *xdelta* on the standard output.

--libs Print the linker flags that are necessary to link a *xdelta* program.

--cflags

Print the compiler flags that are necessary to compile a *xdelta* program.

--prefix=PREFIX

If specified, use PREFIX instead of the installation prefix that *xdelta* was built with when computing the output for the **--cflags** and **--libs** options. This option is also used for the **exec prefix** if **--exec-prefix** was not specified. This option must be specified before any **--libs** or **--cflags** options.

--exec-prefix=PREFIX

If specified, use PREFIX instead of the installation **exec prefix** that *xdelta* was built with when computing the output for the **--cflags** and **--libs** options. This option must be specified before any **--libs** or **--cflags** options.

SEE ALSO

glib-config(1), **xdelta**(1)

COPYRIGHT

Copyright © 1998 Owen Taylor

Permission to use, copy, modify, and distribute this software and its documentation for any purpose and without fee is hereby granted, provided that the above copyright notice appear in all copies and that both that copyright notice and this permission notice appear in supporting documentation.

This man page was modified from the **glib-config** man page for the Debian Project by Frederic Lepied <Lepied@Debian.org>.