

**NAME**

getttyent, getttynam, setttyent, endtttyent – get ttys file entry

**SYNOPSIS**

```
#include <ttyent.h>

struct ttyent *getttyent(void);

struct ttyent *getttynam(const char *name);

int setttyent(void);

int endtttyent(void);
```

**DESCRIPTION**

These functions provide an interface to the file **\_PATH\_TTYS** (e.g., */etc/ttys*).

The function **setttyent()** opens the file or rewinds it if already open.

The function **endtttyent()** closes the file.

The function **getttynam()** searches for a given terminal name in the file. It returns a pointer to a *ttyent* structure (description below).

The function **getttyent()** opens the file **\_PATH\_TTYS** (if necessary) and returns the first entry. If the file is already open, the next entry. The *ttyent* structure has the form:

```
struct ttyent {
    char *ty_name;        /* terminal device name */
    char *ty_getty;       /* command to execute, usually getty */
    char *ty_type;        /* terminal type for termcap */
    int   ty_status;      /* status flags */
    char *ty_window;      /* command to start up window manager */
    char *ty_comment;     /* comment field */
};
```

*ty\_status* can be:

```
#define TTY_ON      0x01 /* enable logins (start ty_getty program) */
#define TTY_SECURE 0x02 /* allow UID 0 to login */
```

**ATTRIBUTES**

For an explanation of the terms used in this section, see **attributes(7)**.

Interface	Attribute	Value
<b>getttyent()</b> , <b>setttyent()</b> , <b>endtttyent()</b> , <b>getttynam()</b>	Thread safety	MT-Unsafe race:ttyent

**CONFORMING TO**

Not in POSIX.1. Present on the BSDs, and perhaps other systems.

**NOTES**

Under Linux, the file */etc/ttys*, and the functions described above, are not used.

**SEE ALSO**

**ttynam(3)**, **ttyslot(3)**

**COLOPHON**

This page is part of release 5.02 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.