

NAME

gio – GIO commandline tool

SYNOPSIS

gio help [*COMMAND*]
gio version
gio cat *LOCATION*...
gio copy [*OPTION*...] *SOURCE*... *DESTINATION*
gio info [*OPTION*...] *LOCATION*...
gio list [*OPTION*...] [*LOCATION*...]
gio mime *MIMETYPE* [*HANDLER*]
gio mkdir [*OPTION*...] *LOCATION*...
gio monitor [*OPTION*...] [*LOCATION*...]
gio mount [*OPTION*...] [*LOCATION*...]
gio move [*OPTION*...] *SOURCE*... *DESTINATION*
gio open *LOCATION*...
gio rename *LOCATION* *NAME*
gio remove [*OPTION*...] *LOCATION*...
gio save [*OPTION*...] *DESTINATION*
gio set [*OPTION*...] *LOCATION* *ATTRIBUTE* *VALUE*...
gio trash [*OPTION*...] [*LOCATION*...]
gio tree [*OPTION*...] [*LOCATION*...]

DESCRIPTION

gio is a utility that makes many of the GIO features available from the commandline. In doing so, it provides commands that are similar to traditional utilities, but let you use GIO locations instead of local files: for example you can use something like `smb://server/resource/file.txt` as a location.

Plain filenames which contain a colon will be interpreted as URIs with an unknown protocol. To avoid this, prefix them with a path such as `./`, or with the `file:` protocol.

COMMANDS

help [*COMMAND*]

Displays a short synopsis of the available commands or provides detailed help on a specific command.

version

Prints the GLib version to which **gio** belongs.

cat *LOCATION*...

Concatenates the given files and prints them to the standard output.

The **cat** command works just like the traditional **cat** utility.

Note: just pipe through **cat** if you need its formatting options like **-n**, **-T** or other.

copy [*OPTION*...] *SOURCE*... *DESTINATION*

Copies one or more files from *SOURCE* to *DESTINATION*. If more than one source is specified, the destination must be a directory.

The **copy** command is similar to the traditional **cp** utility.

Options

- T, --no-target-directory**
Don't copy into *DESTINATION* even if it is a directory.
- p, --progress**
Show progress.
- i, --interactive**
Prompt for confirmation before overwriting files.
- preserve**
Preserve all attributes of copied files.
- b, --backup**
Create backups of existing destination files.
- P, --no-dereference**
Never follow symbolic links.

info [*OPTION...*] *LOCATION...*

Shows information about the given locations.

The **info** command is similar to the traditional **ls** utility.

Options

- w, --query-writable**
List writable attributes.
- f, --filesystem**
Show information about the filesystem that the given locations reside on.
- a --attributes=ATTRIBUTES**
The attributes to get.

Attributes can be specified with their GIO name, e.g. `standard::icon`, or just by namespace, e.g. `unix`, or by `*`, which matches all attributes. Several attributes or groups of attributes can be specified, separated by comma.

By default, all attributes are listed.

- n, --nofollow-symlinks**
Don't follow symbolic links.

list [*OPTION...*] [*LOCATION...*]

Lists the contents of the given locations. If no location is given, the contents of the current directory are shown.

The **list** command is similar to the traditional **ls** utility.

Options

- a --attributes=ATTRIBUTES**
The attributes to get.

Attributes can be specified with their GIO name, e.g. `standard::icon`, or just by namespace, e.g. `unix`, or by `*`, which matches all attributes. Several attributes or groups of attributes can be specified, separated by comma.

By default, all attributes are listed.

- h, --hidden**
Show hidden files.
- l, --long**

Use a long listing format.

-n, --nofollow-symlinks
Don't follow symbolic links.

-u, --print-uris
Print full URIs.

mime *MIMETYPE* [*HANDLER*]

If no handler is given, the **mime** command lists the registered and recommended applications for the mimetype. If a handler is given, it is set as the default handler for the mimetype.

Handlers must be specified by their desktop file name, including the extension. Example:
org.gnome.gedit.desktop.

mkdir [*OPTION...*] *LOCATION...*

Creates directories.

The **mkdir** command is similar to the traditional **mkdir** utility.

Options

-p, --parent
Create parent directories when necessary.

monitor [*OPTION...*] [*LOCATION...*]

Monitors files or directories for changes, such as creation deletion, content and attribute changes, and mount and unmount operations affecting the monitored locations.

The **monitor** command uses the GIO file monitoring APIs to do its job. GIO has different implementations for different platforms. The most common implementation on Linux uses inotify.

Options

-d, --dir=LOCATION
Monitor the given location as a directory. Normally, the file type is used to determine whether to monitor a file or directory.

-f, --file=LOCATION
Monitor the given location as a file. Normally, the file type is used to determine whether to monitor a file or directory.

-D, --direct=LOCATION
Monitor the file directly. This allows changes made via hardlinks to be captured.

-s, --silent=LOCATION
Monitor the file directly, but don't report changes.

-n, --no-moves
Report moves and renames as simple deleted/created events.

-m, --mounts
Watch for mount events.

mount [*OPTION...*] [*LOCATION...*]

Provides commandline access to various aspects of GIO's mounting functionality.

Mounting refers to the traditional concept of arranging multiple file systems and devices in a single tree, rooted at /. Classical mounting happens in the kernel and is controlled by the mount utility. GIO expands this concept by introducing mount daemons that can make file systems available to GIO applications without kernel involvement.

GIO mounts can require authentication, and the **mount** command may ask for user IDs, passwords,

and so on, when required.

Options

- m, --mountable**
Mount as mountable.
- d, --device=DEVICE**
Mount volume with device file.
- u, --unmount**
Unmount the location.
- e, --eject**
Eject the location.
- s, --unmount-scheme=SCHEME**
Unmount all mounts with the given scheme.
- f, --force**
Ignore outstanding file operations when unmounting or ejecting.
- a, --anonymous**
Use an anonymous user when authenticating.
- l, --list**
List all GIO mounts.
- o, --monitor**
Monitor mount-related events.
- i, --detail**
Show extra information.
- tcrypt-pim**
The numeric PIM when unlocking a VeraCrypt volume.
- tcrypt-hidden**
Mount a TCRYPT hidden volume.
- tcrypt-system**
Mount a TCRYPT system volume.

move [*OPTION...*] *SOURCE... DESTINATION*

Moves one or more files from *SOURCE* to *DESTINATION*. If more than one source is specified, the destination must be a directory.

The **move** command is similar to the traditional **mv** utility.

open *LOCATION...*

Opens files with the default application that is registered to handle files of this type.

GIO obtains this information from the shared-mime-info database, with per-user overrides stored in **\$XDG_DATA_HOME/applications/mimeapps.list**.

The **mime** command can be used to change the default handler for a mimetype.

Environment variables will not be set on the application, as it may be an existing process which is activated to handle the new file.

rename *LOCATION NAME*

Renames a file.

The **rename** command is similar to the traditional **rename** utility.

remove [*OPTION...*] *LOCATION...*

Deletes each given file.

This command removes files irreversibly. If you want a reversible way to remove files, see the **trash** command.

Note that not all URI schemes that are supported by GIO may allow deletion of files.

The **remove** command is similar to the traditional **rm** utility.

Options

-f, --force

Ignore non-existent and non-deletable files.

save [*OPTION...*] *DESTINATION*

Reads from standard input and saves the data to the given location.

This is similar to just redirecting output to a file using traditional shell syntax, but the **save** command allows saving to location that GIO can write to.

Options

-b, --backup

Back up existing destination files.

-c, --create

Only create the destination if it doesn't exist yet.

-a, --append

Append to the end of the file.

-p, --private

When creating, restrict access to the current user.

-u, --unlink

When replacing, replace as if the destination did not exist.

-v, --print-etag

Print the new ETag in the end.

-e, --etag=ETAG

The ETag of the file that is overwritten.

set *LOCATION ATTRIBUTE VALUE...*

Sets a file attribute on a file.

File attributes can be specified with their GIO name, e.g `standard::icon`. Note that not all GIO file attributes are writable. Use the **--query-writable** option of the **info** command to list writable file attributes.

If the *TYPE* is unset, *VALUE* does not have to be specified. If the *TYPE* is *stringv*, multiple values can be given.

Options

-t, --type=TYPE

Specifies the type of the attribute. Supported types are `string`, `stringv`, `bytestring`, `boolean`, `uint32`, `int32`, `uint64`, `int64` and `unset`.

If the type is not specified, `string` is assumed.

-n, --nofollow-symlinks

Don't follow symbolic links.

trash [*OPTION...*] [*LOCATION...*]

Sends files or directories to the 'Trashcan'. This can be a different folder depending on where the file is located, and not all file systems support this concept. In the common case that the file lives inside a user's home directory, the trash folder is **\$XDG_DATA_HOME/Trash**.

Note that moving files to the trash does not free up space on the file system until the 'Trashcan' is emptied. If you are interested in deleting a file irreversibly, see the **remove** command.

Inspecting and emptying the 'Trashcan' is normally supported by graphical file managers such as Nautilus, but you can also see the trash with the command: **gio list trash://**.

Options

-f, --force

Ignore non-existent and non-deletable files.

--empty

Empty the trash.

tree [*OPTION...*] [*LOCATION...*]

Lists the contents of the given locations recursively, in a tree-like format. If no location is given, it defaults to the current directory.

The **tree** command is similar to the traditional **tree** utility.

Options

-h, --hidden

Show hidden files.

-l, --follow-symlinks

Follow symbolic links.

EXIT STATUS

On success 0 is returned, a non-zero failure code otherwise.

SEE ALSO

cat(1), **cp(1)**, **ls(1)**, **mkdir(1)**, **mv(1)**, **rm(1)**, **tree(1)**.