

NAME

cvs-debrelease – upload a **cvs-buildpackage**/**cvs-debuild** generated package

SYNOPSIS

cvs-debrelease [*cvs-debrelease options*] [**--dopts** [*dupload/dput options*]]

DESCRIPTION

cvs-debrelease is run from the CVS working directory after **cvs-buildpackage** or **cvs-debuild**. It uses the **cvs-buildpackage** system to locate the *.changes* file generated in that run. It then uploads the package using **debrelease**(1), which in turn calls either **dupload** or **dput**. Note that the **--dopts** option must be specified to distinguish the **cvs-debrelease** options from the **dupload** or **dput** options. Also, the **devscripts** configuration files will be read, as described in the **debrelease**(1) manpage.

Note that unlike **cvs-buildpackage**, the only way to specify the source package name is with the **-P** option; you cannot simply have it as the last command-line parameter.

OPTIONS

All current **cvs-buildpackage** options are silently accepted; however, only the ones listed below have any effect. For more details on all of them, see the **cvs-buildpackage**(1) manpage. All **debrelease** options (as listed below) are also accepted.

--dupload, --dput

This specifies which uploader program to use; the default is **dupload**.

-adebian-architecture, -tGNU-system-type

See **dpkg-architecture**(1) for a description of these options. They affect the search for the *.changes* file. They are provided to mimic the behaviour of **dpkg-buildpackage** when determining the name of the *.changes* file.

-Mmodule

The name of the CVS module.

-Ppackage

The name of the package.

-Vversion

The version number of the package.

-Ttag The CVS tag to use for exporting sources.**-Rroot directory**

Root of the original sources archive.

-Wwork directory

The full path name for the **cvs-buildpackage** working directory.

-xprefix

This option provides the CVS default module prefix.

--no-conf, --noconf

Do not read any configuration files. This can only be used as the first option given on the command-line.

--help, --version

Show help message and version information respectively.

SEE ALSO

cvs-buildpackage(1), **cvs-debuild**(1), **debrelease**(1)

AUTHOR

cvs-buildpackage was written by Manoj Srivastava, and the current version of **debrelease** was written by Julian Gilbey <jdg@debian.org>. They have been combined into this program by Julian Gilbey.