

## NAME

ubuntu-dev-tools – Configuration for the ubuntu-dev-tools package.

## DESCRIPTION

The **ubuntu-dev-tools** package is similar in scope to the **devscripts**(1) package, providing a collection of scripts which may be of use to Ubuntu and Debian developers or others wishing to build Debian packages.

Some of these scripts have options which may be configured on a system-wide and per-user basis. These options are configured in **devscripts.conf**(5).

All variables are described in the script's manpages. Package-wide variables begin with "*UBUNTU-TOOLS*" and are listed below.

Every script which reads the configuration files can be forced to ignore them by using the **--no-conf** command-line option.

## ENVIRONMENT

All **ubuntu-dev-tools** configuration variables can be set (and overridden) by setting them in the environment (unlike **devscripts**).

In addition, several scripts use the following environment variables:

### UBUMAIL

Overrides **DEBEMAIL** and **DEBFULLNAME** when the target is clearly Ubuntu. Can either contain an e-mail address or **Full Name** **<email@example.org>**.

### DEBEMAIL, DEBFULLNAME

As in **devscripts**(1).

## PACKAGE-WIDE VARIABLES

The currently recognised package-wide variables are:

### UBUNTUTOOLS\_BUILDER

This specifies the preferred test-builder, one of **pbuilder** (default), **sbuild**, **pbuilder-dist**.

### UBUNTUTOOLS\_DEBIAN\_MIRROR

The preferred Debian archive mirror. Should be of the form **http://ftp.debian.org/debian** (no trailing slash). If not specified, the master will be used.

### UBUNTUTOOLS\_DEBSEC\_MIRROR

The preferred Debian security archive mirror. Should be of the form **http://security.debian.org** (no trailing slash). If not specified, the master will be used.

### UBUNTUTOOLS\_UBUNTU\_MIRROR

The preferred Ubuntu archive mirror. Should be of the form **http://archive.ubuntu.com/ubuntu** (no trailing slash). If not specified, the master will be used.

### UBUNTUTOOLS\_UBUNTU\_PORTS\_MIRROR

The preferred Ubuntu archive mirror. Should be of the form **http://ports.ubuntu.com** (no trailing slash). If not specified, the master will be used.

### UBUNTUTOOLS\_LPINSTANCE

The launchpad instance to communicate with. e.g. **production** (default) or **staging**.

### UBUNTUTOOLS\_MIRROR\_FALLBACK

Whether or not to fall-back to the master archive mirror. This is usually the desired behaviour, as mirrors can lag the masters. If on a private network with only a local mirror, you may want to set

this to **no**. One of **yes** (default) or **no**.

**UBUNTUTOOLS\_UPDATE\_BUILDER**

Whether or not to update the test-builder before each test build. One of **yes** or **no** (default).

**UBUNTUTOOLS\_WORKDIR**

The directory to use for preparing source packages etc. When unset, defaults to a directory in */tmp/* named after the script.

**SEE ALSO**

**devscripts(1)**, **devscripts.conf(5)**

**AUTHORS**

This manpage was written by Stefano Rivera <stefanor@ubuntu.com>.