

**NAME**

gethostbyname, gethostbyaddr, sethostent, gethostent, endhostent, h\_errno, herror, hstrerror, gethostbyaddr\_r, gethostbyname2, gethostbyname2\_r, gethostbyname\_r, gethostent\_r – get network host entry

**SYNOPSIS**

```
#include <netdb.h>
extern int h_errno;

struct hostent *gethostbyname(const char *name);

#include <sys/socket.h> /* for AF_INET */
struct hostent *gethostbyaddr(const void *addr,
                              socklen_t len, int type);

void sethostent(int stayopen);
void endhostent(void);
void herror(const char *s);
const char *hstrerror(int err);
/* System V/POSIX extension */
struct hostent *gethostent(void);
/* GNU extensions */
struct hostent *gethostbyname2(const char *name, int af);
int gethostent_r(
    struct hostent *ret, char *buf, size_t buflen,
    struct hostent **result, int *h_errnop);
int gethostbyaddr_r(const void *addr, socklen_t len, int type,
    struct hostent *ret, char *buf, size_t buflen,
    struct hostent **result, int *h_errnop);
int gethostbyname_r(const char *name,
    struct hostent *ret, char *buf, size_t buflen,
    struct hostent **result, int *h_errnop);
int gethostbyname2_r(const char *name, int af,
    struct hostent *ret, char *buf, size_t buflen,
    struct hostent **result, int *h_errnop);
```

Feature Test Macro Requirements for glibc (see **feature\_test\_macros(7)**):

**gethostbyname2(), gethostent\_r(), gethostbyaddr\_r(), gethostbyname\_r(), gethostbyname2\_r():**

Since glibc 2.19:

    \_DEFAULT\_SOURCE

Glibc versions up to and including 2.19:

    \_BSD\_SOURCE || \_SVID\_SOURCE

**herror(), hstrerror():**

Since glibc 2.19:

    \_DEFAULT\_SOURCE

Glibc 2.8 to 2.19:

    \_BSD\_SOURCE || \_SVID\_SOURCE

Before glibc 2.8:

    none

**h\_errno:**

Since glibc 2.19

    \_DEFAULT\_SOURCE || \_POSIX\_C\_SOURCE < 200809L

Glibc 2.12 to 2.19:

`_BSD_SOURCE || _SVID_SOURCE || _POSIX_C_SOURCE < 200809L`

Before glibc 2.12:

`none`

## DESCRIPTION

The `gethostbyname()`, `gethostbyaddr()`, `herror()`, and `hstrerror()` functions are obsolete. Applications should use `getaddrinfo(3)`, `getnameinfo(3)`, and `gai_strerror(3)` instead.

The `gethostbyname()` function returns a structure of type *hostent* for the given host *name*. Here *name* is either a hostname or an IPv4 address in standard dot notation (as for `inet_addr(3)`). If *name* is an IPv4 address, no lookup is performed and `gethostbyname()` simply copies *name* into the *h\_name* field and its *struct in\_addr* equivalent into the *h\_addr\_list[0]* field of the returned *hostent* structure. If *name* doesn't end in a dot and the environment variable **HOSTALIASES** is set, the alias file pointed to by **HOSTALIASES** will first be searched for *name* (see `hostname(7)` for the file format). The current domain and its parents are searched unless *name* ends in a dot.

The `gethostbyaddr()` function returns a structure of type *hostent* for the given host address *addr* of length *len* and address type *type*. Valid address types are **AF\_INET** and **AF\_INET6**. The host address argument is a pointer to a struct of a type depending on the address type, for example a *struct in\_addr* \* (probably obtained via a call to `inet_addr(3)`) for address type **AF\_INET**.

The `sethostent()` function specifies, if *stayopen* is true (1), that a connected TCP socket should be used for the name server queries and that the connection should remain open during successive queries. Otherwise, name server queries will use UDP datagrams.

The `endhostent()` function ends the use of a TCP connection for name server queries.

The (obsolete) `herror()` function prints the error message associated with the current value of *h\_errno* on *stderr*.

The (obsolete) `hstrerror()` function takes an error number (typically *h\_errno*) and returns the corresponding message string.

The domain name queries carried out by `gethostbyname()` and `gethostbyaddr()` rely on the Name Service Switch (`nsswitch.conf(5)`) configured sources or a local name server (`named(8)`). The default action is to query the Name Service Switch (`nsswitch.conf(5)`) configured sources, failing that, a local name server (`named(8)`).

## Historical

The `nsswitch.conf(5)` file is the modern way of controlling the order of host lookups.

In glibc 2.4 and earlier, the *order* keyword was used to control the order of host lookups as defined in `/etc/host.conf` (`host.conf(5)`).

The *hostent* structure is defined in `<netdb.h>` as follows:

```
struct hostent {
    char  *h_name;           /* official name of host */
    char **h_aliases;        /* alias list */
    int    h_addrtype;       /* host address type */
    int    h_length;         /* length of address */
    char **h_addr_list;      /* list of addresses */
}
#define h_addr h_addr_list[0] /* for backward compatibility */
```

The members of the *hostent* structure are:

*h\_name*

The official name of the host.

*h\_aliases*

An array of alternative names for the host, terminated by a null pointer.

*h\_addrtype*

The type of address; always **AF\_INET** or **AF\_INET6** at present.

*h\_length*

The length of the address in bytes.

*h\_addr\_list*

An array of pointers to network addresses for the host (in network byte order), terminated by a null pointer.

*h\_addr* The first address in *h\_addr\_list* for backward compatibility.

## RETURN VALUE

The **gethostbyname()** and **gethostbyaddr()** functions return the *hostent* structure or a null pointer if an error occurs. On error, the *h\_errno* variable holds an error number. When non-NULL, the return value may point at static data, see the notes below.

## ERRORS

The variable *h\_errno* can have the following values:

### HOST\_NOT\_FOUND

The specified host is unknown.

### NO\_DATA

The requested name is valid but does not have an IP address. Another type of request to the name server for this domain may return an answer. The constant **NO\_ADDRESS** is a synonym for **NO\_DATA**.

### NO\_RECOVERY

A nonrecoverable name server error occurred.

### TRY\_AGAIN

A temporary error occurred on an authoritative name server. Try again later.

## FILES

*/etc/host.conf*

resolver configuration file

*/etc/hosts*

host database file

*/etc/nsswitch.conf*

name service switch configuration

## ATTRIBUTES

For an explanation of the terms used in this section, see **attributes(7)**.

Interface	Attribute	Value
<b>gethostbyname()</b>	Thread safety	MT-Unsafe race:hostbyname env locale
<b>gethostbyaddr()</b>	Thread safety	MT-Unsafe race:hostbyaddr env locale
<b>sethostent()</b> , <b>endhostent()</b> , <b>gethostent_r()</b>	Thread safety	MT-Unsafe race:hostent env locale
<b>herror()</b> , <b>hstrerror()</b>	Thread safety	MT-Safe
<b>gethostent()</b>	Thread safety	MT-Unsafe race:hostent race:hostentbuf env locale
<b>gethostbyname2()</b>	Thread safety	MT-Unsafe race:hostbyname2 env locale
<b>gethostbyaddr_r()</b> , <b>gethostbyname_r()</b> , <b>gethostbyname2_r()</b>	Thread safety	MT-Safe env locale

In the above table, *hostent* in *race:hostent* signifies that if any of the functions **sethostent()**, **gethostent()**, **gethostent\_r()**, or **endhostent()** are used in parallel in different threads of a program, then data races could occur.

## CONFORMING TO

POSIX.1-2001 specifies **gethostbyname()**, **gethostbyaddr()**, **sethostent()**, **endhostent()**, **gethostent()**, and *h\_errno*; **gethostbyname()**, **gethostbyaddr()**, and *h\_errno* are marked obsolescent in that standard. POSIX.1-2008 removes the specifications of **gethostbyname()**, **gethostbyaddr()**, and *h\_errno*, recommending the use of **getaddrinfo(3)** and **getnameinfo(3)** instead.

## NOTES

The functions **gethostbyname()** and **gethostbyaddr()** may return pointers to static data, which may be overwritten by later calls. Copying the *struct hostent* does not suffice, since it contains pointers; a deep copy is required.

In the original BSD implementation the *len* argument of **gethostbyname()** was an *int*. The SUSv2 standard is buggy and declares the *len* argument of **gethostbyaddr()** to be of type *size\_t*. (That is wrong, because it has to be *int*, and *size\_t* is not. POSIX.1-2001 makes it *socklen\_t*, which is OK.) See also **accept(2)**.

The BSD prototype for **gethostbyaddr()** uses *const char \** for the first argument.

## System V/POSIX extension

POSIX requires the **gethostent()** call, which should return the next entry in the host data base. When using DNS/BIND this does not make much sense, but it may be reasonable if the host data base is a file that can be read line by line. On many systems, a routine of this name reads from the file */etc/hosts*. It may be available only when the library was built without DNS support. The glibc version will ignore ipv6 entries. This function is not reentrant, and glibc adds a reentrant version **gethostent\_r()**.

## GNU extensions

Glibc2 also has a **gethostbyname2()** that works like **gethostbyname()**, but permits to specify the address family to which the address must belong.

Glibc2 also has reentrant versions **gethostent\_r()**, **gethostbyaddr\_r()**, **gethostbyname\_r()** and **gethostbyname2\_r()**. The caller supplies a *hostent* structure *ret* which will be filled in on success, and a temporary work buffer *buf* of size *buflen*. After the call, *result* will point to the result on success. In case of an error or if no entry is found *result* will be NULL. The functions return 0 on success and a nonzero error number on failure. In addition to the errors returned by the nonreentrant versions of these functions, if *buf* is too small, the functions will return **ERANGE**, and the call should be retried with a larger buffer. The global

variable *h\_errno* is not modified, but the address of a variable in which to store error numbers is passed in *h\_errnop*.

## BUGS

**gethostbyname()** does not recognize components of a dotted IPv4 address string that are expressed in hexadecimal.

## SEE ALSO

**getaddrinfo(3)**, **getnameinfo(3)**, **inet(3)**, **inet\_ntop(3)**, **inet\_pton(3)**, **resolver(3)**, **hosts(5)**, **nsswitch.conf(5)**, **hostname(7)**, **named(8)**

## COLOPHON

This page is part of release 5.02 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.