

NAME

envsubst – substitutes environment variables in shell format strings

SYNOPSIS

envsubst [*OPTION*] [*SHELL-FORMAT*]

DESCRIPTION

Substitutes the values of environment variables.

Operation mode:

-v, --variables

output the variables occurring in SHELL-FORMAT

Informative output:

-h, --help

display this help and exit

-V, --version

output version information and exit

In normal operation mode, standard input is copied to standard output, with references to environment variables of the form \$VARIABLE or \${VARIABLE} being replaced with the corresponding values. If a SHELL-FORMAT is given, only those environment variables that are referenced in SHELL-FORMAT are substituted; otherwise all environment variables references occurring in standard input are substituted.

When **--variables** is used, standard input is ignored, and the output consists of the environment variables that are referenced in SHELL-FORMAT, one per line.

AUTHOR

Written by Bruno Haible.

REPORTING BUGS

Report bugs to <bug-gnu-gettext@gnu.org>.

COPYRIGHT

Copyright © 2003-2007 Free Software Foundation, Inc. License GPLv3+: GNU GPL version 3 or later <<http://gnu.org/licenses/gpl.html>>

This is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

The full documentation for **envsubst** is maintained as a Texinfo manual. If the **info** and **envsubst** programs are properly installed at your site, the command

info envsubst

should give you access to the complete manual.