

NAME

pbuilder-dist-simple – simple multi-release pbuilder wrapper

SYNOPSIS

pbuilder-*<dist>* operation [...]

DESCRIPTION

pbuilder-dist-simple is a wrapper that makes it easy to use pbuilder with chroots for many different Ubuntu distributions. If you need more features than **pbuilder-dist-simple** provides, have a look at **pbuilder-dist**(1).

USAGE

Create one symlink to **pbuilder-dist-simple** for each distribution for which you want a build environment, naming them like "pbuilder-lucid", "pbuilder-natty", etc.

Replace *operation* with the action you want **pbuilder-dist-simple** to do (create, update, build, clean, login or execute).

EXAMPLES

pbuilder-natty create

Creates a **pbuilder** environment for Ubuntu Natty.

pbuilder-lucid update

Updates an existing Ubuntu Lucid environment.

pbuilder-lucid build .sample_1.0-0ubuntu1.dsc

Builds the specified package on an already existing Ubuntu Lucid environment.

FILES

By default, **pbuilder-dist-simple** will store all the files it generates in **~/pbuilder/**. This can be changed by modifying the **BASE_DIR** value on the top of the script to any other directory you want. If the directory doesn't exist, it will be created at runtime.

SEE ALSO

pbuilder(1), **pbuilder-rrc**(5), **pbuilder-dist**(1)

AUTHORS

pbuilder-dist was originally written by Jamin W. Collins <jcollins@asgardsrealm.net> and Jordan Mantha <mantha@ubuntu.com>, and this manpage by Siegfried-A. Gevatter <rainct@ubuntu.com>.

Both are released under the GNU General Public License, version 2 or later.