

NAME

ipc – System V IPC system calls

SYNOPSIS

```
int ipc(unsigned int call, int first, int second, int third,  
        void *ptr, long fifth);
```

DESCRIPTION

ipc() is a common kernel entry point for the System V IPC calls for messages, semaphores, and shared memory. *call* determines which IPC function to invoke; the other arguments are passed through to the appropriate call.

User-space programs should call the appropriate functions by their usual names. Only standard library implementors and kernel hackers need to know about **ipc()**.

CONFORMING TO

ipc() is Linux-specific, and should not be used in programs intended to be portable.

NOTES

On some architectures—for example x86-64 and ARM—there is no **ipc()** system call; instead, **msgctl(2)**, **semctl(2)**, **shmctl(2)**, and so on really are implemented as separate system calls.

SEE ALSO

msgctl(2), **msgget(2)**, **msgrcv(2)**, **msgsnd(2)**, **semctl(2)**, **semget(2)**, **semop(2)**, **semtimedop(2)**, **shmat(2)**, **shmctl(2)**, **shmdt(2)**, **shmget(2)**, **sysvipc(7)**

COLOPHON

This page is part of release 5.02 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.