NAME

```
__ppc_yield, __ppc_mdoio, __ppc_mdoom - Hint the processor to release shared resources
```

SYNOPSIS

```
#include <sys/platform/ppc.h>
void __ppc_yield(void);
void __ppc_mdoio(void);
void __ppc_mdoom(void);
```

DESCRIPTION

These functions provide hints about the usage of resources that are shared with other processors on the Power architecture. They can be used, for example, if a program waiting on a lock intends to divert the shared resources to be used by other processors.

__ppc_yield() provides a hint that performance will probably be improved if shared resources dedicated to the executing processor are released for use by other processors.

__ppc_mdoio() provides a hint that performance will probably be improved if shared resources dedicated to the executing processor are released until all outstanding storage accesses to caching-inhibited storage have been completed.

__ppc_mdoom() provides a hint that performance will probably be improved if shared resources dedicated to the executing processor are released until all outstanding storage accesses to cacheable storage for which the data is not in the cache have been completed.

VERSIONS

These functions first appeared in glibc in version 2.18.

ATTRIBUTES

For an explanation of the terms used in this section, see **attributes**(7).

Interface	Attribute	Value
ppc_yield(),ppc_mdoio(),	Thread safety	MT-Safe
ppc_mdoom()		

CONFORMING TO

These functions are nonstandard GNU extensions.

SEE ALSO

```
\_\_ppc\_set\_ppr\_med(3)
```

Power ISA, Book II - Section 3.2 ("or" architecture)

COLOPHON

This page is part of release 5.02 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at https://www.kernel.org/doc/man-pages/.