

NAME

`sem_post` – unlock a semaphore

SYNOPSIS

```
#include <semaphore.h>
```

```
int sem_post(sem_t *sem);
```

Link with `-pthread`.

DESCRIPTION

`sem_post()` increments (unlocks) the semaphore pointed to by `sem`. If the semaphore's value consequently becomes greater than zero, then another process or thread blocked in a `sem_wait(3)` call will be woken up and proceed to lock the semaphore.

RETURN VALUE

`sem_post()` returns 0 on success; on error, the value of the semaphore is left unchanged, `-1` is returned, and `errno` is set to indicate the error.

ERRORS**EINVAL**

`sem` is not a valid semaphore.

EOVERFLOW

The maximum allowable value for a semaphore would be exceeded.

ATTRIBUTES

For an explanation of the terms used in this section, see `attributes(7)`.

Interface	Attribute	Value
<code>sem_post()</code>	Thread safety	MT-Safe

CONFORMING TO

POSIX.1-2001.

NOTES

`sem_post()` is async-signal-safe: it may be safely called within a signal handler.

EXAMPLE

See `sem_wait(3)`.

SEE ALSO

`sem_getvalue(3)`, `sem_wait(3)`, `sem_overview(7)`, `signal-safety(7)`

COLOPHON

This page is part of release 5.02 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.